



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
04.03.2015 Bulletin 2015/10

(51) Int Cl.:
G02F 1/1337^(2006.01) G02F 1/1333^(2006.01)
G02F 1/137^(2006.01)

(21) Application number: **13191535.7**

(22) Date of filing: **05.11.2013**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME

- **Liu, Kuei-Ling**
350 Miao-Li County (TW)
- **Chen, Fu-Cheng**
350 Miao-Li County (TW)
- **Chiu, Kuo-Hao**
350 Miao-Li County (TW)

(30) Priority: **28.08.2013 TW 102130893**

(71) Applicant: **InnoLux Corporation**
Chu-Nan, Miao-Li 350 (TW)

(74) Representative: **Von Kreisler Selting Werner - Partnerschaft**
von Patentanwälten und Rechtsanwälten mbB
Deichmannhaus am Dom
Bahnhofsvorplatz 1
50667 Köln (DE)

(72) Inventors:
• **Hsu, Hsu-Kuan**
350 Miao-Li County (TW)
• **Chu, Hsia-Ching**
350 Miao-Li County (TW)

Remarks:
Amended claims in accordance with Rule 137(2) EPC.

(54) **Light leakage reduction in vertically-aligned liquid crystal displays using polymeric particles formed on an alignment layer**

(57) A vertically-aligned LCD (100) is disclosed, which has improved contrast and display quality by reducing light leakage in the non-display area.

Agglomerate particles (120) in direct contact with the liquid crystal (LC) layer (150) in the LC-cell are formed on an alignment layer (170) by selective irradiation of monomers present either in the alignment layer or in the LC layer. These particles are distributed more densely in the non-display area (B) than in the display area (A). The particles in the display area are formed under application of an electric field which aligns them in preferred directions (forming nano-protrusions), so as to provide ordering of the LC molecules there; however, no field is applied during the formation of the particles in the non-display area: these vary strongly in shape, size and orientation, preventing ordering of the LC layer and greatly reducing light leakage there.




FIG. 1A

100




FIG. 1B

Description

BACKGROUND OF THE INVENTION

Field of the Invention

[0001] The disclosure related in general to a display device, and particularly to a display device having superior display quality.

Description of the Related Art

[0002] Liquid crystal displays have been applied in a variety of electronic products, such as laptops, tablet PCs, and etc. Moreover, along with the rapid advance of large-sized flat panel displays in the market, liquid crystal displays with light weight and miniaturized sizes have played very important roles and gradually replaced CRT displays to become the main stream in the market.

[0003] Currently, vertical alignment liquid crystal display panels are one of the main stream products. However, vertical alignment liquid crystal display panels have issues of light leakage, which affect the display quality thereof. Therefore, researchers have been working on providing vertical alignment liquid crystal display panels having superior display quality.

SUMMARY OF THE INVENTION

[0004] The disclosure is directed to a display device. In the embodiments, the agglomerates located corresponding to at least a portion of the trace area have a higher distribution density than those located corresponding to the pixel area, such that the light transmittance of the trace area is lowered; accordingly, the light leakage of the display device is reduced, and the qualities of the display images are improved.

[0005] According to an embodiment of the present disclosure, a display device is provided. The display device includes a display panel. The display panel includes a first substrate, a second substrate, at least a data line, at least a scan line, a trace area, a liquid crystal layer, an alignment layer, a plurality of spacers, a seal, and a plurality of agglomerates. The first substrate and the second substrate are disposed opposite to the first substrate, and the first substrate has at least a pixel area having a plurality of pixels. The data line and the scan line are intersected for defining the pixel area. The trace area is located outside the pixel area. The liquid crystal layer, the alignment layer, and the spacers are disposed between the first substrate and the second substrate. The seal is disposed between the first substrate and the second substrate and located outside the trace area. The agglomerates are formed on the alignment layer. The distribution density of the agglomerates located corresponding to at least a portion of the trace area is higher than the distribution density of those located corresponding to the pixel area.

[0006] The above and other aspects of the invention will become better understood with regard to the following detailed description of the preferred but non-limiting embodiment(s). The following description is made with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] FIG. 1A shows a top view of a display panel according to an embodiment of the present disclosure;

[0008] FIG. 1B shows a cross-sectional view along the cross-sectional line 1B-1B' of FIG. 1A;

[0009] FIG. 2 shows a cross-sectional view of a display panel according to another embodiment of the present disclosure;

[0010] FIG. 3 shows a top view of a display panel according to a further embodiment of the present disclosure;

[0011] FIG. 4 shows a top view of a display panel according to a still further embodiment of the present disclosure;

[0012] FIG. 5 shows a simplified explosion diagram of a display device according to an embodiment of the present disclosure; and

[0013] FIG. 6 shows a cross-sectional view of a display device according to another embodiment of the present disclosure.

DETAILED DESCRIPTION OF THE INVENTION

[0014] According to the embodiments of the present disclosure, in the display device, the agglomerates located corresponding to at least a portion of the trace area have a higher distribution density than those located corresponding to the pixel area, such that the light transmittance of the trace area is lowered; accordingly, the light leakage of the display device is reduced, and the qualities of the display images are improved. The embodiments are described in details with reference to the accompanying drawings. The identical elements of the embodiments are designated with the same or similar reference numerals. Also, it is to be noted that the drawings may be simplified for illustrating the embodiments. Thus, the specification and the drawings are to be regarded as an illustrative sense rather than a restrictive sense. The details of the structures of the embodiments are for exemplification only, not for limiting the scope of protection of the disclosure. Detailed structures may be modified or changed by one skilled in the art after having the benefit of this description of the disclosure.

[0015] FIG. 1A shows a top view of a display panel 100 according to an embodiment of the present disclosure, and FIG. 1B shows a cross-sectional view along the cross-sectional line 1B-1B' of FIG. 1A. Referring to FIGS. 1A-1B, the display panel 100 includes a first substrate 110 and a plurality of agglomerates 120. The first substrate 110 has a display area A and a non-display area B adjacent to the display area A. The display area A rep-

resents the area of the display panel 100 for displaying images, and the non-display area B represents the area not for displaying images. The agglomerates 120 are disposed on the first substrate 110. In an embodiment, as shown in FIG. 1A, the non-display area B surrounds the display area A.

[0016] In the embodiment, the distribution density of the agglomerates 120 located in at least a portion of the non-display area B is different from the distribution density of the agglomerates 120 located in the display area A. In other words, the agglomerates 120 located in different portions of the non-display area B may have different distribution densities; that is, the agglomerates 120 located in at least some portions of the non-display area B have distribution densities different from the distribution density of the agglomerates 120 located in the display area A. Moreover, the agglomerates 120 have irregular shapes and sizes. In the embodiment, the display area A is such as an area in the pixel area for displaying images, and the non-display area B is such as a trace area. However, the non-display area B may include any area which is not for displaying images and is not limited to the above-mentioned example.

[0017] In an embodiment, the distribution density of the agglomerates 120 located in the non-display area B having a size of 10-50 nm is different from the distribution density of the agglomerates 120 located in the non-display area B having a size of 50-100 nm. Moreover, among the agglomerates 120 located in the non-display area B, those with a size of 10-50 nm have a higher distribution density than those with a size of 50-100 nm.

[0018] In another embodiment, among the agglomerates 120 having a size of 50-100 nm, those located in at least a portion (e.g. some local regions) of the non-display area B have a different distance between the agglomerates 120 from the distance between those located in the display area A. For example, among the agglomerates 120 having a size of 50-100 nm, the distance between any two of the adjacent agglomerates 120 located in the non-display area B is different from the distance between any two of the adjacent agglomerates 120 located in the display area A. In an embodiment, among the agglomerates 120 having a size of 50-100 nm, the distance between any two of the adjacent agglomerates 120 located in the non-display area B is smaller than the distance between any two of the adjacent agglomerates 120 located in the display area A. It is to be noted that the distance described herein indicates at least one of a minimum distance or an average distance.

[0019] In the embodiment, the agglomerates 120 located in the non-display area B do not have any particular arrangement(s) and orientation(s). In other words, the agglomerates 120 are arranged irregularly on the first substrate 110. The agglomerates 120 located in the display area A have particular arrangement(s) for aligning the liquid crystals to tilt toward particular direction(s). The agglomerates 120 located in different areas may be provided with different functions according to the irradiation

curing process applied thereon and whether an electric field is applied thereon. The distribution density of the agglomerates 120 located in at least a portion of the non-display area B is higher than the distribution density of the irregularly arranged agglomerates 120 located in the display area A. Since the agglomerates 120 located in the non-display area B do not have any particular orientation(s), the liquid crystals in the area do not tilt toward particular direction(s), thereby the area turns into a dark area, which lowers the light transmittance, and hence the light leakage issue of the display panel 100 can be improved.

[0020] As shown in FIGS. 1A-1B, the display panel 100 may further include a second substrate 130, a seal 140, a liquid crystal layer 150, and a plurality of spacers 150. The second substrate 130 and the first substrate 110 are disposed opposite to each other. The liquid crystal layer 150 and the seal 140 are disposed between the first substrate 110 and the second substrate 130. The seal 140 is located outside the non-display area B. The spacers 160 are disposed between the first substrate 110 and the second substrate 130 for providing a gap for disposing the liquid crystal layer 150. The spacers 160 may have different heights for providing buffering when the panel is pressed. The agglomerates 120 are in direct contact with the liquid crystal molecules in the liquid crystal layer 150. It is also important to point out that the agglomerates 120 are not necessarily drawn to scale according to the actual products, and the drawings are for illustrating the embodiments only and not for limiting the scope of protection of the disclosure.

[0021] In the embodiment, since the agglomerates 120 located in the non-display area B are not provided with any alignment functions for guiding particular directions, and accordingly are not provided with any alignment functions for the liquid crystal molecules. Therefore, in the non-display area B, the liquid crystal molecules in the liquid crystal layer 150 may tilt toward any possible directions, thereby the light transmittance of the non-display area is lowered, forming an excellent dark area, and the light leakage issue of the display panel 100 is improved, which further increases the contrast and quality of the images displayed in the display area.

[0022] According to the embodiments of the present disclosure, the agglomerates 120 are not limited to have particular sizes or shapes, and the sizes can be adjusted according to application needs. In an embodiment, the distribution density of the agglomerates 120 having a size of 10-100 nm located in the non-display area B is higher than the distribution density of the agglomerates 120 having a size of 10-100 nm located in the display area A. In another embodiment, in the non-display area B, the distribution density of the agglomerates 120 having a size of 10-50 nm is higher than the distribution density of the agglomerates 120 having a size of 50-100 nm. In a further embodiment, in the non-display area B, the distribution density of the agglomerates 120 having a size of 50-100 nm located on the first substrate 110 is lower than the

distribution density of those located on the second substrate 130. It is important to point out that since the agglomerates 120 do not have particular shapes, the term of "size" refers to the dimension(s) of the agglomerates 120, which may be diameter, height, width, or any expression suitable for representing the size of one agglomerate 120.

[0023] In the embodiment, the display panel 100 may further include a thin film transistor array and a color filter layer on the first substrate 110. In an alternative embodiment, the color filter layer may be disposed on the second substrate 130.

[0024] In the embodiment, the display panel 100 may further include an alignment layer 170 disposed between the first substrate 110 and the second substrate 130. For example, the alignment layer 170 is disposed on the first substrate 110 or on the second substrate 130, and the agglomerates 120 are formed on the alignment layer 170. In an embodiment, as shown in FIGS. 1A-1B, the display panel 100 may include two alignment layers 170 formed on the first substrate 110 and the second substrate 130, respectively, and the agglomerates 120 are formed on the alignment layer 170 located close to the first substrate 110. In the embodiment, the alignment layer 170 may be a polyimide (PI) film.

[0025] In the embodiment, the agglomerates 120 may be formed by a variety of processes. In an embodiment, UV curable monomers are added while forming the liquid crystal layer 150 or the alignment layer 170, and then a UV irradiation process is performed from the first substrate 110 side or the second substrate 130 side for forming the agglomerates 120 on the first substrate 110 or on the alignment layer 170. The material of the agglomerates 120 formed by irradiating UV curable monomers is polymer. Polymerization degrees of the polymer in different areas are different from one another; thereby the distribution densities of the agglomerates 120 in different areas are different.

[0026] In an embodiment, the display panel 100 is such as a nano-protrusion vertical aligned liquid crystal display panel, and the agglomerates 120 and the nano-protrusion alignment structure on the surface of the alignment layer 170 can be formed from the same monomers. For example, the nano-protrusion alignment structure can be formed in the display area A by polymerizing the monomers in the display area A while an external electric field is continuously applied thereon, and the agglomerates 120 can be formed by polymerizing the monomers in the non-display area B without applying any external electric field, the agglomerates 120 being irregularly arranged and lacking particular alignment directions. As such, the nano-protrusion alignment structure located in the display area A can help the liquid crystal molecules to align with predetermined direction(s), and the agglomerates 120, lacking particular alignment directions, located in the non-display area B can cause the liquid crystal molecules in the non-display area B to tilt toward various directions for forming an excellent dark area. As such,

the possibility of the light leakage of the display panel 100 is decreased, and the contrast and the displaying quality of the display panel 100 are improved.

[0027] The aforementioned nano-protrusion alignment structure and the agglomerates 120 located in different designated areas may be manufactured by various processes. For example, via the design of a patterned electrode, wherein the patterned electrode is not formed on the area of the substrate corresponding to the non-display area B, the monomers located corresponding to the non-display area B are therefore not influenced by the electric field while being cured by UV irradiation. Alternatively, a patterned mask is applied to shield the non-display area B while the monomers are irradiated with UV light and applied with a continuously electric field, such that the monomers in the non-display area B do not undergo polymerization reaction, and the monomers in the non-display area B undergo polymerization under UV irradiation after the electric field is removed.

[0028] Furthermore, the above-mentioned shielding design from the UV irradiation for the non-display area B can utilize additional patterned masks or structural arrangements of originally existing elements in the display panel. For example, a metal wiring or a black matrix located in the non-display area B can be used for shielding the non-display area B from UV irradiation. The black matrix can be designed as a patterned black matrix with through holes for UV light to pass through, such that the monomers in the non-display area B may undergo polymerization reaction to form the agglomerates 120. In the embodiment, the UV irradiation is preferably performed from the substrate side without the color filter layer disposed thereon.

[0029] In other words, the formation of a number of the agglomerates 120, which are irregularly arranged and lack alignment functions, in the non-display area B can further consume the residual monomers in the liquid crystal layer 150. As such, the polar impurities absorbed by the un-reacted monomers in the liquid crystal layer 150 or that the residual monomers polymerize and form protrusion structures with alignment functions in the non-display area B can be reduced. Accordingly, deterioration of materials is reduced, light leakage of the display panel is decreased, and the contrast and displaying quality of the display panel can be further improved.

[0030] FIG. 2 shows a cross-sectional view of a display panel 200 according to another embodiment of the present disclosure. As shown in FIG. 2, a plurality of the agglomerates 120 may be further disposed on the second substrate 130. In the embodiment, in the non-display area B, the distribution density of the agglomerates 120 located on the first substrate 110 is different from the distribution density of the agglomerates 120 located on the second substrate 130. For example, while the agglomerates 120 are formed by a UV curing process performed on UV curable monomers, the agglomerates 120 formed on the UV irradiation side of the substrate, which side is closer to the UV light, have a relatively high dis-

tribution density and a relatively large size. Alternatively, the sizes and the locations of the agglomerates 120 can be controlled by adjusting the focus or the wavelength range of the UV irradiation.

[0031] In an embodiment, in the non-display area B, the distribution density of the agglomerates 120 having a size of 50-100 nm located on the first substrate 110 is lower than the distribution density of the agglomerates 120 located on the second substrate 130. In the present embodiment, the agglomerates 120 are formed by a UV irradiation process performed on UV curable monomers, and the UV irradiation process is performed from the second substrate 130 side.

[0032] FIG. 3 shows a top view of a display panel 300 according to a further embodiment of the present disclosure. As shown in FIG. 3, the seal 140 has a first width W1 and a first sidewall 140s, and the first sidewall 140s is adjacent to the non-display area B. The non-display area B can be divided into two regions B1 and B2. The region B1 includes the range starting from the first sidewall 140s and extending a second width W2 away from the first sidewall 140s, the second width W2 is the distance between the first sidewall 140s and the second sidewall B1s, and the second width W2 is less than the first width W1. The region B2 includes a range starting from the second sidewall B1s and extending a third width W3 away from the second sidewall B1s, the third width W3 is the distance between the second sidewall B1s and the third sidewall B2s, and the third width W3 is larger than one time the first width W1 to less than two times the first width W1. In the embodiment, the distribution density of the agglomerates 120 on the second substrate 130 and located in the region B1 is different from the distribution density of the agglomerates 120 located in the region B2. The amount of the agglomerates 120 having a size of 50-100 nm located in the region B1 is more than the amount of the agglomerates 120 having a size of 50-100 nm located in the region B2. In the embodiment, by controlling the range the UV irradiation covers and the wavelength of the UV irradiation, the agglomerates 120 can be formed together with the curing of the seal 140 by the UV irradiation process. Accordingly, the seal 140 and the agglomerates 120 can be formed in single UV irradiation step. As such, the irradiation energy is reduced, the monomers neighboring the seal 140 can react together and form the agglomerates 120 having relatively large sizes, and the light leakage of the display panel can be further reduced.

[0033] FIG. 4 shows a top view of a display panel 400 according to a still further embodiment of the present disclosure. In the embodiment, as shown in FIG. 4, the non-display area B' is disposed adjacent to the display area A' but not surrounding the display area A'. The distribution density of the agglomerates 120 located in at least a portion of the non-display area B' is different from the distribution density of the agglomerates 120 located in the display area A'. In an embodiment, the distribution density of the agglomerates 120 having a size of 10-100

nm located in the non-display area B' is higher than the distribution density of the agglomerates 120 having a size of 10-100 nm located in the display area A'. In another embodiment, the distribution density of the agglomerates 120 (with no size limitation) located in at least a portion of the non-display area B' is higher than the distribution density of the agglomerates 120 (with no size limitation) located in the display area A'.

[0034] FIG. 5 shows a simplified explosion diagram of a display device 500 according to an embodiment of the present disclosure, and FIG. 6 shows a cross-sectional view of a display device 600 according to another embodiment of the present disclosure. It is to be noted that some of the elements in FIGS. 5-6 are omitted or simplified for illustrating the embodiments. The details of the structures of the embodiments are not drawn to scale and for exemplification only, thus not for limiting the scope of protection of the disclosure. In the present embodiment, the seal 540 is adjacent to and aligned with the sidewalls of the substrates 110/130. In an alternative embodiment, the seal is not necessarily adjacent to the sidewalls of the substrate 110/130.

[0035] Referring to FIGS. 5-6, the display device 500 includes a display panel 500A. The display panel 500A includes the first substrate 110, the second substrate 130, at least a data line DL, at least a scan line SL, a trace area D, the liquid crystal layer 550, the alignment layer 570, the spacers 560, the seal 540, and the agglomerates 120. The first substrate 110 and the second substrate 130 are disposed opposite to each other. The first substrate 110 has at least a pixel area C having a plurality of pixels P. The data line DL and the scan line SL are intersected for defining the pixel area C. The trace area D is located outside the pixel area C. The liquid crystal layer 550 and the alignment layer 570 are disposed between the first substrate 110 and the second substrate 130. The spacers 560 are disposed between the first substrate 110 and the second substrate 130 for providing a gap for disposing the liquid crystal layer 550. The seal 540 is disposed between the first substrate 110 and the second substrate 130 and located outside the trace area D. The agglomerates 120 are formed on the alignment layer 570. The distribution density of the agglomerates 120 located corresponding to at least a portion of the trace area D is higher than the distribution density of the agglomerates 120 located corresponding to the pixel area C.

[0036] In the embodiment, the display panel 500A includes, for example, two alignment layers 570 formed on the first substrate 110 and the second substrate 130, respectively. The agglomerates 120 are formed on at least one of the alignment layers 570 on at least one of the first substrate 110 or the second substrate 130. The above-mentioned agglomerates 120 located corresponding to the trace area D or corresponding to the pixel area C may be formed on both of the alignment layer 570 on the first substrate 110 and the second substrate 130. In fact, the above-mentioned agglomerates 120 located

corresponding to the trace area D or corresponding to the pixel area C simply refers to the range which the agglomerates 120 are located corresponding to.

[0037] As shown in FIGS. 5-6, the display device 500 may further include a black matrix (BM) 580, a thin film transistor array 590, and a color filter layer 591. The thin film transistor array 590 and the color filter layer 591 are disposed on the first substrate 110, and the black matrix 580 is disposed on the second substrate 130. In the embodiment, the trace area D may include one or more than one driver on panel 585, such as a gate driver on panel (GOP) or a data drive on panel or both of the above. One set of GOP is illustrated in FIG. 5; however, a plurality sets of the gate driver and/or the data drive on panel may be arranged as well depending on the design requirements.

[0038] In an embodiment, in the trace area D, the distribution density of the agglomerates 120 on the first substrate 110 is different from the distribution density of the agglomerates 120 on the second substrate 130.

[0039] In an embodiment, in the trace area D, the distribution density of the agglomerates 120 having a size of 10-50 nm is higher than the distribution density of the agglomerates 120 having a size of 50-100 nm.

[0040] In an embodiment, referring to FIGS. 3 and 5-6, the seal 540 has the first width W1 and the first sidewall 540s adjacent to the trace area D. The trace area D can be divided into two regions. The first region includes the range starting from the first sidewall 540s and extending the second width W2 away from the first sidewall 540s, and the second width W2 is less than the first width W1. The second region includes a range starting from the first region and extending the third width W3 away from the sidewall adjacent to the first region, and the third width W3 is higher than one time the first width W1 to less than two times the first width W1. In the embodiment, the distribution density of the agglomerates 120 on the second substrate 130 and located in the first region is different from the distribution density of the agglomerates 120 located in the second region.

[0041] While the invention has been described by way of example and in terms of the preferred embodiment(s), it is to be understood that the invention is not limited thereto. On the contrary, it is intended to cover various modifications and similar arrangements and procedures, and the scope of the appended claims therefore should be accorded the broadest interpretation so as to encompass all such modifications and similar arrangements and procedures.

Claims

1. A display device, comprising:

a display panel, comprising:

a first substrate and a second substrate dis-

posed opposite to the first substrate, wherein the first substrate has at least a pixel area having a plurality of pixels;
at least a data line and at least a scan line intersected for defining the pixel area;
a trace area located outside the pixel area;
a liquid crystal layer and an alignment layer disposed between the first substrate and the second substrate;
a plurality of spacers disposed between the first substrate and the second substrate;
a seal disposed between the first substrate and the second substrate and located outside the trace area; and
a plurality of agglomerates formed on the alignment layer;

wherein the distribution density of the agglomerates located corresponding to at least a portion of the trace area is higher than the distribution density of those located corresponding to the pixel area.

2. The display device according to claim 1, wherein the distribution density of the agglomerates having a size of 10-100 nm located in the trace area is higher than the distribution density of those located in the pixel area.

3. The display device according to claim 1, wherein the distribution density of the agglomerates located in the trace area on the first substrate is different from the distribution density of those on the second substrate.

4. The display device according to claim 1, wherein the distribution density of the agglomerates located in the trace area having a size of 10-50 nm is higher than the distribution density of those having a size of 50-100 nm.

5. The display device according to claim 1, wherein the seal has a first width and a first sidewall, the first sidewall is adjacent to the trace area, and the distribution density of the agglomerates located on the second substrate within a range starting from the first sidewall to less than one time the first width away from the first sidewall is different from the distribution density of those within a range starting from higher than one time the first width to less than three times the first width away from the first sidewall.

6. The display device according to claim 1, wherein the distance between the agglomerates having a size of 50-100 nm located in the trace area is different from the distance between those located in the pixel area.

7. The display device according to claim 1, wherein the

distribution density of the agglomerates having a size of 50-100 nm located in the trace area on the first substrate is lower than the distribution density of those on the second substrate.

8. The display device according to claim 1, wherein the trace area is adjacent to the pixel area.
9. The display device according to claim 1, further comprising a black matrix on the second substrate.
10. The display device according to claim 1, further comprising a thin film transistor array on the first substrate.
11. The display device according to claim 1, further comprising a color filter layer on the first substrate.
12. The display device according to claim 1, wherein the trace area comprises a gate driver on panel (GOP) or a data driver on panel.

Amended claims in accordance with Rule 137(2) EPC.

1. A vertically-aligned LCD display device, comprising:

a display panel (100), comprising:

a first substrate (110) and a second substrate (130) disposed opposite to the first substrate (110), wherein the first substrate (110) has at least a pixel area having a pixel; at least a data line and at least a scan line intersected for defining the pixel area; a wiring area (D) located outside the pixel area; a liquid crystal layer (150) disposed between the first substrate (110) and the second substrate (130); two alignment layers (170) on the first substrate (110) and the second substrate (130), respectively; a plurality of spacers disposed between the first substrate (110) and the second substrate (130); a seal (140) disposed between the first substrate (110) and the second substrate (130) and located outside the wiring area (D); and a plurality of agglomerate polymer particles (120) formed on at least one of the alignment layers (170);

wherein the number of the agglomerate polymer particles (120) per unit area located corresponding to at least a portion of the wiring area (D) is higher than the number of the agglomerate polymer particles (120) per unit area of those located corresponding to the pixel area.

polymer particles (120) per unit area of those located corresponding to the pixel area.

2. The vertically-aligned LCD display device according to claim 1, wherein the number of the agglomerate polymer particles (120) per unit area having a size of 10-100 nm located in the wiring area (D) is higher than the number of the agglomerate polymer particles (120) per unit area of those located in the pixel area.
3. The vertically-aligned LCD display device according to claim 1, wherein the number of the agglomerate polymer particles (120) per unit area located in the wiring area (D) on the first substrate (110) is different from the number of the agglomerate polymer particles (120) per unit area of those on the second substrate.
4. The vertically-aligned LCD display device according to claim 1, wherein the number of the agglomerate polymer particles (120) per unit area located in the wiring area (D) having a size of 10-50 nm is higher than the number of the agglomerate polymer particles (120) per unit area of those having a size of 50-100 nm.
5. The vertically-aligned LCD display device according to claim 1, wherein the seal (140) has a first width (W1) and a first sidewall (140s), the first sidewall (140s) is adjacent to the wiring area (D), and the number of the agglomerate polymer particles (120) per unit area located on the second substrate (130) within a range starting from the first sidewall (140s) to less than one time the first width (W1) away from the first sidewall (140s) is different from the number of the agglomerate polymer particles (120) per unit area of those within a range starting from higher than one time the first width (W1) to less than three times the first width (W1) away from the first sidewall (140s).
6. The vertically-aligned LCD display device according to claim 1, wherein the distance between the agglomerates having a size of 50-100 nm located in the wiring area (D) is different from the distance between those located in the pixel area.
7. The vertically-aligned LCD display device according to claim 1, wherein the number of the agglomerate polymer particles (120) per unit area having a size of 50-100 nm located in the wiring area (D) on the first substrate (110) is lower than the number of the agglomerate polymer particles (120) per unit area of those on the second substrate (130).
8. The vertically-aligned LCD display device according to claim 1, wherein the wiring area (D) is adjacent to

the pixel area.

9. The vertically-aligned LCD display device according to claim 1, further comprising a black matrix on the second substrate (130). 5
10. The vertically-aligned LCD display device according to claim 1, further comprising a thin film transistor array on the first substrate (110). 10
11. The vertically-aligned LCD display device according to claim 1, further comprising a color filter layer on the first substrate (110).
12. The vertically-aligned LCD display device according to claim 1, wherein the trace area comprises a gate driver on panel (GOP) or a data driver on panel. 15

20

25

30

35

40

45

50

55




FIG. 1A




FIG. 1B

200




FIG. 2

300




FIG. 3

400




FIG. 4

500




FIG. 5




FIG. 6



EUROPEAN SEARCH REPORT

Application Number
EP 13 19 1535

DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 2008/252807 A1 (HUANG SHUI [TW] ET AL) 16 October 2008 (2008-10-16) * paragraphs [0007], [0008] * * figures 1A, 1B *	1	INV. G02F1/1337 G02F1/1333
A	US 2011/304526 A1 (ITOH MASATOSHI [JP]) 15 December 2011 (2011-12-15) * paragraphs [0005], [0042] - [0047] * * figures 1,6 *	1-12	ADD. G02F1/137
X	US 2010/188623 A1 (NAKAGAWA HIDETOSHI [JP]) 29 July 2010 (2010-07-29) * paragraphs [0013] - [0021] * * figures 18-20 *	1 2-12	
A	HANAOKA K ET AL: "40.1: A New MVA-LCD by Polymer Sustained Alignment Technology", 2004 SID INTERNATIONAL SYMPOSIUM. SEATTLE, WA, MAY 25 - 27, 2004; [SID INTERNATIONAL SYMPOSIUM], SAN JOSE, CA : SID, US, vol. XXXV, 25 May 2004 (2004-05-25), pages 1200-1203, XP007011936, * figure 2 * * Also the rest of the document. *	1-12	TECHNICAL FIELDS SEARCHED (IPC) G02F
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 31 March 2014	Examiner Thomas, Kenneth
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03.82 (P04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 13 19 1535

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

31-03-2014

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2008252807 A1	16-10-2008	TW 200841103 A US 2008252807 A1	16-10-2008 16-10-2008
US 2011304526 A1	15-12-2011	CN 102308251 A US 2011304526 A1 WO 2010090039 A1	04-01-2012 15-12-2011 12-08-2010
US 2010188623 A1	29-07-2010	CN 101765806 A US 2010188623 A1 WO 2009037889 A1	30-06-2010 29-07-2010 26-03-2009

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

专利名称(译)	使用在取向层上形成的聚合物颗粒在垂直取向的液晶显示器中减少漏光		
公开(公告)号	EP2843466A1	公开(公告)日	2015-03-04
申请号	EP2013191535	申请日	2013-11-05
[标]申请(专利权)人(译)	群创光电股份有限公司		
申请(专利权)人(译)	群创光电		
当前申请(专利权)人(译)	群创光电		
[标]发明人	HSU HSU KUAN CHU HSIA CHING LIU KUEI LING CHEN FU CHENG CHIU KUO HAO		
发明人	HSU, HSU-KUAN CHU, HSIA-CHING LIU, KUEI-LING CHEN, FU-CHENG CHIU, KUO-HAO		
IPC分类号	G02F1/1337 G02F1/1333 G02F1/137		
CPC分类号	G02F1/133753 G02F1/133788 G02F1/1393 G02F2001/133388 G02F2001/133776 G02F2001/13396 G02F2202/36 G02F1/1337 G02F1/1339 G02F1/13392 G02F1/13394 G02F1/136209 G02F2001/13775		
审查员(译)	THOMAS , KENNETH		
优先权	102130893 2013-08-28 TW		
其他公开文献	EP2843466B1		
外部链接	Espacenet		

摘要(译)

公开了一种垂直对准的LCD (100) , 其通过减少非显示区域中的漏光而改善了对比度和显示质量。通过选择性照射存在于取向层或LC层中的单体, 在取向层 (170) 上形成与LC单元中的液晶 (LC) 层 (150) 直接接触的附聚颗粒 (120) 。这些颗粒在非显示区域 (B) 中比在显示区域 (A) 中更密集地分布。显示区域中的颗粒在施加电场的情况下形成, 该电场使它们在优选方向上对准 (形成纳米突起) , 从而在那里提供LC分子的排序;然而, 在非显示区域中形成颗粒期间没有施加场: 这些在形状, 尺寸和取向上变化很大, 防止了LC层的排序并且大大减少了那里的漏光。




FIG. 1A