



(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
11.09.2019 Bulletin 2019/37

(51) Int Cl.:
G02F 1/1343 (2006.01)

(21) Application number: **17842410.7**

(86) International application number:
PCT/CN2017/093658

(22) Date of filing: **20.07.2017**

(87) International publication number:
WO 2018/129898 (19.07.2018 Gazette 2018/29)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
MA MD

• **Hefei Xinsheng Optoelectronics Technology Co., Ltd**
Anhui 230012 (CN)

(72) Inventors:
• **JIANG, Liangliang**
Beijing 100176 (CN)
• **GAN, Quan**
Beijing 100176 (CN)

(30) Priority: **10.01.2017 PCT/CN2017/001767**

(74) Representative: **AWA Sweden AB**
P.O. Box 45086
104 30 Stockholm (SE)

(71) Applicants:
• **BOE Technology Group Co., Ltd.**
Beijing 100015 (CN)

(54) **SUBPIXEL UNIT AND CONTROL METHOD THEREFOR, PIXEL UNIT, ARRAY SUBSTRATE, AND DISPLAY DEVICE**

(57) The present invention provides a sub-pixel unit and a method of controlling the same, a pixel unit, an array substrate, and a display device. In one embodiment, a sub-pixel unit includes: at least two subpixels. Each of the at least two subpixels includes: a first electrode; a second electrode; and a liquid crystal layer controlled by a voltage between the first electrode and the second electrode; at least one of the first electrode and the second electrode is a slit electrode. The two subpixels have different initial twist angles, and the initial twist angle is an included angle between a slit of the slit electrode and liquid crystal molecules oriented when the liquid crystal layer is in an initial unpowered state, in the respective subpixel.




FIG. 3

Description

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to Chinese Patent Application No. 201710017676.5 filed on January 10, 2017 in the State Intellectual Property Office of China, the disclosure of which are hereby incorporated by reference in their entirety.

TECHNICAL FIELD

[0002] The present invention relates to the field of liquid crystal display technology, and particularly, to a sub-pixel unit and a method of controlling the same, a pixel unit, an array substrate, a display device.

BACKGROUND

[0003] Currently, in the field of Thin Film Transistor-Liquid Crystal Display (TFT-LCD), IPS (In-Plane Switching) and FFS (Fringe Field Switching) modes are used more and more widely due to their advantages of wide visual angle, high transmittance, fast response and the like.

[0004] Regarding a liquid crystal display panel, transmittance T_r and driving voltage V_{op} are important parameters which affect performance and competitiveness of products. Higher transmittance indicates that the backlight brightness is lower or the power consumption is lower, while higher driving voltage indicates that power consumption of the liquid crystal display panel is higher.

SUMMARY

[0005] According to an aspect of the present invention, there is provided a sub-pixel unit. The sub-pixel unit comprises: at least two subpixels; each of the at least two subpixels comprises: a first electrode; a second electrode; and a liquid crystal layer controlled by a voltage between the first electrode and the second electrode; at least one of the first electrode and the second electrode is a slit electrode; and the at least two subpixels have different initial twist angles, and the initial twist angle is an included angle between a slit of the slit electrode and liquid crystal molecules oriented when the liquid crystal layer is in an initial unpowered state, in the respective subpixel.

[0006] In at least some embodiments, in the above sub-pixel unit, the at least two subpixels comprise: a first subpixel and a second subpixel; wherein, the first subpixel has an initial twist angle of θ_1 ; the second subpixel has an initial twist angle of θ_2 ; and, both the θ_1 and the θ_2 are less than 15° .

[0007] In at least some embodiments, in the above sub-pixel unit, the θ_1 and the θ_2 are two different ones selected from a group consisting of 5° , 7° , 11° .

[0008] According to another aspect of the present in-

vention, there is also provided a pixel unit. The pixel unit comprises: several sub-pixel units, and at least one of the several sub-pixel units is any one of the abovementioned sub-pixel unit.

[0009] In at least some embodiments, in the above pixel unit, the several sub-pixel units comprise: a red sub-pixel unit, a green sub-pixel unit and a blue sub-pixel unit; the red sub-pixel unit comprises: a first red subpixel and a second red subpixel having different initial twist angles; the green sub-pixel unit comprises: a first green subpixel and a second green subpixel having different initial twist angles; and the blue sub-pixel unit comprises: a first blue subpixel and a second blue subpixel having different initial twist angles.

[0010] In at least some embodiments, in the above pixel unit, the first red subpixel, the first green subpixel and the first blue subpixel have the same initial twist angle of θ_1 ; and the second red subpixel, the second green subpixel and the second blue subpixel have the same initial twist angle of θ_2 .

[0011] In at least some embodiments, in the above pixel unit, two subpixels of the same sub-pixel unit are arranged in a first direction; and the same type of subpixels of different sub-pixel units are arranged sequentially in a second direction that is neither coincident with nor parallel to the first direction.

[0012] In at least some embodiments, in the above pixel unit, two subpixels of the same sub-pixel unit are arranged in a first direction; and the first subpixels and the second subpixels of different sub-pixel units are arranged alternately in a second direction that is neither coincident with nor parallel to the first direction.

[0013] In at least some embodiments, in the above pixel unit, two subpixels of the same sub-pixel unit are arranged in a first direction; and the first subpixels and the second subpixels of different sub-pixel units are arranged randomly in a second direction that is neither coincident with nor parallel to the first direction.

[0014] According to yet another aspect of the present invention, there is also provided an array substrate. The array substrate comprises: a base substrate; and an array of pixel units disposed on the base substrate and comprising a plurality of pixel units arranged in array; at least one pixel unit of the plurality of pixel units is any one of the abovementioned pixel unit.

[0015] In at least some embodiments, the array substrate further comprises: gate lines and data lines formed on the base substrate; wherein, in the at least one pixel unit, two subpixels of the same sub-pixel unit share the same gate line and are controlled by different data lines.

[0016] In at least some embodiments, in the array substrate, at least one pixel unit of the plurality of pixel units in the array of pixel units is any one of the abovementioned pixel unit; the array substrate further comprises: gate lines and data lines formed on the base substrate; wherein, the first direction is along a direction of the data lines and the second direction is along a direction of the gate lines.

[0017] In at least some embodiments, in the array substrate, the array substrate is an array substrate with an IPS mode or an FFS mode; wherein the subpixel of the pixel unit comprises: a pixel electrode and a common electrode separated by an insulation layer; the first electrode is one of the pixel electrode and the common electrode, and the second electrode is the other of the pixel electrode and the common electrode.

[0018] According to still another aspect of the present invention, there is also provided a display device. The display device comprises: any one of the abovementioned array substrate.

[0019] According to still yet another aspect of the present invention, there is also provided a method of controlling any one of the abovementioned sub-pixel unit. The method comprises: a step A of, acquiring a sub-pixel unit required display luminance value; and a step B of, selecting a corresponding working mode from a group of arrangements of the at least two subpixels, according to the sub-pixel unit required display luminance value.

[0020] In at least some embodiments, in the method, the at least two subpixels comprises: a first subpixel and a second subpixel, the first subpixel has an initial twist angle of θ_1 , the second subpixel has an initial twist angle of θ_2 , and, $\theta_1 > \theta_2$; wherein, the step B comprises: a sub-step B1 of, judging, if $\Delta < \Delta_2$, that the sub-pixel unit requires to display in a low luminance, and controlling only the first subpixel of the sub-pixel unit to work; a sub-step B2 of, judging, if $\Delta_2 \leq \Delta < \Delta_1$, that the sub-pixel unit requires to display in a medium luminance, and controlling only the second subpixel of the sub-pixel unit to work; and, a sub-step B3 of, judging, if $\Delta \geq \Delta_1$, that the sub-pixel unit requires to display in a high luminance, and controlling the first subpixel and the second subpixel of the sub-pixel unit to work simultaneously; in which, Δ is the sub-pixel unit required display luminance value, Δ_1 is a first luminance threshold, Δ_2 is a second luminance threshold, and $\Delta_1 > \Delta_2$.

BRIEF DESCRIPTION OF THE DRAWINGS

[0021]

FIG. 1 is a schematic view showing a sub-pixel unit which adopts a pixel structure having two symmetrical upper and lower domains and a pixel electrode of slit design.

FIG. 2 is a simulated diagram showing a relationship between a transmittance T_r and a driving voltage V_{op} of the sub-pixel unit shown in FIG. 1.

FIG. 3 is a structural schematic view showing a sub-pixel unit according to an embodiment of the present invention.

FIG. 4 is a flow diagram showing a method of controlling the sub-pixel unit shown in FIG. 3.

FIG. 5 is a structural schematic view showing a pixel unit according to an embodiment of the present invention.

FIG. 6 is a schematic view showing a modification of the pixel unit shown in FIG. 5.

FIG. 7 is a schematic view showing an array of pixel units in an array substrate according to an embodiment of the present invention.

FIG. 8 is a schematic view showing an array of pixel units in an array substrate according to another embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0022] FIG. 1 is a schematic view showing a sub-pixel unit which adopts a pixel structure having two symmetrical upper and lower domains and a pixel electrode of slit design. As shown in FIG. 1, the sub-pixel unit adopts a pixel structure having two symmetrical upper and lower domains and a pixel electrode of slit design. For this sub-pixel unit, rubbing occurs in a horizontal direction, to induce liquid crystal molecules to align in the horizontal direction. Here, an included angle between a slit of the slit electrode and liquid crystal molecules oriented in an initial unpowered state is named as initial twist angle. Based on different initial twist angles, a driving voltage and transmittance relationship curve (V-T curve) of the pixel is different.

[0023] FIG. 2 is a simulated diagram showing a relationship between a transmittance T_r and a driving voltage V_{op} of the sub-pixel unit shown in FIG. 1. As shown in FIG. 2, in a pixel having an initial twist angle of 5° , the liquid crystal molecule has a higher transmittance T_r and a higher driving voltage V_{op} , as well as higher luminance and power consumption. In a pixel having an initial twist angle of 7° , it has a lower transmittance T_r and a lower driving voltage V_{op} , as well as lower luminance and power consumption.

[0024] In an existing TFT-LCD liquid crystal display panel, the double domain pixel structure has only one slit angle design of the slit electrode, which only corresponds to one voltage and transmittance (V-T) curve of the pixel. To meet different requirements of luminance and power consumption, it responds relatively slowly, so the applicability and usable range are greatly reduced.

[0025] Currently, an aim of designing a liquid crystal display panel is to pursue high transmittance, but the problem is that it inevitably increases power consumption. During actual working process of the liquid crystal display panel, in many cases, the pixels are required only to display in low gray scale and in low luminance, while more attention is paid on requirements of power consumption and energy savings. However, at present, a liquid crystal panel with a normal design of slit electrode and initial twist angle often has a single function and cannot achieve management and control of multi-level, multi-luminance and different power consumption requirements.

[0026] The present invention proposes a novel design of sub-pixel unit, which can be compatible with the requirements of high luminance and high power consumption.

tion as well as low luminance and low power consumption. Based on the design scheme of the sub-pixel unit, the present invention also provides a sub-pixel unit and a method of controlling the same, an array substrate, and a display device.

[0027] In order to provide a more clear understanding of objects, technique solutions and advantages of the present invention, the present invention will be further described hereinafter in detail in conjunction with specific embodiments and with reference to the attached drawings.

[0028] According to one aspect of the present invention, there is provided a sub-pixel unit. The sub-pixel unit comprises: at least two subpixels. Each of the subpixels comprises: a first electrode; a second electrode; and a liquid crystal layer controlled by a voltage between the first electrode and the second electrode. At least one of the first electrode and the second electrode is a slit electrode. The two subpixels have different initial twist angles, and the initial twist angle is an included angle between a slit of the slit electrode and liquid crystal molecules oriented when the liquid crystal layer is in an initial unpowered state, in the respective subpixel.

[0029] For one pixel unit, it typically comprises: a red sub-pixel unit, a green sub-pixel unit and a blue sub-pixel unit. For some types of pixel units, the pixel unit may further comprise: a white sub-pixel unit. The above sub-pixel unit may be: any one of the red sub-pixel unit, the green sub-pixel unit, the blue sub-pixel unit and the white sub-pixel unit, or else may be other types of sub-pixel units. Moreover, the sub-pixel unit may comprise two subpixels, or else may comprise three, four, five or more subpixels, as long as two of these subpixels have different initial twist angles, all of which are within the scope of the present invention.

[0030] For the first electrode and the second electrode, they indicate electrode layers which are located on either side of the liquid crystal layer and for supplying the liquid crystal layer with control voltage. Types, materials and the likes of the first electrode and the second electrode are not limited in the embodiments of the present invention. For the slit electrode and the pixel layer and the likes, there are general meanings for them in the art, which is not to be discussed herein. The slit electrode may be provided in the first electrode, or may be provided in the second electrode.

[0031] In an exemplary embodiment of the present invention, there is provided a sub-pixel unit. FIG. 3 is a structural schematic view showing a sub-pixel unit according to an embodiment of the present invention. As shown in FIG. 3, in this embodiment, the sub-pixel unit comprises a first subpixel Sub₁ and a second subpixel Sub₂. The first subpixel Sub₁ has an initial twist angle of θ_1 ; the second subpixel Sub₂ has an initial twist angle of θ_2 ; $\theta_1 \neq \theta_2$.

[0032] Taking light efficiency of the liquid crystal layer and transmittance of the liquid crystal panel into consideration, the initial twist angle of the subpixel is preferably

less than 15° . Typically, the initial twist angles of the two subpixels are two different ones selected from a group consisting of 5° , 7° , and 11° . For a sub-pixel unit comprising a first subpixel and a second subpixel, values of the initial twist angle may be as follows.

(1) The first subpixel has an initial twist angle θ_1 of 5° , and the second subpixel has an initial twist angle θ_2 of 7° .

(2) The first subpixel has an initial twist angle θ_1 of 7° , and the second subpixel has an initial twist angle θ_2 of 11° .

(3) The first subpixel has an initial twist angle θ_1 of 5° , and the second subpixel has an initial twist angle θ_2 of 11° .

[0033] In this embodiment, the initial twist angle θ_1 of the first subpixel Sub₁ is 11° , and the initial twist angle θ_2 of the second subpixel Sub₂ is 5° . The sub-pixel unit can be operated in one of the following four working modes.

(1) In a first working mode, the first subpixel Sub₁ works while the second subpixel Sub₂ does not work, in this case, the transmittance is relatively low and the power consumption is low.

(2) In a second working mode, the first subpixel Sub₁ does not work while the second subpixel Sub₂ works, in this case, the transmittance increases and the power consumption increases.

(3) In a third working mode, the first subpixel Sub₁ and the second subpixel Sub₂ work simultaneously, in this case, the transmittance reaches a maximum, and, it displays in a maximum luminance, so the power consumption also reaches a maximum.

(4) In a fourth working mode, both the first subpixel Sub₁ and the second subpixel Sub₂ do not work, in this case, the red sub-pixel unit is completely opaque.

[0034] Please referring to FIG. 3, for the sub-pixel unit according to this embodiment, the first subpixel Sub₁ and the second subpixel Sub₂ share one gate line Gate_n to control gate signal of a corresponding thin-film transistor, and adopt two data lines Data_{m_1} and Data_{m_2} to provide data signals, respectively, to achieve independent controls of the first subpixel and the second subpixel.

[0035] On the basis of the abovementioned sub-pixel unit, the present invention also provides a method of controlling a sub-pixel unit. In this method, the first subpixel and the second subpixel are controlled independently and respectively in accordance with sub-pixel unit required display luminance value.

[0036] FIG. 4 is a flow diagram showing a method of controlling the sub-pixel unit shown in FIG. 3. Please referring to FIG. 4, according to this embodiment, the method of controlling the sub-pixel unit comprises:

a step A of, acquiring a sub-pixel unit required display luminance value Δ ; and
 a step B of, selecting a corresponding working mode from a group of arrangements of the at least two subpixels, according to the sub-pixel unit required display luminance value Δ .

[0037] Specifically, a first luminance threshold $\Delta 1$ and a second luminance threshold $\Delta 2$ are preset, and $\Delta 1 > \Delta 2$, the step B comprises the following.

[0038] There is a sub-step B1 of, judging, if $\Delta < \Delta 2$, that the sub-pixel unit requires to display in a low luminance, and controlling only the first subpixel of the sub-pixel unit to work.

[0039] Since the initial twist angle in the first subpixel is relatively great, the transmittance is relatively low, at the same time, the power consumption for driving the panel is relatively low, which achieves energy saving.

[0040] There is a sub-step B2 of, judging, if $\Delta 2 \leq \Delta < \Delta 1$, that the sub-pixel unit requires to display in a medium luminance, and controlling only the second subpixel of the sub-pixel unit to work.

[0041] Since the initial twist angle in the second subpixel is relatively small, the transmittance increases, at the same time, the power consumption for driving the panel increases slightly.

[0042] There is a sub-step B3 of, judging, if $\Delta \geq \Delta 1$, that the sub-pixel unit requires to display in a high luminance, and controlling the first subpixel and the second subpixel of the sub-pixel unit to work simultaneously.

[0043] In this case, transmittance of the sub-pixel unit as a whole greatly increases, which achieves a high luminance displaying.

[0044] The above merely illustrates one method of controlling the sub-pixel unit, as an example, however, those skilled in the art can envisage other types of controlling methods based on the above description, and it is not discussed in detail herein.

[0045] Thus it can be seen, in this embodiment, the sub-pixel unit is designed to include two subpixels having different initial twist angles, and the two subpixels are controlled respectively, which can be compatible with the requirements of high luminance and high power consumption as well as low luminance and low power consumption so that the liquid crystal display device has wider applicability and usable range.

[0046] On the basis of the abovementioned sub-pixel unit, according to another aspect of the present invention, there is also provided a pixel unit. The pixel unit comprises several sub-pixel units, and at least one of the several sub-pixel units is the aforementioned sub-pixel unit provided according to embodiments of the present invention.

[0047] In an exemplary embodiment of the present invention, there is provided a pixel unit. FIG. 5 is a structural schematic view showing a pixel unit according to an embodiment of the present invention. As shown in FIG. 5, in this embodiment, the pixel unit comprises: a red sub-pixel unit Sub_R , a green sub-pixel unit Sub_G and a blue

sub-pixel unit Sub_B . The three sub-pixel units are the ones according to the abovementioned embodiments. Namely, the red sub-pixel unit Sub_R comprises: the first red subpixel Sub_{R_1} and the second red subpixel Sub_{R_2} ; the green sub-pixel unit Sub_G comprises: the first green subpixel Sub_{G_1} and the second green subpixel Sub_{G_2} ; and the blue sub-pixel unit Sub_B comprises: the first blue subpixel Sub_{B_1} and the second blue subpixel Sub_{B_2} .

[0048] The first red subpixel Sub_{R_1} of the red sub-pixel unit, the first green subpixel Sub_{G_1} of the green sub-pixel unit and the first blue subpixel Sub_{B_1} of the blue sub-pixel unit have the same initial twist angle, of $\theta_1 = 11^\circ$. The second red subpixel Sub_{R_2} of the red sub-pixel unit, the second green subpixel Sub_{G_2} of the green sub-pixel unit and the second blue subpixel Sub_{B_2} of the blue sub-pixel unit have the same initial twist angle, of $\theta_2 = 5^\circ$.

[0049] It can be understood by those skilled in the art that,

(1) in the present embodiment, the description is implemented by taking a pixel unit including the red sub-pixel unit Sub_R , the green sub-pixel unit Sub_G and the blue sub-pixel unit Sub_B as an example, however, for the pixel unit consisted of other types of sub-pixel units, as long as it is satisfied that one of the sub-pixel units includes two subpixels having different initial twist angles, all of which are within the scope of the present invention;

(2) in the present embodiment, three sub-pixel units of the pixel unit each is the sub-pixel unit including two subpixels having different initial twist angles, however, the present invention can also be implemented if only some or even one of the sub-pixel units meets this condition;

(3) in the present embodiment, the first subpixels of the three sub-pixel units have the same initial twist angle and the second subpixels have the same initial twist angle, which is only a preferred implementation of the present invention, and it is not limited by the present invention that first (second) initial twist angles of the sub-pixel units are the same, in other embodiments of the present invention, first (second) initial twist angles of different sub-pixel units may be set to be different, which will not affect implementation of the present invention;

(4) for the initial twist angles θ_1 and θ_2 , those skilled in the art can set them according to requirements, and they are not limited to $\theta_1 = 11^\circ$ and $\theta_2 = 5^\circ$ as mentioned above.

[0050] Please see FIG. 5, for each sub-pixel unit of the pixel unit according to the present embodiment, its two subpixel units share one gate line (Gate) to control gate signal of a corresponding thin-film transistor, and adopt two data lines (Data) to provide data signals, respectively, to achieve independent controls of the first subpixel and the second subpixel.

[0051] Green sub-pixel unit Sub_G is taken as an example, its first green subpixel Sub_{G_1} and second green subpixel Sub_{G_2} share a gate line Gate_n , and the data signals are provided by the data lines Data_{m+1_1} and Data_{m+1_2} , respectively.

[0052] Please continue to see FIG. 5, in the pixel unit according to the present embodiment, two subpixels of the same sub-pixel unit are arranged in a direction of data lines, and first (second) subpixels of the sub-pixel units are arranged sequentially in the same row along a direction of gate lines. It should be understood by those skilled in the art that, the abovementioned direction of data lines and the direction of gate lines are presented as a particular case, it is merely required that the two directions are neither coincident with nor parallel to each other.

[0053] FIG. 6 is a schematic view showing a modification of the pixel unit shown in FIG. 5. In the pixel unit shown in FIG. 6, the first subpixels and the second subpixels of different sub-pixel units are arranged alternately in the same row along the direction of gate lines. In addition, in another modification of the pixel unit, the first subpixels and the second subpixels of different sub-pixel units are arranged randomly in the same row along the direction of gate lines. The two modifications can implement the present invention as the pixel unit shown in FIG. 4.

[0054] The pixel unit according to the present embodiment has all advantages of the sub-pixel unit according to the abovementioned embodiments, and they are not discussed repeatedly herein.

[0055] According to another aspect of the present invention, there is also provided an array substrate. The array substrate comprises: a base substrate; gate lines and data lines formed on the base substrate; and an array of pixel units, wherein, the array of pixel units is disposed on the base substrate and comprises a plurality of pixel units arranged in array. In the embodiments, the pixel unit is the abovementioned pixel unit.

[0056] Hereinafter, in order to facilitate the description, a direction of data lines in the array substrate is defined as a first direction, and a direction of gate lines is defined as a second direction.

[0057] It should be explained that, in the present embodiment, it is defined that, the first direction is the direction of data lines, the second direction is the direction of gate lines, and the first direction and the second direction are perpendicular to each other, however, it is limited to this. In other embodiments of the present invention, the first direction is not necessarily the direction of data line and the second direction is not necessarily the direction of gate lines, as long as it is satisfied that the first direction and the second direction are neither coincident with nor parallel to each other.

[0058] On the basis of the pixel unit shown in FIG. 5, according to an embodiment of the present invention, there is provided an array substrate. FIG. 7 is a schematic view showing an array of pixel units in an array substrate

according to an embodiment of the present invention. In the array of pixel units as shown in FIG. 7, an arrangement of red R, green G, and blue B stripes is taken as an example, which presents four pixel units, $\text{Pixel}_{1,1}$, $\text{Pixel}_{1,2}$, $\text{Pixel}_{2,1}$ and $\text{Pixel}_{2,2}$. Each pixel unit comprises: a red sub-pixel unit Sub_R , a green sub-pixel unit Sub_G and a blue sub-pixel unit Sub_B . For any one of the red sub-pixel unit Sub_R , the green sub-pixel unit Sub_G and the blue sub-pixel unit Sub_B , it comprises: a first subpixel and a second subpixel adjacent to each other and arranged in the first direction. And, the first subpixels of the sub-pixel units have the same initial twist angle, of $\theta_1=11^\circ$, and the second subpixels of the sub-pixel units have the same initial twist angle, of $\theta_2=5^\circ$.

[0059] In the second direction, the first subpixels of different sub-pixels are arranged sequentially, or the second subpixels of different sub-pixels are arranged sequentially. For example, it is shown in FIG. 7 as follows.

(1) In a first row, first red subpixels Sub_{R_1} of the red sub-pixel units, first green subpixels Sub_{G_1} of the green sub-pixel units, and first blue subpixels Sub_{B_1} of the blue sub-pixel units are arranged sequentially and circularly.

(2) In a second row, second red subpixels Sub_{R_2} of the red sub-pixel units, second green subpixels Sub_{G_2} of the green sub-pixel units, and second blue subpixels Sub_{B_2} of the blue sub-pixel units are arranged sequentially and circularly.

[0060] Deduced from the above by analogy, the array of pixel units in a display region of the array substrate according to the present embodiment is formed.

[0061] Please continue to see FIG. 5 and FIG. 7, for one sub-pixel unit, its two subpixels share one gate line (Gate) to control gate signal of a corresponding thin-film transistor, and adopt two data lines (Data) to provide data signals, respectively, to achieve independent controls of the first subpixel and the second subpixel.

[0062] For example, for the red sub-pixel unit Sub_R of the pixel unit $\text{Pixel}_{1,1}$ in the top left, it comprises: a first red subpixel Sub_{R_1} and a second red subpixel Sub_{R_2} , which are arranged in the direction of data lines. The first red subpixel Sub_{R_1} and second red subpixel Sub_{R_2} share one gate line Gate_n to control gate signal of a corresponding thin-film transistor, while, the first red subpixel Sub_{R_1} is provided with data signal through the data line Data_{m_1} , and the first red subpixel Sub_{R_1} is provided with data signal through the data line Data_{m_2} .

[0063] The array substrate according to the present embodiment may be an array substrate with an IPS mode or an FFS mode. In this case, each subpixel comprises: a pixel electrode and a common electrode separated by an insulation layer; one of the pixel electrode and the common electrode is a slit electrode. Preferably, the pixel electrode serves as the slit electrode. For an in-plane display technology, generally, an arrangement in which two electrodes both are slit electrodes is not adopted.

[0064] By adopting the arrangement of the subpixels according to the present embodiment, which is simple in arrangement rule, the manufacturing process is simplified accordingly and the signal control is eased. However, it should be noted that, once voltage in some gate line is not stable, all the sub-pixel units on this gate line will be adversely affected, so that a situation where luminance in a whole line in this position is either relatively high or relatively low occurs in the display region, thereby adversely affecting the display effect.

[0065] On the basis of the pixel unit shown in FIG. 6, according to another embodiment of the present invention, there is provided an array substrate. The present embodiment is similar to the above first embodiment of the array substrate, excepting in that, in the same row within the display region, the first subpixels and the second subpixels are arranged alternately.

[0066] FIG. 8 is a schematic view showing an array of pixel units in an array substrate according to another embodiment of the present invention. In the array of pixel units as shown in FIG. 8, an arrangement of red R, green G, and blue B stripes is also taken as an example. The red R, green G, and blue B subpixels in the array substrate are specifically divided into two kinds of subpixels: first subpixels and second subpixels. In the same kind of subpixels, slits of the slit electrodes have the same inclination angle. In these subpixels, the first subpixels have the initial twist angle of 11° , the second subpixels have the initial twist angle of 5° , and the two in the same row are arranged alternately.

[0067] Please continue to see FIG. 8, for any one of the red sub-pixel unit Sub_R , the green sub-pixel unit Sub_G and the blue sub-pixel unit Sub_B , it comprises: a first subpixel and a second subpixel adjacent to each other and arranged in the first direction. In the same row along the second direction, first subpixels and second subpixels of different sub-pixels are arranged alternately. For example, it is shown in FIG. 8 as follows.

(1) In a first row, the first subpixel Sub_{R_1} of the red sub-pixel unit, the second subpixel Sub_{G_2} of the green sub-pixel unit, the first subpixel Sub_{B_1} of the blue sub-pixel unit, the second subpixel Sub_{R_2} of the red sub-pixel unit, the first subpixel Sub_{G_1} of the green sub-pixel unit, and the second subpixel Sub_{B_2} of the blue sub-pixel unit are arranged sequentially and circularly.

(2) In a second row, the second subpixel Sub_{R_2} of the red sub-pixel unit, the first subpixel Sub_{G_1} of the green sub-pixel unit, the second subpixel Sub_{B_2} of the blue sub-pixel unit, the first subpixel Sub_{R_1} of the red sub-pixel unit, the second subpixel Sub_{G_2} of the green sub-pixel unit, and the first subpixel Sub_{B_1} of the blue sub-pixel unit are arranged sequentially and circularly.

[0068] Deduced from the above by analogy, the array of pixel units in a display region of the array substrate

according to the present embodiment is formed.

[0069] By adopting the arrangement of the subpixels according to the present embodiment, which is relatively complicated in arrangement rule, the manufacturing process and the signal control are relatively complicated accordingly, however, the situation where luminance in the whole line is either relatively high or relatively low, occurred in the display region, addressed in the first embodiment of the array substrate can be eliminated, thereby achieving a relatively better display effect.

[0070] On the basis of a pixel unit in which first subpixels and second subpixels of different sub-pixel units are arranged randomly, there is provided an array substrate according to yet another embodiment of the present invention. In the array substrate according to the present embodiment, for any one of the red subpixels, the green subpixels and the blue subpixels, the first subpixel and the second subpixel are arranged in the first direction; in the second direction, the first subpixels and the second subpixels of different sub-pixels are arranged randomly, that is, in the same row of the display region, the arrangement of the first subpixels and the second subpixels is random.

[0071] By adopting the arrangement of the subpixels according to the present embodiment, which is mostly complicated in arrangement rule, the manufacturing process and the signal control are mostly complicated accordingly, however, the situation where luminance in the whole line is either relatively high or relatively low, occurred in the display region, addressed in the first embodiment of the array substrate can be eliminated completely, thereby achieving a best display effect.

[0072] According to still another aspect of the present invention, there is further provided a display device. The display device comprises any one of the abovementioned array substrates.

[0073] Thus it can be seen from the above that, the sub-pixel unit and the method of controlling the same, the pixel unit, the array substrate, and the display device at least have one of the following advantages.

- (1) A novel structure of sub-pixel unit is provided.
- (2) The sub-pixel unit is designed to include two subpixels having different initial twist angles, and the two subpixels are respectively controlled to achieve management and control of multi-level, multi-luminance and different power consumption requirements, so that the liquid crystal display device has wider applicability and usable range.
- (3) In the same row of effective display region of the array substrate along the second direction, first (second) subpixels of different sub-pixels are arranged sequentially, in this case, arrangement rule is simple, the manufacturing process is simplified accordingly and the signal control is eased.
- (4) In the same row of effective display region of the array substrate along the second direction, first and second subpixels of different sub-pixels are ar-

ranged alternately, in this case, a situation where luminance in the whole line is either relatively high or relatively low, occurred in the display region once the voltage in some gate line is not stable, can be eliminated, thereby achieving a relatively better display effect.

(5) In the same row of effective display region of the array substrate along the second direction, first subpixels and second subpixels of different sub-pixels are arranged randomly, in this case, a situation where luminance in the whole line is either relatively high or relatively low, occurred in the display region once the voltage in some gate line is not stable, can be eliminated completely, thereby achieving the best display effect.

[0074] To this, several embodiments of the present invention have been described in detail in conjunction with the attached drawings. In accordance with the above description, those skilled in the art should have a clear understanding on the sub-pixel unit and the method of controlling the same, the pixel unit, the array substrate, and the display device according to the present invention.

[0075] It should be noted that, all the implementations not shown or described in the drawings or the description are those known by those skilled in the art and are not described in detail. In addition, abovementioned definitions of these elements and methods are not limited to these specific configurations, forms or manners mentioned in the embodiments, and can be altered or replaced easily by those skilled in the art. For example,

- (1) the number of subpixels in each sub-pixel unit may also be three, four or more;
- (2) for the initial twist angle, other suitable angles may also be selected, in addition to the three listed in this description;
- (3) for arrangement manner of the subpixels in the array substrate, those skilled in the art may envisage other arrangement manners based on the three listed in the embodiments, in addition to the three listed in the abovementioned embodiments.

[0076] Concerning the above, the present invention provides a pixel design and corresponding array substrate and display device, which are compatible with the display requirements of low luminance, medium luminance and high luminance, and a corresponding driving manner is adjusted accordingly, to meet power consumption requirement in different use environments. Accordingly, it can greatly improve applicability and usable range of the panel and enhance product competitiveness.

[0077] It should also be noted that, this description may provide examples of parameters that contain certain values, however, these parameters do not need to be exactly equal to corresponding values, but may be approximately the corresponding values within acceptable error

tolerances or design constraints. Directional terminologies mentioned in the embodiments, for example, "upper", "lower", "front", "rear", "left", "right" and the likes are those shown in the figures, and are not intended to limit the scope of the present invention. In addition, unless otherwise specifically described or necessarily to occur in sequence, the order of the above steps is not limited to those listed above and may be varied or rearranged in accordance with required design. Moreover, based on considerations on design and reliability, the above embodiments may be mixed with each other or with other embodiments, that is, technical features described in different embodiments may be combined freely to form more embodiments.

[0078] It should be noted that, in the above embodiments, the word "comprise" does not exclude element(s) or step(s) which is/are not listed in the description. Elements defined by words "a/an" or "one" do not exclude a plurality of identical elements. The present invention can be implemented by means of hardware including several different elements or by means of computer that is suitably programmed. In a unit where several devices are listed, some of these devices can be embodied specifically by same hardware. Words such as first, second, third and the like are explained as definitions, instead of expressing or implying that there is any sequence between them.

[0079] Objects, technical solutions and advantages of the present invention have been further illustrated in the above specific embodiments. It should be understood that the above description is merely used to illustrate specific embodiments of the present invention, but not to limit the present invention. All of changes, equivalent alternatives, improvements, made within principles and spirit of the present invention, should be included within the scope of the present invention.

Claims

1. A sub-pixel unit, comprising: at least two subpixels; wherein, each of the at least two subpixels comprises: a first electrode; a second electrode; and a liquid crystal layer controlled by a voltage between the first electrode and the second electrode; at least one of the first electrode and the second electrode is a slit electrode; and the at least two subpixels have different initial twist angles, and the initial twist angle is an included angle between a slit of the slit electrode and liquid crystal molecules oriented when the liquid crystal layer is in an initial unpowered state, in the respective subpixel.
2. The sub-pixel unit of claim 1, wherein, the at least two subpixels comprise: a first subpixel and a second subpixel; wherein, the first subpixel has an initial twist angle

- of θ_1 ; the second subpixel has an initial twist angle of θ_2 ; and, both the θ_1 and the θ_2 are less than 15° .
3. The sub-pixel unit of claim 2, wherein, the θ_1 and the θ_2 are two different ones selected from a group consisting of 5° , 7° , 11° .
 4. A pixel unit, comprising: several sub-pixel units, at least one of the several sub-pixel units being the sub-pixel unit of claim 1.
 5. The pixel unit of claim 4, wherein, the several sub-pixel units comprise: a red sub-pixel unit, a green sub-pixel unit and a blue sub-pixel unit; the red sub-pixel unit comprises: a first red subpixel and a second red subpixel having different initial twist angles; the green sub-pixel unit comprises: a first green sub-pixel and a second green subpixel having different initial twist angles; and the blue sub-pixel unit comprises: a first blue sub-pixel and a second blue subpixel having different initial twist angles.
 6. The pixel unit of claim 5, wherein, the first red subpixel, the first green subpixel and the first blue subpixel have the same initial twist angle of θ_1 ; and the second red subpixel, the second green subpixel and the second blue subpixel have the same initial twist angle of θ_2 .
 7. The pixel unit of claim 6, wherein, two subpixels of the same sub-pixel unit are arranged in a first direction; and the same type of subpixels of different sub-pixel units are arranged sequentially in a second direction that is neither coincident with nor parallel to the first direction.
 8. The pixel unit of claim 6, wherein, two subpixels of the same sub-pixel unit are arranged in a first direction; and the first subpixels and the second subpixels of different sub-pixel units are arranged alternately in a second direction that is neither coincident with nor parallel to the first direction.
 9. The pixel unit of claim 6, wherein, two subpixels of the same sub-pixel unit are arranged in a first direction; and the first subpixels and the second subpixels of different sub-pixel units are arranged randomly in a second direction that is neither coincident with nor parallel to the first direction.
 10. An array substrate, comprising:
 - a base substrate; and
 - an array of pixel units, disposed on the base substrate and comprising a plurality of pixel units arranged in array, at least one pixel unit of the plurality of pixel units being the pixel unit of any one of claims 4 to 9.
 11. The array substrate of claim 10, further comprising: gate lines and data lines formed on the base substrate; wherein, in the at least one pixel unit, two subpixels of the same sub-pixel unit share the same gate line and are controlled by different data lines.
 12. The array substrate of claim 10, wherein, at least one pixel unit of the plurality of pixel units in the array of pixel units is the pixel unit of any one of claims 7 to 9; the array substrate further comprises: gate lines and data lines formed on the base substrate; wherein, the first direction is along a direction of the data lines and the second direction is along a direction of the gate lines.
 13. The array substrate of claim 10, wherein, the array substrate is an array substrate with an IPS mode or an FFS mode; wherein the subpixel of the pixel unit comprises: a pixel electrode and a common electrode separated by an insulation layer; the first electrode is one of the pixel electrode and the common electrode, and the second electrode is the other of the pixel electrode and the common electrode.
 14. A display device, comprising: the array substrate of any one of claims 10 to 13.
 15. A method of controlling the sub-pixel unit of any one of claims 1 to 3, the method comprising:
 - a step A of, acquiring a sub-pixel unit required display luminance value; and
 - a step B of, selecting a corresponding working mode from a group of arrangements of the at least two subpixels, according to the sub-pixel unit required display luminance value.
 16. The method of claim 15, wherein, the at least two subpixels comprises: a first subpixel and a second subpixel, the first subpixel has an initial twist angle of θ_1 , the second subpixel has an initial twist angle of θ_2 , and, $\theta_1 > \theta_2$; the step B comprises:
 - a sub-step B1 of, judging, if $\Delta < \Delta_2$, that the sub-pixel unit requires to display in a low luminance, and controlling only the first subpixel of the sub-pixel unit to work;

a sub-step B2 of, judging, if $\Delta_2 \leq \Delta < \Delta_1$, that the sub-pixel unit requires to display in a medium luminance, and controlling only the second sub-pixel of the sub-pixel unit to work;

a sub-step B3 of, judging, if $\Delta \geq \Delta_1$, that the sub-pixel unit requires to display in a high luminance, and controlling the first subpixel and the second subpixel of the sub-pixel unit to work simultaneously;

in which, Δ is the sub-pixel unit required display luminance value, Δ_1 is a first luminance threshold, Δ_2 is a second luminance threshold, and $\Delta_1 > \Delta_2$.

15

20

25

30

35

40

45

50

55




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6






FIG. 8

INTERNATIONAL SEARCH REPORT

International application No.
PCT/CN2017/093658

A. CLASSIFICATION OF SUBJECT MATTER

G02F 1/1343 (2006.01) i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G02F 1/-

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI, EPODOC, CNPAT, CNKI: 子像素, 亚子像素, 狭缝电极, 初始, 扭转角度, 不同, 方向, 角度, 透过率, 亮度, sub, pixel, transmissivity, brightness, intensity, slit, electrode, differ+

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	CN 105759516 A (XIAMEN TIANMA MICROELECTRONICS CO. LTD. et al.), 13 July 2016 (13.07.2016), description, paragraphs [0034]-[0038] and [0059], and figures 3 and 7	1-4, 10-11, 13-14
A	CN 103529613 A (BOE TECHNOLOGY GROUP CO., LTD.), 22 January 2014 (22.01.2014), entire document	1-16
A	CN 205581478 U (XIAMEN TIANMA MICROELECTRONICS CO. LTD. et al.), 14 September 2016 (14.09.2016), entire document	1-16
A	CN 102629056 A (BOE TECHNOLOGY GROUP CO., LTD. et al.), 08 August 2012 (08.08.2012), entire document	1-16
A	US 2003117016 A1 (CANON K.K.), 26 June 2003 (26.06.2003), entire document	1-16
A	CN 202583658 U (BOE TECHNOLOGY GROUP CO., LTD.), 05 December 2012 (05.12.2012), entire document	1-16

☐ Further documents are listed in the continuation of Box C. ☒ See patent family annex.

* Special categories of cited documents:

“A” document defining the general state of the art which is not considered to be of particular relevance

“E” earlier application or patent but published on or after the international filing date

“L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

“O” document referring to an oral disclosure, use, exhibition or other means

“P” document published prior to the international filing date but later than the priority date claimed

“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

“X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

“Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

“&” document member of the same patent family

Date of the actual completion of the international search
27 September 2017

Date of mailing of the international search report
20 October 2017

Name and mailing address of the ISA
State Intellectual Property Office of the P. R. China
No. 6, Xitucheng Road, Jimenqiao
Haidian District, Beijing 100088, China
Facsimile No. (86-10) 62019451

Authorized officer

WANG, Xin

Telephone No. (86-10) 62413485

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/CN2017/093658

5	Patent Documents referred in the Report	Publication Date	Patent Family	Publication Date
	CN 105759516 A	13 July 2016	None	
10	CN 103529613 A	22 January 2014	None	
	CN 205581478 U	14 September 2016	None	
	CN 102629056 A	08 August 2012	WO 2013071840 A1	23 May 2013
			US 2013120680 A1	16 May 2013
15	US 2003117016 A1	26 June 2003	JP 2003186065 A	03 July 2003
			US 6873451 B2	29 March 2005
	CN 202583658 U	05 December 2012	None	
20				
25				
30				
35				
40				
45				
50				
55				

Form PCT/ISA/210 (patent family annex) (July 2009)

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- CN 201710017676 [0001]

专利名称(译)	亚像素单元及其控制方法，像素单元，矩阵基板和显示装置		
公开(公告)号	EP3537209A4	公开(公告)日	2020-05-20
申请号	EP2017842410	申请日	2017-07-20
[标]申请(专利权)人(译)	京东方科技集团股份有限公司 合肥鑫晟光电科技有限公司		
申请(专利权)人(译)	京东方科技集团股份有限公司. 合肥新盛光电科技有限公司		
当前申请(专利权)人(译)	京东方科技集团股份有限公司. 合肥新盛光电科技有限公司		
[标]发明人	JIANG LIANGLIANG GAN QUAN		
发明人	JIANG, LIANGLIANG GAN, QUAN		
IPC分类号	G02F1/1343		
CPC分类号	G02F1/133707 G02F1/133753 G02F1/134363 G02F1/13624 G02F2001/134345 G02F2001/134372 G09G3/3637 G09G2300/0443 G09G2300/0452 G09G2320/0626 G09G2330/021 G09G3/3607 G09G3/3655		
优先权	PCT/CN2017/001767 2017-01-10 WO		
其他公开文献	EP3537209A1		
外部链接	Espacenet		

摘要(译)

本发明提供了一种子像素单元及其控制方法，像素单元，阵列基板和显示装置。在一个实施例中，子像素单元包括：至少两个子像素。至少两个子像素中的每个包括：第一电极；以及第二电极。第二电极；液晶层，由第一电极和第二电极之间的电压控制。第一电极和第二电极中的至少一个是缝隙电极。两个子像素具有不同的初始扭曲角，并且初始扭曲角是在各个子像素中狭缝电极的缝隙与当液晶层处于初始未通电状态时取向的液晶分子之间的夹角。