



(51) International Patent Classification:
G02F 1/1362 (2006.01)

(21) International Application Number:
PCT/US2011/038945

(22) International Filing Date:
2 June 2011 (02.06.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
12/813,458 10 June 2010 (10.06.2010) US

(71) Applicant (for all designated States except US): **APPLE, INC.** [US/US]; 1 Infinite Loop, M/S 36-2 Pat, Cupertino, CA 95014 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **GE, Zhibing** [CN/US]; 1 Infinite Loop, Ms 83-D, Cupertino, CA 95014 (US). **CULBERT, Diane, L.** [US/US]; 1 Infinite Loop, M/s 83-D, Cupertino, CA 95014 (US). **DOYLE, David, A.** [US/US]; 1 Infinite Loop, M/s 83-D, Cupertino, CA 95014 (US). **QI, Jun** [CN/US]; 1 Infinite Loop, M/s 83-D, Cupertino, CA 95014 (US). **CHEN, Cheng** [CN/US]; 1 Infinite Loop, Ms 83-D, Cupertino, CA

95014 (US). **GETTEMY, Shawn, R.** [US/US]; 1 Infinite Loop, Ms 83-D, Cupertino, CA 95014 (US).

(74) Agent: **TREYZ, G., Victor**; Treyz Law Group, 870 Market Street, Suite 984, San Francisco, CA 94102 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: DISPLAYS WITH MINIMIZED CURTAIN MURA




FIG. 1

(57) Abstract: Displays such as liquid crystal displays may be provided with structures that minimize curtain mura. A display may have upper and lower polarizers. A color filter layer and a thin film transistor layer may be located between the upper and lower polarizers. A liquid crystal layer may be interposed between the color filter layer and the thin film transistor layer. A first optical film layer that includes a birefringent compensating layer may be located between the upper polarizer and the color filter layer. A second optical film layer that is devoid of birefringent compensating layers may be located between the thin film transistor layer and the lower polarizer. A grid of metal signal lines may be used to distribute signals to thin film transistors on the thin film transistor layer. A black mask may be interposed between the grid of signal lines and the thin film transistor layer.



Published:

- *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*

DISPLAYS WITH MINIMIZED CURTAIN MURA

This application claims priority to United States patent application No. 12/813,458, filed June 10, 2010, which is hereby incorporated by reference herein in its entirety.

5

Background

This relates generally to displays, and, more particularly, to displays such as liquid crystal displays.

10

Displays are widely used in electronic devices to display images. Displays such as liquid crystal displays display images by controlling liquid crystal material associated with an array of image pixels. A typical liquid crystal display has a color filter layer

and a thin film transistor layer formed between polarizer layers. The color filter layer has an array of pixels each of which includes color filter subpixels of different colors. The thin film transistor layer contains an array
5 of thin film transistor circuits. The thin film transistor circuits can be adjusted individually for each subpixel to control the amount of light that is produced by that subpixel. A light source such as a backlight may be used to produce light that travels through each of the
10 layers of the display.

A layer of liquid crystal material is interposed between the color filter layer and the thin film transistor layer. During operation, the circuitry of the thin film transistor layer applies signals to an array of
15 electrodes in the thin film transistor layer. These signals produce electric fields in the liquid crystal layer. The electric fields control the orientation of liquid crystal material in the liquid crystal layer and change how the liquid crystal material affects polarized
20 light.

An upper polarizer is formed on top of the display and a lower polarizer is formed on the bottom of the display. As light travels through the display, the adjustments that are made to the electric fields in the
25 liquid crystal layer are used to control the image that is displayed on the display.

The liquid crystal layer in liquid crystal displays exhibits a natural birefringence. In a birefringent layer, the index of refraction of the layer
30 varies as a function of the polarization of incoming light. If left uncompensated, the birefringence of the liquid crystal layer in a display can adversely affect off-axis image quality and can therefore limit viewing angle.

Off-axis display performance can be improved by including a birefringent compensating layer in a liquid crystal display. The compensating layer, which is typically located between the lower polarizer and the thin film transistor layer, has birefringent properties that counteract the effects of the liquid crystal layer. Birefringent compensating layers are often formed from polymerized liquid crystals and may exhibit indices of refraction of about 1.5 to 1.8.

10 Signals may be applied to the electrodes in the thin-film-transistor layer using a grid of signal lines. The signal lines may include orthogonal sets of gate lines and data lines. The gate lines may be connected to the gates of thin film transistors that drive signals onto the electrodes. The data lines may distribute power supply voltages.

 The electrodes in the thin film transistor layer are generally formed from a transparent conductive material such as indium tin oxide. The electrodes are 20 conductive, so that they can be used to apply an electric field to an associated image pixel region of the liquid crystal layer. The electrodes are transparent so that light that passes through the image pixel regions will not be blocked by the presence of the electrodes.

25 To ensure that the signal lines in the thin film transistor layer are sufficiently conductive to effectively distribute signals to the thin film transistors and their associated electrodes, the signal lines are generally formed from metal. Metals have a 30 significantly higher conductivity than transparent conductive materials such as indium tin oxide and are satisfactory when used to distribute control signals to the thin film transistors and electrodes on the thin film transistor layer.

However, the use of metal in forming the grid of signal lines in a liquid crystal display can lead to unsightly visible artifacts due to optical interference. These artifacts, which are sometimes referred to as curtain mura, result from the Moiré effect. Due to the presence of high index materials beneath the grid lines such as birefringent compensating films, there is an index of refraction discontinuity beneath the grid lines. This discontinuity forms a reflective interface that can reflect and image of the underside of the grid lines towards a viewer. The grid lines and the pattern of the reflected image of the underside of the grid lines can optically interfere with each other, leading to an undesirable Moiré pattern that is visible to a user of the display. Even though the pitch of the grid lines may be small (e.g., tens of microns), the bands of dark and light lines in the Moiré pattern can be one or more centimeters in width and can therefore interfere significantly with a user's ability to discern images on the display.

It would therefore be desirable to be able to provide improved displays such as displays that exhibit minimized curtain mura.

Summary

Displays such as liquid crystal displays may have upper and lower polarizers. A display may have a color filter layer and a thin film transistor layer. The color filter layer and the thin film transistor layer may be located between upper and lower polarizers.

A liquid crystal layer may be interposed between the color filter layer and the thin film transistor layer. Thin film transistors on the thin film transistor layer and transparent electrodes may be used in applying patterns of electric fields to the liquid crystal layer.

A grid of signal lines may be used to distribute signals to the thin film transistors. The grid of signal lines may be formed from a shiny material such as metal. To minimize reflections from the underside of the signal
5 lines, a patterned black mask may be interposed between the grid of signal lines and the thin film transistor layer. Reducing signal line reflections in this way may help to minimize curtain mura.

Curtain mura may also be minimized by ensuring
10 that there are no large index of refraction discontinuities in the films below the thin film transistor layer. A display may have a first optical film layer that is located between the upper polarizer and the color filter layer and a second optical film layer that is
15 located between the thin film transistor layer and the lower polarizer. Reflection-inducing interfaces in the region below the thin film transistor layer may be avoided by ensuring that high-index layers such as birefringent compensating layers are located above the color filter in
20 the first optical film layer rather than below the thin film transistor layer in the second optical film layer.

Further features of the invention, its nature and various advantages will be more apparent from the accompanying drawings and the following detailed
25 description of the preferred embodiments.

Brief Description of the Drawings

FIG. 1 is a cross-sectional side view of an illustrative display such as a liquid crystal display of
30 the type that may be provided with structures to reduce curtain mura in accordance with an embodiment of the present invention.

FIG. 2 is a top view of a display showing how a grid of signal lines may be used in distributing signals

to image pixels in accordance with an embodiment of the present invention.

FIG. 3 is a partially schematic top view of an image pixel showing how a grid of signal lines such as data lines and gate lines may be used in controlling thin film transistor and electrode structures in a display such as a liquid crystal display in accordance with an embodiment of the present invention.

FIG. 4 is a cross-sectional side view of a portion of a conventional display showing how curtain mura may result from optical interference between a pattern of signal lines and a reflected image of the pattern of signal lines.

FIG. 5 is a cross-sectional view of a display such as a liquid crystal display showing structures and layer configurations that may be used in minimizing curtain mura in the display in accordance with an embodiment of the present invention.

Detailed Description

Displays are widely used in electronic devices. For example, displays may be used in computer monitors, laptop computers, media players, cellular telephones, televisions, and other equipment. Displays may be based on plasma technology, organic-light-emitting-diode technology, liquid crystal structures, etc.

Liquid crystal displays are popular because they can exhibit low power consumption and good image quality. Liquid crystal display structures are sometimes described herein as an example.

A cross-sectional side view of an illustrative liquid crystal display is shown in FIG. 1. As shown in FIG. 1, display 10 may include color filter (CF) layer 12 and thin-film-transistor (TFT) layer 14. Color filter

layer 12 may include an array of colored filter elements. In a typical arrangement, the pixels of layer 12 each include three colored pixels (e.g., red, green, and blue subpixels). Liquid crystal (LC) layer 16 includes liquid
5 crystal material and is interposed between color filter layer 12 and thin-film-transistor layer 14. Thin-film-transistor layer 14 may include electrical components such as thin film transistors, capacitors, and electrodes for controlling the electric fields that are applied to liquid
10 crystal layer 16. Optical film layers 18 and 20 may be formed above and below color filter layer 12, liquid crystal layer 16, and thin-film-transistor layer 14. Optical films 18 and 20 may include structures such as quarter-wave plates, half-wave plates, diffusing films,
15 optical adhesives, and birefringent compensating layers.

Display 10 may have upper and lower polarizer layers 22 and 24. Backlight 26 may provide backside illumination for display 10. Backlight 26 may include a light source such as a strip of light-emitting diodes.
20 Backlight 26 may also include a light-guide plate and a back reflector. The back reflector may be located on the lower surface of the light-guide panel to prevent light leakage. Light from the light source may be injected into an edge of the light-guide panel and may scatter upwards
25 in direction 28 through display 10.

Touch sensor structures may be incorporated into the layers of display 10. In a typical touch sensor configuration, an array of capacitive touch sensor electrodes is implemented using pads of a transparent
30 conductive material such as indium tin oxide. Other touch technologies may be used if desired (e.g., resistive touch, acoustic touch, optical touch, etc.).

In black and white displays, color filter layer 12 can be omitted. In color displays, color filter layer

12 can be used to impart colors to an array of image pixels. Each image pixel may, for example, have three corresponding liquid crystal diode subpixels. Each subpixel may be associated with a separate color filter element in the color filter array. The color filter elements may, for example, include red (R) color filter elements, blue (B) color filter elements, and green (G) color filter elements. By controlling the amount of light transmission through each subpixel, a desired colored image can be displayed.

The amount of light transmitted through each subpixel can be controlled using control circuitry and electrodes. Each subpixel may, for example, be provided with a transparent indium tin oxide electrode. The signal on the electrode, which controls the electric field through an associated portion of the liquid crystal layer and thereby controls the light transmission for the subpixel, may be applied using a thin film transistor. The circuitry for the array of subpixels in a display may be controlled using a grid of signal lines. As shown in FIG. 2, an array of colored subpixels R, G, and B may be controlled using a grid of signal lines made up of orthogonal sets of lines 30 and 32.

Lines 30 are sometimes referred to as data lines and may be used to distributing a power supply voltage to the pixel array. Lines 32 are sometimes referred to as gate lines and may be used to distribute gate control signals to an array of thin film transistors. There may be, for example, a respective thin film transistor for controlling the electric field that is produced by each electrode in the display. Each electrode may be associated with a red subpixel R, a green subpixel G, or a blue subpixel B (or other suitable color filter elements). As shown in FIG. 2, the width of each color filter element

and associated cell of liquid crystal material may be L1 and the height of each color filter element and associated cell of liquid crystal material may be about 3L1 (as an example).

5 FIG. 3 is a diagram of an illustrative image pixel (subpixel) in display 10. As shown in FIG. 3, pixel 34 may have a capacitor 36, pixel electrode 38, and thin film transistor 40. Transistor 40 may have a gate that is controlled by gate line 32 and terminals coupled to data
10 line 30, capacitor 36, and electrode 38. Other pixel circuits may be used if desired. The arrangement of FIG. 3 is merely illustrative.

 Signal lines 30 and 32 may be formed from highly conductive materials such as metal (e.g., copper). The
15 use of highly conductive materials such as metal in forming signal lines 30 and 32 ensures that lines 30 and 32 can effectively distribute signals to thin film transistors 40 and electrodes 38.

 However, metals tend to be reflective (shiny),
20 which raises a risk of producing unsightly visible artifacts in display 10 due to optical interference. If care is not taken, these artifacts, which are sometimes referred to as curtain mura, can interfere with the images on display 10.

25 Curtain mura is a result of the Moiré effect. Data lines 30 run parallel to each other and are spaced at regular intervals (e.g., 10-100 microns). Similarly, gate lines 32 are spaced apart at regular intervals (e.g., 30-300 microns). The grid of signal lines (lines 30 and 32)
30 and reflections of the grid of signal lines may potentially interfere with each other to produce unsightly Moiré patterns (curtain mura).

 A cross-sectional diagram of a conventional display showing how curtain mura may arise is shown in

FIG. 4. As shown in FIG. 4, display 40 may have upper optical layers 44 and lower optical layers 46. Upper optical layer 44 may include an upper polarizer formed on top of optical films and a color filter layer. Lower optical layer 46 may include a thin film transistor layer formed on top of optical films and a lower polarizer layer. Liquid crystal layer 60 may be interposed between optical layers 44 and 46.

Signal lines 48 (e.g., data lines or gate lines) may be spaced apart by a distance $L1$. Reflective interface 50 may lie at a depth of $d1/2$ below lines 48. Interface 50 may represent the upper surface of a birefringent compensating film. Compensating films may have maximum indices of refraction of about 1.8 to 2.0.

Adjacent layers such as the glass substrates commonly used in thin film transistor layers typically have refractive index values that differ from this maximum amount by more than 0.2. For example, the index of refraction for a typical glass substrate for a thin film transistor layer might be about 1.45 to 1.55.

The large index different (>0.2) between the thin film transistor layer and the compensating layer gives rise to reflective interface 50. Reflective interface 50, in turn, can produce a reflected image of lines 48 (i.e., reflection 52 in FIG. 4). If the depth of interface 50 is $d1/2$, reflected image 52 of lines 48 will be located at a depth of $d1$, as shown in FIG. 4.

An observer OBS viewing display 40 in direction 42 will view two patterns of lines. The first pattern of lines corresponds to directly observed lines 48 and is conveyed by light rays such as light ray 56 that do not reflect from interface 50. The second pattern of lines corresponds to the reflected image of the undersides of lines 48 (i.e., image pattern 52). The origin of the

second pattern of lines is illustrated by reflected ray 58. The effective spacing of image lines 52 is smaller than L1 due to the larger distance between lines 52 and the observer than between lines 48 and the observer.

5 From the perspective of the observer, both patterns of lines are present. Due to the Moiré effect, a Moiré interference pattern may therefore be observed. This interference pattern is undesirable and detracts from the quality of the image presented by display 40.

10 If a scenario in which the depth d1/2 of interface 50 is 0.4 mm, L1 is 30 microns, the average index of refraction of the layers in display 40 is 1.48, and the distance between the surface of display 40 and the observer OBS is 100 mm, the interference pattern will have
15 a periodicity L given by equation 1 (i.e., about 10 mm in this example).

$$L = 1.48 * (100 \text{ mm}) * (30 \text{ microns}) / (0.4 \text{ mm}) \quad (1)$$

20 Conventional displays include a black mask pattern (grid-shaped black mask 54 of FIG. 4) that covers signal lines 48 and reduces their visibility in direction 42. Conventional displays also sometimes include a diffusing layer such as a layer of hazy glue to smear out the lines
25 in an attempt to reduce curtain mura. However, conventional black masks are generally unable to prevent curtain mura and diffusing layers tend to reduce contrast and make the display subject to washout effects in direct sunlight.

30 These shortcomings of conventional displays can be addressed using a display of the type shown in FIG. 5. As shown in FIG. 5, display 10 may have a liquid crystal layer such as layer 16 located between color filter layer 12 and thin film transistor layer 14. Layer 16 may have a

thickness Z of about 4 microns (as an example). Signal lines 66 may be formed on thin film transistor layer 14. Signal lines 66 may include lines such as data lines 30 and gate lines 32 (FIG. 2) arranged in a grid pattern.

5 Signal lines 66 may be formed from metal or other conductive materials. Signals on signal lines 66 may be used to control a pattern of electric fields imposed on image pixel cells in liquid crystal layer 16 using circuitry of the type shown in FIG. 3, thereby creating a
10 desired image on display 10. Patterned black mask layer 64 may be used to cover signal lines 66 and thereby block the upper surfaces of signal lines 66 from view through the front of display 10.

Backlight for display 10 may be provided by
15 backlight 26. Display 10 may include an upper polarizer such as upper polarizer 22 and a lower polarizer such as lower polarizer 24. Optical films 18 may be located between upper polarizer 22 and color filter layer 12. Optical films 20 may be located between thin film
20 transistor layer 14 and lower polarizer 24. Polarizers 22 and 24 may be formed from layers of polyvinyl alcohol (as an example). A typical index of refraction for polarizer layers 22 and 24 is about 1.5. Color filter layer 12 and thin film transistor layer 14 may be formed using glass
25 substrates (as an example) and may each have an index of refraction of about 1.45 to 1.55.

To ensure that display 10 exhibits a satisfactory viewing angle, display 10 may be provided with a birefringent compensating film such as a
30 polymerized liquid crystal film. The compensating film may exhibit an ordinary index of refraction of about 1.5 and an extraordinary index of refraction of 1.8 (as an example). Because an index of refraction value of 1.8 (the maximum index of refraction of the compensating film

layer) is significantly different than the index of refraction for layer 14 (which is about 1.5), there is a potential for creating a reflective interface such as interface 50 of FIG. 4 if the compensating film is placed
5 below layer 14. To avoid creating a significant reflective interface such as interface 50 in display 10, the compensating film is preferably located above thin film transistor layer 14. As shown in FIG. 5, for example, a birefringent compensating layer may be
10 incorporated into optical layers 18 as layer 62. Compensating layer 62 may be implemented as one or more individual films and may use any suitable material (e.g., polymerized liquid crystals, other birefringent materials, etc.).

15 By placing the compensating layer in layers 18, the amount of reflection that is produced from below thin film transistor layer 14 is reduced or eliminated. Because the strength of the reflected image of signal lines 66 (shown as reflection 52 in the conventional
20 display of FIG. 4) is reduced, curtain mura is minimized.

When the birefringent compensating layer is located where indicated by layer 62 of FIG. 5, there may be no remaining high-index materials below layer 14 (i.e., optical films 20 may contain no birefringent films or may
25 contain only weakly birefringent films and may contain no films having an index of refraction of more than about 1.75 or 1.8). As shown in FIG. 5, in this configuration, films 20 represent non-birefringent or weakly birefringent optical films having an index of refraction different Δn
30 with respect to the index of layer 14 that is no more than 0.15 (or no more than 0.2 or other suitable threshold value). This type of arrangement, in which optical film layer 20 is devoid of any isotropic or birefringent compensating film, ensures that the reflectivity of any

buried reflective interface in layers 20 (i.e., any interface of the type described in connection with reflective interface 50 in conventional display 40 of FIG. 4) will have a reflectivity of less than 0.2%.

5 Curtain mura effects can also be minimized by blocking the lower surface of signal lines 66 from view. Signal lines 66 may be formed from a shiny material such as metal. If care is not taken, the shiny underside of lines 66 will be visible in the form of a reflection from
10 within layers 20, as described in connection with reflection 52 of FIG. 4. The shiny underside of lines 66 can be at least partly blocked from view by including less visible structures beneath signal lines 66. As shown in FIG. 5, for example, light-blocking structures 68 may be
15 formed under lines 66. Light-blocking structures 68 may be formed from oxidized metal (e.g., chromium oxide, which appears black), black ink, other black masks, etc. To prevent structures 68 from being visible themselves, structures 68 may be formed from a non-shiny (matte)
20 substance and are therefore sometimes referred to herein as black mask structures or a black mask.

Thin film transistor layer 14 may have a transparent substrate such as a glass substrate. The lower surface of the glass substrate may be aligned with
25 the upper surface of films 20. The upper surface of the glass substrate, which is illustrated by dashed line 70 of FIG. 5, may be used to support image pixel structures of the type shown in FIG. 3 (e.g., signal lines, etc.)

Black mask structures 68 may be formed between
30 signal lines 66 and surface 70 of the transparent glass thin film transistor substrate in layer 14 or at any other suitable location within display 10 that blocks the shiny underside of lines 66 and prevents the underside of lines 66 from being visible in the form of a reflection from a

reflective interface below thin film transistor layer 20. With one suitable configuration, black mask 68 may be formed on the glass substrate of layer 14 and lines 66 may be deposited and patterned on top of black mask 68 using
5 photolithographic techniques. Lines 66 typically include data lines 30 and gate lines 32 arranged in a grid and black mask 68 preferably has a matching grid shape.

If desired, black mask structures 68 may be used in displays that include a birefringent compensating layer
10 within layer 20. In this type of configuration, a reflective interface such as interface 50 of FIG. 4 may be present but, due to the presence of black mask 68, the lower surfaces of signal lines 66 will be hidden from view and will not be reflected back towards the user through
15 the surface of display 10.

In configurations such as the illustrative configuration of FIG. 5 in which compensating layer 62 is located above color filter layer 12 to ensure that layer 20 has an index difference of less than 0.15 relative to
20 layer 14 and in which black mask 68 is present, the suppression of curtain mura will generally be maximized.

In accordance with an embodiment, a display is provided that includes a thin film transistor layer having a transparent thin film transistor substrate, a grid of
25 signal lines on the thin film transistor substrate, and a patterned black mask between the grid of signal lines and the thin film transistor substrate.

In accordance with another embodiment, a display is provided that also includes a color filter layer, and a
30 liquid crystal layer interposed between the color filter layer and the grid of signal lines.

In accordance with another embodiment, a display is provided that also includes an additional black mask located between the liquid crystal layer and the color

filter layer.

In accordance with another embodiment, a display is provided that also includes a first polarizer, a second polarizer, a first optical film layer located between the
5 first polarizer and the color filter layer, and a second optical film layer located between the second polarizer and the thin film transistor layer.

In accordance with another embodiment, a display is provided wherein the first optical film layer includes
10 a birefringent compensating layer.

In accordance with another embodiment, a display is provided wherein the first optical film layer includes a birefringent compensating layer and wherein the second optical film layer is devoid of any birefringent
15 compensating layers.

In accordance with another embodiment, a display is provided wherein the first optical film layer includes a birefringent compensating layer, wherein the second layer of optical films is characterized by a maximum index
20 of refraction, wherein there are no films between the second polarizer and the thin film transistor layer having an index of refraction greater than the maximum index of refraction, wherein the thin film transistor substrate layer is characterized by an index of refraction, and
25 wherein the maximum index of refraction of the layer of second optical films minus the index of refraction of the thin film transistor substrate layer has a magnitude less than 0.15.

In accordance with another embodiment, a display
30 is provided that also includes a lower polarizer, and a layer of optical films interposed between the lower polarizer and the thin film transistor substrate, wherein the layer of optical films is characterized by a maximum index of refraction, wherein the thin film transistor

substrate is characterized by an index of refraction, and wherein the maximum index of refraction of the layer of optical films minus the index of refraction of the thin film transistor substrate has a magnitude less than 0.15.

5 In accordance with another embodiment, a display is provided that also includes a backlight adjacent to the lower polarizer.

 In accordance with another embodiment, a display is provided that also includes a color filter layer, and a
10 liquid crystal layer interposed between the color filter layer and the grid of signal lines.

 In accordance with another embodiment, a display is provided that also includes a lower polarizer, and a layer of optical films between the thin film transistor
15 layer and the lower polarizer, wherein the layer of optical films exhibits a reflectivity of less than 0.2% for light passing from the thin film transistor layer towards the lower polarizer.

 In accordance with another embodiment, a display
20 is provided that also includes a color filter layer, and a liquid crystal layer interposed between the color filter layer and the grid of signal lines.

 In accordance with another embodiment, a display is provided that also includes a backlight adjacent to the
25 lower polarizer, and an upper polarizer, wherein the color filter layer is interposed between the upper polarizer and the liquid crystal layer.

 In accordance with another embodiment, a display is provided that also includes a birefringent compensating
30 layer between the upper polarizer and the color filter layer.

 In accordance with an embodiment, a display is provided that includes an upper polarizer, a color filter layer, a thin film transistor layer, a layer of liquid

crystal material interposed between the color filter layer and the thin film transistor layer, a lower polarizer, a first layer of optical films that is interposed between the upper polarizer and the color filter layer and that
5 includes a birefringent compensating layer, and a second layer of optical films that is interposed between the lower polarizer and the thin film transistor layer, wherein the second layer of optical films is characterized by a maximum index of refraction, wherein there are no
10 films between the lower polarizer and the thin film transistor layer having an index of refraction greater than the maximum index of refraction, wherein the thin film transistor substrate layer is characterized by an index of refraction, and wherein the maximum index of
15 refraction of the layer of second optical films minus the index of refraction of the thin film transistor substrate layer has a magnitude less than 0.15.

In accordance with another embodiment, a display is provided wherein the display is devoid of birefringent
20 films between the lower polarizer and the thin film transistor layer, the display also including a backlight adjacent to the lower polarizer.

In accordance with another embodiment, a display is provided wherein the thin film transistor layer
25 includes a glass substrate, the display also including a grid of signal lines include data lines and gate lines, and a patterned black mask between the grid of signal lines signal lines and the glass substrate, wherein the patterned black mask is aligned with the grid of signal
30 lines.

In accordance with an embodiment, a display is provided that includes a thin film transistor layer that includes an array of thin film transistors, a color filter layer, and a liquid crystal layer interposed between the

color filter layer and the thin film transistor layer, a grid of signal lines, wherein the signal lines distribute signals to the thin film transistors, and a black mask interposed between the grid of signal lines and the thin film transistor layer.

In accordance with another embodiment, a display is provided that also includes an upper polarizer, and a first layer of optical films that is interposed between the upper polarizer and the color filter layer and that includes a birefringent compensating layer.

In accordance with another embodiment, a display is provided that also includes a lower polarizer, and a second layer of optical films that is interposed between the lower polarizer and the thin film transistor layer, wherein the second layer of optical films is characterized by a maximum index of refraction, wherein there are no films between the lower polarizer and the thin film transistors layer having an index of refraction greater than the maximum index of refraction, wherein the thin film transistor layer is characterized by an index of refraction, and wherein the maximum index of refraction of the layer of second optical films minus the index of refraction of the thin film transistor layer has a magnitude less than 0.15.

In accordance with another embodiment, a display is provided wherein the grid of signal lines includes gate lines, wherein the thin film transistors have gates, wherein the gate lines are connected to the gates, wherein the signal lines includes metal, and wherein the black mask includes a metal oxide.

The foregoing is merely illustrative of the principles of this invention and various modifications can be made by those skilled in the art without departing from the scope and spirit of the invention. The foregoing

embodiments may be implemented individually or in any combination.

What is Claimed is:

1. A display, comprising:
 - a thin film transistor layer having a transparent thin film transistor substrate;
 - a grid of signal lines on the thin film transistor substrate; and
 - a patterned black mask between the grid of signal lines and the thin film transistor substrate.
2. The display defined in claim 1 further comprising:
 - a color filter layer; and
 - a liquid crystal layer interposed between the color filter layer and the grid of signal lines.
3. The display defined in claim 2 further comprising an additional black mask located between the liquid crystal layer and the color filter layer.
4. The display defined in claim 2 further comprising:
 - a first polarizer;
 - a second polarizer;
 - a first optical film layer located between the first polarizer and the color filter layer; and
 - a second optical film layer located between the second polarizer and the thin film transistor layer.
5. The display defined in claim 4 wherein the first optical film layer comprises a birefringent compensating layer.
6. The display defined in claim 4 wherein the first optical film layer comprises a birefringent

compensating layer and wherein the second optical film layer is devoid of any birefringent compensating layers.

7. The display defined in claim 4 wherein the first optical film layer comprises a birefringent compensating layer, wherein the second layer of optical films is characterized by a maximum index of refraction, wherein there are no films between the second polarizer and the thin film transistor layer having an index of refraction greater than the maximum index of refraction, wherein the thin film transistor substrate layer is characterized by an index of refraction, and wherein the maximum index of refraction of the layer of second optical films minus the index of refraction of the thin film transistor substrate layer has a magnitude less than 0.15.

8. The display defined in claim 1 further comprising:

a lower polarizer; and

a layer of optical films interposed between the lower polarizer and the thin film transistor substrate, wherein the layer of optical films is characterized by a maximum index of refraction, wherein the thin film transistor substrate is characterized by an index of refraction, and wherein the maximum index of refraction of the layer of optical films minus the index of refraction of the thin film transistor substrate has a magnitude less than 0.15.

9. The display defined in claim 8 further comprising a backlight adjacent to the lower polarizer.

10. The display defined in claim 9 further

comprising:

a color filter layer; and
a liquid crystal layer interposed between
the color filter layer and the grid of signal lines.

11. The display defined in claim 1 further
comprising:

a lower polarizer; and
a layer of optical films between the thin
film transistor layer and the lower polarizer, wherein the
layer of optical films exhibits a reflectivity of less
than 0.2% for light passing from the thin film transistor
layer towards the lower polarizer.

12. The display defined in claim 11 further
comprising:

a color filter layer; and
a liquid crystal layer interposed between
the color filter layer and the grid of signal lines.

13. The display defined in claim 12 further
comprising:

a backlight adjacent to the lower
polarizer; and
an upper polarizer, wherein the color
filter layer is interposed between the upper polarizer and
the liquid crystal layer.

14. The display defined in claim 13 further
comprising a birefringent compensating layer between the
upper polarizer and the color filter layer.

15. A display, comprising:
an upper polarizer;

a color filter layer;
a thin film transistor layer;
a layer of liquid crystal material
interposed between the color filter layer and the thin
film transistor layer;
a lower polarizer;
a first layer of optical films that is
interposed between the upper polarizer and the color
filter layer and that includes a birefringent compensating
layer; and
a second layer of optical films that is
interposed between the lower polarizer and the thin film
transistor layer, wherein the second layer of optical
films is characterized by a maximum index of refraction,
wherein there are no films between the lower polarizer and
the thin film transistor layer having an index of
refraction greater than the maximum index of refraction,
wherein the thin film transistor substrate layer is
characterized by an index of refraction, and wherein the
maximum index of refraction of the layer of second optical
films minus the index of refraction of the thin film
transistor substrate layer has a magnitude less than 0.15.

16. The display defined in claim 15 wherein the
display is devoid of birefringent films between the lower
polarizer and the thin film transistor layer, the display
further comprising:

a backlight adjacent to the lower
polarizer.

17. The display defined in claim 16 wherein the
thin film transistor layer comprises a glass substrate,
the display further comprising:

a grid of signal lines include data lines

and gate lines; and

a patterned black mask between the grid of signal lines and the glass substrate, wherein the patterned black mask is aligned with the grid of signal lines.

18. A display, comprising:

a thin film transistor layer that includes an array of thin film transistors;

a color filter layer; and

a liquid crystal layer interposed between the color filter layer and the thin film transistor layer;

a grid of signal lines, wherein the signal lines distribute signals to the thin film transistors; and

a black mask interposed between the grid of signal lines and the thin film transistor layer.

19. The display defined in claim 18 further comprising:

an upper polarizer; and

a first layer of optical films that is interposed between the upper polarizer and the color filter layer and that includes a birefringent compensating layer.

20. The display defined in claim 19 further comprising:

a lower polarizer; and

a second layer of optical films that is interposed between the lower polarizer and the thin film transistor layer, wherein the second layer of optical films is characterized by a maximum index of refraction, wherein there are no films between the lower polarizer and the thin film transistors layer having an index of

refraction greater than the maximum index of refraction, wherein the thin film transistor layer is characterized by an index of refraction, and wherein the maximum index of refraction of the layer of second optical films minus the index of refraction of the thin film transistor layer has a magnitude less than 0.15.

21. The display defined in claim 18 wherein the grid of signal lines includes gate lines, wherein the thin film transistors have gates, wherein the gate lines are connected to the gates, wherein the signal lines comprises metal, and wherein the black mask comprises a metal oxide.




FIG. 1

2 / 5




FIG. 2





FIG. 3

4 / 5



(PRIOR ART)
FIG. 4

5 / 5




FIG. 5

专利名称(译)	液晶显示器具有减少的莫尔效应		
公开(公告)号	EP2580620A2	公开(公告)日	2013-04-17
申请号	EP2011724920	申请日	2011-06-02
[标]申请(专利权)人(译)	苹果公司		
申请(专利权)人(译)	苹果公司.		
当前申请(专利权)人(译)	苹果公司.		
[标]发明人	GE ZHIBING CULBERT DIANE L DOYLE DAVID A QI JUN CHEN CHENG GETTEMY SHAWN R		
发明人	GE, ZHIBING CULBERT, DIANE, L. DOYLE, DAVID, A. QI, JUN CHEN, CHENG GETTEMY, SHAWN, R.		
IPC分类号	G02F1/1362		
CPC分类号	G02F1/133502 G02F1/13363 G02F1/136209 G02F1/136286 G02F2001/133562 G02F2001/133567 G02F2413/07		
优先权	12/813458 2010-06-10 US		
外部链接	Espacenet		

摘要(译)

诸如液晶显示器的显示器可以设置有使窗帘mura最小化的结构。显示器可以具有上偏振器和下偏振器。滤色器层和薄膜晶体管层可以位于上偏振器和下偏振器之间。可以在滤色器层和薄膜晶体管层之间插入液晶层。包括双折射补偿层的第一光学膜层可以位于上偏振器和滤色器层之间。没有双折射补偿层的第二光学膜层可以位于薄膜晶体管层和下偏振器之间。金属信号线栅格可用于将信号分配到薄膜晶体管层上的薄膜晶体管。可以在信号线的栅格和薄膜晶体管层之间插入黑色掩模。