


(19)



(11)

EP 2 337 015 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
11.11.2015 Bulletin 2015/46

(51) Int Cl.:
G09G 3/36 ^(2006.01) **G02F 1/133** ^(2006.01)
G09G 3/20 ^(2006.01)

(21) Application number: **09817572.2**

(86) International application number:
PCT/JP2009/063277

(22) Date of filing: **24.07.2009**

(87) International publication number:
WO 2010/038535 (08.04.2010 Gazette 2010/14)

(54) **LIQUID CRYSTAL DISPLAY DEVICE, METHOD FOR DRIVING THE LIQUID CRYSTAL DISPLAY DEVICE, AND TV RECEIVER**

FLÜSSIGKRISTALLANZEIGEVORRICHTUNG, VERFAHREN ZUR ANSTEUERUNG DER
FLÜSSIGKRISTALLANZEIGEVORRICHTUNG UND FERNSEHEMPFÄNGER

DISPOSITIF D'AFFICHAGE À CRISTAUX LIQUIDES, PROCÉDÉ DE COMMANDE DU DISPOSITIF
D'AFFICHAGE À CRISTAUX LIQUIDES ET RÉCEPTEUR DE TÉLÉVISION

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL
PT RO SE SI SK SM TR**

- **SHIMOSHIKIRYOH, Fumikazu**
Osaka 545-8522 (JP)
- **KAWABATA, Masae**
Osaka 545-8522 (JP)

(30) Priority: **03.10.2008 JP 2008258724**

(43) Date of publication of application:
22.06.2011 Bulletin 2011/25

(73) Proprietor: **Sharp Kabushiki Kaisha**
Osaka-shi, Osaka 545-8522 (JP)

(72) Inventors:

- **IRIE, Kentaroh**
Osaka 545-8522 (JP)

(74) Representative: **Goddard, Heinz J. et al**
Boehmert & Boehmert
Anwaltpartnerschaft mbB
Patentanwälte Rechtsanwälte
Pettenkoferstrasse 20-22
80336 München (DE)

(56) References cited:
JP-A- 8 087 000 JP-A- 2006 053 428
JP-A- 2006 284 823 US-A1- 2006 041 805

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 2 337 015 B1

Description

Technical Field

[0001] The present invention relates to a driving (block-reversal driving) in which polarities of signal electric potentials supplied to a data signal line are reversed for every plurality of horizontal scan periods.

Background Art

[0002] A liquid crystal display device has excellent properties such as high-definition, a thin shape, lightweight, and low power consumption. Owing to the properties, a market scale of the liquid crystal display device has been rapidly expanded in these years. According to the liquid crystal display device, a dot-reversal driving has been widely employed in which polarities of signal electric potentials supplied to a data signal line are reversed for each horizontal scan period. However, according to the dot-reversal driving, a polarity-reversal frequency of a data signal line becomes high and thereby (i) a pixel charging rate is decreased and (ii) power consumption is increased. In view of this, a block-reversal driving has been proposed in which polarities of signal electric potentials to be supplied to a data signal line are reversed for every plural horizontal scan periods (for example, see Patent Literature 1). According to the block-reversal driving, it is possible to (i) improve a pixel charging rate and (ii) suppress power consumption and a heating value.

[0003] JP 2001-51252 (published February 23, 2001) discloses a technique regarding a block-reversal driving in which a dummy scan period is added right after a polarity reversal (see Fig. 18). According to the configuration, a piece of data (n+2) which is the one right after a polarity reversal corresponds to a dummy scan period (third horizontal scan period in Fig. 18) for pre-charge and a horizontal scan period (fourth horizontal scan period in Fig. 18) for actual charge (writing). Accordingly, a charging ratio of a pixel corresponding to the piece of data (n+2) can be enhanced.

[0004] Another example of a method for line-reversal driving in which a dummy scan period is inserted after polarity inversion is known from US 2006/0041805 A1. This document relates to an array substrate for an LCD of an N-line inversion type includes m data lines extending in a first direction, n scan lines extending in second direction that is substantially perpendicular to the first direction, and pixels. Each of the scan lines has a contact terminal that makes contact with corresponding ones of output terminals of a scan driving part that generates scan signals. A K(N+1)-th output terminal is disconnected from the scan lines. The mxn pixels are formed in regions defined by the data and scan lines, so that no potential is applied to the scan lines.

Summary of Invention

Technical Problem

[0005] However, the inventors of the present invention found that the technique shown in Fig. 18 has problems as shown in Figs. 19 and 20. Specifically, a rectangular gate pulse GP(n+1) for carrying out a horizontal scan is supplied to a scanning signal line G(n+1), while a potential waveform GV(n+1) of the scanning signal line G(n+1) does not become rectangle due to parasitic resistor and parasitic capacitor but has a dull section (shaded part in Fig. 19). Accordingly, a TFT of a pixel P(n+1) corresponding to the scanning signal line G(n+1) keeps turning on for a while (during a dull period) after the gate pulse GP(n+1) becomes nonactive.

[0006] The dummy scan period is started (a signal electric potential corresponding to the piece of data (n+2) is supplied to the data signal line) in sync with the gate pulse GP(n+1) becoming nonactive. Accordingly, the signal electric potential corresponding to the piece of data (n+2) is written into the pixel P(n+1) in the dull period. Moreover, the signal electric potential corresponding to the piece of data (n+1) has a positive polarity, whereas the signal electric potential corresponding to the piece of data (n+2) has a negative polarity. Accordingly, electricity is discharged from the pixel P(n+1) during the dull period, and thereby the pixel P(n+1) becomes dark in the normally black liquid crystal display device (see Fig. 20). According to the technique shown in Fig. 18, blackish lateral stripes could be seen in the conventional display as shown in Fig. 20.

[0007] The present invention is accomplished in view of the problem, and its object is to improve display quality of a liquid crystal display device in which a block-reversal driving is carried out.

Solution to Problem

[0008] The object is solved by the subject matter of the independent claims. Advantageous embodiments are subject to the dependent claims.

[0009] According to a liquid crystal display device of the present invention, a plurality of groups each of which includes a plurality of scanning signal lines are sequentially selected; data signal electric potentials having identical polarities are sequentially supplied to a data signal line for each horizontal scan period, in response to a plurality of scanning signal lines, which belong to a selected one of the plurality of groups, being sequentially subjected to horizontal scans; a scanning pulse for each of the horizontal scans is supplied to each of the plurality of scanning signal lines; a polarity of the data signal electric potentials for a first group is different from that of a second group, the first and second groups being sequentially selected, the second group being selected after the first group is selected; n-piece (n is an integer of 1 or more) of dummy scan period(s) is(are) put between (i) a hori-

zontal scan period corresponding to a last horizontal scan in the first group and (ii) a horizontal scan period corresponding to a first horizontal scan in the second group; a dummy signal electric potential is supplied to the data signal line in a dummy scan period included in the n-piece of dummy scan period(s); and a time period from a time point when a scanning pulse which corresponds to the last horizontal scan in the first group becomes nonactive to a time point when the dummy scan period is started is set to be longer than a time period from a time point when a scanning pulse corresponding to one of consecutive two horizontal scans becomes nonactive in the first group to a time point when a horizontal scan period corresponding to the other of the consecutive two horizontal scans is started.

[0010] According to the configuration, the horizontal scan period corresponding to the last horizontal scan in the first group is set to be longer than the other horizontal scan period. This makes it possible to prevent a phenomenon in which electric charge written into a pixel during the last horizontal scan period is discharged when the dummy scan period following the last horizontal scan period is started. Accordingly, it is possible to reduce the blackish lateral stripes (see Fig. 20) which are the problem seen in the conventional technique.

[0011] According to the liquid crystal display device of the present invention, it is possible that the dummy signal electric potential has a polarity which is identical to a polarity of the data signal electric potentials in the second group.

[0012] According to the liquid crystal display device of the present invention, it is possible that the scanning pulse corresponding to the other of the consecutive two horizontal scans becomes active in sync with the scanning pulse corresponding to the one of the consecutive two horizontal scans becoming nonactive.

[0013] According to the liquid crystal display device of the present invention, it is possible that a horizontal scan period corresponding to an arbitrary horizontal scan is started after a scanning pulse corresponding to the arbitrary horizontal scan becomes active.

[0014] According to the liquid crystal display device of the present invention, it is possible that the horizontal scan period corresponding to the last horizontal scan in the first group is longer than a previous horizontal scan period which comes before the horizontal scan period corresponding to the last horizontal scan in the first group.

[0015] According to the liquid crystal display device of the present invention, it is possible that a scanning pulse corresponding to the first horizontal scan in the second group becomes active before the dummy scan period is started.

[0016] According to the liquid crystal display device of the present invention, it is possible that a scanning pulse corresponding to the first horizontal scan in the second group becomes active after the dummy scan period is started.

[0017] According to the liquid crystal display device of

the present invention, it is possible that the horizontal scan period corresponding to the other of the consecutive two horizontal scans is started in sync with the scanning pulse corresponding to the one of the consecutive two horizontal scans becoming nonactive.

[0018] According to the liquid crystal display device of the present invention, it is possible that plural pieces of video data which correspond to respective horizontal scans on the plurality of scanning signal lines are arranged in an order corresponding to the horizontal scans; n-piece of dummy data is(are) put between (i) a piece of video data corresponding to the last horizontal scan in the first group and (ii) a piece of video data corresponding to the first horizontal scan in the second group; the data signal electric potentials correspond to the respective plural pieces of video data; and the dummy signal electric potential corresponds to a piece of dummy data included in the n-piece of dummy data.

[0019] According to the liquid crystal display device of the present invention, it is possible that the plural pieces of video data and the piece of dummy data are latched in sync with latch pulses; an interval, between (i) a latch pulse, in sync with which the piece of video data corresponding to the last horizontal scan in the first group is latched and (ii) a latch pulse, in sync with which the piece of dummy data is latched, is wider than an interval between (i) a latch pulse, in sync with which a piece of video data corresponding to a second last horizontal scan in the first group is latched and (ii) the latch pulse, in sync with the piece of video data corresponding to the last horizontal scan in the first group is latched.

[0020] According to the liquid crystal display device of the present invention, a plurality of groups each of which includes a plurality of scanning signal lines are sequentially selected; data signal electric potentials which have identical polarities and correspond to respective plural pieces of video data are sequentially supplied to a data signal line, in response to a plurality of scanning signal lines, which belong to a selected one of the plurality of groups, being sequentially subjected to horizontal scans; a scanning pulse for each of the horizontal scans is supplied to each of the plurality of scanning signal lines; a polarity of the data signal electric potentials for a first group is different from that of a second group, the first and second groups being sequentially selected, the second group being selected after the first group is selected; n-piece (n is an integer of 1 or more) of dummy data is(are) put between (i) a piece of video data corresponding to a last horizontal scan in the first group and (ii) a piece of video data corresponding to a first horizontal scan in the second group; a dummy signal electric potential which corresponds to a piece of dummy data included in the n-piece of dummy data is supplied to the data signal line; and a time period from outputting of a piece of video data corresponding to the last horizontal scan in the first group, after a scanning pulse which corresponds to the last horizontal scan becomes nonactive, to switching to outputting of the piece of dummy data is

set to be longer than a time period from outputting of a piece of video data corresponding to one of consecutive two horizontal scans in the first group, after a scanning pulse which corresponds to the one of consecutive two horizontal scans becomes nonactive, to switching to outputting of a piece of video data corresponding to the other of the consecutive two horizontal scans.

[0021] According to the liquid crystal display device of the present invention, it is possible that the dummy signal electric potential has a polarity which is identical to a polarity of the data signal electric potentials in the second group.

[0022] According to the liquid crystal display device of the present invention, it is possible that the scanning pulse corresponding to the other of the consecutive two horizontal scans becomes active in sync with the scanning pulse corresponding to the one of the consecutive two horizontal scans becoming nonactive.

[0023] According to the liquid crystal display device of the present invention, it is possible that outputting of a piece of video data corresponding to an arbitrary horizontal scan is started after a scanning pulse corresponding to the arbitrary horizontal scan becomes active.

[0024] According to the liquid crystal display device of the present invention, it is possible that a scanning pulse corresponding to the first horizontal scan in the second group becomes active before outputting of the dummy signal electric potential is started.

[0025] According to the liquid crystal display device of the present invention, it is possible that a scanning pulse corresponding to the first horizontal scan in the second group becomes active after outputting of the dummy signal electric potential is started.

[0026] According to the liquid crystal display device of the present invention, it is possible that the plural pieces of video data and the piece of dummy data are outputted in sync with latch pulses, in sync with which the plural pieces of video data and the piece of dummy data are latched; an interval, between (i) a latch pulse, in sync with which the piece of video data corresponding to the last horizontal scan in the first group is latched and (ii) a latch pulse, in sync with which the piece of dummy data is latched is wider than an interval between (i) a latch pulse, in sync with which a piece of video data corresponding to a second last horizontal scan in the first group is latched and (ii) the latch pulse, in sync with the piece of video data corresponding to the last horizontal scan in the first group is latched.

[0027] According to the liquid crystal display device of the present invention, it is possible that, in a case where a certain scanning signal line is defined as a first scanning signal line in numerical order, one of the first and second groups includes only odd-numbered scanning signal lines, and the other of the first and second groups includes only even-numbered scanning signal lines.

[0028] According to the liquid crystal display device of the present invention, it is possible that, in a case where (i) a certain scanning line and its subsequent scanning

signal lines are divided into a plurality of blocks and (ii) a block to which the certain scanning line belongs and which is one end block of the plurality of blocks is referred to as a most upstream block and a block which is the other end block is referred to as a most downstream block, scanning signal lines which belong to each of the plurality of blocks are divided into groups, and the plurality of blocks are sequentially selected from groups of the most upstream block to groups of the most downstream block.

[0029] According to the liquid crystal display device of the present invention, it is possible that each of a plurality of pixels is made up of a plurality of subpixels. In this case, it is possible that the plurality of subpixels include respective pixel electrodes; retention capacitor lines are provided for the respective pixel electrodes; and a luminance of each of the plurality of subpixels is controlled in response to a retention capacitor line signal supplied to a corresponding one of the retention capacitor lines.

[0030] According to the liquid crystal display device of the present invention, at least one dummy scan period is inserted every consecutive horizontal scan periods; a polarity of signal electric potentials supplied to a data signal line is reversed in the at least one dummy scan period following a horizontal scan period; and a previous horizontal scan period of the at least one dummy scan period is set to be longer than a horizontal scan period which is not the previous horizontal scan period.

[0031] According to the liquid crystal display device of the present invention, it is possible that a scanning pulse is outputted in each of the horizontal scan periods; and a scanning pulse corresponding to the previous horizontal scan period has a width which is identical to that of a scanning pulse corresponding to the horizontal scan period which is not the previous horizontal scan period.

[0032] According to the liquid crystal display device of the present invention, it is possible that the at least one dummy scan period immediately after a horizontal scan period is set to be shorter than the horizontal scan period which is not the previous horizontal scan period. A method of the present invention for driving a liquid crystal display device, in which device a plurality of groups each of which includes a plurality of scanning signal lines are sequentially selected, data signal electric potentials having identical polarities are sequentially supplied to a data signal line for each horizontal scan period, in response to a plurality of scanning signal lines, which belong to a selected one of the plurality of groups, being sequentially subjected to horizontal scans, the method includes the steps of: supplying a scanning pulse for each of the horizontal scans to each of the plurality of scanning signal lines; causing a polarity of the data signal electric potentials for a first group to be different from that of a second group, the first and second groups being sequentially selected, the second group being selected after the first group is selected; putting n-piece (n is an integer of 1 or more) of dummy scan period(s) between (i) a horizontal scan period corresponding to a last horizontal scan in

the first group and (ii) a horizontal scan period corresponding to a first horizontal scan in the second group; supplying a dummy signal electric potential to the data signal line in a dummy scan period included in the n-piece of dummy scan period(s); and causing a time period from a time point when a scanning pulse which corresponds to the last horizontal scan in the first group becomes non-active to a time point when the dummy scan period is started to be set to be longer than a time period from a time point when a scanning pulse corresponding to one of consecutive two horizontal scans becomes nonactive in the first group to a time point when a horizontal scan period corresponding to the other of the consecutive two horizontal scans is started.

[0033] A television receiver of the present invention includes: the above described liquid crystal display device; and a tuner section which receives television broadcasting.

Advantageous Effects of Invention

[0034] According to the liquid crystal display device of the present invention, the horizontal scan period corresponding to the last horizontal scan in the first group is set to be longer than the other horizontal scan period. This makes it possible to prevent a phenomenon in which electric charge written into a pixel during the last horizontal scan period is discharged when the dummy scan period following the last horizontal scan period is started. Accordingly, it is possible to reduce the blackish lateral stripes which are the problem seen in the conventional technique.

Brief Description of Drawings

[0035]

Fig. 1

Fig. 1 is a timing chart illustrating a driving example of a liquid crystal display device of Embodiment 1.

Fig. 2

Fig. 2 is a schematic view illustrating a configuration of the liquid crystal display device of Embodiment 1.

Fig. 3

Fig. 3 is a timing chart for describing the driving example shown in Fig. 1.

Fig. 4

Fig. 4 is a schematic view illustrating a polarity distribution of electric potentials written into pixels in a case where the driving example shown in Fig. 3 is used.

Fig. 5

Fig. 5 is a timing chart illustrating more details of the driving example shown in Fig. 1.

Fig. 6

Fig. 6 is a timing chart illustrating a modification of the driving example shown in Fig. 1.

Fig. 7

Fig. 7 is a timing chart illustrating a modification of the driving example shown in Fig. 1.

Fig. 8

Fig. 8 is a timing chart illustrating another driving example of the liquid crystal display device of Embodiment 1.

Fig. 9

Fig. 9 is a timing chart for describing the driving example shown in Fig. 8.

Fig. 10

Fig. 10 is a schematic view illustrating a polarity distribution of electric potentials written into pixels in a case where the driving example shown in Fig. 8 is used.

Fig. 11

Fig. 11 is a schematic view illustrating a configuration of the liquid crystal display device of Embodiment 2.

Fig. 12

Fig. 12 is a timing chart illustrating a driving example of the liquid crystal display device of Embodiment 2.

Fig. 13

Fig. 13 is a timing chart for describing the driving example shown in Fig. 12.

Fig. 14

Fig. 14 is a schematic view illustrating a connection relation between retention capacitor lines and retention capacitor trunk lines.

Fig. 15

Fig. 15 is a schematic view illustrating a polarity distribution and bright and dark states of electric potentials written into pixels in a case where the driving example shown in Fig. 12 is used.

Fig. 16

Fig. 16 is a block diagram illustrating an entire configuration of the liquid crystal display device of the present invention.

Fig. 17

Fig. 17 is a block diagram illustrating a function of a television receiver of the present invention.

Fig. 18

Fig. 18 is a timing chart illustrating a driving example of a conventional liquid crystal display device.

Fig. 19

Fig. 19 is a timing chart for describing a problem of the conventional liquid crystal display device.

Fig. 20

Fig. 20 is a schematic view illustrating a display state of the conventional liquid crystal display device.

Description of Embodiments

[0036] The following describes embodiments of the present invention with reference to Figs. 1 through 17.

[Embodiment 1]

[0037] A liquid crystal display device of Embodiment 1 has a display section (e.g., of a normally black mode) in

which (i) pixels are provided in a matrix manner and (ii) scanning signal lines G1 through G1080 are provided (see Fig. 2). For example, a pixel column is made up of pixels P1 through P1080, and a pixel electrode included in a pixel P_i (i is an integer of 1 to 1080) is connected with a scanning signal line G_i and a data signal line S, via a transistor.

[0038] According to Embodiment 1, the scanning signal lines are sequentially scanned while the data signal line is being subjected to the block-reversal driving (see Fig. 3). First, the scanning signal line G1 and its subsequent scanning signal lines G2 through G1080 are divided into 90 blocks (i.e., blocks B1 through B90) which are demarcated by 89 boundaries extending in parallel with the scanning signal lines G1 through G1080. Each of the blocks B1 through B90 includes 12 scanning signal lines which have respective consecutive numbers. For example, the block B1 which is a most upstream block includes scanning signal lines G1 through G12, the block B2 includes scanning signal lines G13 through G24, the block B3 includes scanning signal lines G25 through G36, and the block B90 which is a most downstream block includes scanning signal lines G1069 through G1080.

[0039] The 12 scanning signal lines (G1, G2, ..., G12) included in the block B1 which is the most upstream block belong to a first group Gr1, and the 12 scanning signal lines (G13, G14, ..., G24) included in the block B2 which follows the block B1 belong to a group Gr2. Subsequently, 12 scanning signal lines included in the blocks belong to respective groups Gr3 through Gr90. The groups Gr1 through Gr90 are sequentially selected from the group Gr1 to the group Gr90. During the sequential selection, data signal electric potentials having identical polarities are sequentially supplied to a data signal line for each horizontal scan period, in response to 12 scanning signal lines, which belong to a selected one of the groups Gr1 through Gr90, being sequentially subjected to horizontal scans (gate pulses being sequentially supplied to the respective 12 scanning signal lines). Note that a polarity (positive or negative) of data signal electric potentials for a first group is different from that of a second group, the first and second groups being sequentially selected, the second group being selected after the first group is selected. Note that pieces of data D1, D2, D3, ... are pieces of video data (digital data) which respectively correspond to the pixel P1 connected to the scanning signal line G1, the pixel P2 connected to the scanning signal line G2, ... (see Fig. 2). A polarity-reversal signal POL is a signal which controls a polarity of a signal electric potential supplied to the data signal line S.

[0040] Specifically, while the group Gr1 is being selected, the scanning signal lines G1 through G12, which belong to the selected group Gr1, are sequentially subjected to horizontal scans (i.e., gate pulses GP1 through GP12 are sequentially supplied to the scanning signal lines G1 through G12, respectively). During the horizontal scans, data signal electric potentials, which have a positive polarity and correspond to respective pieces of

video data D1 through D12, are supplied to the data signal line S during respective horizontal scan periods H1 through H12. Subsequently, while the group Gr2 is being selected, the scanning signal lines G13 through G24, which belong to the selected group Gr2, are sequentially subjected to horizontal scans (i.e., gate pulses GP13 through GP24 are sequentially supplied to the scanning signal lines G13 through G24, respectively). During the horizontal scans, data signal electric potentials, which have a negative polarity and correspond to respective pieces of video data D13 through D24, are supplied to the data signal line S during respective horizontal scan periods H13 through H24. Then, while the group Gr3 is being selected, the scanning signal lines G25 through G36, which belong to the selected group Gr3, are sequentially subjected to horizontal scans. During the horizontal scans, data signal electric potentials, which have a positive polarity and correspond to respective pieces of video data D25 through D36, are supplied to the data signal line S during respective horizontal scan periods H25 through H36. Consequently, a polarity distribution of electric potentials of respective pixels in the display section becomes as shown in Fig. 4.

[0041] Moreover, first and second dummy scan periods are put between (i) a horizontal scan period corresponding to a last horizontal scan in the first group and (ii) a horizontal scan period corresponding to a first horizontal scan in the second group, the second group being selected after the first group is selected. In each of the dummy scan periods, a dummy signal electric potential is supplied to a data signal line.

[0042] For example, a first dummy scan period HX and a second dummy scan period HY are put between the horizontal scan period H12 and the horizontal scan period H13. The horizontal scan period H12 corresponds to the last horizontal scan in the group Gr1, and the horizontal scan period H13 corresponds to the first horizontal scan in the group Gr2. The first and second groups are consecutively selected in this order. Moreover, pieces of dummy data DA and DB are put between pieces of video data D12 and D13. In the first dummy scan period HX, a dummy signal electric potential corresponding to the dummy data DA (e.g., data identical to the video data D13) is supplied to the data signal line S. In the second dummy scan period HY, a dummy signal electric potential corresponding to the dummy data DB (e.g., data identical to the video data D13) is supplied to the data signal line S. Similarly, a first dummy scan period Hx and a second dummy scan period Hy are put between a horizontal scan period H24 and a horizontal scan period H25. Moreover, pieces of dummy data Da and Db are put between the pieces of video data D24 and D25. In the first dummy scan period Hx, a dummy signal electric potential corresponding to the dummy data Da (e.g., data identical to the video data D25) is supplied to the data signal line S. In the second dummy scan period Hy, a dummy signal electric potential corresponding to the dummy data Db (e.g., data identical to the video data D13) is supplied to

the data signal line S.

[0043] Note here that, in a case where consecutive first and second horizontal scans are carried out in this order in each of the groups, a gate pulse corresponding to the second horizontal scan becomes active in sync with a gate pulse, which corresponds to the first horizontal scan, becoming nonactive. Note also that a horizontal scan period corresponding to an arbitrary horizontal scan is started after a gate pulse, which corresponds to the arbitrary horizontal scan, becomes active, and the horizontal scan period corresponding to the arbitrary horizontal scan is ended after the gate pulse becomes nonactive.

[0044] For example, the gate pulse GP2 becomes active (rises) in sync with the gate pulse GP1 becoming nonactive (falls), and the gate pulse GP3 becomes active in sync with the gate pulse GP2 becoming nonactive. Moreover, the horizontal scan period H1 is started after the gate pulse GP1 becomes active, and the horizontal scan period H1 is ended after the gate pulse GP1 becomes nonactive. Moreover, the horizontal scan period H2 is started after the gate pulse GP2 becomes active, and the horizontal scan period H2 is ended after the gate pulse GP2 becomes nonactive. Note that the gate pulse GP13 becomes active in sync with the gate pulse GP12 becoming nonactive, and after the first and second dummy scan periods HX and HY, the gate pulse GP13 becomes nonactive in sync with the gate pulse GP14 becoming active.

[0045] It should be noted here that, in a case where first and second groups are consecutively selected in this order, a time period from a time point when a gate pulse which corresponds to the last horizontal scan in the first group becomes nonactive to a time point when a dummy scan period is started is set to be longer than a time period from a time point when a gate pulse corresponding to one of consecutive two horizontal scans becomes nonactive in the first group to a time point when a horizontal scan period corresponding to the other of the consecutive two horizontal scans is started. In other words, a time period from a time point when a scanning pulse which corresponds to the last horizontal scan in the first group becomes nonactive to a time point when outputting of image data corresponding to the last horizontal scan is switched to outputting of dummy data is set to be longer than a time period from a time point when a scanning pulse corresponding to one of consecutive two horizontal scans becomes nonactive in the first group to a time point when outputting of image data corresponding to the one of the consecutive two horizontal scans is switched to outputting of image data corresponding to the other of the consecutive two horizontal scans.

[0046] Specifically, a time period from a time point when the gate pulse GP12 corresponding to the last horizontal scan in the group Gr1 becomes nonactive (falls) to a time point when the first dummy scan period HX is started (i.e., outputting of D12 is switched to outputting of DA) is set to be longer than a time period from a time point when the gate pulse GP1 becomes nonactive (falls)

to a time point when the horizontal scan period H2 is started (i.e., outputting of D1 is switched to outputting of D2); and a time period from a time point when the gate pulse GP24 corresponding to the last horizontal scan in the group Gr2 becomes nonactive (falls) to a time point when the first dummy scan period Hx is started (i.e., outputting of D24 is switched to outputting of Da) is set to be longer than a time period from a time point when a gate pulse GP11 becomes nonactive (falls) to a time point when the horizontal scan period H12 is started (i.e., outputting of D11 is switched to outputting of D12). The following describes this effect with reference to Fig. 1.

[0047] As shown in Fig. 1, the horizontal scan period H11 (a time period during which a data signal electric potential which has a positive polarity and corresponds to the video data D11 is being supplied to the data signal line S) is started after the gate pulse GP11 becomes active, and then the horizontal scan period H11 is ended after a time period t is elapsed since the gate pulse GP11 becomes nonactive. The horizontal scan period H12 (a time period during which a data signal electric potential which has a positive polarity and corresponds to the video data D12 is being supplied to the data signal line S) is started concurrently with the horizontal scan period H11 being ended. Note that a TFT of a pixel P12 connected to the scanning signal line G12 is turning on during at least part of the time period t. This is because the gate pulse GP12 becomes active in sync with the gate pulse GP11 becoming nonactive. Therefore, in a case where the time period t is too long, an image to be displayed on the pixel 11 is temporarily displayed on the pixel P12, which is visually recognized as a phenomenon called ghost.

[0048] As described above, the gate pulse GP 12 becomes active in sync with the gate pulse GP11 becoming nonactive. Then, the horizontal scan period H12 (a time period during which a data signal electric potential which has a positive polarity and corresponds to the video data D12 is being supplied to the data signal line S) is started. The horizontal scan period H12 is ended after a time period T (>t) is elapsed since the gate pulse GP12 becomes nonactive. The dummy scan period HX is started concurrently with the horizontal scan period H12 being ended.

[0049] Note here that, even though the gate pulse GP12 becomes nonactive, an electric potential GV12 of the scanning signal line G12 does not fall precipitously but falls while becoming dull due to parasitic resistor and parasitic capacitor. That is, the TFT of the pixel P12 connected to the scanning signal line G12 is turning on for a while (during a dull period) after the gate pulse GP12 becomes nonactive.

[0050] In view of the circumstances, the time period T from a time point when the gate pulse GP12 becomes nonactive to a time point when the dummy scan period HX (a time period during which a dummy signal electric potential which has a negative polarity and corresponds to the dummy data DA is being supplied to the data signal

line S) is started is set to be longer than the time period t (i.e., the horizontal scan period H12 is extended). This allows the horizontal scan period H12 to contain the dull period (most part of the dull period) of the electric potential GV12 of the scanning signal line G12. Accordingly, it is possible to prevent a phenomenon in which positive electric charge written into the pixel P12 during the horizontal scan period H12 is discharged by the dummy scan period HX being started. This makes it possible to reduce blackish lateral stripes (see Fig. 20) which have been the problem of a conventional display.

[0051] Note that the time periods t and T are set based on, for example, a degree of dullness of the electric potential GV12 which is applied to the scanning signal line (a time constant of the scanning signal line), a degree of dullness of a data signal electric potential SV (a time constant of the data signal line), and a characteristic of a source driver. For example, $t = 2 [\mu s]$, and $T = 5 [\mu s]$. Note that it is preferable to set $(T - t)$ (extended time period of the horizontal scan period H12 with respect to the other horizontal scan period) to be, for example, a time period from a time point when the gate pulse GP12 supplied to the scanning signal line G12 becomes non-active to a time point when the electric potential GV12 of the scanning signal line G12 falls to a nonactive (low) electric potential.

[0052] Fig. 5 is a timing chart illustrating a case where a gate pulse is generated based on a gate clock GCK, and a horizontal scan period is defined by a latch stroke (latch pulse) signal LS. In this case, a rising edge of one of adjacent two gate clocks is in sync with a rising edge (activation) of a certain gate pulse, and a rising edge of the other of the adjacent two gate clocks is in sync with a falling edge (nonactivation) of the certain gate pulse. Moreover, the video data and the dummy data are latched in sync with rising edges of respective latch pulses, and signal electric potentials (data signal electric potentials and dummy signal electric potentials) are supplied to the data signal line S in sync with falling edges of the respective latch pulses. For example, the outputting of a data signal electric potential (horizontal scan period H11) corresponding to the video data D11 is started in sync with the falling edge of a latch pulse LS11. In sync with the falling edge of a latch pulse LS12, (i) the outputting of a data signal electric potential (horizontal scan period H12) corresponding to the video data D12 is started and (ii) the outputting of the data signal electric potential (horizontal scan period H11) corresponding to the video data D11 is ended. In sync with the falling edge of a latch pulse LSX, (i) the outputting of a dummy signal electric potential (dummy scan period HX) corresponding to the dummy data DA is started and (ii) the outputting of the data signal electric potential (horizontal scan period H12) corresponding to the video data D12 is ended. It is therefore possible to satisfy $T > t$ (T : the time period from a time point when the gate pulse G12 becomes nonactive to a time period when the dummy scan period HX is started, t : time period from a time point when a gate pulse corre-

sponding to one of consecutive two horizontal scans becomes nonactive to a time point when a horizontal scan period corresponding to the other of the consecutive two horizontal scans is started), by setting an interval between the latch pulse LS12 and the latch pulse LSX to be wider than an interval between the latch pulse LS11 and the latch pulse LS12.

[0053] In this case, it is preferable to reduce, by a time period corresponding to the extension of the horizontal scan period H12, the dummy scan period HX (i.e., $HX < HY$) which follows the horizontal scan period H12. For example, a sum of the horizontal scan period H12 and the dummy scan period HX is set to be, for example, twice as long as the horizontal scan period H11 (= HY). This makes it possible to extend the horizontal scan period H12 only by changing the setting of the latch stroke signal LS (changing the position of the latch pulse LSX), instead of changing input intervals of the video data and the dummy data.

[0054] According to Fig. 1, the time period t (time period from a time point when a gate pulse corresponding to one of consecutive two horizontal scans becomes non-active to a time point when a horizontal scan period corresponding to the other of the consecutive two horizontal scans is started) is set to be a predetermined time period (e.g., $2 \mu s$). However, the present embodiment is not limited to this. For example, it is possible to set the time period $t \approx 0$ (see Fig. 6).

[0055] According to Fig. 1, a gate pulse corresponding to a first horizontal scan of a group becomes active before a dummy scan period is started (i.e., the gate pulse GP13 becomes active in sync with the gate pulse GP12 becoming nonactive, and after the first and second dummy scan periods HX and HY, the gate pulse GP13 becomes nonactive in sync with the gate pulse GP14 becoming active). However, the present embodiment is not limited to this. The gate pulse corresponding to the first horizontal scan of the group can become active after the dummy scan period is started. For example, the gate pulse GP13 does not become active in sync with the gate pulse GP12 becoming nonactive but becomes active immediately before the second dummy scan period HY is ended (horizontal scan period H13 is started) (see Fig. 7).

[0056] In a case where a scanning signal line (e.g., G13 or G25) which is firstly subjected to a horizontal scan in a group is insufficiently charged, it is preferable that a gate pulse (e.g., GP13) corresponding to the first horizontal scan of the group becomes active before the dummy scan period is started (see Fig. 1). In a case where a scanning signal line (e.g., G13 or G25) which is firstly subjected to a horizontal scan in a group is excessively charged, it is preferable that a gate pulse corresponding to the first horizontal scan of the group becomes active after the dummy scan period is started (see Fig. 7).

[0057] According to the present embodiment, it is possible to carry out interlaced scanning with respect to the scanning signal lines while carrying out the block-reversal driving with respect to the data signal line (see Fig. 8).

In this case, it is assumed that the scanning signal line G1 and the following scanning signal lines in the display section are divided into 45 blocks (B1 through B45) demarcated by 44 boundaries extending in parallel with the scanning signal lines. Each of the 45 blocks B1 through B45 includes 24 scanning signal lines which have respective consecutive numbers. For example, the block B1 which is a most upstream block includes scanning signal lines G1 through G24, the block B2 includes scanning signal lines G25 through G48, the block B3 includes scanning signal lines G49 through G72, and the block B45 which is a most downstream block includes scanning signal lines G1057 through G1080.

[0058] Moreover, odd-numbered 12 scanning signal lines (G1, G3, ..., G23) included in the block B1 which is the most upstream block belong to a first group Gr1, and even-numbered 24 scanning signal lines (G2, G4, ..., G48) included in the block B1 and the block B2 which follows the block B1 belong to a group Gr2. Odd-numbered 24 scanning signal lines (G25, G27, ..., G71) included in the second block B2 and the block B3 which follows the block B2 belong to a group Gr3. Subsequently, groups Gr4 through Gr45 are prepared by (i) grouping even-numbered 24 scanning signal lines included in a block Bj (j is an odd number between 3 through 43) and a following block B(j+1) and (ii) grouping odd-numbered 24 scanning signal lines included in the block B(j+1) and a following block B(j+2), in turn. A last group Gr46 includes even-numbered 12 scanning signal lines (G1058, G1060, ..., G1080) included in the block B45 which is the most downstream block. The groups Gr1 through Gr46 are sequentially selected from the group Gr1 to the group Gr46. During the sequential selection, data signal electric potentials having identical polarities are sequentially supplied to a data signal line for each horizontal scan period, in response to the scanning signal lines, which belong to a selected one of the groups Gr1 through Gr46, being sequentially subjected to horizontal scans (gate pulses being sequentially supplied to the respective scanning signal lines). Note that a polarity (positive or negative) of data signal electric potentials for a first group is different from that of a second group, the first and second groups being sequentially selected, the second group being selected after the first group is selected.

[0059] Specifically, while the group Gr1 is being selected, the scanning signal lines G1, G3, ..., G23, which belong to the selected group Gr1, are sequentially subjected to horizontal scans (i.e., gate pulses GP1, GP3, ..., GP23 are sequentially supplied to the scanning signal lines G1, G3, ..., G23, respectively). During the horizontal scans, data signal electric potentials, which have a positive polarity and correspond to respective pieces of video data D1, D3, ..., D23, are supplied to the data signal line S during respective horizontal scan periods. Subsequently, while the group Gr2 is being selected, the scanning signal lines G2, G4, ..., G48, which belong to the selected group Gr2, are sequentially subjected to horizontal scans (i.e., gate pulses GP2, GP4, ..., GP48 are

sequentially supplied to the scanning signal lines G2, G4, ..., G48, respectively). During the horizontal scans, data signal electric potentials, which have a negative polarity and correspond to respective pieces of video data D2, D4, ..., D48, are supplied to the data signal line S during respective horizontal scan periods. Then, while the group Gr3 is being selected, the scanning signal lines G25, G27, ..., which belong to the selected group Gr3, are sequentially subjected to horizontal scans (i.e., gate pulses GP25, GP27, ... are sequentially supplied to the scanning signal lines G25, G27, ..., respectively). During the horizontal scans, data signal electric potentials, which has a positive polarity and correspond to respective pieces of video data D25, D27, ..., are supplied to the data signal line S during respective horizontal scan periods. Consequently, a polarity distribution of electric potentials of respective pixels in the display section becomes as shown in Fig. 10.

[0060] Moreover, first and second dummy scan periods are put between (i) a horizontal scan period corresponding to a last horizontal scan in the first group and (ii) a horizontal scan period corresponding to a first horizontal scan in the second group, the second group being selected after the first group is selected. In each of the dummy scan periods, a dummy signal electric potential is supplied to a data signal line.

[0061] For example, a first dummy scan period HX and a second dummy scan period HY are put between the horizontal scan period H23 and the horizontal scan period H2. The horizontal scan period H23 corresponds to the last horizontal scan in the group Gr1, and the horizontal scan period H2 corresponds to the first horizontal scan in the group Gr2. The first and second groups are consecutively selected in this order. Moreover, pieces of dummy data DA and DB are put between pieces of video data D23 and D2. In the first dummy scan period HX, a dummy signal electric potential corresponding to the dummy data DA (e.g., data identical to the video data D2) is supplied to the data signal line S. In the second dummy scan period HY, a dummy signal electric potential corresponding to the dummy data DB (e.g., data identical to the video data D2) is supplied to the data signal line S. Similarly, a first dummy scan period Hx and a second dummy scan period Hy are put between a horizontal scan period H48 and a horizontal scan period H25. Moreover, pieces of dummy data Da and Db are put between the pieces of video data D48 and D25. In the first dummy scan period Hx, a dummy signal electric potential corresponding to the dummy data Da (e.g., data identical to the video data D25) is supplied to the data signal line S. In the second dummy scan period HY, a dummy signal electric potential corresponding to the dummy data Db (e.g., data identical to the video data D25) is supplied to the data signal line S.

[0062] Note here that, in case where consecutive first and second horizontal scans are carried out in this order in each of the groups, a gate pulse corresponding to the second horizontal scan becomes active in sync with a

gate pulse, which corresponds to the first horizontal scan, becoming nonactive. Note also that, a horizontal scan period corresponding to an arbitrary horizontal scan is started after a gate pulse, which corresponds to the arbitrary horizontal scan, becomes active, and the horizontal scan period corresponding to the arbitrary horizontal scan is ended after the gate pulse becomes nonactive.

[0063] For example, the gate pulse GP3 becomes active (rises) in sync with the gate pulse GP1 becoming nonactive (falls), and the gate pulse GP5 becomes active in sync with the gate pulse GP3 becoming nonactive. Moreover, the horizontal scan period H1 is started after the gate pulse GP1 becomes active, and the horizontal scan period H1 is ended after the gate pulse GP1 becomes nonactive. Moreover, the horizontal scan period H3 is started after the gate pulse GP3 becomes active, and the horizontal scan period H3 is ended after the gate pulse GP3 becomes nonactive. Note that the gate pulse GP2 becomes active in sync with a gate pulse GP23 becoming nonactive, and after the first and second dummy scan periods HX and HY, the gate pulse GP2 becomes nonactive in sync with the gate pulse GP4 becoming active.

[0064] It should be noted here that, in a case where first and second groups are consecutively selected in this order, a time period from a time point when a gate pulse which corresponds to the last horizontal scan in the first group becomes nonactive to a time point when a dummy scan period is started is set to be longer than a time period from a time point when a gate pulse corresponding to one of consecutive two horizontal scans becomes nonactive in the first group to a time point when a horizontal scan period corresponding to the other of the consecutive two horizontal scans is started.

[0065] Specifically, a time period from a time point when the gate pulse GP23 corresponding to the last horizontal scan in the group Gr1 becomes nonactive (falls) to a time point when the first dummy scan period HX is started is set to be longer than a time period from a time point when the gate pulse GP1 becomes nonactive (falls) to a time point when the horizontal scan period H3 is started; and a time period from a time point when the gate pulse GP48 corresponding to the last horizontal scan in the group Gr2 becomes nonactive (falls) to a time point when the first dummy scan period Hx is started is set to be longer than a time period from a time point when a gate pulse GP21 becomes nonactive (falls) to a time point when the horizontal scan period H23 is started. The following describes this feature with reference to Fig. 9.

[0066] As shown in Fig. 9, the horizontal scan period H21 (a time period during which a data signal electric potential which has a positive polarity and corresponds to the video data D21 is being supplied to the data signal line S) is started after the gate pulse GP21 becomes active, and then the horizontal scan period H21 is ended after a time period t is elapsed since the gate pulse GP21 becomes nonactive.

[0067] The gate pulse GP 23 becomes active in sync

with the gate pulse GP21 becoming nonactive. Then, the horizontal scan period H23 (a time period during a data signal electric potential which has a positive polarity and corresponds to the video data D23 is being supplied to the data signal line S) is started. The horizontal scan period H23 is ended after a time period $T (>t)$ is elapsed since the gate pulse GP23 becomes nonactive. The dummy scan period HX is started concurrently with the horizontal scan period H23 being ended.

[0068] Note here that, even though the gate pulse GP23 becomes nonactive, an electric potential GV23 of the scanning signal line G23 does not fall precipitously but falls while becoming dull due to parasitic resistor and parasitic capacitor. That is, the TFT of the pixel P23 connected to the scanning signal line G23 is turning on for a while (during a dull period) after the gate pulse GP23 becomes nonactive.

[0069] In view of the circumstances, the time period T from a time point when the gate pulse GP23 becomes nonactive to a time point when the dummy scan period HX (a time period during which a dummy signal electric potential which has a negative polarity and corresponds to the dummy data DA is being supplied to the data signal line S) is started is set to be longer than the time period t (i.e., the horizontal scan period H23 is extended). This allows the horizontal scan period H23 to contain the dull period (most part of the dull period) of the electric potential GV23 of the scanning signal line G23. Accordingly, it is possible to prevent a phenomenon in which positive electric charge written into the pixel P23 during the horizontal scan period H23 is discharged by the dummy scan period HX being started. This makes it possible to reduce blackish lateral stripes (see Fig. 20) which have been the problem of a conventional display.

[Embodiment 2]

[0070] A liquid crystal display device of Embodiment 2 has a display section (e.g., of a normally black mode) in which scanning signal lines (G1 through G1080) and retention capacitor lines (CS1 through CS1081) which extend in parallel with the scanning signal lines (see Fig. 11) are provided. Each of pixels has two subpixels provided in a column direction (in a direction in which data signal lines extend), and one (1) pixel electrode is provided for each of the subpixels. Moreover, one (1) retention capacitor line is provided for each gap between any adjacent two pixels in the column direction. A capacitor is defined by the one (1) retention capacitor line and a pixel electrode provided in one of the adjacent two pixels, and a capacitor is defined by the one (1) retention capacitor line and a pixel electrode provided in the other of the adjacent two pixels.

[0071] Specifically, in a case where an i -th pixel in a pixel column is referred to as a pixel P_i , the retention capacitor lines CS1 and CS1081 are provided on both sides of the pixel column, and a retention capacitor line $CS(i+1)$ (i is an integer of 1 to 1079) is provided for a gap

between the pixel P_i and a pixel $P_{(i+1)}$. Moreover, the pixel P_i (i is an integer of 1 to 1080) has two pixel electrodes each of which is connected to a scanning signal line G_i and a data signal line SL via a corresponding transistor. A retention capacitor is defined by one of the two pixel electrodes and a retention capacitor line CS_i and a retention capacitor is defined by the other of the two pixel electrodes and the retention capacitor line $CS_{(i+1)}$.

[0072] For example, a retention capacitor line CS_1 is provided on one side (on an upstream side) of a pixel column, a retention capacitor line CS_2 is provided for a gap between a pixel P_1 and a pixel P_2 , and a retention capacitor line CS_3 is provided for a gap between the pixel P_2 and a pixel P_3 . The pixel P_1 has two pixel electrodes each of which is connected to the scanning signal line G_1 and the data signal line SL via a transistor. A retention capacitor is defined by one of the two pixel electrodes and the retention capacitor line CS_1 , and a retention capacitor is defined by the other of the two pixel electrodes and the retention capacitor line CS_2 . The pixel P_2 has two pixel electrodes each of which is connected to the scanning signal line G_2 and the data signal line SL via a transistor. A retention capacitor is defined by one of the two pixel electrodes and the retention capacitor line CS_2 , and a retention capacitor is defined by the other of the two pixel electrodes and the retention capacitor line CS_3 .

[0073] According to the liquid crystal display device of

[0074] Embodiment 2, (i) driving of the data signal line S and the scanning signal lines G_1 through G_{1080} and (ii) setting of the horizontal scan periods and the dummy scan periods are identical to those shown in Figs. 8 and 9.

[0075] The following describes a retention capacitor line signal SCS_i which is to be supplied to the retention capacitor line CS_i (i is an integer of 1 to 1080) from a CS driver circuit (CS driver), with reference to Figs. 12 through 14. Each of retention capacitor line signals SCS_1 through SCS_{1081} has a waveform which has any one of 14 phases (the first phase as represented by the retention capacitor line signal SCS_1 , the second phase as represented by SCS_2 , the third phase as represented by SCS_3 , the fourth phase as represented by SCS_4 , the fifth phase as represented by SCS_5 , the sixth phase as represented by SCS_6 , the seventh phase represented by SCS_7 , the eighth phase as represented by SCS_8 , the ninth phase as represented by SCS_9 , the tenth phase as represented by SCS_{10} , the eleventh phase as represented by SCS_{11} , the twelfth phase as represented by SCS_{12} , the thirteenth phase as represented by SCS_{13} , and the fourteenth phase as represented by SCS_{14}) (see Figs. 12 and 13).

[0076] The phases have identical cycles (each of which has a cycle of 14H including (i) a first stage in which a high level continues for 7H and (ii) a second stage in which a low level continues for 7H). The second phase as represented by SCS_2 has a phase-delay of half cycle (7H) with respect to the first phase as represented by SCS_1 . With regard to an arbitrary odd-numbered phase

and a subsequent odd-numbered phase, the subsequent odd-numbered phase has a phase-delay of 1H with respect to the arbitrary odd-numbered phase. With regard to an arbitrary even-numbered phase and a subsequent even-numbered phase, the subsequent even-numbered phase has a phase-delay of 1H with respect to the arbitrary even-numbered phase. For example, the third phase as represented by the retention capacitor line signal SCS_3 has a phase-delay of 1H with respect to the first phase as represented by SCS_1 , and the fourth phase as represented by SCS_4 has a phase-delay of 1H with respect to the second phase as represented by SCS_2 .

[0077] Retention capacitor line signals $SCS_{(28j+1)}$ and $SCS_{(28k+16)}$ have a waveform which has the first phase, where j is an integer of 0 to 38, and k is an integer of 0 to 38. Retention capacitor line signals $SCS_{(28j+2)}$ and $SCS_{(28k+15)}$ have a waveform which has the second phase, where j is an integer of 0 to 38, and k is an integer of 0 to 38. Retention capacitor line signals $SCS_{(28j+3)}$ and $SCS_{(28k+18)}$ have a waveform which has the third phase, where j is an integer of 0 to 38, and k is an integer of 0 to 37 (same applies to the followings). Retention capacitor line signals $SCS_{(28j+4)}$ and $SCS_{(28k+17)}$ have a waveform which has the fourth phase. Retention capacitor line signals $SCS_{(28j+5)}$ and $SCS_{(28k+20)}$ have a waveform which has the fifth phase. Retention capacitor line signals $SCS_{(28j+6)}$ and $SCS_{(28k+19)}$ have a waveform which has the sixth phase. Retention capacitor line signals $SCS_{(28j+7)}$ and $SCS_{(28k+22)}$ have a waveform which has the seventh phase. Retention capacitor line signals $SCS_{(28j+8)}$ and $SCS_{(28k+21)}$ have a waveform which has the eighth phase. Retention capacitor line signals $SCS_{(28j+9)}$ and $SCS_{(28k+24)}$ have a waveform which has the ninth phase. Retention capacitor line signals $SCS_{(28j+10)}$ and $SCS_{(28k+23)}$ have a waveform which has the tenth phase. Retention capacitor line signals $SCS_{(28j+11)}$ and $SCS_{(28k+26)}$ have a waveform which has the eleventh phase. Retention capacitor line signals $SCS_{(28j+12)}$ and $SCS_{(28k+25)}$ have a waveform which has the twelfth phase. Retention capacitor line signals $SCS_{(28j+13)}$ and $SCS_{(28k+28)}$ have a waveform which has the thirteenth phase. Retention capacitor line signals $SCS_{(28j+14)}$ and $SCS_{(28k+27)}$ have a waveform which has the fourteenth phase.

[0078] Note that the retention capacitor line signals which have first through fourteenth phases are supplied to retention capacitor trunk lines M_1 through M_{14} , respectively (see Fig. 14). The retention capacitor lines $CS_{(28j+1)}$ and $CS_{(28k+16)}$ are connected to the retention capacitor trunk line M_1 , where j is an integer of 0 to 38, and k is an integer of 0 to 38. The retention capacitor lines $CS_{(28j+2)}$ and $CS_{(28k+15)}$ are connected to the retention capacitor trunk line M_2 , where j is an integer of 0 to 38, and k is an integer of 0 to 38. The retention capacitor lines $CS_{(28j+3)}$ and $CS_{(28k+18)}$ are connected to the retention capacitor trunk line M_3 , where j is an integer of 0 to 38, and k is an integer of 0 to 37 (same

applies to the followings). The retention capacitor lines CS(28j+4) and CS(28k+17) are connected to the retention capacitor trunk line M4. The retention capacitor lines CS(28j+5) and CS(28k+20) are connected to the retention capacitor trunk line M5. The retention capacitor lines CS(28j+6) and CS(28k+19) are connected to the retention capacitor trunk line M6. The retention capacitor lines CS(28j+7) and CS(28k+22) are connected to the retention capacitor trunk line M7. The retention capacitor lines CS(28j+8) and CS(28k+21) are connected to the retention capacitor trunk line M8. The retention capacitor lines CS(28j+9) and CS(28k+24) are connected to the retention capacitor trunk line M9. The retention capacitor lines CS(28j+10) and CS(28k+23) are connected to the retention capacitor trunk line M10. The retention capacitor lines CS(28j+11) and CS(28k+26) are connected to the retention capacitor trunk line M11. The retention capacitor lines CS(28j+12) and CS(28k+25) are connected to the retention capacitor trunk line M12. The retention capacitor lines CS(28j+13) and CS(28k+28) are connected to the retention capacitor trunk line M13. The retention capacitor lines CS(28j+14) and CS(28k+27) are connected to the retention capacitor trunk line M 14.

[0079] The retention capacitor line signals SCS1 through SCS1081 have respective waveforms as described above. Moreover, according to the liquid crystal display device of the present embodiment, (i) the retention capacitor line signal SCS1 (first phase) is being at an "L" level during the horizontal scan period H1 which corresponds to the scanning signal line G1, and the "L" level is shifted to an "H" level at a timing when 1 H is elapsed after the horizontal scan period H1 is ended and (ii) the retention capacitor line signal SCS2 (second phase) is being at an "H" level during the horizontal scan period H1 which corresponds to the scanning signal line G1, and the "H" level is shifted to an "L" level at a timing when 1H is elapsed after the horizontal scan period H1 is ended (see Fig. 13).

[0080] One of two subpixels of the pixel P1 includes a first pixel electrode, which causes a retention capacitor to be defined by the pixel electrode and the retention capacitor line CS1, and the other of the two subpixels includes a second pixel electrode, which causes a retention capacitor to be defined by the pixel electrode and the retention capacitor line CS2. Signal electric potentials having a positive polarity are supplied to the two pixel electrodes in the horizontal scan period H1. The electric potential of the first pixel electrode is increased in response to the retention capacitor line signal SCS1 being shifted from the level "L" to level "H". The electric potential of the second pixel electrode is decreased in response to the retention capacitor line signal SCS2 being shifted from the level "H" to level "L". This causes (i) the subpixel, which includes the first pixel electrode, to be a "bright subpixel" and (ii) the subpixel, which includes the second pixel electrode, to be a "dark subpixel" (see Fig. 15). The bright and dark subpixels make it possible to display a halftone.

[0081] According to the retention capacitor line signals SCS1 and SCS2 (first and second phases), (i) the retention capacitor line signal SCS2 (second phase) is being at a level "H" during the horizontal scan period H2 which corresponds to the scanning signal line G2, and the level "H" is shifted to a level "L" at a timing when 1H is elapsed after the horizontal scan period H2 is ended and (ii) the retention capacitor line signal SCS3 (third phase) is being at a level "L" during the horizontal scan period H2 which corresponds to a scanning signal line G2, and the level "L" is shifted to a level "H" at a timing when 2H is elapsed after the horizontal scan period H2 is ended.

[0082] One of two subpixels of the pixel P2 includes a third pixel electrode, which causes a retention capacitor to be defined by the pixel electrode and the retention capacitor line CS2, and the other of the two subpixels includes a fourth pixel electrode which causes a retention capacitor to be defined by the pixel electrode and the retention capacitor line CS3. Signal electric potentials having a negative polarity are supplied to the two pixel electrodes in the horizontal scan period H2. The electric potential of the third pixel electrode is decreased in response to the retention capacitor line signal SCS2 being shifted from the level "H" to level "L". The electric potential of the fourth pixel electrode is increased in response to the retention capacitor line signal SCS3 being shifted from the level "L" to level "H". This causes (i) the subpixel, which includes the third pixel electrode to be a "bright subpixel" and (ii) the subpixel, which includes the fourth pixel electrode to be a "dark subpixel" (see Fig. 15). The bright and dark subpixels make it possible to display a halftone.

[0083] According to the retention capacitor line signals SCS1 and SCS2 (first and second phases), (i) the retention capacitor line signal SCS3 (third phase) is being at the level "L" during the horizontal scan period H3 which corresponds to the scanning signal line G3, and the level "L" is shifted to the level "H" at a timing when 1H is elapsed after the horizontal scan period H3 is ended and (ii) the retention capacitor line signal SCS4 (fourth phase) is being at a level "H" during the horizontal scan period H3 which corresponds to the scanning signal line G3, and the level "H" is shifted to a level "L" at a timing when 1 H is elapsed after the horizontal scan period H3 is ended.

[0084] One of two subpixels of the pixel P1 includes a fifth pixel electrode which causes a retention capacitor to be defined by the pixel electrode and the retention capacitor line CS3, and the other of the two subpixels includes a sixth pixel electrode which causes a retention capacitor to be defined by the pixel electrode and the retention capacitor line CS4. Signal electric potentials having a positive polarity are supplied to the two pixel electrodes in the horizontal scan period H3. The electric potential of the fifth pixel electrode is increased in response to the retention capacitor line signal SCS3 being shifted from the level "L" to level "H". The electric potential of the sixth pixel electrode is decreased in response to the retention capacitor line signal SCS4 being shifted

from the level "H" to level "L". This causes (i) the subpixel, which includes the fifth pixel electrode, to be a "bright subpixel" and (ii) the subpixel, which includes the sixth pixel electrode, to be a "dark subpixel" (see Fig. 15). The bright and dark subpixels make it possible to display a halftone.

[0085] According to the liquid crystal display device of the present embodiment, two subpixels in one (1) pixel serve as respective of a "bright subpixel" and a "dark subpixel" so as to display a halftone (see Fig. 15). This makes it possible to enhance a viewing angle characteristic. Further, one (1) pixel column is alternated between the bright subpixel and the dark subpixel (in a checkered manner). This makes it possible to achieve a smooth display with little roughness.

[0086] Fig. 16 is a block diagram illustrating an example configuration of the liquid crystal display device of Embodiment 1. As shown in Fig. 16, the liquid crystal display device includes a display section (liquid crystal panel), a source driver, a gate driver, a backlight, a backlight driving circuit, and a display control circuit. The source driver drives the data signal line. The gate driver drives the scanning signal lines. The display control circuit controls the source driver, the gate driver, and the backlight driving circuit.

[0087] The display control circuit receives, from an external signal source (e.g., a tuner), (i) a digital video signal Dv which is indicative of an image to be displayed, (ii) a horizontal sync signal HSY and a vertical sync signal VSY which correspond to the digital video signal Dv, and (iii) a control signal Dc for controlling display behavior. Based on the received signals Dv, HSY, VSY, and Dc, the display control circuit generates and outputs, as signals for causing the display section to display the image indicated by the digital video signal Dv, (i) a data start pulse signal SSP, (ii) a data clock signal SCK, (iii) a digital image signal DA (corresponding to the video signal Dv) indicative of the image to be displayed, (iv) a gate start pulse signal GSP, (v) a gate clock signal GCK, (vi) a gate driver output control signal (scanning signal output control signal) GOE, (vii) a polarity-reversal signal POL for controlling a polarity of a signal electric potential to be supplied to the data signal line, and (viii) a latch strobe signal LS for defining a horizontal scan period and a dummy scan period.

[0088] More specifically, the video signal Dv, which has been subjected to timing adjustment, etc. as appropriate in an internal memory, is supplied from the display control circuit as the digital image signal DA. The data clock signal SCK is generated as a signal having pulses corresponding to respective pixels of the image indicated by the digital image signal DA. The data start pulse signal SSP is generated as a signal which becomes a high level (H level) for a predetermined period for each horizontal scan period in response to the horizontal sync signal HSY. The gate start pulse signal GSP is generated as a signal which becomes an H level for a predetermined period for each frame period (one vertical scan period)

in response to the vertical sync signal VSY. The gate clock signal GCK is generated based on the horizontal sync signal HSY. The gate driver output control signal GOE is generated based on the horizontal sync signal HSY and the control signal Dc.

[0089] Out of the signals generated in the display control circuit, the digital image signal DA, the polarity-reversal signal POL, the data start pulse signal SSP, and the data clock signal SCK are supplied to the source driver, whereas the gate start pulse signal GSP, the gate clock signal GCK, and the gate driver output control signal GOE are supplied to the gate driver.

[0090] The source driver sequentially generates, for each horizontal scan period, a data signal based on the digital image signal DA, the data clock signal SCK, the data start pulse signal SSP, the latch strobe signal LS, and the polarity-reversal signal POL. The data signal is generated as an analog electric potential which corresponds to a pixel value, for a corresponding scanning signal line, of the image indicated by the digital image signal DA. The data signals thus generated are sequentially supplied to the data signal line S for each horizontal scan period.

[0091] The gate driver generates scan signals, based on the gate start pulse signal GSP, the gate clock signal GCK, and the gate driver output control signal GOE. The scan signals thus generated are supplied to the respective scanning signal lines so that the scanning signal lines are selectively driven.

[0092] The data signal line and the scanning signal lines of the display section (liquid crystal panel) are driven by the source driver and the gate driver as described above. Accordingly, a signal electric potential, via the data signal line, is written into a pixel electrode via a TFT connected to a selected scanning signal line. This allows the liquid crystal layer of a pixel to receive a voltage in response to the digital image signal DA, and a transmission amount of the light emitted from the backlight is controlled in response to the voltage thus received so that the image indicated by the digital video signal Dv is displayed by the pixel.

[0093] In a case where an image is displayed on a liquid crystal display device 800 based on television broadcasting, the liquid crystal display device 800 is connected to a tuner section 90. This causes realization of a television receiver 601 of the present embodiment (see Fig. 17). The tuner section 90 extracts a signal of a channel to be received among waves (high-frequency signals) received via an antenna (not illustrated), and then converts the signal thus extracted into an intermediate frequency signal so as to extract a composite color video signal Scv (a television signal) by detecting the intermediate frequency signal. The composite color video signal Scv is supplied to the liquid crystal display device 800 as described above so that the liquid crystal display device 800 displays an image based on the composite color video signal Scv.

[0094] Note that, in the present invention, "a polarity

of an electric potential" indicates whether the electric potential is larger or smaller than a reference electric potential. Specifically, an "electric potential having a positive polarity" indicates an electric potential larger than the reference electric potential, and an "electric potential having a negative polarity" indicates an electric potential smaller than the reference electric potential. Note also that the reference electric potential can be an electric potential Vcom (common electric potential) of a common electrode (counter electrode). Alternatively, the reference electric potential can be another arbitrary electric potential.

[0095] Note that the present invention is not limited to the embodiments, but can be altered by a skilled person in the art within the scope of the claims. An embodiment derived from a proper combination of technical means disclosed in respective different embodiments is also encompassed in the technical scope of the present invention.

Industrial Applicability

[0096] The liquid crystal display device of the present invention is suitable for, for example, a liquid crystal television.

Reference Signs List

[0097]

G1 through G1080: Scanning signal line
 B1 through B3: Block
 P1 through P1080: Pixel
 D: Video data
 H: Horizontal scan period
 HX, Hx: First dummy scan period
 HY, Hy: Second dummy scan period
 S: Data signal line
 CS1 through 1081: Retention capacitor line
 601: Television receiver
 800: Liquid crystal display device

Claims

1. A method for driving a liquid crystal display device, the method comprising the steps of:

sequentially selecting, by a gate driver of said liquid crystal display, groups (Gr1, Gr2) each of which includes scanning signal lines (G1-G12, G13-G24) of said liquid crystal display; sequentially supplying, by a source driver of said liquid crystal display, data signal electric potentials corresponding to pieces of image data (D11, D12) and having an identical polarity to a data signal line (S) of a plurality of data signal lines of said liquid crystal display during respec-

tive horizontal scan periods (H11, H12), in response to sequentially supplying scanning pulses (GP11, GP12) to respective scanning signal lines (G11, G12) which belong to a selected group (Gr1), correspondingly to the respective horizontal scan periods (H11, H12);

putting, by the gate driver of said liquid crystal display, a dummy scan period (HX) between a last horizontal scan period (H12) for a first group (Gr1) and a first horizontal scan period (H13) for a second group (Gr2) selected subsequently to the first group (Gr1); and

supplying, by the source driver of said liquid crystal display, a dummy signal electric potential corresponding to dummy data (DA) to the data signal line (S) during the dummy scan period (HX), wherein the dummy scan period is a time period during which the dummy signal electric potential is being supplied to the data signal line, wherein the polarity of the data signal electric potentials for the first group (Gr1) is different from that of the second group (Gr2) and the polarity of the dummy signal electric potential; and **characterized in that**

a time period (T) from a time point when a scanning pulse (GP12) corresponding to the last horizontal scan period (H12) for the first group (Gr1) becomes non-active to a time point when the dummy scan period (HX) is started is longer than a time period (t) from a time point when a scanning pulse (GP11) corresponding to a former one (H11) of two consecutive horizontal scan periods (H11, H12) for the first group (Gr1) becomes non-active to a time point when a subsequent one (H12) of the two consecutive horizontal scan periods (H11, H12) is started.

2. The method according to claim 1, wherein the scanning pulse corresponding to the subsequent one (H12) of the two consecutive horizontal scan periods becomes active in sync with the scanning pulse corresponding to the former one (H11) of the two consecutive horizontal scan periods becoming non-active.
3. The method according to claim 1 or 2, wherein each horizontal scan period (H11) is started by said liquid crystal display after a corresponding scanning pulse (GP11) becomes active.
4. The method according to one of claims 1 to 3, wherein the last horizontal scan period (H12) for the first group is longer than a horizontal scan period (H11) previous to the last horizontal scan period (H12).
5. The method according to one of claims 1 to 4, wherein a scanning pulse (GP13) corresponding to the first horizontal scan period for the second group be-

comes active before the dummy scan period (HX) is started.

6. The method according to one of claims 1 to 4, wherein a scanning pulse (GP13) corresponding to the first horizontal scan period for the second group becomes active after the dummy scan period is started.

7. The method according to one of claims 1 to 6, wherein the subsequent one (H12) of the two consecutive horizontal scan periods is started in sync with the scanning pulse (GP11) corresponding to the former one (H11) of the two consecutive horizontal scan periods becoming non-active.

8. A liquid crystal display device comprising:

scanning signal lines (G1, ...G24);
a data signal line (S) of a plurality of data signal lines of said liquid crystal display device;
a gate driver adapted to sequentially select groups (Gr1, Gr2) each of which includes plural of said scanning signal lines (G1-G12, G13-G24);

a source driver adapted to sequentially supply data signal electric potentials corresponding to pieces of image data (D11, D12) and having an identical polarity to the data signal line (S) during respective horizontal scan periods (H11, H12), in response to the gate driver sequentially supplying scanning pulses (GP11, GP12) to respective scanning signal lines (G11, G12) which belong to a selected group (Gr1), correspondingly to the respective horizontal scan periods (H11, H12);

wherein the gate driver is adapted to put a dummy scan period (HX) between a last horizontal scan period (H12) for a first group (Gr1) and a first horizontal scan period (H13) for a second group (Gr2) selected subsequently to the first group (Gr1); and

wherein the source driver is adapted to supplying a dummy signal electric potential corresponding to dummy data (DA) to the data signal line (S) during the dummy scan period (HX), wherein the dummy scan period is a time period during which the dummy signal electric potential is being supplied to the data signal line, wherein the source driver is adapted to make the polarity of the data signal electric potentials for the first group (Gr1) different from that of the second group (Gr2) and the polarity of the dummy signal electric potential; and

characterized in that

the gate driver is adapted to make a time period (T) from a time point when a scanning pulse (GP12) corresponding to the last horizontal scan period (H12) for the first group (Gr1) becomes

non-active to a time point when the dummy scan period (HX) is started longer than a time period (t) from a time point when a scanning pulse (GP11) corresponding to a former one (H11) of two consecutive horizontal scan periods (H11, H12) for the first group (Gr1) becomes non-active to a time point when a subsequent one (H12) of the two consecutive horizontal scan periods (H11, H12) is started.

9. The crystal display device of claim 8, comprising a plurality of pixels each made up of a plurality of sub-pixels.

10. The liquid crystal display device of claim 9, wherein the plurality of subpixels include respective pixel electrodes;

the crystal display device comprises retention capacitor lines that are provided for the respective pixel electrodes; and

wherein the liquid crystal display device is adapted to control a luminance of each of the plurality of subpixels in response to a retention capacitor line signal supplied to a corresponding one of the retention capacitor lines.

11. The liquid crystal display of one of claims 8 to 10, wherein the liquid crystal display is adapted to implement the steps of one of claims 1 to 7.

Patentansprüche

1. Verfahren zum Ansteuern einer Flüssigkristallanzeigevorrichtung, wobei das Verfahren folgende Schritte umfasst:

sequenzielles Auswählen, durch einen Gate-Treiber der Flüssigkristallanzeige, von Gruppen (Gr1, Gr2), von denen jede Abtastsignalleitungen (G1-G12, G13-G24) der Flüssigkristallanzeige enthält;

sequenzielles Zuführen, durch einen Source-Treiber der Flüssigkristallanzeige, von elektrischen Datensignalspotenzialen, die einzelnen Bilddatenelementen (D11, D12) entsprechen und eine identische Polarität haben, zu einer Datensignalleitung (S) von mehreren Datensignalleitungen der Flüssigkristallanzeige während jeweiliger horizontaler Abtastzeiträume (H11, H12), in Reaktion auf das sequenzielle Zuführen von Abtastimpulsen (GP11, GP12) zu jeweiligen Abtastsignalleitungen (G11, G12), die zu einer ausgewählten Gruppe (Gr1) gehören, entsprechend den jeweiligen horizontalen Abtastzeiträumen (H11, H12);

Einfügen, durch den Gate-Treiber der Flüssigkristallanzeige, eines Dummy-Abtastzeitraums

- (HX) zwischen einen letzten horizontalen Abtastzeitraum (H12) für eine erste Gruppe (Gr1) und einen ersten horizontalen Abtastzeitraum (H13) für eine zweite Gruppe (Gr2), die nach der ersten Gruppe (Gr1) ausgewählt wurde; und
 Zuführen, durch den Source-Treiber der Flüssigkristallanzeige, eines elektrischen Dummy-Signalpotenzials, das Dummy-Daten (DA) entspricht, zu der Datensignalleitung (S) während des Dummy-Abtastzeitraums (HX), wobei der Dummy-Abtastzeitraum ein Zeitraum ist, während dem das elektrische Dummy-Signalpotential zu der Datensignalleitung zugeführt wird, wobei die Polarität der elektrischen Datensignalsignale für die erste Gruppe (Gr1) eine andere ist als die der zweiten Gruppe (Gr2) und eine andere ist als die Polarität des elektrischen Dummy-Signalsignals; und
dadurch gekennzeichnet, dass
 ein Zeitraum (T) ab einem Zeitpunkt, wo ein Abtastimpuls (GP12), der dem letzten horizontalen Abtastzeitraum (H12) für die erste Gruppe (Gr1) entspricht, inaktiv wird, bis zu einem Zeitpunkt, wo der Dummy-Abtastzeitraum (HX) begonnen wird, länger ist als ein Zeitraum (t) ab einem Zeitpunkt, wo ein Abtastimpuls (GP11), der einem früheren (H11) von zwei aufeinanderfolgenden horizontalen Abtastzeiträumen (H11, H12) für die erste Gruppe (Gr1) entspricht, inaktiv wird, bis zu einem Zeitpunkt, wo ein späterer (H12) der zwei aufeinanderfolgenden horizontalen Abtastzeiträume (H11, H12) begonnen wird.
2. Verfahren nach Anspruch 1, wobei der Abtastimpuls, der dem späteren (H12) der zwei aufeinanderfolgenden horizontalen Abtastzeiträume entspricht, synchron in dem Moment aktiv wird, in dem der Abtastimpuls, der dem früheren (H11) der zwei aufeinanderfolgenden horizontalen Abtastzeiträume entspricht, inaktiv wird.
 3. Verfahren nach Anspruch 1 oder 2, wobei jeder horizontale Abtastzeitraum (H11) durch die Flüssigkristallanzeige begonnen wird, nachdem ein entsprechender Abtastimpuls (GP11) aktiv wird.
 4. Verfahren nach einem der Ansprüche 1 bis 3, wobei der letzte horizontale Abtastzeitraum (H12) für die erste Gruppe länger ist als ein horizontaler Abtastzeitraum (H11) vor dem letzten horizontalen Abtastzeitraum (H12).
 5. Verfahren nach einem der Ansprüche 1 bis 4, wobei ein Abtastimpuls (GP13), der dem ersten horizontalen Abtastzeitraum für die zweite Gruppe entspricht, aktiv wird, bevor der Dummy-Abtastzeitraum (HX) begonnen wird.
 6. Verfahren nach einem der Ansprüche 1 bis 4, wobei ein Abtastimpuls (GP13), der dem ersten horizontalen Abtastzeitraum für die zweite Gruppe entspricht, aktiv wird, nachdem der Dummy-Abtastzeitraum begonnen wurde.
 7. Verfahren nach einem der Ansprüche 1 bis 6, wobei der spätere (H12) der zwei aufeinanderfolgenden horizontalen Abtastzeiträume synchron in dem Moment begonnen wird, in dem der Abtastimpuls (GP11), der dem früheren (H11) der zwei aufeinanderfolgenden horizontalen Abtastzeiträume entspricht, inaktiv wird.
 8. Flüssigkristallanzeigevorrichtung, die Folgendes umfasst:
 Abtastsignalleitungen (G1, ... G24);
 eine Datensignalleitung (S) von mehreren Datensignalleitungen der Flüssigkristallanzeigevorrichtung;
 einen Gate-Treiber, der dafür ausgelegt ist, sequenziell Gruppen (Gr1, Gr2) auszuwählen, von denen jede mehrere der Abtastsignalleitungen (G1-G12, G13-G24) enthält;
 einen Source-Treiber, der dafür ausgelegt ist, elektrische Datensignalsignale, die einzelnen Bilddatenelementen (D11, D12) entsprechen und eine identische Polarität haben, sequenziell zu der Datensignalleitung (S) während jeweiliger horizontaler Abtastzeiträume (H11, H12) in Reaktion auf das sequenzielle Zuführen von Abtastimpulsen (GP11, GP12) durch den Gate-Treiber zu jeweiligen Abtastsignalleitungen (G11, G12), die zu einer ausgewählten Gruppe (Gr1) gehören, entsprechend den jeweiligen horizontalen Abtastzeiträumen (H11, H12) zuzuführen;
 wobei der Gate-Treiber dafür ausgelegt ist, einen Dummy-Abtastzeitraum (HX) zwischen einen letzten horizontalen Abtastzeitraum (H12) für eine erste Gruppe (Gr1) und einen ersten horizontalen Abtastzeitraum (H13) für eine zweite Gruppe (Gr2), die nach der ersten Gruppe (Gr1) ausgewählt wurde, einzufügen; und
 wobei der Source-Treiber dafür ausgelegt ist, ein elektrisches Dummy-Signalpotential, das Dummy-Daten (DA) entspricht, zu der Datensignalleitung (S) während des Dummy-Abtastzeitraums (HX) zuzuführen, wobei der Dummy-Abtastzeitraum ein Zeitraum ist, während dem das elektrische Dummy-Signalpotential zu der Datensignalleitung zugeführt wird;
 wobei der Source-Treiber dafür ausgelegt ist, die Polarität der elektrischen Datensignalsignale für die erste Gruppe (Gr1) zu einer anderen Polarität zu machen als die Polarität der zweiten Gruppe (Gr2) und die Polarität des elek-

trischen Dummy-Signalpotenzials; und

dadurch gekennzeichnet, dass

der Gate-Treiber dafür ausgelegt ist, einen Zeitraum (T) ab einem Zeitpunkt, wo ein Abtastimpuls (GP12), der dem letzten horizontalen Abtastzeitraum (H12) für die erste Gruppe (Gr1) entspricht, inaktiv wird, bis zu einem Zeitpunkt, wo der Dummy-Abtastzeitraum (HX) begonnen wird, länger zu machen als einen Zeitraum (t) ab einem Zeitpunkt, wo ein Abtastimpuls (GP11), der einem früheren (H11) von zwei aufeinanderfolgenden horizontalen Abtastzeiträumen (H11, H12) für die erste Gruppe (Gr1) entspricht, inaktiv wird, bis zu einem Zeitpunkt, wo ein späterer (H12) der zwei aufeinanderfolgenden horizontalen Abtastzeiträume (H11, H12) begonnen wird.

9. Kristallanzeigevorrichtung nach Anspruch 8, die mehrere Pixel umfasst, die jeweils aus mehreren Subpixeln bestehen.
10. Flüssigkristallanzeigevorrichtung nach Anspruch 9, wobei die mehreren Subpixel jeweilige Pixelelektroden enthalten;
wobei die Kristallanzeigevorrichtung Haltekondensatorleitungen umfasst, die für die jeweiligen Pixelelektroden bereitgestellt sind; und
wobei die Flüssigkristallanzeigevorrichtung dafür ausgelegt ist, eine Leuchtdichte eines jeden der mehreren Subpixel in Reaktion auf das Zuführen eines Haltekondensatorleitungssignals zu einer entsprechenden der Haltekondensatorleitungen zu steuern.
11. Flüssigkristallanzeige nach einem der Ansprüche 8 bis 10, wobei die Flüssigkristallanzeige dafür ausgelegt ist, die Schritte nach einem der Ansprüche 1 bis 7 zu implementieren.

Revendications

1. Procédé pour commander un dispositif d'affichage à cristaux liquides, le procédé comprenant les étapes :

de sélection séquentielle, par un dispositif de commande de grille dudit afficheur à cristaux liquides, de groupes (Gr1, Gr2) comprenant chacun des lignes de signal de balayage (G1 à G12, G13 à G24) dudit afficheur à cristaux liquides ;
de fourniture séquentielle, par un dispositif de commande de source dudit afficheur à cristaux liquides, de potentiels électriques de signal de données correspondant à des éléments de données d'image (D11, D12) et ayant une polarité

identique à celle d'une ligne de signal de données (S) d'une pluralité de lignes de signal de données dudit afficheur à cristaux liquides pendant des périodes de balayage horizontal (H11, H 12) respectives, en réponse à la fourniture séquentielle d'impulsions de balayage (GP11, GP12) aux lignes de signal de balayage (G11, G12) respectives qui appartiennent à un groupe (Gr1) sélectionné, en correspondance avec les périodes de balayage horizontal (H11, H 12) respectives ;

de placement, par le dispositif de commande de grille dudit afficheur à cristaux liquides, d'une période de balayage fictive (HX) entre une dernière période de balayage horizontal (H12) pour un premier groupe (Gr1) et une première période de balayage horizontal (H13) pour un deuxième groupe (Gr2) sélectionné à la suite du premier groupe (Gr1) ; et

de fourniture, par le dispositif de commande de source dudit afficheur à cristaux liquides, d'un potentiel électrique de signal fictif correspondant à des données fictives (DA) à la ligne de signal de données (S) pendant la période de balayage fictive (HX), dans lequel la période de balayage fictive est une période de temps pendant laquelle le potentiel électrique de signal fictif est appliqué à la ligne de signal de données, dans lequel la polarité des potentiels électriques de signal de données pour le premier groupe (Gr1) est différente de celle du deuxième groupe (Gr2) et de la polarité du potentiel électrique de signal fictif ; et

caractérisé en ce que

une période de temps (T) à partir d'un instant auquel une impulsion de balayage (GP12) correspondant à la dernière période de balayage horizontal (H 12) pour le premier groupe (Gr1) devient non active jusqu'à un instant auquel la période de balayage fictive (HX) est débutée est plus longue qu'une période de temps (t) à partir d'un instant auquel une impulsion de balayage (GP11) correspondant à une première période (H 11) de deux périodes de balayage horizontal consécutives (H11, H12) pour le premier groupe (Gr1) devient non active jusqu'à un instant auquel une période suivante (H12) des deux périodes de balayage horizontal consécutives (H 11, H12) est débutée.

2. Procédé selon la revendication 1, dans lequel l'impulsion de balayage correspondant à la période suivante (H12) des deux périodes de balayage horizontal consécutives devient active en synchronisation avec le passage de l'impulsion de balayage correspondant à la première période (H11) des deux périodes de balayage horizontal consécutives dans l'état non actif.

3. Procédé selon la revendication 1 ou 2, dans lequel chaque période de balayage horizontal (H 11) est débutée par ledit afficheur à cristaux liquides après qu'une impulsion de balayage (GP11) correspondante est devenue active. 5
4. Procédé selon l'une des revendications 1 à 3, dans lequel la dernière période de balayage horizontal (H 12) pour le premier groupe est plus longue qu'une période de balayage horizontal (H 11) qui précède la dernière période de balayage horizontal (H 12). 10
5. Procédé selon l'une des revendications 1 à 4, dans lequel une impulsion de balayage (GP13) correspondant à la première période de balayage horizontal pour le deuxième groupe devient active avant que la période de balayage fictive (HX) soit débutée. 15
6. Procédé selon l'une des revendications 1 à 4, dans lequel une impulsion de balayage (GP13) correspondant à la première période de balayage horizontal pour le deuxième groupe devient active après que la période de balayage fictive a débuté. 20
7. Procédé selon l'une des revendications 1 à 6, dans lequel la période suivante (H 12) des deux périodes de balayage horizontal consécutives est débutée en synchronisation avec le passage de l'impulsion de balayage (GP11) correspondant à la première période (H11) des deux périodes de balayage horizontal consécutives dans l'état non actif. 25
30
8. Dispositif d'affichage à cristaux liquides comprenant : 35
 - des lignes de signal de balayage (G1, ... G24) ;
 - une ligne de signal de données (S) d'une pluralité de lignes de signal de données dudit dispositif d'affichage à cristaux liquides ;
 - un dispositif de commande de grille conçu pour sélectionner séquentiellement des groupes (Gr1, Gr2) comprenant chacun plusieurs desdites lignes de signal de balayage (G1 à G12, G13 à G24) ; 40
 - un dispositif de commande de source conçu pour fournir séquentiellement des potentiels électriques de signal de données correspondant à des éléments de données d'image (D11, D12) et ayant une polarité identique à celle de la ligne de signal de données (S) pendant des périodes de balayage horizontal (H11, H12) respectives, en réponse à la fourniture séquentielle, par le dispositif de commande de grille, d'impulsions de balayage (GP11, GP12) aux lignes de signal de balayage (G11, G12) respectives qui appartiennent à un groupe (Gr1) sélectionné, en correspondance avec les périodes de balayage horizontal (H11, H12) respectives ; 45
50
55

dans lequel le dispositif de commande de grille est conçu pour placer une période de balayage fictive (HX) entre une dernière période de balayage horizontal (H12) pour un premier groupe (Gr1) et une première période de balayage horizontal (H13) pour un deuxième groupe (Gr2) sélectionné à la suite du premier groupe (Gr1) ; et

dans lequel le dispositif de commande de source est conçu pour fournir un potentiel électrique de signal fictif correspondant à des données fictives (DA) à la ligne de signal de données (S) pendant la période de balayage fictive (HX), dans lequel la période de balayage fictive est une période de temps pendant laquelle le potentiel électrique de signal fictif est appliqué à la ligne de signal de données,

dans lequel le dispositif de commande de source est conçu pour rendre la polarité des potentiels électriques de signal de données pour le premier groupe (Gr1) différente de celle pour le deuxième groupe (Gr2) et de la polarité du potentiel électrique de signal fictif ; et

caractérisé en ce que

le dispositif de commande de grille est conçu pour rendre une période de temps (T) d'un instant auquel une impulsion de balayage (GP12) correspondant à la dernière période de balayage horizontal (H 12) pour le premier groupe (Gr1) devient non active jusqu'à un instant auquel la période de balayage fictive (HX) est débutée plus longue qu'une période de temps (t) d'un instant auquel une impulsion de balayage (GP11) correspondant à une première période (H11) de deux périodes de balayage horizontal consécutives (H11, H12) pour le premier groupe (Gr1) devient non active jusqu'à un instant auquel une période suivante (H 12) des deux périodes de balayage horizontal consécutives (H11, H12) est débutée.

9. Dispositif d'affichage à cristaux selon la revendication 8, comprenant une pluralité de pixels constitués chacun d'une pluralité de sous-pixels.
10. Dispositif d'affichage à cristaux liquides selon la revendication 9, dans lequel la pluralité de sous-pixels comprennent des électrodes de pixel respectives ; le dispositif d'affichage à cristaux comprend des lignes de condensateur de maintien qui sont prévues pour les électrodes de pixel respectives ; et dans lequel le dispositif d'affichage à cristaux liquides est conçu pour commander une luminance de chacun de la pluralité de sous-pixels en réponse à un signal de ligne de condensateur de maintien appliqué à l'une correspondante des lignes de condensateur de maintien.

11. Afficheur à cristaux liquides selon l'une des revendications 8 à 10, dans lequel l'afficheur à cristaux liquides est conçu pour effectuer les étapes de l'une des revendications 1 à 7.

5

10

15

20

25

30

35

40

45

50

55

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19






FIG. 20


ADEQUATE DISPLAY
(TWO PIXELS)



CONVENTIONAL DISPLAY
(TWO PIXELS)



CONVENTIONAL DISPLAY
(WHOLE)



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 2001051252 A [0003]
- US 20060041805 A1 [0004]

专利名称(译)	液晶显示装置，用于驱动液晶显示装置的方法和TV接收器		
公开(公告)号	EP2337015B1	公开(公告)日	2015-11-11
申请号	EP2009817572	申请日	2009-07-24
[标]申请(专利权)人(译)	夏普株式会社		
申请(专利权)人(译)	夏普株式会社		
当前申请(专利权)人(译)	夏普株式会社		
[标]发明人	IRIE KENTAROH SHIMOSHIKIRYOH FUMIKAZU KAWABATA MASAE		
发明人	IRIE, KENTAROH SHIMOSHIKIRYOH, FUMIKAZU KAWABATA, MASAE		
IPC分类号	G09G3/36 G02F1/133 G09G3/20		
CPC分类号	G09G3/3614 G09G2310/0205 G09G2310/0248 G09G2310/04 G09G2320/0209 G09G2320/0219		
优先权	2008258724 2008-10-03 JP		
其他公开文献	EP2337015A1 EP2337015A4		
外部链接	Espacenet		

摘要(译)

依次选择多个组，每个组包括多条扫描信号线;将顺序选择的组中的一个（第一组）中的数据信号电位的极性设置为与两个组中的另一个（第二组）的极性不同;两个虚拟扫描周期（HX和HY）被置于（i）对应于第一组中的最后一个水平扫描的水平扫描周期（H12）和（ii）对应于a的水平扫描周期（H13）之间。第二组中的第一次水平扫描;虚拟信号电位在虚拟扫描周期中提供给数据信号线;从与第一组中的最后一次水平扫描相对应的扫描脉冲（GP12）变为无效的时间到开始虚拟扫描周期（HX）时的时间段（T）被设定为长于时间段（t）从对应于连续两个水平扫描中的一个（H11）的扫描脉冲（GP11）在第一组中变为非有效时到当开始对应于连续两个水平扫描中的另一个的水平扫描时段（H12）时。这使得可以在数据信号线经历块反转驱动的情况下提高显示质量。

FIG. 1

