



(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
11.05.2011 Bulletin 2011/19

(51) Int Cl.:
G02F 1/1343 ^(2006.01) **G02F 1/1333** ^(2006.01)
G02F 1/1337 ^(2006.01)

(21) Application number: **09804696.4**

(86) International application number:
PCT/JP2009/003640

(22) Date of filing: **31.07.2009**

(87) International publication number:
WO 2010/016209 (11.02.2010 Gazette 2010/06)

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR
Designated Extension States:
AL BA RS

(72) Inventors:
• **YOSHIDA, Hiroshi**
Osaka-shi, Osaka 545-8522 (JP)
• **TASAKA, Yasutoshi**
Osaka-shi, Osaka 545-8522 (JP)
• **KAISE, Yasuyoshi**
Osaka-shi, Osaka 545-8522 (JP)


(30) Priority: **04.08.2008 JP 2008201116**

(74) Representative: **Müller - Hoffmann & Partner**
Patentanwälte
Innere Wiener Strasse 17
81667 München (DE)

(71) Applicant: **Sharp Kabushiki Kaisha**
Osaka-shi, Osaka 545-8522 (JP)

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

(57) A liquid crystal display device of a high image quality is provided in which occurrence of a leakage current between pixel electrodes is prevented. A liquid crystal display device of the present invention has a plurality of pixels **10**, including a first pixel **10a** and a second pixel **10b** which are side by side along the first direction. The liquid crystal display device includes: a first substrate **60** which includes a first electrode **20a** provided in the first pixel **10a** and a second electrode **20b** provided in the second pixel **10b**; a second substrate **70** which is arranged so as to oppose the first substrate **60**; and a liquid crystal layer **80** interposed between the first substrate **60** and the second substrate **70**. The first electrode **20a** includes a plurality of first branch portions **30a** extending toward the second pixel **10b**. The second electrode **20b** includes a plurality of second branch portions **30b** extending toward the first pixel **10a** side. When viewed along the first direction, at least part of the end portions of the plurality of first branch portions **30a** faces to a gap between end portions of two of the plurality of second branch portions **30b**.



Description**TECHNICAL FIELD**

5 **[0001]** The present invention relates to a liquid crystal display device and specifically to a liquid crystal display device which has a liquid crystal alignment control structure in a pixel.

BACKGROUND ART

10 **[0002]** As of now, liquid crystal display devices under development which have wide viewing angle characteristics includes liquid crystal display devices utilizing the IPS (In-Plane-Switching) mode which is a transverse electric field mode or the FFS (Fringe Field Switching) mode, and liquid crystal display devices utilizing the VA (Vertical Alignment) mode. The VA mode is better for mass production than the transverse electric field mode and is therefore used in a wide range of TV applications and mobile applications.

15 **[0003]** The VA mode liquid crystal display devices are generally classified into MVA (Multidomain Vertical Alignment) mode liquid crystal display devices, in which one pixel includes a plurality of domains of different liquid crystal alignment directions, and CPA (Continuous Pinwheel Alignment) mode liquid crystal display devices in which the liquid crystal alignment direction continuously varies around a rivet or the like formed on an electrode at the center of a pixel.

20 **[0004]** In the MVA mode liquid crystal display devices, the alignment control means which extend in two mutually-orthogonal directions are provided to form four liquid crystal domains in one pixel, in which the azimuthal angles of the directors representing the liquid crystal domains are 45° relative to the polarization axes (transmission axes) of a pair of polarizing plates in a crossed nicols arrangement. Assuming that the direction of the polarization axis of one of the polarizing plates is azimuthal angle 0° and that the counterclockwise direction is the positive direction, the azimuthal angles of the directors of the four liquid crystal domains are 45°, 135°, 225°, and 315°. Selection of these azimuthal angles of the directors is most preferable in respect of transmittance because linearly-polarized light in the direction of 45° relative to the polarization axis is not absorbed by the polarizing plates. Such a structure which includes four domains in one pixel is referred to as "four-division alignment structure" or simply "4D structure".

25 **[0005]** The MVA mode liquid crystal display devices are not suitable to small pixels (e.g., pixels whose shorter side is less than 100 μm, especially less than 60 μm). For example, when slits (or ribs) are used as the alignment control means, the width of the slits need to be about 10 μm or more in order to obtain a sufficient alignment control force. If the slit width is narrower than this, sufficient alignment control force cannot be obtained. To form four domains, it is necessary to form, in a counter electrode, slits ("<-"-shaped slit) extending in directions different by 90° from each other when seen in a direction normal to the substrate and to form, in a pixel electrode, slits which are separated by a certain space from the counter electrode slits and which extend parallel to the counter electrode slits. Specifically, both the counter electrode and the pixel electrode in one pixel need to have a plurality of slits extending in the direction of 45°-225° and the direction of 135°-315° and having the width of about 10 μm.

30 **[0006]** However, when the above-described slits are applied to pixels whose shorter side is less than 100 μm, the ratio of the area of the slits to the pixel area increases, and accordingly, part of the pixel area which fails to contribute to display increases, so that the transmittance (brightness) significantly decreases. In the case of a small-size liquid crystal display device of finer definition, e.g., 2.4-inch VGA for use in mobile phones, the pixel pitch (row direction×vertical direction) is, for example, 25.5 μm×76.5 μm. In such a small pixel, the above-described slits cannot be formed.

35 **[0007]** In the CPA mode liquid crystal display devices, a rivet is formed of a resin or the like in the counter electrode at the pixel center, such that the rivet and a diagonal electric field produced at an edge of the pixel electrode serve to regulate the alignment of the liquid crystal. Provided in the respective gaps between the two polarizing plates and the liquid crystal layer are 1/4-wave plates (quarter wave plates). By utilizing omniazimuthal, radial slope alignment domains and circular polarization, high transmittance (brightness) can be achieved.

40 **[0008]** The CPA mode which utilizes the 1/4-wave plates achieves high transmittance but disadvantageously provides a low contrast ratio and a narrow viewing angle as compared with the MVA mode. Specifically, when the 1/4-wave plates are used, the display (especially, the display at lower gray levels (lower brightness)) appears brighter, i.e., so-called "whitish dots" are conspicuous, when observed in a diagonal viewing angle than when observed in front of the display surface (when observed in a direction normal to the display surface (viewing angle 0°)).

45 **[0009]** To solve the above problems of the liquid crystal display device in the MVA mode and the CPA mode, liquid crystal display devices as disclosed in Patent Document 1 and Patent Document 2 have been proposed. In the liquid crystal display devices of these patent documents, the four-division alignment structure is realized by forming in the pixel electrodes a large number of narrow slits extending in the direction of 45°-225° and in the direction of 135°-315° (referred to as "fishbone pixel electrode") such that the liquid crystal is aligned parallel to the slits. In liquid crystal display devices which use such fishbone pixel electrodes, large slits or rivets are not formed in pixels, and linearly-polarized light is used without using 1/4-wave plates. Therefore, display can be realized with high transmittance, high contrast ratio, and wide

viewing angle.

[0010] Note that the liquid crystal display devices of these patent documents include alignment sustaining layers on surfaces of the upper and lower substrates on the liquid crystal layer side for making the liquid crystal have an appropriate pretilt angle during absence of voltage application to the liquid crystal. These alignment sustaining layers are formed by polymerizing monomers contained in the liquid crystal layer during application of a voltage to the liquid crystal.

[0011] Liquid crystal display devices other than the above examples which include electrodes having slits are described in Patent Document 3, Patent Document 4, and Patent Document 5.

CITATION LIST

PATENT LITERATURE

[0012]

[Patent Document 1] Japanese Laid-Open Patent Publication No. 2003-149647

[Patent Document 2] Japanese Laid-Open Patent Publication No. 2006-330638

[Patent Document 3] Japanese Laid-Open Patent Publication No. 2003-330028

[Patent Document 4] Japanese Laid-Open Patent Publication No. 2003-322868

[Patent Document 5] Japanese Laid-Open Patent Publication No. 2004-4315

SUMMARY OF INVENTION

TECHNICAL PROBLEM

[0013] FIG. 11 is a diagram showing the shape of typical fishbone pixel electrodes. As shown in FIG. 11, a fishbone pixel electrode **120** (hereinafter, simply referred to as "pixel electrode **120**") includes a plurality of branch portions ("linear electrode portions" or "line portions") **130** extending diagonally to the X direction (the left-to-right direction of the drawing) and the Y direction (the bottom-to-top direction of the drawing) which are the arrangement directions of the pixels **110**. Between any adjacent two of the plurality of branch portions **130**, there is a slit (linear cut) extending parallel to the branch portions **130**, from an edge portion of the pixel electrode **120** to an inner portion of the pixel electrode **120**.

[0014] More specifically, the pixel electrode **120** includes trunk portions **135a** and **135b** extending in the X direction and the Y direction, respectively, and branch portions **130a** and **130c** extending in the 45°-225° direction from the trunk portion **135a** or **135b** and branch portions **130b** and **130d** extending in the 135°-315° direction from the trunk portion **135a** or **135b**.

[0015] Among the pixels **110**, the shape of the pixel electrode **120** is the same. Each pixel electrode **120** has a shape which is symmetric about an axis passing through the center of the pixel electrode **120** and extending in the X direction and an axis passing through the center of the pixel electrode **120** and extending in the Y direction. Therefore, the end portions of branch portions **130** which face each other with the intervention of a boundary area **112** between the two pixel electrodes **120** are at positions which are equal in terms of the Y direction. In other words, when viewed along the X direction, the end portions of the plurality of branch portions **130** of one of the pixel electrodes **120** and the end portions of the plurality of branch portions **130** of the other pixel electrode **120** are arranged so as to face each other with no difference in position.

[0016] In recent years, to perform display of finer definition, further increasing the density of the pixels has been demanded. To perform display with higher luminance, it is necessary to increase the size of the pixel electrode **120** and the pixel aperture as much as possible such that the effective area of the pixel can be increased. Therefore, to perform display with higher luminance or display of finer definition, it is necessary to further decrease the distance between adjacent pixel electrodes **120**. However, when the distance between two adjacent pixel electrodes **120** is decreased, an unnecessary electrically-conductive material, such as the material of the pixel electrodes, may disadvantageously remain between the pixel electrodes in the production process. Thus, there is a concern that the pixel electrodes become electrically conducting due to such a conductive material, so that leakage of a pixel voltage occurs.

[0017] The present invention was conceived in order to solve the above problems. One of the objects of the present invention is to provide a liquid crystal display device in which leakage of a voltage (or a leakage current) between electrodes is less likely to occur, and which is capable of high quality display with high luminance or finer definition.

SOLUTION TO PROBLEM

[0018] A liquid crystal display device of the present invention has a plurality of pixels which are arranged along a first direction and a second direction that is different from the first direction, the plurality of pixels including a first pixel and

a second pixel which is adjacent to the first pixel along the first direction. The liquid crystal display device includes: a first substrate which includes a first electrode provided in the first pixel and a second electrode provided in the second pixel; a second substrate which is arranged so as to oppose the first substrate, the second substrate including a counter electrode; and a liquid crystal layer interposed between the first substrate and the second substrate, wherein the first electrode includes a plurality of first branch portions extending toward the second pixel, the second electrode includes a plurality of second branch portions extending toward the first pixel, and some of the plurality of first branch portions have end portions directed toward an edge of the second electrode and, when viewed along the first direction, at least part of the end portions faces to a gap (the mouth of a slit) between end portions of two of the plurality of second branch portions.

[0019] In one embodiment, some of the plurality of first branch portions have end portions directed toward an edge of the second electrode and, when viewed along the first direction, at least part of every one of the end portions faces to a gap between end portions of two of the plurality of second branch portions.

[0020] In one embodiment, some of the plurality of first branch portions have end portions directed toward an edge of the second electrode and, when viewed along the first direction, an entirety of the end portions faces to a gap between end portions of two of the plurality of second branch portions.

[0021] In one embodiment, a distance between an edge of the first electrode on the second electrode side and an edge of the second electrode on the first electrode side is not more than 5.0 μm and, when viewed along the first direction, an end portion of one of the plurality of first branch portions overlaps an end portion of one of the plurality of second branch portions, and a length of the overlap along the second direction is not more than 2.5 μm .

[0022] In one embodiment, the first electrode includes a first trunk portion extending in the first direction and a second trunk portion extending in the second direction, and the plurality of first branch portions extend from the first trunk portion or the second trunk portion.

[0023] In one embodiment, the first electrode includes a plurality of third branch portions extending from the first trunk portion or the second trunk portion in a direction away from the second pixel, and the first electrode has an asymmetric shape about the second trunk portion that is assumed as a symmetry axis.

[0024] In one embodiment, the first electrode includes a plurality of fourth branch portions extending from the first trunk portion or the second trunk portion in a direction away from the second pixel and a plurality of fifth branch portions extending from the first trunk portion or the second trunk portion toward the second pixel in a direction different from the direction that the first branch portions extend, and the first electrode has an asymmetric shape about the first trunk portion that is assumed as a symmetry axis.

[0025] In one embodiment, the liquid crystal display device is a vertical alignment type liquid crystal display device, the liquid crystal layer includes a liquid crystal of negative dielectric constant anisotropy, and when a voltage is applied across the liquid crystal layer, a plurality of domains among which an alignment direction of the liquid crystal is different are formed according to a shape of the first electrode.

[0026] In one embodiment, the plurality of first branch portions have first widths which are generally equal to one another, and a space between any adjacent two of the plurality of first branch portions is equal to the first width.

[0027] In one embodiment, the plurality of first branch portions have first widths which are generally equal to one another, and a space between any adjacent two of the plurality of first branch portions is different from the first width.

[0028] In one embodiment, a position of an edge of the first electrode in terms of the second direction and a position of an edge of the second electrode in terms of the second direction are different.

[0029] In one embodiment, the first substrate includes a source bus line extending in the second direction, and the first electrode and the second electrode are adjacent to each other with the intervention of the source bus line.

[0030] In one embodiment, the plurality of pixels include a third pixel which is adjacent to the first pixel along the second direction, the first substrate includes a third electrode which is provided in the third pixel, and a position of an edge of the first electrode in terms of the first direction and a position of an edge of the third electrode in terms of the first direction are different.

[0031] In one embodiment, the first substrate includes a gate bus line extending in the first direction, and the first electrode and the third electrode are adjacent to each other with the intervention of the gate bus line.

ADVANTAGEOUS EFFECTS OF INVENTION

[0032] In a liquid crystal display device of the present invention, the end portion of a branch portion (protruding portion) of the electrode of a pixel faces to the end portion of a slit (a cut between two branch portions) of the electrode of an adjacent pixel. Therefore, even when the electrodes are placed near to each other, the distance (or area) between the nearest portions of the electrodes can be decreased. Thus, even when the pixels are arranged with a high density or arranged such that the effective area can be increased, leakage of a current between the electrodes is prevented, so that high quality display with high luminance or fine definition is possible.

BRIEF DESCRIPTION OF DRAWINGS**[0033]**

[FIG. 1] A plan view schematically showing the structure of a liquid crystal display device **1** of an embodiment of the present invention.

[FIG. 2] A schematic cross-sectional view of the liquid crystal display device **1** taken along line **A-A** of FIG. **1**.

[FIG. 3] A plan view showing the shape of pixel electrodes **20** of the liquid crystal display device **1** of embodiment 1.

[FIG. 4] An enlarged view of the shape of two adjacent pixel electrodes **20**, showing a portion in the vicinity of the boundary between the electrodes **20**.

[FIG. 5] **(a)** and **(b)** are variations of the shape of pixel electrodes **20**, showing a portion in the vicinity of their boundary.

[FIG. 6] A plan view showing the shape of the pixel electrodes **20** of the liquid crystal display device **1** of embodiment 2.

[FIG. 7] A plan view schematically showing the shape of the pixel electrodes **20** of the liquid crystal display device **1** of embodiment 3.

[FIG. 8] A plan view schematically showing the shape of the pixel electrodes **20** of the liquid crystal display device **1** of embodiment 4.

[FIG. 9] A plan view schematically showing an arrangement of the pixel electrodes **20** of the liquid crystal display device **1** of embodiment 5.

[FIG. 10] A plan view schematically showing an arrangement of the pixel electrodes **20** of the liquid crystal display device **1** of embodiment 6.

[FIG. 11] A plan view schematically showing the shape of pixel electrodes **120** of a conventional liquid crystal display device.

DESCRIPTION OF EMBODIMENTS

[0034] Hereinafter, the structure of a liquid crystal display device of an embodiment of the present invention is described with reference to the drawings. Note that, however, the present invention is not limited to embodiments which will be described below.

(Embodiment 1)

[0035] FIG. **1** is a plan view schematically showing the structure of a liquid crystal display device **1** of the first embodiment of the present invention. FIG. **2** is a schematic cross-sectional view of the liquid crystal display device **1** taken along line **A-A** of FIG. **1**. Note that, in FIG. **1**, the shape of pixel electrodes **20** is simply represented by a square. A specific shape of the pixel electrodes **20** will be described later with reference to FIG. **3** and other relevant figures.

[0036] The liquid crystal display device **1** is a vertical alignment type (VA type) liquid crystal display device which performs display in a normally-black mode using a plurality of pixels **10** arranged in a display region as shown in FIG. **1**. The plurality of pixels **10** are in a matrix arrangement along the X direction (the left-to-right direction of the drawing) and the Y direction (the bottom-to-top direction of the drawing). The liquid crystal display device **1** includes, as shown in FIG. **2**, a TFT substrate **60** which is an active matrix substrate, a counter substrate **70** which is a color filter substrate, and a liquid crystal layer **80** interposed between these substrates. The liquid crystal layer **80** includes nematic liquid crystal which has negative dielectric constant anisotropy ($\Delta\epsilon < 0$).

[0037] The outer side surface of the TFT substrate **60** (opposite to the liquid crystal layer **80**) is provided with a polarizing plate **69**. The outer side surface of the counter substrate **70** is provided with a polarizing plate **79**. The polarizing plates **69** and **79** are in a crossed nicols arrangement such that the light transmission axis of one of the polarizing plates extends in the X direction, and the light transmission axis of the other extends in the Y direction. In the description below, the azimuthal direction from left to right in FIG. **1** is referred to as "azimuthal direction 0°", relative to which the azimuthal angles are allocated counterclockwise.

[0038] As shown in FIG. **1** and FIG. **2**, the TFT substrate **60** includes a transparent substrate **62**, such as a glass substrate, a gate insulation layer **64** provided on the transparent substrate **62** (on the liquid crystal layer **80** side), an insulation layer (PAS layer) **66** provided on the gate insulation layer **64**, and a resin layer (JAS layer) **67** provided on the insulation layer **66**. The resin layer **67** functions as an insulation layer. Between the transparent substrate **62** and the gate insulation layer **64**, scanning lines (gate bus lines) **14** and unshown storage capacitor lines (Cs lines) are interposed. Between the gate insulation layer **64** and the insulation layer **66**, TFTs **12** and signal lines (data bus lines or source bus lines) **16** are interposed. Over the resin layer **67**, the pixel electrodes **20** are provided, and an alignment film **68** is provided so as to cover the pixel electrodes **20**.

[0039] Each of the pixels **10** is surrounded by two adjacent scanning lines **14** and two adjacent signal lines **16**. Every one of the pixels **10** has the pixel electrode **20** and the TFT **12** for switching the display voltage that is to be supplied to

the pixel electrode **20**. The gate electrode, the source electrode, and the drain electrode of the TFT **12** are electrically coupled to the scan line **14**, the signal line **16**, and the pixel electrode **20**, respectively. The gate electrode is supplied with a gate signal of the TFT **12** from the scan line **14**. The pixel electrode **20** is supplied with a display signal from the signal line **16** via the TFT **12**.

[0040] The counter substrate **70** includes a transparent substrate **72**, a color filter (CF) layer **74** arranged on the transparent substrate **72** (on the liquid crystal layer **80** side), a counter electrode (common electrode) **76** provided on the color filter layer **74**, and an alignment film **78** provided on the counter electrode **76**.

[0041] Each of the alignment film **68** of the TFT substrate **60** and the alignment film **78** of the counter substrate **70** may include an alignment layer and an alignment sustaining layer formed by a polymer structure. The alignment layer is a vertical alignment film formed over the substrate by application. The alignment sustaining layers may be formed, after formation of a liquid crystal cell, by photopolymerizing photopolymerizable monomers contained beforehand in a liquid crystal material while a voltage is applied across the liquid crystal layer **80**. In this process, oblique electric fields produced by application of the voltage according to the shape of the pixel electrodes **20** define the alignment of liquid crystal molecules, and the cell is irradiated with light such that the monomers are polymerized while the defined alignment of the liquid crystal molecules is maintained.

[0042] The thus formed alignment sustaining layers have a function as an alignment control structure. These alignment sustaining layers enable the liquid crystal molecules to sustain (memorize) some orientations (pretilt azimuths) even after removal of the voltage (in the absence of an applied voltage). Such an alignment film formation technique is called PSA (Polymer Sustained Alignment) technique.

[0043] Next, the shape of the pixel electrodes **20** of the liquid crystal display device **1** is described with reference to FIG. **3** and FIG. **4**. FIG. **3** is a schematic diagram mainly illustrating the shape of the pixel electrodes **20a** and **20b** of two of the plurality of pixels **10** shown in FIG. **1**, pixels **10a** and **10b**, which are side by side along the X direction with the intervention of the signal line **16**. FIG. **4** is an enlarged view of a boundary portion **S1** extending between the pixel electrodes **20a** and **20b** shown in FIG. **3**. In embodiment 1, all the pixel electrodes **20** have the same shape.

[0044] As shown in FIG. **3**, each of the pixel electrodes **20** includes a trunk portion **35a** extending in the direction of azimuthal angle 0°-180° ("X direction" or "first direction"), a trunk portion **35b** extending in the direction of azimuthal angle 90°-270° ("Y direction" or "second direction"), and a plurality of branch portions **30** extending diagonally to these directions. The plurality of branch portions **30** include a plurality of branch portions **30a** and a plurality of branch portions **30c** extending in the direction of azimuthal angle 45°-225° and a plurality of branch portions **30b** and a plurality of branch portions **30d** extending in the direction of azimuthal angle 135°-315°. The branch portions **30a**, **30b**, **30c**, and **30d** branch off from the trunk portion **35a** or **35b** and extend in the directions of azimuthal angles 45°, 135°, 225°, and 315°.

[0045] Between any adjacent two of the plurality of branch portions **30a**, there is a slit (linear cut) **32** extending parallel to the branch portions **30**, from an edge portion of the pixel electrode **20** to an inner portion of the pixel electrode **20**. More specifically, there are a slit **32a** provided between any adjacent two of the plurality of branch portions **30a**, a slit **32b** provided between any adjacent two of the plurality of branch portions **30b**, a slit **32c** provided between any adjacent two of the plurality of branch portions **30c**, and a slit **32d** provided between any adjacent two of the plurality of branch portions **30d**.

[0046] The width of each branch portion **30** (the dimension perpendicular to the direction of extension of the branch portion **30**: d_r in FIG. **4**) is 3.0 μm . The width of each slit **32** (the dimension perpendicular to the direction of extension of the slit **32**: d_s in FIG. **4**) is also 3.0 μm . As the width of the branch portion **30** and the width of the slit **32** decrease, the liquid crystal is more readily aligned along the branch portion **30**, so that brighter display can be obtained. Therefore, the width of the branch portion **30** and the width of the slit **32** are preferably not more than 3.5 μm . More preferably, the width of the branch portion **30** and the width of the slit **32** are not less than 1.0 μm and not more than 3.5 μm . Note that the widths d_r of the respective branch portions **30** are substantially equal, and the widths d_s of the respective slits are also substantially equal. The width d_r of the branch portion **30** and the width d_s of the slit may be substantially equal to each other or may be different from each other.

[0047] By the pixel electrode **20** having the above-described shape and the alignment films **68** and **78**, a multidomain of 4D structure is formed in each of the pixels **10**. When no voltage is applied, the pretilt azimuths of the liquid crystal molecules in the four domains are parallel to the branch portions **30a**, **30b**, **30c**, and **30d** in accordance with the azimuths memorized in the alignment films **68** and **78**. When a voltage is applied, the liquid crystal molecules of the four domains are oriented in polar angle directions whose azimuthal directions are parallel to the branch portions **30a**, **30b**, **30c**, and **30d** (the azimuths of the directors of the domains) and which are more parallel to the substrate surface. In this case, the azimuths of the orientation are coincident with the azimuths of the pretilt, and therefore, the orientation in correct azimuths with an extremely high response rate is realized.

[0048] Hereinafter, the shape of the pixel electrodes **20** is described more specifically.

[0049] The shape of the pixel electrode **20** is asymmetric about the trunk portion **35a** that is assumed as the symmetry axis and is also asymmetric about the trunk portion **35b** that is assumed as the symmetry axis. Specifically, the positions of connecting portions of the branch portion **30a** and the branch portion **30d** with the trunk-portion **35a** (**D1** and **D2** in

FIG. 3) are different in terms of the X direction. Also, the positions of connecting portions of the branch portion **30b** and the branch portion **30c** with the trunk portion **35a** are different in terms of the X direction. Meanwhile, the positions of connecting portions of the branch portion **30a** and the branch portion **30b** with the trunk portion **35b** (**D3** and **D4** in FIG. 3) are different in terms of the Y direction. Also, the positions of connecting portions of the branch portion **30c** and the branch portion **30d** with the trunk portion **35b** are different in terms of the Y direction.

[0050] Thus, the positions of the end portions of the branch portion **30a** and the branch portion **30d** (**D5** or **D9**, and **D6**) are different in terms of the X direction. Also, the positions of the end portions of the branch portion **30b** and the branch portion **30c** are different in terms of the X direction. Meanwhile, the positions of the end portions of the branch portion **30a** and the branch portion **30b** (**D7** and **D8**) are different in terms of the Y direction. Also, the positions of the end portions of the branch portion **30c** and the branch portion **30d** are different in terms of the Y direction.

[0051] The branch portions **30a** and **30d** of the pixel electrode **20a** extend from an inner portion of the pixel electrode **20a** toward the pixel electrode **20b**. The branch portions **30b** and **30c** of the pixel electrode **20b** extend from an inner portion of the pixel electrode **20b** toward the pixel electrode **20a**. When viewed along the X direction, part of the end portion **Er** of the branch portion **30a** of the pixel electrode **20a** faces to the mouth **Es** of the slit **32b** of the pixel electrode **20b** (the gap between the end portions of two branch portions **30**), while the other part faces to the end portion **Er** of the branch portion **30b** of the pixel electrode **20b**. Likewise, when viewed along the X direction, part of the end portion **Er** of the branch portion **30d** of the pixel electrode **20a** faces to the mouth **Es** of the slit **32c** of the pixel electrode **20b**, while the other part faces to the end portion **Er** of the branch portion **30c** of the pixel electrode **20b**. The lengths of **Er** and **Es** (lengths along the Y direction) are preferably not more than 5.0 μm and not less than 1.5 μm .

[0052] As described above, according to the present embodiment, the positions of the end portions of the branch portions **30** of adjacent pixel electrodes **20** are different in terms of the Y direction. When viewed along the X direction, the end portions of the branch portions **30** of adjacent pixel electrodes **20** and the mouths of the slits **32** face each other. Therefore, the distance (or area) between branch portions **30** which face each other is smaller than in the pixel electrodes **120** shown in FIG. 11. Therefore, occurrence of a leakage current between the pixel electrodes is prevented, so that the potential of the pixel voltage can be stably maintained at a desired potential.

[0053] Some of the branch portions **30a** and **30d** of the pixel electrode **20a** have end portions directed toward the left edge of the pixel electrode **20b**. It is preferred that, when viewed along the X direction, at least part of every one of the end portions of these branch portions **30a** and **30d** faces to the mouth of a corresponding one of the slits **32b** and **32c** of the pixel electrode **20b**. This arrangement can effectively prevent occurrence of a leakage current between the pixel electrodes. However, at least part of at least one of the end portions of the branch portions **30a** and **30d** of the pixel electrode **20a** may face to the mouth of the slit **32b** or **32c** of the pixel electrode **20b**. This arrangement can also achieve the effect of reducing occurrence of a leakage current to some extent.

[0054] The distance between the pixel electrodes **20a** and **20b**, i.e., the distance along the X direction between the end portion of the branch portion **30a** of the pixel electrode **20a** and the end portion of the branch portion **30b** of the pixel electrode **20b**, **d2** in FIG. 4, is preferably not more than 5.0 μm . Preferably, the length along the Y direction of an overlapping part of the end portion of the branch portion **30a** of the pixel electrode **20a** and the end portion of the branch portion **30b** of the pixel electrode **20b** which overlap each other when viewed along the X direction, **d1** in FIG. 4, is not more than 2.5 μm . By employing such distances for **d1** and **d2**, high density arrangement of the pixels **10** and prevention of occurrence of a leakage current between the pixel electrodes can be realized. Note that **d1** may be considered as the distance along the Y direction between the upper corner of the end portion of the branch portion **30a** of the pixel electrode **20a** and the lower corner of the end portion of the branch portion **30b** of the pixel electrode **20b** which is adjacent to the branch portion **30a**. To reduce the leakage current so as to be equal to or smaller than half of that which would occur in the conventional structure, **d2** is preferably not more than 2.5 μm .

[0055] FIGS. 5(a) and 5(b) respectively show the first and second variations of the pixel electrode **20** of embodiment 1, corresponding to the region **S1** of FIG. 3.

[0056] As shown in FIG. 5(a), in the pixel electrode **20** of the first variation, the slit **32** has the width **ds** which is larger than the width **dr** of the branch portion **30**. When viewed along the X direction, the entirety of the end portion **Er** of the branch portion **30a** of the pixel electrode **20a** faces to the mouth **Es** of the slit **32b** of the pixel electrode **20b**. This also applies to the relationship between the branch portion **30d** of the pixel electrode **20a** and the slit **32c** of the pixel electrode **20b**.

[0057] When the pixel electrodes **20** have such a shape, the distance between adjacent pixel electrodes **20** is larger than in the pixel electrodes **120** shown in FIG. 11 and the pixel electrodes **20** shown in FIG. 4. Therefore, occurrence of a leakage current can be more readily prevented.

[0058] The pixel electrode **20** of the second variation shown in FIG. 5(b) is different from the configuration shown in FIG. 3 in the shape of the end portion of the branch portion **30**. In this example, the end portion of the branch portion **30** has an edge which is perpendicular to the direction of extension of the branch portion **30**. Another variation is possible in which the end portion of the branch portion **30** has an edge which is not perpendicular to the direction of extension of the branch portion **30**.

[0059] In such a variation, the distance along the Y direction between the upper corner of the end portion of the branch portion **30a** of the pixel electrode **20a** and the lower corner of the end portion of the branch portion **30b** of the pixel electrode **20b** which is adjacent to the branch portion **30a**, d1, is preferably not more than 2.5 μm . The shortest distance between the end portions of the branch portion **30a** of the pixel electrode **20a** and the branch portion **30b** of the pixel electrode **20b** which is adjacent to the branch portion **30a**, d2, is preferably not more than 5.0 μm .

[0060] In the second variation, the distance between the corners of adjacent branch portions **30a** and **30b**, d3 in FIG. 5(b), is larger than in the conventional pixel electrodes. Therefore, a leakage current between the pixel electrodes can be prevented. Note that such a shape of the end portion of the branch portion **30** is applicable to embodiments which will be described below.

[0061] In the liquid crystal display device **1** of embodiment 1, as shown in FIG. 1 and FIG. 3, a pixel **10c**, which is adjacent to the pixel **10a** along the Y direction with the intervention of the scan line **14**, includes a pixel electrode **20c** which have the same shape as the pixel electrodes **20a** and **20b**. The relationship between the branch portion **30c** of the pixel electrode **20a** and the branch portion **30b** of the pixel electrode **20c** and the relationship between the branch portion **30d** of the pixel electrode **20a** and the branch portion **30a** of the pixel electrode **20c** are equivalent to the relationship between the branch portions **30** of the pixel electrodes **20a** and **20b** as shown in FIG. 4 and FIG. 5. The end portions of the branch portions are arranged at positions which are different when viewed along the Y direction, without being at the same position. Thus, occurrence of a leakage current between the pixel electrodes **20a** and **20c** is also prevented.

(Embodiment 2)

[0062] Next, a liquid crystal display device of the second embodiment of the present invention is described.

[0063] The liquid crystal display device of embodiment 2 is different from the liquid crystal display device **1** of embodiment 1 in that the pixel electrode **20** is replaced by another pixel electrode **20** of a different fishbone shape, and the other elements are basically the same as those of embodiment 1. Therefore, only the shape of the pixel electrode **20** is described below.

[0064] FIG. 6 is a plan view schematically showing the shape of the pixel electrodes **20a** and **20b** of two adjacent ones of the plurality of pixels **10** arranged in the liquid crystal display device of embodiment 2 (the pixels **10a** and **10b** of FIG. 1). As shown in FIG. 6, in embodiment 2, each of the pixel electrode **20a** and the pixel electrode **20b** has a symmetric shape about the central axes of the trunk portion **35a** and the trunk portion **35b**. The shapes of the pixel electrodes **20a** and **20b** are different from each other such that the shape of the pixel electrode **20a** is equal to that obtained by replacing the branch portions **30** and the slits **32** with each other in the pixel electrode **20b**. In the liquid crystal display device of embodiment 2, the pixel electrodes **20** of any adjacent two pixels **10** which are side by side along the X direction or the Y direction have such different shapes of the pixel electrodes **20a** and **20b**.

[0065] Thus, when viewed along the X direction, the end portions of the branch portions **30a** and **30d** of the pixel electrode **20a** respectively face to the mouths of the slits **32b** and **32c** of the pixel electrode **20b**. Meanwhile, although not shown in FIG. 6, a pixel electrode **20** of a pixel **10** which is adjacent to the pixel **10a** along the Y direction also has the same shape as that of the pixel electrode **20b**. Thus, when viewed along the Y direction, the end portions of the branch portions **30a** and **30b** of the pixel electrode **20a** face to the mouths of the slits **32d** and **32c** of another pixel electrode **20** which is adjacent to the pixel electrode **20a** along the Y direction. By employing the pixel electrodes **20** of such shapes, occurrence of a leakage current between the pixel electrodes can effectively be prevented as in embodiment 1.

[0066] The width of the branch portion **30** or the slit **32** in one of the pixel electrodes **20** may be changed such that part of the end portion of the branch portion **30** of the pixel electrode **20a** faces to the mouth of the slit **32** of the pixel electrode **20b** while the other part faces to the end portion of the branch portion **30** of the pixel electrode **20b**. This arrangement can also achieve the effect of reducing occurrence of a leakage current.

(Embodiment 3)

[0067] Next, a liquid crystal display device of the third embodiment of the present invention is described.

[0068] The liquid crystal display device of embodiment 3 is different from the liquid crystal display device **1** of embodiment 1 in that the pixel electrode **20** is replaced by a different pixel electrode **20** which has a shape as shown in FIG. 7, and the other elements are basically the same as those of embodiment 1. Therefore, only the shape of the pixel electrode **20** is described below.

[0069] FIG. 7 is a plan view schematically showing the shape of the pixel electrodes **20a** and **20b** of any two of the plurality of pixels **10** of the liquid crystal display device of embodiment 3 which are side by side along the X direction (corresponding to the pixels **10a** and **10b** of FIG. 1). As shown in FIG. 7, in embodiment 3, each of the pixel electrode **20a** and the pixel electrode **20b** includes a plurality of branch portions **30** extending in the X direction and a plurality of

slits 32 each of which is interposed between adjacent two of the plurality of branch portions 30. Note that, however, the position of the branch portion 30 of the pixel electrode 20a in terms of the Y direction is different from the position of the branch portion 30 of the pixel electrode 20b in terms of the Y direction. The end portion of the branch portion 30 of the pixel electrode 20a faces to the mouth of a slit of the pixel electrode 20b. This arrangement can effectively prevent occurrence of a leakage current between the pixel electrodes.

[0070] Note that, in each of the pixel electrodes 20a and 20b, the plurality of branch portions 30 are electrically coupled by an unshown connector. The connector is provided in part of the pixel electrode 20 excluding the perimeter portion, preferably about the middle of the pixel electrode 20 in terms of the X direction. The plurality of branch portions 30 may be electrically coupled via a contact hole formed in an underlying insulation layer.

[0071] The width of the branch portion 30 or the slit 32 in one of the pixel electrodes 20 may be changed such that part of the end portion of the branch portion 30 of the pixel electrode 20a faces to the mouth of the slit 32 of the pixel electrode 20b while the other part faces to the end portion of the branch portion 30 of the pixel electrode 20b. This arrangement can also achieve the effect of reducing occurrence of a leakage current.

[0072] Although, in the embodiment shown in FIG. 7, the branch portions 30 of the pixel electrode 20a and the pixel electrode 20b extend in the X direction, the branch portions 30 may extend in the Y direction. In this case, the pixel electrode 20a and the pixel electrode 20b are side by side along the Y direction and, when viewed along the Y direction, the end portion of the branch portion 30 of the pixel electrode 20a faces to the mouth of the slit of the pixel electrode 20b.

(Embodiment 4)

[0073] Next, a liquid crystal display device of the fourth embodiment of the present invention is described.

[0074] The liquid crystal display device of embodiment 4 is different from the liquid crystal display device 1 of embodiment 1 in that the pixel electrode 20 is replaced by a different pixel electrode 20 which has a shape as shown in FIG. 8, and the other elements are basically the same as those of embodiment 1. Therefore, only the shape of the pixel electrode 20 is described below.

[0075] FIG. 8 is a plan view schematically showing the shape of the pixel electrodes 20a and 20b of any two of the plurality of pixels 10 of the liquid crystal display device of embodiment 4 which are side by side along the X direction (corresponding to the pixels 10a and 10b of FIG. 1). As shown in FIG. 8, in embodiment 4, each of the pixel electrode 20a and the pixel electrode 20b includes a plurality of slits 32, each of which is cut into the electrode along the X direction or the Y direction from the edges of the electrode. Part of the electrode which is interposed between adjacent two of the plurality of slits 32 forms a branch portion 30 of the pixel electrode 20.

[0076] In the vicinity of the boundary between the pixel electrode 20a and the pixel electrode 20b, the position of the branch portion 30 of the pixel electrode 20a in terms of the Y direction is different from the position of the branch portion 30 of the pixel electrode 20b in terms of the Y direction. The end portion of the branch portion 30 of the pixel electrode 20a faces to the mouth of the slit of the pixel electrode 20b. This arrangement can effectively prevent occurrence of a leakage current between the pixel electrodes. In this arrangement, the ratio of the area of the pixel electrode which does not include the branch portions 30 and the slits 32 (the area enclosed by broken line L2 in FIG. 8) to the area of a pixel electrode region which includes the slits 32 (the area enclosed by broken line L1 in FIG. 8) is preferably 50% or higher. When a pixel electrode which does not include the branch portion 30 or the slit 32, disturbance would occur in the alignment of the liquid crystal due to the effects of the bus line potential, for example. However, by employing the above-described structure of the present embodiment, the effects of the bus line potential can be decreased so that the alignment of the liquid crystal can be stabilized.

[0077] Although not shown, the neighboring pixels 10 at the top and the bottom of the pixel electrode 20a include pixel electrodes 20 which have the same shape as that of the pixel electrode 20b. In the vicinity of the borders with the neighboring pixel electrodes 20 at the top and the bottom, the position of the branch portion 30 of the pixel electrode 20a in terms of the X direction is different from the positions of the branch portions 30 of the neighboring pixel electrodes 20 at the top and the bottom in terms of the X direction. The end portions of the branch portions 30 of the pixel electrode 20a face to the mouths of the slits of the neighboring pixel electrodes 20 at the top and the bottom. This arrangement can effectively prevent occurrence of a leakage current between the pixel electrodes.

[0078] The width of the branch portion 30 or the slit 32 in one of the pixel electrodes 20 may be changed such that part of the end portions of the branch portions 30 of the pixel electrode 20a faces to the mouths of the slits 32 of the neighboring pixel electrodes 20 on the top side and the bottom side and on the right side and the left side while the other part faces to the end portions of the branch portions 30 of the neighboring pixel electrodes 20. This arrangement can also prevent occurrence of a leakage current.

(Embodiment 5)

[0079] Next, a liquid crystal display device of the fifth embodiment of the present invention is described. The liquid

crystal display device of embodiment 5 is different from the liquid crystal display device **1** of embodiment 1 in that the arrangement of the plurality of pixel electrodes **20** is replaced by a different arrangement as shown in FIG. **9**. The pixel electrodes **20** have substantially equal shapes. The shape of each of the pixel electrodes **20** may be the same as any of the pixel electrodes **20a** or any of the pixel electrodes **20b** of embodiments 1 to 4. The other elements are basically

the same as those of embodiment 1. Therefore, only the arrangement pattern of the pixel electrodes **20** is described below. **[0080]** FIG. **9** is a plan view showing an arrangement of the pixel electrodes **20** in a liquid crystal display device of embodiment 5. The pixels **10a** to **10d** shown in FIG. **9** represent four pixels **10** which are adjacent to one another in the liquid crystal display device of embodiment 5. The pixels **10a** to **10d** include pixel electrodes **20a** to **20d**, respectively.

[0081] As shown in FIG. **9**, the pixel electrodes **20a** and **20b** which are side by side along the X direction are arranged such that the positions of their edges in terms of the Y direction (the position of the upper edge and the position of the lower edge) are different by distance d_4 . Likewise, the pixel electrodes **20c** and **20d** which are side by side along the X direction are arranged such that the positions of their edges in terms of the Y direction are different by distance d_4 . Here, the length of the end portion of the branch portion **30** of the pixel electrode **20** along the Y direction (for example, length **Er** in FIG. **4**) is preferably not more than $5.0\ \mu\text{m}$ and not less than $1.5\ \mu\text{m}$. The length of the end portion of the slit **32** along the Y direction (for example, length **Es** in FIG. **4**) is preferably not more than $5.0\ \mu\text{m}$ and not less than $1.5\ \mu\text{m}$. It is also preferred that distance d_4 is approximately equal to length **Er** or length **Es** (not more than $5.0\ \mu\text{m}$ and not less than $1.5\ \mu\text{m}$).

[0082] In this way, by arranging two pixel electrodes **20** which are side by side along the X direction such that the positions of their edges in terms of the Y direction are different, the end portions of the branch portions **30** of the pixel electrodes **20a** and **20c** face to the mouths of the slits **32** of the pixel electrodes **20b** and **20d** in the vicinity of the boundary between these pixel electrodes. This arrangement can effectively prevent occurrence of a leakage current between the pixel electrodes. Note that, in the present embodiment, two pixel electrodes which are side by side along the Y direction (e.g., **20a** and **20c**) are arranged such that the positions of their edges in terms of the X direction are equal, although the edge positions of these pixel electrodes in terms of the X direction may be different.

(Embodiment 6)

[0083] Next, a liquid crystal display device of the sixth embodiment of the present invention is described. The liquid crystal display device of embodiment 6 is different from the liquid crystal display device **1** of embodiment 1 in that the arrangement of the plurality of pixel electrodes **20** is replaced by a different arrangement as shown in FIG. **10**. The pixel electrodes **20** have substantially equal shapes. The shape of each of the pixel electrodes **20** may be the same as any of the pixel electrodes **20a** or any of the pixel electrodes **20b** of embodiments 1 to 4. The other elements are basically the same as those of embodiment 1. Therefore, only the arrangement pattern of the pixel electrodes **20** is described below.

[0084] FIG. **10** is a plan view showing an arrangement of the pixel electrodes **20** in a liquid crystal display device of embodiment 6. The pixels **10a** to **10d** shown in FIG. **10** represent four pixels **10** which are adjacent to one another in the liquid crystal display device of embodiment 6. The pixels **10a** to **10d** include pixel electrodes **20a** to **20d**, respectively.

[0085] As shown in FIG. **10**, the pixel electrodes **20a** and **20c** which are side by side along the Y direction are arranged such that the positions of their edges in terms of the X direction (the positions of the right and left edges) are different by distance d_5 . Likewise, the pixel electrodes **20b** and **20d** which are side by side along the Y direction are arranged such that the positions of their edges in terms of the X direction are different by distance d_5 . Here, the length of the end portion of the branch portion **30** of the pixel electrode **20** along the X direction is preferably not more than $5.0\ \mu\text{m}$ and not less than $1.5\ \mu\text{m}$. The length of the end portion of the slit **32** along the X direction is also preferably not more than $5.0\ \mu\text{m}$ and not less than $1.5\ \mu\text{m}$. It is also preferred that distance d_5 is approximately equal to length **Er** or length **Es** (not more than $5.0\ \mu\text{m}$ and not less than $1.5\ \mu\text{m}$).

[0086] In this way, by arranging two pixel electrodes **20** which are side by side along the Y direction such that the positions of their edges in terms of the X direction are different, the end portions of the branch portions **30** of the pixel electrodes **20a** and **20b** face to the mouths of the slits **32** of the pixel electrodes **20c** and **20d** in the vicinity of the boundary between these pixel electrodes. This arrangement can effectively prevent occurrence of a leakage current between the pixel electrodes. Note that, in the present embodiment, the positions of the edges of two pixel electrodes which are side by side along the X direction (e.g., **20a** and **20b**) are equal in terms of the Y direction, although the positions of the edges of these pixel electrodes may be different in terms of the Y direction.

INDUSTRIAL APPLICABILITY

[0087] A liquid crystal display device of the present invention is suitably applicable to liquid crystal display devices for cell phones, PDAs, notebook PCs, display monitors, television receivers, etc.

REFERENCE SIGNS LIST**[0088]**

5	1	liquid crystal display device
	10, 10a, 10b	pixel
	12	TFT
	14	scan line
	16	signal line
10	20, 20a, 20b, 20c, 20d	pixel electrode
	30, 30a, 30b, 30c, 30d	branch portion
	32, 32a, 32b, 32c, 32d	slit
	35a, 35b	trunk portion
	60	TFT substrate
15	62, 72	transparent substrate
	64	gate insulation layer
	66	insulation layer
	67	resin layer
	68, 78	alignment film
20	69, 79	polarizing plate
	70	counter substrate
	74	color filter layer
	76	counter electrode
	80	liquid crystal layer
25	110	pixel
	112	boundary area
	120	pixel electrode
	130, 130a, 130b, 130c, 130d	branch portion
30	135a, 135b	trunk portion

Claims

- 35 1. A liquid crystal display device that has a plurality of pixels which are arranged along a first direction and a second direction that is different from the first direction, the plurality of pixels including a first pixel and a second pixel which is adjacent to the first pixel along the first direction, the liquid crystal display device comprising:

a first substrate which includes a first electrode provided in the first pixel and a second electrode provided in the second pixel;

40 a second substrate which is arranged so as to oppose the first substrate, the second substrate including a counter electrode; and

a liquid crystal layer interposed between the first substrate and the second substrate,

wherein the first electrode includes a plurality of first branch portions extending toward the second pixel, the second electrode includes a plurality of second branch portions extending toward the first pixel, and

45 some of the plurality of first branch portions have end portions directed toward an edge of the second electrode and, when viewed along the first direction, at least part of the end portions faces to a gap between end portions of two of the plurality of second branch portions.
- 50 2. The liquid crystal display device of claim 1, wherein

some of the plurality of first branch portions have end portions directed toward an edge of the second electrode and, when viewed along the first direction, at least part of every one of the end portions faces to a gap between end portions of two of the plurality of second branch portions.
- 55 3. The liquid crystal display device of claim 1 or 2, wherein

some of the plurality of first branch portions have end portions directed toward an edge of the second electrode and, when viewed along the first direction, an entirety of the end portions faces to a gap between end portions of two of the plurality of second branch portions.

4. The liquid crystal display device of any of claims 1 to 3, wherein
a distance between an edge of the first electrode on the second electrode side and an edge of the second electrode
on the first electrode side is not more than 5.0 μm , and
when viewed along the first direction, an end portion of one of the plurality of first branch portions overlaps an end
portion of one of the plurality of second branch portions, and a length of the overlap along the second direction is
not more than 2.5 μm .
5. The liquid crystal display device of any of claims 1 to 4, wherein
the first electrode includes a first trunk portion extending in the first direction and a second trunk portion extending
in the second direction, and
the plurality of first branch portions extend from the first trunk portion or the second trunk portion.
6. The liquid crystal display device of claim 5, wherein
the first electrode includes a plurality of third branch portions extending from the first trunk portion or the second
trunk portion in a direction away from the second pixel, and
the first electrode has an asymmetric shape about the second trunk portion that is assumed as a symmetry axis.
7. The liquid crystal display device of claim 6, wherein
the first electrode includes a plurality of fourth branch portions extending from the first trunk portion or the second
trunk portion in a direction away from the second pixel and a plurality of fifth branch portions extending from the first
trunk portion or the second trunk portion toward the second pixel in a direction different from the direction that the
first branch portions extend, and
the first electrode has an asymmetric shape about the first trunk portion that is assumed as a symmetry axis.
8. The liquid crystal display device of any of claims 1 to 7, wherein
the liquid crystal display device is a vertical alignment type liquid crystal display device,
the liquid crystal layer includes a liquid crystal of negative dielectric constant anisotropy, and
when a voltage is applied across the liquid crystal layer, a plurality of domains among which an alignment direction
of the liquid crystal is different are formed according to a shape of the first electrode.
9. The liquid crystal display device of any of claims 1 to 8, wherein
the plurality of first branch portions have first widths which are generally equal to one another, and
a space between any adjacent two of the plurality of first branch portions is equal to the first width.
10. The liquid crystal display device of any of claims 1 to 8, wherein
the plurality of first branch portions have first widths which are generally equal to one another, and
a space between any adjacent two of the plurality of first branch portions is different from the first width.
11. The liquid crystal display device of any of claims 1 to 9, wherein
a position of an edge of the first electrode in terms of the second direction and a position of an edge of the second
electrode in terms of the second direction are different.
12. The liquid crystal display device of any of claims 1 to 10, wherein
the first substrate includes a source bus line extending in the second direction, and
the first electrode and the second electrode are adjacent to each other with the intervention of the source bus line.
13. The liquid crystal display device of any of claims 1 to 10, wherein
the plurality of pixels include a third pixel which is adjacent to the first pixel along the second direction,
the first substrate includes a third electrode which is provided in the third pixel, and
a position of an edge of the first electrode in terms of the first direction and a position of an edge of the third electrode
in terms of the first direction are different.
14. The liquid crystal display device of claim 13, wherein
the first substrate includes a gate bus line extending in the first direction, and
the first electrode and the third electrode are adjacent to each other with the intervention of the gate bus line.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 11



INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP2009/003640

A. CLASSIFICATION OF SUBJECT MATTER

G02F1/1343(2006.01)i, G02F1/1333(2006.01)i, G02F1/1337(2006.01)i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G02F1/1343, G02F1/1333, G02F1/1337

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Jitsuyo Shinan Koho 1922-1996 Jitsuyo Shinan Toroku Koho 1996-2009

Kokai Jitsuyo Shinan Koho 1971-2009 Toroku Jitsuyo Shinan Koho 1994-2009

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	JP 2003-315800 A (Toshiba Corp.), 06 November, 2003 (06.11.03), Claim 10; Par. No. [0050]; Figs. 1, 7 & US 2005/36085 A1 & TW 225959 B	1-3, 5, 8-14 4, 6, 7

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

25 August, 2009 (25.08.09)

Date of mailing of the international search report

01 September, 2009 (01.09.09)

Name and mailing address of the ISA/
Japanese Patent Office

Authorized officer

Facsimile No.

Telephone No.

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 2003149647 A [0012]
- JP 2006330638 A [0012]
- JP 2003330028 A [0012]
- JP 2003322868 A [0012]
- JP 2004004315 A [0012]

专利名称(译)	液晶显示装置		
公开(公告)号	EP2320269A1	公开(公告)日	2011-05-11
申请号	EP2009804696	申请日	2009-07-31
[标]申请(专利权)人(译)	夏普株式会社		
申请(专利权)人(译)	夏普株式会社		
当前申请(专利权)人(译)	夏普株式会社		
[标]发明人	YOSHIDA HIROSHI TASAKA YASUTOSHI KAISE YASUYOSHI		
发明人	YOSHIDA, HIROSHI TASAKA, YASUTOSHI KAISE, YASUYOSHI		
IPC分类号	G02F1/1343 G02F1/1333 G02F1/1337		
CPC分类号	G02F1/134309 G02F1/133707 G02F1/133753 G02F1/136204 G02F1/1393		
优先权	2008201116 2008-08-04 JP		
其他公开文献	EP2320269A4		
外部链接	Espacenet		

摘要(译)

提供一种高图像质量的液晶显示装置，其中防止在像素电极之间出现漏电流。本发明的液晶显示装置具有多个像素10，包括沿第一方向并排的第一像素10a和第二像素10b。液晶显示装置包括：第一基板60，其包括设置在第一像素10a中的第一电极20a和设置在第二像素10b中的第二电极20b；第二基板70，其布置成与第一基板60相对；第一电极20a包括朝向第二像素10b延伸的多个第一分支部分30a，以及插入在第一基板60和第二基板70之间的液晶层80。第二电极20b包括朝向第一像素10a侧延伸的多个第二分支部分30b。当沿第一方向观察时，多个第一分支部分30a的至少一部分端部面向多个第二分支部分30b中的两个的端部之间的间隙。

