

(19)



(11)

EP 2 485 082 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
27.09.2017 Bulletin 2017/39

(51) Int Cl.:
G02F 1/1333 (2006.01)

(21) Application number: **12154090.0**

(22) Date of filing: **06.02.2012**

(54) **Liquid crystal display device**

Flüssigkristallanzeigevorrichtung

Dispositif d'affichage à cristaux liquides

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(30) Priority: **07.02.2011 JP 2011023917**

(43) Date of publication of application:
08.08.2012 Bulletin 2012/32

(73) Proprietor: **Japan Display Inc.
Tokyo 105-0003 (JP)**

(72) Inventors:
• **Harayama, Takeshi
Chiba, 297-8622 (JP)**
• **Yoshimoto, Takashi
Chiba, 297-8622 (JP)**

- **Ishii, Katsuhiko
Chiba, 297-8622 (JP)**
- **Kobayashi, Setsuo
Chiba, 297-8622 (JP)**
- **Ishii, Akira
Chiba, 297-8622 (JP)**
- **Tanabe, Shinji
Chiba, 297-8622 (JP)**
- **Sento, Kiyoshi
Chiba, 297-8622 (JP)**

(74) Representative: **Beetz & Partner mbB
Patentanwälte
Steinsdorfstraße 10
80538 München (DE)**

(56) References cited:
**US-A1- 2005 151 899 US-A1- 2008 153 377
US-A1- 2010 231 821 US-A1- 2010 245 707**

EP 2 485 082 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

FIELD OF THE INVENTION

[0001] The present invention relates to a liquid crystal display device and particularly to a technique for improving the strength and visibility of a miniature display device for use in a digital still camera, a cell phone, etc. A liquid crystal display device as described in the preamble portion of patent claim 1 has been known from US 2005/151899 A1.

BACKGROUND OF THE INVENTION

[0002] In a liquid crystal display device, a TFT substrate over which pixel electrodes and thin-film transistors (TFTs), inter alia, are formed in a matrix and an opposing substrate over which color filters, inter alia, are formed in positions corresponding to the pixel electrodes in the TFT substrate are placed facing each other and liquid crystals are sandwiched between the TFT substrate and the opposing substrate. An image is produced by controlling light transmissibility through liquid crystal molecules pixel by pixel.

[0003] An upper polarizing plate is attached to the upper surface of the opposing substrate and the upper polarizing plate is prone to damage because it is made of resin. As a countermeasure against this, a front window made of glass is often put over the opposing substrate. An arrangement is used in which the front window is positioned apart from the liquid crystal display panel in order to provide mechanical protection for the liquid crystal display panel, as shown in Fig. 8.

[0004] In the case of related art as typified in Fig. 8, a problem of ghost image appearance arises. Fig. 8 is an explanatory diagram about ghost image appearance, taking a reflective liquid crystal display panel as an example. In Fig. 8, an incoming external light beam L passes through the front window 30 and is reflected by the liquid crystal display panel. After passing back through the front window 30 again, it enters a human eye. Although the external light beam L is refracted by the front window 30, this refraction is here ignored in Fig. 8.

[0005] A part of the light beam reflected at a point P1 on the front surface of the liquid crystal display panel is reflected back by the undersurface Q1 of the front window 30 and comes at and is reflected again by a point P2 on the front surface of the liquid crystal display panel. When the human views the light beam reflected by the point P2, the phenomenon of ghost image appearance takes place. Although Fig. 8 explains ghost image appearance taking the reflective liquid crystal display panel as an example, this is also true for a transmissive type. That is, in the transmissive type, when a light beam transmitted through the liquid crystal display panel travels at the same angle as the light beam reflected at the point P1 on the front surface of the liquid crystal display panel, it is reflected back by the undersurface Q1 of the front window

30 and follows the same path as shown for the reflective type. This phenomenon of ghost image appearance deteriorates image quality.

[0006] Another problem that is encountered by a liquid crystal display panel is that light is reflected from the edge faces of the TFT substrate 10 and the opposing substrate 20 and radiated from the display region, which degrades the contrast of the screen. To take a countermeasure against this problem, "Japanese Published Unexamined Patent Application No. 2003-5160" discloses an arrangement in which the edge faces of the TFT substrate 10 and the opposing substrate 20 are shielded from light to prevent light reflection from the edge faces. In "Japanese Published Unexamined Patent Application No. 2003-5160", however, there is no disclosure about the front window and there is no description about light leakage in the margins of the screen due to the front window.

[0007] US 2005/151899 A1 discloses a liquid crystal display device comprising a liquid crystal display panel that includes a TFT substrate having a matrix arrangement of pixel electrodes and TFTs for controlling signals to the pixel electrodes and an opposing substrate having color filters formed corresponding to the pixel electrodes, the TFT substrate being formed larger than the opposing substrate and a terminal section being formed in a portion where the opposing substrate does not extend over the TFT substrate.

SUMMARY OF THE INVENTION

[0008] In order to solve the problem discussed with respect to Fig. 8, it is advisable to bond the front window 30 and the opposing substrate 20 with a bonding material having the same degree of refractive index as glass. Fig. 7 is a cross-sectional view representing a liquid crystal display panel having such a structure. In Fig. 7, a liquid crystal layer 100 is sandwiched between the TFT substrate 10 and the opposing substrate 20, and the edges of the liquid crystal layer are sealed by a sealing material 15. A black matrix 22 is formed in the opposing substrate 20. In frame-like portions occupied by the sealing material 15, the black matrix 22 is not formed to prevent peel-off of the sealing material 15. In the portions where no black matrix is formed, the light of a backlight may leak into the front surface. A lower polarizing plate 11 is attached to the TFT substrate 10, while an upper polarizing plate 21 is attached to the opposing substrate 20. A backlight 200 is located under the TFT substrate 10. The backlight 200 and the liquid crystal display panel are accommodated in a bottom frame 120 made of a metal.

[0009] The upper polarizing plate 21 and the front window 30 are bonded with a bonding material 40 which is an UV (ultraviolet) curable resin. The front window 30 is provided with a light shielding print 32 in its margins to block out light from its periphery. Moreover, in order to block out light from outside the edges of the front window 30, a light shielding tape 60 shaped for marginal edges is placed in the periphery of the front window 30. In spite

of this structure, a light beam from the backlight 200 can reach the margins of the screen, as indicated by an arrow. More specifically, the front window 30 is provided with chamfers 31 in its edges. The bonding material 40 abuts on the chamfered edges 31. Because the refractive index of the bonding material 40 is nearly equal to that of glass, incoming light in the chamfered edges 31 reaches the margins of the front window 30 without being reflected and refracted. This transmitted light deteriorates contrast in the margins of the screen.

[0010] Such light that is emitted from the margins of the screen poses no problem, if a viewing angle θ_1 which is shown in Fig. 9 is more or less 60 degrees. Recently, however, there is a demand for a product with a viewing angle θ_2 that is close to 180 degrees, particularly, like a digital still camera (DSC). In such a case, incoming light in the margins of the front window 30, as indicated by the arrow in Fig. 7, poses a problem. Although the polarizing plate 21 is present under the chamfered edges 31, it is difficult to block out leaked light only by the polarizing plate 21.

[0011] In fact, in the structure in which the front window 30 and the liquid crystal display panel are bonded with the bonding material 40, as shown in Fig. 7, a problem is the incoming light through the chamfered edges of the front window 30. In the structure in which the front window 30 is attached to the liquid crystal display panel with the bonding material 40, the present invention is intended to prevent light from the backlight 200 or external light from entering the margins of the front window 30 and to prevent contrast deterioration in the margins of the screen when the viewing angle is wide.

[0012] This object is accomplished, according to the present invention, by a liquid crystal display device having the features of claim 1.

[0013] Dependent claims are directed on features of preferred embodiments of the invention.

[0014] According to the present invention, in a liquid crystal display device having a front window, it is possible to block out light of a backlight that enters the front window through its chamfers. Hence, it is possible to prevent light leakage in the margins of the screen when the screen is viewed obliquely. Thus, a liquid crystal display device that provides a good contrast, even if the screen is viewed from an oblique direction, can be achieved.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015]

Fig. 1 is a plan view of a liquid crystal display device of a first embodiment;

Fig. 2 is a cross-sectional view through line A-A in Fig. 1;

Fig. 3 is a diagram representing a fabrication flow of the liquid crystal display device of the first embodiment;

Fig. 4 is a plan view of a liquid crystal display device

of a second embodiment;

Fig. 5 is a cross-sectional view through line B-B in Fig. 4;

Fig. 6 is a diagram representing a fabrication flow of the liquid crystal display device of the second embodiment;

Fig. 7 is a cross-sectional view representing an example of a conventional liquid crystal display device having a front window;

Fig. 8 is a cross-sectional view of a conventional liquid crystal display device having a front window;

Fig. 9 is a schematic diagram for defining viewing angles; and

Fig. 10 is a cross-sectional view of a liquid crystal display device of an example not falling under the scope of the claims.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0016] Details of the present invention are now disclosed in accordance with exemplary embodiments.

[First Embodiment]

[0017] Fig. 1 is a plan view representing a first embodiment of the present invention and Fig. 2 is a cross-sectional view taken along line A-A in Fig. 1. In Fig. 1, a liquid crystal display panel is formed by a TFT substrate 10 and an opposing substrate 20. A lower polarizing plate 11 is attached to the TFT substrate 10, while an upper polarizing plate 21 is attached to the upper surface of the opposing substrate 20. A backlight 200 is located under the TFT substrate 10. The TFT substrate 10 is formed larger than the opposing substrate 20. A region where the TFT substrate 10 only extends is a terminal section 12 in which an IC driver and other components, which are not shown, are installed.

[0018] On top of the liquid crystal display panel and the upper polarizing plate 21, a front window 30 made of glass is attached. In Fig. 1, the outlines of the front window 30, its three sides with the exception of a side congruent with the terminal section 12 of the liquid crystal display panel, are smaller than the liquid crystal display panel. As explained with regard to Fig. 7, the front window 30 is provided with chamfers 31 through which light from the backlight enters the front window 30. The backlight 200 emits light from the back surface of the liquid crystal display panel toward the front surface and its light source is located near to a first side. The first side is the side where the IC driver is installed and the terminal section 12 is formed. The light source emits light through a lateral side of a light guide plate from the first side toward a second side opposite to the first side. Therefore, this phenomenon is marked particularly at a short side of the front window 30 opposite to the terminal section 12. This embodiment is arranged to block out light from the backlight by laying a light shielding material 50 along the short side

opposite to the terminal section 12. The light shielding material 50 is laid flush with the upper polarizing plate 21. It is impossible to prevent light leakage sufficiently even by attaching a light shielding tape 60 on top of a bonding material 40. Light leakage can be prevented, even if the substrates 10, 20 are made thinner.

[0019] Fig. 2 is a cross-sectional view through line A-A in Fig. 1. In Fig. 2, the liquid crystal display panel that is formed by the TFT substrate 10 and the opposing substrate 20 is the same as explained with regard to Fig. 7 and, therefore, an explanation about the display panel is omitted. Again, the liquid crystal display panel and the backlight 200 are accommodated in the bottom frame 120, which is the same as in Fig. 7. In Fig. 2, the upper polarizing plate 21 is formed smaller than the front window 30. The upper polarizing plate 21 and the light shielding material 50 abut each other such that they are flush with each other. The front window 30 is provided with a light shielding print 32 in its margins. The front window 30 and the upper polarizing plate 21 are bonded with a UV bonding material 40. Because the UV bonding material 40 is fluid before curing, it can extend to cover even the light shielding material 50.

[0020] In Fig. 2, it is distinctive that the bonding material 40 does not abut on the chamfers 31 of the front window 30. Because an air layer is formed between the substrate 20 and the front window 30, leaked light that reaches the chamfers 31 is in part reflected by the boundary faces. In consequence, light leakage directed toward the display surface can be reduced. Another feature of the present invention resides in that the light shielding material 50 layer formed on the upper surface of the opposing substrate 20 in its margin underlies the bonding material 40 layer. Due to this structure, leaked light indicated by the arrow (in Fig. 7) does not reach the bonding material 40. In the display device of Fig. 2, the light shielding material 50 is laid in contact with the upper surface of the opposing substrate 20. Leaked light from the backlight 200, as indicated by the arrow (in Fig. 7), can thus be prevented from being emitted through the upper surface of the opposing substrate 20. Hence, the viewer is unable to see the leaked light and can see an image being displayed satisfactorily. Leaked light is inhibited from entering the chamfered edges 31. For this purpose, the structure may involve tape attachment or print. Because light from the backlight, which is not shown, is blocked out by the light shielding material 50, the light from the backlight is unlikely to reach the chamfers 31 of the front window 30. Even if the light from the backlight reaches the surroundings of the chamfers 31 of the front window 30 through any path, this light is unlikely to enter the front window 30, because the boundary faces of the chamfers 31 are exposed to air, where there is a large difference in refractive index. Hence, no light enters a visual field from the surface of the front window 30.

[0021] In Fig. 2, the front window 30 is 0.8 mm thick and inhibits leaked light from entering the chamfers 31. For this purpose, the structure may involve tape attach-

ment or print. Because light from the backlight, which is not shown, is blocked out by the light shielding material 50, the light from the backlight is unlikely to reach the chamfers 31 of the front window 30. Even if the light from the backlight reaches the surroundings of the chamfers 31 of the front window 30 through any path, this light is unlikely to enter the front window 30, because the boundary faces of the chamfers 31 are exposed to air, where there is a large difference in refractive index. Hence, no light enters a visual field from the surface of the front window 30.

[0022] In Fig. 2, the front window 30 is 0.8 mm thick and a chamfer dimension *c* is about 0.15 mm. As the light shielding material 50, a light shielding tape with an adhesive material can be used. Alternatively, the light shielding material 50 can be formed in required locations by print or the like. In this context, the adhesive material produces adhesiveness by applying pressure thereto and the bonding material is initially liquid and cures under heating or UV irradiation, thus producing adhesiveness.

[0023] Fig. 3 is a process flow for forming a module as shown in Fig. 2. In Fig. 3, first, the upper polarizing plate 21 is attached to the opposing substrate 20 of the liquid crystal display panel. Then, a light shielding tape with an adhesive material is attached to the upper surface of the opposing substrate 20 with its one side abutting on the upper polarizing plate 21. Here, the light shielding tape with an adhesive material is the light shielding material 50. The light shielding tape and the upper polarizing plate are not necessarily in contact with each other.

[0024] Subsequently, a UV-curable resin 40, which is liquid, is applied on top of the upper polarizing plate 21 and the opposing substrate 20. This acrylic resin is characterized in that it is initially a liquid including an acrylic oligomer. Then, the front window 30 is bonded. After that, the bonding material 40 is caused to cure under UV irradiation. Subsequently, the backlight, which is not shown, is installed under the liquid crystal display panel.

[0025] An advantage of bonding the liquid crystal display panel and the front window 30 using the bonding material 40 resides in that the liquid crystal display panel and the front window 30 can be positioned while being modified, because the bonding material 40 is initially liquid. Once they have been positioned accurately, accurate assembly can be performed by causing the bonding material to cure under ultraviolet irradiation. Another advantage lies in that the UV-curable resin used as the bonding material 40 is less costly than the adhesive material.

[0026] Although it is preferable that the bonding material 40 does not adhere to the chamfers 31, as in Fig. 2, some of the bonding material 40 may adhere to the chamfers 31, because the bonding material 40 is initially liquid. According to the present invention, light leakage can be prevented because of the presence of the light shielding material, even if the liquid bonding material adheres to the chamfers 31.

[0027] Although, in Fig. 1 and Fig. 2, the light shielding

material 50 is laid along the side opposite to the terminal section, it may be more beneficial if the light shielding material 50 is also laid along other two sides where the front window 30 is smaller than the dimensions of the opposing substrate 20 or the TFT substrate 10. When a top frame, which is not shown in Fig. 2, is placed outside the front window 30, it is possible to reduce incoming external light through a lateral side of the front window 30. Even if external light enters the front window 30 through its lateral side, the light entered through the lateral side is fully reflected within the front window 30 and goes out through its opposite lateral side. Hence, the light entered through the lateral side is not emitted through the front surface of the front window and does not impede the viewer's vision in seeing an image being displayed. According to this embodiment, it is possible to prevent light of the backlight from leaking into the front surface even in a case where the black matrix 22 is not formed to prevent peel-off of the sealing material in frame-like portions occupied by the sealing material.

[Second Embodiment]

[0028] Fig. 4 is a plan view of a liquid crystal display device according to a second embodiment of the present invention and Fig. 5 is a cross-sectional diagram through line B-B in Fig. 4. In Fig. 4, a difference from Fig. 1 is that a (frame-like) light shielding tape 60 shaped for marginal edges is formed around the front window 30. The inner edges of the light shielding tape 60 shaped for marginal edges coincide with the outer edges of the front window 30. Other structural details are the same as those in Fig. 1.

[0029] Fig. 5 is a cross-sectional diagram through line B-B in Fig. 4. Fig. 5 differs from Fig. 2 in that the light shielding tape 60 shaped for marginal edges is formed around the front window 30. The inner edges of the light shielding tape 60 shaped for marginal edges coincide with the outer edges of the front window 30. The light shielding tape 60 shaped for marginal edges serves to block out light from the backlight that is leaked from the edge portions of the opposing substrate 20 not covered by the light shielding material 50 or light from the backlight that enters the opposing substrate 20 from outside. Accordingly, it is possible to prevent light leakage in the periphery of the front window 30.

[0030] As is the case for Fig. 2, the bonding material 40 is not formed in the vicinity of the chamfered edges 31 of the front window 30. Even if light of the backlight leaks in the vicinity of the chamfers 31 of the front window 30, the light is unlikely to enter the internal part of the front window 30 through the chamfered edges 31, due to a difference in refractive index between the chamfered edges 31 and air. Accordingly, it is possible to prevent light leakage of this light in the margins of the screen.

[0031] Fig. 6 is a flow representing a fabrication process of the liquid crystal display device of Fig. 4 and Fig. 5, which is the second embodiment. Earlier steps up to

UV irradiation are the same as in the flow shown in Fig. 3. Subsequently, the backlight, which is not shown in Fig. 5, is similarly installed. In Fig. 6, the following step is placing the light shielding tape 60 shaped for marginal edges around the liquid crystal display panel in a position that is flush with the edges of the front window 30. The light shielding tape 60 shaped for marginal edges is a light blocking PET film and its thickness including an adhesive material is about 80 μm .

[0032] In this embodiment, it is possible to shield light from the backlight traveling through the margins of the opposing substrate 20 and it is also possible to prevent light that passes through the outermost portions not covered by the light shielding material 50 and light transmitted outside the opposing substrate 20. Therefore, it is possible to prevent light leakage in the margins of the screen even better than the case of the first embodiment.

Example

[0033] Fig. 10 is a cross-sectional view representing an example not falling under the scope of the present invention. In Fig. 10, the liquid crystal display panel and the backlight 200 are accommodated within a mold 110 and this mold 110 is accommodated with the bottom frame 120. In Fig. 2, Fig. 5, Fig. 7, etc. the mold 110 is excluded for convenience sake. In this embodiment, by providing the light shielding material 50 directly on the upper surface of the opposing substrate 20 in its margins, light from the backlight 200, as indicated by an arrow, is prevented from being emitted through the upper surface of the opposing substrate 20.

[0034] A major difference between this example and the preceding embodiments is that the light shielding material 50 is attached below the polarizing plate 21. In addition, the light shielding material 50 and the polarizing plate 21 are placed overlapping each other. The light shielding material 50 may be provided by tape attachment or print in the structure. In order to reduce a level difference in a portion where the polarizing plate 21 is attached to the surface, it is preferable to provide a print form of the light shielding material. Further, the light shielding tape 60 may be laid to cover the light shielding material 50 and the bonding material 40. By configuring the display device in this way, it is possible to prevent light leakage because of the presence of the light shielding material, even if a liquid bonding material adheres to the chamfered edges 31.

[0035] The above embodiments of the invention as well as the appended claims and figures show multiple characterizing features of the invention in specific combinations. The skilled person will easily be able to consider further combinations or sub-combinations of these features in order to adapt the invention as defined in the claims to his specific needs.

Claims

1. A liquid crystal display device comprising a liquid crystal display panel that includes a thin film transistor substrate (10) having a matrix arrangement of pixel electrodes and thin film transistors for controlling signals to be applied to the pixel electrodes and an opposing substrate (20) having color filters formed at positions corresponding to the pixel electrodes, the thin film transistor substrate (10) being larger than the opposing substrate (20) and comprising a terminal section (12) formed in a portion where the thin film transistor substrate (10) extends beyond the opposing substrate (20),
 wherein
 an upper polarizing plate (21) is bonded to the opposing substrate (20) and a light shielding material (50) is laid in the periphery of the upper polarizing plate (21) on the opposing substrate (20) along a side thereof opposite to the terminal section; **characterised in that**
 a front window (30) is placed over the upper polarizing plate (21), and the upper polarizing plate (21) is smaller than the front window (30) and edges of the upper polarizing plate (21) are located inward of the edges of the front window (30);
 wherein the upper polarizing plate (21) and the front window (30) are bonded with a bonding material (40) made from an ultraviolet curable resin and the light shielding material (50) is laid between the ultraviolet curable resin (40) and the opposing substrate (20);
 wherein the edges of the front window (30), except the edge congruent with the terminal section (12), are located inward of the edges of the opposing substrate (20);
 wherein chamfers (31) are formed in the front window (30) and the bonding material (40) does not adhere to the chamfers (31), and
 wherein the upper polarizing plate (21) and the light shielding material (50) abut each other.
2. The liquid crystal display device according to claim 1, wherein the ultraviolet curable resin (40) is a liquid including an acrylic oligomer before being cured.
3. The liquid crystal display device according to claim 1, wherein the light shielding material (50) is formed by a light shielding tape with an adhesive material.
4. The liquid crystal display device according to any one of claims 1 to 3,
 wherein a frame-like light shielding tape (60) is placed along and outside the outer edges of the front window (30) on the ultraviolet curable resin and above the light shielding material (50) of the opposing substrate; and
 wherein the outer edges of the frame-like light shielding tape (60) are located outward of the edges of the

opposing substrate (20).

Patentansprüche

1. Flüssigkristallanzeigevorrichtung mit einem Flüssigkristallanzeigefeld, welches aufweist: ein Dünnschichttransistorsubstrat (10) mit einer Matrixanordnung von Pixelelektroden und Dünnschichttransistoren zur Steuerung von Signalen, die an die Pixelelektroden anzulegen sind, und ein gegenüberliegendes Substrat (20) mit Farbfiltern, die an Stellen ausgeformt sind, die den Pixelelektroden entsprechen, wobei das Dünnschichttransistorsubstrat (10) größer ist als das gegenüberliegende Substrat (20) und einen Endabschnitt (12) aufweist, der in einem Bereich ausgeformt ist, in dem sich das Dünnschichttransistorsubstrat (10) über das gegenüberliegende Substrat (20) erstreckt,
 wobei eine obere polarisierende Platte (21) an dem gegenüberliegenden Substrat (20) befestigt ist, und ein lichtabschirmendes Material (50) in dem Randbereich der oberen polarisierenden Platte (21) auf dem gegenüberliegenden Substrat (20) entlang einer seiner Seiten gegenüber dem Endabschnitt niedergeschlagen ist, **dadurch gekennzeichnet, dass** ein vorderseitiges Fenster (30) über der oberen polarisierenden Platte (21) angeordnet ist, und die obere polarisierende Platte (21) kleiner als das vordere Fenster (30) ist, und Kanten der oberen polarisierenden Platte (21) nach innen zurückgesetzt gegenüber den Kanten des vorderen Fensters (30) gelegen sind,
 wobei die obere polarisierende Platte (21) und das vordere Fenster (30) mit einem Klebematerial (40) aus einem mit UV-Licht härtbaren Harz miteinander verbunden sind, und das lichtabschirmende Material (50) zwischen dem mit UV-Licht härtbaren Harz (40) und dem gegenüberliegenden Substrat (20) niedergeschlagen ist,
 wobei die Kanten des vorderen Fensters (30), mit Ausnahme der Kante, die deckungsgleich ist mit dem Endabschnitt (12), nach innen zurückgesetzt gegenüber den Kanten des gegenüberliegenden Substrats (20) angeordnet sind,
 wobei Schrägkanten (31) in dem vorderen Fenster (30) ausgeformt sind und das Klebematerial (40) nicht an den Schrägkanten (31) klebt, und
 wobei die obere polarisierende Platte (21) und das lichtabschirmende Material (50) aneinanderstoßen.
2. Flüssigkristallanzeigevorrichtung nach Anspruch 1, wobei das mit UV-Licht aushärtbare Harz (40) eine Flüssigkeit ist, die, bevor sie ausgehärtet ist, ein Acryl oligomer aufweist.
3. Flüssigkristallanzeigevorrichtung nach Anspruch 1, wobei das lichtabschirmende Material (50) aus einer

lichtabschirmenden Folie mit einem Klebematerial geformt ist.

4. Flüssigkristallanzeigevorrichtung nach einem der Ansprüche 1 bis 3, wobei eine rahmenähnliche lichtabschirmende Folie (60) entlang und außerhalb der äußeren Kanten des vorderen Fensters (30) auf dem mit UV-Licht härtbaren Harz und über dem lichtabschirmenden Material (50) des gegenüberliegenden Substrats angeordnet ist, und wobei die äußeren Kanten der rahmenähnlichen lichtabschirmenden Folie (60) nach außen vorspringend gegenüber den Kanten des gegenüberliegenden Substrats (20) angeordnet sind.

Revendications

1. Dispositif d'affichage à cristaux liquides comprenant un panneau d'affichage à cristaux liquides qui inclut un substrat de transistors en couche mince (10) ayant un agencement en matrice d'électrodes de pixels et de transistors en couche mince pour commander des signaux devant être appliqués aux électrodes de pixels et un substrat en opposition (20) ayant des filtres couleur formés en des positions correspondant aux électrodes de pixels, le substrat de transistors en couche mince (10) étant plus grand que le substrat en opposition (20) et comprenant une section terminale (12) formée dans une partie où le substrat de transistors en couche mince (10) s'étend au-delà du substrat en opposition (20), dans lequel une plaque supérieure (21) de polarisation est liée au substrat en opposition (20) et un matériau pare-lumière (50) est déposé dans la périphérie de la plaque supérieure (21) de polarisation sur le substrat en opposition (20) le long d'un côté de celui-ci opposé à la section terminale ;
caractérisé en ce que
 une fenêtre avant (30) est placée sur la plaque supérieure (21) de polarisation, et la plaque supérieure (21) de polarisation est plus petite que la fenêtre avant (30) et des bords de la plaque supérieure (21) de polarisation sont situés à l'intérieur des bords de la fenêtre avant (30) ;
 dans lequel la plaque supérieure (21) de polarisation et la fenêtre avant (30) sont liées avec un matériau de liaison (40) constitué d'une résine durcissable aux ultraviolets et le matériau pare-lumière (50) est déposé entre la résine durcissable aux ultraviolets (40) et le substrat en opposition (20) ;
 dans lequel les bords de la fenêtre avant (30), à l'exception du bord congruent avec la section terminale (12), sont situés vers l'intérieur des bords du substrat en opposition (20) ;
 dans lequel des chanfreins (31) sont formés dans la fenêtre avant (30) et le matériau de liaison (40) n'ad-

hère pas aux chanfreins (31), et dans lequel la plaque supérieure (21) de polarisation et le matériau pare-lumière (50) butent l'un contre l'autre.

2. Dispositif d'affichage à cristaux liquides selon la revendication 1, dans lequel la résine durcissable aux ultraviolets (40) est un liquide incluant un oligomère acrylique avant d'être durcie.
3. Dispositif d'affichage à cristaux liquides selon la revendication 1, dans lequel le matériau pare-lumière (50) est formé par un ruban pare-lumière avec un matériau adhésif.
4. Dispositif d'affichage à cristaux liquides selon l'une quelconque des revendications 1 à 3, dans lequel un ruban pare-lumière (60) de type en cadre est placé le long et à l'extérieur des bords extérieurs de la fenêtre avant (30) sur la résine durcissable aux ultraviolets et au-dessus du matériau pare-lumière (50) du substrat en opposition ; et dans lequel les bords extérieurs du ruban pare-lumière (60) de type en cadre sont situés à l'extérieur des bords du substrat en opposition (20).

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9





FIG. 10



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 2005151899 A1 [0001] [0007]
- JP 2003005160 A [0006]

专利名称(译)	液晶显示装置		
公开(公告)号	EP2485082B1	公开(公告)日	2017-09-27
申请号	EP2012154090	申请日	2012-02-06
[标]申请(专利权)人(译)	株式会社日立显示器		
申请(专利权)人(译)	日立显示器有限公司.		
当前申请(专利权)人(译)	日本展示INC.		
[标]发明人	HARAYAMA TAKESHI YOSHIMOTO TAKASHI ISHII KATSUHIKO KOBAYASHI SETSUO ISHII AKIRA TANABE SHINJI SENTO KIYOSHI		
发明人	HARAYAMA, TAKESHI YOSHIMOTO, TAKASHI ISHII, KATSUHIKO KOBAYASHI, SETSUO ISHII, AKIRA TANABE, SHINJI SENTO, KIYOSHI		
IPC分类号	G02F1/1333		
CPC分类号	G02F1/133308 G02F1/133512 G02F2001/133331 G02F2202/023 G02F2202/28		
优先权	2011023917 2011-02-07 JP		
其他公开文献	EP2485082A1		
外部链接	Espacenet		

摘要(译)

在具有前窗 (30) 的液晶显示装置中，防止来自背光的光通过前窗 (30) 的倒角边缘 (31) 泄漏。上偏振片 (21) 形成在相对基板 (20) 上，并且遮光材料 (50) 形成为邻接在上偏振片 (21) 的外边缘上。上偏振板 (21) 的边缘位于前窗 (30) 的边缘的内侧。上偏振片和前窗用包含紫外线固化树脂的粘合材料 (40) 粘合。紫外线固化树脂也位于遮光材料 (50) 上。倒角 (31) 形成在前窗 (30) 中，并且紫外线固化树脂不会粘附到前窗的倒角上。通过这种结构，防止来自背光的光通过前窗的倒角 (31) 进入前窗 (30) 的内部，并防止漏光。

FIG. 1

