



(11)

EP 2 537 064 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
01.04.2015 Bulletin 2015/14

(51) Int Cl.:
G02F 1/13357 ^(2006.01) **G02F 1/1335** ^(2006.01)
F21V 8/00 ^(2006.01)

(21) Application number: **10846223.5**

(86) International application number:
PCT/KR2010/006982

(22) Date of filing: **12.10.2010**

(87) International publication number:
WO 2011/102585 (25.08.2011 Gazette 2011/34)

(54) **BACKLIGHT UNIT AND LIQUID CRYSTAL DISPLAY INCLUDING THE SAME**

RÜCKLICHT EINHEIT UND FLÜSSIGKRISTALLANZEIGE DAMIT

UNITÉ DE RÉTROÉCLAIRAGE ET AFFICHEUR À CRISTAUX LIQUIDES COMPRENANT CETTE
UNITÉ

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(30) Priority: **21.02.2010 US 306514 P**
12.03.2010 KR 20100022199

(43) Date of publication of application:
26.12.2012 Bulletin 2012/52

(60) Divisional application:
14004097.3 / 2 851 742

(73) Proprietor: **LG Electronics Inc.**
Seoul 150-721 (KR)

(72) Inventors:
• **KIM, Sangjeon**
Seoul 137-724 (KR)
• **RYU, Seonghwan**
Seoul 137-724 (KR)

(74) Representative: **Beyer, Andreas**
Wuesthoff & Wuesthoff
Patent- und Rechtsanwälte
Schweigerstrasse 2
81541 München (DE)

(56) References cited:
JP-A- 2004 279 864 JP-A- 2005 534 071
JP-A- 2006 253 108 JP-A- 2009 049 017
US-A1- 2003 223 020 US-A1- 2005 254 236
US-A1- 2007 297 195

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

Technical Field

[0001] A backlight unit and a liquid crystal display including the same are disclosed herein.

Background Art

[0002] With the development of the information society, various demands for display devices have been increasing. Various display devices, such as a liquid crystal display (LCD), a plasma display panel (PDP), an electroluminescent display (ELD), and a vacuum fluorescent display (VFD), have been recently studied and used, so as to meet the various demands for the display devices.

Disclosure of Invention

Technical Problem

[0003] The liquid crystal display includes a liquid crystal display panel and a backlight unit providing light to the liquid crystal display panel. The liquid crystal display panel transmits light provided by the backlight unit and adjusts a transmittance of the light, thereby displaying an image.

[0004] The backlight unit may be classified into an edge type backlight unit and a direct type backlight unit depending on a location of light sources. In the edge type backlight unit, light sources are disposed at a side of the liquid crystal display panel, and a light guide plate is disposed on a back surface of the liquid crystal display panel and guides the light emitted from the side of the liquid crystal display panel to the back surface of the liquid crystal display panel. In the direct type backlight unit, light sources are disposed on a back surface of the liquid crystal display panel, and the light emitted from the light sources may be directly provided to the back surface of the liquid crystal display panel.

[0005] Examples of the light sources may include an electroluminescence (EL) device, a cold cathode fluorescent lamp (CCFL), a hot cathode fluorescent lamp (HCFL), and a light emitting diode (LED). The LED has low power consumption and high light emitting efficiency.

[0006] US 2005/254236 discloses a backlight unit comprising an optical film having holes in a periphery thereof for coupling with corresponding supporting portions disposed on a periphery of a frame. The holes may be oblong in shape such that the optical film may be placed in the frame with the supporting portions extending through the holes, and the optical film may then be displaced when it moves with respect to the frame and the supporting portions move within the oblong holes. Holes and corresponding slots are provided in a symmetrical fashion along two perpendicular bisecting axes of the backlight unit. The unit may be rotated 180 degrees or 90 degrees, and because the holes and corresponding

supporting portions are provided in a symmetrical fashion, the optical film remains supported in each orientation.

[0007] US 2007/297195 discloses a backlight unit comprising a frame and an optical film, wherein the optical film contains at least one through-hole corresponding to a protuberance disposed on the frame. The protuberance extends through the through-hole when the optical film is hung on the frame. The display unit is configured to be rotated 90 degrees to switch between landscape and portrait view. Therefore, the number of through-holes and protuberances are provided on a top side and two lateral sides of the display, such that the frame supports the optical film in either orientation and so that the weight of the optical film is uniformly distributed on the frame. In an alternative embodiment, through-holes and protuberances are provided only along a top side.

[0008] However, they suffer from various disadvantages.

Solution to Problem

[0009] A display device according to independent claim is provided.

[0010] Exemplary embodiments of the invention provide a liquid crystal display including the features of independent claim 1.

Advantageous Effects of Invention

[0011] The liquid crystal display according to the exemplary embodiment, a margin allowing for thermal expansion of the optical sheet due to heat generated by the light sources may be created between the holes and the fixing parts, thereby preventing possible creases in the optical sheet.

[0012] Also, as the optical sheet contracts, the fixing parts may serve to apply tension to the optical sheet to prevent the optical sheet from contracting. Thus, deformation of the optical sheet may be prevented.

Brief Description of Drawings

[0013]

FIGURE 1 illustrates a liquid crystal display (LCD) according to an embodiment;

FIGURES 2 and 3 illustrate a backlight unit according to the embodiment;

FIGURES 4 to 14 illustrate an optical sheet according to the embodiment;

FIGURES 15 to 17 illustrate a housing and a fixing part according to the embodiment;

FIGURE 18 illustrates shapes of a hole of the optical sheet and the fixing part of the housing;

FIGURE 19 illustrates a liquid crystal display panel and the optical sheet coupled with the housing according to the embodiment;

FIGURES 20 and 23 are enlarged views of a portion 'C' in FIGURE 19;

FIGURES 21 and 24 are enlarged views of a portion 'D' in FIGURE 19;

FIGURE 22 and 25 are enlarged views of a portion 'E' in FIGURE 19;

FIGURES 26 and 27 are sectional views of the LCD according to the embodiment;

FIGURES 28 and 29 illustrate a backlight unit and an optical assembly according to another embodiment;

FIGURE 30 illustrates a direct type backlight unit;

FIGURE 31 illustrates an LCD according to another embodiment; and

FIGURE 32 illustrates an edge type backlight unit.

[0014] The embodiments illustrated in Figs. 5, 6, 8, 9, 12 to 17 and 19 do not fall within the scope of the appended claims.

Best Mode for Carrying out the Invention

[0015] Figure 1 illustrates a liquid crystal display (LCD) according to a first embodiment of the invention. As shown in Figure 1, the LCD 100 may include a liquid crystal display panel 110, a backlight unit 120, cover 130, housing 135, a driving unit 140, and a back case 150.

[0016] The liquid crystal display panel 110, on which an image may be displayed, may include a first and second substrates 111 and 112 attached to face a liquid crystal layer interposed therebetween. A plurality of scan lines and a plurality of data lines may cross in a matrix form to define a plurality of pixels on the first substrate 111 called a thin film transistor (TFT) array substrate. Each pixel may include a TFT to turn the pixel on or off and a pixel electrode to electrically connect the TFT. Red (R), green (G), and blue (B) color filters corresponding to the plurality of pixels and black matrixes surrounding the color filters and covering non-display elements such as the scan lines, the data lines, and the TFTs may be formed on the second substrate 112 called a color filter substrate.

[0017] In addition, a transparent common electrode covering the non-display elements may also be provided

on the second substrate 112. A printed circuit board (PCB) may be connected to at least one side of the liquid crystal display panel 110 by a connection member such as a flexible circuit board or a tape carrier package (TCP), and may be tightly attached to a rear surface of the housing 135 during a modularization process.

[0018] In the liquid crystal display panel 110, when TFTs selected by the scan lines are turned on according to ON/OFF signals of a gate driving circuit 113, a data voltage of a data driving circuit 114 may be transferred to a corresponding pixel electrode through the data lines. Accordingly, an alignment direction of liquid crystal molecules may be changed by an electric field generated by the data voltage between the pixel electrode and the common electrode.

[0019] The LCD 100 according to an embodiment may include the backlight unit 120 that may provide light to the liquid crystal display panel 110 from a rear surface of the liquid crystal display panel 110. The backlight unit 120 may include an optical assembly 123 and a plurality of optical sheets 125 disposed on the optical assembly 123.

[0020] The liquid crystal display panel 110 and the backlight unit 120 may be modularized through the cover 130 and the housing 135. The cover 130 may be positioned on the front surface of the liquid crystal display panel 110, and may be a top cover shaped as a rectangular frame that may cover an upper surface and a side surface of the liquid crystal display panel 110. A front surface of the cover 130 may be open to allow displaying of an image generated on the liquid crystal display panel 110.

[0021] The housing 135 may be positioned on a rear surface of the backlight unit 120 and may include a bottom plate 135a and a supporting plate 135b. The bottom plate 135a may be a bottom cover, to which the liquid crystal display panel 110 and the backlight unit 120 are coupled, that may serve as a base for the LCD 100. The bottom plate 135a may be shaped as a single rectangular plate. The supporting plate 135b may support and couple the cover 130 and the bottom plate 135a.

[0022] The driving unit 140 may be disposed on one surface of the housing 135 positioned on the rear surface of the backlight unit 120. The driving unit 140 may include a driving controller 141, a main board 142, and a power supply unit 143. The driving controller 141 may be a timing controller that adjusts an operation timing of each driving circuit of the liquid crystal display panel 110. The main board 142 may transfer a vertical synchronous signal, a horizontal synchronous signal, and R, G, and B resolution signals to the timing controller. The power supply unit 143 may provide power to the liquid crystal display panel 110 and the backlight unit 120. The driving unit 140 may be coupled to the housing 135 by using a driving unit chassis 145. The driving unit 140 may be covered by the back case 150.

[0023] Figures 2 and 3 illustrate a backlight unit according to the first embodiment. Referring to Figures 2

and 3, the backlight unit 200 may include an optical assembly 210 and an optical sheet 250. The optical assembly 210 may include a first layer 215, a plurality of light sources 217, a reflective layer 220, a second layer 230, and a diffusion plate 240. The plurality of light sources 217 may be formed on the first layer 215, and the second layer 230 may be disposed on the first layer 215 to cover the plurality of light sources 217.

[0024] The first layer 215 may be a board (or substrate) on which the plurality of light sources 217 may be mounted. An electrode pattern may be formed on the first layer 215 in order to connect an adapter that may supply power and the light sources 217. For example, a carbon nanotube (CNT) electrode pattern for connecting the light sources 217 and the adapter may be formed on an upper surface of the substrate. The first layer 215 may be a PCB formed of polyethylene terephthalate (PET), glass, poly-carbonate (PC), silicon (Si), or other appropriate materials on which the plurality of light sources 217 may be mounted. The first layer 215 may also be formed as a film.

[0025] The light sources 217 may be one of a light emitting diode (LED) chip and an LED package including at least one LED chip. In this embodiment, simply for ease of explanation, light sources 217 will be described herein as having an LED package.

[0026] The LED package constituting the light sources 217 may be classified into a top view type LED package and a side view type LED package depending on the direction of a light emission surface. The light sources 217 may be configured by using at least one of a top view type LED package in which a light emission surface may be formed toward the upper side and a side view type LED package in which the light emission surface may be formed toward the side. When the light sources 217 are the side view type LED package, the light emission surface of each of the plurality of light sources 217 may be disposed on the side, and the plurality of light sources 217 may emit light in a lateral direction, for example, in the direction in which the first layer 215 or the reflective layer 220 extends. Thus, the thickness of the second layer 230 formed on the light sources 217 may be reduced, making the backlight unit 200 and the LCD 100 thinner.

[0027] The light sources 217 may be color LEDs that may emit at least one of red, blue, and green colors, or white LEDs. The colored LEDs may include at least one of red LEDs, blue LEDs, and green LEDs. Accordingly, the disposition and color of light emitted from the LEDs may be variably modified.

[0028] The second layer 230 may be disposed on the first layer 215 and may cover the plurality of light sources 217. The second layer 230 may allow light emitted from the light sources 217 to transmit therethrough and spread the light, whereby the light emitted from the light sources 217 may be uniformly provided to the liquid crystal display panel.

[0029] The reflective layer 220 may reflect light emitted

from the light sources 217 and may be positioned on the first layer 215. The reflective layer 220 may be formed on an area of the first layer 215, other than the area where the light sources 217 are formed. For example, as shown in Figure 3, reflective layer 220 may include recesses corresponding to the light sources 217 in which the light sources 217 may be positioned.

[0030] The reflective layer 220 may reflect light emitted from the light sources 217 and reflect again light totally reflected from the boundary of the second layer 230 to further increase the area of light dispersion.

[0031] The reflective layer 220 may contain at least one of metal or a metal oxide, a reflective material. For example, the reflective layer 220 may be formed of metal or metal oxide having a high reflectance, for example, aluminum (Al), silver (Ag), gold (Au), titanium dioxide (TiO₂), or other appropriate reflective materials. The reflective layer 220 may be formed by depositing or coating the metal or metal oxide on the first layer 215 or by printing metal ink on the first layer 215. Here, a vacuum deposition method, for example, a thermal deposition method, an evaporation method, a sputtering method, or other appropriate deposition methods may be used as the deposition method. Further, a printing method, a gravure coating method, a silk screen method, or other appropriate methods may be used as the coating or printing method.

[0032] The second layer 230 on the first layer 215 may be formed of a light-transmissive material, for example, a silicon or acrylic resin. However, the second layer 230 is not limited thereto and may be formed of various other resins. In order to allow the backlight unit 200 to have a uniform luminance in diffusing light emitted from the light sources 217, the second layer 230 may be formed of a resin having a refractive index of about 1.4 to 1.6. For example, the second layer 230 may be formed of polyethylene terephthalate (PET), polycarbonate (PC), polypropylene (PP), polyethylene (PE), polystyrene (PS), polyepoxy (PE), silicon, acryl, or other appropriate materials.

[0033] The second layer 230 may include a polymer resin having an adhesive property so as to be firmly and tightly attached to the light sources 217 and the reflective layer 220. For example, the second layer 230 may be formed of acryl group, urethane group, epoxy group, and melamine group such as unsaturated polyester, methyl methacrylate, ethyl methacrylate, isobutyl methacrylate, n-butyl methacrylate, n-butyl methyl methacrylate, acrylic acid, methacrylic acid, hydroxyl ethyl methacrylate, hydroxyl propyl methacrylate, hydroxyl ethyl acrylate, acrylamide, methylol acrylamide, glycidyl methacrylate, ethyl acrylate, isobutyl acrylate, n-butyl acrylate, 2-ethyl hexyl acrylate polymer, copolymer, terpolymer, other appropriate materials.

[0034] The second layer 230 may be formed by coating a liquid or gel phase resin on the first layer 215 having the plurality of light sources 217 and the reflective layer 220 formed thereon, and then hardening the resin. Alter-

natively, the second layer 230 may be formed by coating a resin on a support sheet, partially hardening the resin, and then bonding the same to the first layer 215.

[0035] The diffusion plate 240 may be formed on the second layer 230 that may allow light emitted from the light sources 217 to be diffused upward. The diffusion plate 240 may be bonded to the second layer 230 using an additional adhesive member.

[0036] Figures 4 to 14 illustrate an optical sheet according to the first embodiment. The optical sheet 250 may be positioned on the foregoing optical assembly 210. Referring to Figure 4, the optical sheet 250 according to this embodiment may be a diffusion sheet that may diffuse light outputted from the light sources or a prism sheet that may concentrate light.

[0037] The optical sheet 250 may include a plurality of holes or slots 251 on at least one side such that the optical sheet 250 may be coupled to the cover 130 or the housing 135. The optical sheet 250 may have a rectangular shape, and the plurality of holes 251 may be positioned on the upper side 255 and lower side 256 of the optical sheet 250. Here, the upper side 255 of the optical sheet 250 may correspond to an upper side of the LCD when assembled and positioned to stand or mounted for use. Likewise, the lower side 256 of the optical sheet 250 may correspond to a lower side of the LCD.

[0038] The holes 251 may be formed at protrusions or tabs 252 protruded from at least one side of the optical sheet 250, for example, at the upper side 255 and the lower side 256 of the optical sheet 250. The protrusions 252 may subsequently be coupled with the cover 130 or the housing 135, and may be formed such that they protrude from one side of the optical sheet 250.

[0039] The holes 251 formed at the protrusions 252 may have various shapes including a polygonal shape, a triangular shape, a circular shape, a quadrangular shape, or other appropriate shapes. Also, the protrusions 252 may have various shapes that allow the protrusions 252 to be easily coupled with the cover 130 or the housing 135. For example, the portions of the protrusions 252 in contact with the cover 130 or the housing 135 may have a large quadrangular shape.

[0040] The plurality of holes 251 may be formed such that a number of holes 251 formed on one of the plurality of sides of the optical sheet 250 is less than a number of holes 251 formed on another of the plurality of sides of the optical sheet 250. For example, as shown in Figure 4, the number of holes 251 formed on the upper side 255 of the optical sheet 250 may be greater than the number of holes 251 formed on the lower side 256 of the optical sheet 250. As discussed above, the upper side 255 of the optical sheet 250 may correspond to the upper side of the LCD when the LCD is assembled. In order to prevent the optical sheet 250 from sagging due to the weight of the LCD components when assembled, a greater number of holes 251 may be formed on the upper side 255.

[0041] A plurality of holes 251 may also be formed on

the sides of the optical sheet 250 which face each other. For example, as shown in Figures 4 to 9, the plurality of holes 251 may be positioned on the upper side 255 and the lower side 256 of the optical sheet 250 which face each other. The plurality of holes 251 may also be positioned on the left side 257 and the right side 258 of the optical sheet 250. Moreover, the plurality of holes 251 may be positioned on all sides, for example, on the upper side 255, the lower side 256, the left side 257, and the right side 258.

[0042] Referring to Figure 5, the plurality of holes 251 formed on the upper side 255 of the optical sheet 250 may be positioned to be symmetrical with the plurality of holes 251 formed on the lower side 256 of the optical sheet which faces the upper side 255. Alternatively, with reference to Figure 4, the plurality of holes 251 formed on the upper side 255 of the optical sheet 250 may be asymmetrical with the plurality of holes 251 formed on the lower side 256 of the optical sheet 250 which faces the holes 251 of the upper side 255.

[0043] Referring to Figures 6 and 7, the plurality of holes 251 may be positioned on all of the sides, for example, on the upper side 255, on the lower side 256, on the left side 257, and on the right side 258 of the optical sheet 250. Here, as shown in Figure 6, the plurality of holes 251 disposed on the upper side 255 of the optical sheet 250 may be symmetrical to the plurality of holes 251 disposed on the lower side 256 of the optical sheet 250, and the plurality of holes 251 disposed on the left side 257 of the optical sheet 250 may be symmetrical to the plurality of holes 251 disposed on the right side 258 of the optical sheet 250. Alternatively, as shown in Figure 7, the plurality of holes 251 disposed on the upper side 255 of the optical sheet 250 may be asymmetrical to the plurality of holes 251 disposed on the lower side 256 of the optical sheet 250, and the plurality of holes 251 disposed on the left side 257 of the optical sheet 250 may be asymmetrical to the plurality of holes 251 disposed on the right side 258 of the optical sheet 250.

[0044] Referring to Figures 8 to 9, the plurality of holes 251 may be positioned on the sides of the optical sheet 250, for example, on the left side 257 and right side 258 which face each other. Here, the plurality of holes 251 are not positioned on the upper and lower sides 255 and 256 of the optical sheet 250. As shown in Figure 8, the plurality of holes 251 disposed on the left side 257 of the optical sheet 250 may be symmetrical to the plurality of holes 251 disposed on the right side 258 of the optical sheet 250. Alternatively, as shown in Figure 9, the plurality of holes 251 disposed on the left side 257 of the optical sheet 250 may be asymmetrical to the plurality of holes 251 disposed on the right side 258 of the optical sheet 250.

[0045] Referring now to Figure 10, the holes or slots 251 may be formed at an inner side of at least one side of the optical sheet 250, for example, at an inner side of the upper side 255 and the lower side 256 of the optical sheet 250. For example, the slots or holes 251 may be

formed on the optical sheet 250 inside the side edges thereof. The plurality of holes 251 formed at an inner side of at least one side of the optical sheet 250 may be formed on the sides of the optical sheet 250 which face each other. For example, as shown in Figures 10 and 12, the plurality of holes 251 may be positioned at the inner side of the upper side 255 and the lower side 256 of the optical sheet 250 which face each other. Further, the plurality of holes 251 may be positioned at the inner side of the left and right sides 257 and 258 of the optical sheet 250, and the plurality of holes 251 may be positioned at the inner side of the upper, lower, left, and right sides 255, 256, 257, and 258, respectively, of the optical sheet 250.

[0046] Further, with reference to Figure 10, the plurality of holes 251 formed at the inner side of the upper side 255 of the optical sheet 250 may be asymmetrical to the plurality of holes 251 formed at the inner side of the lower side 256 of the optical sheet 250 which faces the upper side 255. Also, with reference to Figure 12, the plurality of holes 251 formed at the inner side of the left side 257 of the optical sheet 250 may be symmetrical to the plurality of holes 251 formed at the inner side of the right side 258 of the optical sheet 250 which faces the left side 257.

[0047] As shown in Figure 11, the plurality of holes 251 may be positioned at the inner side of all of the sides, for example, at the inner side of the upper, lower, left, and right sides 255, 256, 257, and 258 of the optical sheet 250. Also, as shown in Figure 12, the plurality of holes 251 may be positioned at the inner side of the sides, for example, at the inner side of the left and right sides 257 and 258 of the optical sheet 250 that face each other. Here, the plurality of holes 251 are not positioned at the upper and lower sides 255 and 256 of the optical sheet 250.

[0048] Referring now to Figure 13, the plurality of holes 251 may be positioned at the four corners 259 of the optical sheet 250. Alternatively, as shown in Figure 14, the plurality of holes 251 may be positioned at opposite corners 259 of the optical sheet 250 that face each other.

[0049] As described above, the optical sheet 250 according to the first embodiment may include the plurality of holes 251 on at least one side or at the corners thereof to fixedly couple the optical sheet 250 to the cover 130 or the housing 135. Thus, the reliability of the coupled optical sheet 250 and cover 130 or the housing 135 may be improved. Further, the optical characteristics of light emitted from the light sources may be effectively enhanced. The disposition of the holes of the optical sheet as illustrated in Figures 4 to 14 are not limited to this embodiment, and may be disposed, for example, only at one side of the optical sheet to couple with the cover or the housing.

[0050] Figures 15 to 17 illustrate a cover and a fixing part according to this embodiment. Referring now to Figure 15, a cover 300 may have a shape of a rectangular frame and, as shown in Figure 1, the cover 300 may cover the front side of the LCD 100. A fixing part 310 to couple

the optical sheet 250 may be formed as a rail and may be positioned on a side wall of the cover 300. For example, a plurality of fixing parts 310 may be provided and positioned on at least one side wall of the cover 300. Further, as shown in Figure 15, the fixing parts 310 may be positioned on upper and lower side walls 321 and 322. The fixing parts 310 may be also positioned on left and right side walls 323 and 324 of the cover 300. The placement of the fixing parts 310 may correspond to the placement of the holes 251 of the optical sheet 250 as described above.

[0051] The fixing parts 310 may be formed on a step portion 315 of the side walls 323 and 324 of the cover 300 such that it may protrude upward from the side walls 323 and 324. The protrusion may have a hexahedral shape, cylindrical shape, spherical shape, or other appropriate shape and is not particularly limited thereto. Further, as described above the fixing part may also be formed as a rail. The step portion 315 may be a size sufficient to allow a hole 251 formed at a protrusion 252 of the optical sheet 250 to be mounted thereon. Further, the fixing part 310 may be positioned at a central portion of the step portion 315. The size of the fixing part 310 formed at the step portion 315 may be the same as that of the hole 251 formed on the protrusion 252, or may be slightly larger than that of the hole 251. Accordingly, the hole 251 of the optical sheet 250 may be coupled with the fixing part 310 of the cover 300 to fix the optical sheet 250 to the cover 300.

[0052] Referring to Figure 16, the step portions 315 may be formed along an entire lateral length of the side wall of the cover 300. The step portions 315 may be formed on the entire upper side wall 321 of the cover 300, and the step portions 315 may be formed on the entire lower side wall 322 of the cover 300.

[0053] The fixing parts 310 may be disposed on the step portions 315. The step portions 315 illustrated in Figure 16 may allow mounting of the optical sheet illustrated in Figures 10 and 12 having the plurality of holes formed at the inner side of one side thereof. In this case, the plurality of holes formed on the optical sheets may be coupled to the fixing parts 310 formed at the step portions 315 of the cover 300.

[0054] As shown in Figure 17, the fixing parts 310 may be positioned at the corners 325 of the cover 300. Here, the fixing parts 310 may be disposed to be slanted, or diagonally, at the corners 325, but is not limited thereto. Thus, the optical sheet illustrated in Figures 13 and 14 as described above, for example, the optical sheet having the plurality of holes at the corners may be coupled to the fixing parts 310 positioned at the corners 325 of the cover 300.

[0055] Figure 18 illustrates the shapes of the hole of the optical sheet and the fixing part of the cover. The holes 251 of the optical sheet 250 and the fixing parts 310 of the cover 300 may have a quadrangular shape or any other appropriate shapes. The hole 251 of the optical sheet 250 or the fixing part 310 of the cover 300 may

have a rectangular shape as shown in Figure 18(a). Also, the hole 251 of the optical sheet 250 or the fixing part 310 of the cover 300 may have a square shape as shown in Figure 18(b) or a pentagonal shape as shown in Figure 18(c). However, the shapes are not limited thereto and the hole 251 of the optical sheet 250 or the fixing part 310 of the cover 300 may have any appropriate shapes including a polygonal shape having more sides than the pentagonal shape.

[0056] Also, the hole 251 of the optical sheet 250 or the fixing part 310 of the cover 300 may have a circular shape as shown in Figure 18(d) or an oval shape as shown in Figure 18(e). The shapes of the hole 251 of the optical sheet 250 or the fixing part 310 of the cover 300 are not limited thereto, and they may have any shape so long as it may allow for the coupling of the hole 251 of the optical sheet 250 and the fixing part 310 of the cover 300.

[0057] Hereinafter, the configuration in which the hole 251 of the optical sheet 250 and the fixing part 310 of the cover 300 are coupled will now be described in detail. Simply for ease of explanation, the hole 251 of the optical sheet 250 and the fixing part 310 of the cover 300 will be described with reference to a hole having a rectangular shape.

[0058] Figure 19 illustrates the liquid crystal display panel and the optical sheet coupled to the cover according to an embodiment; Figures 20 and 23 are an enlarged view of a portion 'C' in Figure 19; Figures 21 and 24 are an enlarged view of a portion 'D' in Figure 19; and Figures 22 and 25 are an enlarged view of a portion 'E' in Figure 19.

[0059] As shown in Figure 19, a liquid crystal display panel 400 may be positioned on the cover 300, and the optical sheet 250 may be positioned on the liquid crystal display panel 400. A plurality of gate driving circuits 410 may be disposed at left and right sides of the liquid crystal display panel 400, and a printed circuit board (PCB) 420 may be disposed on the optical sheet 250 on the liquid crystal display panel 400. A plurality of data driving circuits 430 may be disposed on the PCB 420.

[0060] Here, the optical sheet 250 may be disposed on the cover 300 such that the holes 251 of the optical sheet 250 may be coupled with the fixing parts 310 of the cover 300. For example, referring to enlarged portion 'A' in Figure 19, the slot or hole 251 that may be formed at the tab or protrusion 252 and disposed at the upper side of the optical sheet 310 may be coupled with the rail or fixing part 310 formed at the upper side wall of the cover 300. For example, the fixing part 310 may be inserted into the hole 251 of the optical sheet 250.

[0061] Referring to a portion 'B' in Figure 19, the hole 251 that may be formed at the protrusion 252 and disposed at the lower side of the optical sheet 310 may be coupled with the fixing part 310 formed at the lower side wall of the cover 300. Here, the protrusions 252 of the optical sheet 250 and the fixing parts 310 of the cover 300 may be disposed between the data driving circuits

430 of the liquid crystal display panel 400.

[0062] For example, in order to secure an area at the side of the cover 300 where the data driving circuits 430 may be mounted, the fixing parts 310 may be disposed between the data driving circuits 430, and the protrusions 252 and the holes 251 of the optical sheet 250 may be disposed between the data driving circuits 430 according to the disposition of the fixing parts 310.

[0063] Referring to Figure 20, enlarged portion 'C' shows the hole 251 that may be coupled to the fixing part 310 at the edge on the upper side of the optical sheet 250. Here, the hole 251 may include a first side 251a, a second side 251b, a third side 251c, and a fourth side 251d, and the fixing part 310 may include a fifth side 310a facing the first side 251a of the hole 251, a sixth side 310b facing the second side 251b, a seventh side 310c facing the third side 251c, and an eighth side 310d facing the fourth side 251d. Here, the first side 251a of the hole 251 may be adjacent to the cover 300, and the second side 251b may be separated to be positioned away from the cover 300.

[0064] For example, in the enlarged portion 'C' where the hole 251 may be coupled to the fixing part 310 at the edge on the upper side of the optical sheet 250, a first distance d1 may be formed between the first side 251a of the hole 251 and the fifth side 310a of the fixing part 310, a second distance d2 may be formed between the second side 251b of the hole 251 and the sixth side 310b of the fixing part 310, a third distance d3 may be formed between the third side 251c of the hole 251 and the seventh side 310c of the fixing part 310, and a fourth distance d4 may be formed between the fourth side 251d of the hole 251 and the eighth side 310d of the fixing part 310.

[0065] The first distance d1 may range from 0.05 mm to 0.3 mm, and may preferably be 0.1 mm. Here, when the first distance d1 is longer than 0.05 mm, a sufficient margin may be provided to allow for an expansion of the optical sheet 250 due to heat generated in the LCD. Thus, a crease in the optical sheet 250 due to thermal expansion may advantageously be prevented. When the first distance d1 is shorter than 0.3 mm, tension may be caused on the optical sheet 250 by the fixing part 310 when the optical sheet 250 contracts as heat dissipates from the optical sheet 250. Thus, a crease in the optical sheet 250 due to thermal contraction may advantageously be prevented.

[0066] The second distance d2 may range from 0.1 mm to 1 mm, and may preferably be 0.5 mm. Here, when the second distance d2 is longer than 0.1 mm, a sufficient margin may be provided to allow for an expansion of the optical sheet 250 due to heat generated in the LCD. Thus, a crease in the optical sheet 250 due to thermal expansion may advantageously be prevented. When the second distance d2 is shorter than 1 mm, the second distance d2 between the fixing part 310 and the hole 251 may increase as the optical sheet 250 contracts as heat dissipates from the optical sheet 250, thus advantageously preventing the hole 251 from being released

from the fixing part 310. For example, a length of the slot or hole 251 may be 0.15 mm to 1.3 mm larger than a length of the rail or fixing part 310.

[0067] The third distance d3 and the fourth distance d4 may range from 1 mm to 5 mm, and may preferably be 2 mm. Here, when the third distance d3 and the fourth distance d4 are longer than 1 mm, a sufficient margin may be provided to allow for an expansion of the optical sheet 250 due to heat generated in the LCD, thus a crease in the optical sheet 250 may advantageously be prevented. When the third distance d3 and the fourth distance d4 are shorter than 5 mm, the third distance d3 and the fourth distance d4 between the fixing part 310 and the hole 251 may increase, thus advantageously preventing the hole 251 and the fixing part 310 from being released. For example, a width of the slot or hole 251 may be 2 mm to 10 mm larger than a width of the rail or fixing part 310.

[0068] Referring to Figure 21, enlarged portion 'D' shows the hole 251 that may be coupled to fixing part 310 at the center among the holes 251 disposed on the upper side of the optical sheet 250. Here, a fifth distance d5 may be formed between the first side 251a of the hole 251 and the fifth side 310a of the fixing part 310, a sixth distance d6 may be formed between the second side 251b of the hole 251 and the sixth side 310b of the fixing part 310, a seventh distance d7 may be formed between the third side 251c of the hole 251 and the seventh side 310c of the fixing part 310, and an eighth distance d8 may be formed between the fourth side 251d of the hole 251 and the eighth side 310d of the fixing part 310.

[0069] The fifth distance d5 may range from 0.05 mm to 0.3 mm, and may preferably be 0.1 mm. Here, when the fifth distance d5 is longer than 0.05 mm, a sufficient margin may be provided to allow for an expansion of the optical sheet 250 due to heat generated in the LCD. Thus, creasing of the optical sheet 250 may be prevented. When the fifth distance d5 is shorter than 0.3 mm, tension may be created on the optical sheet 250 by the fixing part 310 as the optical sheet 250 contracts due to dissipation of heat, thus advantageously preventing the optical sheet 250 from being creased.

[0070] The sixth distance d6 may range from 0.1 mm to 1 mm, and may preferably be 0.5 mm. Here, when the sixth distance d6 is longer than 0.1 mm, a margin sufficient for thermal expansion of the optical sheet 250 may be provided, thus advantageously preventing the optical sheet 250 from being creased. When the sixth distance d6 is shorter than 1 mm, the sixth distance d6 between the fixing part 310 and the hole 251 may increase as the optical sheet 250 contracts as heat is dissipated, thus advantageously preventing the hole 251 from being released from the fixing part 310. For example, the length of hole 251 may be 0.15 mm to 1.3 mm larger than a length of the rail or fixing part 310.

[0071] The seventh distance d7 and the eighth distance d8 may range from 0.1 mm to 1 mm, and may preferably be 0.5 mm. Here, when the seventh distance

d7 and the eighth distance d8 are longer than 0.1 mm, a sufficient margin may be provided to allow for an expansion of the optical sheet 250 due to heat generated in the LCD, thus a crease in the optical sheet 250 may advantageously be prevented. When the seventh distance d7 and the eighth distance d8 are shorter than 1 mm, the hole 251 and the fixing part 310 may serve to fix the optical sheet 250 at the central portion of the optical sheet 250, thus advantageously preventing the optical sheet 250 from being distorted at its position. For example, a width of the slot or hole 251 may be 0.15 mm to 1.3 mm larger than a width of the rail or fixing part 310.

[0072] As discussed above with reference to Figures 20 and 21, the seventh distance d7 and the eighth distance d8 between the hole 251 and the fixing part 310 disposed at enlarged portion 'D' positioned near a central portion of optical sheet 250 may be shorter than the third distance d3 and the fourth distance d4 between the hole 251 and the fixing part 310 disposed at enlarged portion 'C'.

[0073] As for the relationship between the hole 251 and the fixing part 310 disposed at the central portion 'D' of the optical sheet 250, they may be positioned near a central portion of the optical sheet 250 and may serve to fix the overall position of the optical sheet 250 as stated above. Accordingly, the optical sheet 250 may be fixed to prevent its position from changing due to an expansion or contraction of the optical sheet 250.

[0074] Also, as for the relationship between the hole 251 and the fixing part 310 disposed at enlarged portion 'C' of the optical sheet 250, they may be positioned at the edge of the optical sheet 250 to secure a margin sufficient to allow for the extraction and contraction of the optical sheet 250. Thus, the third distance d3 and the fourth distance d4 may be larger than the corresponding distances at the central position 'D'.

[0075] Referring to Figure 22, an enlarged portion 'E' shows the hole 251 that may be disposed at the lower side of the optical sheet 250 coupled to the fixing part 310. Here, a ninth distance d9 may be formed between the first side 251a of the hole 251 and the fifth side 310a of the fixing part 310, a tenth distance d10 may be formed between the second side 251b of the hole 251 and the sixth side 310b of the fixing part 310, an eleventh distance d11 may be formed between the third side 251c of the hole 251 and the seventh side 310c of the fixing part 310, and a twelfth distance d12 may be formed between the fourth side 251d of the hole 251 and the eighth side 310d of the fixing part 310.

[0076] The ninth distance d9 may range from 0.1 mm to 1 mm, and may preferably be 0.5 mm. Here, when the ninth distance d9 is longer than 0.1 mm, a margin sufficient to allow for thermal expansion of the optical sheet 250 may be provided, thus advantageously preventing the optical sheet 250 from being creased. When the ninth distance d9 is shorter than 1 mm, tension may be provided to the optical sheet 250 by the fixing part 310 when the optical sheet 250 contracts as heat dissipates from

the optical sheet 250, thus advantageously preventing the optical sheet 250 from being creased.

[0077] The tenth distance d10 may range from 0.1 mm to 1 mm, and may preferably be 0.5 mm. Here, when the tenth distance d10 is longer than 0.1 mm, a margin sufficient to allow for thermal expansion of the optical sheet 250 may be provided, thus advantageously preventing the optical sheet 250 from being creased. When the tenth distance d10 is shorter than 1 mm, the tenth distance d10 between the fixing part 310 and the hole 251 may increase as the optical sheet 250 contracts as heat dissipates from the optical sheet 250, thus advantageously preventing the hole 251 from being released from the fixing part 310. For example, a length of slot or hole 251 may be 0.2 mm to 2 mm larger than a length of rail or fixing part 310.

[0078] The eleventh distance d11 and the twelfth distance d12 may range from 1 mm to 5 mm, and may preferably be 2 mm. Here, when the eleventh distance d11 and the twelfth distance d12 are longer than 1 mm, a margin sufficient to allow for thermal expansion of the optical sheet 250 may be provided, thus advantageously preventing the optical sheet 250 from being creased. When the eleventh distance d11 and the twelfth distance d12 are shorter than 5 mm, the eleventh distance d11 and the twelfth distance d12 between the fixing part 310 and the hole 251 may be lengthened, thus advantageously preventing the hole 251 and the fixing part 310 from being released. For example, a width of slot or hole 251 may be 2 mm to 5 mm larger than a width of rail or fixing part 310.

[0079] Moreover, the range of distances for d1 and d5 as described above are applicable when the LCD 100 is positioned horizontally. However, when the LCD is positioned vertically, for example, when mounted on a stand or on a wall for use, as enlarged portions 'C' and 'D' are positioned at the upper side 255 of the optical sheet 250, distances d1 and d5 will become zero. Further, in the vertical position, distances d2, d6, d10, and d9 will adjust accordingly.

[0080] Meanwhile, with reference to Figure 19, the one or more holes 251 of the optical sheet 250 may be formed to correspond to the periphery of an active area of the display panel 400. The active area of the display panel 400 may be an area on which an image is displayed, and the periphery of the active area of the display panel 400 may be an area between an outer edge of the active area of the display panel 400 and the cover 300. Here, the area between the outer edge of the active area and the cover 300 may refer to an area extending from the outer edge of the active area to the cover 300. For example, the area may include the cover 300. The holes 251 of the optical sheet 250 may be positioned between the display panel 400 and the cover 300, and may be fixedly coupled with the fixing parts 310 of the cover 300.

[0081] The holes 215 provided on the optical sheet 250 according to this embodiment may be positioned on the upper side 255 and the lower side 256 of the optical sheet

250, and the size of the holes 251 positioned on the upper side 255 of the optical sheet 250 may be different from that of the holes 251 positioned on the lower side 256 of the optical sheet 250. For example, the size of the holes 251 positioned on the upper side 255 of the optical sheet 250 may be smaller than the size of the holes 251 positioned on the lower side 256 of the optical sheet 250.

[0082] Figure 23 illustrates the hole 251 of the optical sheet 250 at a portion 'D' in Figure 19, Figure 24 illustrates the hole 251 of the optical sheet 250 at a portion 'E' in Figure 19, and Figure 25 illustrates the hole 251 of the optical sheet 250 at a portion 'C' in Figure 19. With reference to Figures 23 and 24, the length of a longer axis $\ell 1$ and a shorter axis $\ell 2$ of the hole 251 positioned on the upper side 255 of the optical sheet 250 illustrated in Figure 23 may be shorter than the length of a longer axis $\ell 3$ and a shorter axis $\ell 4$ positioned on the lower side 256 of the optical sheet 250 illustrated in Figure 24. Here, the longer axis of the hole 251 may be the longest axis in an x-axis direction of the hole 251, and the shorter axis of the hole 251 may be the shortest axis in a y-axis direction of the hole 251.

[0083] For example, the size of the hole 251 positioned on the upper side 255 of the optical sheet 250 may be smaller than the size of the hole 251 positioned on the lower side 256 of the optical sheet 250. Thus, as aforementioned, the hole 251 positioned on the upper side 255 of the optical sheet 250 may act as a reference point for fixing the optical sheet 250 to the cover 300 to prevent the optical sheet 250 from being deformed, for example, by heat, which may cause it to shift or move from its original position. Further, the hole 251 positioned on the lower side 256 of the optical sheet 250 may serve to provide a margin for thermal expansion when the optical sheet 250 is deformed by heat.

[0084] With reference to Figures 23 and 25, the length of the longer axis $\ell 1$ of the hole 251 positioned at a central portion of the upper side 255 of the optical sheet 250 illustrated in Figure 23 may be shorter than the length of the longer axis $\ell 5$ of the hole 251 positioned at the edge of the upper side 255 of the upper side 255 of the optical sheet 250 illustrated in Figure 25. Also, the length of the shorter axis $\ell 2$ of the hole 251 positioned at the central portion of the upper side 255 of the optical sheet 250 may be equal to the length of the shorter axis $\ell 6$ of the hole 251 positioned at the edge of the upper side 255 of the optical sheet 250.

[0085] For example, the size of the hole 251 positioned at the central portion of the upper side 255 of the optical sheet 250 may be smaller than that of the hole 251 positioned at the edge of the upper side 255 of the optical sheet 250. Thus, as previously discussed, the hole 251 positioned at the central portion of the upper side 255 of the optical sheet 250 may act as a reference point for fixing the optical sheet 250 to the cover 300 to prevent the optical sheet 250 from being deformed, shifted, or moved due to thermal expansion, while the hole 251 positioned at the edge of the upper side 255 of the optical

sheet 250 may serve to provide a margin for thermal expansion when the optical sheet 250 is deformed by heat.

[0086] In the foregoing description, simply for ease of explanation, the fixing parts 310 have been described as being provided on the cover 300 and shaped as a rail. However, the present invention is not limited thereto. For example, the fixing parts 310 may be provided on the bottom plate of the housing and may be formed in any appropriate shape as previously described.

[0087] Figures 26 and 27 are sectional views of the LCD according to the first embodiment. Specifically, Figure 26 is a vertical sectional view of the upper side of the cover perpendicular to a lengthwise direction, and Figure 27 is a vertical sectional view of the lateral side of the cover perpendicular to the lengthwise direction. As shown in Figures 26 and 27, the LCD 100 may be configured such that a liquid crystal display panel 400 is disposed on a front cover 300 and the optical sheet 250 is disposed on the liquid crystal display panel 400. The optical sheet 250 may be fixedly coupled with the cover 300. For example, the optical sheet 250 may be fixedly coupled with the cover 300 such that the hole 251 of the optical sheet 250 may be coupled with the fixing part 310 provided at the side wall of the cover 300.

[0088] The optical assembly 210 may be disposed on the optical sheet 250, and the cover 300 and a bottom plate 320 may be coupled by means of a screw 330. Here, as shown in Figure 26, at the upper side of the cover 300, a side portion of the bottom plate 320 may be inserted into a side portion of the cover 300. Meanwhile, as shown in Figure 27, at the lateral side of the cover 300, the bottom plate 320 may be mounted on the cover 300 and coupled by means of a screw 330.

[0089] As described above, in the LCD 100, the liquid crystal display panel 400, the optical sheet 250, and the optical assembly 210 may be received in the cover 300 and the bottom plate 320, and the hole 251 of the optical sheet 250 may be fixedly coupled to the fixing part 310 of the cover 300. Thus, the optical sheet 250 may be prevented from being deformed as it thermally contacts or expands due to heat generated from the light sources of the optical assembly 210. Therefore, light uniformity of the backlight unit may be improved.

Mode for the Invention

[0090] Figures 28 and 29 illustrate a backlight unit including light source assemblies according to a second embodiment. As shown in Figure 28, an LCD 500 according to this embodiment may include a bottom plate 510, an optical assembly 540, an optical sheet 560, and a liquid crystal display panel 580. The bottom plate 510 may receive the optical assembly 540 and the optical sheet 560 therein. The bottom plate 510 may also be a rear cover.

[0091] The optical assembly 540 received in the bottom plate 510 may include a first layer 541, light sources 542, light guide plates 543, and a reflective plate 544.

The first layer 541 may be a board (or substrate) on which a plurality of light sources 542 may be mounted. An electrode pattern may be formed on the first layer 541 to connect an adapter that may supply power and the light sources 542. The first layer 541 may be a PCB formed of polyethylene terephthalate (PET), glass, polycarbonate (PC), silicon (Si), or other appropriate materials, on which the plurality of light sources 542 may be mounted. The first layer 541 may be formed as a film.

[0092] The light sources 542 may be one of a light emitting diode (LED) chip and an LED package including at least one LED chip. In this embodiment, simply for ease of explanation, the light sources 542 will be described as being an LED package. The LED package constituting the light sources 542 may be classified into a top view type LED package and a side view type LED package depending on the direction of a light emission surface. The light sources 542 may be configured by using at least one of the top view type LED package in which a light emission surface may be formed toward the upper side and the side view type LED package in which the light emission surface may be formed toward the side.

[0093] The light guide plates 543 may be disposed in a direction in which light may be emitted from the light sources 542 and may serve to widely spread light formed incident from the light sources 542. In this embodiment, the light guide plate 543 may be configured such that a side contiguous with the light source 542 may include a step that may allow a neighboring light guide plate 543 to be mounted thereon. A lower surface of the light guide plate 543 may be formed to slope, or positioned at an angle, to upwardly reflect light received from the light source 542. The reflective plate 544 may be disposed on the lower surface of the light guide plate 543 and may serve to upwardly reflect light which may be reflected downward from the light guide plate 543.

[0094] The optical assembly 540 including the first layer 541, the light sources 542, the light guide plates 543, and the reflective plate 544 may implement light in an edge manner. A plurality of light source assemblies 540 may be provided in the LCD 500. With reference to Figure 29, the foregoing light source assemblies 540 may be coupled in a recess formed on the cover member 510. The light source assemblies 540 may be coupled to the entire lower surface of the bottom plate 510. Thus, because the light source assemblies 540 that implement light in an edge manner are formed on the entire lower surface of the bottom plate 510, they may function as a backlight unit that provides light in a direct manner.

[0095] As shown in Figure 28, the optical sheet 560 may be positioned on the plurality of light source assemblies 540 formed on the lower surface of the bottom plate 510. The optical sheet 560 may be a diffusion sheet that diffuses light or a prism sheet that concentrates light. Further, a plurality of optical sheets may be formed.

[0096] The optical sheet 560 may be mounted on the plurality of light source assemblies 540 and may be coupled to the fixing part 520 formed on the side wall of the

bottom plate 510. Here, as shown in Figures 4 to 14 according to the first embodiment, the optical sheet 560 may include a plurality of holes 565. Also, as shown in Figures 15 to 17 according to the first embodiment as described above, the bottom plate 510 may include a plurality of fixing parts 520.

[0097] Accordingly, as the holes 565 of the optical sheet 560 may be coupled to the fixing parts 520 formed on the side wall of the bottom plate 510, the optical sheet 560 may be fixed to the bottom plate 510. Thus, the optical sheet 560 may be prevented from being deformed as it contracts or expands due to heat generated from the light sources 542 of the optical assembly 540. Therefore, light uniformity of the backlight unit may be improved.

[0098] Figure 30 illustrates a direct type backlight unit. Referring to Figure 30, a backlight unit 600 may include a bottom plate 610, a reflective plate 620, light sources 630, a diffusion plate 650, and an optical sheet 650. The reflective plate 620 may be positioned on the entire inner surface of the bottom plate 610 and may serve to reflect light emitted from the light sources 630 upwards. The light sources 630 may be a CCFL (cold cathode fluorescent lamp), an HCFL (hot cathode fluorescent lamp), an EEFL (extended electrode fluorescent lamp), or other appropriate light source. A plurality of light sources may be positioned to be separated at predescribed intervals. The diffusion plate 640 may serve to diffuse linear light emitted from the light sources 630 and may change it into surface-type light. The optical sheet 650 may be positioned at an upper side of the diffusion plate 640.

[0099] The direct type backlight unit 600 as illustrated in Figure 30 may use a plurality of lamps having a large diameter as light sources, and may cause increase in the thickness of the space within the bottom plate 610 in which the light sources 630 are disposed. This may result in an increase in the thickness of the backlight unit 600. Accordingly, because there may be a relatively large space between the light sources 630 and the optical sheet 650, heat generated by the light sources 630 may be prevented from being transferred to the optical sheet 650. Thus, the optical sheet 650 may be protected from being deformed by the heat by the light sources 630.

[0100] Meanwhile, the backlight units according to the first and second embodiments may be configured to have the light source assemblies including very small LED light sources. For example, in the backlight unit according to the first embodiment as shown in Figure 3, the second layer 230 may be positioned to cover the light sources 217, the diffusion plate 240 may be formed contiguously on the second layer 230, and the optical sheet 250 may be positioned on the diffusion plate 240. Further, in the backlight unit according to the second embodiment as shown in Figure 28, the light sources 542 and the light guide plates 543 may be formed, and then the optical sheet 560 may be disposed on the light guide plates 543.

[0101] For example, the backlight units according to the first and second embodiments may have a relatively

thin structure as they may use very small LED light sources. Thus, the space between the LED light sources and the optical sheet may be very narrow. Heat discharged from the light sources, therefore, may be directly transferred to the optical sheet. In particular, in case of the backlight unit according to the first embodiment, there may not be sufficient space for releasing heat that is generated by the LED light sources. This may result in deformation of the optical sheet formed of a resin material as it contracts or expands due to the heat generated by the light sources.

[0102] Thus, in order to overcome this problem, in the first and second embodiments, the plurality of holes may be formed on the optical sheet and coupled to the plurality of fixing parts that may be formed on the bottom plate. Accordingly, a margin, allowing for thermal expansion of the optical sheet due to heat generated by the light sources, may be created between the holes and the fixing parts, thereby preventing possible creases in the optical sheet. Also, as the optical sheet contracts, the fixing parts may serve to apply tension to the optical sheet to prevent the optical sheet from contracting. Thus, deformation of the optical sheet may be prevented.

[0103] Figure 31 illustrates an LCD according to a third exemplary embodiment of the invention. As shown in Figure 31, an LCD 700 according to the third embodiment may include a bottom plate 710, an optical assembly 740, an optical sheet 760, and a liquid crystal display panel 780. The bottom plate 710 may receive the optical assembly 740 and the optical sheet 760 therein. The bottom plate 710 may be a rear cover member.

[0104] The optical assembly 740 received in the bottom plate 710 may include a first layer 741 and the light sources 742. The first layer 741 may be a board (or substrate) on which a plurality of light sources 742 may be mounted. An electrode pattern may be formed on the first layer 741 in order to connect an adapter that may supply power and the light sources 542. The first layer 741 may be a PCB formed of polyethylene terephthalate (PET), glass, polycarbonate (PC), silicon (Si), or other appropriate materials on which the plurality of light sources 742 may be mounted. The first layer 741 may be formed as a film.

[0105] The light sources 742 may be one of a light emitting diode (LED) chip and an LED package including at least one LED chip. In this embodiment, simply for ease of explanation, the light sources 742 will be described as being an LED package. The LED package constituting the light sources 742 may be classified into a top view type LED package and a side view type LED package depending on the direction of a light emission surface. The light sources 742 according to this embodiment may be configured by using at least one of the top view type LED package in which a light emission surface may be formed toward the upper side and the side view type LED package in which the light emission surface may be formed toward the lateral side.

[0106] A light guide plate 743 may be disposed in a

direction in which light may be emitted from the light sources 742 and may serve to widely spread light formed incident from the light sources 742. A reflective plate 744 may be disposed at a lower portion of the light guide plate 743 to reflect upwards light which may be reflected downward from the light guide plate 743. The optical assembly 740 including the first layer 741 and the light sources 742 may be positioned on the side of the bottom plate 710 as a backlight unit implementing light in an edge manner.

[0107] The optical sheet 760 may be positioned on the light guide plate 743. The optical sheet 760 may be a diffusion sheet that may diffuse light or a prism sheet that may concentrate light. A plurality of optical sheets may be formed. The optical sheet 760 may be mounted on the light guide plate 760 and may be coupled to the fixing part 720 formed on the side wall of the bottom plate 710. Here, as shown in Figures 4 to .14 according to the first embodiment as described above, the optical sheet 760 may include a plurality of holes 765. Also, as shown in Figures 15 to 17 according to the first embodiment as described above, the bottom plate 710 may include a plurality of fixing parts 720. Accordingly, as the holes 765 of the optical sheet 760 may be coupled to the fixing parts 720 formed on the side wall of the bottom plate 710, the optical sheet 760 may be fixed to the bottom plate 710. Thus, deformation of the optical sheet 760 may be prevented as it contracts or expands due to heat generated from the light sources 742 of the optical assembly 740. Accordingly, light uniformity of the backlight unit may be improved.

[0108] Figure 32 illustrates an edge type backlight unit. Referring to Figure 32, a backlight unit 800 may include a bottom plate 810, a reflective plate 820, light sources 830, a light guide plate 840, and an optical sheet 850. The reflective plate 820 may be positioned on an entire inner surface of the bottom plate 810 to serve to reflect upwards light emitted from the light sources 830. The light sources 830 may be a CCFL (cold cathode fluorescent lamp), an HCFL (hot cathode fluorescent lamp), an EEFL (extended electrode fluorescent lamp), or other appropriate light sources. The light sources 830 may be disposed at one side of the bottom plate 810.

[0109] The light guide plate 840 may be positioned on the side portion of the light sources 830 and on the entire surface of the bottom plate 810. The light guide plate 840 may also serve to reflect light emitted from the light sources 830 to change it into a surface-type light. The optical sheet 850 may be positioned at an upper side of the light guide plate 840.

[0110] The edge type backlight unit 800 illustrated in Figure 32 may use a plurality of lamps as light sources having a large diameter increasing the relative thickness of the space within the bottom plate 810 in which the light sources 830 are disposed. This may result in an increase in the overall thickness of the backlight unit 800. Accordingly, because there may be relatively large space between the light sources 830 and the optical sheet 850, heat generated by the light sources 830 may be prevented

ed from being transferred to the optical sheet 850. The optical sheet 850 may thus be protected from being deformed by the heat generated by the light sources 830.

[0111] Meanwhile, the backlight unit according to the third embodiment may be configured to have the light source assemblies including very small LED light sources. For example, the backlight unit according to the third exemplary embodiment of the invention may have a relatively thin structure in which the very small LED light sources may be used. Thus, the space between the LED light sources and the optical sheet may be very narrow. Accordingly, heat discharged from the light sources may be directly transferred to the optical sheet.

[0112] Also, in order to emit light with an equal luminance as that of the fluorescent lamp light sources, a large amount of current may be required by the LED light sources. In this case, as the applied current increases the amount of heat generated by the LED may also increase. Then, the optical sheets that are formed of a resin material may be deformed and may contract or expand due to heat emitted from the light sources.

[0113] Thus, in the edge type backlight unit according to the third embodiment, a plurality of holes may be formed at the optical sheet and a plurality of fixing parts may be formed at the bottom plate, wherein the holes of the optical sheet and the fixing parts of the bottom plate may be coupled to each other. Accordingly, a margin allowing for thermal expansion of the optical sheet due to heat generated by the light sources may be created between the holes and the fixing parts, thereby preventing possible creases in the optical sheet. Also, as the optical sheet contracts, the fixing parts may serve to apply tension to the optical sheet to prevent the optical sheet from contracting. Thus, deformation of the optical sheet may be prevented.

[0114] A display device is broadly described and embodied herein and may include a display panel having a plurality of electrodes and pixels; a backlight provided adjacent to the display panel, the backlight unit including at least one light guide panel having at least one light incident area to receive light from a first direction and a light emitting area to emit light received through the light incident area in a second direction, the first and second directions being different directions; at least one light source, at least one incident area of the light guide panel being adjacent to at least one light source to receive light output; and a reflector adjacent to the light guide panel to reflect light towards the second direction; and at least one optical sheet provided between the display panel and the backlight, the at least one optical sheet including a first optical sheet; and a cover provided adjacent to the display panel or the backlight, wherein the cover includes a first rail near a first side of the cover and a second rail near a second side of the cover, the first and second sides being opposite sides, the first optical sheet has a first slot near a first side and a second slot near a second side, the first and second sides being opposite sides of the first optical sheet, and the first slot is fitted over the

first rail and the second slot is fitted over the second rail.

[0115] The display device is disclosed wherein the first slot is smaller than the second slot; wherein the first and second rails have the same size; wherein when the display device is positioned to be vertical such that the second direction is perpendicular to a direction of gravity, the first slot of the first optical sheet hangs onto the first rail, and the second slot is provided loosely over the second slot.

[0116] The display device is disclosed wherein the first optical sheet includes a plurality of tab portions, a first tab portion extending from the first side of the optical sheet and the first slot being provided on the first tab portion, and a second tab portion extending from the second side of the optical sheet and the second slot being provided on the second tab portion; wherein the backlight is provided within a first area of the cover, and at least a portion of the first tab portion and the second tab portion are provided outside of the first area; and wherein the at least one light guide panel is provided within a first area of the cover, and the at least a portion of the first tab portion and the second tab portion are provided outside of the first area; wherein the at least one light guide panel is provided within a first area of the cover, and the at least a portion of the first tab portion and the second tab portion are provided outside of the first area.

[0117] The display device is disclosed wherein the cover further includes a third rail near a third side, which is between the first and second sides, and the first optical sheet further includes a third slot near the third side, which is between the first and second sides of the first optical sheet, the third slot being fitted over the third rail, and the third slot being bigger than the first slot; and wherein the first optical sheet includes a plurality of tab portions, a first tab portion extending from the first side of the optical sheet and the first slot being provided on the first tab portion, a second tab portion extending from the second side of the optical sheet and the second slot being provided on the second tab portion, and a third tab portion extending from the third side of the optical sheet and the third slot being provided on the third tab portion.

[0118] The display device is disclosed wherein the third rail has a first width and a first length and the third slot has a first width and a first length, the first width of the third slot being larger than the first width of the third rail by 2mm to 10mm, and the first length of the third slot being larger than the first length of the third rail by 0.15 mm to 1.3 mm; wherein the first rail has a first width and a first length and the first slot has a first width and a first length, the first width of the first slot being larger than the first width of the first rail by 0.2 mm to 2 mm, and the first length of the first slot being larger than the first length of the first rail by 0.15 mm to 1.3 mm; and wherein the second rail has a first width and a first length and the second slot has a first width and a first length, the first width of the second slot being larger than the first width of the second rail by 2mm to 10mm, and the first length of the second slot being larger than the first length of the second rail by 0.2 mm to 2 mm.

ond rail by 0.2 mm to 2 mm.

[0119] A display device comprises a display panel having a plurality of electrodes and pixels; a backlight provided adjacent to the display panel; at least one optical sheet provided between the display panel and the backlight, the at least one optical sheet including a first optical sheet; and a cover provided adjacent to the display panel or the backlight, wherein the cover includes a first rail near a first side of the cover and a second rail near a second side of the cover, the first and second sides being opposite sides, the first optical sheet has a first slot near a first side and a second slot near a second side, the first and second sides being opposite sides of the first optical sheet, the first slot is fitted over the first rail and the second slot is fitted over the second rail, and the first slot is smaller than the second slot.

[0120] The display device is disclosed wherein the first and second rails have the same size; wherein the first optical sheet includes a plurality of tab portions, a first tab portion extending from the first side of the optical sheet and the first slot being provided on the first tab portion, and a second tab portion extending from the second side of the optical sheet and the second slot being provided on the second tab portion; wherein the backlight is provided within a first area of the cover, and at least a portion of the first tab portion and the second tab portion are provided outside of the first area; and wherein the at least one light guide panel is provided within a first area of the cover, and the at least a portion of the first tab portion and the second tab portion are provided outside of the first area.

[0121] The display device is disclosed wherein the first rail has a first width and a first length and the first slot has a first width and a first length, the first width of the first slot being larger than the first width of the first rail by 0.2 mm to 2 mm, and the first length of the first slot being larger than the first length of the first rail by 0.15 mm to 1.3 mm; and wherein the second rail has a first width and a first length and the second slot has a first width and a first length, the first width of the second slot being larger than the first width of the second rail by 2mm to 10mm, and the first length of the second slot being larger than the first length of the second rail by 0.2 mm to 2 mm.

Claims

1. A display device (100) comprising:

a display panel (110) having a plurality of electrodes and pixels;
a backlight unit (120, 200) provided adjacent to the display panel (110), the backlight unit (120, 200) including:

at least one light guide panel (230) having at least one light incident area to receive light from a first direction and a light emitting

area to emit light received through the light incident area in a second direction, the first and second directions being different directions;

at least one light source (217), at least one incident area of the light guide panel (230) being adjacent to at least one light source (217) to receive light output;

a reflector (220) adjacent to the light guide panel (230) to reflect light towards the second direction; and

at least one optical sheet (250) provided between the display panel (110) and the backlight unit (120, 200), the at least one optical sheet (250) including a first optical sheet (250); and

a cover (300; 130; 135) provided adjacent to the display panel (110) or the backlight unit (120, 200),

wherein:

the cover (300) includes:

a plurality of first fixing parts (310) provided on and protruding from a first side wall (321) of the cover (300); and

at least one second fixing part (310) provided on and protruding from a second side wall (322) of the cover (300), wherein the first and second side walls (321, 322) are opposite each other and the first side wall (321) corresponds to an upper side of the display device (100);

the first optical sheet (250) has:

a plurality of first holes (251) formed on a first side (255) of the optical sheet (250); and

at least one second hole (251) formed on a second side (256) of the optical sheet (250);

wherein the first and second sides (255, 256) are opposite each

other and the first side (255) corresponds to an upper side of the display device (100);

each of the first holes (251) is fitted over one of the first fixing parts (310) and the second hole (251) is fitted over a second fixing part (310), and

characterized in that the number of the first holes (251) is greater than the number of the second holes (251); and

the fixing parts (310) are provided corresponding to the placement of the holes (251) of the optical sheet (250).

2. The display device of claim 1, wherein the first holes (251) are smaller than the second hole (251).

3. The display device of claim 2, wherein the first and second fixing parts (310) have the same size.

4. The display device of claim 1, wherein when the display device (100) is positioned to be vertical such that the second direction is perpendicular to the direction of gravity, the first holes (251) of the first optical sheet (250) hang onto the first fixing parts (310), and the second hole (251) is provided loosely over the second fixing part (310).

5. The display device of claim 1, wherein the first optical sheet (250) includes a plurality of tab portions (252), first tab portions (252) extending from the first side (255) of the optical sheet (250) and the first holes (251) being provided on the first tab portions (252), and at least one second tab portion (252) extending from the second side (256) of the optical sheet (250) and the at least one second hole (251) being provided on the second tab portion (252).

6. The display device of claim 5, wherein the backlight unit (120, 200) is provided within a first area of the cover (300), and at least a portion of each first tab portion (252) and the second tab portion (252) are provided outside of the first area.

7. The display device of claim 5, wherein the at least one light guide panel (230) is provided within a first area of the cover (300), and the at least a portion of each first tab portion (252) and the second tab portion (252) are provided outside of the first area.

8. The display device of claim 1, wherein the cover (300) further includes a third fixing part (310) provided on and protruding from a third side wall (323, 324), which is between the first and second side walls (321, 322), and the first optical sheet (250) further includes a third hole (251) provided on and protruding from a third side (257, 258), which is between the first and second sides (255, 256) of the first optical sheet (250), the third hole (251) being fitted over the third fixing part (310), and the third hole (251) being bigger than each of the first holes (251).

9. The display device of claim 8, wherein the first optical sheet (250) includes a plurality of tab portions (252), first tab portions (252) extending from the first side (255) of the optical sheet (250) and the first holes (251) being provided on the first tab portions (252), at least one second tab portion (252) extending from

the second side (256) of the optical sheet (250) and the second hole (251) being provided on the second tab portion (252), and a third tab portion (252) extending from the third side (257, 258) of the optical sheet (250) and the third hole (251) being provided on the third tab portion (252). 5

10. The display device of claim 8, wherein the third fixing part (310) has a first width and a first length and the third hole (251) has a first width and a first length, the first width of the third hole (251) being larger than the first width of the third fixing part (310) by 2mm to 10mm, and the first length of the third hole (251) being larger than the first length of the third fixing part (310) by 0.15 mm to 1.3 mm. 10 15
11. The display device of claim 1, wherein each first fixing part (310) has a first width and a first length and each first hole (251) has a first width and a first length, the first width of the first holes (251) being larger than the first width of the first fixing parts (310) by 0.2 mm to 2 mm, and the first length of the first holes (251) being larger than the first length of the first fixing parts (310) by 0.15 mm to 1.3 mm. 20 25
12. The display device of claim 1, wherein the second fixing part (310) has a first width and a first length and the second hole (251) has a first width and a first length, the first width of the second hole (251) being larger than the first width of the second fixing part (310) by 2mm to 10mm, and the first length of the second hole (251) being larger than the first length of the second fixing part (310) by 0.2 mm to 2 mm. 30 35

Patentansprüche

1. Anzeigevorrichtung (100) mit: 40
- einem Anzeigefeld (110), das eine Vielzahl Elektroden und Pixel aufweist, einer Hinterleuchtungseinrichtung (120, 200), die benachbart zum Anzeigefeld (110) vorhanden ist, wobei die Hinterleuchtungseinrichtung (120, 200) umfasst: 45
- wenigstens eine Lichtleitplatte (230) mit:
- wenigstens einer Lichteinfallfläche zum Aufnehmen von Licht aus einer ersten Richtung und einer Lichtemissionsfläche zum Emittieren von durch die Lichteinfallfläche aufgenommenem Licht in eine zweite Richtung, wobei die erste und zweite Richtung unterschiedliche Richtungen sind, 50 55

wenigstens eine Lichtquelle (217), wobei wenigstens eine Einfallfläche der Lichtleitplatte (230) benachbart zu wenigstens einer Lichtquelle (217) angeordnet ist, um ausgegebenes Licht aufzunehmen, einen Reflektor (220), der benachbart zur Lichtleitplatte (230) angeordnet ist, um Licht zur zweiten Richtung zu reflektieren, und wenigstens eine optische Folie (250), die zwischen dem Anzeigefeld (110) und der Hinterleuchtungseinrichtung (120, 200) vorhanden ist, wobei die wenigstens eine optische Folie (250) eine erste optische Folie (250) umfasst, und einer Abdeckung (300; 130; 135), die benachbart zum Anzeigefeld (110) oder zur Hinterleuchtungseinrichtung (120, 200) vorgesehen ist, wobei:

die Abdeckung (300) umfasst:

eine Mehrzahl erster Befestigungsteile (310), die an einer ersten Seitenwand (321) der Abdeckung (300) vorhanden sind und von dieser vorstehen, und wenigstens ein zweites Befestigungsteil (310), das an einer zweiten Seitenwand (322) der Abdeckung (300) vorhanden ist und von dieser vorsteht, wobei die erste und zweite Seitenwand (321, 322) einander entgegengesetzt sind und die erste Seitenwand (321) einer Oberseite der Anzeigevorrichtung (100) entspricht, 30 35

die erste optische Folie (250) umfasst:

eine Mehrzahl erster Löcher (251), die an einer ersten Seite (255) der optischen Folie (250) ausgebildet sind, und wenigstens ein zweites Loch (251), das an einer zweiten Seite (256) der optischen Folie (250) ausgebildet ist, wobei die erste und zweite Seite (255, 256) einander entgegengesetzt sind und die erste Seite (255) einer Oberseite der Anzeigevorrichtung (100) entspricht, 40 45

wobei die ersten Löcher (251) jeweils auf einem der Befestigungsteile (310) und das zweite Loch (251) auf einem zweiten Befestigungsteil (310) angebracht sind, und **dadurch gekennzeichnet, dass** die Anzahl der ersten Löcher (251) größer ist als die Anzahl der zweiten Löcher (251), und die Befestigungsteile (310) übereinstimmend mit der Platzierung der Löcher (251) der opti-

schen Folie (250) vorgesehen sind.

2. Anzeigevorrichtung nach Anspruch 1, bei der die ersten Löcher (251) kleiner sind als das zweite Loch (251).
3. Anzeigevorrichtung nach Anspruch 2, bei der die ersten und zweiten Befestigungsteile (310) die gleiche Größe haben.
4. Anzeigevorrichtung nach Anspruch 1, bei der, wenn die Anzeigevorrichtung (100) vertikal positioniert ist, so dass die zweite Richtung senkrecht zur Lotrichtung ist, die ersten Löcher (251) der ersten optischen Folie (250) an den ersten Befestigungsteilen (310) hängen und das zweite Loch (251) lose auf dem zweiten Befestigungsteil (310) angeordnet ist.
5. Anzeigevorrichtung nach Anspruch 1, bei der die erste optische Folie (250) eine Mehrzahl Ansatzabschnitte (252) umfasst, wobei sich erste Ansatzabschnitte (252) von der ersten Seite (255) der optischen Folie (250) erstrecken und die ersten Löcher (251) an den ersten Ansatzabschnitten (252) vorhanden sind, und wobei sich wenigstens ein zweiter Ansatzabschnitt (252) von der zweiten Seite (256) der optischen Folie (250) erstreckt und das wenigstens eine zweite Loch (251) am zweiten Ansatzabschnitt (252) vorhanden ist.
6. Anzeigevorrichtung nach Anspruch 5, bei der die Hinterleuchtungseinrichtung (120, 200) innerhalb einer ersten Fläche der Abdeckung (300) vorgesehen ist und wenigstens ein Abschnitt jedes ersten Ansatzabschnitts (252) und des zweiten Ansatzabschnitts (252) außerhalb der ersten Fläche vorgesehen sind.
7. Anzeigevorrichtung nach Anspruch 5, bei der die wenigstens eine Lichtleitplatte (230) innerhalb einer ersten Fläche der Abdeckung (300) vorgesehen ist und der wenigstens eine Abschnitt jedes ersten Ansatzabschnitts (252) und des zweiten Ansatzabschnitts (252) außerhalb der ersten Fläche vorgesehen sind.
8. Anzeigevorrichtung nach Anspruch 1, bei der die Abdeckung (300) ferner ein drittes Befestigungsteil (310) umfasst, das an einer dritten Seitenwand (323, 324) vorhanden ist und von dieser vorsteht, welche sich zwischen der ersten und zweiten Seitenwand (321, 322) befindet, und wobei die erste optische Folie (250) ferner ein drittes Loch (251) aufweist, das an einer dritten Seite (257, 258) bereitgestellt ist und von dieser vorsteht, welche sich zwischen der ersten und zweiten Seite (255, 256) der ersten optischen Folie (250) befindet, wobei das

dritte Loch (251) auf dem dritten Befestigungsteil (310) angebracht ist, und wobei das dritte Loch (251) größer ist als jedes der ersten Löcher (251).

9. Anzeigevorrichtung nach Anspruch 8, bei der die erste optische Folie (250) eine Mehrzahl Ansatzabschnitte (252) umfasst, wobei sich erste Ansatzabschnitte (252) von der ersten Seite (255) der optischen Folie (250) erstrecken und die ersten Löcher (251) an den ersten Ansatzabschnitten (252) vorhanden sind, wobei sich wenigstens ein zweiter Ansatzabschnitt (252) von der zweiten Seite (256) der optischen Folie (250) erstreckt und das zweite Loch (251) am zweiten Ansatzabschnitt (252) vorhanden ist, und wobei sich ein dritter Ansatzabschnitt (252) von der dritten Seite (257, 258) der optischen Folie (250) erstreckt und das dritte Loch (251) am dritten Ansatzabschnitt (252) vorhanden ist.
10. Anzeigevorrichtung nach Anspruch 8, bei der das dritte Befestigungsteil (310) eine erste Breite und eine erste Länge hat und das dritte Loch (251) eine erste Breite und eine erste Länge hat, wobei die erste Breite des dritten Lochs (251) um 2 mm bis 10 mm größer ist als die erste Breite des dritten Befestigungsteils (310), und wobei die erste Länge des dritten Lochs (251) um 0,15 mm bis 1,3 mm größer ist als die erste Länge des dritten Befestigungsteils (310).
11. Anzeigevorrichtung nach Anspruch 1, bei der jedes erste Befestigungsteil (310) eine erste Breite und eine erste Länge hat und jedes erste Loch (251) eine erste Breite und eine erste Länge hat, wobei die erste Breite der ersten Löcher (251) um 0,2 mm bis 2 mm größer ist als die erste Breite der ersten Befestigungsteile (310), und wobei die erste Länge der ersten Löcher (251) um 0,15 mm bis 1,3 mm größer ist als die erste Länge der ersten Befestigungsteile (310).
12. Anzeigevorrichtung nach Anspruch 1, bei der das zweite Befestigungsteil (310) eine erste Breite und eine erste Länge hat und das zweite Loch (251) eine erste Breite und eine erste Länge hat, wobei die erste Breite des zweiten Lochs (251) um 2 mm bis 10 mm größer ist als die erste Breite des zweiten Befestigungsteils (310), und wobei die erste Länge des zweiten Lochs (251) um 0,2 mm bis 2 mm größer ist als die erste Länge des zweiten Befestigungsteils (310).

Revendications

1. Dispositif d'affichage (100) comprenant :
un panneau d'affichage (110) comportant une

pluralité d'électrodes et de pixels ;
une unité de rétroéclairage (120, 200) prévue
adjacente au panneau d'affichage (110), l'unité
de rétroéclairage (120, 200) comprenant :

au moins un panneau de guidage de lumière (230) comportant
au moins une zone d'incidence de lumière
pour recevoir la lumière depuis une première
direction et une zone d'émission de lumière
pour émettre la lumière reçue à tra-
vers la zone d'incidence de lumière dans
une deuxième direction, les première et
deuxième directions étant des directions
différentes ;
au moins une source de lumière (217), au
moins une zone incidente du panneau de
guidage de lumière (230) étant adjacente à
au moins une source de lumière (217) pour
recevoir la lumière délivrée en sortie ;
un réflecteur (220) adjacent au panneau de
guidage de lumière (230) pour réfléchir la
lumière vers la deuxième direction ; et
au moins une feuille optique (250) prévue
entre le panneau d'affichage (110) et l'unité
de rétroéclairage (101, 200), la au moins
une feuille optique (250) comprenant une
première feuille optique (250) ; et
un couvercle (300 ; 130 ; 135) prévu adja-
cent au panneau d'affichage (110) ou à
l'unité de rétroéclairage (101, 200),
dans lequel :

le couvercle (300) comprend :

une pluralité de premières parties
de fixation (310) prévues sur et fai-
sant saillie depuis une première
paroi latérale (321) du couvercle
(300) ; et
au moins une deuxième partie de
fixation (310) prévue sur et faisant
saillie depuis une deuxième paroi
latérale (322) du couvercle (300),
dans lequel les première et deuxiè-
me parois latérales (321, 322) sont
opposées l'une à l'autre et la pre-
mière paroi latérale (321) corres-
pond à un côté supérieur du dispo-
sitif d'affichage (100) ;

la première feuille optique (250)
comporte :

une pluralité de premiers trous
(251) formés sur un premier côté
(255) de la feuille optique (250) ; et
au moins un deuxième trou (251)

formé sur un deuxième côté (256)
de la feuille optique (250) ;
dans laquelle les premier et
deuxième côtés (255, 256) sont
opposés l'un à l'autre et le premier
côté (255) correspond à un côté
supérieur du dispositif d'affichage
(100) ;


chacun des premiers trous (251) est
ajusté sur l'une des premières parties
de fixation (310) et le deuxième trou
(151) est ajusté sur une deuxième par-
tie de fixation (310), et

caractérisé en ce que le nombre de
premiers trous (251) est supérieur au
nombre de deuxième trous (251) ; et
les parties de fixation (310) sont pré-
vues pour correspondre au placement
des trous (251) de la feuille optique
(250).


2. Dispositif d'affichage selon la revendication 1, dans lequel les premiers trous (251) sont plus petits que le deuxième trou (251).
3. Dispositif d'affichage selon la revendication 2, dans lequel les premières et deuxième parties de fixation (310) présentent la même taille.
4. Dispositif d'affichage selon la revendication 1, dans lequel lorsque le dispositif d'affichage (100) est positionné pour être vertical d'une manière telle que la deuxième direction est perpendiculaire à la direction de gravité, les premiers trous (251) de la première feuille optique (250) s'accrochent aux premières parties de fixation (310), et le deuxième trou (251) est prévu de manière lâche sur la deuxième partie de fixation (310).
5. Dispositif d'affichage selon la revendication 1, dans lequel la première feuille optique (250) comprend une pluralité de parties de languettes (252), des premières parties de languettes (252) s'étendant à partir du premier côté (255) de la feuille optique (250) et les premiers trous (251) étant prévus sur les premières parties de languettes (252), et au moins une deuxième partie de languette (252) s'étendant depuis le deuxième côté (256) de la feuille optique (250) et le au moins un deuxième trou (251) étant prévu sur la deuxième partie de languette (252).
6. Dispositif d'affichage selon la revendication 5, dans lequel l'unité de rétroéclairage (120, 200) est prévue à l'intérieur d'une première zone du couvercle (300), et au moins une partie de chaque première partie de languette (252) et de la deuxième partie de languette (252) est prévue à l'extérieur de la première zone.

7. Dispositif d'affichage selon la revendication 5, dans lequel le au moins un panneau de guidage de lumière (230) est prévu à l'intérieur d'une première zone du couvercle (300), et la au moins une partie de chaque première partie de languette (252) et de la deuxième partie de languette (252) est prévue à l'extérieur de la première zone.
8. Dispositif d'affichage selon la revendication 1, dans lequel le couvercle (300) comprend en outre une troisième partie de fixation (310) prévue sur et faisant saillie depuis une troisième paroi latérale (323, 324), qui se situe entre les première et deuxième parois latérales (321, 322), et la première feuille optique (250) comprend en outre un troisième trou (251) prévu sur et faisant saillie depuis un troisième côté (257, 258), qui se situe entre les premier et deuxième côtés (255, 256) de la première feuille optique (250), le troisième trou (251) étant ajusté sur la troisième partie de fixation (310), et le troisième trou (251) étant plus gros que chacun des premiers trous (251).
9. Dispositif d'affichage selon la revendication 8, dans lequel la première feuille optique (250) comprend une pluralité de parties de languettes (252), les premières parties de languettes (252) s'étendant à partir du premier côté (255) de la feuille optique (250) et les premiers trous (251) étant prévus sur les premières parties de languettes (252), au moins une deuxième partie de languette (252) s'étendant à partir du deuxième côté (256) de la feuille optique (250) et le deuxième trou (251) étant prévu sur la deuxième partie de languette (252), et une troisième partie de languette (252) s'étendant à partir du troisième côté (257, 258) de la feuille optique (250) et le troisième trou (251) étant prévu sur la troisième partie de languette (252).
10. Dispositif d'affichage selon la revendication 8, dans lequel la troisième partie de fixation (310) présente une première largeur et une première longueur et le troisième trou (251) présente une première largeur et une première longueur, la première largeur du troisième trou (251) étant plus grande que la première largeur de la troisième partie de fixation (310) de 2 mm à 10 mm, et la première longueur du troisième trou (251) étant plus grande que la première longueur de la troisième partie de fixation (310) de 0,15 mm à 1,3 mm.
11. Dispositif d'affichage selon la revendication 1, dans lequel chaque première partie de fixation (310) présente une première largeur et une première longueur et chaque premier trou (251) présente une première largeur et une première longueur, la première largeur des premiers trous (251) étant plus grande que la première largeur des premières parties de fixation (310) de 0,2 mm à 2 mm, et la première longueur
- des premiers trous (251) étant plus grande que la première longueur des premières parties de fixation (310) de 0,15 mm à 1,3 mm.
12. Dispositif d'affichage selon la revendication 1, dans lequel la deuxième partie de fixation (310) présente une première largeur et une première longueur et le deuxième trou (251) présente une première largeur et une première longueur, la première largeur du deuxième trou (251) étant plus grande que la première largeur de la deuxième partie de fixation (310) de 2 mm à 10 mm, et la première longueur du deuxième trou (251) étant plus grande que la première longueur de la deuxième partie de fixation (310) de 0,2 mm à 2 mm.


[Fig. 1]




[Fig. 2]




[Fig. 3]




[Fig. 4]




[Fig. 5]




[Fig. 6]




[Fig. 7]




[Fig. 8]




[Fig. 9]




[Fig. 10]




[Fig. 11]




[Fig. 12]




[Fig. 13]




[Fig. 14]




[Fig. 15]




[Fig. 16]




[Fig. 17]




[Fig. 18]




[Fig. 19]




[Fig. 20]




[Fig. 21]




[Fig. 22]




[Fig. 23]




[Fig. 24]




[Fig. 25]




[Fig. 26]




[Fig. 27]




[Fig. 28]




[Fig. 29]




[Fig. 30]



[Fig. 31]



[Fig. 32]



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 2005254236 A [0006]
- US 2007297195 A [0007]

专利名称(译)	背光单元和包括其的液晶显示器		
公开(公告)号	EP2537064A4	公开(公告)日	2013-08-14
申请号	EP2010846223	申请日	2010-10-12
申请(专利权)人(译)	LG电子株式会社.		
当前申请(专利权)人(译)	LG电子株式会社.		
[标]发明人	KIM SANGJEON RYU SEONGHWAN		
发明人	KIM, SANGJEON RYU, SEONGHWAN		
IPC分类号	G02F1/13357 G02F1/1333 F21V8/00 G02F1/1335		
CPC分类号	G02F1/133608 G02B6/005 G02B6/0051 G02B6/0053 G02B6/0055 G02B6/008 G02B6/0085 G02B6/0088 G02F2001/133322		
代理机构(译)	拜尔 , ANDREAS		
优先权	1020100022199 2010-03-12 KR 61/306514 2010-02-21 US		
其他公开文献	EP2537064B1 EP2537064A1		
外部链接	Espacenet		

摘要(译)

液晶显示器包括液晶显示面板，背光和盖子。背光源包括光学片，该光学片构造使用设置在光学片上的多个孔安装到盖上，所述多个孔的材料是设置在盖上的相应突起。孔和突起被配置为减少可能由液晶显示器内部产生的热量引起的对光学片的损坏或未对准。