



(11) **EP 1 953 586 A1**

(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 158(3) EPC

(43) Date of publication:
06.08.2008 Bulletin 2008/32

(51) Int Cl.:
G02F 1/133 ^(2006.01) **G02F 1/1343** ^(2006.01)
G09G 3/20 ^(2006.01) **G09G 3/36** ^(2006.01)

(21) Application number: **06810401.7**

(86) International application number:
PCT/JP2006/318741

(22) Date of filing: **21.09.2006**

(87) International publication number:
WO 2007/034876 (29.03.2007 Gazette 2007/13)

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI
SK TR**

(30) Priority: **22.09.2005 JP 2005276419**

(71) Applicant: **Sharp Kabushiki Kaisha**
Osaka-shi, Osaka 545-8522 (JP)

(72) Inventors:
• **NARUSE, Yohichi**
Atsuta-ku,
Nagoya-shi,
Aichi 456-0002 (JP)

- **OCHI, Takashi**
Tenri-shi,
Nara 632-0082 (JP)
- **KUBO, Masumi**
Ikoma-shi,
Nara 630-0121 (JP)
- **YAMAMOTO, Akihiro**
Yamatokoriyama-shi,
Nara 639-1134 (JP)


(74) Representative: **Brown, Kenneth Richard et al**
R.G.C. Jenkins & Co.
26 Caxton Street
London SW1H 0RJ (GB)

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

(57) A liquid crystal display device includes a plurality of pixels each connected to a signal line via a switching element. Each pixel includes first and second sub-pixels having voltage vs. luminance characteristics different from each other with respect to a signal voltage supplied from the signal line. A threshold signal voltage of the first sub-pixel is lower than that of the second sub-pixel. The

pixels form color display pixels which are red, green pixel and blue pixels. Where the area ratio of the first sub-pixel in each of the red, green and blue pixels is SR1, SG1 and SB1, and the ratio of the lighting-up time period of the first sub-pixel of each of the red, green and blue pixels in one vertical scanning period is TR1, TG1 and TB1, the relationship of $(SR1 \times TR1) > (SG1 \times TG1) > (SB1 \times TB1)$ holds.

FIG.5



Description

TECHNICAL FIELD

[0001] The present invention relates to a liquid crystal display device, and specifically to a color liquid crystal display device.

BACKGROUND ART

[0002] Liquid crystal display devices have recently been improved in the display quality and are now widely used for TVs, but are still strongly desired to be further improved in the display quality.

[0003] One problem unique to liquid crystal display devices is that the display quality varies in accordance with the angle at which the display is observed (viewing angle), namely, that the so-called viewing angle characteristic is lowered. In conventional TN mode liquid crystal display devices, the grayscale is occasionally inverted. The liquid crystal display devices which are widely used today can display images at a contrast ratio of 10 or greater in a relatively wide viewing angle range, but still have the problem that the grayscale characteristic (γ characteristic) is dependent on the viewing angle.

[0004] In order to solve this problem, the so-called pixel division technique is proposed. "Pixel division" refers to a method by which the luminance, that is conventionally displayed with one pixel, is displayed with 2 or more sub-pixels obtained by dividing one pixel in a space-wise or time-wise manner. The two or more sub-pixels include at least a bright sub-pixel displaying a luminance higher than the luminance to be displayed and a dark sub-pixel displaying a luminance lower than the luminance to be displayed. The technique of space-wise pixel division is described in, for example, Patent Documents 1 through 3. The technique of time-wise pixel division is described in, for example, Patent Document 4.

Patent Document 1: Japanese Laid-Open Patent Publication No. 2004-62146

Patent Document 2: Japanese Laid-Open Patent Publication No. 2004-78157

Patent Document 3: Japanese Laid-Open Patent Publication No. 2005-189804

Patent Document 4: Japanese Laid-Open Patent Publication No. 2005-173573

Non-patent Document 1: Shinpen Shikisai Kagaku Handbook (Color Science Handbook, Revised) (2nd ed.), edited by the Color Science Association of Japan, published by University of Tokyo Press, pp. 1026-1027, 1303 (1998)

DISCLOSURE OF THE INVENTION

PROBLEMS TO BE SOLVED BY THE INVENTION

[0005] However, the viewing angle dependence of the

grayscale characteristic (also referred to as the " γ characteristic") cannot be completely compensated for even by using the techniques described in Patent Documents 1 through 4.

[0006] This problem will be described with the technique of space-wise pixel division described in Patent Documents 1 through 3 with reference to FIG. 1.

[0007] FIG. 1(a) schematically shows a structure of one pixel P_0 of a conventional liquid crystal display device of the vertical alignment mode (VA mode) with no pixel division. FIG. 1(b) is a graph schematically showing the input grayscale vs. luminance characteristic thereof. FIG. 1(c) schematically shows a structure of one pixel P of a liquid crystal display device of the VA mode having a pixel division structure. FIG. 1(d) is a graph schematically showing the input grayscale vs. luminance characteristic thereof.

[0008] The conventional VA mode liquid crystal display device shown in FIG. 1(a) has the input grayscale vs. luminance characteristic shown in FIG. 1(b). In order to obtain a prescribed luminance at a front viewing angle (in the direction normal to the display screen), the grayscale characteristic is set to be represented by, for example, a curve of $\gamma = 2.2$. However, when the viewing angle (polar angle from the direction normal to the display screen) is 45° (such a viewing angle will be referred to as the "oblique 45° viewing angle"), the grayscale characteristic significantly deviates from the curve of $\gamma = 2.2$. The azimuth angle direction representing the grayscale characteristic of FIG. 1(b) is parallel or perpendicular to the transmission axes of a pair of polarizing plates, which are located in a crossed Nicols state while having a liquid crystal layer therebetween. In the following description, the azimuth angle direction is as described above unless otherwise specified.

[0009] By contrast, as shown in FIG. 1(c), in a liquid crystal display device described in Patent Documents 1 through 3 in which one pixel P includes a first sub-pixel $SP1$ and a second sub-pixel $SP2$, the deviation of the grayscale characteristic at the oblique 45° viewing angle from the grayscale characteristic at the front viewing angle (the curve of $\gamma = 2.2$) is smaller.

[0010] For example, it is assumed that the first sub-pixel is a bright sub-pixel displaying a luminance higher than the luminance to be displayed, and the second sub-pixel is a dark sub-pixel displaying a luminance lower than the luminance to be displayed. In FIG. 1(d), the part on the low grayscale side is mainly governed by the characteristic of the first sub-pixel $SP1$, and the part on the high grayscale side is mainly governed by the characteristic of the second sub-pixel $SP2$. In consideration of the transmittance (grayscale) characteristic of the two sub-pixels with respect to the signal voltage supplied to the pixel P (V-T characteristic), the first sub-pixel $SP1$ has a lower optical threshold voltage V_{0th} and the second sub-pixel $SP2$ has a higher optical threshold voltage V_{0th} .

[0011] As described in Patent Documents 1 through 3, in a structure in which a bright sub-pixel and a dark

sub-pixel are formed by providing the two sub-pixels with storage capacitances electrically independent from each other and thus making a difference between the voltages to be supplied to the storage capacitance counter electrodes of the storage capacitances, there are advantages that a signal voltage can be supplied from a signal line common to the two sub-pixels **SP1** and **SP2** and a common scanning line is usable (for example, Figure 12 of Patent Document 1). This structure is also highly effective in improving the grayscale characteristic on the low grayscale side (the side closer to the black display) and thus is highly effective in improving the display quality. In this structure, the other electrodes of the storage capacitances (storage capacitance electrodes) are supplied with a voltage which is the same as the signal voltage supplied from the signal line to the sub-pixels.

[0012] As represented by the grayscale characteristic in FIG. 1(d), the viewing angle dependence of the grayscale characteristic is lowered but the curve at the oblique 45° viewing angle matches the curve at the front viewing angle only at one point (in a very small range). Namely, at a specific grayscale level, the luminance scarcely changes even when the viewing angle is inclined; whereas at the other grayscale levels, the luminance changes when the viewing angle is inclined (when the polar angle is increased). Such a change in the luminance appears as a color change in color display.

[0013] Needless to say, it is possible to further lower the viewing angle dependence of the grayscale characteristic (color reproducibility) by increasing the number of sub-pixels into which the pixel is divided in a space-wise or time-wise manner, but this naturally raises the cost. In order to present a liquid crystal display device capable of displaying high quality images at a reasonable price to the market, it is desired to improve the grayscale characteristic (color reproducibility) without increasing the number of sub-pixels into which the pixel is divided.

[0014] The present invention made in light of the above-described points has an object of lowering the viewing angle dependence of the grayscale characteristic (color reproducibility) of a liquid crystal display device without increasing the number of sub-pixels into which the pixel is divided by a pixel division structure.

MEANS FOR SOLVING THE PROBLEMS

[0015] A liquid crystal display device according to the present invention includes a plurality of pixels each connected to a signal line via a switching element. Each of the plurality of pixel includes a first sub-pixel and a second sub-pixel having voltage vs. luminance characteristics different from each other with respect to a signal voltage supplied from the signal line, a threshold signal voltage of the first sub-pixel being lower than that of the second sub-pixel. The plurality of pixels form color display pixels including a red pixel, a green pixel and a blue pixel. Where the area ratio of the first sub-pixel in each of the red pixel, the green pixel and the blue pixel is SR1, SG1 and SB1,

and the ratio of a time period in which the first sub-pixel of each of the red pixel, the green pixel and the blue pixel is lit up with respect to one vertical scanning period is TR1, TG1 and TB1, the relationship of $(SR1 \times TR1) > (SG1 \times TG1) > (SB1 \times TB1)$ holds.

[0016] In one embodiment, it is preferable that the relationships of $0.15 < (SR1 \times TR1) \leq 1.00$, $0.03 < (SG1 \times TG1) < 0.75$, and $0.02 < (SB1 \times TB1) < 0.71$ are fulfilled. Furthermore, it is preferable that the relationships of $0.42 < \text{red } (SR1 \times TR1) \leq 0.95$, $0.22 < \text{green } (SG1 \times TG1) < 0.78$, and $0.15 < \text{blue } (SB1 \times TB1) < 0.44$ are fulfilled.

[0017] In one embodiment, it is preferable that the red pixel has a point, at which an input grayscale vs. luminance curve at the front viewing angle matches an input grayscale vs. luminance curve at the oblique 45° viewing angle, within the grayscale level range of 105/255 or greater and 255/255 or less; the G pixel has a point, at which the input grayscale vs. luminance curve at the front viewing angle matches the input grayscale vs. luminance curve at the oblique 45° viewing angle, within the grayscale level range of 52/255 or greater and 223/255 or less; and the B pixel has a point, at which the input grayscale vs. luminance curve at the front viewing angle matches the input grayscale vs. luminance curve at the oblique 45° viewing angle, within the grayscale level range of 44/255 or greater and 217/255 or less.

[0018] In one embodiment, the ratio of the time period in which the first sub-pixel of each of the red pixel, the green pixel and the blue pixel is lit up with respect to one vertical scanning period, i.e., TR1, TG1 and TB1, are each 1.00.

EFFECTS OF THE INVENTION

[0019] In a liquid crystal display device according to the present invention, the area ratio and/or the ratio of the lighting-up time period of the sub-pixel is set such that the skin color reproducibility does not change in accordance with the viewing angle. Therefore, the viewing angle dependence of the grayscale characteristic (color reproducibility) of the liquid crystal display device can be decreased without increasing the number of sub-pixels into which a pixel is divided by a pixel division structure.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020]

[FIG. 1] (a) schematically shows a structure of one pixel **P**₀ of a conventional liquid crystal display device of the vertical alignment mode (VA mode) with no pixel division; (b) is a graph schematically showing the input grayscale vs. luminance characteristic thereof; (c) schematically shows a structure of one pixel **P** of a liquid crystal display device of the VA mode having a pixel division structure; and (d) is a graph schematically showing the input grayscale vs.

luminance characteristic thereof.

[FIG. 2] FIG. 2 shows a skin color distribution of Japanese men and women shown in the CIE color system, which is converted from the Muncell color system.

[FIG. 3] FIG. 3 shows the reason why the color reproducibility of the skin color is decreased depending on the viewing angle in a conventional pixel division structure.

[FIG. 4] FIG. 4 is a graph showing the grayscale characteristics where the area ratio between a first sub-pixel **SP1** and a second sub-pixel **SP2** is 1:1 in the conventional pixel division structure.

[FIG. 5] FIG. 5 is a graph showing the grayscale characteristics of an R pixel of a liquid crystal display device according to an embodiment of the present invention.

[FIG. 6] FIG. 6 is a graph showing the grayscale characteristics of a G pixel of the liquid crystal display device according to the embodiment of the present invention.

[FIG. 7] FIG. 7 is a graph showing the grayscale characteristics of a B pixel of the liquid crystal display device according to the embodiment of the present invention.

[FIG. 8] FIG. 8 schematically shows a structure of one pixel **10** of a liquid crystal display device **100** according to another embodiment of the present invention.

DESCRIPTION OF THE REFERENCE NUMERALS

[0021]

10 Pixel

10a, 10b Sub-pixel

12a, 12b Scanning line

14 Signal line

16a, 16b TFT

18a, 18b Sub-pixel electrode

100 Liquid crystal display device

BEST MODE FOR CARRYING OUT THE INVENTION

[0022] The present inventors made studies on the improvement of the grayscale characteristic (color reproducibility) while the number of sub-pixels into which one pixel is divided is kept relatively small, e.g., while the number of sub-pixels is the minimum number of 2.

[0023] For the color reproducibility of a display device, memory colors are considered important. In most cases, an image displayed on a display device cannot be directly compared with a subject of display. Therefore, the relationship between the displayed image and the image memorized by the observer is important. For a display device used for TVs, the color of the skin of humans (hereinafter, referred to as the "skin color") is considered especially important among memory colors (see, for exam-

ple, Non-patent Document 1).

[0024] FIG. 2 shows a skin color distribution of Japanese men and women in the CIE color system, which is converted from the Muncell color system shown on page 1303 of Non-Patent Document 1. As understood from FIG. 2, the skin colors of Japanese men and women are existent in the range which has x and y of $0.3 \leq x, y \leq 0.5$ and also is sandwiched between straight lines A and B. According to Jamie Sherrah et al., the skin color is existent in a range limited in accordance with the hue regardless of the ethnicity (see, for example, http://homepages.inf.ed.ac.uk/rbf/CVonline/LOCAL_COPIES/GONG1/cvOnline-skinColourAnalysis.html, Fig. 1). According to the study of the present inventors, the hue range of the skin color shown in Fig. 1 of the above webpage mostly matches the range shown in FIG. 2.

[0025] The present inventors sampled 25 skin colors (of the ethnicities including white, black and yellow races) from various images and displayed each skin color with grayscale levels of three primary colors of R (red), G (green) and B (blue) (256 grayscale levels from level 0 through level 255). The results are shown in Table 1. Table 1 also shows the maximum value and the minimum value of each primary color.

[0026] [Table 1]

Skin color	R	G	B
1	208	144	105
2	226	180	150
3	192	154	130
4	192	156	129
5	194	154	136
6	233	190	165
7	119	93	83
8	203	141	121
9	218	177	151
10	152	97	66
11	182	124	96
12	255	201	175
13	180	154	138
14	184	162	151
15	171	128	111
16	180	139	119
17	208	145	130
18	141	96	77
19	173	120	112
20	159	101	94
21	184	125	121

(continued)

Skin color	R	G	B
22	136	89	61
23	206	171	151
24	246	223	217
25	105	52	44
max	255	223	217
min	105	52	44

[0027] As understood from Table 1, the grayscale levels of R, G and B are different from one another. In addition, the range of the grayscale levels (the range from the minimum level to the maximum level) are quite large as follows: the range is from level 105 to level 255 for R, from level 52 to level 233 for G, and from level 44 to level 217 for B. It is also understood that the grayscale levels of the three primary colors for each skin color is in the order of $R > G > B$ from the highest to the lowest.

[0028] Now, a case where a skin color is displayed on a liquid crystal display device having the grayscale characteristic shown in FIG. 1 will be discussed. Referring to FIG. 3, it is assumed that the displayed skin color has the grayscale levels represented by the positions on the horizontal axis of the R, G and B columns. When the display is observed at the oblique 45° viewing angle, the luminance of each of R, G and B changes by the amount represented by the corresponding column. Namely, the luminance of G scarcely changes, whereas the luminance of R and B significantly changes. In other words, when the viewing angle is inclined, the skin color appears differently.

[0029] As described above, the skin color is especially important as a memory color. Therefore, when the skin color reproducibility is poor, the observer considers that the reproducibility of the display device is poor. In order to solve the problem of the poor skin color reproducibility, the viewing angle dependence of the grayscale characteristic is improved using the pixel division technique as follows. The viewing angle dependence is improved for a grayscale level, of each of the three primary colors, which is important for the skin color reproducibility. Namely, instead of providing all the pixels with the same grayscale characteristic, the R pixel, G pixel and B pixel are provided with different grayscale characteristics, respectively.

[0030] Hereinafter, an embodiment using the pixel division technique described in Patent Documents 1 through 3 will be described.

[0031] In this embodiment, a plurality of pixels P in the liquid crystal display device each include a first sub-pixel **SP1** and a second sub-pixel **SP2**. The first sub-pixel **SP1** and the second sub-pixel **SP2** are connected to a signal line via a switching element (e.g., a TFT), and have voltage vs. luminance characteristics different from each other

with respect to the voltage of the signal supplied from the signal line. In this example, the first sub-pixel **SP1** has a threshold signal voltage lower than that of the second sub-pixel **SP2**. Namely, the first sub-pixel **SP1** is a bright sub-pixel displaying a luminance higher than the luminance to be displayed by the pixel, and the second sub-pixel **SP2** is a dark sub-pixel displaying a luminance lower than the luminance to be displayed by the pixel.

[0032] The plurality of pixels P form color display pixels. Each of the color display pixels consists of an R pixel, a G pixel and a B pixel. The color display pixel is the minimum unit of color display. The R pixels, the G pixels and the B pixels are arranged in, for example, stripes. The area ratio between the first sub-pixel **SP1** and the second sub-pixel **SP2** is different among the R pixel, the G pixel and the B pixel. Where the ratio of the area of the first sub-pixel **SP1** with respect to the total area of each of the R pixel, the G pixel and the B pixel is $SR1$, $SG1$ and $SB1$, the relationship of $SR1 > SG1 > SB1$ holds. Where the ratio of the area of the second sub-pixel **SP2** with respect to the total area of each of the R pixel, the G pixel and the B pixel is $SR2$, $SG2$ and $SB2$, the relationship of $SR2 < SG2 < SB2$ holds because $SR2 = 1 - SR1$, $SG2 = 1 - SG1$, and $SB2 = 1 - SB1$.

[0033] Where the R pixel, the G pixel and the B pixel are formed such that the area ratios of the first sub-pixel **SP1** fulfill the relationship of $SR1 > SG1 > SB1$, the grayscale level, at which the viewing angle dependence of the grayscale characteristic is most improved by the pixel division structure, is highest for red, next highest for green and lowest for blue. This matches the above-described order of the grayscale levels of red, green and blue for the skin colors.

[0034] As an example, FIG. 4 shows the grayscale characteristics in the case where the area ratio between the first sub-pixel **SP1** and the second sub-pixel **SP2** is 1:1. FIG. 4 shows the grayscale characteristics at the front viewing angle, the oblique 45° viewing angle, and the oblique 60° viewing angle. As described above with reference to FIG. 3, where the R, G and B pixels each have the grayscale characteristic shown in FIG. 4, when the viewing angle is increased, the skin color reproducibility is decreased.

[0035] By contrast, in the liquid crystal display device in this embodiment, for example, $SR1$ is set to 0.54, $SG1$ is set to 0.27, and $SB1$ is set to 0.20. FIG. 5 shows the grayscale characteristics of the R pixel, FIG. 6 shows the grayscale characteristics of the G pixel, and FIG. 7 shows the grayscale characteristics of the B pixel. FIGS. 5 through 7 show the grayscale characteristics at the front viewing angle, the oblique 45° viewing angle, and the oblique 60° viewing angle.

[0036] As shown in FIG. 5, in the case of the R pixel having the $SR1$ of 0.54, the grayscale characteristics at the oblique 45° viewing angle and the oblique 60° viewing angle match the grayscale characteristic at the front viewing angle (in this example, a curve of $\gamma = 2.2$) when the input grayscale level is 192/255 or the vicinity thereof.

[0037] As shown in FIG. 6, in the case of the G pixel having the SG1 of 0.27, the grayscale characteristics at the oblique 45° viewing angle and the oblique 60° viewing angle match the grayscale characteristic at the front viewing angle when the input grayscale level is 140/255 or the vicinity thereof.

[0038] As shown in FIG. 7, in the case of the B pixel having the SB1 of 0.20, the grayscale characteristics at the oblique 45° viewing angle and the oblique 60° viewing angle match the grayscale characteristic at the front viewing angle when the input grayscale level is 120/255 or the vicinity thereof.

[0039] Accordingly, in the liquid crystal display device according to this embodiment of the present invention in which the SR1 = 0.54, SG1 = 0.27 and SB1 = 0.20, the color reproducibility of the skin color represented with an R pixel having a grayscale level of 192/255 or the vicinity thereof, a G pixel having a grayscale level of 140/255 or the vicinity thereof, and a B pixel having a grayscale level of 120/255 or the vicinity thereof scarcely depends on the viewing angle.

[0040] From the results shown in Table 1, the viewing angle dependence of the skin color reproducibility can be decreased in the following case: the R pixel has the point, at which the input grayscale vs. luminance curve at the front viewing angle matches the input grayscale vs. luminance curve at the oblique 45° viewing angle, within the grayscale level range of 105/255 or greater and 255/255 or less; the G pixel has the point, at which the input grayscale vs. luminance curve at the front viewing angle matches the input grayscale vs. luminance curve at the oblique 45° viewing angle, within the grayscale level range of 52/255 or greater and 223/255 or less; and the B pixel has the point, at which the input grayscale vs. luminance curve at the front viewing angle matches the input grayscale vs. luminance curve at the oblique 45° viewing angle, within the grayscale level range of 44/255 or greater and 217/255 or less. The "point at which the input grayscale vs. luminance curve at the front viewing angle matches the input grayscale vs. luminance curve at the oblique 45° viewing angle" is considered to be the point at which the voltage applied to the second sub-pixel reaches the threshold signal voltage. Therefore, in order to fulfill the above-described relationships, SR1, SG1 and SB1 need to fulfill the relationships of $0.15 < SR1 \leq 1.00$, $0.03 < SG1 < 0.75$, and $0.02 < SB1 < 0.71$ as shown in Table 2.

[0041] [Table 2]

	Dark		Bright	
	A	B	A	B
R	0.15	0.85	1	0
G	0.03	0.97	0.75	0.25
B	0.02	0.98	0.71	0.29

[0042] In addition, from the viewpoint that the skin color of young women deviates less than the memory colors (Hideaki CHIJIWA, Shikisaigaku Gairon (An Outline of Color Science), Tokyo University Press, page 130), it is more preferable to fulfill the relationships of $0.42 < SR1 \leq 0.95$, $0.22 < SG1 < 0.78$, and $0.15 < SB1 < 0.44$. The "point at which the input grayscale vs. luminance curve at the front viewing angle matches the input grayscale vs. luminance curve at the oblique viewing angle" refers to a point at which the luminance at the oblique viewing angle is within $\pm 1\%$ of the luminance at the front viewing angle. Where the luminance at the oblique viewing angle is within $\pm 1\%$ of the luminance at the front viewing angle, a change of even a skin color which is important as a memory color is scarcely recognized. The oblique viewing angle (polar angle) may be any angle up to 45° because this range of angles encompasses most forms of usual TV uses. In uses where a wider viewing angle is especially desired, it is desirable that the grayscale characteristic at the oblique 60° viewing angle matches the grayscale characteristic at the front viewing angle. It is not absolutely necessary that the input grayscale vs. luminance curve at the front viewing angle should match the input grayscale vs. luminance curve at the oblique viewing angle. As long as the point at which the voltage applied to the second sub-pixel reaches the threshold signal voltage is within the above-described range, a change of the skin color is prevented from being recognized.

[0043] In the above embodiment, the grayscale level at which the viewing angle characteristic is optimized is adjusted by changing the area ratio between the first sub-pixel SP1 and the second sub-pixel SP2 of each of the three primary colors (in this example, R, G and B). Substantially the same effect is provided by adjusting the ratio of the time period in which the first sub-pixel SP1 is lit up with respect to one vertical scanning period. The "one vertical scanning period" is a period defined for the liquid crystal display device and is not a period defined by the input video signal. The "one vertical scanning period" refers to a period from when a signal voltage is supplied to a certain pixel until a signal voltage is supplied the next time. For example, one frame of an NTSC signal is 33.3 ms, but generally in liquid crystal display devices, signal voltages are written to all the pixels within 1/2 frame of the NTSC signal, i.e., within 1 field (16.7 ms). In this case, one vertical scanning period of the liquid crystal display device is 16.7 ms. When the liquid crystal display device is driven at twice the speed for the purpose of, for example, improving the response characteristic, one vertical scanning period of the liquid crystal display device is further halved to 8.4 ms.

[0044] Now, another embodiment according to the present invention in which the pixel division structure described in Patent Documents 1 through 3 is adopted as in the above embodiment and also time division is adopted will be described below.

[0045] FIG. 8 schematically shows a structure of one

pixel **10** of a liquid crystal display device 100 according to such another embodiment of the present invention.

[0046] The pixel **10** is divided into sub-pixels **10a** and **10b**, and the sub-pixels **10a** and **10b** are respectively connected to TFTs **16a** and **16b** and storage capacitances (CS) **22a** and **22b**. Gate electrodes of the TFTs **16a** and **16b** are respectively connected to scanning lines **12a** and **12b**, and source electrodes of the TFTs **16a** and **16b** are connected to a common (same) signal line **14**. The storage capacitances **22a** and **22b** are respectively connected to storage capacitance lines (CS bus lines) **24a** and **24b**. The storage capacitances **22a** and **22b** are respectively formed of storage capacitance electrodes electrically connected to sub-pixel electrodes **18a** and **18b** respectively, storage capacitance counter electrodes electrically connected to the storage capacitance lines **24a** and **24b** respectively, and an insulating layer (not shown) provided between the storage capacitance electrodes and the storage capacitance counter electrodes. The storage capacitance counter electrodes of the storage capacitances **22a** and **22b** are independent from each other and are respectively supplied with storage capacitance counter voltages, different from each other, from the storage capacitance lines **24a** and **24b**. The electric connections of this liquid crystal display device are the same as those in the above described embodiment (Figure 12 of Patent Document 1) except that the gate electrodes of the TFTs **16a** and **16b** are respectively connected to scanning lines **12a** and **12b**, which are independent from each other.

[0047] In the liquid crystal display device **100** in this embodiment, the TFT **16a** of the sub-pixel **10a** and the TFT **16b** of the sub-pixel **10b** are respectively connected to the scanning lines **12a** and **12b**, which are electrically independent from each other. Therefore, the time to start lighting up the sub-pixel **10a** can be shifted from the time to start lighting up the sub-pixel **10b**. Thus, the ratio of the time period in which the sub-pixel **10a** is lit up with respect to one vertical scanning period can be adjusted. It is here assumed that the sub-pixel **10a** is the first sub-pixel **SP1**, the sub-pixel **10b** is the second sub-pixel **SP2**, and the ratio of the lighting-up time period of the first sub-pixel **SP1** with respect to one vertical scanning period in each of the R pixel, the G pixel and the B pixel is TR1, TG1 and TB1. Where TR1, TG1 and TB1 are adjusted to be TR1 > TG1 > TB1, the same effect as that of the above embodiment can be provided even when the area ratio between the first sub-pixel **SP1** and the second sub-pixel **SP2** is 1:1 in all the R pixel, the G pixel and the B pixel. Namely, the area ratio (e.g., SR1) in the above embodiment and the ratio of the lighting-up time period (e.g., TR1) in this embodiment are equivalent in the influence made on the grayscale characteristic.

[0048] Accordingly, the liquid crystal display device **100** in the shown in FIG. 8 can have a combination of the above two embodiments by adjusting the area ratio between the sub-pixels **10a** and **10b**.

[0049] It is assumed that the area ratio of the first sub-

pixel **SP1** in each of the R pixel, the G pixel and the B pixel is SR1, SG1 and SB1, and the ratio of the lighting-up time period of the first sub-pixel **SP1** with respect to one vertical scanning period in each of the R pixel, the G pixel and the B pixel is TR1, TG1 and TB1. The above two embodiments can be combined by fulfilling the relationship of $(SR1 \times TR1) > (SG1 \times TG1) > (SB1 \times TB1)$. Alternatively, the above two embodiments can be combined by adjusting the area ratio and/or the ratio of the lighting-up time period of the sub-pixel so as to fulfill the relationships of $0.15 < (SR1 \times TR1) \leq 1.00$, $0.03 < (SG1 \times TG1) < 0.75$, and $0.02 < (SB1 \times TB1) < 0.71$. In the case where the structure in which only the area ratio is adjusted, namely, the structure in which TR1, TG1 and TB1 are each 1.00 is adopted, there is an advantage that the two sub-pixels **SP1** and **SP2** (**10a** and **10b** in FIG. 8) can be driven by one scanning line and thus the structure of the liquid crystal display device is simplified.

[0050] The present invention can preferably utilize the space-wise pixel division technique described in Patent Documents 1 through 3. The present invention can also utilize the space-wise pixel division techniques described in, for example, Japanese Laid-Open Patent Publications No. 5-289108 and 2004-213011 or a combination of the above-described techniques. As described above, a time-wise pixel division technique (e.g., Patent Document 4) may be utilized, or a combination of a time-wise pixel division technique and a space-wise pixel division technique may be utilized.

[0051] Japanese Patent Application No. 2005-276419 upon which the present application claims the benefit of priority, Patent Documents 1 through 4, Japanese Laid-Open Patent Publications Nos. 5-289108 and 2004-213011 are entirely incorporated herein by reference.

INDUSTRIAL APPLICABILITY

[0052] The present invention is preferably usable for liquid crystal display devices, especially for liquid crystal display devices for TVs.

Claims

1. A liquid crystal display device, comprising a plurality of pixels each connected to a signal line via a switching element; wherein each of the plurality of pixel includes a first sub-pixel and a second sub-pixel having voltage vs. luminance characteristics different from each other with respect to a signal voltage supplied from the signal line, a threshold signal voltage of the first sub-pixel being lower than that of the second sub-pixel; the plurality of pixels form color display pixels including a red pixel, a green pixel and a blue pixel; where the area ratio of the first sub-pixel in each of the red pixel, the green pixel and the blue pixel is

SR1, SG1 and SB1, and the ratio of a time period in which the first sub-pixel of each of the red pixel, the green pixel and the blue pixel is lit up with respect to one vertical scanning period is TR1, TG1 and TB1, the relationship of $(SR1 \times TR1) > (SG1 \times TG1) > (SB1 \times TB1)$ holds. 5

2. The liquid crystal display device of claim 1, wherein the relationships of $0.15 < (SR1 \times TR1) \leq 1.00$, $0.03 < (SG1 \times TG1) < 0.75$, and $0.02 < (SB1 \times TB1) < 0.71$ are fulfilled. 10

3. The liquid crystal display device of claim 1 or 2, wherein: 15

the red pixel has a point, at which an input grayscale vs. luminance curve at the front viewing angle matches an input grayscale vs. luminance curve at the oblique 45° viewing angle, within the grayscale level range of 105/255 or greater and 255/255 or less, 20

the green pixel has a point, at which the input grayscale vs. luminance curve at the front viewing angle matches the input grayscale vs. luminance curve at the oblique 45° viewing angle, within the grayscale level range of 52/255 or greater and 223/255 or less, and 25

the blue pixel has a point, at which the input grayscale vs. luminance curve at the front viewing angle matches the input grayscale vs. luminance curve at the oblique 45° viewing angle, within the grayscale level range of 44/255 or greater and 217/255 or less. 30

4. The liquid crystal display device of any one of claims 1 through 3, wherein the ratio of the time period in which the first sub-pixel of each of the red pixel, the green pixel and the blue pixel is lit up with respect to one vertical scanning period, i.e., TR1, TG1 and TB1, are each 1.00. 35 40

45

50

55

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG.5




FIG.6




FIG. 7





FIG. 8



INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP2006/318741

A. CLASSIFICATION OF SUBJECT MATTER

G02F1/133(2006.01)i, G02F1/1343(2006.01)i, G09G3/20(2006.01)i, G09G3/36(2006.01)i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G02F1/133, G02F1/1343, G09G3/20, G09G3/36

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Jitsuyo Shinan Koho 1922-1996 Jitsuyo Shinan Toroku Koho 1996-2006

Kokai Jitsuyo Shinan Koho 1971-2006 Toroku Jitsuyo Shinan Koho 1994-2006

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	JP 2006-48055 A (Samsung Electronics Co., Ltd.), 16 February, 2006 (16.02.06), Full text; all drawings & US 2006/0028589 A1 & EP 1624332 A1	1-4
A	JP 2005-250085 A1 (Sharp Corp.), 15 September, 2005 (15.09.05), Full text; all drawings (Family: none)	1-4
A	JP 2005-189804 A (Sharp Corp.), 14 July, 2005 (14.07.05), Full text; all drawings & US 2005/0122441 A1 & EP 1538599 A2 & CN 1693945 A	1-4

☒ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search
13 October, 2006 (13.10.06)Date of mailing of the international search report
24 October, 2006 (24.10.06)Name and mailing address of the ISA/
Japanese Patent Office

Authorized officer

Facsimile No.

Telephone No.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP2006/318741

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	JP 2004-302270 A (Fujitsu Display Technologies Kabushiki Kaisha), 28 October, 2004 (28.10.04), Full text; all drawings & US 2004/0239698 A1 & KR 2004/086777 A	1-4
A	JP 2006-506683 A (Samsung Electronics Co., Ltd.), 23 February, 2006 (23.02.06), Full text; all drawings & WO 2004/046793 A2 & AU 2003/282417 A1 & KR 2004/043964 A	1-4
A	JP 2005-241932 A (Fujitsu Display Technologies Kabushiki Kaisha), 08 September, 2005 (08.09.05), Full text; all drawings (Family: none)	1-4
A	JP 2005-234552 A (Sharp Corp.), 02 September, 2005 (02.09.05), Full text; all drawings & US 2005/0184944 A1 & EP 1564714 A2 & CN 1658269 A	1-4

Form PCT/ISA/210 (continuation of second sheet) (April 2005)

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 2004062146 A [0004]
- JP 2004078157 A [0004]
- JP 2005189804 A [0004]
- JP 2005173573 A [0004]
- JP 5289108 A [0050] [0051]
- JP 2004213011 A [0050] [0051]
- JP 2005276419 A [0051]

Non-patent literature cited in the description

- Shinpen Shikisai Kagaku Handbook. University of Tokyo Press, 1998, 1026-10271303 [0004]

专利名称(译)	液晶显示装置		
公开(公告)号	EP1953586A4	公开(公告)日	2010-06-30
申请号	EP2006810401	申请日	2006-09-21
[标]申请(专利权)人(译)	夏普株式会社		
申请(专利权)人(译)	夏普株式会社		
当前申请(专利权)人(译)	夏普株式会社		
[标]发明人	NARUSE YOHICHI OCHI TAKASHI KUBO MASUMI YAMAMOTO AKIHIRO		
发明人	NARUSE, YOHICHI OCHI, TAKASHI KUBO, MASUMI YAMAMOTO, AKIHIRO		
IPC分类号	G02F1/133 G02F1/1343 G09G3/20 G09G3/36		
CPC分类号	G09G3/3648 G02F1/133 G02F2203/30 G09G2300/0452 G09G2320/028		
优先权	2005276419 2005-09-22 JP		
其他公开文献	EP1953586A1 EP1953586B1		
外部链接	Espacenet		

摘要(译)

一种液晶显示装置，包括多个像素，每个像素通过开关元件连接到信号线。每个像素包括第一和第二子像素，其具有相对于从信号线提供的信号电压彼此不同的电压 - 亮度特性。第一子像素的阈值信号电压低于第二子像素的阈值信号电压。像素形成彩色显示像素，其为红色，绿色像素和蓝色像素。其中红色，绿色和蓝色像素中的每一个中的第一子像素的面积比是SR1，SG1和SB1，以及每个红色，绿色的第一子像素的点亮时间周期的比率在一个垂直扫描周期中的蓝色和蓝色像素是TR1，TG1和TB1， $(SR1 \times TR1) > (SG1 \times TG1) > (SB1 \times TB1)$ 的关系成立。