



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
13.05.2009 Bulletin 2009/20

(51) Int Cl.:
G02F 1/1333^(2006.01) G02F 1/1343^(2006.01)

(21) Application number: **08161527.0**

(22) Date of filing: **31.07.2008**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR
Designated Extension States:
AL BA MK RS

(71) Applicant: **TPO Displays Corp.**
Miao-Li County (TW)

(72) Inventor: **Dessaud, Nathalie Magali Danielle**
5655 AE Eindhoven (NL)

(74) Representative: **Ketelaars, Maarten F.J.M.**
Nederlandsch Octrooibureau
Postbus 29720
2502 LS Den Haag (NL)

(30) Priority: **07.11.2007 US 986276 P**

(54) **Multidomain liquid crystal display device having particular electrode structure**

(57) A liquid crystal display device including a liquid crystal layer, a common electrode, and an electrode set is disclosed. The liquid crystal layer is placed between said common electrode and the electrode set, and the electrode set is provided for switching the liquid crystal layer. The electrode set includes a first electrode (104a) and a second electrode (104b). The first electrode (104a) switches a first area of the liquid crystal layer. The second electrode (104b) switches a second area of the liquid crystal layer. Particularly, the second area includes at least a part of the area of the liquid crystal layer that the first area does not include. The first electrode has a shape which in cooperation with the second electrode allow alignment of the LC molecules in substantially two orthogonal directions. The invention provides a method to get rid of the circular polarizers which provide a good on-axis aperture but which show reduced off-axis performance compared to linear polarizers.

Fig 7a





Fig 10



Description

Field of Invention

[0001] The present invention relates to a liquid crystal display, particular to a vertical aligned (VA) liquid crystal display device.

Background of the Invention

[0002] A liquid crystal display (LCD) is one of the most widely used flat panel displays. An LCD includes two panels provided with field-generating electrodes such as pixel electrodes and a common electrode and a liquid crystal (LC) layer sandwiched there between. The LCD displays images by applying voltages to the field-generating electrodes to generate an electric field in the LC layer, which determines orientations of LC molecules in the LC layer to adjust polarization of incident light.

[0003] A commonly used LCD mode is a vertical alignment (VA) mode LCD (VA-LCD), which aligns LC molecules such that the long axes of the LC molecules are perpendicular to the panels in absence of electric field. The VA-LCD mode exhibits several advantages such as: good viewing angle performances, high contrast ratio due to its excellent black state (independent of temperature or chromatic), low operating voltages, cost effective fabrication process (as it is a rubbing free process).

[0004] The good viewing angle properties are obtained by creating multi-domains in the pixel design. This can be done by using mechanical protrusions, as disclosed in US7295274, or slits in the ITO electrodes, as disclosed in US6424398, or a combination of both. The slits create fringing fields which direct the switching of the LC. The slope of the protrusions has a similar effect. From their initial homeotropic orientation, which is perpendicular to the glass substrate, the specially chosen dielectrically negative LC molecules tend to reorient perpendicular to the electrical field. With protrusions or slits, the molecules tilt in a defined direction as an electrical field is applied.

[0005] The switching time of VA mode LCD is limited by the material and cell configuration. But it is also limited by what is referred to as the reverse flow effect (or back-flow effect). This phenomenon occurs if a too high voltage is applied to a VA cell and inversely results in a longer switching time. This phenomenon has been described in the following references: [1] De Gennes and Prost, Physics of Liquid Crystals 2nd Ed, Oxford; Clarendon Press, (1995); [2] Chandrasekar S., Liquid Crystals, 2nd edition, Cambridge University Press, (1992); [3] Roosendaal, Dessaud, Hector, Hughes, Boer, IDRC conference proceeding, 10-3, 127-130 2006; [4] Dessaud, Roosendaal, Hector, Hughes, Boer, IDW'06 Digest, LCT7-2, 651-654, 2006; [5] Sang Soo Kim, Brian H. Berkeley, Kyeong-Hyeon Kim, and Jang Kun Song, J. Soc. Inf. Display 12, 353 (2004).

[0006] It is known that a more uniform switching could be obtained by increasing the number of domains in a

display. However, the approaches in the prior art would unfavourably reduce the total aperture as, because of the shape of the electrode, some areas of LC will never switch and this will reduce the total aperture. Furthermore, when the pixel size gets smaller, the size of the areas of an LC cell that will never switch will remain the same. As a result the percentage of never switching area will increase, resulting in a reduction of total aperture.

[0007] The VA-LCD mode is very interesting in both transmissive and reflective mode making transfective displays possible. Optical foils play an important role in the final front of screen performance of the display.

[0008] A good reflective VA-LCD can be obtained by placing a circular polarizer on top of the display and a reflector after the LC-layer. A circular polarizer can be obtained by combination of a linear polarizer and a quarter wave plate between the linear polarizer and the LC layer. In its OFF mode, the display appears black and in its ON mode, maximum transmission can be reached.

Figure 3a shows the simulated optical response of a 45 μ m pixel between crossed polarizers 0° - 90°. Figure 3b shows the simulated optical response of a 45 μ m pixel between crossed polarizers 45° - 135° and figure 3c shows the simulated optical response of a 45 μ m pixel between circular polarizers. Finally, figure 3d shows the director profile of the LC molecules in a prior art 45 μ m pixel. It is clear that, circular polarizers provides the best aperture in combination with a 45 μ m pixel.

[0009] In transfective displays, the need to have a good working reflective area (normally black) makes the use of circular polarisation very interesting. A good match between transmission and reflective mode curves can be obtained by using the double cell gap approach.

[0010] There are several reasons to prefer linear polarizers over circular polarizers. They provide higher contrast ratio, less retardation films, thinner polarizer stack, lower manufacturing cost and stronger against the deviation of the retardation film properties. Furthermore, it is commonly known that the off-axis performance of circular polarizers is lower than the off-axis performance of linear polarizers. Furthermore, in transmissive mode the quarter lambda wave plate is not necessary. By omitting the quarter lambda wave plate in a transfective display, the off-axis performance can be improved.

[0011] For very small pixel sizes and especially for squared pixels, the LC alignment can not allow the use of linear polarizers as the loss in aperture is too high when a "flower type" optical response occurs. Figure 4a-d shows simulated optical responses from top to bottom of a 100 μ m pixel, a 60 μ m pixel, a 45 μ m pixel and a 25 μ m pixel between two crossed polarizers placed at 45° - 135°. As can be seen, the loss in aperture increases as the pixel size decreases.

[0012] In Shibazaki-san et. al, "57.5L: Late-News Paper: MVA Mode with Improved Color-wash-out for mobile Applications", Society for information display 2007 International symposium, SID 07 DIGEST, 1665-1668, a new MVA technology for wider viewing angle is described. A

new pixel structure with an optimized ITO slit design on the Colour Filter (CF) side is described which increases the transmittance of a transmissive MVA mode with a linear polarizer. The ITO slit provides an alignment of the LC molecules in four directions (two orthogonal directions) and therefore allow the use of linear polarizers in such configuration. The disadvantages of etching the colour filter substrate are: more strict ITO etching design rules (i.e. the ITO slits and gap minimum size) than on the TFT substrate, difficult to etch the CF substrate without damaging the colour filters.

[0013] Figure 5a shows an embodiment of an ITO hole 52 in the electrode 50 on the CF side. Figure 5b shows the director profile of the LC molecules in a cell with said ITO hole. Figures 5c-d show the optical response of such a cell with ITO hole on the CF side between circular polarizers and crossed polarizers $0^\circ - 90^\circ$, respectively. The black spots in the middle of the cells corresponds to the part of the LC layer that is not switched as an electric field is missing at the location of the ITO hole in the electrode 50 on CF side. The unswitched area of LC layer is related to the size and the shape of the ITO hole. This effect decreases the aperture of the LCD.

[0014] Therefore, it is desirable to have a LCD design which can overcome some of the disadvantages of the known designs.

Summary of the Invention

[0015] It is an object of the invention to provide an improved LCD device. More specific, it is an object of the invention to provide an LCD device with improved aperture. It is another object of the invention to provide an LCD device which allows to use linear polarizers, which improves the off-axis-performance.

[0016] Furthermore, it is another object of the invention to provide an LCD device with reduced cost price of the display by reducing the number of foils necessary and the amount of process steps.

[0017] Furthermore, it is still a further object of the invention to provide an LCD device with improved switching times of the LC.

[0018] Another object of the present invention is to provide an LCD in which the backflow effect is eliminated or reduced.

[0019] The object of the present invention has been achieved by a liquid crystal display device according to the independent claim. Advantageous embodiments and further embodiments of the present invention are subject of the dependent claims.

[0020] A liquid crystal display device (LCD) according to the invention comprises a liquid crystal layer, comprising liquid crystal (LC) molecules, a common electrode, and an electrode set for switching said liquid crystal layer. The liquid crystal layer is placed between said common electrode and said electrode set. The electrode set is provided for switching the LC layer. The electrode set comprises a first electrode provided for switching a first

area of said liquid crystal layer and a second electrode provided for switching a second area of said liquid crystal layer. The second area includes at least a part of the area of said liquid crystal layer that said first area does not include. Furthermore, the first electrode has a shape which in cooperation with the second electrode allow alignment of the LC molecules in substantially two orthogonal directions. Compared to the general VA-mode where squared pixels are used, the invention allows us to use linear crossed polarizers. The special shaped electrode in cooperation with the second electrode controls the LC orientation and therefore reduces the huge loss in aperture due to the diversity of LC orientations when crossed polarizers are used.

[0021] In an embodiment of the invention, the first electrode has a cross shape. In another embodiment, the first electrode has a shape corresponding to the combination of a cross shape and rectangle shape and wherein the centre of the cross shape and rectangle shape coincides.

[0022] In an embodiment, the second electrode has a rectangle shape, which can be a square, which covers the LC-layer and in yet another embodiment, the first electrode and said second electrode together cover substantially all the area of said liquid crystal layer. In this way, the whole LC-layer can be switched.

[0023] In another embodiment, the second electrode has an opening coinciding with at least a part of said first electrode. In yet another embodiment, the common electrode has an opening coinciding with at least a part of the first electrode. This allows us to increase the design freedom.

[0024] The first electrode and the second electrode can be in the same plane or can be in two planes wherein the first and second electrode are separated by a dielectric layer.

[0025] In an embodiment the LCD device comprises a driver unit for driving the first and second electrodes. The first and second electrodes can be driven with different voltages and similar voltages.

[0026] In yet another embodiment, the LCD device comprises two or more sections and the common electrode and the first and second electrodes extend to allow alignment of the LC molecules in each of said one or more sections in substantially two orthogonal directions, wherein the shape and/or orientation of the first electrode in the two or more sections differ.

[0027] In still another embodiment, the LCD device is a transmissive LCD device and linear polarizers are disposed respectively on both outer surfaces of the LCD device, having polarization axes that are orthogonal to each other.

[0028] In another embodiment, the LCD device is a transmissive LCD device, comprising reflective LCD cells and transmissive LCD cells. Linear polarizers are disposed respectively on both outer surfaces of the LC-layer corresponding to the transmissive LCD cells. The linear polarizers have polarization axes that are orthogonal to each other.

[0029] Another aspect of the invention provides electronic device, comprising the LCD device according to the invention and a power supply connected to the LCD device to supply power to the LCD device.

Brief description of the drawings

[0030] The present invention will be discussed in more detail below, using exemplary embodiments, with reference to the attached drawings, in which similar notations indicate similar elements.

FIG. 1 is a block diagram of the electronic device according to an embodiment of the present invention;

FIG. 2a exemplarily shows a profile of LCD pixel cell according to an embodiment;

FIG. 2b exemplarily shows a profile of components of LCD pixel cell according to an embodiment;

FIG. 2c exemplarily shows a profile of components of an LCD pixel cell according to another embodiment;

FIG. 3a shows the simulated optical response of a $45\mu\text{m}$ pixel between crossed polarizers $0^\circ - 90^\circ$;

FIG. 3b shows the simulated optical response of a $45\mu\text{m}$ pixel between crossed polarizers $45^\circ - 135^\circ$;

FIG. 3c shows the simulated optical response of a $45\mu\text{m}$ pixel between circular polarizers;

FIG. 3d shows the director profile of the LC molecules in a prior art $45\mu\text{m}$ pixel in the centre of the cell;

FIG. 4a-4d show respectively the simulated optical response of a $100\mu\text{m}$, $60\mu\text{m}$, $45\mu\text{m}$ pixel and $25\mu\text{m}$ between crossed polarizers $45^\circ - 135^\circ$;

FIG. 5a shows an embodiment of an ITO hole on CF side;

FIG. 5b shows the director profile of the LC molecules in a prior art cell with ITO hole on CF side;

FIG. 5c-d show the optical response of a prior art cell with ITO hole on CF side between circular polarizers and crossed polarizers $0^\circ - 90^\circ$, respectively;

FIG. 6a shows an embodiment of a first electrode according to the invention;

FIG. 6b shows the director profile of the LC molecules in a cell with the first electrode shown in FIG. 6a in the centre of the cell;

FIG. 6c-d show the simulated response of a cell with the first electrode shown in FIG 6a between circular polarizers and crossed polarizers $0^\circ - 90^\circ$, respectively;

FIG. 7a shows a set of electrodes according to a first embodiment of the invention;

FIG. 7b shows the director profile of the LC molecules in a cell with the set of electrodes shown in FIG. 7a in the centre of the cell;

FIG. 7c-d show the simulated response of a cell with the set of electrodes shown in FIG 7a between circular polarizers and crossed polarizers $0^\circ - 90^\circ$, respectively;

FIG. 8a-c show a combination of common electrode (a) and set of electrodes (b) and (c) according to a second embodiment of the invention;

FIG. 9a-c show a combination of common electrode and set of electrodes according to a third embodiment of the invention;

FIG. 10 shows another embodiment of the first electrode;

FIG. 11 shows another embodiment of the second electrode;

FIG. 12 shows the first electrode and the second electrode on the same plane according to an embodiment of the present invention;

FIG. 13a-c show a combination of common electrode and set of electrodes according to a fourth embodiment of the invention;

FIG. 14a-c show a combination of common electrode and set of electrodes according to a fifth embodiment of the invention;

FIG. 15a shows an embodiment of the first electrode for use in a transfective LCD; and

FIG. 15b shows an embodiment of the second electrode for use in a transfective LCD.

Detailed Description of exemplary embodiments

[0031] The present invention is useful for a vertical aligned (VA) LCD and will be described with reference to the accompanying drawings. However, those skilled in the art can understand that the present invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein.

[0032] The present invention is especially useful in a transmissive LCD or transmissive sections of a transfective LCD.

[0033] FIG. 1 is a diagram of an electronic device 1 with an LCD 10 according to an embodiment of the present invention. The electronic device 1 also has a power supply 20 connected to the LCD 10 to supply power to the LCD 10. In this embodiment, the LCD 10 is a colour or monochromatic image display integrated into the electronic device 1. As known to those skilled in the art, the electronic device 1 can be a mobile phone, a personal digital assistant (PDA), a notebook computer, a desktop computer, a television, a car media player, a portable video player, digital camera, global positioning system (GPS), avionics display, and any other apparatus comprising an LCD.

[0034] According to an embodiment of the present invention, FIG. 2a further illustrates the profile of an LCD 10. The LCD 10 includes a liquid crystal (LC) layer 100, a common electrode 102, an electrode set 104, two glass substrates 130 and two polarizers 108. The polarizers 108 can be circular polarizers or crossed polarizers. LCD 10 may have many cells, but FIG. 2a illustrates only one cell of LCD 10 to explain the present invention. In this example, the pixel cell, corresponding to a sub pixel, can

have a size of $40\ \mu\text{m} \times 40\ \mu\text{m}$ and a thickness of $4.15\ \mu\text{m}$. Note that the pixel cell can have other sizes like $20\ \mu\text{m} \times 20\ \mu\text{m}$, $30\ \mu\text{m} \times 30\ \mu\text{m}$, $39.5\ \mu\text{m} \times 39.5\ \mu\text{m}$, $40\ \mu\text{m} \times 80\ \mu\text{m}$ or any other size and the thickness can be any suitable one greater than $1.5\ \mu\text{m}$. As shown, the LC layer 100, where the LC molecules are vertical aligned (not shown in FIG. 2a), is sandwiched between the common electrode 102 and the pixel electrode set 104, which in turn are sandwiched between the two glass substrates 130, which in turn are sandwiched between two polarizers 108. The electrode set 104, which is placed on the Thin Film Transistor (TFT) (not shown) side, is provided for switching the LC layer 100. Note that the LCD 10 may include other components, such as substrates 130, colour filters (CF) 140, TFT 150, as shown in FIG. 2b.

[0035] The common electrode 102, the LC layer 100, and the pixel electrode set 104 form a liquid crystal capacitor, which stores applied voltages after turn-off of the TFT(s) (not shown). The pixel electrode set 104, supplied with the data voltages, generates electric fields in cooperation with the common electrode 102, which reorients LC molecules of the LC layer 100. The common electrode 102, which can be a conventional common electrode, can be made of ITO or IZO. The pixel electrode set 104, like conventional pixel electrode but with a different structure, can be made of ITO or IZO. As shown in FIG. 2a, the electrode set 104 includes a first electrode 104a, a second electrode 104b, and a dielectric layer 104c (e.g., a SiO_x or SiN layer with a thickness of, for example, $0.1\ \mu\text{m}$ or $0.25\ \mu\text{m}$) placed between the first and second electrode 104a, 104b. In this embodiment, the first electrode 104a and second electrode 104b are plane electrodes. Those skilled in the art will understand that the present invention is not limited to an electrode set 104 with two electrodes but can also be applied to electrode sets 104 which has more than two electrodes and more dielectric layers to separate the electrodes.

[0036] The first electrode 104a and the second electrode 104b are driven by a driver unit 30. The first electrode 104a and the second electrode 104b can be driven with similar or different voltages or driven according to different time sequences (e.g., be turned on at different time) to achieve the desired switching effect and orientation of the LC-molecules. In one scenario, a voltage of $5\ \text{V}$ is first applied to the first electrode 104a, and after $5\ \text{milliseconds (ms)}$, a voltage of $6\ \text{V}$ is applied to the second electrode 104b. In another scenario, a voltage of $4\ \text{V}$ is first applied to the first electrode 104a, and after $5\ \text{ms}$, a voltage of $6\ \text{V}$ is applied to the second electrode 104b. Or a same voltage of $5\ \text{V}$ can be applied to both the first electrode 104a and the second electrode 104b, but the first electrode 104a is turned on $5\ \text{ms}$ prior to the second electrode 104b. Nevertheless, that using only one TFT and one storage capacitor to respectively drive the first electrode 104a and the second electrode 104b is also covered by the present invention. According to the invention, the driving unit 30 supplies voltages to the first electrode and second electrode to generate a fringing

field to provide in the LC-layer 100 at least two domains, wherein the orientation of the LC molecules in each of said at least two domains is substantially in one direction and the orientation of the LC-molecules in a domain of said at least two domains is orthogonal with respect to the orientation of the LC molecules in another domain of said at least two domains. In other words, to obtain the advantage of the invention, at least two domains have to be provided wherein the orientation of the LC molecules in the at least two domains are perpendicular with respect to each other. Preferably, the LC-layer of a cell comprises four different domains, wherein the orientation of the LC-molecules of in the four domains differ from each other and be in perpendicular directions.

[0037] Compared with the conventional design for pixel electrode (e.g., as a single square electrode to cover the whole area of the LC layer), the first electrode 104a may have a particular shape for switching the LC layer 100 (as later shown in the figures). In an embodiment, the first electrode 104a has a fringing structure (not shown in FIG. 2a) and generates a fringing field for switching a first area 100a instead of the whole area of LC layer 100. The switched area of LC layer 100a is related to the size and the shape of the first electrode 104a and the common electrode. For example, a small-size first electrode 104a can only effectively switch the LC molecules of LC layer 100 in a small area 100a, and the shape of the switched area 100a more or less looks like the first electrode 104a. Figure 6a shows an embodiment of the first electrode 104a and figure 6b shows the corresponding director profile of the LC molecules. Furthermore, FIG. 6c shows the simulated response of a cell with the first electrode shown in FIG 6a between circular polarizers, whereas figure 6d shows the simulated response of the same cell between crossed polarizers $0^\circ - 90^\circ$.

[0038] Regarding the shape of the first electrode 104a, the present invention does not like to specify any specific ones, but it has at least two parts extending in perpendicular horizontal directions, to provide the multiple and diverse domains switching effect. For example, as shown in FIG. 6a, the first electrode 104a has a shape corresponding to the combination of a cross shape and rectangle shape, thus having four parts extending in different horizontal and perpendicular directions. Moreover, when incorporated into the LCD 10 of FIG. 2a, the first electrode 104a can be placed within a square of $35\ \mu\text{m} \times 35\ \mu\text{m}$, which corresponds to the size of the second electrode 104b in one embodiment.

[0039] Meanwhile, in order to gain some uniformity for the switching, the first electrode 104a can have a symmetrical shape as shown in the examples. Symmetrical can be line symmetrical or point symmetrical.

[0040] Those skilled in the art should understand the arrangement of the aforementioned first electrode 104a can be directed to, but not limited to, the fast switching by reducing the backflow effect. The increased number of edges of the first electrode 104a effectively reduces

the backflow effect. From figures 6c and 6d can be seen that the first electrode does not provide sufficient aperture on its own. It is desired to maintain a high aperture of the LC cell at the same time. For that, a second electrode 104b of the electrode set 104 is configured to switch a second area 100b of the LC layer 100, as shown in FIG. 2a. Note that in the present invention, the second area 100b may or may not overlap the first area 100a of the first electrode 104a, as long as the second area 100b includes at least a part of the area of LC layer that the first area 100a does not include, so that those LC molecules not affected by the first electrode 104a can be led by the electric field of the second electrode 104b. Also note that the "boundary" of the first area 100a and the second area 100b may be judged by a predetermined transmission at a given time, e.g., 20 or 100 ms, after the voltage(s) is applied to the first electrode 104a and to the second electrode 104b. Therefore, by arranging the first electrode 104a along with the second electrode 104b, a higher aperture is obtained than the one resulted from the first electrode 104a only.

[0041] Figure 7a shows a set of electrodes according to a first embodiment of the invention. An electrode set can be configured for a pixel cell of an LCD device 10. The first electrode 104a has a shape corresponding to the combination of a cross shape and rectangle shape and wherein the centre 74 of the cross shape and rectangle shape coincides. The second electrode 104b substantially covers all the area of the LC layer 100. Only a small area 104d is not covered by the second electrode 104b. This area forms a boundary between the second electrodes of neighbouring pixel cells. The width of the area along sides of the cell is in a range from 2 μm up to about 15 μm . The first and second electrodes are placed in this embodiment above each other, wherein the first electrode 104a is between LC layer 100 and the second electrode 104. Figure 7b shows the director profile of the LC molecules in a cell with the set of electrodes shown in Figure 7a. The LC molecules in the centre of the cell are aligned in substantially two orthogonal directions. When the LCD is switched on, the LC-layer 100 comprises four domains, wherein in each domain the LC molecules are mainly aligned in one of the two orthogonal directions.

[0042] Figures 7c-d show the simulated response of a cell with the set of electrodes shown in figure 7a between circular polarizers and crossed polarizers 0° - 90°, respectively. It can be seen that the aperture is significantly improved by applying the second electrode.

[0043] In this embodiment, wherein the first and second electrode 104a, 104b are separated by a dielectric layer, the voltage applied to the first and second electrodes can be the same voltage. The distance between the first electrode 104a and the common electrode 102 and the distance between the second electrode 104b and the common electrode 102 is sufficient to apply different switching voltages across the LC layer 100. This allows to provide the four domains. Having four domains, where-

in the directions of the LC molecules are orthogonal with respect to each domain allows us to use linear (crossed) polarizers instead of circular polarizers, without losing much aperture on axis. The use of linear polarizers, allows us to reduce production costs of transmissive LCD-devices. Furthermore, this improves the off-axis performance. The use of a set of electrodes improves the aperture with respect to the ITO hole in the electrode on the CF side. As both the common electrode and set of electrodes substantially covers all the area of the LC-layer at both sides, i.e. without holes in the effective area, a large area of the LC-molecules between the common electrode and set of electrodes will be switched. A small stripe 104d along the area covered by the first and second electrodes, which forms a boundary between the sets of electrodes of neighbouring pixel cells, is almost not switched in the LC-layer.

[0044] Compared with the first electrode 104a, the shape of the second electrode 104b is less important and is less related to the backflow effect. In case, the first electrode 104a and second electrode 104b are different layers, the shape of the second electrode 104b resembles a conventional pixel electrode as a square and plain shape. From a vertical perspective, the second electrode 104b would overlap the first electrode 104a, and the second electrode 104b alone covers substantially all the area of the LC layer 100 to ensure a high aperture. Moreover, when incorporated into the LCD 10 of FIG. 2a, the second electrode 104b can be simply a square of 35 μm x 35 μm . Thus, the second area 100b includes at least a part of the area of the LC layer 100 that the first area 100a does not include. Also that part of the area of the LC layer 100, included by the second area 100b, has at least two parts extending in different horizontal and perpendicular directions.

[0045] Figure 8a-c show a combination of common electrode and set of electrodes according to a second embodiment of the invention. Figure 8a shows the common electrode 102, figure 8b shows the first electrode 104a of the set of electrodes and figure 8c shows the second electrode 104b of the set of electrodes. In this embodiment, the first electrode 104a has the shape of a cross.

[0046] Figure 9a-c show a combination of common electrode and set of electrodes according to a third embodiment of the invention. In this embodiment, the first electrode 104a has the shape of a multiplication sign or the cross shown in figure 8b rotated by 45 degrees. When using linear polarizers, this embodiment has the advantage over the embodiment shown in figure 8 in that the orientation of the LC molecules is in a direction of 0 and 90 degrees, which is in favour when the LCD 10 is viewed by a human wearing polarized glasses. The viewer of the display in the vertical or horizontal direction will see similar display content.

[0047] Figure 10 shows another embodiment of the first electrode 104a, which corresponds to the shape of the first electrode in the first embodiment rotated by 45

degrees.

[0048] Figure 11 shows an embodiment wherein the shape of a hole or opening in the second electrode 104b corresponds to the shape of the first electrode 104a as shown in figure 8B. In this case, the second electrode 104b alone does not cover all the area of LC layer 100 in the cell, and the second electrode 104b does not overlap the first electrode 104a either. Now, the first electrode 104a and the second electrode 104b together cover substantially all the area of the LC layer 100 to maintain a high aperture. Moreover, when incorporated into the LCD 10 of FIG. 2a, both the first electrode 104a and the second electrode 104b are placed within a square $35\ \mu\text{m} \times 35\ \mu\text{m}$. The high aperture will remain as long as the second electrode 104b has one or more openings which coincide with the area covered by the first electrode 104a. Any second electrode 104b having opening coinciding with at least a part of said first electrode 104a and an area not covered by said first electrode 104a, will improve the aperture of the LCD 10 compared to an LCD device with only an electrode at said side of the LC-layer 100.

[0049] Referring back to FIG. 2a, the first electrode 104a and the second electrode 104b are separated by a dielectric layer 104c, e.g., a layer of SiOx or SiNx. When applied to the same voltage, the first electrode 104a and the second electrode 104b in this arrangement can provide different capacitances in cooperation with the common electrode 102, and thus generate different switching effects providing the alignment of the LC molecules in four directions (2 orthogonal directions) and therefore allow us the use of linear polarizers in such a configuration.

[0050] The first electrode 104a and the second electrode 104b can be patterned by photolithographic and wet etching processes, and may not be limited to transmitting electrodes. Note that in figure 2a and 2b, the first electrode 104a is placed above the second electrode 104b, but in another embodiment, the first electrode 104a can be placed underneath the second electrode 104b (i.e., the first electrode 104a becomes closer to the substrate 130 on which the electrodes are etched), as long as the second electrode 104b would not shield the electric field of the first electrode 104a. This is the case when the second electrode 104b has an opening that has an area that coincides at least with the first electrode 104a.

[0051] Figure 2c and Figure 12 show another embodiment of the electrode set. In this embodiment, the first electrode 104a is similar to the first electrode in figure 8b and the second electrode 104b has an opening to encompass the first electrode 104a without making electrical contact. In this embodiment the first electrode 104a and second electrode 104b are on the same plane above the substrate 130, as shown in FIG. 2c. The second electrode 104b has an opening corresponding to a shape of the first electrode 104a. Advantageous is that the first electrode 104a and the second electrode 104b can be formed at the same time in a photolithography process. And by being independently driven, the first electrode 104a and the second electrode 104b on the same plane

can create different switching effect from the conventional single pixel electrode, while still preserving a high aperture. In this embodiment, the driving unit 30 shown in figure 1, should supply different voltages to the first electrode 104a and second electrode 104b, to provide the fringing fields in the LC-layer 100. A small stripe 104d along the area covered by the first and second electrodes forms a boundary between the sets of electrodes of neighbouring pixel cells.

[0052] Figure 13a-c show a combination of common electrode and set of electrodes according to a fourth embodiment of the invention. In this embodiment the LC alignment is obtained by combination of the common electrode 102 of the CF side and the set of electrodes. The fourth embodiment differs from the embodiment shown in figure 8 in that the common electrode 102 comprises an opening 131. The centre 131 of the opening coincides with the centre 132 of the cross shaped first electrode 104a as shown in figure 13b. Figure 13c shows an embodiment of a corresponding second electrode 104b. This embodiment will provide similar optical properties as the embodiment shown in figure 7.

[0053] Figure 14a-c show a combination of common electrode and set of electrodes according to a fifth embodiment of the invention. In this embodiment the LC-cell is a rectangle and not a square design as in the previous embodiments. The LC-cell comprises three squared sections 140, 141, 142. In figure 14a is shown the common electrode 102. In figure 14b is shown the first electrode 104a of the set of electrodes and in figure 14c is shown the second electrode 104b. In this embodiment, each section comprises a differently shaped first electrode. This could be used to improve the off-axis characteristics and to provide one cell with different polarizing directions.

[0054] FIG. 15a shows an embodiment of the first electrode for use in a transmissive LCD. In such an embodiment the transmissive part 150 of the LC-cell comprises a common electrode and a set of electrodes and the reflective part 151 of the LC-cell comprises the common electrode and one other electrode. An embodiment of a combination of the other electrode of the reflective part 151 and the second electrode 104b of the transmissive part 150 is shown in figure 15b. Preferably, the transmissive part 150 of the LC-layer is between linear polarizers and the reflective part 151 of the LC-layer is between circular polarizers.

[0055] While this invention has been described with reference to the illustrative embodiments, these descriptions should not be construed in a limiting sense. Various modifications of the illustrative embodiment, as well as other embodiments of the invention, will be apparent upon reference to these descriptions. It is therefore contemplated that the appended claims will cover any such modifications or embodiments as falling within the true scope of the invention and its legal equivalents.

Claims**1.** A liquid crystal display device (LCD), comprising:

a liquid crystal layer, comprising liquid crystal (LC) molecules;
 a common electrode;
 an electrode set for switching said liquid crystal layer, wherein said liquid crystal layer is placed between said common electrode and said electrode set, and said electrode set comprises:

a first electrode provided for switching a first area of said liquid crystal layer; and
 a second electrode provided for switching a second area of said liquid crystal layer; wherein said second area includes at least a part of the area of said liquid crystal layer that said first area does not include, wherein the first electrode has a shape which in cooperation with the second electrode allow alignment of the LC molecules in substantially two orthogonal directions.

2. The LCD device according to claim 1, wherein said first electrode has a cross shape.**3.** The LCD device according to claim 1, wherein said first electrode has a shape corresponding to the combination of a cross shape and rectangle shape and wherein the centre of the cross shape and rectangle shape coincides.**4.** The LCD device according to claim 2 or 3, wherein said second electrode has a rectangle shape.**5.** The LCD device according to claim 2 or 3, wherein said second electrode has an opening coinciding with at least a part of said first electrode.**6.** The LCD device according to claim 2, wherein the common electrode has an opening coinciding with at least a part of the first electrode.**7.** The LCD device according to any of the claims 1 - 6, wherein said first electrode and said second electrode together cover substantially all the area of said liquid crystal layer.**8.** The LCD device according to any of the claims 1 - 7, wherein said first electrode and said second electrode are in the same plane.**9.** The LCD device according to any of the claims 1 - 7, wherein said first electrode and said second electrode are separated by a dielectric layer.**10.** The LCD device according to any of the claims 1 -

9, wherein the LCD device further comprises a driver unit for driving said first electrode and said second electrode.

11. The LCD device according to claim 10, wherein said first electrode and said second electrode are driven with different voltages.**12.** The LCD device according to any of the claims 1 - 11, wherein the LCD device comprises two or more sections and the common electrode and the first and second electrode extend to allow alignment of the LC molecules in each of said one or more sections in substantially two orthogonal directions, wherein the shape and/or orientation of the first electrode in the two or more sections differ.**13.** The LCD device according to any of the claim 1 - 12, wherein the LCD device is a transmissive LCD device and linear polarizers are disposed respectively on both outer surfaces of the LCD device, having polarization axes that are orthogonal to each other.**14.** The LCD device according to any of the claim 1 - 12, wherein the LCD device is a transmissive LCD device, comprising reflective LCD cells and transmissive LCD cells and linear polarizers are disposed respectively on both outer surfaces of the LCD device corresponding to the transmissive LCD cells, wherein the linear polarizers have polarization axes that are orthogonal to each other.**15.** An electronic device, comprising:

the LCD device according to claim 1;
 a power supply connected to the LCD device to supply power to the LCD device.

Fig 1




Fig 2a




Fig 2b




Fig 2c




Fig 3a




Fig 3b




Fig 3c




Fig 3d




Fig 4a




Fig 4b




Fig 4c




Fig 4d




Fig 5a




Fig 5b




Fig 5c




Fig 5d




Fig 6a




Fig 6b




Fig 6c




Fig 6d




Fig 7a




Fig 7b




Fig 7c




Fig 7d




Fig 8a




Fig 9a




Fig 8b




Fig 9b




Fig 8c




Fig 9c




Fig 10




Fig 13a




Fig 11




Fig 13b




Fig 12




Fig 13c




Fig 14a




Fig 14b




Fig 14c




Fig 15a





Fig 15b





EUROPEAN SEARCH REPORT

Application Number
EP 08 16 1527

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 6 407 791 B1 (SUZUKI TERUAKI [JP] ET AL) 18 June 2002 (2002-06-18)	1,2,4,5,7-15	INV. G02F1/1333
Y	* abstract *	6	G02F1/1343
A	* figures 1,2,8,11-14,17,20,22,23,37,38,44 *	3	
Y	----- US 5 608 556 A (KOMA NORIO [JP]) 4 March 1997 (1997-03-04) * abstract; figures 4-6 * -----	6	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (IPC)
			G02F
Place of search		Date of completion of the search	Examiner
Munich		31 December 2008	Wolfrum, Georg
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

1
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 08 16 1527

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

31-12-2008

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
US 6407791	B1	18-06-2002	KR	20010007523 A		26-01-2001
			TW	227804 B		11-02-2005

US 5608556	A	04-03-1997	JP	2975844 B2		10-11-1999
			JP	7199190 A		04-08-1995

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 7295274 B [0004]
- US 6424398 B [0004]

Non-patent literature cited in the description

- De Gennes and Prost, Physics of Liquid Crystals. Clarendon Press, 1995 [0005]
- **CHANDRASEKAR S.** Liquid Crystals. Cambridge University Press, 1992 [0005]
- **ROSENDAAL ; DESSAUD ; HECTOR ; HUGHES ; BOER.** IDRC conference proceeding, 2006, vol. 10-3, 127-130 [0005]
- **DESSAUD ; ROSENDAAL ; HECTOR ; HUGHES ; BOER.** IDW'06 Digest, 2006, vol. LCT7-2, 651-654 [0005]
- **SANG SOO KIM ; BRIAN H. BERKELEY ; KYEONG-HYEON KIM ; JANG KUN SONG.** J. Soc. Inf. Display, 2004, vol. 12, 353 [0005]
- **SHIBAZAKI-SAN.** 57.5L: Late-News Paper: MVA Mode with Improved Color-wash-out for mobile Applications. Society for information display 2007 International symposium, SID 07 DIGEST, 1665-1668 [0012]

专利名称(译)	具有特定电极结构的多畴液晶显示装置		
公开(公告)号	EP2058694A1	公开(公告)日	2009-05-13
申请号	EP2008161527	申请日	2008-07-31
[标]申请(专利权)人(译)	统宝光电股份有限公司		
申请(专利权)人(译)	TPO DISPLAYS CORP.		
当前申请(专利权)人(译)	TPO DISPLAYS CORP.		
[标]发明人	DESSAUD NATHALIE MAGALI DANIELLE		
发明人	DESSAUD, NATHALIE MAGALI DANIELLE		
IPC分类号	G02F1/1333 G02F1/1343		
CPC分类号	G02F1/134336 G02F1/133707 G02F2001/134345 G02F2201/40		
优先权	60/986276 2007-11-07 US		
外部链接	Espacenet		

摘要(译)

公开了一种包括液晶层，公共电极和电极组的液晶显示装置。液晶层位于所述公共电极和电极组之间，电极组用于切换液晶层。电极组包括第一电极（104a）和第二电极（104b）。第一电极（104a）切换液晶层的第一区域。第二电极（104b）切换液晶层的第二区域。特别地，第二区域包括第一区域不包括的液晶层区域的至少一部分。第一电极具有与第二电极配合的形状，允许LC分子在基本上两个正交的方向上对准。本发明提供了一种去除圆偏振器的方法，该圆偏振器提供良好的轴上孔径，但与线性偏振器相比显示出降低的离轴性能。

Fig 7a

