



(11) **EP 2 128 690 A1**

(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
02.12.2009 Bulletin 2009/49

(51) Int Cl.:
G02F 1/1335 ^(2006.01) **G02F 1/1343** ^(2006.01)
G02F 1/1368 ^(2006.01)

(21) Application number: **07850173.1**

(86) International application number:
PCT/JP2007/073557

(22) Date of filing: **06.12.2007**

(87) International publication number:
WO 2008/090682 (31.07.2008 Gazette 2008/31)

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

(72) Inventors:
• **IMAI, Hajine**
Osaka-shi, Osaka 545-8522 (JP)
• **MATSUMOTO, Hitoshi**
Osaka-shi, Osaka 545-8522 (JP)

(30) Priority: **24.01.2007 JP 2007013654**


(71) Applicant: **Sharp Kabushiki Kaisha**
Osaka-shi, Osaka 545-8522 (JP)

(74) Representative: **Müller - Hoffmann & Partner**
Patentanwälte
Innere Wiener Strasse 17
81667 München (DE)

(54) **LIQUID DISPLAY DEVICE**

(57) A transmissive-type liquid crystal display device with a high image quality which has a high aperture ratio and an excellent efficiency of utility of reflected light is provided at low cost. A liquid crystal display device according to the present invention is a liquid crystal display device having a transistor and a reflection section in each of a plurality of pixels; the reflection section includes a metal layer, an insulating layer formed on the metal layer, a semiconductor layer formed on the insulating layer, and a reflective layer formed on the semiconductor layer; a plurality of recesses are formed on the surface of the reflective layer; a storage capacitor is formed between at least a portion of the metal layer and at least a portion of the reflective layer; and at least one of the metal layer and the reflective layer includes two portions which are electrically isolated from each other.

FIG. 3



Description**TECHNICAL FIELD**

5 **[0001]** The present invention relates to a transfective-type liquid crystal display device which performs display by utilizing reflected light and transmitted light.

BACKGROUND ART

10 **[0002]** Liquid crystal display devices (LCDs) include the transmission-type liquid crystal display device which utilizes backlight from behind the display panel as a light source for displaying, the reflection-type liquid crystal display device which utilizes reflected light of external light, and the transfective-type liquid crystal display device (reflection/transmission-type liquid crystal display device) which utilizes both reflected light of external light and backlight. The reflection-type liquid crystal display device and the transfective-type liquid crystal display device are characterized in that they
15 have smaller power consumptions than that of the transmission-type liquid crystal display device, and their displayed images are easy to see in a bright place. The transfective-type liquid crystal display device is **characterized in that** its screen is easier to see than that of the reflection-type liquid crystal display device, even in a dark place.

[0003] FIG. 12 is a cross-sectional view showing an active matrix substrate **100** in a conventional reflection-type liquid crystal display device (e.g., Patent Document 1).

20 **[0004]** As shown in this figure, the active matrix substrate **100** includes an insulative substrate **101**, as well as a gate layer **102**, a gate insulating layer **104**, a semiconductor layer **106**, a metal layer **108**, and a reflective layer **110**, which are stacked on the insulative substrate **101**. After being stacked on the insulative substrate **101**, the gate layer **102**, the gate insulating layer **104**, the semiconductor layer **106**, and the metal layer **108** are subjected to etching by using one mask, thus being formed so as to have an islandlike multilayer structure. Thereafter, the reflective layer **110** is formed
25 on this multilayer structure, whereby a reflection surface **112** having ruggednesses is formed. Although not shown, transparent electrodes, a liquid crystal panel, a color filter substrate (CF substrate), and the like are formed above the active matrix substrate **100**.

[0005] FIG. 13 is a cross-sectional view of a conventional transfective-type liquid crystal display device (e.g., Patent Document 2).

30 **[0006]** As shown in the figure, in this conventional transfective-type liquid crystal display device, an interlayer insulating film **204** is formed on a drain electrode **222** of a switching element (TFT) **203**, and a galvanic corrosion preventing film **205**, a reflection electrode film **206**, and an amorphous transparent electrode film **218** are stacked on the interlayer insulating film **204**. The region where the reflection electrode film **206** is formed is a reflection region of the transfective-type liquid crystal display device. Ruggednesses are formed in an upper portion of the interlayer insulating film **204**
35 within the reflection region, and conforming to these ruggednesses, ruggednesses are also formed on the galvanic corrosion preventing film **205**, the reflection electrode film **206**, and the amorphous transparent electrode film **218**.

[Patent Document 1] Japanese Laid-Open Patent Publication No. 9-54318

[Patent Document 2] Japanese Laid-Open Patent Publication No. 2005-277402

DISCLOSURE OF INVENTION**PROBLEMS TO BE SOLVED BY THE INVENTION**

45 **[0007]** In the active matrix substrate **100** described in Patent Document 1, portions of the reflective layer **110** are formed so as to reach the insulative substrate **101** in portions where the gate layer **102** and the like are not formed (i.e., portions between the islands, hereinafter referred to as "gap portions"). Therefore, in the gap portions, the surface of the reflection surface **112** is recessed in the direction of the insulative substrate **101**, thus forming a plane having deep dents (or recesses).

50 **[0008]** In the reflection-type liquid crystal display device or the transfective-type liquid crystal display device, in order to perform bright display in a wide viewing angle, it is necessary to allow incident light entering the display device to be more uniformly and efficiently reflected by the reflection surface **112** across the entire display surface, without causing specular reflection in one direction. For this purpose, it is better if the reflection surface **112** has moderate ruggednesses rather than being a complete plane.

55 **[0009]** However, the reflection surface **112** of the aforementioned active matrix substrate **100** has deep dents. Therefore, light is unlikely to reach the reflection surface located in lower portions of the dents, and even if at all light reaches there, the reflected light thereof is unlikely to be reflected toward the liquid crystal panel, thus resulting in a problem in that the reflected light is not effectively utilized for displaying. Furthermore, many portions of the reflection surface **110**

have a large angle with respect to the display surface of the liquid crystal display device, thus resulting in a problem in that so that the reflected light from those portions is not effectively utilized for displaying.

[0010] FIG. 14 is a diagram showing a relationship between the tilt of the reflection surface **112** and reflected light. FIG. 14(a) shows a relationship between an incident angle α and an outgoing angle β when light enters a medium b having a refractive index N_b from a medium a having a refractive index N_a . In this case, according to Snell's Law, the following relationship holds true.

$$N_a \times \sin \alpha = N_b \times \sin \beta$$

[0011] FIG. 14(b) is a diagram showing a relationship between incident light and reflected light when incident light perpendicularly entering the display surface of a liquid crystal display device is reflected from a reflection surface which is tilted by θ with respect to the display surface (or the substrate). As shown in the figure, the incident light perpendicularly entering the display surface is reflected from the reflection surface which is tilted by angle θ with respect to the display surface, and goes out in a direction of an outgoing angle ϕ .

[0012] Results of calculating the outgoing angle ϕ according to Snell's Law with respect to each angle θ of the reflection surface are shown in Table 1.

[0013]

[Table 1]

θ	ϕ	$90-\phi$
0	0	90
2	6.006121	83.99388
4	12.04967	77.95033
6	18.17181	71.82819
8	24.42212	65.57788
10	30.86588	59.13412
12	37.59709	52.40291
14	44.76554	45.23446
16	52.64382	37.35618
18	61.84543	28.15457
20	74.61857	15.38143
20.5	79.76542	10.23458
20.6	81.12757	8.872432
20.7	82.73315	7.266848
20.8	84.80311	5.19888
20.9	88.85036	1.149637
20.905	89.79914	0.200856

[0014] The values in this Table are calculated by assuming that air has a refractive index of 1.0 and the glass substrate and the liquid crystal layer have a refractive index of 1.5. As shown in Table 1, when the angle θ of the reflection surface exceeds 20 degrees, the outgoing angle ϕ becomes very large (i.e., $90-\phi$ becomes very small), so that most of the outgoing light does not reach the user. Therefore, even if ruggednesses are provided on the reflection surface of the reflective layer, in order to effectively utilize reflected light, it must be ensured in more portions of the reflection surface that the angle θ is 20 degrees or less.

[0015] Since the reflection surface **112** of the aforementioned active matrix substrate **100** has many portions which are greater than 20 degrees, reflected light is not very effectively used for displaying. In order to solve this problem, it might be possible to form an insulating layer under the reflective layer **110** and form the reflective layer **110** upon this

insulating layer. However, in this case, a step of forming an insulating layer and a step of forming contact holes for connecting the reflective layer **110** to the drains of the TFTs in the insulating layer are needed, thus resulting in a problem of an increase in the material and the number of steps.

[0016] Moreover, in the transfective-type liquid crystal display device of Patent Document 2, after stacking the interlayer insulating film **204** on the drain electrode **222**, a step of forming ruggednesses in an upper portion thereof is needed, and a step of stacking the galvanic corrosion preventing film **205**, the reflection electrode film **206**, and the amorphous transparent electrode film **218** further thereupon is needed. Thus, the conventional transfective-type liquid crystal display device also has a problem in that the material and number of steps are increased for forming the reflection region.

[0017] Furthermore, in a conventional transfective-type liquid crystal display device, ruggednesses are formed on the surface of the amorphous transparent electrode film **218**, which is in contact with the liquid crystal layer **211**, and therefore the electric field which is formed across the liquid crystal layer **211** is not uniform, thus making it difficult to uniformly control the liquid crystal orientation in a desired direction in the reflection region. Moreover, although a slope which conforms to the end shape of the interlayer insulating film **204** is formed at an end of the amorphous transparent electrode film **218**, there is also a problem in that this slope disturbs the orientation of the liquid crystal near the end of the reflection region.

[0018] Moreover, in the case where a storage capacitor (Cs) is formed in each pixel of a transfective-type liquid crystal display device, there has also been a problem in that the area of the transmission region is decreased due to the presence of a storage capacitor portion, a storage capacitor line (Cs line), or a TFT, thus resulting in a reduced aperture ratio of the liquid crystal display device. In particular, when a reflection region is to be formed in a storage capacitor portion, for example, trying to obtain a sufficiently broad reflection region will even necessitate an increased storage capacitance. In order to stably supply an electric charge to such a storage capacitor, there exists a problem in that the drain width of the TFT needs to be broadened, whereby a portion of the transmission region would be blocked and the aperture ratio lowered.

[0019] The present invention has been made in view of the above problems, and an objective thereof is to provide at low cost a transfective-type liquid crystal display device with a high image quality which has a high aperture ratio and an excellent efficiency of utility of reflected light.

MEANS FOR SOLVING THE PROBLEM

[0020] A liquid crystal display device according to the present invention is a liquid crystal display device having a plurality of pixels, and comprising, in each of the plurality of pixels, a transistor and a reflection section for reflecting incident light toward a display surface, wherein, the reflection section includes a metal layer, an insulating layer formed on the metal layer, a semiconductor layer formed on the insulating layer, and a reflective layer formed on the semiconductor layer; a plurality of recesses are formed on a surface of the reflective layer; a storage capacitor is formed between at least a portion of the metal layer and at least a portion of the reflective layer; and at least one of the metal layer and the reflective layer includes two portions which are electrically isolated from each other.

[0021] In one embodiment, the metal layer includes a first portion and a second portion which are electrically isolated from each other; the first portion of the metal layer is connected to a storage capacitor line; the reflective layer is connected to a drain of the transistor; and the storage capacitor is formed between the first portion of the metal layer and the reflective layer.

[0022] In one embodiment, the reflective layer includes a first portion and a second portion which are electrically isolated from each other; the first portion of the reflective layer is connected to a drain of the transistor; the metal layer is connected to a storage capacitor line; and the storage capacitor is formed between the metal layer and the first portion of the reflective layer.

[0023] In one embodiment, the metal layer includes a first portion and a second portion which are electrically isolated from each other; the reflective layer includes a first portion and a second portion which are electrically isolated from each other; the first portion of the metal layer is connected to a storage capacitor line; the first portion of the reflective layer is connected to a drain of the transistor; and the storage capacitor is formed between the first portion of the metal layer and the first portion of the reflective layer.

[0024] In one embodiment, the plurality of recesses include a first recess and a second recess overlapping the first recess.

[0025] In one embodiment, the first recess is formed so as to conform to the shape of the metal layer, and the second recess is formed so as to conform to the shape of the semiconductor layer.

[0026] In one embodiment, the metal layer includes an aperture or a recess, and the first recess is formed correspondingly to the aperture or recess in the metal layer.

[0027] In one embodiment, the semiconductor layer includes an aperture or a recess, and the second recess is formed correspondingly to the aperture or recess in the semiconductor layer.

[0028] In one embodiment, a level difference is formed on side faces of the plurality of recesses.

[0029] In one embodiment, the first recess and the second recess are formed based on the shape of an aperture or a recess which is included in at least two layers among the metal layer, the insulating layer, and the semiconductor layer.

[0030] In one embodiment, the metal layer, the semiconductor layer, and the reflective layer are formed from same materials as, respectively, a gate electrode, a semiconductor portion, and source and drain electrodes of the transistor.

[0031] One embodiment comprises: a liquid crystal layer; and an interlayer insulating layer and a pixel electrode interposed between the liquid crystal layer and the reflective layer, wherein a face of the pixel electrode facing the liquid crystal layer is formed flat without conforming to shapes of the recesses in the reflective layer.

EFFECTS OF THE INVENTION

[0032] According to the present invention, a transfective-type liquid crystal display device with a high image quality which has a high aperture ratio and an excellent efficiency of utility of reflected light can be provided at low cost.

BRIEF DESCRIPTION OF DRAWINGS

[0033]

[FIG. 1] A diagram schematically showing a cross-sectional shape of a liquid crystal display device according to the present invention.

[FIG. 2] A plan view showing the construction of pixel regions of a liquid crystal display device according to the present invention.

[FIG. 3] A plan view showing the construction of a pixel according to Embodiment 1.

[FIG. 4] Cross-sectional views showing the construction of a TFT section and a reflection section of Embodiment 1, where (a) shows the construction of a reflection section, and (b) shows the construction of a TFT section.

[FIG. 5] A schematic diagram for comparison of a liquid crystal display device according to the present invention and a conventional liquid crystal display device with respect to their reflection section constructions, where (a) is a diagram showing a cross section of a reflection section according to the present invention, (b) is a diagram showing a cross section of a conventional reflection section, and (c) is a diagram describing surface angles at a corner portion of the reflection section.

[FIG. 6] A plan view showing a pixel construction of a liquid crystal display device of Reference Example.

[FIG. 7] Plan views showing a production method for a reflection section of Embodiment 1.

[FIG. 8] Cross-sectional views showing a production method for a reflection section of Embodiment 1.

[FIG. 9] A plan view showing a reflection section of a liquid crystal display device according to Embodiment 2.

[FIG. 10] A plan view showing a reflection section of a liquid crystal display device according to Embodiment 3.

[FIG. 11] A cross-sectional view showing a liquid crystal display device according to Embodiment 4.

[FIG. 12] A cross-sectional view showing an active matrix substrate of a conventional reflection-type liquid crystal display device.

[FIG. 13] A cross-sectional view of a conventional transfective-type liquid crystal display device.

[FIG. 14] A diagram showing a relationship between a tilt of a reflection surface and reflected light in a liquid crystal display device, where (a) shows a relationship between an incident angle α and an outgoing angle β when light enters a medium b having a refractive index N_b from a medium a having a refractive index N_a , and (b) is a diagram showing a relationship between incident light and reflected light as well as the angle of the display surface of the liquid crystal display device.

DESCRIPTION OF REFERENCE NUMERALS

[0034]

10	liquid crystal display device
12	TFT substrate
14	counter substrate
16	liquid crystal
18	liquid crystal layer
22	transparent substrate
26	interlayer insulating layer
28	pixel electrode
30	reflection section
31	layer

	32	TFT section
	34	counter electrode
	36	CF layer
	38	transparent substrate
5	40	display surface
	42	reflection region
	44	TFT region
	46	transmission region
	48	recess
10	50, 50'	pixel
	52	source line
	53	drain
	54	gate line
	56	Cs line
15	56A, 56B, 56C, 56'	Cs metal layer
	58	contact hole
	61	insulating layer
	62	semiconductor layer
	63, 63A, 63B, 63'	reflective layer
20	65, 66	aperture
	68, 69	recess
	100	active matrix substrate
	101	insulative substrate
	102	gate layer
25	104	gate insulating layer
	106	semiconductor layer
	108	metal layer
	110	reflective layer
	112	reflection surface
30	203	switching element
	204	interlayer insulating film
	205	galvanic corrosion preventing film
	206	reflection electrode film
	211	liquid crystal layer
35	218	amorphous transparent electrode film
	222	drain electrode

BEST MODE FOR CARRYING OUT THE INVENTION

40 (Embodiment 1)

[0035] Hereinafter, with reference to the drawings, a first embodiment of the liquid crystal display device according to the present invention will be described.

45 **[0036]** FIG. 1 is a diagram schematically showing a cross-sectional shape of a liquid crystal display device **10** of the present embodiment. The liquid crystal display device **10** is a transfective-type liquid crystal display device (LCD) by an active matrix method. As shown in FIG. 1, the liquid crystal display device **10** includes a TFT (Thin Film Transistor) substrate **12**, a counter substrate **14** such as a color filter substrate (CF substrate), and a liquid crystal layer **18** containing liquid crystal **16** which is sealed between the TFT substrate **12** and the counter substrate **14**.

50 **[0037]** The TFT substrate **12** includes a transparent substrate **22**, an interlayer insulating layer **26**, and a pixel electrode **28**, and includes reflection sections **30** and TFT sections **32**. Note that gate lines (scanning lines), source lines (signal lines), Cs lines (storage capacitor lines), and the like are also formed on the TFT substrate **12**, which will be described later.

[0038] The counter substrate **14** includes a counter electrode **34**, a color filter layer (CF layer) **36**, and a transparent substrate **38**. The upper face of the transparent substrate **38** serves as a display surface **40** of the liquid crystal display device. Note that although the TFT substrate **12** and the counter substrate **14** each have an alignment film and a polarizer, they are omitted from the figure.

55 **[0039]** In the liquid crystal display device **10**, a region where a reflection section **30** is formed is referred to as a reflection region **42**, whereas a region where a TFT section **32** is formed is referred to as a TFT region **44**. In the reflection region, light entering from the display surface **40** is reflected by the reflection section **30**, and travels through the liquid

crystal layer **18** and the counter substrate **14** so as to go out from the display surface **40**. Furthermore, the liquid crystal display device **10** has transmission regions **46** which are formed in regions other than the reflection regions **42** and the TFT regions **44**. In the transmission regions **46**, light which is emitted from a light source in the liquid crystal display device **10** travels through the TFT substrate **12**, the liquid crystal layer **18**, and the counter substrate **14** so as to go out from the display surface **40**.

[0040] Note that, by providing a layer **31** made of transmissive resin or the like on the counter substrate **14** side above each reflection section **30** as shown in FIG. **1**, it is possible to reduce the thickness of the liquid crystal layer **18** in the reflection region **42** to a half of the thickness of the liquid crystal layer **18** in the transmission region **46**. As a result, the optical path length can be made equal between the reflection region **42** and the transmission region **46**. Although FIG. **1** illustrates the layer **31** as being formed between the counter electrode **34** and the CF layer **36**, the layer **31** may be formed on the face of the counter electrode **34** facing the liquid crystal layer **18**.

[0041] FIG. **2** is a plan view of a portion of the liquid crystal display device **10**, as seen from above the display surface **40**. As shown in the figure, a plurality of pixels **50** are disposed in a matrix shape in the liquid crystal display device **10**. The aforementioned reflection section **30** and TFT section **32** are formed in each pixel **50**, with a TFT being formed in the TFT section **32**.

[0042] In the border of the pixel **50**, source lines **52** extend along the column direction (up-down direction in the figure), and gate lines (also referred to as gate metal layers) **54** extend along the row direction (right-left direction in the figure). In the central portion of the pixel **50**, a Cs line **56** extends along the row direction. In the interlayer insulating layer **26** of the reflection section **30**, a contact hole **58** for connecting the pixel electrode **28** and the drain electrode of the TFT is formed. Hereinafter, the construction of the pixel **50** will be described more specifically with reference to FIG. **3**.

[0043] FIG. **3** is a plan view schematically showing the construction of the pixel **50**. In this figure, the contact hole **58** is omitted from illustration. As will be described later with reference to FIG. **4**, the reflection section **30** includes an insulating layer (also referred to as gate insulating layer) **61** formed on the Cs metal layers (also referred to as metal layers) **56A** and **56B**, a semiconductor layer **62** formed on the insulating layer **61**, and a reflective layer **63** formed on the semiconductor layer **62**.

[0044] The Cs metal layer (first portion) **56A** and the Cs metal layer (second portion or isolated portion) **56B** are formed in the same layer as and from the same material as the Cs line **56**, and the Cs metal layer **56A** is electrically connected to the Cs line **56**. The Cs metal layer **56B** is formed so as to be electrically isolated from the Cs line **56** and the Cs metal layer **56A**.

[0045] The reflective layer **63** is connected to a drain **53** of the TFT, so that a storage capacitor (Cs) is formed between the Cs metal layer **56A** and the reflective layer **63** thereabove. Herein, the Cs metal layer **56A** and the reflective layer **63** thereabove serve as a storage capacitor electrode and a counter electrode. Since the Cs metal layer **56B** is not electrically connected to the Cs line **56A**, the electrical capacitance between the reflective layer **63** and the Cs metal layer **56B** is substantially zero, so that no substantial electrical capacitance is formed therebetween.

[0046] As shown in FIG. **3**, a plurality of recesses **48** are formed on the surface of the reflective layer **63** in the reflection section **30**. Although six recesses **48** are illustrated herein for ease of understanding the construction, more recesses **48** may actually be formed. Moreover, although the plurality of recesses **48** are disposed at an equal interval vertically and laterally in the figure, they do not need to be disposed at an equal interval.

[0047] Each recess **48** includes a recess **68** and a recess **69** which is formed inside the recess **68**. The recess **68** is formed so as to conform to the shape of a recess or aperture in the Cs metal layer **56A** or **56B**, whereas the recess **69** is formed so as to conform to the shape of a recess or aperture in the semiconductor layer **62**. Note that the recess **69** does not need to be formed inside the recess **68**, but the recess **68** may be formed inside the recess **69**, or the recess **68** and the recess **69** may be formed so that their ends overlap or intersect.

[0048] In the present specification, the recess **68** and the recess **69** will be said to be overlapping in both a configuration in which one of the recess **68** and the recess **69** contains the other and a configuration in which the edges of the recesses overlap or intersect. Thus, since the recess **68** and the recess **69** overlap each other, level differences are formed on a side face of any recess **48** formed on the surface of the reflective layer **63**.

[0049] Next, with reference to FIG. **4**, the construction of the reflection section **30** and the TFT section **32** will be described more specifically.

[0050] FIG. **4(a)** shows a cross section of the reflection section **30** (a cross section of a portion shown by arrow **B** in FIG. **3**). Although this figure represents a cross section of the recess **48** formed on the Cs metal layer **56A**, a cross section of the recess **48** formed on the Cs metal layer **56B** also has a similar shape.

[0051] As shown in the figure, in the reflection section **30**, the Cs metal layer **56A** and **56B**, the insulating layer **61**, the semiconductor layer **62**, and the reflective layer **63** are stacked. The semiconductor layer **62** is composed of an intrinsic amorphous silicon layer (Si(i) layer) and an n⁺ amorphous silicon layer (Si(n⁺) layer) which is doped with phosphorus, for example.

[0052] The Cs metal layer **56A** and **56B** has an aperture **65**, whereas the semiconductor layer **62** has an aperture **66**. The aperture **66** is located inside the aperture **65**. The recess **68** is formed on the surface of the reflective layer **63**

above the aperture **65** of the Cs metal layer **56A** and **56B**, whereas the recess **69** is formed on the surface of the reflective layer **63** above the aperture **66** of the semiconductor layer **62**. Since the recess **68** and the recess **69** overlap, level differences are formed on the inner slope of the recess **48**.

[0053] The recess **68** is formed by stacking the reflective layer **63** over the aperture **65** of the Cs metal layer, via the insulating layer **61** and the semiconductor layer **62**. On the other hand, the recess **69** is formed as a result of forming the reflective layer **63** over the aperture **66** of the semiconductor layer. Note that a recess (dent) may be formed instead of the aperture **65** of the Cs metal layer or the aperture **66** of the semiconductor layer. In that case, the recess **68** and the recess **69** of the reflective layer **63** is to be formed in accordance with that recess (dent) in the Cs metal layer and the semiconductor layer.

[0054] By adding a level difference to the side face of the aperture **65** of the Cs metal layer, a level difference may be introduced to the side face of the recess **68** of the reflective layer. Moreover, by adding a level difference to the side face of the aperture **66** of the semiconductor layer **62**, a level difference may be introduced to the side face of the recess **69** of the reflective layer. Moreover, by further providing an aperture or a recess in the insulating layer **61**, a recess may be formed in the reflective layer. Moreover, instead of the aperture **65** of the Cs metal layer or the aperture **66** of the semiconductor layer, an aperture or a recess may be provided in the insulating layer **61**, thereby forming the recess **68** or **69** of the reflective layer. In either case, the recesses **68** and **69** of the reflective layer can be formed based on the shapes of the apertures or the recesses which are included in at least two layers among the Cs metal layer, the insulating layer, and the semiconductor layer.

[0055] Instead of forming an aperture or a recess in the Cs metal layer, the insulating layer, or the semiconductor layer, these layers may be formed in island shapes at a recess position. In this case, a plurality of protrusions will be formed in the reflective layer **63** corresponding to these layers which are disposed in island shapes, and a plurality of mutually overlapping recesses having a level difference on the side face will be formed in the neighborhood of these protrusions.

[0056] FIG. 4(b) is a diagram showing the construction of the gate metal layer (metal layer) **54**, the insulating layer (gate insulating layer) **61**, the semiconductor layer **62**, and the reflective layer **63** in the TFT section **32**, and is a cross-sectional view of a portion at arrow **A** in FIG. 2. The gate metal layer **54** in the TFT section **32** is formed concurrently with and from the same members as the Cs line **56** and the Cs metal layer **56A** and **56B** in the reflection section **30**. Similarly, the insulating layer **61**, the semiconductor layer **62**, and the reflective layer **63** in the TFT section **32** are formed concurrently with and from the same members as, respectively, the insulating layer **61**, the semiconductor layer **62**, and the reflective layer **63** in the reflection section **30**. The reflective layer **63** is connected to the drain electrode of the TFT.

[0057] FIG. 5 is cross-sectional views for structural comparison between the reflection section **30** of Embodiment 1 and the reflection section of the conventional liquid crystal display device shown in FIG. 12. FIG. 5(a) schematically shows the structure of the reflection section **30** of Embodiment 1, and FIG. 5(b) schematically shows the structure of the reflection section of the conventional liquid crystal display device. Note that, in these figures, for simplicity, the slopes of each layer of the reflection section **30** and the slopes of each layer of the conventional liquid crystal display device are illustrated as vertical planes, and the corner portions of each level difference (portions shown by dotted circles in the figure) are illustrated as making perpendicular turns.

[0058] As shown in these figures, on the surface of the reflective layer **63** in the reflection section **30** of Embodiment 1, a total of eight corner portions are formed by one recess **48**. On the other hand, in the conventional liquid crystal display device, only four corner portions are formed in one recess of the reflection section.

[0059] Although these corner portions are illustrated as being perpendicular in FIGS. 5(a) and (b), in an actual corner portion, as shown in FIG. 5(c), a face having angles which are larger than 20 degrees (exemplified as 30 degrees in this figure) with respect to the substrate is continuously formed from a plane (with an angle of 0 degrees) which is parallel to the substrate. Therefore, by forming more recesses in the reflection section, it becomes possible to form more faces (effective reflection surfaces) whose angle with respect to the substrate is 20 degrees or less on the surface of the reflective layer.

[0060] Moreover, since the effective reflection surfaces that are formed in a corner portion have various tilting angles which are different from one another, the reflected light will not travel in one fixed direction. Therefore, by forming more recesses, it becomes possible to obtain more reflected light which spans a broad range. Moreover, by increasing the number of recesses and ensuring that the tilting angle of the side face of any recess is 20 degrees or less, more reflected light which spans an even broader range can be obtained.

[0061] As shown in FIGS. 5(a) and (b), more corner portions than in the conventional liquid crystal display device are formed in the reflection section **30** of Embodiment 1. This makes it possible to form more effective reflection surfaces on the surface of the reflective layer **63**, whereby more light can be reflected toward the display surface across a broad range. Moreover, the recess **48** is formed in accordance with the shapes to which the Cs metal layer and the semiconductor layer are shaped. Therefore, the shapes, depths, the slope tilting angles, and the like of the recess **48** can be easily adjusted during the shaping of the Cs metal layer or the semiconductor layer.

[0062] Moreover, the reflective layer **63** which is located inside the recess **48** in Embodiment 1 is formed above the

insulating layer **61**, or above the insulating layer **61** and the semiconductor layer **62**. On the other hand, in the conventional liquid crystal display device, the reflective layer inside the recess is directly formed on the glass substrate, via neither the gate insulating layer nor the semiconductor layer. Therefore, the bottom face of the recess **48** of Embodiment 1 is formed at a position shallower than the bottom face of a recess of the conventional liquid crystal display device. As a result, incident light can be reflected more effectively across a broad range.

[0063] In the conventional liquid crystal display device, the bottom face of a recess is formed at a deep position, so that the tilting angle of the recess inner surface is large, which makes it difficult to form a large number of effective reflection surfaces having a tilt of 20 degrees or less within the recess. Moreover, since this recess is formed by forming the gate layer **102**, the gate insulating layer **104**, and the semiconductor layer **106**, and thereafter altogether removing these layers, it has been difficult to increase the effective reflection surface by controlling the tilting angle of the recess inner surface.

[0064] In the display device of the present embodiment, a recess in the reflective layer is formed in accordance with the shapes of the Cs metal layer and the semiconductor layer, and therefore the position, size, and shape of the recess can be adjusted when stacking these layers. As a result, the tilt of the recess slope can be controlled, whereby a larger number of effective reflection surfaces with a tilt of 20 degrees or less can be formed, thus allowing more light to be reflected toward the display surface.

[0065] Furthermore, in the liquid crystal display device of the present embodiment, as shown in FIG. **1**, the faces of the interlayer insulating layer **26** and the pixel electrode **28** that are on the liquid crystal layer **18** side are formed flat without conforming to the shapes of the recesses of the reflective layer **63**, similarly to the face of the counter electrode **34** that is on the liquid crystal layer **18** side. Therefore, as compared to the conventional transmissive-type liquid crystal display device shown in FIG. **13**, the electric field which is formed across the liquid crystal layer **18** becomes uniform, thus making it possible to uniformly control the orientation of the liquid crystal of the reflection region **42** in a desired direction.

[0066] Moreover, since no level differences are formed in the pixel electrode **28** near the ends of the reflection section **30**, the liquid crystal orientation is not disturbed. As a result, according to the present embodiment, a liquid crystal display device can be provided which has a high transmittance and excellent viewing angle characteristics, with little display unevenness.

[0067] Furthermore, according to the liquid crystal display device of Embodiment 1, advantages which are described below with reference to FIG. **6** can also be obtained.

[0068] FIG. **6** is a plan view showing the construction of a pixel **50'** of a liquid crystal display device of Reference Example. This liquid crystal display device has a similar construction to that of the liquid crystal display device of Embodiment 1 except as shown in FIG. **6**. Moreover, the construction of the pixel **50'** is similar to the construction of Embodiment 1 except for the portion described below. Constituent elements which are identical to those of the liquid crystal display device of Embodiment 1 are denoted by like numerals, and the descriptions thereof are omitted.

[0069] In the liquid crystal display device of Reference Example, as shown in the figure, a Cs metal layer **56'** and a reflective layer **63'** in the reflection section **30** are both formed across the entire reflection section **30**, and have no electrically isolated portions. Therefore, a storage capacitor is formed by the entire reflective layer **63'** and the entire Cs metal layer **56'** in the reflection section **30**.

[0070] In a transmissive-type liquid crystal display device, in order to efficiently utilize external light or to obtain a required reflectance according to the manner of use, it is necessary allow the reflection section **30** to have an area of a specific proportion (e.g. corresponding to a reflectance of 3%) relative to the pixel area. However, as in the liquid crystal display device of Reference Example, when a storage capacitor is formed by the reflective layer **63'** and the Cs metal layer **56'** which span the entire reflection section **30**, in order to charge the storage capacitor at a practically suitable speed, the width of the TFT (or the width of the drain of the TFT) **W'** needs to be set to be relatively broad. This not only reduces the area of the transmission region and lowers the aperture ratio of the pixel, but also induces a deterioration in the production efficiency of the device and an increase in cost.

[0071] In the liquid crystal display device of Embodiment 1, as shown in FIG. **3**, the Cs metal layer in the reflection section **30** is split into two portions (**56A** and **56B**) which are electrically isolated from each other, and a storage capacitor is formed only of the portion corresponding to the Cs metal layer **56A**. Therefore, according to Embodiment 1, while ensuring a required reflectance, a storage capacitor of a necessary size can be obtained. As a result, there is no need to form the size of the TFT or the width **W** of the TFT to be larger than necessary, whereby the aperture ratio of the pixel can be increased. Furthermore, the production efficiency of the device can be enhanced, and the production cost can be reduced.

[0072] Next, a production method for the TFT substrate **12** will be described with reference to FIG. **7** and FIG. **8**. FIG. **7** is plan views showing a production process, in the reflection region **42**, for the TFT substrate **12**; and FIG. **8** is cross-sectional views showing a production process, in the reflection region **42**, for the TFT substrate **12** (a portion shown at arrow **B** in FIG. **3**).

[0073] As shown in FIG. **7(a)** and FIG. **8(a)**, first, by a method such as sputtering, a thin metal film of Al (aluminum)

is formed on the transparent substrate **22** having been cleaned. Other than Al, this thin metal film may be formed by using Ti (titanium), Cr (chromium), Mo (molybdenum), Ta (tantalum), W (tungsten), or an alloy thereof, etc., or formed from a multilayer body of a layer of such materials and a nitride film.

[0074] Thereafter, a resist film is formed on the thin metal film, and after forming a resist pattern through an exposure-development step, a dry or wet etching is performed to form the Cs metal layer **56A** and **56B** having the apertures **65**. The thickness of the Cs metal layer **56A** and **56B** is 50 to 1000 nm, for example. Note that, although the apertures **65** are illustrated as being formed in the Cs metal layer, a projecting shape of Cs metal layer (or an island-shaped layer) may be formed only at the position of each aperture, by using a resist pattern in which the light shielding portions and the transmitting portions are inverted in the reflection section **30**. In this step, the gate line **54** and the Cs line **56** shown in FIG. **2** and the gate metal layer **54** of the TFT section **32** shown in FIG. **4(b)** are also formed concurrently from the same metal.

[0075] Next, as shown in FIG. **7(b)** and FIG. **8(b)**, by using P-CVD technique and a gaseous mixture of SiH_4 , NH_3 , and N_2 , the insulating layer **61** composed of SiN (silicon nitride) is formed across the entire substrate surface. The insulating layer **61** may also be composed of SiO_2 (silicon oxide), Ta_2O_5 (tantalum oxide), Al_2O_3 (aluminum oxide), or the like. The thickness of the insulating layer **61** is 100 to 600 nm, for example. In this step, the insulating layer **61** of the TFT section **32** shown in FIG. **4(b)** is also formed concurrently.

[0076] Next, on the gate insulating layer **61**, an amorphous silicon (a-Si) film and an $\text{n}^+\text{a-Si}$ film obtained by doping amorphous silicon with phosphorus (P) are formed. The thickness of the a-Si film is 30 to 300 nm. The thickness of the $\text{n}^+\text{a-Si}$ film is 20 to 100 nm. Thereafter, these films are patterned by photolithography technique and etching technique, whereby the semiconductor layer **62** having the apertures **66** is formed. Herein, the semiconductor layer **62** may be formed only at positions corresponding to the apertures, by using a resist pattern in which the light shielding portions and the transmitting portions are inverted in the reflection section **30**. In this step, the semiconductor layer **62** of the TFT section **32** shown in FIG. **4(b)** is also formed concurrently.

[0077] Next, as shown in FIG. **7(c)** and FIG. **8(c)**, a thin metal film of Al or the like is formed across the entire substrate surface by sputtering technique or the like, thus forming the reflective layer **63**. For the thin metal film, the materials which are mentioned above as materials for the Cs metal layer **56** may be used. The thickness of the reflective layer **63** is 30 to 1000 nm or less.

[0078] At this time, the recess **68** is formed on the surface of the reflective layer **63** above each aperture **65** in the Cs metal layer **56A** and **56B**, and the recess **69** is formed on the surface of the reflective layer **63** above each aperture **66** in the semiconductor layer **62**. In this step, the reflective layer **63** of the TFT section **32** shown in FIG. **4(b)** is also formed concurrently, and in the TFT section **32**, the reflective layer **63** forms a source electrode and a drain electrode of the TFT. Also at this time, the source line **52** in FIG. **2** is also formed as a portion of the reflective layer **63**.

[0079] Next, as shown in FIG. **7(d)** and FIG. **8(d)**, a photosensitive acrylic resin is applied by spin-coating, whereby the interlayer insulating layer (interlayer resin layer) **26** is formed. The thickness of the interlayer insulating layer **26** is 0.3 to 5 μm or less. Although a thin film such as SiN_x or SiO_2 may be formed by P-CVD technique as a protection film between the reflective layer **63** and the interlayer insulating layer **26**, such is omitted from the figure. The thickness of the protection film is 50 to 1000 nm or less. The interlayer insulating layer **26** and the protection film are formed not only on the reflection region **42**, but also on the entire upper surface of the transparent substrate **22** including the TFT region **44**. Thereafter, through a development process using an exposure apparatus, a contact hole **58** is formed near the center of the reflection section **30**.

[0080] Next, as shown in FIG. **7(e)** and FIG. **8(e)**, a transparent electrode film of ITO, IZO, or the like is formed on the interlayer insulating layer **26** by sputtering technique or the like, and this transparent electrode film is subjected to pattern shaping by photolithography technique, whereby the pixel electrode **28** is formed. The pixel electrode **28** is formed not only on the reflection region **42** but also on the entire upper surface of the pixel including the TFT region **44**.

[0081] In the reflection region **42**, the pixel electrode **28** is formed above the interlayer insulating layer **26** and the contact hole **58**, such that the metal member of the pixel electrode **28** is in contact with the reflective layer **63** via the contact hole **58**. As a result, the drain electrode of the TFT in the TFT section **32** is electrically connected to the pixel electrode **28** via the contact hole **58**. In the above step, the upper face of the interlayer insulating layer **26** and the surface of the pixel electrode **28** are formed flat without conforming to the shapes of the recesses **48** in the reflective layer **63**.

[0082] Preferably, as many recesses **68** and **69** as possible are formed in the reflective layer **63**. Therefore, it is preferable that as many apertures in the Cs metal layer and the semiconductor layer as possible are formed, within the limitations of the masks and photoexposure during the production step. The preferable maximum width of each aperture in the Cs metal layer and the semiconductor layer is 2 to 17 μm .

[0083] According to the present embodiment, reflected light can be utilized efficiently, and not only a necessary reflectance is ensured but also a higher aperture ratio can be obtained. Furthermore, the production efficiency can be improved, and the production cost can be reduced. Therefore, a liquid crystal display device which is capable of high-quality displaying with a high luminance can be provided inexpensively.

(Embodiment 2)

[0084] Hereinafter, a second embodiment of the liquid crystal display device according to the present invention will be described. Constituent elements which are identical to those of Embodiment 1 are denoted by like reference numerals, and the descriptions thereof are omitted.

[0085] The liquid crystal display device of the present embodiment basically has the same construction as that of the liquid crystal display device **10** of Embodiment 1 described above, except only for the construction of the Cs metal layer and the reflective layer in the reflection section **30**. Therefore, the construction of the reflection section **30** will be mainly described below, while omitting the descriptions of any other portions.

[0086] FIG. **9** is a plan view schematically showing the construction of a pixel **50** of the liquid crystal display device of Embodiment 2. In Embodiment 2, a Cs metal layer **56C** is formed across the entire reflection section **30**, and as shown in FIG. **4**, an insulating layer **61** and a semiconductor layer **62** are formed above the Cs metal layer **56C**. On the semiconductor layer **62**, a reflective layer (first portion) **63A** and a reflective layer (second portion or isolated portion) **63B** are formed. The reflective layer **63A** is connected to a drain **53** of the TFT, and the reflective layer **63B** is electrically isolated from the reflective layer **63A**.

[0087] The reflective layer **63A** and the reflective layer **63B** are concurrently formed in the same layer, and from the same material. The Cs metal layer **56C** is formed in the same layer and from the same material as the Cs line **56** concurrently, and is electrically connected to the Cs line **56**. The Cs metal layer **56C** and the reflective layer **63A** serve as a storage capacitor electrode and a counter electrode, both of which form a storage capacitor (Cs). Since the reflective layer **63B** is not electrically connected to the drain **53** of the TFT, no substantial electrical capacitance is formed between the reflective layer **63B** and the Cs metal layer **56C**.

[0088] On the surface of the reflective layers **63A** and **63B** in the reflection section **30**, similarly to Embodiment 1, a plurality of recesses **48** are formed. The structure, formation method, and the like of the recesses **48** and the effects and the like obtained by forming the recesses **48** are as set forth in the descriptions of Embodiment 1. Although not shown in the figure, the contact holes **58** as shown in FIG. **2** are formed in the reflective layer **63A**.

[0089] In the liquid crystal display device of Embodiment 2, the reflective layer in the reflection section **30** is split into two portions (**63A** and **63B**) which are electrically isolated from each other, and a storage capacitor is formed only of the portion corresponding to the reflective layer **63A**. Therefore, according to Embodiment 2, a storage capacitor of a necessary size can be obtained while ensuring a required reflectance, similarly to Embodiment 1. As a result, there is no need to form the TFT to be larger than necessary, whereby the aperture ratio of the pixel can be enhanced. Furthermore, the production efficiency of the device can be enhanced, and the production cost can be reduced.

(Embodiment 3)

[0090] Hereinafter, a third embodiment of the liquid crystal display device according to the present invention will be described. Constituent elements which are identical to the constituent elements of Embodiments 1 and 2 are denoted by like reference numerals, and the descriptions thereof are omitted.

[0091] The liquid crystal display device of the present embodiment basically has the same construction as that of the liquid crystal display device **10** of Embodiment 1 described above, except only for the construction of the Cs metal layer and the reflective layer in the reflection section **30**. Therefore, the construction of the reflection section **30** will be mainly described below, while omitting the descriptions of any other portions.

[0092] FIG. **10** is a plan view schematically showing the construction of a pixel **50** of the liquid crystal display device of Embodiment 3. In Embodiment 3, a Cs metal layer **56A** and a Cs metal layer **56B** which are electrically isolated from each other are formed in the reflection section **30**, and an insulating layer **61** and a semiconductor layer **62** are formed above both, as shown in FIG. **4**. A reflective layer (first portion) **63A** is formed on the semiconductor layer **62** above the Cs metal layer **56A**, and a reflective layer (second portion or isolated portion) **63B** is formed on the semiconductor layer **62** above the Cs metal layer **56B**. The reflective layer **63A** and the reflective layer **63B** are electrically isolated from each other.

[0093] The reflective layer **63A** and the reflective layer **63B** are concurrently formed in the same layer, and from the same material. The Cs metal layer **56A** and the Cs metal layer **56B** are formed in the same layer and from the same material as the Cs line **56** concurrently. The Cs metal layer **56A** is connected to the Cs line **56**, whereas the reflective layer **63A** is connected to a drain **53** of the TFT.

[0094] The Cs metal layer **56A** and the reflective layer **63A** serve as a storage capacitor electrode and a counter electrode, both of which form a storage capacitor (Cs). Since the Cs metal layer **56B** is not connected to the Cs line **56** and the reflective layer **63B** is not electrically connected to the drain **53** of the TFT, no substantial electrical capacitance is formed between the Cs metal layer **56B** and the reflective layer **63B**.

[0095] On the surface of the reflective layers **63A** and **63B** in the reflection section **30**, a plurality of recesses **48** are formed, similarly to Embodiment 1. The structure, formation method, and the like of the recesses **48** and the effects and

the like obtained by forming the recesses **48** are as set forth in the descriptions of the Embodiment 1. Although not shown in the figure, the contact holes **58** as shown in FIG. **2** are formed in the reflective layer **63A**.

[0096] In the liquid crystal display device of Embodiment 3, each of the Cs metal layer and the reflective layer in the reflection section **30** is split into two portions which are electrically isolated from each other, and a storage capacitor is formed only of the Cs metal layer **56A** and the reflective layer **63A**. Thus, according to Embodiment 3, a storage capacitor of a necessary size can be obtained while ensuring a required reflectance, similarly to Embodiment 1. As a result, there is no need to form the TFT to be larger than necessary, whereby the aperture ratio of the pixel can be enhanced. Furthermore, the production efficiency of the device can be enhanced, and the production cost can be recorded.

(Embodiment 4)

[0097] Hereinafter, with reference to the drawings, a fourth embodiment of the liquid crystal display device according to the present invention will be described. Constituent elements which are identical to the constituent elements of Embodiments 1 to 3 are denoted by like reference numerals, and the descriptions thereof are omitted.

[0098] FIG. **11** is a diagram schematically showing a cross-sectional shape of the liquid crystal display device of the present embodiment. This liquid crystal display device is based on the liquid crystal display devices of Embodiments 1 to 3 from which the interlayer insulating layer **26** is excluded, and is identical to the liquid crystal display devices of Embodiments 1 to 3 except for the points discussed below. Note that, in FIG. **11**, the detailed structure of the counter substrate **14** and the TFT section **32** are omitted from illustration.

[0099] As shown in the figure, in Embodiment 4, no interlayer insulating layer **26** is formed, and therefore the pixel electrode **28** is formed upon the reflective layer **63** in the reflection section **30** and the TFT section **32**, via an insulative film not shown. The structure and production method for the reflection section **30** and the TFT section **32** are the same as those which were described in Embodiment 1 except that the interlayer insulating layer **26** is eliminated. The pixel layout and wiring structure in the display device are also similar to what is shown in FIG. **2**. Also with the construction of Embodiment 4, similarly to Embodiments 1 to 3, the effective reflection surface of the reflective layer is expanded in area, so that more light can be reflected toward the display surface, and the aperture ratio of the transmission region can be increased.

[0100] Embodiments 1 to 4 illustrate that the apertures in the Cs metal layer and the semiconductor layer and the recesses in the reflective layer are circular, but they may be formed into ellipses, polygons such as triangles or rectangles, or formed into various shapes such as apertures or recesses with sawtoothed edges, or combinations thereof.

[0101] As has been illustrated by the above Embodiments, a liquid crystal display device according to the present invention includes a large number of level differences and corner portions on the surface of a reflective layer, as well as a large number of slopes with a tilting angle of 20 degrees or less, and therefore acquires reflection regions with broad effective reflection surfaces and excellent scattering characteristics. Moreover, since the shape of the reflective layer surface is not likely to have symmetry, occurrence of moiré and coloration due to interference of reflected light can be reduced or prevented. Thus, a liquid crystal display device having a high brightness and being capable of clear displaying can be provided.

[0102] Moreover, since the level differences and corner portions on the reflection surface are formed in accordance with the shapes of the Cs metal layer and the semiconductor layer just when they are shaped, reflection regions having excellent reflection characteristics can be easily obtained without increasing the production steps. Furthermore, since the liquid crystal display device according to the present invention is formed by the above-described production method, it can be produced with the same material and the same steps as those of a transmission-type liquid crystal display device. Therefore, a high-quality liquid crystal display device can be provided inexpensively.

[0103] Furthermore, according to the present invention, the face of a pixel electrode facing the liquid crystal layer is formed flat, similarly to its face on the counter electrode side, and no level difference is formed in the pixel electrode near the end of the reflection section, thus making it possible to uniformly control the orientation of liquid crystal in a desired direction. Therefore, it is possible to provide a liquid crystal display device which has a high transmittance, excellent viewing angle characteristics, and little display unevenness.

[0104] Moreover, according to the present invention, while ensuring a necessary reflectance, the storage capacitors can be reduced to an appropriate size, and thus the TFTs can be formed to be smaller. Therefore, the transmission regions can be increased in area, whereby the aperture ratio of the liquid crystal display device can be increased. This makes possible a high-quality displaying with a higher luminance.

[0105] The liquid crystal display device according to the present invention encompasses display apparatuses, television sets, mobile phones, etc., in which a liquid crystal panel is utilized.

INDUSTRIAL APPLICABILITY

[0106] According to the present invention, a transfective-type liquid crystal display device having a high image quality

can be provided inexpensively. Liquid crystal display devices according to the present invention are suitably used for various transfective-type liquid crystal display devices, e.g., mobile phones, onboard display devices such as car navigation systems, display devices of ATMs and vending machines, etc., portable display devices, laptop PCs, and the like.

5

Claims

1. A liquid crystal display device having a plurality of pixels, and comprising, in each of the plurality of pixels, a transistor and a reflection section for reflecting incident light toward a display surface, wherein,
 10 the reflection section includes a metal layer, an insulating layer formed on the metal layer, a semiconductor layer formed on the insulating layer, and a reflective layer formed on the semiconductor layer;
 a plurality of recesses are formed on a surface of the reflective layer;
 a storage capacitor is formed between at least a portion of the metal layer and at least a portion of the reflective layer; and
 15 at least one of the metal layer and the reflective layer includes two portions which are electrically isolated from each other.
2. The liquid crystal display device of claim 1, wherein,
 the metal layer includes a first portion and a second portion which are electrically isolated from each other;
 20 the first portion of the metal layer is connected to a storage capacitor line;
 the reflective layer is connected to a drain of the transistor; and
 the storage capacitor is formed between the first portion of the metal layer and the reflective layer.
3. The liquid crystal display device of claim 1, wherein,
 25 the reflective layer includes a first portion and a second portion which are electrically isolated from each other;
 the first portion of the reflective layer is connected to a drain of the transistor;
 the metal layer is connected to a storage capacitor line; and
 the storage capacitor is formed between the metal layer and the first portion of the reflective layer.
4. The liquid crystal display device of claim 1, wherein,
 30 the metal layer includes a first portion and a second portion which are electrically isolated from each other;
 the reflective layer includes a first portion and a second portion which are electrically isolated from each other;
 the first portion of the metal layer is connected to a storage capacitor line;
 the first portion of the reflective layer is connected to a drain of the transistor; and
 35 the storage capacitor is formed between the first portion of the metal layer and the first portion of the reflective layer.
5. The liquid crystal display device of any one of claims 1 to 4, wherein the plurality of recesses include a first recess and a second recess overlapping the first recess.
6. The liquid crystal display device of claim 5, wherein the first recess is formed so as to conform to the shape of the metal layer, and the second recess is formed so as to conform to the shape of the semiconductor layer.
7. The liquid crystal display device of claim 5 or 6, wherein the metal layer includes an aperture or a recess, and the first recess is formed correspondingly to the aperture or recess in the metal layer.
8. The liquid crystal display device of any one of claims 5 to 7, wherein the semiconductor layer includes an aperture or a recess, and the second recess is formed correspondingly to the aperture or recess in the semiconductor layer.
9. The liquid crystal display device of any one of claims 5 to 8, wherein a level difference is formed on a side face of the plurality of recesses.
10. The liquid crystal display device of claim 5, wherein the first recess and the second recess are formed based on the shape of an aperture or a recess which is included in at least two layers among the metal layer, the insulating layer, and the semiconductor layer.
11. The liquid crystal display device of any one of claims 1 to 10, wherein the metal layer, the semiconductor layer, and the reflective layer are formed from same materials as, respectively, a gate electrode, a semiconductor portion, and source and drain electrodes of the transistor.

55

12. The liquid crystal display device of any one of claims 1 to 11, comprising: a liquid crystal layer; and an interlayer insulating layer and a pixel electrode interposed between the liquid crystal layer and the reflective layer, wherein a face of the pixel electrode facing the liquid crystal layer is formed flat without conforming to shapes of the recesses in the reflective layer.

5

10

15

20

25

30

35

40

45

50

55

FIG. 1




FIG.2




FIG. 3





FIG. 4

(a)



(b)




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9





FIG. 10










FIG.14

(a)



INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP2007/073557

A. CLASSIFICATION OF SUBJECT MATTER G02F1/1335(2006.01)i, G02F1/1343(2006.01)i, G02F1/1368(2006.01)i		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) G02F1/1335, G02F1/1343, G02F1/1368		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Jitsuyo Shinan Koho 1922-1996 Jitsuyo Shinan Toroku Koho 1996-2007 Kokai Jitsuyo Shinan Koho 1971-2007 Toroku Jitsuyo Shinan Koho 1994-2007		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	JP 2004-258366 A (Seiko Epson Corp.), 16 September, 2004 (16.09.04), Full text; Figs. 1 to 10 (Family: none)	1-12
A	JP 9-54318 A (NEC Corp.), 25 February, 1997 (25.02.97), Full text; Figs. 1 to 36 & US 6208395 B1	1-12
A	JP 11-337974 A (Semiconductor Energy Laboratory Co., Ltd.), 10 December, 1999 (10.12.99), Full text; Figs. 1 to 14 & US 6839108 B1	1-12
☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 28 December, 2007 (28.12.07)		Date of mailing of the international search report 15 January, 2008 (15.01.08)
Name and mailing address of the ISA/ Japanese Patent Office		Authorized officer
Facsimile No.		Telephone No.

Form PCT/ISA/210 (second sheet) (April 2007)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP2007/073557

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	JP 11-109390 A (Toshiba Corp.), 23 April, 1999 (23.04.99), Full text; Figs. 1 to 5 (Family: none)	1-12

Form PCT/ISA/210 (continuation of second sheet) (April 2007)

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 9054318 A [0006]
- JP 2005277402 A [0006]

专利名称(译)	液晶显示装置		
公开(公告)号	EP2128690A1	公开(公告)日	2009-12-02
申请号	EP2007850173	申请日	2007-12-06
[标]申请(专利权)人(译)	夏普株式会社		
申请(专利权)人(译)	夏普株式会社		
当前申请(专利权)人(译)	夏普株式会社		
[标]发明人	IMAI HAJINE MATSUMOTO HITOSHI		
发明人	IMAI, HAJINE MATSUMOTO, HITOSHI		
IPC分类号	G02F1/1335 G02F1/1343 G02F1/1368		
CPC分类号	G02F1/136213 G02F1/133371 G02F1/133555 G02F2201/34		
优先权	2007013654 2007-01-24 JP		
其他公开文献	EP2128690B1 EP2128690A4		
外部链接	Espacenet		

摘要(译)

本发明提供一种低成本的具有高图像质量的半透射型液晶显示装置,其具有高孔径比和优异的反射光效用。根据本发明的液晶显示装置是在多个像素的每一个中具有晶体管和反射部分的液晶显示装置;反射部分包括金属层,形成在金属层上的绝缘层,形成在绝缘层上的半导体层,以及形成在半导体层上的反射层;在反射层的表面上形成多个凹槽;在至少一部分金属层和至少一部分反射层之间形成存储电容器;金属层和反射层中的至少一个包括彼此电隔离的两个部分。

FIG. 3

