



(11) **EP 2 372 437 A1**

(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
05.10.2011 Bulletin 2011/40

(51) Int Cl.:
G02F 1/1335^(2006.01) G02F 1/1333^(2006.01)
G09F 9/30^(2006.01)

(21) Application number: **09834245.4**

(86) International application number:
PCT/JP2009/003743

(22) Date of filing: **05.08.2009**

(87) International publication number:
WO 2010/073427 (01.07.2010 Gazette 2010/26)

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

(72) Inventor: **ENOMOTO Hiromi**
Osaka-shi, Osaka 545-8522 (JP)

(30) Priority: **26.12.2008 JP 2008334594**

(74) Representative: **Rocke, Carsten**
Müller-Boré & Partner
Grafinger Strasse 2
D-81671 München (DE)


(71) Applicant: **Sharp Kabushiki Kaisha**
Osaka-shi, Osaka 545-8522 (JP)

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

(57) A liquid crystal display device includes a first substrate having a plurality of pixels defined thereon, each of which is provided with a reflection layer, a second substrate disposed opposite the first substrate, and a display surface which displays images by the pixels, where

the display surface is curved in one direction, and each of the reflection layers is formed so that a reflectance of light reflected from each of the reflection layers in a direction normal to the display surface is higher in both edge portions in a curvature direction than in a middle portion in the curvature direction on the display surface.

FIG.3



EP 2 372 437 A1

Description

TECHNICAL FIELD

[0001] The present invention relates to liquid crystal display (hereinafter referred to as "LCD") devices.

BACKGROUND ART

[0002] A transmissive LCD device is configured such that light of a backlight unit is transmitted through an LCD panel having a pair of substrates bonded together, and images are generated by the transmitted light. In addition to the transmissive LCD devices, reflective and transreflective LCD devices are conventionally known. A reflective LCD device is configured such that light of a front light unit, or external light, incident upon an LCD panel is reflected from a substrate opposite the one in the incident side, and images are generated by the reflected light. A transreflective LCD device is configured such that images are generated by using both the transmitted light and the reflected light.

[0003] The reflective and the transreflective LCD devices are each provided with a reflection layer to reflect light in each pixel of the LCD panel. The surface of each reflection layer is formed with a homogeneous raised and recessed profile in each pixel in order to scatter the light incident from the surroundings, and to uniformly reflect the light toward the front of the LCD device, and the raised and recessed profile of each reflection layer is formed so that the reflectance of light in the direction normal to the display surface is relatively high to allow bright display (see, e.g., Patent Document 1).

CITATION LIST

PATENT DOCUMENT

[0004]

PATENT DOCUMENT 1: Japanese Patent Publication No. 2002-221716

SUMMARY OF THE INVENTION

TECHNICAL PROBLEM

[0005] However, if a flat LCD panel is transformed only to a curved shape in order to produce a curved reflective or transreflective LCD device, the direction of light reflected uniformly from each reflection layer varies along the curved shape of the LCD panel, and thus the reflectance of light in the direction toward the front of the LCD device is likely to decrease along the directions from the middle portion to the both edge portions in the curvature direction on the display surface. Accordingly, a curved LCD device has a problem in that brightness may vary along the curvature direction of the display surface.

[0006] The present invention was made in view of the above problem, and it is an object of the present invention to reduce variation in brightness and to improve display quality in curved LCD devices.

SOLUTION TO THE PROBLEM

[0007] In order to achieve the above object, in the present invention, the reflection layer provided in each pixel is formed so that the reflectance of light reflected from each reflection layer in the direction normal to the display surface is higher in both edge portions in the curvature direction than in a middle portion in the curvature direction on the display surface.

[0008] Specifically, a liquid crystal display device according to the present invention includes a first substrate having a plurality of pixels defined thereon, each of which is provided with a reflection layer, a second substrate disposed opposite the first substrate, and a display surface configured to display images by the pixels, where the display surface is curved in one direction; and each of the reflection layers is formed so that a reflectance of light reflected from each of the reflection layers in a direction normal to the display surface is higher in both edge portions in a curvature direction than in a middle portion in the curvature direction on the display surface.

[0009] As used herein, the term "curvature direction" means the direction along the curvature of the display surface.

[0010] With this configuration, each of the reflection layers is formed so that the reflectance of light reflected from each of the reflection layers in the direction normal to the display surface is higher in both edge portions in the curvature direction than in a middle portion in the curvature direction on the display surface. Accordingly, the reflectance of light reflected from each of the reflection layers toward the front of the LCD device is higher in the both edge portions in the curvature direction relative to that in a middle portion in the curvature direction on the display surface, and thus variation in brightness is reduced, and display quality is improved in the curved LCD device.

[0011] A surface of each of the reflection layers may be formed with a raised and recessed profile, and the raised and recessed profile of each of the reflection layers may be formed so that the reflectance of each of the reflection layers is higher in the both edge portions in the curvature direction than in the middle portion in the curvature direction on the display surface.

[0012] With this configuration also, the raised and recessed profile of each of the reflection layers causes the reflectance at each of the reflection layers in a direction normal to the display surface to be higher in the both edge portions in the curvature direction than in the middle portion in the curvature direction on the display surface. Thus, the features and advantages of the present invention are specifically achieved.

[0013] A display area formed by the plurality of pixels

may include a first region, provided in the middle portion in the curvature direction on the display surface, where a reflectance of each of the reflection layers is a first reflectance, second regions, respectively provided on both sides of the first region, where a reflectance of each of the reflection layers is a second reflectance which is higher than the first reflectance, and third regions, respectively provided on opposite sides of the respective second regions from the first region, where a reflectance of each of the reflection layers is a third reflectance which is higher than the second reflectance.

[0014] With this configuration, the reflectance of light in each of the reflection layers in a direction normal to the display surface increases in a stepwise fashion along the directions from the middle portion in the curvature direction to the both edge portions in the curvature direction on the display surface. Thus, variation in brightness is effectively reduced in the curved LCD device.

[0015] Each of the pixels may include a reflection region in which the reflection layer is provided and a transmission region in which the reflection layer is not provided.

[0016] With this configuration, the features and advantages of the present invention are specifically achieved in a transfective LCD device in which each of the pixels includes a reflection region and a transmission region.

[0017] The raised and recessed profile of each of the reflection layers may be formed so that the reflectance toward a peripheral side of the display surface is lower than the reflectance toward a front side of the display surface.

[0018] With this configuration, the raised and recessed profile of each of the reflection layers causes the reflectance toward a peripheral side of the display surface to be lower than the reflectance toward a front side of the display surface. Thus, image displays are hardly visible from a peripheral side of the display surface. Accordingly, intentional reduction in the visibility in peripheral sides of the display surface so that image displays are only visible to a user in front can prevent the image displays from being viewed by others.

ADVANTAGES OF THE INVENTION

[0019] According to the present invention, the reflection layer provided in each of the pixels is formed so that the reflectance of light reflected from each of the reflection layers in the direction normal to the display surface is higher in the both edge portions in the curvature direction than in the middle portion in the curvature direction on the display surface. Thus, variation in brightness is reduced, and display quality is improved in curved LCD devices.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020]

[FIG. 1] FIG. 1 is a perspective view schematically illustrating an LCD device according to the first embodiment.

[FIG. 2] FIG. 2 is a cross-sectional view schematically illustrating the LCD device, taken along line II-II of FIG. 1.

[FIG. 3] FIG. 3 is a plan view schematically illustrating a display area of the LCD panel.

[FIG. 4] FIG. 4 is a plan view schematically illustrating a part of the thin film transistor (hereinafter referred to as "TFT") substrate of the first embodiment.

[FIG. 5] FIG. 5 is a cross-sectional view of a part corresponding to locations along line X-X of FIG. 4 in a first region of the first embodiment.

[FIG. 6] FIG. 6 is a cross-sectional view of a part corresponding to locations along line X-X of FIG. 4 in a second region of the first embodiment.

[FIG. 7] FIG. 7 is a cross-sectional view of a part corresponding to locations along line X-X of FIG. 4 in a third region of the first embodiment.

[FIG. 8] FIG. 8 is a plan view schematically illustrating a part of the TFT substrate of the second embodiment.

[FIG. 9] FIG. 9 is a cross-sectional view of a part corresponding to locations along line Y-Y of FIG. 8 in a first region of the second embodiment.

[FIG. 10] FIG. 10 is a cross-sectional view of a part corresponding to locations along line Y-Y of FIG. 8 in a second region of the second embodiment.

[FIG. 11] FIG. 11 is a cross-sectional view of a part corresponding to locations along line Y-Y of FIG. 8 in a third region of the second embodiment.

[FIG. 12] FIG. 12 is a perspective view schematically illustrating an LCD device according to the third embodiment.

[FIG. 13] FIG. 13 is a plan view schematically illustrating a part of the TFT substrate of the fourth embodiment.

DESCRIPTION OF EMBODIMENTS

[0021] Example embodiments of the present invention will be described below in detail with reference to the drawings. Note that the present invention is not limited to the embodiments described hereinafter.

«First Embodiment»

[0022] FIGS. 1 to 7 illustrate the first embodiment of the present invention. FIG. 1 is a perspective view schematically illustrating an LCD device S according to this embodiment. FIG. 2 is a cross-sectional view schematically illustrating the LCD device S, taken along line II-II of FIG. 1. FIG. 3 is a plan view schematically illustrating a display area 2 of an LCD panel 1. FIG. 4 is a plan view schematically illustrating a part of a TFT substrate 10. FIGS. 5 to 7 are cross-sectional views of parts corresponding to locations along line X-X of FIG. 4 in respec-

tive regions A, B, and C of the display area 2. Note that polarizing plates 43 and 44 are not shown in FIG. 1.

[0023] As shown in FIGS. 1 and 2, the LCD device S includes the LCD panel 1 and a backlight unit 5 disposed on the back side (lower side in FIG. 2) of the LCD panel 1.

[0024] The LCD panel 1 includes the TFT substrate 10, which is a first substrate, disposed on the backlight unit 5 side, and a color filter substrate 30, which is a second substrate, both of which are bonded together so as to face each other across a liquid crystal layer 40. In the LCD panel 1, the display area 2 is defined in an area where the TFT substrate 10 and the color filter substrate 30 face each other across the liquid crystal layer 40. The LCD panel 1 has a display surface 2s for displaying images on a surface on the color filter substrate 30 side in the display area 2.

[0025] Each of the substrates 10 and 30 included in the LCD panel 1 has flexibility, and the LCD panel 1 is fixed under transformation into a curved shape as a whole. Specifically, as shown in FIGS. 1 and 2, the LCD panel 1 is curved in one direction (downward direction in the figures) throughout the long side direction (lateral direction in the figures) so that the display surface 2s forms a concave curved surface. The display surface 2s has a curvature of, for example, approximately 1/500 to 1/50 (1/mm). The arrows in FIG. 1 indicate the curvature direction of the LCD panel 1 (the display surface 2s). Here, the term "curvature direction" means the direction along the curvature of the LCD panel 1.

[0026] Although this embodiment assumes that the LCD panel 1 is curved in the long side direction, the LCD panel 1 may be curved in a short side direction (longitudinal direction in FIG. 1). In addition, the LCD panel 1 is not limited to the one described above, but a rectangular display surface 2s may be configured to curve in an oblique direction.

[0027] The TFT substrate 10 and the color filter substrate 30 are formed in, for example, a rectangular shape etc., and as shown in FIG. 2, alignment films 41 and 42 are respectively provided on surfaces on the liquid crystal layer 40 side, and polarizing plates 43 and 44 are respectively provided on surfaces opposite the liquid crystal layer 40. A sealing member 45, having a frame structure, made of epoxy resin etc. is provided between the TFT substrate 10 and the color filter substrate 30 so as to surround the display area 2, and sealing in liquid crystal material within the space surrounded by the sealing member 45 forms the liquid crystal layer 40.

[0028] As shown in FIG. 4, the TFT substrate 10 includes a plurality of pixels 11 defined in a matrix, which form the display area 2. The LCD device S of this embodiment is a transmissive LCD device, and thus each of the pixels 11 includes a reflection region 11r which reflects external light incident from the color filter substrate 30 side, and a transmission region 11t which transmits light from the backlight unit 5. For example, the reflection region 11r is disposed in an upper portion column-wise (longitudinal direction in FIG. 4) in each of the pixels 11,

and the transmission region 11t is disposed in an under-side of the reflection region 11r column-wise in each of the pixels 11.

[0029] The TFT substrate 10 has a thin glass substrate 12 shown in FIG. 5. On the glass substrate 12, as shown in FIG. 4, a plurality of gate bus lines 13 are provided so as to extend row-wise (in the lateral direction in the figure) with respect to the pixels 11 in parallel with each other, a plurality of source bus lines 14 are provided so as to extend, in parallel with each other, in a perpendicular direction to each of the gate bus lines 13, and storage capacitor bus lines 15 are provided in lower portions column-wise (in the longitudinal direction in the figure) of the respective pixels 11 so as to extend between respective pairs of the gate bus lines 13. The gate bus lines 13 and the source bus lines 14 define the pixels 11, and TFTs 16, connected to both the gate bus lines 13 and the source bus lines 14 which form intersections, are respectively provided near the intersections of the gate bus lines 13 and source bus lines 14.

[0030] As shown in FIG. 5, each of the TFTs 16 includes a gate electrode 16g, provided on the glass substrate 12, and including a part of a gate bus line 13, a semiconductor layer 16h, provided so as to overlap the gate electrode 16g across a gate insulating film 17 provided over nearly the entire surface of the glass substrate 12 so as to cover the gate electrode 16g, a source electrode 16s, connected to an end portion of the semiconductor layer 16h and connected to a source bus line 14, and a drain electrode 16d, connected to the other end portion of the semiconductor layer 16h. As shown in FIG. 4, a terminal layer 18 is provided in an upper portion column-wise of each of the pixels 11, and a storage capacitor electrode 19 is provided in a lower portion column-wise of each of the pixels 11 so as to overlap a storage capacitor bus line 15, both in a monolithic fashion with the drain electrode 16d of the TFT 16 in each of the pixels 11, over the gate insulating film 17.

[0031] In addition, as shown in FIG. 5, an insulating film 20 is provided in the TFT substrate 10 so as to cover the source bus lines 14, the TFTs 16, the terminal layers 18, and the storage capacitor electrodes 19. A pixel electrode 21 is provided for each of the pixels 11 on the insulating film 20.

[0032] As shown in FIG. 4, contact holes 20h are provided in the insulating film 20 respectively over a terminal layer 18 and a storage capacitor electrode 19. As shown in FIGS. 5 to 7, the surface of the reflection region 11r of each of the pixels 11 of the insulating film 20 is formed with a raised and recessed profile, and this raised and recessed profile is, for example, a crease-like profile in which recessed portions and raised portions extend in a random manner.

[0033] As shown in FIG. 4, each of the pixel electrodes 21 includes a reflective electrode 21r, which is provided in the reflection region 11r, and which is a reflection layer formed of metal material having a high reflectance such as Al or Ag, and a transparent electrode 21t, which is

provided in the transmission region 11t, and formed of metal material having a high transmittance such as indium tin oxide (ITO). In each of the pixels 11, the reflective electrode 21r and the transparent electrode 21t are spaced apart from each other. The reflective electrode 21r is connected to the terminal layer 18 through a contact hole 20h, and the transparent electrode 21t is connected to the storage capacitor electrode 19 through a contact hole 20h.

[0034] As shown in FIG. 4, the surface of each of the reflective electrodes 21r is formed with a crease-like, raised and recessed profile where recessed portions 22 and raised portions 23 extend in a random manner, reflecting the raised and recessed profile of the insulating film 20. Thus, the surface of each of the reflective electrode 21r scatters light incident from the surroundings, and reflects the light toward the front of the LCD device S. In addition, the raised and recessed profile of each of the reflective electrodes 21r is formed so that the reflectance of light reflected from each of the reflective electrodes 21r in the direction normal to the display surface 2s is higher in both edge portions in the curvature direction than in a middle portion in the curvature direction on the display surface 2s.

[0035] As shown in FIG. 3, the display area 2 has a plurality of elongated regions (first through third regions A to C) whose reflectances of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r differ from each other along the directions from a middle portion in the curvature direction (longitudinal direction in the figure) to both edge portions in the curvature direction on the display surface 2s, and the elongated regions are arranged in parallel. Specifically, the display area 2 includes a first region A, which is provided in a middle portion in the curvature direction of the display surface 2s, and in which a reflectance of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r is greater than 0% and less than 5%, second regions B, which are respectively provided on both sides of the first region A, and in which a reflectance of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r is equal to or greater than 5% and less than 10%, and third regions C, which are respectively provided on opposite sides of the respective second regions B from the first region A, and in which a reflectance of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r is equal to or greater than 10% and less than 15%.

[0036] The reflectances of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r in the plurality of elongated regions A to C arranged in parallel increase in a stepwise fashion along the directions from the middle portion to the both edge portions in the curvature direction on the display surface 2s by adjusting, in each of the elongated regions A to C, the distribution range of slope angle α and the level of average slope angle of the raised and recessed profile in each of the reflective electrodes 21r by the surface

conditions of the insulating film 20.

[0037] The raised and recessed profile of each of the reflective electrodes 21r in the first through third regions A to C of this embodiment is formed with the distribution range of slope angle α being adjusted so that the average slope angle increases along the directions from the middle portion in the curvature direction to the both edge portions in the curvature direction on the display surface 2s. Here, as shown in FIGS. 5 to 7, the phrase "slope angle α of the raised and recessed profile in a reflective electrode 21r" means the slope angle between the bottom of a recessed portion 22 and the top of a raised portion 23 adjacent to each other, that is, an angle contained by the line connecting the bottom of a recessed portion 22 and the top of a raised portion 23 adjacent to each other and a plane parallel to the surface of the glass substrate 12, in the raised portion 23. The term "average slope angle" means the arithmetic average of all the values of slope angle α between the bottoms of the recessed portions 22 and the tops of the raised portions 23 adjacent to each other in the reflective electrodes 21r.

[0038] In this embodiment, the raised and recessed profile in each of the reflective electrodes 21r in the first region A is a relatively gradually raised and recessed profile as shown in FIG. 5. For example, the slope angle α lies in a range between 1.0 and 4.0°, and the average slope angle is approximately 2.5°. The raised and recessed profile in each of the reflective electrodes 21r in each of the second regions B is more steeply raised and recessed than the raised and recessed profile in each of the reflective electrodes 21r in the first region A as shown in FIG. 6. For example, the slope angle α lies in a range between 4.0 and 7.0°, and the average slope angle is approximately 5.5°. The raised and recessed profile in each of the reflective electrodes 21r in each of the third regions C is even more steeply raised and recessed than the raised and recessed profile in each of the reflective electrodes 21r in each of the second regions B as shown in FIG. 7. For example, the slope angle α lies in a range between 7.0 and 10.0°, and the average slope angle is approximately 8.5°.

[0039] In addition, as shown in FIGS. 1 and 2, the TFT substrate 10 is longer in the long side direction of the LCD panel 1, and has a larger area, than the color filter substrate 30; and has a mounting portion 10a protruding externally of the color filter substrate 30. In the mounting portion 10a, an integrated circuit chip 25 for driving the TFT etc., a flexible printed wiring board 26 for supplying power to the integrated circuit chip 25 and for supplying a signal from an external circuit to the LCD panel 1, etc. are mounted.

[0040] As shown in FIG. 5, the color filter substrate 30 includes a glass substrate 31. A plurality of color filters 32 are provided over the glass substrate 31 so as to overlap the pixel electrodes 21. A black matrix 33 is provided so as to define each of the color filters 32. A transparent layer 34 is provided in the color filter substrate 30 so as to overlap the reflection region 11r of each of the pixels

11 in order to reduce the thickness of the liquid crystal layer 40 over each of the reflection regions 11r to a thickness less than the thickness of the liquid crystal layer 40 over each of the transmission regions 11t. Thus, the thickness of the liquid crystal layer 40 over each of the reflection regions 11r is reduced to approximately half of the thickness of the liquid crystal layer 40 over each of the transmission regions 11t so that the optical path lengths of light passing through the liquid crystal layer 40 over a reflection region 11r and over a transmission region 11t are almost the same, thereby improving display quality. In addition, in the color filter substrate 30, a common electrode 35 is provided so as to cover the transparent layers 34 and the color filters 32.

[0041] Although not shown, the backlight unit 5 includes a light source such as a fluorescent lamp (cold cathode fluorescent tube) or a light emitting diode (LED), a light guide plate, and a plurality of optical sheets such as prism sheets. The light guide plate and the optical sheets are made of resin, and have flexibility. As shown in FIGS. 1 and 2, the backlight unit 5 is fixed under transformation into a curved shape as a whole along the LCD panel 1, and is configured so as to emit light incident from the light source onto the light guide plate, from an emitting surface of the light guide plate through the optical sheets to the LCD panel 1 side, as uniform plane light.

[0042] Thus, the transfective LCD device S applies a voltage across each of the pixel electrodes 21 and the common electrode 35, and controls the orientation of liquid crystal molecules on each of the pixels 11 while, in each of the pixels 11, the reflection region 11r reflects external light and the transmission region 11t transmits light from the backlight unit 5, so as to display images as desired on the display surface 2s (display area 2).

-Manufacturing Method-

[0043] Next, a manufacturing method of the LCD device S described above will be described.

[0044] First, the two glass substrates 12 and 31 are prepared. Next, the bus lines 13, 14, and 15, the TFTs 16, the terminal layers 18, and the storage capacitor electrodes 19 are formed on the glass substrate 12. Then, positive photosensitive resin is applied and a film thereof is formed on the glass substrate 12 using a spin coater etc., and prebaking at a temperature about 110°C for two minutes, an exposure treatment using a mask, and development are sequentially conducted on the photosensitive resin film to form the contact holes 20h.

[0045] Next, the photosensitive resin film in which the contact holes 20h are formed is postbaked at a temperature about 135°C for about eight minutes, and thereafter, ultraviolet light is sequentially radiated using a mask onto regions, of the photosensitive resin film, which will be the reflection regions 11r of the elongated regions A to C with irradiation energies suitable for the raised and recessed profiles of the insulating film 20 formed in the respective regions. That is, on the photosensitive resin

film, ultraviolet light is respectively radiated onto a region which will be the first region A with a relatively low irradiation energy, onto regions which will be the second regions B with a higher irradiation energy than the irradiation energy for the region which will be the first region A, and onto regions which will be the third regions C with an even higher irradiation energy than the irradiation energy for the regions which will be the second regions B. Then, final baking on the photosensitive resin film at a temperature about 210°C for about 60 minutes yields, on a surface of the photosensitive resin film, a crease-like, raised and recessed profile having different distribution ranges of slope angle α and different levels of average slope angle between the regions which will be the elongated regions A to C. Thus, the insulating film 20 having a surface with a predetermined raised and recessed profile in each of the regions which will be the elongated regions A to C is formed.

[0046] Thereafter, the reflective electrodes 21r are respectively formed in regions, of the insulating film 20, which will be the respective reflection regions 11r. In doing so, the surface of each of the reflective electrodes 21r is formed with a raised and recessed profile, reflecting the raised and recessed profile of the insulating film 20. In addition, respectively forming the transparent electrodes 21t in regions of the insulating film 20 which will be the respective transmission regions 11t produces the TFT substrate 10. Then, the alignment film 41 is formed over the TFT substrate 10 by a printing method etc.

[0047] Moreover, forming the black matrix 33, the color filters 32, the transparent layers 34, and the common electrode 35 on and over the other glass substrate 31 produces the color filter substrate 30. Then, the alignment film 42 is formed on the surface of the color filter substrate 30 by a printing method. Next, the sealing member 45 is formed in a frame structure on the TFT substrate 10 by drawing using a dispenser etc. or by a printing method. Thereafter, a predetermined amount of liquid crystal material is dropped into a region, on the TFT substrate 10, surrounded by the sealing member 45. Subsequently, in the processing chamber under vacuum, the TFT substrate 10 and the color filter substrate 30 are aligned so that the respective pixel electrodes 21 and the respective color filters 32 overlap, and the both substrates 10 and 30 are bonded together with the sealing member 45 therebetween. Then, the sealing member 45 is cured to make the both substrates 10 and 30 adhere with respect to each other. Thus, the LCD panel 1 is produced.

[0048] Although, in this embodiment, the manufacturing process of the LCD panel 1 has been described using an example of so-called "one drop filling" in which the material of the sealing member 45 is supplied onto the TFT substrate 10 in a frame structure, and liquid crystal material is dropped into the space surrounded by the sealing member 45, and then the TFT substrate 10 and the color filter substrate 30 are bonded together, the LCD panel may be manufactured by so-called "vacuum injec-

tion method" in which the material of the sealing member is applied to the TFT substrate 10 to form the sealing member almost in a frame structure having incision, the TFT substrate 10 and the color filter substrate 30 are bonded together with the sealing member therebetween, and then, the liquid crystal material is injected under vacuum through an injection hole configured by the incision in the sealing member, before sealing the injection hole.

[0049] Thereafter, the polarizing plates 43 and 44 are bonded to the respective surfaces of the LCD panel 1, and the integrated circuit chip 25 and the flexible printed wiring board 26 are each mounted on the mounting portion 10a of the TFT substrate 10. Then, the previously prepared backlight unit 5 is attached on the backside of the LCD panel 1, and the LCD panel 1 and the backlight unit 5 are transformed and fixed so that the display surface 2s forms a concave curved surface. Thus, the LCD device S shown in FIG. 1 is completed.

-Advantages of First Embodiment-

[0050] Thus, according to the first embodiment, the raised and recessed profile in each of the reflective electrodes 21r is formed such that the reflectance of light reflected from each of the reflective electrodes 21r in the direction normal to the display surface 2s is higher in the both edge portions in the curvature direction than in the middle portion in the curvature direction on the display surface 2s. Accordingly, the reflectance of light reflected from each of the reflective electrodes 21r toward the front of the LCD device S can be higher in the both edge portions in the curvature direction than in the middle portion in the curvature direction on the display surface 2s, and thus, variation in brightness is reduced, and display quality is improved in the curved LCD device S.

[0051] Moreover, since the display area 2 includes the first through third regions A to C, the reflectance of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r increases in a stepwise fashion along the directions from the middle portion to the both edge portions in the curvature direction on the display surface 2s. Thus, variation in brightness can be effectively reduced in the curved LCD device S.

«Second Embodiment»

[0052] FIGS. 8 to 11 illustrate the second embodiment of the present invention. In the embodiments hereafter, the same reference numerals are used to represent equivalent elements to those shown in FIGS. 1 to 7, and the detailed explanation thereof will be omitted. FIG. 8 is a plan view schematically illustrating a part of the TFT substrate 10 of this embodiment. FIGS. 9 to 11 are cross-sectional views of parts corresponding to locations along line Y-Y of FIG. 8 in the respective regions A, B, and C of the display area 2.

[0053] While the first embodiment described above has been presented in terms of the transmissive LCD

device S, this embodiment is presented in terms of a reflective LCD device S.

[0054] As shown in FIG. 8, the LCD device S according to this embodiment includes pixel electrodes 21 each having a reflective electrode 21r. Each of the reflective electrodes 21r is connected through a contact hole 20h to the storage capacitor electrode 19, which is formed in a monolithic fashion with the drain electrode 16d of the TFT 16 with respect to each of the pixels 11. As with the first embodiment described above, the LCD panel 1 of this embodiment also has the display surface 2s which is curved to form a concave curved surface, and the display surface 2s has a plurality of elongated regions A to C whose reflectances of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r differ from each other. As shown in FIG. 8, the surface of each of the reflective electrodes 21r is formed with a crease-like, raised and recessed profile where recessed portions 22 and raised portions 23 extend in a random manner; and adjustment, in each of the elongated regions A to C, of the distribution range of slope angle α and the level of average slope angle of the raised and recessed profile in each of the reflective electrodes 21r causes the reflectance of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r to increase in a stepwise fashion along the directions from the middle portion to the both edge portions in the curvature direction on the display surface 2s.

[0055] As with the first embodiment described above, the raised and recessed profile of each of the reflective electrodes 21r in the first through third regions A to C of this embodiment is also formed with the distribution range of slope angle α being adjusted so that the average slope angle increases along the directions from the middle portion in the curvature direction to the both edge portions in the curvature direction on the display surface 2s. The raised and recessed profile in each of the reflective electrodes 21r in the first region A is a relatively gradually raised and recessed profile as shown in FIG. 9. For example, the slope angle α lies in a range between 1.0 and 4.0°, and the average slope angle is approximately 2.5°. The raised and recessed profile in each of the reflective electrodes 21r in each of the second regions B is more steeply raised and recessed than the raised and recessed profile in each of the reflective electrodes 21r in the first region A as shown in FIG. 10. For example, the slope angle α lies in a range between 4.0 and 7.0°, and the average slope angle is approximately 5.5°. The raised and recessed profile in each of the reflective electrodes 21r in each of the third regions C is even more steeply raised and recessed than the raised and recessed profile in each of the reflective electrodes 21r in each of the second regions B as shown in FIG. 11. For example, the slope angle α lies in a range between 7.0 and 10.0°, and the average slope angle is approximately 8.5°.

[0056] The configuration of the other part of the LCD device S of this embodiment is similar to that of the first embodiment described above, and a front light unit is

attached as necessary on the front face side (upper side in FIG. 1) of the LCD panel 1.

-Advantages of Second Embodiment-

[0057] Thus, also according to the second embodiment, since the display area 2 includes the first through third regions A to C, the reflectance of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r increases in a stepwise fashion along the directions from the middle portion to the both edge portions in the curvature direction on the display surface 2s. Thus, similar advantages to those of the first embodiment described above can be obtained.

«Third Embodiment»

[0058] FIG. 12 illustrates the third embodiment of the present invention. FIG. 12 is a perspective view schematically illustrating an LCD device S according to this embodiment.

[0059] While the first and second embodiments described above have assumed that the LCD panel 1 has the display surface 2s which is curved to form a concave curved surface, the LCD panel 1 of this embodiment is configured such that the display surface 2s is curved in the long side direction so as to form a convex curved surface as shown in FIG. 12. The arrows in FIG. 12 indicate the curvature direction of the LCD panel 1 (the display surface 2s). The backlight unit 5 is also configured to curve along the LCD panel 1.

[0060] Although this embodiment assumes that the LCD panel 1 is curved in the long side direction, the LCD panel 1 may be curved in a short side direction, and moreover, the rectangular display surface 2s may be configured to curve in an oblique direction.

[0061] Also in the LCD device S of this embodiment, as with the first embodiment described above, the surface of each of the reflective electrodes 21r is formed with a crease-like, raised and recessed profile; and adjustment, in each of the elongated regions (first through third regions) A to C, of the distribution range of slope angle α and the level of average slope angle of the raised and recessed profile in each of the reflective electrodes 21r causes the reflectance of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r to increase in a stepwise fashion along the directions from the middle portion to the both edge portions in the curvature direction on the display surface 2s.

-Advantages of Third Embodiment-

[0062] Thus, also according to the third embodiment, since the display area 2 includes the first through third regions A to C, the reflectance of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r increases in a stepwise fashion along the directions from the middle portion to the both edge por-

tions in the curvature direction on the display surface 2s. Thus, similar advantages to those of the first embodiment described above can be obtained.

5 «Fourth Embodiment»

[0063] FIG. 13 illustrates the fourth embodiment of the present invention. FIG. 13 is a plan view schematically illustrating a part of the TFT substrate 10 according to this embodiment.

[0064] While the second embodiment described above has assumed that the surface of each of the reflective electrodes 21r is formed with a crease-like, raised and recessed profile where recessed portions 22 and raised portions 23 extend in a random manner, the crease-like, raised and recessed profile of each of the reflective electrodes 21r of this embodiment is formed in a ladder structure as shown in FIG. 13, in which recessed portions 22 and raised portions 23 are provided so as to extend row-wise (in the lateral direction in the figure) in each of the pixels 11 in parallel with each other inside a raised portion 23 having a frame structure, and to lie alternately in stripes column-wise (in the longitudinal direction in the figure) with respect to the pixels 11. Accordingly, the raised and recessed profile of each of the reflective electrodes 21r of this embodiment is formed so that a smaller area of sloped surface faces row-wise in each of the pixels 11, and that the reflectance of light toward the both side portions on the display surface 2s is lower than the reflectance of light toward the front portion on the display surface 2s. The configuration of the other part of the LCD device S of this embodiment is similar to that of the second embodiment described above.

[0065] The raised and recessed profiles of the reflective electrodes 21r as described above are formed, in a manufacturing method of the TFT substrate 10, such that when the source bus lines 14 and the drain electrodes 16d are formed, a plurality of patterns extending row-wise and lying in stripes column-wise are formed in each region which will be a pixel 11. Then, by forming the insulating film 20 in a similar way to that of the first embodiment described above, final baking yields recessed portions 22 and raised portions 23 extending along the respective patterns, and thus the raised and recessed profile in a ladder structure is formed on the insulating film 20. Thereafter, formation of the reflective electrodes 21r causes the surface of each of the reflective electrodes 21r to be formed with the raised and recessed profile in a ladder structure, reflecting the raised and recessed profile of the insulating film 20.

-Advantages of Fourth Embodiment-

[0066] Thus, according to the fourth embodiment, variation in brightness can be effectively reduced, and display quality can be improved in the curved LCD device S as with the second embodiment. Moreover, the raised and recessed profile of each of the reflective electrodes

21r allows the reflectance of light at each of the reflective electrodes 21r to be lower in the both side portions on the display surface 2s than in the front portion on the display surface 2s, and thus image displays can be hardly visible from the both side portions of the display surface 2s. Accordingly, intentional reduction in the visibility in the both side portions of the display surface 2s so that image displays are only visible to a user in front can prevent the image displays from being viewed by others.

«Other Embodiments»

[0067] Although the first embodiment described above has been presented in terms of a method for forming the raised and recessed profile on the surface of the insulating film 20 in which ultraviolet light is radiated onto the photosensitive resin film forming the insulating film 20, and then final baking is conducted, the present invention is not limited thereto, the raised and recessed profile may be formed on the surface of the insulating film in such a way that ultraviolet light is radiated onto the photosensitive resin film forming the insulating film, and then the photosensitive resin film is developed, or the raised and recessed profile may be formed on the surface of the insulating film 20 by another known method in which, for example, a pattern is formed on a layer under the insulating film to form the surface of the insulating film with a raised and recessed profile.

[0068] In addition, although each of the described embodiments assumes that the raised and recessed profile of each surface of the reflective electrodes 21r is formed with a crease-like profile where the recessed portions and the raised portions extend in a random manner, or is formed in a ladder structure, the present invention is not limited thereto, the raised and recessed profile of the insulating film 20 may be a raised and recessed profile in which a plurality of dot-shaped raised portions are provided at random, or otherwise, various raised and recessed profiles may be used.

[0069] Although the fourth embodiment described above has been presented in terms of the reflective LCD device S in which each of the reflective electrodes 21r is configured such that the reflectance of light at each of the reflective electrodes 21r is lower in the both side portions on the display surface 2s than in the front portion on the display surface 2s, the present invention is not limited thereto, the transmissive LCD device S may be configured such that the surface of each of the reflective electrodes 21r is formed with a raised and recessed profile in a ladder structure as with the fourth embodiment described above, and thus the reflectance of light at each of the reflective electrodes 21r is lower in the both side portions on the display surface 2s than in the front portion on the display surface 2s. With such a configuration, in the curved transmissive LCD device S, the raised and recessed profile of each of the reflective electrodes 21r allows the reflectance of light at each of the reflective electrodes 21r to be lower in the both side portions on

the display surface 2s than in the front portion on the display surface 2s, and thus image displays can be hardly visible from the both side portions of the display surface 2s, and can be prevented from being viewed by others.

INDUSTRIAL APPLICABILITY

[0070] As described above, the present invention is useful for LCD devices, and more particularly for curved LCD devices in which reduction in variation in brightness and improvement in display quality are demanded.

DESCRIPTION OF REFERENCE CHARACTERS

[0071]

A	First Region
B	Second Region
C	Third Region
S	Liquid Crystal Display (LCD) Device
2	Display Area
2s	Display Surface
10	Thin Film Transistor (TFT) Substrate (First Substrate)
11	Pixel
11r	Reflection Region
11t	Transmission Region
21r	Reflective Electrode (Reflection Layer)
30	Color Filter Substrate (Second Substrate)

Claims

1. A liquid crystal display device, comprising:
 - a first substrate having a plurality of pixels defined thereon, each of which is provided with a reflection layer;
 - a second substrate disposed opposite the first substrate; and
 - a display surface configured to display images by the pixels, wherein the display surface is curved in one direction, and each of the reflection layers is formed so that a reflectance of light reflected from each of the reflection layers in a direction normal to the dis-

play surface is higher in both edge portions in a curvature direction than in a middle portion in the curvature direction on the display surface.

2. The liquid crystal display device of claim 1, wherein a surface of each of the reflection layers is formed with a raised and recessed profile, and the raised and recessed profile of each of the reflection layers is formed so that the reflectance of each of the reflection layers is higher in the both edge portions in the curvature direction than in the middle portion in the curvature direction on the display surface. 5 10
3. The liquid crystal display device of claim 1 or 2, wherein a display area formed by the plurality of pixels includes a first region, provided in the middle portion in the curvature direction on the display surface, where a reflectance of each of the reflection layers is a first reflectance, second regions, respectively provided on both sides of the first region, where a reflectance of each of the reflection layers is a second reflectance which is higher than the first reflectance, and third regions, respectively provided on opposite sides of the respective second regions from the first region, where a reflectance of each of the reflection layers is a third reflectance which is higher than the second reflectance. 15 20 25 30
4. The liquid crystal display device of any one of claims 1 to 3, wherein each of the pixels includes a reflection region in which the reflection layer is provided and a transmission region in which the reflection layer is not provided. 35
5. The liquid crystal display device of claim 2, wherein the raised and recessed profile of each of the reflection layers is formed so that the reflectance toward a peripheral side of the display surface is lower than the reflectance toward a front side of the display surface. 40 45

50

55

FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8




FIG.9




FIG.10




FIG.11




FIG.12





FIG.13



INTERNATIONAL SEARCH REPORT

International application No.
PCT/JP2009/003743

<p>A. CLASSIFICATION OF SUBJECT MATTER G02F1/1335(2006.01)i, G02F1/1333(2006.01)i, G09F9/30(2006.01)i</p> <p>According to International Patent Classification (IPC) or to both national classification and IPC</p>												
<p>B. FIELDS SEARCHED</p> <p>Minimum documentation searched (classification system followed by classification symbols) G02F1/1335, G02F1/1333, G09F9/30</p> <p>Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Jitsuyo Shinan Koho 1922-1996 Jitsuyo Shinan Toroku Koho 1996-2009 Kokai Jitsuyo Shinan Koho 1971-2009 Toroku Jitsuyo Shinan Koho 1994-2009</p> <p>Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)</p>												
<p>C. DOCUMENTS CONSIDERED TO BE RELEVANT</p> <table border="1"> <thead> <tr> <th>Category*</th> <th>Citation of document, with indication, where appropriate, of the relevant passages</th> <th>Relevant to claim No.</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>JP 2007-193077 A (Sharp Corp.), 02 August, 2007 (02.08.07), Par. Nos. [0017] to [0051]; Figs. 1, 2, 4, 6 (Family: none)</td> <td>1-5</td> </tr> <tr> <td>A</td> <td>JP 11-295750 A (NEC Corp.), 29 October, 1999 (29.10.99), Par. No. [0016]; Fig. 9 (Family: none)</td> <td>1-5</td> </tr> </tbody> </table>			Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.	A	JP 2007-193077 A (Sharp Corp.), 02 August, 2007 (02.08.07), Par. Nos. [0017] to [0051]; Figs. 1, 2, 4, 6 (Family: none)	1-5	A	JP 11-295750 A (NEC Corp.), 29 October, 1999 (29.10.99), Par. No. [0016]; Fig. 9 (Family: none)	1-5	
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.										
A	JP 2007-193077 A (Sharp Corp.), 02 August, 2007 (02.08.07), Par. Nos. [0017] to [0051]; Figs. 1, 2, 4, 6 (Family: none)	1-5										
A	JP 11-295750 A (NEC Corp.), 29 October, 1999 (29.10.99), Par. No. [0016]; Fig. 9 (Family: none)	1-5										
<p><input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.</p>												
<p>* Special categories of cited documents:</p> <table border="0"> <tr> <td>“A” document defining the general state of the art which is not considered to be of particular relevance</td> <td>“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</td> </tr> <tr> <td>“E” earlier application or patent but published on or after the international filing date</td> <td>“X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</td> </tr> <tr> <td>“L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</td> <td>“Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</td> </tr> <tr> <td>“O” document referring to an oral disclosure, use, exhibition or other means</td> <td>“&” document member of the same patent family</td> </tr> <tr> <td>“P” document published prior to the international filing date but later than the priority date claimed</td> <td></td> </tr> </table>			“A” document defining the general state of the art which is not considered to be of particular relevance	“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention	“E” earlier application or patent but published on or after the international filing date	“X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	“L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	“Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art	“O” document referring to an oral disclosure, use, exhibition or other means	“&” document member of the same patent family	“P” document published prior to the international filing date but later than the priority date claimed	
“A” document defining the general state of the art which is not considered to be of particular relevance	“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention											
“E” earlier application or patent but published on or after the international filing date	“X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone											
“L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	“Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art											
“O” document referring to an oral disclosure, use, exhibition or other means	“&” document member of the same patent family											
“P” document published prior to the international filing date but later than the priority date claimed												
<p>Date of the actual completion of the international search 27 August, 2009 (27.08.09)</p>		<p>Date of mailing of the international search report 08 September, 2009 (08.09.09)</p>										
<p>Name and mailing address of the ISA/ Japanese Patent Office</p>		<p>Authorized officer</p>										
<p>Facsimile No.</p>		<p>Telephone No.</p>										

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 2002221716 A [0004]

专利名称(译)	液晶显示装置		
公开(公告)号	EP2372437A4	公开(公告)日	2012-09-26
申请号	EP2009834245	申请日	2009-08-05
[标]申请(专利权)人(译)	夏普株式会社		
申请(专利权)人(译)	夏普株式会社		
当前申请(专利权)人(译)	夏普株式会社		
[标]发明人	ENOMOTO HIROMI		
发明人	ENOMOTO HIROMI		
IPC分类号	G02F1/1335 G02F1/1333 G09F9/30		
CPC分类号	G09F9/35 G02F1/1323 G02F1/133305 G02F1/133504 G02F1/133553 G02F1/133555 G02F2001/133391 G02F2203/02 G09F9/301		
代理机构(译)	ROCKE , CARSTEN		
优先权	2008334594 2008-12-26 JP		
其他公开文献	EP2372437B1 EP2372437A1		
外部链接	Espacenet		

摘要(译)

一种液晶显示装置，包括：第一基板，具有限定在其上的多个像素，每个像素设置有反射层；第二基板，与第一基板相对设置；以及显示表面，通过像素显示图像，其中显示器表面在一个方向上弯曲，并且每个反射层形成为使得在垂直于显示表面的方向上从每个反射层反射的光的反射率在曲率方向上的两个边缘部分中比在中间的中间更高在显示表面上的曲率方向上的部分。