



(11)

EP 2 725 409 A1

(12)

EUROPEAN PATENT APPLICATION
published in accordance with Art. 153(4) EPC

(43) Date of publication:
30.04.2014 Bulletin 2014/18

(51) Int Cl.:
G02F 1/133 ^(2006.01) **G06F 3/044** ^(2006.01)

(21) Application number: **12876074.1**

(86) International application number:
PCT/CN2012/086113

(22) Date of filing: **07.12.2012**

(87) International publication number:
WO 2014/032374 (06.03.2014 Gazette 2014/10)

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(30) Priority: **27.08.2012 CN 201210308846**

(71) Applicant: **Shanghai Tianma Micro-Electronics
Co., Ltd.
201201 Shanghai (CN)**

(72) Inventor: **ZHOU, Xingyao
Shanghai 201201 (CN)**

(74) Representative: **Stöckeler, Ferdinand et al
Schoppe, Zimmermann, Stöckeler, Zinkler &
Partner
Patentanwälte
Postfach 246
82043 Pullach bei München (DE)**

(54) **EMBEDDED TOUCH DISPLAY DEVICE**

(57) An embedded touch display device includes a first substrate (100) and a second substrate (200) which are opposite; a liquid crystal display unit and a capacitive touch unit located between the first substrate and the second substrate. The liquid crystal display structure includes a pixel electrode layer (120), a common electrode layer and a liquid crystal layer (30), the pixel electrode layer (120) and the common electrode layer are located on two sides of the liquid crystal layer (30), and liquid crystal (30) in the liquid crystal layer (30) is ferroelectric

liquid crystal. Nematic liquid crystal is replaced with ferroelectric liquid crystal in the embedded touch display device, thereby solving a problem that in a TN mode embedded touch display device, liquid crystal molecules rotate from a horizontal direction to a vertical direction or from a vertical direction to a horizontal direction, thus the rotational angle is large, which results a great variation of permittivity of the liquid crystal layer, and thus seriously affects the sensitivity effect of the touch electrodes.




FIG.5

Description

[0001] The present application claims the priority of Chinese Patent Application No. 201210308846.2, entitled "EMBEDDED TOUCH DISPLAY DEVICE", filed with the Chinese Patent Office on August 27, 2012, the content of which is incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

[0002] The present invention relates to the field of liquid crystal display, and in particular to an embedded touch display device.

BACKGROUND OF THE INVENTION

[0003] Touch display devices on the market are mostly separated touch screens, and the separated touch screen is obtained by assembling a touch panel and a liquid crystal panel manufactured separately together. The obtained display device is rather thick, and since multiple layers of glass and film are added, the light transmittance and the contrast gradient of the display screen are observably decreased. Moreover, the cost of the above touch display device is high. In order to make the liquid crystal display device with the touch panel lighter, thinner, good display effect and low-cost, an embedded touch technology emerges, which is a technology for integrating the touch panel with the liquid crystal panel. Specifically, the touch technology of the touch panel may be implemented by a capacitive touch control, a resistive touch control, infrared touch control or the like, and the structure of the liquid crystal panel may be implemented by a common Twisted Nematic Liquid Crystal (TN) mode, In Plane Switching Liquid Crystal (IPS) mode, Fringe Field Switching Liquid Crystal (FFS) mode or the like. Currently, the main developing trend of the embedded touch technology refers to an On-Cell embedded touch display device and an In-Cell embedded touch display device.

[0004] For the On-Cell embedded touch display device, the touch sensor is provided on the liquid crystal panel. The liquid crystal panels and the touch components need to be assembled by bonding. In this manner, improving the success rate of bonding and reducing the times for bonding are the keys of the touch panel processing technology.

[0005] For the In-Cell embedded touch display device, the touch sensor is embedded into the liquid crystal pixels. The manufacture of the touch sensing elements may be completed according to the TFT LCD standard processing. Moreover, there are no problems of screen face bonding and components in alignment, the weight and the thickness are reduced greatly, and thus the device is lighter and thinner. In addition, the viewing angle of the device may not be affected, and the light transmittance of the panel and the picture quality of the screen

are much better.

[0006] In summary, the using effects of the embedded touch display devices produced by using the prior arts are not ideal.

SUMMARY OF THE INVENTION

[0007] A problem to be solved in the invention is that the using effects of the embedded touch display devices are not ideal.

[0008] To solve the above problem, an embedded touch display device is provided in the invention, and the embedded touch display device includes:

a first substrate and a second substrate which are opposite to each other; and

a liquid crystal display unit and a capacitive touch unit disposed between the first substrate and the second substrate, where the liquid crystal display unit includes a pixel electrode layer, a common electrode layer and a liquid crystal layer, the pixel electrode layer and the common electrode layer are disposed respectively on two sides of the liquid crystal layer, and the liquid crystal in the liquid crystal layer is ferroelectric liquid crystal.

[0009] Optionally, the first substrate and the second substrate may be formed of transparent insulating material.

[0010] Optionally, the pixel electrode layer and the common electrode layer may be formed of transparent conductive material.

[0011] Optionally, the liquid crystal in the liquid crystal layer may be Semi-V shaped ferroelectric liquid crystal, which is obtained by performing asymmetrical anchoring on the ferroelectric liquid crystal.

[0012] Optionally, the performing asymmetrical anchoring on the ferroelectric liquid crystal may include setting the alignment direction of an upper alignment film reaching an upper surface of the liquid crystal layer and the alignment direction of a lower alignment film reaching a lower surface of the liquid crystal layer to be antiparallel, and setting the alignment intensity of the upper alignment film reaching the upper surface of the liquid crystal layer and the alignment intensity of the lower alignment film reaching the lower surface of the liquid crystal layer to be different, and an azimuth angle of the ferroelectric liquid crystal may be 22.5°.

[0013] Optionally, the alignment direction of an upper alignment film reaching an upper surface of the liquid crystal layer may be perpendicular to the alignment direction of a lower alignment film reaching a lower surface of the liquid crystal layer, the upper alignment film and the lower alignment film have the same alignment intensity, the ferroelectric liquid crystal may be twisted ferroelectric liquid crystal, and an azimuth angle of the ferroelectric liquid crystal may be 45°.

[0014] Optionally, the common electrode layer may include multiple parallel common electrodes.

[0015] Optionally, the capacitive touch unit may include: multiple parallel driving electrodes crossing the common electrodes or multiple parallel sensing electrodes crossing the common electrodes, and an insulating layer is disposed between the common electrodes and the driving electrodes or between the common electrodes and the sensing electrodes.

[0016] Optionally, one side of the liquid crystal layer may be closer to the second substrate, and the other side of the liquid crystal layer may be covered with a color film; the capacitive touch unit may be disposed on one side of the color film relatively far from the liquid crystal layer, and the first substrate may be disposed on one side of the capacitive touch unit relatively far from the liquid crystal layer.

[0017] Optionally, the capacitive touch unit may include multiple parallel sensing electrodes and multiple parallel driving electrodes crossing the sensing electrodes, the driving electrodes are disposed in the same layer as the sensing electrodes.

[0018] Optionally, the capacitive touch unit may be a bi-layer structure, which may include multiple parallel sensing electrodes and multiple parallel driving electrodes crossing the sensing electrodes, and an insulating layer is disposed between the driving electrodes and the sensing electrodes.

[0019] Optionally, the driving electrodes and/or the sensing electrodes may include an indium tin metal oxide layer and a metal layer which are overlapped, and the metal layer may be a net-like structure.

[0020] Optionally, a surface of the metal layer may be covered with a protection layer which is a black matrix for shading.

[0021] Optionally, a planarization layer may be disposed between the liquid crystal layer and the color film.

[0022] Optionally, the planarization layer may be formed of transparent organic material.

[0023] Compared with the prior art, the present invention mainly has the following advantages.

[0024] Nematic liquid crystal is replaced with ferroelectric liquid crystal, thereby solving a problem that in a TN mode embedded touch display device, liquid crystal molecules rotate from a horizontal direction to a vertical direction or from a vertical direction to a horizontal direction, and the rotational angle is large, resulting in the great variation of permittivity of the liquid crystal layer, and thus the sensitivity of the touch electrodes is affected seriously.

BRIEF DESCRIPTION OF THE DRAWINGS

[0025]

Figure 1 is an equivalent circuit diagram of a touch electrode in an embedded capacitive touch display device;

Figure 2 is a schematic structural diagram of a TN mode capacitive embedded touch display device in the prior art;

Figure 3 is a schematic diagram of an arrangement of an upper polarizer, a lower polarizer and liquid crystal molecules in an Off state of a TN mode in the prior art;

Figure 4 is a schematic diagram of an arrangement of an upper polarizer, a lower polarizer and liquid crystal molecules in an On state of a TN mode in the prior art;

Figure 5 is a schematic diagram of replacing nematic liquid crystal with ferroelectric liquid crystal in a liquid crystal layer in a TN mode; and

Figure 6 is a top view of an implementation of a capacitive touch unit according to the third embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0026] An embedded capacitive touch display device includes a capacitive touch unit and a liquid crystal display unit. Specifically, the capacitive touch unit includes a touch sensor which includes touch electrodes. The touch electrodes include driving electrodes and sensing electrodes. Display electrodes in the liquid crystal display unit include pixel electrodes and common electrodes. There are parasitic capacitances between the touch electrodes and the display electrodes which are the closest to the touch electrodes in the liquid crystal display unit, and the parasitic capacitances would seriously affect the signal to noise ratio of the capacitive touch unit.

[0027] Figure 1 illustrates an equivalent circuit of a crossover point of each driving electrode and each sensing electrode in an embedded capacitive touch display device, where C_t and C_r respectively mean the parasitic capacitances between the driving electrode of the touch screen and other display electrode in the liquid crystal display unit and between the detection electrode of the touch screen and the other display electrode in the liquid crystal display unit. The driving electrode is equivalent as a driving line 121 and a resistance 122, the sensing electrode is equivalent as a sensing line 141 and a resistance 142, and a mutual capacitance 16 is formed at each crossover point of the driving electrode and the sensing electrode. There is a parasitic capacitance C_t between the driving electrode and the ground, and there is a parasitic capacitance C_r between the sensing electrode and the ground. A touch detection circuit 30 is a charge amplifier, which converts the current of the sensing electrode into a voltage signal output V_{out} . When the touch panel (the touch unit) is touched by a finger, the mutual capacitance 16 at the touch point is changed, resulting in the variation of output current I of the sensing

electrode, and thus the output voltage V_{out} varies.

[0028] If the liquid crystal display unit is filled with the liquid crystal in a TN mode, the parasitic capacitance would have a stronger effect on the touch electrode. The TN mode is a liquid crystal mode where nematic liquid crystal with liquid crystal molecule twist angle of 90° is used, and the TN mode is a basic liquid crystal mode of a liquid crystal panel. The TN mode liquid crystal panel is configured as below: nematic liquid crystal is injected between glass substrates with transparent electrodes, and polarizers are provided on the outside of the glass substrates. The transparent electrodes include common electrodes and pixel electrodes. The 90° twist of the nematic liquid crystal molecules is achieved by mutually perpendicular rubbing and anchoring of alignment films on the surfaces of the glass substrates, i.e., the alignment films located on the upper surface and lower surface of the nematic liquid crystal layer. It is known by those skilled in the art that before the liquid crystal is used in a display, the liquid crystal molecules need to be oriented towards a certain direction, which is referred to as alignment. Generally, the method of alignment is as follows: coating polyimide resin on opposite surfaces of the upper glass substrate and the lower glass substrate to form a thin film, and then rubbing the resin along a certain direction by using a rubbing cloth (rubbing process) to form tiny gaps, and in this manner the liquid crystal molecules may be oriented towards the same direction along the gaps. The resin film in which the tiny gaps are formed in a certain direction is referred to as an alignment film.

[0029] The liquid crystal molecule is a rod-like molecule with a long axis and a short axis, and the permittivity of the liquid crystal molecule in the long axis direction is different from that in the short axis direction. In the case where images are displayed in a TN mode liquid crystal display unit, the liquid crystal molecules rotate from a horizontal direction to a vertical direction or from a vertical direction to a horizontal direction. The rotational angle is large, resulting in great variation of the permittivity of the liquid crystal layer, which in turn seriously affects the changes of the parasitic capacitances C_t and C_r . Therefore, the output current I of the sensing electrode is changed, and the output voltage V_{out} is changed, resulting in seriously effect on the sensitivity of the touch electrode of the touch screen.

[0030] The above problem is solved by replacing the nematic liquid crystal with ferroelectric liquid crystal through pondering and many trials of the inventor. Because the ferroelectric liquid crystal can realize a rather small rotation angle, the variation of the permittivity of the liquid crystal layer is decreased.

[0031] Specifically, the ferroelectric liquid crystal is the liquid crystal with ferroelectricity, which is mainly smectic C^* phase (chiral smectic C phase). The smectic C phase may be obtained by cooling the nematic phase at a certain temperature, and the smectic C phase composed of the chiral carbon is the smectic C^* phase. All these three liquid crystal molecules are comprised of rod-like or strip-

like molecules which are arranged to be a layer, where the long axes of molecules in the nematic liquid crystal molecule layer are parallel and the direction of the long axes is perpendicular to the normal line of the layer. The long axes of molecules in the smectic C phase liquid crystal molecule layer are parallel and the direction of the long axes is inclined to the normal line of the layer. The smectic C^* phase liquid crystals are arranged to be a layer-like structure, as shown in Figure 2. The angle between the long axis of the molecule in the layer and the normal line of the layer is θ , molecules in each layer are distributed on the surface of a cone with a vertex angle of 2θ , and liquid crystal molecules in each layer have the same inclination angle. However, in the adjacent layers, the offset angle of liquid crystal molecules changes with a helical structure, such that the liquid crystal molecules along the same normal line of the layer are arranged in a helical structure. An inclined smectic liquid crystal composed of the smectic C^* phase (chiral smectic C phase liquid crystal) may have no mirror symmetry, and thus may have a spontaneous polarization dipole moment and have a ferroelectric property, so it is referred to as ferroelectric liquid crystal.

[0032] The principle of the ferroelectric liquid crystal display is as follows. Similar to the metal in the magnetic field, ferroelectric liquid crystal molecules may form an accurate and ordered arrangement when affected by an external electric field. The ferroelectric liquid crystal molecules may be regularly arranged on a conical surface rotatably under the action of an electric field, and modulation of the light transmission intensity may be achieved by the rotation of the liquid crystal molecules. In this way, the light and shade display may be generated under the action of the electric field. A desired image may be formed by controlling every pixel according to the principle. Because the rotation of the ferroelectric liquid crystal molecule is a result of coupling of an external electric field and the electric dipole moment, and the molecules do a conical surface rotation, advantages such as fast response and wide viewing angle may be obtained.

[0033] In order to make the above objects, features and advantages of the present invention more apparent and easier to be understood, specific embodiments of the present invention will be described in detail below in conjunction with the accompanying drawings.

[0034] Many specific details are described in the description below for full understanding of the present invention. However, the present invention may also be implemented by many other methods different from the description herein, and similar extension may be made by those skilled in the art without departing from the connotation of the present invention. Therefore, the present invention is not limited to the specific embodiments disclosed below.

First embodiment

[0035] In the embodiment, nematic liquid crystal in the

TN mode is replaced by Semi-V shaped ferroelectric liquid crystal.

[0036] A TN mode capacitive embedded touch display device in the prior art is shown in Figure 2, which includes a first substrate 100 and a second substrate 200 disposed to be opposite to each other, and a liquid crystal display unit and a capacitive touch unit disposed between the first substrate 100 and the second substrate 200, where the liquid crystal display unit includes a pixel electrode layer 120, a common electrode layer and a liquid crystal layer 30. The pixel electrode layer 120 and the common electrode layer are disposed respectively on two sides of the liquid crystal layer, and the liquid crystal in the liquid crystal layer 30 is nematic liquid crystal.

[0037] The opposite surfaces of the first substrate 100 and the second substrate 200 are covered with alignment films, and the 90° twist of the nematic liquid crystal molecules in the liquid crystal layer 30 is achieved by mutually perpendicular rubbing and anchoring of the alignment films.

[0038] The first substrate and the second substrate are formed of transparent insulating material. In the embodiment, the first substrate and the second substrate are formed of glass panels generally used in the manufacturing field of liquid crystal panel. A TFT array layer 110 is also provided between the pixel electrode 110 and the first substrate 100. The material of the pixel electrode layer 120 and the common electrode layer are transparent conductive material, and the main material of the TFT array layer 110 is transparent conductive material. In the embodiment, the transparent conductive material may be indium tin metal oxide generally used in the manufacturing field of liquid crystal panel. In the Figure, the common electrode includes a common electrode 210 and a common electrode 211 separated with each other, which may also serve as the touch unit of the capacitive touch unit which includes sensing electrodes and driving electrodes. The common electrode in the liquid crystal display unit may serve as the touch unit, which may be realized by inputting different voltage at different time to perform different function at different time. The touch operating time is rather short, which is about 10% of display refresh time, and the liquid crystal molecules do not have enough time to response in the period of voltage change, therefore the sharing of the common electrode and the touch electrode has almost no serious effect on display.

[0039] Similarly, in other embodiments, the common electrode may serve as only one of the driving electrode and the sensing electrode of the touch electrode, and the other one is disposed on the liquid crystal layer. For example, the common electrode serves as the driving electrode, and the surface of the side of the liquid crystal layer on which the common electrode is formed is covered with an insulating layer which is covered with the sensing electrode. Alternatively, the common electrode serves as the sensing electrode, and the surface of the side of the liquid crystal layer on which the common electrode is formed is covered with an insulating layer which is covered with

the driving electrode.

[0040] The arrangement of an upper polarizer, a lower polarizer and liquid crystal molecules is shown in Figure 3 and Figure 4, where the optical axis directions of the upper polarizer 610 and the lower polarizer 620 are orthogonal to each other. Figure 3 shows that when light is transmitted, the liquid crystal molecules 30 on the upper surface and lower surface are parallel to the directions of optical axes of their closer polarizers respectively, liquid crystal molecules 30 in the middle of the liquid crystal layer rotate gradually, and the light through the upper polarizer and the lower polarizer passes through the liquid crystal layer by rotating synchronously with the rotating of the liquid crystal molecules 30. Figure 4 shows that when a voltage is applied, under the action of the electric field, liquid crystal molecules in the middle are all upright, and the liquid crystal molecules 30 on the upper surface and lower surface are still parallel to the directions of optical axes of their closer polarizers respectively. In this way, the light can not pass through the liquid crystal layer by the liquid crystal molecules. The liquid crystal layer is in a dark state.

[0041] Because TN mode is a liquid crystal mode where a 90° twist angle of a liquid crystal molecule of nematic liquid crystal is used. In such a structure, the vertical rotation of the liquid crystal 30 causes a great change of permittivity of the liquid crystal layer, which seriously affects the judgment of sensitivity of the common electrode 210 and the common electrode 211 which also function as the common electrode and the touch electrode when serving as the touch electrode.

[0042] In the embodiment, the nematic liquid crystal 30 in the TN mode is replaced with ferroelectric liquid crystal 40, as shown in Figure 5. The ferroelectric liquid crystal 40 is Semi-V shaped ferroelectric liquid crystal, and the Semi-V shape means that the morphology of the electro-optical characteristic alignment of the ferroelectric liquid crystal is Semi-V shaped. The morphology of the electro-optical characteristic alignment of a ferroelectric liquid crystal is generally V-shaped, which has a bi-stable state, and thus it is difficult to show grayscale display, therefore the V-shaped ferroelectric liquid crystal needs to be turned into Semi-V shape ferroelectric liquid crystal to achieve grayscale display, thereby realizing picture display with much complicated changes in color and luminance. The Semi-V shaped ferroelectric liquid crystal may be obtained by performing asymmetrical anchoring on the ferroelectric liquid crystal. The asymmetrical anchoring process is carried out in this way that: an alignment film on the first substrate 100 has an alignment direction antiparallel to that of an alignment film on the second substrate 200, and an rubbing alignment intensity different from that of the alignment film on the second substrate 200, which are realized by rubbing along antiparallel directions with different strength when rubbing the resin. In this way, the depths of the tiny gaps formed on the alignment films (an upper alignment film and a lower alignment film) of the first substrate 100 and the

second substrate 200 are different.

[0043] In this way, in the case where no voltage is applied, the ferroelectric liquid crystal molecules 40 disposed between the upper alignment film and the lower alignment film are arranged along the rubbing alignment direction, with the long axis direction along a horizontal direction. The liquid crystal display unit is in the dark state. When a bright-state voltage is applied between the common electrodes 210, 211 and the pixel electrodes 120, a column of ferroelectric liquid crystal molecules 40 are twisted and functions as a liquid crystal light valve, and thus the liquid crystal display unit starts to display a picture. The ferroelectric liquid crystal 40 rotates according to the azimuth angle θ of its own helical structure, and compared with the vertical rotation in the TN mode, the rotation of the ferroelectric liquid crystal 40 realizes a rather small angle, similar to rotating in a horizontal plane. Therefore the use of the ferroelectric liquid crystal can reduce the change of the permittivity of the liquid crystal layer.

[0044] In this case, those skilled in the art can infer the formula of the transmittance ratio for the liquid crystal molecule rotating in a plane for display:

$$T \equiv \frac{i(\lambda)}{I_0} = \sin^2 \frac{2\pi\Delta n d}{\lambda} \sin^2 4\theta$$

[0045] It can be obtained that T gets a maximum value when $\theta=22.5^\circ$, so the transmittance ratio is the best when $\theta=22.5^\circ$. Therefore, preferably, in the embodiment, the azimuth angle θ of the ferroelectric liquid crystal is 22.5° , which may be achieved by controlling the temperature to which the ferroelectric liquid crystal is cooled down during the phase change when preparation of the ferroelectric liquid crystal by cooling, or by selecting the dipole moment of the ferroelectric liquid crystal molecule. In practical application, it may be customized by a liquid crystal manufacturer.

Second embodiment

[0046] In this embodiment, the liquid crystal in the liquid crystal layer of the capacitive embedded touch display device is twisted ferroelectric liquid crystal.

[0047] Specifically, the rubbing direction of alignment film on the surface of the first substrate is perpendicular to the rubbing direction of alignment film on the surface of the second substrate, both of the rubbing directions of alignment films are consistent to the optical axis of the polarizer. Other structures in the capacitive embedded touch display device are similar to those in the first embodiment.

[0048] In the embodiment, the liquid crystal molecule layer in the twisted ferroelectric liquid crystal is perpendicular to the surface of the substrate, which are achieved

by mutually perpendicular anchoring of the first substrate and the second substrate, i.e., the rubbing directions of the alignment films on the surfaces of the first substrate and the second substrate are mutually perpendicular, but director of the molecules between the two substrates are twisted to 90° . When a voltage is applied, anti-ferroelectric liquid crystal molecules only rotate almost in a plane. In such a structure, the arrangement of twisted ferroelectric liquid crystal molecules between the upper substrate and the lower substrate is the same as the arrangement of the liquid crystal molecules in the TN liquid crystal mode.

[0049] For the liquid crystal display mode of the liquid crystal display unit of the embodiment, a bright state is obtained when no voltage is applied, and when a voltage is applied, the spontaneous polarization directions of the twisted ferroelectric liquid crystal molecules are the same, and the liquid crystal molecules rotate almost in a plane, so a dark state is obtained. In this way, the variation of the permittivity of the liquid crystal layer is much smaller than that of the TN liquid crystal, which may effectively reduce the variations of the mutual capacitance and the parasitic capacitance caused by the rotation of the liquid crystal molecules. But the off-state response time is almost the same as that of the TN liquid crystal mode.

[0050] Similar to the first embodiment, in order to obtain a maximum transmittance ratio, the azimuth angle θ of the twisted ferroelectric liquid crystal is preferably 45° .

30 Third embodiment

[0051] In the embodiment, the capacitive touch unit in the embedded capacitive touch display device may be provided on one side of a color film. Specifically, one side of the liquid crystal layer is closer to the first substrate, and the other side of the liquid crystal layer is covered with a color film. The capacitive touch unit is disposed on the side of the color film relatively far from the liquid crystal layer, and the other side of the capacitive touch unit is toward the inner surface of the second substrate. The structure of the liquid crystal panel is similar to that of the first embodiment or the second embodiment.

[0052] The capacitive touch unit includes multiple parallel sensing electrodes and multiple parallel driving electrodes crossing the sensing electrodes, and the driving electrodes and the sensing electrodes are located in the same layer or in different layers.

[0053] A top view of an embodiment is shown in Figure 6, including a driving electrode layer 12 and a sensing electrode layer 14. The driving electrode layer 12 or the sensing electrode layer 14 is formed by multiple small-sized and diamond-shaped electrode patterns in which multiple parallel driving electrodes or multiple parallel sensing electrodes are formed by connecting the electrode patterns. The driving electrode layer 12 includes multiple driving electrodes 12a, 12b, 12c..., and the sensing electrode layer 14 includes multiple sensing electrodes 14a, 14b, 14c.... In this embodiment, the driving

electrodes cross the sensing electrodes, and all the diamond-shaped patterns of the driving electrodes are connected in the same horizontal direction. The sensing electrodes and the driving electrodes are covered with a dielectric layer having via holes, all diamond-shaped patterns of the sensing electrode are electrically connected by an interconnecting wire through the via holes. Or all diamond-shaped patterns of the sensing electrode are connected in the same horizontal direction. The sensing electrodes and the driving electrodes are covered with a dielectric layer having via holes, and all diamond-shaped patterns of the driving electrode are electrically connected by an interconnecting wire through the via holes.

[0054] In an embodiment where driving electrodes and sensing electrodes are of a bi-layer structure, the shape of the driving electrodes and the sensing electrodes in the driving electrode layer and the sensing electrode layer may be similar to that described above, i.e., may be a diamond-shaped pattern. The driving electrodes cross the sensing electrodes, and the diamond-shaped patterns of the driving electrodes or the sensing electrodes are connected in the same horizontal direction. A transparent insulating layer is disposed between the driving electrodes and the sensing electrodes to serve as a dielectric layer for isolation.

[0055] The driving electrodes and the sensing electrodes include an indium tin metal oxide layer and a metal layer which are overlapped. The diamond-shaped patterns are formed of the indium tin metal oxide layer, and the edge of each diamond-shaped pattern is covered with the metal of the metal layer to form a net-like structure, which improves the whole conductive properties of the touch electrode. The grids of the metal layer are further covered with a protection layer.

Fourth embodiment

[0056] In the embodiment, the ferroelectric liquid crystal layer is filled with bi-stable ferroelectric liquid crystal molecules. The anchoring directions of alignment films on the first substrate and the second substrate are parallel, other structures are similar to or the same as those of the aforementioned embodiments. In such a structure, the bi-stable ferroelectric liquid crystal molecules only display in a bright state or a dark state, but don't display in the gray state. Therefore, the liquid crystal display unit according to the embodiment is only adapted to occasions where only bright state and dark state are needed for display, such as display of a character or display of a monochromatic identifier.

[0057] Although preferred embodiments of the present invention have been disclosed above, they are not intended to limit the present invention. Any possible changes and modifications may be made to the technical solutions of the present invention by those skilled in the art according to the method and the technical content disclosed above without departing from the spirit and the scope of the present invention. Therefore the scope of

protection of the present invention should be defined by the claims.

5 Claims

1. An embedded touch display device, comprising:

a first substrate and a second substrate which are opposite to each other; and
a liquid crystal display unit and a capacitive touch unit disposed between the first substrate and the second substrate,
wherein the liquid crystal display unit comprises a pixel electrode layer, a common electrode layer and a liquid crystal layer,
wherein the pixel electrode layer and the common electrode layer are disposed on two sides of the liquid crystal layer respectively, and
wherein the liquid crystal in the liquid crystal layer comprises a ferroelectric liquid crystal material.

2. The embedded touch display device according to claim 1, wherein the first substrate and the second substrate are made of a transparent insulating material.

3. The embedded touch display device according to claim 1, wherein the pixel electrode layer and the common electrode layer are made of a transparent conductive material.

4. The embedded touch display device according to claim 1, wherein the liquid crystal in the liquid crystal layer comprises Semi-V shaped ferroelectric liquid crystals, which are obtained by performing asymmetrical anchoring on the ferroelectric liquid crystal.

5. The embedded touch display device according to claim 1, wherein the process of asymmetrical anchoring on the ferroelectric liquid crystal comprises setting an alignment direction of an upper alignment film reaching an upper surface of the liquid crystal layer and an alignment direction of a lower alignment film reaching a lower surface of the liquid crystal layer to be antiparallel, and setting an alignment intensity of the upper alignment film reaching the upper surface of the liquid crystal layer and an alignment intensity of the lower alignment film reaching the lower surface of the liquid crystal layer to be different.

6. The embedded touch display device according to claim 1, wherein an upper alignment film reaching an upper surface of the liquid crystal layer has an alignment direction perpendicular to an alignment intensity of a lower alignment film reaching a lower surface of the liquid crystal layer, and a same align-

ment intensity as an alignment direction of the lower alignment film reaching the lower surface of the liquid crystal layer, and the ferroelectric liquid crystal is twisted ferroelectric liquid crystal.

7. The embedded touch display device according to claim 1, wherein the common electrode layer comprises a plurality of parallel common electrodes. 5
8. The embedded touch display device according to claim 7, wherein the capacitive touch unit comprises: a plurality of parallel driving electrodes crossing the common electrodes or a plurality of parallel sensing electrodes crossing the common electrodes, and an insulating layer is disposed between the common electrodes and the driving electrodes or between the common electrodes and the sensing electrodes. 10 15
9. The embedded touch display device according to claim 1, wherein one side of the liquid crystal layer is facing to the second substrate, and an opposite side of the liquid crystal layer is covered with a color film; 20
the capacitive touch unit is disposed on one side of the color film away from the liquid crystal layer, and the first substrate is disposed on one side of the capacitive touch unit away from the liquid crystal layer. 25
10. The embedded touch display device according to claim 9, wherein the capacitive touch unit comprises a plurality of parallel sensing electrodes and a plurality of parallel driving electrodes crossing the sensing electrodes, the driving electrodes being disposed in a same layer as the sensing electrodes. 30 35
11. The embedded touch display device according to claim 9, wherein the capacitive touch unit is a bi-layer structure comprising: a plurality of parallel sensing electrodes and a plurality of parallel driving electrodes crossing the sensing electrodes, and an insulating layer disposed between the driving electrodes and the sensing electrodes. 40 45
12. The embedded touch display device according to claim 8, 10 or 11, wherein the driving electrodes and/or the sensing electrodes comprise an indium tin metal oxide layer and a metal layer which are overlapped, and the metal layer has a net-like structure. 50
13. The embedded touch display device according to claim 12, wherein the metal layer has a surface covered with a protection layer which is a black matrix for shading. 55
14. The embedded touch display device according to claim 9, further comprising a planarization layer is disposed between the liquid crystal layer and the

color film.

15. The embedded touch display device according to claim 9, wherein the planarization layer is made of a transparent organic material.




FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2012/086113

A. CLASSIFICATION OF SUBJECT MATTER

See the extra sheet

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC: G02F, G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

CNABS, CNTXT, VEN: touch sensitive, feel+, touch+, pressure 1w force, stress, sens+, ferroelectric, align+, direct+, orient+, antiparallel, anti 1w parallel

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	CN 101251667 A (AU OPTRONICS CORP.), 27 August 2008 (27.08.2008), description, page 5, line 28 to page 8, line 14, and figures 1a-2c	1-15
Y	US 5122787 A (SEIKOSHA CO., LTD.), 16 June 1992 (16.06.1992), description, column 2, line 53 to column 4, line 30, and figures 1-3	1-15
Y	CN 101055395 A (SHANTOU GOWORLD DISPLAY CO., LTD.), 17 October 2007 (17.10.2007), description, page 3, lines 7-19, and figures 1-2	4, 5
Y	JP 63-204313 A (SEMICONDUCTOR ENERGY LAB), 24 August 1988 (24.08.1988), the whole document	1-15
Y	CN 101794038 A (SEMICONDUCTOR ENERGY LABORATORY), 04 August 2010 (04.08.2010), description, paragraphs 58-143, and figures 4-5D and 9	1-15

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	
"E" earlier application or patent but published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	"&" document member of the same patent family

Date of the actual completion of the international search 23 May 2013 (23.05.2013)	Date of mailing of the international search report 06 June 2013 (06.06.2013)
Name and mailing address of the ISA/CN: State Intellectual Property Office of the P. R. China No. 6, Xitucheng Road, Jimenqiao Haidian District, Beijing 100088, China Facsimile No.: (86-10) 62019451	Authorized officer YANG, Xi Telephone No.: (86-10) 62085560

Form PCT/ISA/210 (second sheet) (July 2009)

INTERNATIONAL SEARCH REPORT

International application No.
PCT/CN2012/086113

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	CN 1723517 A (ROYAL DUTCH PHILIPS ELECTRONICS LTD.), 18 January 2006 (18.01.2006), the whole document	1-15
A	US 5805129 A (CANON KK.), 08 September 1998 (08.09.1998), the whole document	1-15

Form PCT/ISA/210 (continuation of second sheet) (July 2009)

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/CN2012/086113

Patent Documents referred in the Report	Publication Date	Patent Family	Publication Date
CN 101251667 A	27.08.2008	US 7924350 B2	12.04.2011
		US 2009096760 A1	16.04.2009
		CN 101251667 B	16.03.2011
		TW 373659 B1	01.10.2012
		JP 5135118 B2	30.01.2013
		TW 200916896 A	16.04.2009
		JP 2009098629 A	07.05.2009
US 5122787 A	16.06.1992	JP 9138385 A	27.05.1997
		JP 2649402 B2	03.09.1997
		JP 2188718 A	24.07.1990
CN 101055395 A	17.10.2007	CN 100555052 C	28.10.2009
JP 63-204313 A	24.08.1988	US 4875378 A	24.10.1989
		JP 4029086 B	18.05.1992
CN 101794038 A	04.08.2010	US 2010188354 A1	29.07.2010
		TW 201033960 A	16.09.2010
		JP 2010198608 A	09.09.2010
CN 1723517 A	18.01.2006	US 2006071819 A1	06.04.2006
		KR 20050088303 A	05.09.2005
		TW 200414088 A	01.08.2004
		WO 2004053909 A1	24.06.2004
		EP 1573764 A1	14.09.2005
		DE 60305973 D1	20.07.2006
		AU 2003276542 A1	30.06.2004
		JP 2006509302 T	16.03.2006
		EP 1573764 B1	07.06.2006
		DE 60305973 T2	01.02.2007
		AT 329361 T	15.06.2006
US 5805129 A	08.09.1998	US 5500749 A	19.03.1996
		DE 69228956 D1	27.05.1999
		EP 0494626 B1	21.04.1999
		EP 0494626 A2	15.07.1992
		EP 0494626 A3	13.01.1993
		AT 179260 T	15.05.1999
		DE 69228956 T2	02.12.1999
		JP 2802685 B2	24.09.1998
		JP 4251218 A	07.09.1992

Form PCT/ISA/210 (patent family annex) (July 2009)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2012/086113

CLASSIFICATION OF SUBJECT MATTER:

G02F 1/133 (2006.01) i

G06F 3/044 (2006.01) i

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- CN 201210308846 [0001]

专利名称(译)	嵌入式触控显示装置		
公开(公告)号	EP2725409A1	公开(公告)日	2014-04-30
申请号	EP2012876074	申请日	2012-12-07
[标]申请(专利权)人(译)	上海天马微电子有限公司		
申请(专利权)人(译)	上海天马微电子有限公司.		
当前申请(专利权)人(译)	上海天马微电子有限公司.		
[标]发明人	ZHOU XINGYAO		
发明人	ZHOU, XINGYAO		
IPC分类号	G02F1/133 G06F3/044		
CPC分类号	G02F1/13338 G02F1/141 G02F2001/133738 G02F2001/133773 G06F3/0412 G06F3/0416 G06F3/044		
优先权	201210308846.2 2012-08-27 CN		
其他公开文献	EP2725409B1 EP2725409A4		
外部链接	Espacenet		

摘要(译)

一种嵌入式触控显示装置，包括相对的第一基板（100）和第二基板（200）；液晶显示单元和位于第一基板和第二基板之间的电容式触摸单元。液晶显示结构包括像素电极层（120），公共电极层和液晶层（30），像素电极层（120）和公共电极层位于液晶层的两侧（30），液晶层（30）中的液晶（30）是铁电液晶。在嵌入式触控显示装置中，向列液晶被铁电液晶取代，解决了TN模式嵌入式触控显示装置中液晶分子从水平方向向垂直方向或从垂直方向向水平方向旋转的问题。因此，旋转角度大，这导致液晶层的介电常数的很大变化，从而严重影响触摸电极的灵敏度效果。




FIG.5