



Europäisches
Patentamt
European
Patent Office
Office européen
des brevets



(11)

EP 2 031 437 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
04.03.2009 Bulletin 2009/10

(51) Int Cl.:
G02F 1/13357 (2006.01) G09G 3/34 (2006.01)

(21) Application number: 08251483.7

(22) Date of filing: 22.04.2008

(84) Designated Contracting States:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT
RO SE SI SK TR

Designated Extension States:

AL BA MK RS

(30) Priority: 27.08.2007 KR 20070086197
11.03.2008 KR 20080022437

(71) Applicant: Samsung Electro-Mechanics Co., Ltd.
Suwon, Kyungki-do (KR)

(72) Inventors:

- Shin, Chang Ho
Seoul (KR)
- Cho, Dong Hyun
Gyunggi-do (KR)

- Yoo, Chul Hee
Seoul (KR)
- Kim, Dae Yeon
Gyunggi-do (KR)
- Kim, Hyung Suk
Gyunggi-do (KR)
- Hahm, Hun Joo
Gyunggi-do (KR)
- Shin, Jae Hong
Gyunggi-do (KR)

(74) Representative: Powell, Timothy John
Potter Clarkson LLP
Park View House
58 The Ropewalk
Nottingham
NG1 5DD (GB)

(54) **Surface light source using white light emitting diodes and liquid crystal display backlight unit having the same**

(57) There is provided a surface light source (200) using white light emitting diodes (110) including: a plurality of white light emitting diodes (110) arranged at a predetermined distance (a,b,c) from one another, wherein the white light emitting diodes are arranged such that

a light emitting diode unit defined by each of the white light emitting diodes and corresponding ones of the white light emitting diodes disposed at a closest distance (U) from the each white light emitting diode has a central light amount ranging from 80% to 120% with respect to an average light amount of the white light emitting diodes.




FIG. 3

Description**CROSS-REFERENCE TO RELATED APPLICATIONS**

5 [0001] This application claims the priorities of Korean Patent Application No. 2007-86197 filed on August 27, 2007, and Korean Patent Application No. 2008-22437 filed on March 11, 2008, in the Korean Intellectual Property Office, the disclosure of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION**10 Field of the Invention**

15 [0002] The present invention relates to a surface light source using white light emitting diodes (LEDs) and a liquid crystal display (LCD) backlight unit having the same, and more particularly, to a surface light source capable of producing uniform white light overall using white light emitting diodes, and an LCD backlight unit having the same.

Description of the Related Art

20 [0003] A cold cathode fluorescent lamp (CCFL) used as a light source of a conventional liquid crystal display (LCD) employs mercury gas, which may trigger environmental pollution. Besides, the CCFL is slow in response rate, low in color reproducibility and inappropriate for a smaller-sized and lighter-weight LCD panel.

25 [0004] In contrast, a light emitting diode (LED) is environment-friendly, high in response rate with several nano seconds, thus effective for a video signal stream and impulsively driven. Moreover, the LED is capable of reproducing color by 100% and varying brightness and color temperature by adjusting a light amount of red, green and blue LEDs. Also, the LED carries advantages suitable for a smaller-sized and lighter-weight LCD panel. Therefore, of late, the LED has been actively employed as a backlight source of the LCD panel.

30 [0005] An LCD backlight adopting the LED is broken down into an edge-type backlight and a direct-type backlight according to location of a light source. In the former, a light source of an elongated bar shape is disposed at an edge of the LCD panel to irradiate light onto the LCD panel using a light guide plate. In the latter, a surface light source with a substantially identical area to the LCD panel is disposed below the LCD panel to directly irradiate light onto the LCD panel.

35 [0006] FIGS. 1 and 2 illustrate arrangement of red (R), green (G) and blue (B) LEDs of a conventional surface light source.

40 [0007] The surface light source 10 for use in a conventional direct-type LCD panel emits white light by combining the red (R), green (G) and blue (B) light together. Thus, as shown in FIG. 1, a plurality of LED units (U) are arranged to define a square shape. In each of the LED units U, the red, green and blue LEDs 11, 12 and 13 are disposed within a proximity to respective vertices of a triangle. Alternatively, as shown in FIG. 2, a plurality of LED units U are arranged, to define a triangular shape. However, when the LED units U are arranged to define a square shape as shown in FIG. 1, the red LEDs 11 are located with such density that a red line appears in the display.

45 [0008] Meanwhile, when the LED units U are arranged to define a triangular shape as shown in FIG. 2, the red, green and blue LEDs are relatively evenly disposed. However, a light source including the red, green and blue LEDs 11, 12, and 13 in each of the LED units U is arranged such that the LED unit U can produce white light. Thus, to ensure the light source to maintain appropriate brightness level with respect to the other light sources adjacent-thereto-in the triangular shape, the LED units U should be balanced with one another and the light sources of each of the LED units should be balanced with one another in an overall backlight unit. This accordingly renders it hard to manufacture the backlight unit or degraded quality thereof.

50 [0009] Also, a difference in the light amount of the red, green and blue LEDs may adversely affect uniformity, or degrade contrast uniformity despite good color uniformity.

[0010] That is, the LED units are shown partially red or partially blue. Also, with hither temperature, each color is darkened more to hardly ensure a properly functional white surface light source.

55 [0011] Therefore, in the conventional surface light source 10 and the LCD backlight unit having the same, colors are added together with limitation, thereby not realising uniformiy-distributed white light.

SUMMARY OF THE INVENTION

55 [0012] An aspect of the present invention provides a surface light source capable of producing uniform white light using white light emitting diodes (LEDs) and a liquid crystal display (LCD) backlight unit having the same.

[0013] Another aspect of the present invention provides an LCD backlight units having a surface light source capable of producing overall uniform white light using white light emitting diodes.

[0014] According to an aspect of the present invention, there is provided a surface light source using white light emitting diodes, including: a plurality of white light emitting diode arranged at a predetermined distance from one another, wherein the white light emitting diodes are arranged such that a light emitting diode unit defined by each of the white light emitting diodes and corresponding ones of the white light emitting diodes disposed at a closest distance from the each white light emitting diode has a central light amount ranging from 80% to 120% with respect to an average light amount of the white light emitting diodes.

[0015] The white light emitting diode may include: a blue light emitting diode chip; a red phosphor disposed around the blue light emitting diode chip, the red phosphor excited by the blue light emitting diode chip to emit red light; and a green phosphor disposed around the blue light emitting diode chip, the green phosphor excited by the blue light emitting diode chip to emit green light.

[0016] The blue LED used for the white LED may have a dominant wavelength of 430 to 456nm.

[0017] The red light emitted from the red phosphor may have a color coordinate falling within a space defined by four coordinate points (0.6448, 0.4544), (0.8079, 0.2920), (0.6427, 0.2905) and (0.4794, 0.4633) based on the CIE 1931 chromaticity diagram, and the green light emitted from the green phosphor may have a color coordinate falling within a space defined by four coordinate points (0.1270, 0.8037), (0.4117, 0.5661), (0.4197, 0.5316) and (0.2555, 0.5030) based on the CIE 1931 chromaticity diagram.

[0018] An emission spectrum of the blue light emitting diode chip may have a full width at half-maximum of 10 to 30nm, the green phosphor may have a full width at half-maximum of 30 to 100nm and the red phosphor may have a full width at half-maximum of 50 to 200nm.

[0019] The white light emitting diode may include an ultraviolet light emitting diode chip having a dominant wavelength of 250 to 420nm, a red phosphor disposed around the ultraviolet light emitting diode chip to emit red light, a green phosphor emitting green light and a blue phosphor emitting blue light.

[0020] The white light emitting diodes may be arranged in a matrix of columns and rows having a spacing of 8.2 to 70mm from one another, respectively. The white light emitting diodes may be arranged by adjusting at least one of spacing of columns, spacing of rows, and arrangement angles thereof.

[0021] The light emitting diode unit may have a shape selected from one of a polygon, a circle and a combination thereof.

[0022] The red phosphor may be represented by $\text{CaAlSiN}_3:\text{Eu}$ which is a nitride composition, or $(\text{Ca},\text{Sr})\text{S}:\text{Eu}$ which is a silicate composition.

[0023] The green phosphor may be represented by $(\text{Ba}_x,\text{Sr}_y,\text{Mg}_z)\text{SiO}_4:\text{Eu}^{2+}$, F, Cl, where $0 < x, y \leq 2$, $0 \leq z \leq 2$, $0 \text{ ppm} \leq F, Cl \leq 5.00000 \text{ ppm}$, which is a silicate composition, $\text{SrGa}_2\text{S}_4:\text{Eu}$ which is a sulfide composition or $\beta\text{-SiAlON}$ which is a nitride composition.

[0024] According to another aspect of the present invention, there is provided a liquid crystal display backlight unit including: a board; a reflective plate disposed on the board; a surface light source disposed on the reflective plate, the surface light source including: a plurality of white light emitting diodes arranged at a predetermined distance from one another, wherein the white light emitting diodes are arranged such that a light emitting diode unit defined by each of the white light emitting diodes and corresponding ones of the white light emitting diodes disposed at a closest distance from the each white light emitting diode has a central light amount ranging from 80% to 120% with respect to an average light amount of the white light emitting diodes, a diffusing sheet disposed on the surface light source to diffuse light incident from the surface light source uniformly; and a light collecting sheet disposed on the diffusing sheet to collect the light diffused by the diffusing sheet.

[0025] The liquid crystal display backlight unit may further include a protective sheet disposed on the light collecting sheet.

[0026] According to still another aspect of the present invention, there is provided a liquid crystal display backlight unit including: a plurality of light emitting diode modules each including a conductive board having at least one first connector and a plurality of second connectors formed thereon, and an $m \times n$ number of white light emitting diode chips mounted on the conductive board, the white light emitting diode chips arranged in a matrix having an m number of rows and an n number of columns, where m and n are positive integers of at least two, respectively, wherein the $m \times n$ number of light emitting diode light sources are defined into a plurality of blocks, the plurality of blocks are connected to the first and second, connectors to allow the white light emitting diode chips to be independently driven based on each of the blocks, the $m \times n$ number of white light emitting diode chips are arranged at a predetermined distance from one another, and the white light emitting diodes are arranged such that a light emitting diode unit defined by each of the white light emitting diodes and corresponding ones of the white light emitting diodes disposed at a closest distance from the each white light emitting diode has a central light amount ranging from 80% to 120% with respect to an average light amount of the white light emitting diodes.

[0027] The plurality of blocks may be commonly connected to the first connector, the plurality of second connectors are formed in a number identical to the blocks of each of the modules, and the plurality of blocks may be connected to the plurality of second connectors.

[0028] The light emitting diode modules may include 2 to 28 light emitting diode modules, each of the modules may

include 1 to 28 blocks and each of the blocks may have 2 to 240 white light emitting diodes arranged therein.

BRIEF DESCRIPTION OF THE DRAWINGS

5 [0029] The above and other aspects, features and other advantages of the present invention will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which

[0030] FIGS. 1 and 2 illustrate arrangement of red (R), green. (G) and blue (B) LEDs of a conventional surface light source;

10 [0031] FIGS. 3 and 4 illustrate arrangement of a surface light source according to an exemplary embodiment of the invention;

[0032] FIG. 5 is an exploded side sectional view illustrating an LCD backlight unit having a surface light source using white light emitting diodes (LEPs) according to an exemplary embodiment of the invention;

15 [0033] FIG. 6A illustrates a simulation test result of light amount uniformity when an average light amount of white LEDs is 80% to 120%, and FIG. 6B illustrates a simulation test result of light amount uniformity when an average light amount of white LEDs is in excess of 20%;

[0034] FIG. 7 illustrates arrangement of light sources in a separately driven liquid crystal display (LCD) backlight unit according to an exemplary embodiment of the invention;

[0035] FIG. 8 is a view for explaining a circuit configuration for separate driving in a separately driven LCD backlight unit shown in FIG. 7; and

20 [0036] FIG. 9 illustrates a color coordinate range obtained when white LED light sources are employed in an LCD backlight unit.

DETATLED DESCRIPTION OF THE PREFERRED EMBODIMENT

25 [0037] Exemplary embodiments of the present invention will now be described in detail with reference to the accompanying drawings.

Surface light source using white LEDs

30 [0038] First, a surface light source using white light remitting diodes (LEDs) according to an exemplary of the invention will be described in detail with reference to FIGS. 3 and 4.

[0039] FIGS. 3 and 4 illustrate arrangement of white W LEDs of a surface light source according to the present embodiment.

35 [0040] As shown in FIGS. 3 and 4, the surface light source 100 using the white LED according to the present embodiment includes a plurality of white W LEDs 110 arranged at a predetermined distance from one another.

[0041] Although not illustrated, each of the white LEDs 110 may be formed of a blue LED chip, a red phosphor and a green phosphor. Alternatively, the white LED 110 may be formed or an ultraviolet (UV) LED chip, a red phosphor, a green phosphor and a blue phosphor. The red phosphor may utilize $\text{CaAlSiN}_3:\text{Eu}$ which is a nitride composition, or $(\text{Ca}, \text{Sr})\text{S}:\text{Eu}$ which is a sulfide composition. Also, the green phosphor may adopt $(\text{Ba}_x, \text{Sr}_y, \text{Mg}_z)\text{SiO}_4:\text{Eu}^{2+}$, F , Cl ($0 < x, y \leq 2$, $0 \leq z \leq 2$, $0 \text{ppm} \leq \text{F}, \text{Cl} \leq 5000000 \text{ppm}$), which is a silicate composition, $\text{SrGa}_2\text{S}_4:\text{Eu}$ which is a sulfide composition, or $\beta\text{-SiAlON}$ which is a nitride composition.

40 [0042] Moreover, the blue phosphor is formed of one of a silicate-based composition, a sulfide-based composition, a nitride-based composition, and an aluminate-based composition.

[0043] As described, when the white light is produced using the white LEDs 110, only one chip is utilized to ensure easier manufacture of the backlight unit and simpler configuration of a circuit than the conventional method in which white light is obtained using red, green and blue LEDs 11, 12, and 13.

45 [0044] Particularly, in the present embodiment, the plurality of white LEDs are arranged by adjusting, e.g., spacing D_1 of rows L_c , spacing D_2 of columns L_r of the white LEDs 110 or arrangement angles (θ) thereof. The white light emitting diodes are arranged such that a light emitting diode unit U defined by each of the white LEDs 110 and corresponding ones of the white LEDs disposed at a closest distance from the each white light emitting diode has a light amount in a center C ranging from 80% to 120% with respect to an average light amount of the white LEDs 110. Here, the average light amount of the white LEDs 110 is derived by dividing a total light amount by the number of the white LEDs 110.

[0045] Here, the LED unit U may have a triangular shape as shown in FIG. 3. Alternatively, the LED unit U may have a square shape as shown in FIG. 4. Therefore, the center C of the LED unit U may be a weight center of the three white LEDs 110 in the triangular shape (see FIG. 3), or a weight center of the four white LEDs 110 in the square shape (see FIG. 4).

55 [0046] Unlike the conventional configuration, the white light sources are arranged as in FIGS. 3 and 4 to define a polygon including a triangle. Here, the LED unit defined by the each light source and the corresponding ones of the light

sources disposed at a closest distance, i.e., LEDs surrounding the center C as shown in FIGS. 3 and 4 has a central light amount, ... i.e., light amount measured in the center C ranging from 80 to 120% with respect to an average light amount. This ensures optimal uniformity as shown in FIG. 6A.

[0047] The LED unit U has a shape not limited to the aforesaid ones but may be variously shaped as one of a polygon including a triangle, a circle and a combination thereof within the scope of the present invention.

[0048] When all measurements are based on the center of the LED unit, in FIG. 3, a may be 20 to 140 mm, b. and e may be adjusted in a range of 15 and 90 mm, respectively, That is, b and e, when are equal, assures optimal uniformity and b+e should be greater than a. Also, θ denotes an angle of one of the white LEDs located on a row line connecting an array of the white LEDs with respect to an adjacent one of the white LEDs located on another row line connecting an array of the white LEDs. For' example, θ denotes an angle of b or e with respect to the line L connecting the array of the white LEDs. Referring to FIG. 3, θ ranging from 70 to 110° ensures optimal arrangement of the white LEDs. D_1 , and D_2 , when ranging from 8.2 to 70 mm ensure optical uniformity.

[0049] In a similar manner, as shown in FIG. 4, even when θ is substantially 90°, D_1 , and D_2 range from 8.2 to 70mm, respectively to ensure optimal arrangement.

[0050] The arrangement described above may employ light sources satisfying following conditions. Such arrangement is expected to result in superior color reproducibility and improve brightness.

[0051] The white LED light source of the present embodiment may include a blue chip having a dominant wavelength of 430 to 456mm, a red phosphor disposed around the blue LED chip and excited by the blue LED chip to emit red light and a green phosphor disposed around the blue LED chip and excited by the blue LED chip to emit green light.

[0052] The red phosphor may have a color coordinate falling within a space defined by four coordinate points (0.6448, 0.4544), (0.8079, 0.2920), (0.6427, 0.2905) and (0.4794, 0.4633) based on the CIE 1931 chromaticity diagram. The green phosphor may have a color coordinate falling within a space defined by four coordinate points (0.1270, 0.8037), (0.4117, 0.5861), (0.4197, 0.5316) and (0.2555, 0.5030) based on the CIE 1931 chromaticity diagram.

[0053] The LCD backlight unit employing the white LED light source exhibits high color reproducibility as represented by a color coordinate space corresponding to an s-RGB area on the CIE 1976 chromaticity diagram (see FIG. 9). This high color reproducibility cannot be achieved by virtue of a CCFL BLU, a combination of red, blue and green LEDs. i.e., RGB LED BLU and a conventional combination of a blue LED chip, and red and green phosphors.

[0054] Furthermore, an emission spectrum of the blue LED chip has a full width at half-maximum (FWHM) of 10 to 30mm, the green phosphor 105 may have an FWHM of 30 to 100nm and the red phosphor may have an FWHM of 50 to 200nm. Each of the light sources has an FWHM ranging as described above, thereby producing white light with better color uniformity and color quality. Such FWHM conditions may be beneficially employed to enhance performance of the white LED light source. This FWHM range may be more beneficially applied in combination with other conditions such as the dominant wavelength of the blue LED chip and color coordinates of the red phosphor and green phosphor as described above.

[0055] Particularly, the blue LED chip may have a dominant wavelength set to a range of 430 and 456nm and an FWHM set to a range of 10 to 30nm. This significantly enhances efficiency of a $\text{CaAlSiN}_3:\text{Eu}$ red phosphor and efficiency of a $(\text{Ba}_x, \text{Sr}_y, \text{Mg}_z)\text{SiO}_4:\text{Eu}^{2+}$, F, Cl ($0 < x, y \leq 2, 0 \leq z \leq 2, 0 \text{ppm} \leq F, \text{Cl} \leq 5000000 \text{ppm}$) green phosphor.

[0056] That is, according to the present embodiment, the white LEDs 110 employed can be arranged with much less limitation than the conventional surface light source using the red, green and blue LEDs.

[0057] Moreover, according to the present embodiment, as described above, the LED unit U has a light amount in the center C ranging from 80% to 120% with respect to an average light amount of the white LEDs 110, thereby ensuring a uniform light amount, and stable production and quality.

[0058] Here, in a case where the LED unit U has a light amount in the center C smaller than 80% of an average light amount of the white LEDs 110, the white LEDs 110 are degraded in power efficiency to increase temperature and consumption power, thereby undermining uniformity. In a case where the LED unit U has a light amount in the center C greater than 120%, brightness can be increased but the white LEDs 110 employed in a great number result in higher costs, posing difficulty to manufacture of the backlight unit.

[0059] Therefore, in the present embodiment, the white LEDs 110 are arranged such that the LED unit U has a light amount in the center C set to the aforesaid range, thereby obtaining optimal uniformity.

LCD backlight unit having a surface light source using white LEDs

[0060] The surface light -source as described above may be employed in an LCD backlight unit backlighting an LCD panel in an LCD.

[0061] Hereinafter, the LCD backlight unit having a surface light source using white LEDs will be described with reference to FIG. 5.

[0062] FIG. 5 is an exploded side sectional view illustrating an LCD backlight unit having a surface light source using white LEDs.

[0063] As shown in FIG. 5, according to the present embodiment, the LCD backlight unit 200 disposed behind an LCD panel 270 includes a board 210, a reflective plate 220 disposed on the board 210 and a surface light source including white LEDs 110. The reflective plate 220 reflects light emitted from the white LEDs 110 upwards.

[0064] The surface light source is disposed on the reflective plate 220. As described with reference to FIGS. 3 and 4, the plurality of white LEDs 110 are arranged at a predetermined distance from one another. The white LEDs 110 are arranged by adjusting spacing D_1 of columns, spacing D_2 of rows D_2 or arrangement angles θ thereof. Here, the white LEDs 110 are arranged such that a light emitting diode unit U defined by each of the white LEDs 110 and corresponding ones of the white LEDs disposed at a closest distance from the each white light emitting diode has a central light amount ranging from 80% to 120% with respect to an average light amount of the white LEDs.

[0065] A side wall 230 is formed at an edge of the reflective plate 220 to surround the white LEDs 110. The side wall 230 has an inclination surface 235. Here, the inclination surface 235 of the side wall 230 may be additionally applied with a reflective material to ensure light emitted sideward from the white LEDs 110 to be directed upward.

[0066] A diffusing sheet 240 is provided on the surface light source to uniformly diffuse light incident from the surface light source, thereby preventing light from being concentrated locally.

[0067] A light collecting sheet 250 is disposed on the diffusing sheet 240 to collect the light diffused from the diffusing sheet 240 in a direction perpendicular to the LCD panel 270.

[0068] Here, a protective sheet 260 may be further disposed on the light collecting sheet 250 to protect an underlying optical structure. The protective sheet 260 serves to protect a surface of the light collecting sheet 250 while contributing to uniform distribution of light.

[0069] An LCD panel 270 is disposed on the protective sheet 260. The LCD backlight unit 200 of the present embodiment irradiates uniform white light onto the LCD panel by virtue of the surface light source using the white LEDs 110, thereby ensuring a clear LCD image.

Separately driven LCD backlight unit

[0070] The arrangement of the white LEDs described above is applicable to a separately driven LCD backlight unit.

[0071] In the present embodiment, the board 210 may be a conductive board where at least one first connector and a plurality of second connectors are formed to enable flow of positive and negative currents. The separately driven LCD backlight unit includes a plurality of white LED modules mounted on the conductive board to be arranged in a matrix having an m number of rows and an n number of columns, where m and n are positive integers of at least two. The $m \times n$ number of LED light sources are defined into a plurality of blocks. The plurality of blocks are connected to the first and second connectors to independently drive the white LED chips based on each of the blocks.

[0072] In the connector configuration for separate driving, the blocks are commonly connected to the first connector and the second connectors are identical in number to the blocks of each of the modules. The plurality of blocks are connected to the second connectors, respectively.

[0073] In the separately driven LCD backlight of the present embodiment, the number of LED modules, the number of blocks of the LED module and/or the number of the white LED chips in the each block may be adequately adjusted to ensure an appropriate number of LED chips and arrangement for attaining light amount necessary for the separately driven LCD backlight unit.

[0074] The number of the LED modules may be 2 to 28, the number of the blocks may be 1 to 28 for the each module and the number of the white LEDs may be 2 to 240 for the each block.

[0075] Particularly, in a case where the LCD backlight unit is utilized in a 40-inch LCD, the LED module may include 1 to 14 blocks. In a case where the LCD backlight unit is used in a 46-inch LCD, the LED module may include 1 to 15 blocks. Given the assumption that an active area of the 46-inch LCD TV is 1020×580 mm, when the number of the LEDs for the each block is 2 to 240, a total 4 to 100800 of LEDs will be employed.

[0076] Meanwhile, in a larger-sized backlight unit, the number of modules may be increased to employ a necessary number of LED chips easily. Specifically, the LED module may include 1 to 28 blocks and 2 to 240 white LEDs may be arranged in the each block of the LED modules.

[0077] Notably, in a case where the LCD backlight unit is utilized in a 52 inch LCD, the number of the LED modules may be 4 to 12. Also, in a case where the LCD backlight unit is adopted in a 57 inch LCD, the number of the LED modules may be 6 to 20.

[0078] As shown in FIG. 7, an LCD backlight unit 300 according to an exemplary embodiment of the present invention includes four LED modules 320. Each of the LED modules 320 includes a conductive board 311, and a plurality of LED chips 310, mounted on the conductive board 311. The LED chips 310 are white LEDs arranged in a matrix having four rows and nine columns.

[0079] The LED module 320 may be defined into six blocks B1 to B6. In the present embodiment, the blocks B1 to B6 constituting the LED module 320 serve as respective units which can be driven independently.

[0080] As in the present embodiment, the LED chips 310 in each of the blocks B1 to B6 may be connected in series

with one another. Here, the each block B1 to B6 as a circuit has at least one end connected to an individual connector so that the LED chips 310 can be separately driven based on the respective units.

[0081] To ensure connection for this separate driving, the conductive board 311 of the LED module 320 is illustrated to include two first connectors 312 and six second connectors 314a, 314b, and 314c. The first and second connectors 312, and 314a, 314b, 314c are connected to different polarities from each other to provide an external voltage to the LED chips 310.

[0082] FIG. 8 illustrates a circuit configuration for separate driving in the separately driven LCD backlight of FIG. 7.

[0083] Referring to FIG. B, an LED module 320 includes a conductive board 311 and a plurality of LED chips 310 arranged on the conductive board 311 in a matrix having four rows and nine columns.

[0084] In the LED module 320, the LED chips 310 are defined into six blocks B1 to B6 as described in FIG. 8

[0085] In the present embodiment, six white LED chips 310 in the first and second rows and corresponding three columns of the nine columns define first to third blocks B1 to B3, respectively. In a similar manner, six white LED chips 310 in the third and fourth rows and corresponding three columns of the nine columns define fourth to sixth blocks B4 to B6, respectively.

[0086] The LED chips 310 of each of the blocks are connected in series with one another. In a circuit configuration where the first to third blocks B1, B2, and B3 are connected in series with one another, a plus (+) terminal is commonly connected to a first connector P1 and a minus (-) terminal is divided based on the each block to connect to respective three second connectors P21, P22, and P23.

[0087] Likewise, in a circuit configuration where the fourth to sixth blocks B4, B5, and B6 are connected in series with one another, a plus (+) terminal is commonly connected to a first connector and a minus (-) terminal is divided based on the each block to connect to respective three second connectors. Here, reference numerals P1, and P21, P22, P23 of FIG. 8 are construed to correspond to the first and second connectors, respectively shown in FIG. 7.

[0088] As described above, the separately driven LCD backlight unit of the present invention realizes a structure necessary for separate driving using the unit of blocks. The separate driving LCD backlight unit can be defined largely into three blocks, and the necessary number of LEDs may be adjusted.

[0089] More specifically, in the separately driven LCD backlight unit, the white LEDs are arranged in a matrix having a plurality of rows and columns to ensure uniform density overall. Also, the white LEDs can be arranged by adjusting the number of the LED modules, the number of the blocks for enabling separate driving in the LED module and the number of the LED chips in the each block, thereby assuring an appropriate number of the LED chips according to area. As a result, the white LEDs can be arranged easily in a necessary number to have adequate density. This consequently improves local dimming effect and overall color uniformity in a medium or large-sized display

[0090] Hereinafter, a description will be given of a suitable number of LEDs and numbers of respective units such as the LED modules, blocks and chips for each block according to size of the backlight unit (BLU).

[0091] Here, the BLUs are applied to displays with representative sizes of 40 inch, 46 inch, 52 inch and 57 inch.

[0092] First, a total required light amount (unit: lumens) for the BLUs of each size can be set to 7000, 8000, 93000, and 13000, respectively. The number of LED chips satisfying such a total required light amount can be determined by a light amount of the unit LED chip as shown in Table 1.

[0093] A necessary number of the LED chips with 4, 8, 10, and 15 lumens, respectively for general use can be noted as in Table 1.

Table 1

BLU size (inch)	40	46	52	57
Total required light amount (lumens)	7000	8000	9300	13000
Number of LEDs according to unit LED light amount	4 lumens LED	1750	2000	2325
	8 lumens LED	875	1000	1162
	10 lumens LED	700	800	930
	15 lumens LED	466	533	622

[0094] As shown in Table 1, a necessary number of the LED chips may be slightly varied according to a unit light amount of the LED chips used. A great number of the LED chips need to be arranged suitably to ensure optimum density considering color uniformity and brightness.

[0095] To ensure that this arrangement allows for various areas and numbers more easily, according to the present embodiment, the number of LED modules, the number of blocks for each module, the number of LED chips for each block should be adequately selected to obtain optimum brightness and color uniformity.

[0096] To satisfy conditions shown in Table 1, the number of LED modules, the number of blocks for each module, and the number of LED chips for each block can be selected in the BLU of each size, as noted in Table 2.

Table 2

5	BLU size (inch)	40	46	52	57
10	Number of LED chips	466~1750	533~2000	622~2325	866~3250
15	Number of modules	6~12	6~12	6~12	6~20
20	Number of blocks	4~14	5~15	6~28	6~28
25	Number of LED chips for each block	6~24	6~24	6~24	6~24

[0097] In a case where the BLU is utilized in LCDs of a medium size such as 40 inch, and 46 inch, the number of the LED modules and the number of the LED chips for the each block may be selected identically. In a case where the LCD BLU is employed in a 40-inch LCD, each of the LED modules is defined into 4 to 14 blocks. Also, in a case where the LCD BLU is used in a 46-inch LCD, the LED module may include 5 to 15 blocks. Of course, the number of the modules and the number of the chips for the each block can be varied appropriately in a range shown in Table 2.

[0098] Moreover, in a case where the LCD BLU is utilized in LCDs with a relatively big size of 52 inch and 57 inch, the number of the blocks for the each LED module may be selected to range from 6 to 28, and the number of the LED chips for the each block may be selected to range from 6 to 24. In a case where the LCD BLU is utilized in a 52 inch LCD, the number of the modules may be 6 to 12. Also, in a case where the LCD BLU is used in a 57 inch LCD, the number of LED modules may be 6 to 20.

[0099] Of course, the white LEDs for use in the separately driven LCD backlight unit may be any type of the white LED light sources described above (see "surface light source using white LEDs".)

[0100] As set forth above, according to exemplary embodiments of the invention, in a surface light source using white LEDs and an LCD backlight unit having the same, white LEDs can be arranged appropriately to produce uniform white light overall. Also, unlike a conventional surface light source including a combination of red, green and blue LEDs, only one-chip, i.e., white LEDs are employed to allow the LEDs to be arranged with less limitation. This also ensures easier manufacture of the backlight unit and simpler configuration of circuits.

[0101] In addition, uniform white light can be irradiated onto an LCD panel to assure a clearer LCD image.

[0102] While the present invention has been shown and described in connection with the exemplary embodiments, it will be apparent to those skilled in the art that modifications and variations can be made without departing from the spirit and scope of the invention as defined by the appended claims.

Claims

1. A surface light source using white light emitting diodes comprising:

40 a plurality of white light emitting diodes arranged at a predetermined distance from one another, wherein the white light emitting diodes are arranged such that a light emitting diode unit defined by each of the white light emitting diodes and corresponding ones of the white light emitting diodes disposed at a closest distance from the each white light emitting diode has a central light amount ranging from 80% to 120% with respect to an average light amount of the white light emitting diodes.

45 2. The surface light source of claim 1, wherein the white light emitting diode comprises:

50 a blue light emitting diode chip; a red phosphor disposed around the blue light emitting diode chip, the red phosphor excited by the blue light emitting diode chip to emit red light; and a green phosphor disposed around the blue light emitting diode chip, the green phosphor excited by the blue light emitting diode chip to emit green light.

55 3. A surface light source using white light emitting diodes comprising:

a plurality of white light emitting diodes arranged at a predetermined distance from one another, wherein the white light emitting diodes are arranged such that a light emitting diode unit defined by each of the

white light emitting diodes and corresponding ones of the white light emitting diodes disposed at a closest distance from the each white light emitting diode has a central light amount ranging from 80% to 120% with respect to an average light amount of the white light emitting diodes, and
 5 the white light emitting diode comprises a blue light emitting diode chip having a dominant wavelength of 430 to 456nm, a red phosphor emitting red light and a green phosphor emitting green light.

4. A surface light source using white light emitting diodes comprising:

a plurality of white light emitting diodes arranged at a predetermined distance from one another,
 10 wherein the white light emitting diodes are arranged such that a light emitting diode unit defined by each of the white light emitting diodes and corresponding ones of the white light emitting diodes disposed at a closest distance from the each white light emitting diode has a central light amount ranging from 80% to 120% with respect to an average light amount of the white light emitting diodes, and
 15 the white light emitting diode comprises a blue light emitting diode chip having a dominant wavelength of 430 to 456nm, a red phosphor emitting red light and a green phosphor emitting green light,
 wherein the red light emitted from the red phosphor has a color coordinate falling within a space defined by four coordinate points (0.6448, 0.4544), (0.8079, 0.2920), (0.6427, 0.2905) and (0.4794, 0.4633) based on the CIE 1931 chromaticity diagram, and
 20 the green light emitted from the green phosphor has a color coordinate falling within a space defined by four coordinate points (0.1270, 0.8037), (0.4117, 0.5861), (0.4197, 0.5316) and (0.2555, 0.5030) based on the CIE 1931 chromaticity diagram.

5. A surface light source using white light emitting diodes comprising:

a plurality of white light emitting diodes arranged at a predetermined distance from one another,
 25 wherein the white light emitting diodes are arranged such .. that a light emitting diode unit defined by each of the white light emitting diodes and corresponding ones of the white light emitting diodes disposed at a closest distance from the each white light emitting diode has a central light amount ranging from 80% to 120% with respect to an average light amount of the white light emitting diodes,
 30 the white light emitting diode comprises a blue light emitting diode chip, a red phosphor and a green phosphor, and an emission spectrum of the blue light emitting diode chip has a full width at half-maximum of 10 to 30nm, the green phosphor has a full width at half-maximum of 30 to 100nm and the red phosphor has a full width at half-maximum of 50 to 200nm.

35 6. A surface light source using white light emitting diodes comprising:

a plurality of white light emitting diodes arranged at a predetermined distance from one another,
 40 wherein the white light emitting diodes are arranged such that a light emitting diode unit defined by each of the white light emitting diodes and corresponding ones of the white light emitting diodes disposed at a closest distance from the each white light emitting diode has a central light amount ranging from 80% to 120% with respect to an average light amount of the white light emitting diodes,
 the white light emitting diode comprises an ultraviolet light emitting diode chip having a dominant wavelength of 250 to 420nm, a red phosphor disposed around the ultraviolet light emitting diode chip to emit red light, a green phosphor emitting green light and a blue phosphor emitting blue light.
 45

7. The surface light source of claim 4, wherein the white light emitting diodes are arranged in a matrix of columns and rows having a spacing of 8.2 to 70mm from one another, respectively.

50 8. The surface light source of one of claim 4, wherein the white light emitting diodes are arranged by adjusting at least one of spacing of columns, spacing of rows and arrangement angles thereof.

9. The surface light source of claim 4, wherein the light emitting diode unit has a shape selected from one of a polygon, a circle and a combination thereof.

55 10. The surface light source of claim 4, wherein the red phosphor is represented by one of $\text{CaAlSiN}_3:\text{Eu}$ and $(\text{Ca},\text{Sr})\text{S}:\text{Eu}$.

11. The surface light source of claim 4, wherein the green phosphor is represented by one of $(\text{Ba}_x,\text{Sr}_y,\text{Mg}_z)\text{SiO}_4:\text{Eu}^{2+}$, F, Cl , where $0 < x, y \leq 2, 0 \leq z \leq 2, 0 \text{ppm} \leq F, \text{Cl} \leq 5000000 \text{ppm}$, $\text{SrGa}_2\text{S}_4:\text{Eu}$ and $\beta\text{-SiAlON}$.

12. A liquid crystal display backlight unit comprising:

a board;
 a reflective plate disposed on the board;
 5 a surface light source disposed on the reflective plate, the surface light source comprising: a plurality of white light emitting diodes arranged at a predetermined distance from one another, wherein the white light emitting diodes are arranged such that a light emitting diode unit defined by each of the white light emitting diodes and corresponding ones of the white light emitting diodes disposed at a closest distance from the each white light emitting diode has a central light amount ranging from 80% to 120% with respect to an average light amount of the white light emitting diodes,
 10 a diffusing sheet disposed on the surface light source to diffuse light incident from the surface light source uniformly; and
 a light collecting sheet disposed on the diffusing sheet to collect the light diffused by the diffusing sheet.

15 13. The liquid crystal display backlight unit of claim 12, further comprising a protective sheet disposed on the light collecting sheet.

14. A liquid crystal display backlight unit comprising:

20 a plurality of light emitting diode modules each comprising a conductive board having at least one first connector and a plurality of second connectors formed thereon, and an $m \times n$ number of white light emitting diode chips mounted on the conductive board, the white light emitting diode chips arranged in a matrix having an m number of rows and an n number of columns, where m and n are positive integers of at least two, respectively, wherein the $m \times n$ number of light emitting diode light sources are defined into a plurality of blocks,
 25 the plurality of blocks are connected to the first and second connectors to allow the white light emitting diode chips to be independently driven based on each of the blocks,
 the $m \times n$ number of white light emitting diode chips are arranged at a predetermined distance from one another, and
 30 the white light emitting diodes are arranged such that a light emitting diode unit defined by each of the white light emitting diodes and corresponding ones of the white light emitting diodes disposed at a closest distance from the each white light emitting diode has a central light amount ranging from 80% to 120% with respect to an average light amount of the white light emitting diodes.


35 15. The liquid crystal display backlight unit of claim 14, wherein the plurality of blocks are commonly connected to the first connector, the second connectors are formed in a number identical to the blocks of each of the modules, and the plurality of blocks are connected to the plurality of second connectors.

40 16. The liquid crystal display backlight unit of claim 14, wherein the light emitting diode modules comprise 2 to 28 light emitting diode modules, each of the modules comprises 1 to 28 blocks and each of the blocks has 2 to 240 white light emitting diodes arranged therein.

45


50

55



PRIOR ART

FIG. 1



PRIOR ART

FIG. 2




FIG. 3




FIG. 4




FIG. 5



FIG. 6A



FIG. 6B




FIG. 7




FIG. 8




FIG. 9



EUROPEAN SEARCH REPORT

Application Number
EP 08 25 1483

DOCUMENTS CONSIDERED TO BE RELEVANT			CLASSIFICATION OF THE APPLICATION (IPC)
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	
X	EP 1 717 633 A (SAMSUNG ELECTRONICS CO LTD [KR]) 2 November 2006 (2006-11-02) * abstract * * paragraphs [0059] - [0081] * * figures 1,3,5 *	1,7-9, 12,13	INV. G02F1/13357 G09G3/34
Y	-----	2-6,10, 11,14-16	
Y	US 2007/153515 A1 (HONG HEE-JUNG [KR] ET AL) 5 July 2007 (2007-07-05) * abstract * * paragraphs [0037], [0045] * * figure 3 *	2-5,10, 11	
Y	----- WO 01/24229 A (LUMILEDS LIGHTING LLC [US]) 5 April 2001 (2001-04-05) * abstract * * page 4, line 27 - page 5, line 2 * * page 6, lines 9-16 * * figure 1 *	2-5,10, 11	
Y	----- WO 2006/068141 A (TOKYO SHIBAURA ELECTRIC CO [JP]; TOSHIBA MATERIALS CO LTD; ISHII TSUTO) 29 June 2006 (2006-06-29) * abstract *	6	TECHNICAL FIELDS SEARCHED (IPC)
P,Y	-& EP 1 830 415 A (TOSHIBA KK [JP]; TOSHIBA MATERIALS CO LTD [JP]) 5 September 2007 (2007-09-05) * abstract *	6	G02F G09G
Y	----- EP 1 521 235 A (LUMILEDS LIGHTING LLC [US]) 6 April 2005 (2005-04-06) * abstract * * paragraphs [0019] - [0023], [0030] * * figures 8B,11A,11B *	14-16	
	----- ----- -----	-/-	
3	The present search report has been drawn up for all claims		
EPO FORM 1503 03.82 (P04C01)	Place of search	Date of completion of the search	Examiner
	Munich	28 November 2008	Hauser, Markus
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			



EUROPEAN SEARCH REPORT

Application Number
EP 08 25 1483

DOCUMENTS CONSIDERED TO BE RELEVANT			CLASSIFICATION OF THE APPLICATION (IPC)
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	
Y	US 2007/013647 A1 (LEE SANG YUN [KR] ET AL) 18 January 2007 (2007-01-18) * abstract * * paragraphs [0034], [0035] * * figure 3 * -----	14-16	
			TECHNICAL FIELDS SEARCHED (IPC)
3	The present search report has been drawn up for all claims		
EPO FORM 1503 03.82 (P04C01)	Place of search	Date of completion of the search	Examiner
	Munich	28 November 2008	Hauser, Markus
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			



CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing claims for which payment was due.

Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for those claims for which no payment was due and for those claims for which claims fees have been paid, namely claim(s):

No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for those claims for which no payment was due

LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.

As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.

Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:

None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:

The present supplementary European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims (Rule 164 (1) EPC).



LACK OF UNITY OF INVENTION
SHEET B

Application Number
EP 08 25 1483

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. claims: 1-13

Surface light source and liquid crystal display device comprising such a light source with white LEDs having particular properties.

2. claims: 14-16

Liquid crystal display device wherein the LEDs of the backlight are connected so as to allow driving them in blocks.

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 08 25 1483

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on. The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

28-11-2008

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
EP 1717633	A	02-11-2006		CN 1854859 A JP 2006310319 A KR 20060113174 A US 2006244879 A1		01-11-2006 09-11-2006 02-11-2006 02-11-2006
US 2007153515	A1	05-07-2007		JP 2007183560 A KR 20070070711 A		19-07-2007 04-07-2007
WO 0124229	A	05-04-2001		AU 7715800 A EP 1145282 A2 JP 2002060747 A US 6686691 B1		30-04-2001 17-10-2001 26-02-2002 03-02-2004
WO 2006068141	A	29-06-2006		EP 1830415 A1 KR 20070101856 A TW 287306 B US 2008106186 A1		05-09-2007 17-10-2007 21-09-2007 08-05-2008
EP 1830415	A	05-09-2007		WO 2006068141 A1 KR 20070101856 A TW 287306 B US 2008106186 A1		29-06-2006 17-10-2007 21-09-2007 08-05-2008
EP 1521235	A	06-04-2005		JP 2005115372 A US 2005073495 A1		28-04-2005 07-04-2005
US 2007013647	A1	18-01-2007		CN 1896586 A JP 2007027745 A KR 20070009149 A NL 2000141 A1		17-01-2007 01-02-2007 18-01-2007 16-01-2007

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- KR 200786197 [0001]
- KR 200822437 [0001]

专利名称(译)	使用白色发光二极管的表面光源和具有该表面光源的液晶显示器的背光单元		
公开(公告)号	EP2031437A1	公开(公告)日	2009-03-04
申请号	EP2008251483	申请日	2008-04-22
[标]申请(专利权)人(译)	三星电机株式会社		
申请(专利权)人(译)	三星机电股份有限公司.		
当前申请(专利权)人(译)	三星机电股份有限公司.		
[标]发明人	SHIN CHANG HO CHO DONG HYUN YOO CHUL HEE KIM DAE YEON KIM HYUNG SUK HAHM HUN JOO SHIN JAE HONG		
发明人	SHIN, CHANG HO CHO, DONG HYUN YOO, CHUL HEE KIM, DAE YEON KIM, HYUNG SUK HAHM, HUN JOO SHIN, JAE HONG		
IPC分类号	G02F1/13357 G09G3/34 F21V9/40 H01L33/50 H01L33/60		
CPC分类号	G02F1/133603 G02F1/133606 G02F1/133611 G09G3/3413 G09G3/3426 G09G2320/0233		
优先权	1020070086197 2007-08-27 KR 1020080022437 2008-03-11 KR		
其他公开文献	EP2031437B1		
外部链接	Espacenet		

摘要(译)

提供一种使用白色发光二极管(110)的面光源(200)，包括：多个白色发光二极管(110)，彼此以预定距离(a，b，c)布置，其中白色发光二极管被布置成使得由每个白色发光二极管限定的发光二极管单元和设置在距每个白色发光二极管最近距离(U)的相应白色发光二极管具有中心光量范围相对于白色发光二极管的平均光量，鳟鱼为80%至120%。




FIG. 3