



US007671952B2

(12) **United States Patent**
Su et al.

(10) **Patent No.:** **US 7,671,952 B2**
(45) **Date of Patent:** **Mar. 2, 2010**

(54) **MULTI-DOMAIN VERTICAL ALIGNMENT
LIQUID CRYSTAL DISPLAY PANEL**

(75) Inventors: **Mu-Jen Su**, Hsin-Chu (TW);
Chih-Ming Chang, Hsin-Chu (TW)

(73) Assignee: **AU Optonics Corp.**, Hsin-Chu (TW)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 343 days.

(21) Appl. No.: **11/749,748**

(22) Filed: **May 16, 2007**

(65) **Prior Publication Data**

US 2008/0180607 A1 Jul. 31, 2008

(30) **Foreign Application Priority Data**

Jan. 29, 2007 (TW) 96103229 A

(51) **Int. Cl.**

G02F 1/1337 (2006.01)

G02F 1/1343 (2006.01)

G02F 1/1335 (2006.01)

(52) **U.S. Cl.** **349/129**; 349/144; 349/146;
349/106

(58) **Field of Classification Search** 349/129,
349/144, 146, 106
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,504,592 B1 * 1/2003 Takatori et al. 349/129

7,001,714 B2 * 2/2006 Takagi et al. 430/321
7,145,619 B2 * 12/2006 Sawasaki et al. 349/129
7,511,789 B2 * 3/2009 Inoue et al. 349/129
2001/0030726 A1 * 10/2001 Yoshida et al. 349/117

FOREIGN PATENT DOCUMENTS

CN	1385738 A	12/2002
CN	1244843 C	3/2006
CN	1818758 A	8/2006
JP	11-242211	9/1999
JP	2000-081622	3/2000
JP	2000-081623	3/2000
JP	2000-356775	12/2000
JP	2005-274668	10/2005

* cited by examiner


Primary Examiner—Mike Qi

(74) *Attorney, Agent, or Firm*—Winston Hsu

(57) **ABSTRACT**

A liquid crystal display panel is disclosed. The liquid crystal display panel includes a bottom substrate, a plurality of wires disposed on the bottom substrate, a plurality of pixel units electrically connected to the wires, a top substrate disposed opposite to the bottom substrate, a liquid crystal layer disposed between the top and bottom substrates, and at least one protrusion disposed on the top substrate corresponding to the wires formed between two adjacent pixel units. Each pixel unit includes a thin film transistor and a pixel electrode disposed on the bottom substrate. The pixel electrode is electrically connected to the thin film transistor, in which the pixel electrode has a plurality of main slits.

16 Claims, 16 Drawing Sheets






Fig. 1A Prior Art




Fig. 1B Prior Art




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15

1

MULTI-DOMAIN VERTICAL ALIGNMENT LIQUID CRYSTAL DISPLAY PANEL

BACKGROUND OF THE INVENTION

1. Field of the Invention

The invention relates to a liquid crystal display panel, and more particularly, to a multi-domain vertical alignment liquid crystal display panel.

2. Description of the Prior Art

Liquid crystal displays (LCDs) are commonly utilized in various electronic products including cell phones, PDAs, and notebook computers. As the market demand for flat display panels continues to increase, liquid crystal displays become popular due to the advantages such as thin and lightweight. In fact, liquid crystal displays are gradually replacing cathode ray tube (CRT) displays that had dominated the market for so many years. However, the viewing angle of a conventional liquid crystal display is not wide enough to ensure a high display quality, therefore, multi-domain vertical alignment (MVA) liquid crystal displays capable of orientating liquid crystals in various directions are proposed to improve the above problem.

Please refer to FIG. 1A. FIG. 1A illustrates a cross-sectional view of an MVA LCD panel 10 according to the prior art. As shown in FIG. 1A, the MVA LCD panel 10 includes a top substrate 12, a bottom substrate 14, a liquid crystal layer 16 composed of negative liquid crystals disposed between the top substrate 12 and the bottom substrate 14, a common electrode 18 disposed on the top substrate 12 opposite to the bottom substrate 14, a color filter 15 disposed between the top substrate 12 and the common electrode 18, a plurality of protrusions 22 disposed over the common electrode 18 opposite to the bottom substrate 14, and a plurality of thin film transistors and pixel electrodes 28 disposed on the bottom substrate 14.

Please refer to FIG. 1B. FIG. 1B illustrates a plan view of a pixel unit of a MVA LCD panel according to the prior art. As shown in FIG. 1B, the MVA LCD panel includes a plurality of pixel units (only a pixel unit 180 is shown in the figure) and a plurality of scan lines 182 and data lines 184 disposed surrounding the pixel units 180. Each of the pixel units 180 includes a pixel electrode 186 composed of indium tin oxide or indium zinc oxide and a switch element (not shown), and each pixel electrode 186 includes a plurality of main slits 190 and fine slits 192, and a plurality of protrusions 188 disposed respectively above the central region of the pixel electrode 186.

SUMMARY OF THE INVENTION

A liquid crystal display panel is disclosed. The liquid crystal display panel includes a bottom substrate, a plurality of wires disposed on the bottom substrate, a plurality of pixel units electrically connected to the wires, a top substrate disposed opposite to the bottom substrate, a liquid crystal layer disposed between the top and bottom substrates, and at least one protrusion disposed on the top substrate corresponding to the wires formed between two adjacent pixel units. Each pixel unit includes a thin film transistor and a pixel electrode disposed on the bottom substrate. The pixel electrode is electrically connected to the thin film transistor, in which the pixel electrode has a plurality of main slits.

It is an objective of the present invention to provide a multi-domain vertical alignment liquid crystal display panel

2

for improving the problem of poor liquid crystal arrangement or low aperture ratio caused by the increased number of protrusions.

Specifically, the protrusions of the present invention are disposed on the top substrate where correspond to the scan lines or the data lines, such that the quantity of protrusions can be reduced significantly while fabricating high resolution liquid crystal displays. Additionally, a plurality of main slits is formed in the pixel electrode and the quantity of protrusions is reduced to increase the aperture ratio of the display panel, increase the stability of the liquid crystal arrangement, reduce the opportunity of light leakage during dark state and increase the overall contrast.

These and other objectives of the present invention will no doubt become obvious to those of ordinary skill in the art after reading the following detailed description of the preferred embodiment that is illustrated in the various figures and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A illustrates a cross-sectional view of a MVA LCD panel according to the prior art.

FIG. 1B illustrates a plan view of a pixel unit of a MVA LCD panel according to the prior art.

FIG. 2 illustrates a plan view of a pixel unit of a MVA LCD panel according to the present invention.

FIG. 3 illustrates a cross-sectional view of a MVA LCD panel according to the first embodiment of the present invention.

FIG. 4 illustrates a plan view of a pixel unit of the MVA LCD panel according to the first embodiment of the present invention.

FIG. 5 illustrates a cross-sectional view taken along line AA' of FIG. 4.

FIG. 6 illustrates a cross-sectional view taken along line BB' of FIG. 4.

FIG. 7 illustrates a plan view of a pixel unit of the MVA LCD panel according to the second embodiment of the present invention.

FIG. 8 illustrates a plan view of a pixel unit of the MVA LCD panel according to the third embodiment of the present invention.

FIG. 9 illustrates a plan view of a pixel unit of the MVA LCD panel according to the fourth embodiment of the present invention.

FIG. 10 illustrates a plan view of a pixel unit of the MVA LCD panel according to the fifth embodiment of the present invention.

FIG. 11 illustrates a plan view of the pixel units of the MVA LCD panel according to the sixth embodiment of the present invention.

FIG. 12 illustrates a plan view of the pixel units of the MVA LCD panel according to the seventh embodiment of the present invention.

FIG. 13 illustrates a plan view of the pixel units of the MVA LCD panel according to the eighth embodiment of the present invention.

FIG. 14 illustrates a plan view of the pixel units of the MVA LCD panel according to the ninth embodiment of the present invention.

FIG. 15 illustrates a plan view of the pixel units of the MVA LCD panel according to the tenth embodiment of the present invention.

Please refer to FIG. 2. FIG. 2 illustrates a plan view of a pixel unit of a MVA LCD panel according to the present invention. As shown in FIG. 2, the MVA LCD panel includes a plurality of pixel units 20 and a plurality of scan lines 30 and data lines 32 disposed between the pixel units 20. Each pixel unit 20 includes a pixel electrode 28, in which the pixel electrode 28 is composed of indium tin oxide or indium zinc oxide. Each pixel electrode 28 has a plurality of main slits 24 and fine slits 26. A plurality of protrusions 22 is disposed on the top substrate where correspond to the central region of the pixel electrode 28 divided by the main slits 24. The pixel unit 20 is driven by a switch element 23 electrically connected to the scan lines 30, the data lines 32, and the pixel electrode 28, in which the switch element 23 is preferably a thin film transistor. Depending on the design of the product, the main slits 24 and the fine slits 26 can be formed in the pixel electrode 28 or extended to the edge of the pixel electrode 28.

Typically, the protrusions occupy a relatively large proportion of the liquid crystal display panel. Despite the development of small size display panels continues to move toward a direction of high resolution, the reduction of the size of the protrusions still remains a difficult task due to the fabrication limitation of the color filters.

The protrusions of conventional MVA LCD panels are typically positioned with respect to the central region of pixel unit to facilitate the arrangement of the liquid crystals. Nevertheless, as resolution increases (pixel size become smaller), protrusion size can not decrease synchronously. The density of protrusion in pixel increases and leads to low aperture ratio and low brightness. Moreover, uneven arrangement of the liquid crystals surrounding the protrusions also causes light leakage and lowering of contrast. Hence, how to effectively reduce the quantity of protrusions for reducing the problem of uneven liquid crystal arrangement and light leakage during dark state has become an important task.

First Embodiment

Please refer to FIG. 3. FIG. 3 illustrates a cross-sectional view of an MVA LCD panel 40 according to the first embodiment of the present invention. As shown in FIG. 3, the MVA LCD panel 40 includes a top substrate 42, a bottom substrate 44, a liquid crystal layer 46 disposed between the top substrate 42 and the bottom substrate 44, a common electrode 48 disposed on the top substrate 42, a color filter 45 disposed between the top substrate 42 and the common electrode 48, a plurality of protrusions 52 disposed on the common electrode 48, and a plurality of thin film transistors (not shown) and pixel electrodes 58 disposed on the bottom substrate 44. The liquid crystal layer 46 can be composed of negative or positive liquid crystals. Alternatively, the color filter 45 can be formed on the bottom substrate 44 to form a color filter on array substrate, which are all within the scope of the present invention.

Please refer to FIGS. 4-6. FIG. 4 illustrates a plan view of a pixel unit 60 of the MVA LCD panel according to the first embodiment of the present invention. FIG. 5 and FIG. 6 illustrate cross-sectional views respectively taken along line AA' and line BB' of FIG. 4. As shown in FIG. 4, the MVA LCD panel 40 includes a pixel unit 60, a plurality of scan lines 62 and data lines 64 disposed around the pixel unit 60, and a plurality of rectangular or circular protrusions 66 disposed on the top substrate where correspond to the overlapped region of the scan lines 62 and data lines 64. As shown in FIG. 5 and FIG. 6, a first dielectric 621 is disposed between the scan line

62 and the data line 64, and a second dielectric 622 is disposed on the first dielectric 621 and the data line 64. The protrusions 66 are positioned on the top substrate 42 corresponding to the overlapped region of the scan line 62 and data line 64.

Referring back to FIG. 4, the pixel unit 60 is driven by a switch element 63 electrically connected to the scan lines 62, the data lines 64, and the pixel electrode 68, in which the switch element 63 can be a thin film transistor. The pixel unit 60 includes a pixel electrode 68, in which the pixel electrode 68 is composed of indium tin oxide or indium zinc oxide. The pixel electrode 68 also has a plurality of main slits 70 and fine slits 72, in which the fine slits 72 are arranged in a radiating manner. Depending on the design of the product, the main slits 70 and the fine slits 72 can be formed in the pixel electrode 68 or extended to the edge of the pixel electrode 68. Additionally, the main slits 70 and the fine slits 72 can be arranged according to the manner disclosed in Taiwan Patent No. 95127983, which are all within the scope of the present invention.

Second Embodiment

Please refer to FIG. 7. FIG. 7 illustrates a plan view of a pixel unit 80 of the MVA LCD panel according to the second embodiment of the present invention. As shown in FIG. 7, the MVA LCD panel includes a pixel unit 80, a plurality of scan lines 82 and data lines 84 disposed around the pixel unit 80, and a plurality of protrusions 86 disposed on the top substrate where correspond to the scan lines 82 and data lines 84. The pixel unit 80 is driven by a switch element 83 electrically connected to the scan lines 82, the data lines 84, and the pixel electrode 88, in which the switch element 83 is preferably a thin film transistor.

The pixel unit 80 includes a pixel electrode 88 having a plurality of main slits 89. Depending on the design of the product, the main slits 89 can be formed in the pixel electrode 88 or extended to the edge of the pixel electrode 88. In contrast to the first embodiment, the left protrusions 86 of the second embodiment are positioned corresponding to the overlapped portion of the scan lines 82 and data lines 84, whereas the right protrusion 86 is disposed corresponding to the central region of the right data line 84.

Third Embodiment

Please refer to FIG. 8. FIG. 8 illustrates a plan view of a pixel unit 90 of the MVA LCD panel according to the third embodiment of the present invention. As shown in FIG. 8, the MVA LCD panel includes a pixel unit 90, a plurality of scan lines 92 and data lines 94 disposed around the pixel unit 90, and a plurality of protrusions 96 disposed on the top substrate where correspond to the scan lines 92 and data lines 94. The pixel unit 90 is driven by a switch element 93 electrically connected to the scan lines 92, the data lines 94, and the pixel electrode 98, in which the switch element 93 is preferably a thin film transistor.

The pixel unit 90 includes a pixel electrode 98 having a plurality of main slits 97 and fine slits 99. Depending on the design of the product, the main slits 97 and the fine slits 99 can be formed in the pixel electrode 98 or extended to the edge of the pixel electrode 98. Similar to the second embodiment of the present invention, the left protrusions 96 are disposed corresponding to the overlapped portion of the scan lines 92

5

and data lines **94**, and the right protrusion **96** is disposed corresponding to the central region of the right data line **94**.

Fourth Embodiment

Please refer to FIG. **9**. FIG. **9** illustrates a plan view of a pixel unit **100** of the MVA LCD panel according to the fourth embodiment of the present invention. As shown in FIG. **9**, the MVA LCD panel includes a pixel unit **100**, a plurality of scan lines **102** and data lines **104** disposed around the pixel unit **100**, and a plurality of protrusions **106** disposed on the top substrate where correspond to the scan lines **102** and data lines **104**. The pixel unit **100** is driven by a switch element **103** electrically connected to the scan lines **102**, the data lines **104**, and the pixel electrode **108**, in which the switch element is preferably a thin film transistor.

The pixel unit **100** includes a pixel electrode **108** having a plurality of main slits **107** and fine slits **109**. Depending on the design of the product, the main slits **107** and the fine slits **109** can be formed in the pixel electrode **108** or extended to the edge of the pixel electrode **108**. Similar to the first embodiment of the present invention, the protrusions **106** of the fourth embodiment are disposed corresponding to the overlapped portion of the scan lines **102** and data lines **104**.

Fifth Embodiment

Please refer to FIG. **10**. FIG. **10** illustrates a plan view of a pixel unit **110** of the MVA LCD panel according to the fifth embodiment of the present invention. As shown in FIG. **10**, the MVA LCD panel includes a pixel unit **110**, a plurality of scan lines **112** and data lines **114** disposed around the pixel unit **110**, and a plurality of protrusions **116** disposed on the top substrate where correspond to the scan lines **112**. The pixel unit **110** is driven by a switch element **113** electrically connected to the scan lines **112**, the data lines **114**, and the pixel electrode **118**, in which the switch element **113** is preferably a thin film transistor.

The pixel unit **110** includes a pixel electrode **118** having a plurality of main slits **117** and fine slits **119**. Depending on the design of the product, the main slits **117** and the fine slits **119** can be formed in the pixel electrode **118** or extended to the edge of the pixel electrode **118**. As shown in FIG. **10**, the protrusions **116** of the fifth embodiment are disposed corresponding to the center of each scan line **112**.

Sixth Embodiment

Please refer to FIG. **11**. FIG. **11** illustrates a plan view of the pixel units of the MVA LCD panel according to the sixth embodiment of the present invention. As shown in FIG. **11**, the MVA LCD panel includes four pixel units **120**, a plurality of scan lines **122** and data lines **124** disposed between the pixel units **120**, and a plurality of protrusions **126** disposed on the top substrate where correspond to the data lines **124**. The pixel units **120** are driven by a plurality of switch elements **123** electrically connected to the scan lines **122**, the data lines **124** and the pixel electrode **128**, in which the switch elements are preferably thin film transistors.

Each of the pixel units **120** includes a pixel electrode **128** having a plurality of fine slits **129**. Depending on the design of the product, the fine slits **129** can be formed in the pixel electrode **128** or extended to the edge of the pixel electrode **128**. As shown in FIG. **11**, the protrusions **126** of the sixth embodiment are disposed corresponding to the center of the data lines **124** between two adjacent pixel units **120**. Hence, a

6

protrusion **126** can be shared by every two adjacent pixel units **120** for increasing the usability of the pixels.

Seventh Embodiment

Please refer to FIG. **12**. FIG. **12** illustrates a plan view of the pixel units of the MVA LCD panel according to the seventh embodiment of the present invention. As shown in FIG. **12**, the MVA LCD panel includes four pixel units **130**, a plurality of scan lines **132** and data lines **134** disposed between the pixel units **130**, and a plurality of protrusions **136** disposed on the top substrate where correspond to the center of the data lines **134**. The pixel units **130** are driven by a plurality of switch elements **133** electrically connected to the scan lines **132**, the data lines **134**, and the pixel electrode **138**, in which the switch elements **133** are preferably thin film transistors.

Each of the pixel units **130** includes a pixel electrode **138** having a plurality of fine slits **139**. Depending on the design of the product, the fine slits **139** can be formed in the pixel electrode **138** or extended to the edge of the pixel electrode **138**. Similar to the sixth embodiment, the protrusions **136** are positioned corresponding to the center of the data lines **134** between two adjacent pixel units **130**. In addition to the fine slits **139**, the pixel electrode **138** of the seventh embodiment also includes a plurality of main slits **137** disposed in the central region of the pixel electrode **138**.

Eighth Embodiment

Please refer to FIG. **13**. FIG. **13** illustrates a plan view of the pixel units of the MVA LCD panel according to the eighth embodiment of the present invention. As shown in FIG. **13**, the MVA LCD panel includes four pixel units **140**, a plurality of scan lines **142** and data lines **144** disposed between the pixel units **140**, and a plurality of protrusions **146** disposed on the top substrate where correspond to the data lines **144**. The pixel units **140** are driven by a plurality of switch elements **143** electrically connected to the scan lines **142**, the data lines **144**, and the pixel electrode **148**, in which the switch elements **143** are preferably thin film transistors.

Each of the pixel units **140** includes a pixel electrode **148** having a plurality of fine slits **149**. Depending on the design of the product, the fine slits **149** can be formed in the pixel electrode **148** or extended to the edge of the pixel electrode **148**. In addition to the protrusions **146** disposed corresponding to the data lines **144**, the quantity of fine slits **149** of this embodiment is significantly higher than the one disclosed in the sixth embodiment. The protrusions **146** are disposed corresponding to the center of the data line **144**, in which a protrusion **146** can be shared by every two adjacent pixel units **140** for increasing the usability of the pixels.

Ninth Embodiment

Please refer to FIG. **14**. FIG. **14** illustrates a plan view of the pixel units of the MVA LCD panel according to the ninth embodiment of the present invention. As shown in FIG. **14**, the MVA LCD panel includes four pixel units **150**, a plurality of scan lines **152** and data lines **154** disposed between the pixel units **150**, and a plurality of protrusions **156** disposed on the top substrate where correspond to the data lines **154**. The pixel units **150** are driven by a plurality of switch elements **153** electrically connected to the scan lines **152**, the data lines **154**, and the pixel electrode **158**, in which the switch elements **153** are preferably thin film transistors.

Each of the pixel units **150** includes a pixel electrode **158** having a plurality of main slits **157**. Depending on the design of the product, the main slits **157** can be formed in the pixel electrode **158** or extended to the edge of the pixel electrode **158**. In contrast to the aforementioned embodiments, the protrusions **156** of the ninth embodiment are disposed according to a scattering manner corresponding to each of the data lines **154**, such that each of the pixel units **150** would have a pixel domain of four different directions. Additionally, the protrusions **156** are not disposed corresponding to the center of the pixel units **150**, but are disposed according to an alternating manner, which can be either regular or irregular.

Tenth Embodiment

Please refer to FIG. **15**. FIG. **15** illustrates a plan view of the pixel units of the MVA LCD panel according to the tenth embodiment of the present invention. As shown in FIG. **15**, the MVA LCD panel includes four pixel units **160**, a plurality of scan lines **162** and data lines **164** disposed between the pixel units **160**, and a plurality of protrusions **166** disposed on the top substrate where correspond to the data lines **164**. The pixel units **160** are driven by a plurality of switch elements **163** electrically connected to the scan lines **162**, the data lines **164**, and the pixel electrode **168**, in which the switch elements **163** are preferably thin film transistors.

Each of the pixel units **160** includes a pixel electrode **168** having a plurality of main slits **167** and fine slits **169**. Depending on the design of the product, the main slits **167** and the fine slits **169** can be formed in the pixel electrode **168** or extended to the edge of the pixel electrode **168**. In contrast to the ninth embodiment, the tenth embodiment not only places the protrusions **166** in an alternating manner corresponding to each data line **164**, but also includes a plurality of fine slits **169**. In this embodiment, a protrusion **166** can be shared by two adjacent pixel units **160** to increase the usability of the pixels.

In the aforementioned embodiments, the main slits and the fine slits are specifically formed in the pixel electrodes. However, depending on the design of the product, the main slits and the fine slits can be formed according to a fish-bone shape within the pixel electrode or extended to the edge of the pixel electrode, which are all within the scope of the present invention.

In contrast to the conventional MVA LCD panels of placing the protrusions in the relative central position of the pixel electrode, the present invention preferably places the protrusions on the top substrate where correspond to the scan lines or data lines formed between the pixel units. By having this design, the number of protrusions can be reduced significantly while fabricating display panels having much higher resolution. Additionally, a plurality of main slits and fine slits can also be formed in the pixel electrode and the number of protrusions can be reduced to increase the aperture of the display panel, increase the stability of the liquid crystal arrangement, reduce the phenomenon of light leakage and increase the overall contrast.

Those skilled in the art will readily observe that numerous modifications and alterations of the device and method may be made while retaining the teachings of the invention. Accordingly, the above disclosure should be construed as limited only by the metes and bounds of the appended claims.

What is claimed is:

1. A liquid crystal display panel, comprising:
a bottom substrate;

a plurality of wires disposed on the bottom substrate;
a plurality of pixel units electrically connected to the wires,
wherein each of the pixel units comprises:

a thin film transistor disposed on the bottom substrate;
and

a pixel electrode, having a plurality of main slits, disposed on the bottom substrate and electrically connected to the thin film transistor;

a top substrate disposed opposite to the bottom substrate;
a liquid crystal layer disposed between the top substrate and the bottom substrate; and

at least one protrusion disposed on the top substrate opposite to the surface of the bottom substrate and corresponding to the wires formed between two adjacent pixel units, wherein the liquid crystal layer is disposed between the protrusion and the wires.

2. The liquid crystal display panel of claim 1, further comprising a color filter disposed on the top substrate.

3. The liquid crystal display panel of claim 1, further comprising a color filter disposed on the bottom substrate.

4. The liquid crystal display panel of claim 1, wherein the pixel electrode further has a plurality of fine slits.

5. The liquid crystal display panel of claim 1, wherein the pixel electrode is comprised of indium tin oxide or indium zinc oxide.

6. The liquid crystal display panel of claim 1, wherein the protrusion is a rectangular shape or a circular shape.

7. The liquid crystal display panel of claim 1, wherein the wires comprise scan lines or data lines.

8. The liquid crystal display panel of claim 7, wherein the protrusion is disposed corresponding to the overlapped portion of the scan line and data line.

9. A liquid crystal display panel, comprising:

a first substrate and a second substrate opposite to the first substrate;

a liquid crystal layer disposed between the first substrate and the second substrate;

a plurality of pixel electrodes, having a plurality of main slits, disposed on the second substrate;

a plurality of wires disposed on the second substrate and between the pixel electrodes; and

at least one protrusion disposed on the first substrate and corresponding to the wires, wherein the liquid crystal layer is disposed between the protrusion and the wires.

10. The liquid crystal display panel of claim 9, wherein each of the pixel electrodes comprises a plurality of fine slits.

11. The liquid crystal display panel of claim 9, further comprising a common electrode disposed on the first substrate.

12. The liquid crystal display panel of claim 11, further comprising a plurality of color filters disposed between the first substrate and the common electrode.

13. The liquid crystal display panel of claim 9, wherein the pixel electrodes is comprised of indium tin oxide or indium zinc oxide.

14. The liquid crystal display panel of claim 9, wherein the protrusion is disposed corresponding to the overlapped portion of the wires.

15. The liquid crystal display panel of claim 9, wherein the protrusion is a rectangular shape or a circular shape.

16. The liquid crystal display panel of claim 9, wherein the protrusion is disposed corresponding to the wires other than the overlapped portion of the wires.

* * * * *

专利名称(译)	多域垂直对准液晶显示面板		
公开(公告)号	US7671952	公开(公告)日	2010-03-02
申请号	US11/749748	申请日	2007-05-16
[标]申请(专利权)人(译)	苏牧JEN 张之明		
申请(专利权)人(译)	苏牧仁 张之洞MING		
当前申请(专利权)人(译)	友达光电.		
[标]发明人	SU MU JEN CHANG CHIH MING		
发明人	SU, MU-JEN CHANG, CHIH-MING		
IPC分类号	G02F1/1337 G02F1/1335 G02F1/1343		
CPC分类号	G02F1/133707 G02F1/1393 G02F2001/134345		
代理机构(译)	HSU , WINSTON		
优先权	096103229 2007-01-29 TW		
其他公开文献	US20080180607A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种液晶显示面板。液晶显示面板包括底部基板，设置在底部基板上的多个导线，电连接到导线的多个像素单元，与底部基板相对设置的顶部基板，设置在顶部和底部之间的液晶层。底部基板和设置在顶部基板上的至少一个突起对应于在两个相邻像素单元之间形成的导线。每个像素单元包括薄膜晶体管和设置在底部基板上的像素电极。像素电极电连接到薄膜晶体管，其中像素电极具有多个主狭缝。

