



US008368866B2

(12) **United States Patent**
Lee et al.

(10) **Patent No.:** **US 8,368,866 B2**
(45) **Date of Patent:** **Feb. 5, 2013**

(54) **LIQUID CRYSTAL DISPLAY DEVICE
HAVING HEAT GENERATING ELECTRODE**

(75) Inventors: **Sun-Hwa Lee**, Gyeonggi-Do (KR);
Kyo-Seop Choo, Gyeonggi-Do (KR)

(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 889 days.

(21) Appl. No.: **11/166,917**

(22) Filed: **Jun. 27, 2005**

(65) **Prior Publication Data**

US 2006/0139501 A1 Jun. 29, 2006

(30) **Foreign Application Priority Data**

Dec. 29, 2004 (KR) 10-2004-0115619

(51) **Int. Cl.**

G02F 1/133	(2006.01)
G02F 1/1333	(2006.01)
G02F 1/1335	(2006.01)
G02F 1/1345	(2006.01)
H01L 29/04	(2006.01)
H01L 29/10	(2006.01)
H01L 31/00	(2006.01)
H01L 27/14	(2006.01)
H01L 29/15	(2006.01)
H01L 31/036	(2006.01)

(52) **U.S. Cl.** **349/161**; 349/21; 349/40; 349/58;
349/96; 349/110; 349/150; 349/162; 257/59;
257/72

(58) **Field of Classification Search** 349/21,
349/161, 40, 58, 96, 110, 111, 150, 162;
257/59, 72

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,584,461 A *	4/1986	Teshima et al.	219/209
5,150,231 A *	9/1992	Iwamoto et al.	349/60
5,694,147 A *	12/1997	Gaalema et al.	345/101
6,133,979 A *	10/2000	Komatsu et al.	349/161
7,265,809 B2 *	9/2007	Dunn et al.	349/161
2005/0073640 A1 *	4/2005	Dunn et al.	349/161

FOREIGN PATENT DOCUMENTS

JP 61020017 A * 1/1986

* cited by examiner

Primary Examiner — Mark Robinson

Assistant Examiner — Paisley L. Arendt

(74) *Attorney, Agent, or Firm* — McKenna, Long and
Aldridge, LLP.

(57) **ABSTRACT**

A liquid crystal display device includes first and second sub-
strates, liquid crystal molecules positioned between the first
and second substrates, a heat generating electrode for gener-
ating heat in response to a direct current being supplied to the
heating electrode, and a backlight unit for irradiating light
onto the first and second substrates.

15 Claims, 5 Drawing Sheets




FIG. 1
RELATED ART




FIG. 2
RELATED ART




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8



LIQUID CRYSTAL DISPLAY DEVICE HAVING HEAT GENERATING ELECTRODE

The present invention claims the benefit of Korean Patent Application No. 115619/2004 filed in Korea on Dec. 29, 2004, which is hereby incorporated by reference in its entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a display device, and particularly, to a liquid crystal display device.

2. Description of the Related Art

Recently, liquid crystal display (hereinafter, called "LCD") devices have better image quality due to the improvement of liquid crystal materials and the development of fine pixel processing techniques. Further, LCD devices are light, thin and have low power consumption. The range of applications for LCD devices is increasing. An LCD device includes a liquid crystal display (LCD) panel, a driving circuit unit for driving the LCD panel and a backlight unit for supplying light to the LCD panel. The LCD panel has liquid crystal cells arranged in a matrix format. More particularly, the LCD panel has liquid crystal cells between two glass substrates (i.e., upper and lower substrates). Each of the liquid crystal cells includes a switching device (i.e., TFT array) for switching signals supplied to the liquid crystal cells. A driving circuit unit is connected to a printed circuit board for driving the LCD panel. The LCD panel is mounted on a member together with the backlight unit, to thereby form an LCD device.

FIGS. 1 and 2 are plan views illustrating an LCD panel mounted on a member. More particularly, FIG. 1 is a plan view of the related art liquid crystal display device, and FIG. 2 is a cross-sectional view of the related art liquid crystal display device taken along line I-I'. As shown in FIG. 1, an LCD device 1 includes an LCD panel 10 and a backlight unit 15 disposed under the LCD panel 10 for supplying light to the LCD panel 10. Meanwhile, a driving circuit unit (not shown) for driving the LCD panel 10 is connected to one side of the LCD panel 10.

The LCD panel 10 and the backlight unit 15 are mounted on a mold frame 20. The LCD panel 10 and the backlight unit 15 are fixed to the mold frame 20 by a top case 19 compressing an edge of an upper surface of the LCD panel 10 and coupled with the side of the mold frame 20. A bottom cover 17 for supporting and protecting the mold frame 20 is provided under the mold frame 20.

The backlight unit 15 includes lamps for generating light. An optical sheet is positioned over the lamps for efficiently supplying the light generated from the lamps to the LCD panel 10. The optical sheet includes a light guide plate, a diffusion plate and prism sheets.

The LCD panel 10 is constructed by attaching a color filter substrate 10a to a thin film transistor substrate 10b with a cell gap therebetween. Liquid crystal molecules are positioned in the cell gap. Polarization plates 13a and 13b are attached to both surfaces of the LCD panel 10.

A color filter and a black matrix are formed on the color filter substrate 10a. A transparent electrode 11 is formed at the rear surface of the color filter substrate 10a. The transparent electrode 11 discharges static electricity that accumulates on the LCD panel 10 to the outside. The transparent electrode 11 is connected to the top case 19 and the bottom cover 17 by a conductive tape 18. Accordingly, the static electricity gener-

ated at the LCD panel 10 is supplied by the conductive tape 18 to the top case 19 and the bottom cover 17, which are grounded.

A common electrode and a pixel electrode for generating an in-plane field and driving liquid crystal molecules are formed on the thin film transistor substrate 10b. In the alternative, the common electrode may be formed on the color filter substrate 10a. In this case, the liquid crystal molecules are controlled by a vertical electric field generated between the pixel electrode and the common electrode. The LCD device displays an image by driving the liquid crystal molecules according to signals applied to the pixel electrodes.

In general, liquid crystal molecules can be driven within a temperature range of -20°C. to 60°C. Thus, when an LCD panel is used with a temperature outside of the temperature range of -20°C. to 60°C. , an image cannot be normally displayed. For example, if an LCD panel is used in as a display for an airplane, it may not be possible to normally display an image in an environment below -20°C.

When the LCD panel is driven in a low-temperature environment (below -20°C.), the movement of the liquid crystal molecules is slow and thus the screen can not be normally driven. However, after a certain period of time, normal driving is possible. This is because heat generated from the backlight is transmitted to the LCD panel, thereby increasing the temperature of the liquid crystal molecules. Accordingly, since a temperature range in which liquid crystal molecules can be driven is limited in the related art, an image can not normally be displayed in a very low temperature state, which is outside the normal temperature range for driving an LCD panel.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a liquid crystal display device that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

An object of the present invention is to provide a liquid crystal display device that can display an image at a low temperatures.

Another object of the present invention is to provide a liquid crystal display device having improved reliability at low temperatures.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described herein, there is provided a liquid crystal display device including first and second substrates, liquid crystal molecules positioned between the first and second substrates, a heat generating electrode for generating heat in response to a direct current being supplied to the heating electrode, and a backlight unit for irradiating light onto the first and second substrates.

In another aspect, a liquid crystal display device includes a liquid crystal display panel having first and second substrates facing each other and liquid crystal molecules positioned between the first and second substrates, a backlight disposed under the display panel for supplying light to the liquid crystal display panel, a mold frame for mounting and affixing the

liquid crystal display panel and the backlight, and a heat generating electrode for generating heat.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

In the drawings:

FIG. 1 is a plan view of the related art liquid crystal display device.

FIG. 2 is a cross-sectional view of the related art liquid crystal display device taken along line I-I'.

FIG. 3 is a cross-sectional view of a liquid crystal display device in accordance with an embodiment of the present invention;

FIG. 4 is a plan view of a unit pixel on the thin film transistor substrate of the liquid crystal display device in accordance with an embodiment of the present invention;

FIG. 5 is cross-sectional view taken along line II-II' of FIG. 4, including the color filter substrate;

FIG. 6 illustrates a first exemplary embodiment of a heat generating electrode in accordance with an embodiment present invention;

FIG. 7 illustrates a second exemplary embodiment of a heat generating electrode in accordance with an embodiment present invention; and

FIG. 8 illustrates a third exemplary embodiment of a heat generating electrode in accordance with an embodiment present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to a liquid crystal display (LCD) device of the present invention, examples of which are illustrated in the accompanying drawings, hereinafter.

FIG. 3 is a cross-sectional view of a liquid crystal display device in accordance with an embodiment of the present invention. FIG. 4 is a plan view of a unit pixel on the thin film transistor substrate of a liquid crystal display device in accordance with an embodiment of the present invention. FIG. 5 is cross-sectional view taken along line II-II' of FIG. 4, including the color filter substrate. FIG. 5 is a view schematically illustrating the rear of a second substrate including a heat generating electrode.

FIG. 3 is a cross-sectional view of a liquid crystal display device in accordance with an embodiment of the present invention. As shown in FIG. 3, an LCD device in accordance with an embodiment of the present invention includes an LCD panel having first and second substrates **100** and **200**, which are attached by a seal **350** to form a cell gap therebetween. A layer of liquid crystal molecules **300** is positioned in the cell gap between the first and second substrates **100** and **200**. A backlight unit **400** is installed under the second substrate **200** for supplying light to the first and second substrates **100** and **200**.

First and second polarization plates **110** and **310** are respectively attached to the rear and front surfaces of the first substrate **100** and the second substrate **200**. A heat generating

electrode **250** is interposed between the second substrate **200** and the second polarization plate **310**. The heat generating electrode **250** generates heat in response to a direct current supplied to the heat generating electrode. The temperature of the liquid crystal molecules **300** between the first and second substrates **100** and **200** is increased by the heat from the heat generating electrode.

Although not illustrated in FIG. 3, the backlight unit **400** includes lamps for generating light. Further, the backlight unit **400** can include an optical sheet for efficiently distributing the light generated from the lamps across the entire surface of the LCD panel. The optical sheet can include a light guide plate, a diffusion plate and prism sheets.

As shown in FIG. 3, the LCD panel (P) and the backlight unit **400** are mounted on a mold frame **500**. The LCD panel (P) and the backlight unit **400** are affixed to the mold frame **500** by a top case **510** compressing an edge of an upper surface of the second substrate **200** and coupled with the side of the mold frame **500**. A bottom cover (not illustrated) for supporting and protecting the mold frame **500** is provided under the mold frame **500**.

FIG. 4 is a plan view of a unit pixel on the thin film transistor substrate of the liquid crystal display device in accordance with an embodiment of the present invention. FIG. 5 is cross-sectional view taken along line II-II' of FIG. 4, including the color filter substrate. As shown in FIGS. 4 and 5, gate lines **101** arranged in a first direction and data lines **103** arranged in a second direction on the transparent substrate **100** cross each other to define pixel regions. A switching device **109** is formed adjacent to the crossing of a gate line **101** and a data line **103**. The switching device **109** can be a thin film transistor that includes a gate electrode **101a**, a semiconductor layer **105** formed on the gate electrode **101a**, and source/drain electrodes **102a** and **102b** disposed on the semiconductor layer **105** at a predetermined interval.

At least a common electrode **106** and a pixel electrode **107**, which generate an in-plane electric field, are formed in each of the pixels. In addition, a common line **104** for electrically connecting the common electrode **106** is arranged parallel to the gate line **101**, and a pixel electrode line **114** for electrically connecting the pixel electrode **107** is disposed on the common line **104**. The common line **104** and the pixel electrode line **114** have a gate insulation layer **108** interposed therebetween to form a storage capacitor (Cst). A passivation film **111** is formed over the pixel electrode **107** and the pixel electrode line **114**.

Although the common electrode **106** is formed on the first substrate **100**, and the pixel electrode **107** is formed on the gate insulation layer **108** in FIGS. 4 and 5, locations of the common electrode **106** and the pixel electrode **107** are not limited in embodiments of the present invention. The common electrode **106** and the pixel electrode **107** can be formed on the passivation film **111**. The common electrode **106** and the pixel electrode **107** may be formed of transparent conductive materials. In the alternative, the pixel electrode can be formed on the first substrate and the common electrode may be formed on the second substrate such that the liquid crystal molecules are driven by a vertical electric field generated between the pixel electrode and the common electrode.

A black matrix **221** for preventing light leakage between the pixels is formed on the second substrate **200**. A color filter **223** for providing color display capabilities is also formed on the second substrate **200**. Alignment layers **112** and **212** for determining an initial alignment direction of liquid crystal molecules are applied at facing surfaces of the first substrate **100** and the second substrate **200**.

The LCD panel controls light transmission by driving liquid crystal molecules **300** with an in-plane electric field generated by the pixel electrode **107** and the common electrode **106**. In the related art, an LCD device can only be reliably driven when temperatures external to the device are in a temperature range of -20°C . to 60°C . However, in embodiments of the present invention, an LCD device can be driven when external temperatures are below -20°C . by providing a heat generating electrode **250** that supplies heat to the liquid crystal molecules of the LCD device when a direct current is supplied to the heat generating electrode **250**.

Although not illustrated in the drawing, a heating pad for supplying a direct current to the heat generating electrode **250** is separately formed on the first substrate **100**. The heating pad can be formed together when forming a gate pad and a data pad (not illustrated). The heat generating electrode **250** and the heating pad can be connected to each other by a conductive tape formed of an Al material.

A driving circuit unit for driving the LCD panel is connected to one side of the LCD panel. The gate pad and the data pad formed at one side of the gate lines and the data lines of the first substrate are connected to the driving circuit unit. Accordingly, the heating pad can be formed together in the process of forming the gate pad and the data pad so as to be formed without a separate additional process.

When the LCD panel comes in contact with an electrified object from the outside, electrification of the color filter substrate affects an arrangement state of the liquid crystal molecules located under the color filter substrate (i.e., liquid crystal molecules in an upper portion of the liquid crystal layer), and image quality deteriorates because of the abnormal arrangement of the liquid crystal molecules. In the case of the common electrode being formed on the color filter substrate, the effects of static electricity are minimal. In the case of an in-plane switching mode in which the common electrode and the pixel electrode are formed on the same substrate, since no metal layer exists on the color filter substrate, the problem of static electricity generation is worse.

To prevent deterioration in image quality caused by static electricity in an in-plane switching mode LCD device, a transparent electrode is separately formed at the rear surface of the color filter substrate. In the embodiments of the present invention, the heat generating electrode **250** is formed in the same process step when forming the electrode for reducing the effect of static electricity. In other words, the heat generating electrode **250** can serve as the electrode to reduce the effect of static electricity. Thus, the heat generating electrode **250** is formed without a separate additional fabrication process. The heat generating electrode **250** prevents static electricity from accumulating on the LCD panel and simultaneously generates heat such that the heat generating electrode **250** serves as a heater for increasing the temperature of the liquid crystal molecules in the LCD panel.

On the other hand, an LCD device in which the common electrode and the pixel electrode are formed on different substrates, the heat generating electrode **250** is formed at the rear surface of the color filter substrate through a separate additional process. In the alternative, an additional heating electrode can also be formed at the rear surface of the color filter substrate. In either case, the heat generating electrode **250** may be formed of a transparent conductive material, such as ITO (indium tin oxide) or IZO (indium zinc oxide).

When a direct current is supplied to the heat generating electrode **250** through the heating pad, heat is generated as result of the sheet resistance of the heat generating electrode **250**. Thus, the temperature of the liquid crystal molecules increase because of the heat generated. Since the generated

heat is in proportion to the sheet resistance, the amount of generated heat can be controlled by changing an area or the thickness of the heat generating electrode **250**. The heat generating electrode **250** may be formed over the entire surface of the second substrate **200** or formed as a pattern on the second substrate **200**. In order to generate the same amount of heat, the thickness of the heat generating electrode **250** according to the above two cases are formed differently from each other.

FIGS. **6** to **8** illustrate additional exemplary embodiments of how a heat generating electrode can be formed on the second substrate. FIG. **6** illustrates a first exemplary embodiment of a heat generating electrode in accordance with the present invention. As shown in FIG. **6**, a heat generating electrode **250a** may be formed over the entire surface of the second substrate **200**. The color filter **220** and the black matrix **221** are formed at an opposite side to the heat generating electrode **250a**. The color filter regions **223** shown in FIG. **6** is a pixel region where an image is actually displayed.

The direct current is supplied to the heat generating electrode **250a** may interfere with the electric field generated between the pixel electrode and the common electrode. To minimize the deterioration of image quality that is caused by such interference, the heat generating electrode **250a** is implemented in a pattern form. FIG. **7** illustrates a second exemplary embodiment of a heat generating electrode in accordance with the present invention. As shown in FIG. **7**, a heat generating electrode **250b** may be formed in a pattern corresponding to the black matrix **221**. When the heat generating electrode **250b** is formed corresponding to the black matrix **221**, deterioration in image quality is reduced because the effect of the direct current upon the electric field between the pixel electrode and the common electrode is greatly reduced as compared to the prior embodiment shown in FIG. **6**.

FIG. **8** illustrates a third exemplary embodiment of a heat generating electrode in accordance with the present invention. The interference due to the direct current may be reduced by forming a heat generating electrode **250c** at a position corresponding to the pixel region, as shown in FIG. **8**. That is, portions of the heat generating electrode pattern **250c** that are not carrying the direct current of the heat generating electrode coincides with the pixel electrode. In other words, fingers extend over the pixel regions to conduct heat to the pixel regions from another portion of the heating electrode through which current passes. Accordingly, deterioration in image quality can be reduced as compared to the prior embodiment shown in FIG. **5** by forming the heat generating electrode **250c** in a pattern covering the pixel region to conduct heat to the pixel region without current passing through that portion of the pattern. However, a heat generating electrode in accordance with the present invention is not limited to a specific pattern but can be formed in any shape so long as the heat generating electrode can increase the temperature of liquid molecules to a temperature range in which the liquid crystal molecules can be reliably driven. As described in the examples above, to lessen an effect of a direct current, which is supplied to the heat generating electrode, the heat generating electrode may be designed to have appropriate pattern to prevent deterioration of image quality.

As described, the embodiments of present invention allow the display of an image in spite of a LCD device being in an environment in which the temperature is below -20°C . by increasing the temperature of the liquid crystal molecules with a heat generating electrode and thus being able to normally drive the liquid crystal molecules. The heat generating electrode can be formed without a separate additional fabri-

cation process. Further, the heat generating electrode can prevent the build up of static electricity in an in-plane switching mode LCD device.

A separate heat generating electrode can be formed at the rear surface of the color filter substrate. In this instance, the heat generating electrode may be formed over an entire surface of the color filter substrate or formed in a pattern. The heat generating electrode is not limited to any specific shape or pattern.

Embodiments of the present invention have a heat generating electrode for increasing the temperature of the liquid crystal molecules in a LCD device at low environmental temperatures where liquid crystal molecules typically cannot be driven. Embodiments of the present invention can be applied to all kinds of LCD devices and are not limited to IPS (in plane switching) and TN (twisted nematic) modes. Further, a heat generating electrode, which is formed at the rear of the color filter substrate, can be used in all types of LCD devices. As described above, according to embodiments of the present invention, since a heat generating electrode for increasing the temperature of liquid crystal molecules is additionally formed at the rear of the color filter substrate, an image can be displayed despite a low environmental temperature.

It will be apparent to those skilled in the art that various modifications and variations can be made in the liquid crystal display device of the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A liquid crystal display device comprising:

- a first substrate having a plurality of gate and data lines on a first side thereof to define a plurality of pixels and a plurality of gate and data pads connected to the respective gate and data lines, the pixel including an image displaying unit for displaying an image and an image non-displaying unit;
- a thin film transistor formed adjacent to a crossing of the gate line and the data line;
- a second substrate having a black matrix and a color filter on the first side thereof, the black matrix being disposed in a first region corresponding to the image non-displaying unit of the first substrate;
- a first polarization plate and a second polarization plate attached respectively to the first substrate and the second substrate;
- liquid crystal molecules positioned between the first and second substrates;
- a heat generating electrode for generating heat in response to a direct current being supplied to the heat generating electrode, the heat generating electrode being directly deposited in a second region corresponding to the black matrix on a second side of the second substrate opposing to the first side;
- a heating pad formed at the first side of the first substrate, the heating pad being electrically connected to the heat generating electrode at the second side of the second substrate for supplying the direct current to the heat generating electrode, wherein the heating pad is made of a same material as the gate and data pads;
- a conductive tape for connecting electrically the heating pad with the heat generating electrode and with a case enclosing the first and second substrates; and
- a backlight unit for irradiating light onto the first and second substrates,

wherein the heat generating electrode is disposed between the second substrate and the second polarization plate.

2. The device of claim 1, wherein the first substrate includes:

a pixel electrode and a common electrode for generating an in-plane field in the pixel.

3. The device of claim 2, wherein the heat generating electrode is grounded to discharge static electricity.

4. The device of claim 1, wherein the heat generating electrode is formed over an entire surface of the second substrate.

5. The device of claim 1, wherein the conductive tape is formed of an Al material.

6. The device of claim 1, wherein the heat generating electrode is formed of a transparent material.

7. The device of claim 6, wherein the transparent material is formed of one of indium tin oxide and indium zinc oxide.

8. The device of claim 1, further comprising:

a pixel electrode on the first substrate; and

a common electrode on the second substrate.

9. A liquid crystal display device comprising:

a liquid crystal display panel including a first substrate having a thin film transistor array and a plurality of gate and data pads to electrically connect the thin film transistor array with a driver and a second substrate having a color filter, the first substrate and the second substrate being facing each other and liquid crystal molecules being positioned between the first and second substrates;

a first polarization plate and a second polarization plate attached respectively to the first substrate and the second substrate;

a backlight disposed under the liquid crystal display panel for supplying light to the liquid crystal display panel;

a mold frame for mounting and affixing the liquid crystal display panel and the backlight;

a heat generating electrode for generating heat, the heat generating electrode being directly formed on a surface of the second substrate outside of the liquid crystal display panel;

a heating pad formed at a surface of the first substrate inside of the liquid crystal display panel, the heating pad being electrically connected to the heat generating electrode at the outside of the liquid crystal display panel for supplying a direct current to the heat generating electrode, wherein the heating pad is made of the same material as the gate and data pads; and

a conductive tape for connecting electrically the heating pad with the heat generating electrode and with a case enclosing the first and second substrates and the mold frame,

wherein the heat generating electrode is disposed between the second substrate and the second polarization plate.

10. The device of claim 9, wherein the second substrate includes:

a black matrix formed on the second substrate; and the color filter formed on the black matrix.

11. The device of claim 10, wherein the heat generating electrode is formed in a pattern at an outside surface of the second substrate corresponding to the black matrix.

12. The device of claim 9, further comprising:

a plurality of gate lines arranged in a first direction on the first substrate;

a plurality of data lines arranged perpendicular to the gate lines and defining a plurality of pixels; and

the heat generating electrode has a pattern form disposed in a direction of a long side of the pixels and covers a width of the pixels,

9

wherein the heat generating electrode has a pattern in which fingers extend over the pixels to conduct heat to the pixels from another portion of the heat generating electrode through which the direct current passes.

13. The device of claim **9**, wherein the heat generating electrode is formed over an entire surface of the second substrate.

10

14. The device of claim **9**, wherein the conductive tape is formed of an Al material.

15. The device of claim **9**, wherein the heat generating electrode is formed of one of indium tin oxide and indium zinc oxide.

* * * * *

专利名称(译)	具有发热电极的液晶显示装置		
公开(公告)号	US8368866	公开(公告)日	2013-02-05
申请号	US11/166917	申请日	2005-06-27
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG.PHILIPS LCD CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	LEE SUN HWA CHOO KYO SEOP		
发明人	LEE, SUN-HWA CHOO, KYO-SEOP		
IPC分类号	G02F1/133 G02F1/1335 G02F1/1345 H01L31/036 H01L29/15 H01L27/14 H01L31/00 H01L29/10 G02F1/1333 H01L29/04		
CPC分类号	G02F1/133382 G02F1/134363		
审查员(译)	ROBINSON , MARK		
优先权	1020040115619 2004-12-29 KR		
其他公开文献	US20060139501A1		
外部链接	Espacenet USPTO		

摘要(译)

一种液晶显示装置，包括第一和第二基板，位于第一和第二基板之间的液晶分子，用于响应于提供给加热电极的直流电产生热量的发热电极，以及用于将光照射到其上的背光单元第一和第二基板。

