



US007907243B2

(12) **United States Patent**
Wang

(10) **Patent No.:** **US 7,907,243 B2**
(45) **Date of Patent:** **Mar. 15, 2011**

(54) **TRANSFLECTIVE LIQUID CRYSTAL
DISPLAY PANEL**

(75) Inventor: **Ching-Yi Wang**, Hsinchu (TW)

(73) Assignee: **Au Optonics Corporation**, Hsinchu
(TW)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 17 days.

(21) Appl. No.: **12/406,934**

(22) Filed: **Mar. 18, 2009**

(65) **Prior Publication Data**

US 2009/0174850 A1 Jul. 9, 2009

Related U.S. Application Data

(63) Continuation of application No. 11/163,396, filed on
Oct. 17, 2005, now Pat. No. 7,576,816.

(30) **Foreign Application Priority Data**

Dec. 24, 2004 (TW) 93140408 A

(51) **Int. Cl.**

G02F 1/1333 (2006.01)

G02F 1/1335 (2006.01)

(52) **U.S. Cl.** 349/138; 349/114; 349/112

(58) **Field of Classification Search** 349/114,
349/138, 112, 122
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,067,797 A * 11/1991 Yokokura et al. 349/124
5,986,738 A * 11/1999 Tagusa et al. 349/138
6,707,521 B2 * 3/2004 Satake et al. 349/138
7,440,055 B2 * 10/2008 Nam et al. 349/114
2005/0083459 A1 * 4/2005 Ukawa et al. 349/114
* cited by examiner


Primary Examiner — W. Patty Chen

(74) *Attorney, Agent, or Firm* — Jianq Chyun IP Office

(57) **ABSTRACT**

A transflective pixel structure including a scan line, a data line, a thin film transistor, a pixel electrode and an organic material layer is provided. The scan line and the data line are disposed over a substrate. The thin film transistor is disposed over the substrate and electrically connected to the scan line and the data line. The pixel electrode is disposed over a substrate and is electrically connected to the thin film transistor. The pixel electrode has a reflective region and a transmissive region. The organic material layer covers both the thin film transistor and the pixel electrode. The organic material layer disposed correspondently above the transmissive region of the pixel electrode has a plurality of refracting patterns on its upper surface. The refracting patterns refract external light into the reflective region.

18 Claims, 6 Drawing Sheets






FIG. 1A




FIG. 1B




FIG. 1C

FIG. 1F




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4




FIG. 5

TRANSFLECTIVE LIQUID CRYSTAL DISPLAY PANEL

CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation application of and claims the priority benefit of a prior application Ser. No. 11/163,396, filed on Oct. 17, 2005, now pending. The prior application Ser. No. 11/163,396 claims the priority benefit of Taiwan application serial no. 93140408, filed on Dec. 24, 2004. The entirety of each of the above-mentioned patent applications is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention generally relates to a liquid crystal display (LCD) panel, a pixel structure and manufacturing process thereof, and more particularly, to a transfective LCD panel, a transfective pixel structure and manufacturing process thereof.

2. Description of Related Art

Due to rapid development of information industry, the application of display technology, especially for portable products, is striding forward to miniaturization, being thin and light, high brightness, low power wastage and high quality output of full color image etc.

In order to meet the requirements of the above mentioned portable products, a reflective LCD is provided in the prior art. The conventional reflective LCD panel uses electrical conductive materials having light beam reflectable character as the pixel electrode. The light reflection of the pixel from external light source is used as the light source for displaying images. The reflective LCD panel is not only taken as one of the most developing potential technologies, but also has been used for some massively-produced products. However, though the display device with the reflective LCD panel can display a clear image under ambient light condition, it is unable to output high quality images when the external light source is insufficient resulting in shortage of light source in the display device of the LCD. In other words, the recent conventional reflective LCD cannot effectively solve the problem that the performance of a display device is restricted by the brightness of the external environment.

In view of the above-mentioned situation, a transfective LCD panel, which integrates a reflective LCD panel with a transmissive LCD panel is provided. The transmissive LCD panel uses a transparent electrical conductive material as the pixel electrode of a pixel, such as indium tin oxide (ITO), and a backlight module is used to make light pass through the transparent pixel electrode for image display. In the transfective LCD panel, each pixel electrode comprises a reflective electrical conductive thin film and a transparent electrical conductive thin film. The display device adapted with this LCD panel outputs a good image when the external light is sufficient. Furthermore, the display device can also achieve a good image output effect when the external light source is insufficient through the backlight module of the display device. However, for the LCD, the light reflecting ratio of the pixel is in a direct proportion to the area of the reflective electrical conductive thin film. The area of the reflective electrical conductive thin film must be increased accordingly if the light reflecting ratio of the reflecting portion of the pixel is to be increased. As a result, the opening ratio of the transmissive portion of the pixel will be affected. If the opening ratio

of the transmissive portion of the pixel is not sufficient, in order to maintain image output quality, the brightness of the backlight source must be increased. Consequently, more power wastage is occurred.

SUMMARY OF THE INVENTION

An objective of the present invention is to provide a transfective pixel structure with high light reflecting ratio and a manufacturing process thereof.

Another objective of the present invention is to provide a transfective LCD panel with high brightness and low power wastage.

The present invention provides a transfective pixel structure, which comprises a scan line, a data line, a thin film transistor, a pixel electrode and an organic material layer. The scan line and the data line are disposed over a substrate. The thin film transistor is disposed over the substrate and is electrically connected to the scan line and data line. The pixel electrode is disposed over the substrate and is electrically connected to the thin film transistor, and the pixel electrode comprises a reflective region and a transmissive region. The organic material layer covers the thin film transistor and the pixel electrode, wherein the organic material layer disposed over the transmissive region of the pixel electrode comprises a plurality of refracting patterns on its upper surface, and the refracting patterns refract external light into the reflective region.

In accordance with the transfective pixel structure described in the preferred embodiments of the present invention, wherein the thickness of the organic material layer is, for example, between 500 angstroms to 30000 angstroms.

In accordance with the transfective pixel structure described in the preferred embodiments of the present invention, wherein the refracting patterns are concave patterns, convex patterns or a combination thereof.

In accordance with the transfective pixel structure described in the preferred embodiments of the present invention, wherein the concave patterns comprise, for example, a plurality of round recessions with a diameter, for example, between 2 μm to 10 μm .

In accordance with the transfective pixel structure described in the preferred embodiments of the present invention, wherein the transfective pixel structure, for example, further comprises a refracting material layer which covers conformably on the upper surface of the organic material layer over the transmissive region of the pixel electrode. The thickness of the organic material layer is, for example, between 20000 angstroms to 25000 angstroms, and the refracting material layer comprises, for example, crystallized silicon.

In accordance with the transfective pixel structure in the preferred embodiments of the present invention, wherein the transfective pixel structure further comprises a plurality of bumps disposed correspondingly underneath the reflective region of the pixel electrode, and the reflective region of the pixel electrode comprises, for example, a metal material.

In accordance with the transfective pixel structure in the preferred embodiments of the present invention, wherein the transmissive region of the pixel electrode comprises, for example, a metal oxide material.

The present invention provides a transfective LCD panel comprising a first substrate, a second substrate and a liquid crystal layer. The second substrate comprises at least one electrode film thereon, and the liquid crystal layer is disposed between the first substrate and the second substrate. The first substrate comprises a plurality of scan lines, a plurality of

data lines, a plurality of thin film transistors, a plurality of pixel electrodes and an organic material layer. The scan lines and the data lines define a plurality of pixel regions. Each thin film transistor is disposed in each of the pixel regions, and each thin film transistor is electrically connected to one of the scan lines and one of the data lines correspondingly. The pixel electrodes are respectively disposed in each of the pixel regions and electrically connected to each of the thin film transistors. In particular, each pixel electrode comprises a reflective region and a transmissive region.

In accordance with the transfective LCD panel in the preferred embodiments of the present invention, wherein the thickness of the organic material layer is for example between 500 angstroms and 30000 angstroms, and the refracting patterns which are formed on the upper surface of the organic material layer are concave patterns, convex patterns or a combination thereof, and the refracting patterns refract external light into the reflective region.

In accordance with the transfective LCD panel in the preferred embodiments of the present invention, wherein the concave patterns can be, for example, a plurality of round recessions with a diameter, for example, between 2 μm to 10 μm .

In accordance with the transfective LCD panel in the preferred embodiments of the present invention, further comprising a refracting material layer which covers conformably on the upper surface of the organic material layer over the transmissive region of the pixel electrode. The thickness of the organic material layer is, for example, between 20000 angstroms to 25000 angstroms, and the refracting material layer comprises, for example, crystallized silicon.

In accordance with the transfective LCD panel in the preferred embodiments of the present invention, further including a plurality of bumps disposed underneath the reflective region of the pixel electrode, and the reflective region of the pixel electrode comprises, for example, a metal material.

In accordance with the transfective LCD panel in the preferred embodiments of the present invention, wherein the transmissive region of the pixel electrode comprises, for example, a metal oxide material.

In accordance with the transfective LCD panel in the preferred embodiments of the present invention, wherein the second substrate further comprises a color filter layer thereon.

The present invention provides a manufacturing process of a pixel structure. First, a scan line and a gate are formed on a substrate. Then a gate insulating layer is formed on the substrate to cover the scan line and the gate. A channel layer is formed on the gate insulating layer over the gate. A source and a drain are formed on the channel layer, and a data line is also formed and electrically connected to the source. Further, a pixel electrode is formed over the substrate which is electrically connected to the drain, and the pixel electrode comprises a reflective region and a transmissive region. Furthermore, an organic material layer is formed over the substrate to cover the pixel electrode and the thin film transistor. A plurality of refracting patterns is formed on the upper surface of the organic material layer over transmissive region of the pixel electrode.

In accordance with the manufacturing process described in the preferred embodiments of the present invention, wherein the refracting pattern is selected from a concave pattern, a convex pattern or a combination thereof.

In accordance with the manufacturing process in the preferred embodiments of the present invention, further comprising forming a refracting material layer conformably on the upper surface of the organic material layer over the trans-

missive region of the pixel electrode after forming the refracting patterns on the upper surface of the organic material layer.

In accordance with the manufacturing process in the preferred embodiments of the present invention, wherein the refracting patterns on the upper surface of the organic material layer are formed by a photolithography process.

Since the refracting patterns are formed on the upper surface of the organic material layer over the transmissive region of the pixel electrode, the external light which originally emits to the transmissive region but was unable are utilized by the reflective region because the external light originally unable can be refracted by the refracting patterns and emits into the reflective region so as to increase the light reflecting ratio of the reflective region of the pixel electrode. Besides, if the refracting material layer is formed on the organic material layer, the light refracting effect is further improved so as to further increase the light reflecting ratio of the reflective region of the pixel electrode. Since the above mentioned refracting pattern design is used in the LCD panel of the present invention, the effect of the light reflecting ratio of the reflective region of the pixel electrode can be increased and the LCD panel brightness can be therefore increased.

The above is a brief description of some deficiencies in the prior art and advantages of the present invention. Other features, advantages and embodiments of the invention will be apparent to those skilled in the art from the following description, accompanying drawings and appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A to FIG. 1F are drawings schematically showing cross-sectional views of a manufacturing process flow of a transfective pixel structure according to a first embodiment of the present invention.

FIG. 2 is a drawing schematically showing a top view of a transfective pixel structure according to the first embodiment of the present invention.

FIG. 3A to FIG. 3D are drawings schematically showing cross-sectional views of a manufacturing process flow of a transfective pixel structure according to a second embodiment of the present invention.

FIG. 4 is a drawing schematically showing a view of a transfective LCD panel according to an embodiment of the present invention.

FIG. 5 is a drawing schematically showing a top view of the first substrate according to FIG. 4.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

First Embodiment

FIG. 1A to FIG. 1F are drawings schematically showing cross-sectional views of a manufacturing process flow of a transfective pixel structure according to a first embodiment of the present invention. FIG. 2 is a drawing schematically showing a top view of a transfective pixel structure according to the first embodiment of the present invention. As shown in FIG. 1A and FIG. 2, a scan line 190 and a gate 120 are formed on a substrate 110. The substrate 110 is for example a glass substrate, a plastic substrate or other suitable substrates. The scan line 190 and the gate 120 are, for example, made of chromium, tantalum or other metal materials. A gate insulating layer 130 is formed to cover the scan line 190 and the gate 120. The gate insulating layer 130 is, for example, a silicon oxide layer, a silicon nitride layer or other dielectric layers. Furthermore, a channel layer 140 is formed on the gate insu-

lating layer **130**, wherein the channel layer **140** is made of, for example, amorphous silicon. In an embodiment of the present invention, an ohmic contact layer **142** may further be formed on the channel layer **140**. The ohmic contact layer **142** is, for example, an n-type doped amorphous silicon layer.

As shown in FIG. 1B, a source S and a drain D are formed on the channel layer **140**, and a data line **150** is also formed at the same time. The data line **150** is electrically connected to the source S. The source S, the drain D and the data line **150** are made of, for example, chromium, tantalum or other metal materials. After forming the source S and the drain D, a portion of the ohmic contact layer **142**, which is not covered by the source S and the drain D, is removed by utilizing the source S and the drain D as an etching mask (In general, it is called "back channel etching"). A thin film transistor **200** is accordingly formed.

As shown in FIG. 1C, after the thin film transistor **200** has been formed, a protective layer **160** is formed over the substrate **110**. Further, an opening **162** is formed in the protective layer **160** for exposing the drain D.

As shown in FIG. 1D, a pixel electrode **170** is formed on the protective layer **160**, and the pixel electrode **170** is electrically connected to the drain D. In the embodiment of the present invention, the pixel electrode **170** is electrically connected to the drain D through the opening **162**. Further, the pixel electrode **170** has two parts, a reflective region **170a** and a transmissive region **170b**. The material of the reflective region **170a** can be, for example, aluminum or other metal materials having reflecting character, and the material of the transmissive region **170b** can be, for example, indium tin oxide (ITO) or indium zinc oxide (IZO). In FIG. 2 of the embodiment of the present invention, the transmissive region **170b** is disposed at the center of the pixel region **172** and the reflective region **170a** is disposed in the surrounding area of the transmissive region **170b**. It is to be understood that the illustrated embodiment herein should not be treated as limitation thereof. In the present invention, the reflective region **170a** and the transmissive region **170b** of the pixel electrode **170** can be arranged in any manner.

Referring to FIG. 1E, an organic material layer **180** is formed over the substrate **110** to cover the pixel electrode **170** and the thin film transistor **200**. The organic material layer **180** can be, for example, a photoresist material with a thickness, for example, approximately between 500 angstroms and 30000 angstroms. The method of forming the organic material layer **180**, for example, is to prepare a photoresist material solution first. Then, the solution is, for example, spin coated on the pixel electrode **170** and the thin film transistor **200**, and a baking process is performed so that the pixel electrode **170** and the thin film transistor **200** are covered by the organic material layer **180**. Next, a photolithography process is performed to form several refracting patterns **182** on an upper surface of the organic material layer **180** over the transmissive region **170b** of the pixel electrode **170**. Thus, a transfective pixel structure **100** is formed. The refractive patterns **182** can be concave patterns, convex patterns or a combination thereof. In the embodiment of the present invention, the refractive patterns **182** are, for example, round recessions or similar patterns, and the diameter of the round recessions is between 2 μm and 10 μm . In another embodiment of the present invention as shown in FIG. 1F, after the refracting patterns **182** are formed, a refracting material layer **184** can be further formed conformably on the organic material layer **180** over the transmissive region **170b** of the pixel electrode **170**, wherein the refracting material layer **184** comprises, for example, crystallized silicon. If the refracting material layer **184** is further formed on the organic material layer **180**, the

suitable thickness of the organic material layer **180** is between 20000 angstroms and 25000 angstroms.

In accordance with FIG. 1E and FIG. 2, the transfective pixel structure **100**, which is formed by the above-mentioned manufacturing process, comprises a scan line **190**, a data line **150**, a thin film transistor **200**, a pixel electrode **170** and an organic material layer **180**. The scan line **190** and the data line **150** are disposed over the substrate **100**. A pixel region **172** is defined by the scan line **190**, a next scan line (not shown), the data line **150** and a next data line (not shown). The thin film transistor **200** is disposed in the pixel region **172** and is electrically connected to the scan line **190** and the data line **150**. The pixel electrode **170** is disposed in the pixel region **172** and is electrically connected to the thin film transistor **200**. The pixel electrode **170** further comprises a refractive region **170a** and a transmissive region **170b**. The organic material layer **180** covers the thin film transistor **200** and the pixel electrode **170**, and comprises refractive patterns **182** on the upper surface of the organic material layer **180** over the transmissive region **170b** of the pixel electrode **170**.

Further, according to FIG. 1E and FIG. 2, when external light **10** is radiated onto the reflective region **170a** of the pixel electrode **170** through the organic material layer **180**, the external light **10** is reflected from the reflective region **170a** and becomes the light source for display. When external light **12** is radiated onto the refracting patterns **182** on the organic material layer **180**, the external light **12** can be refracted onto the reflective region **170a**, and through reflection, becomes one of the light sources for display. Furthermore, in another embodiment of the present invention as shown in FIG. 1F, the refracting material layer **184** covers conformably the surface of the organic material layer **180** over the transmissive region **170b** of the pixel electrode **170** for increasing the effect of the light refract into the reflective region **170a**.

As described, the transfective pixel structure of the embodiment of the present invention, through the refracting patterns on the organic material layer or with an additional design of the refracting material layer on the organic material layer can refract external light, such as the light **12**, which originally emitted to the transmissive region but was unable, into the reflective region as a light source for display. Hence, the reflecting ratio of the pixel electrode is increased.

Second Embodiment

FIG. 3A to FIG. 3D are drawings schematically showing cross-sectional views of a manufacturing process flow of a transfective pixel structure according to a second embodiment of the present invention. Since the embodiment is similar with the first embodiment, the references in the first embodiment are used in the embodiment. Referring to FIG. 3A, first, the manufacturing process steps mentioned in the first embodiment shown as FIG. 1A to FIG. 1B are performed. Further, a protective layer **160** is formed over the substrate **110**. Then, a plurality of bumps **164** is formed on the protective layer **160** that a reflective region of the pixel electrode will be formed subsequently. The bumps **164** are made of, for example, organic resin or other organic material. The method for forming the bumps **164** is that, for example, an organic material (not shown) is formed on the above-mentioned structure, and then a photolithography process is performed to form the bumps **164**.

Referring to FIG. 3B, a pixel electrode **170** is formed on the protective layer **160** and covers the bumps **164**, and the pixel electrode **170** is electrically connected to the drain D. The pixel electrode **170** has two parts, a reflective region **170a** and a transmissive region **170b**. The reflective region **170a** of the

pixel electrode **170** is formed in the region that the bumps **164** have been formed correspondingly.

According to FIG. 3C, an organic material layer **180** is formed over the substrate **110** and covers the pixel electrode **170** and the thin film transistor **200**. The material and forming process of the organic material layer **180** are the same or similar as in the first embodiment. After the organic material layer **180** covering the pixel electrode **170** and the thin film transistor **200** is formed, the refracting patterns **182** are formed on the upper surface of the organic material layer **180** over the transmissive region **170b** of the pixel electrode **170**. A transfective pixel structure **100** is therefore formed. In another embodiment of the present invention as shown in FIG. 3D, after the refracting pattern **182** has been formed, a refracting material layer **184** can be further formed conformably on the organic material layer **180** over the transmissive region **170b** of the pixel electrode **170**. The refracting material layer **184** comprises, for example, crystallized silicon.

According to the above mentioned, owing to the design of the bumps **164** of the embodiment in the present invention, the surface of the reflective region **170a** of the pixel electrode **170** is a curving surface with rise and fall. Therefore, the light reflecting effect of the reflective region **170a** can be increased and the light reflecting ratio of the reflective region **170a** can also be improved.

FIG. 4 is a drawing schematically showing a view of a LCD panel with the transfective pixel structure according to an embodiment of the present invention. As shown in FIG. 4, the transfective LCD panel **600** comprises a first substrate **300**, a second substrate **400** and a liquid crystal layer **500**. The second substrate **400** comprises at least an electrode film **410** thereon, and the liquid crystal layer **500** is formed the first substrate **300** and the second substrate **400**, and the first substrate **300** and the second substrate **400** are sealed by a sealant **450**.

FIG. 5 is a drawing schematically showing a top view of the first substrate **300** according to FIG. 4. Since the manufacturing process of the first substrate **300** is similar with that of the first embodiment or of the second embodiment, the same references as indicated in the first embodiment or the second embodiment are used in the embodiment. As shown in FIG. 5, the first substrate **300** comprises a plurality of pixel structures, and each pixel structure is as shown in FIG. 1E or FIG. 1F of the first embodiment, or FIG. 3C or FIG. 3D of the second embodiment. Further, the second substrate **400**, in addition to comprising the electrode film **410**, may further comprise a color filter layer **420**, for example.

As mentioned, each pixel structure of the transfective LCD panel of the present invention comprises the character of the transfective pixel structure mentioned in the first embodiment or the second embodiment, i.e. utilizing the refracting patterns on the organic material layer or with the additional refracting material layer to increase the reflecting ratio of the reflective region of the pixel electrode, and thus the transfective LCD panel of the present invention has advantages of high brightness and low power wastage.

In summary of the above mentioned, the transfective pixel structure of the present invention adds an organic material layer having the refracting patterns in the manufacturing process. Through the refracting patterns of the organic material layer or the design of the refracting patterns and the refracting material layer, the lights emits to the transmissive region, that were originally unable, can now be refracted into the reflective region to be utilized. Hence, the light reflecting ratio of the pixel electrode can be increased. Besides, by utilizing the bumps disposed underneath the reflective region of the pixel electrode, the light reflecting ratio of the transfective pixel

structure is further increased. Application of the transfective pixel structure to the transfective LCD panel will improve the brightness and reduce power wastage.

The above description provides a full and complete description of the preferred embodiments of the present invention. Various modifications, alternate construction, and equivalent may be made by those skilled in the art without changing the scope or spirit of the invention. Accordingly, the above description and illustrations should not be construed as limiting the scope of the invention which is defined by the following claims.

What is claimed is:

1. A transfective pixel structure, comprising:

a scan line and a data line disposed over a substrate;

a thin film transistor disposed over a substrate, wherein the thin film transistor is electrically connected to the scan line and the data line;

a pixel electrode disposed over a substrate, wherein the pixel electrode is electrically connected to the thin film transistor, and the pixel electrode comprises a reflective region and a transmissive region;

an organic material layer covering the thin film transistor and the pixel electrode, wherein the organic material layer comprises a plurality of refracting patterns on an upper surface of the organic material layer over the transmissive region of the pixel electrode, and the refracting patterns refract external light into the reflective region; and

a refracting material layer which covers conformably on the upper surface of the organic material layer over the transmissive region of the pixel electrode.

2. The transfective pixel structure of claim 1, wherein the organic material layer has a thickness between 500 angstroms and 30000 angstroms.

3. The transfective pixel structure of claim 1, wherein the refracting patterns are concave patterns, convex patterns or a combination thereof.

4. The transfective pixel structure of claim 3, wherein the concave patterns formed on the upper surface of the organic material layer comprise a plurality of round recessions.

5. The transfective pixel structure of claim 4, wherein the round recessions have a diameter between 2 μm and 10 μm .

6. The transfective pixel structure of claim 1, wherein the organic material layer has a thickness between 20000 angstroms and 25000 angstroms.

7. The transfective pixel structure of claim 1, wherein the refracting material layer comprises crystallized silicon.

8. The transfective pixel structure of claim 1, further comprising a plurality of bumps disposed underneath the reflective region of the pixel electrode.

9. The transfective pixel structure of claim 1, wherein the reflective region of the pixel electrode comprises a metal material.

10. The transfective pixel structure of claim 1, wherein the transmissive region of the pixel electrode comprises a metal oxide material.

11. A transfective liquid crystal display panel, comprising: a first substrate, comprising:

a plurality of scan lines and a plurality of data lines to define a plurality of pixel regions;

a plurality of thin film transistors respectively disposed in each of the pixel regions, wherein each thin film transistor is electrically connected to one of the scan lines and one of the data lines correspondingly;

a plurality of pixel electrodes respectively disposed in each of the pixel regions, wherein each pixel electrode is electrically connected to one of the thin film transistors

9

correspondingly, and each pixel electrode comprises a reflective region and a transmissive region;
 an organic material layer, covering the thin film transistors and the pixel electrodes, wherein the organic material layer comprises a plurality of refracting patterns on its upper surface over the transmissive regions of the pixel electrodes, and the refracting patterns refract external light into the reflective region;
 a second substrate comprising an electrode film thereon;
 a liquid crystal layer disposed between the first substrate and the second substrate; and
 a refracting material layer which covers conformably on the upper surface of the organic material layer over the transmissive region of the pixel electrode.

12. The transflective liquid crystal display panel of claim **11**, wherein the refracting pattern are concave patterns, convex patterns or a combination thereof.

13. The transflective liquid crystal display panel of claim **11**, wherein the organic material layer has a thickness between 500 angstroms and 30000 angstroms.

10

14. The transflective liquid crystal display panel of claim **12**, wherein the concave patterns formed on the upper surface of the organic material layer comprises a plurality of round recessions.

15. The transflective liquid crystal display panel of claim **14**, wherein the round recessions has a diameter between 2 μm and 10 μm .

16. The transflective liquid crystal display panel of claim **11**, wherein the organic material layer has a thickness between 20000 angstroms and 25000 angstroms.

17. The transflective liquid crystal display panel of claim **11**, wherein the refracting material layer comprises crystallized silicon.

18. The transflective liquid crystal display panel of claim **11**, wherein the second substrate further comprises a color filter layer thereon.

* * * * *

专利名称(译)	透反液晶显示面板		
公开(公告)号	US7907243	公开(公告)日	2011-03-15
申请号	US12/406934	申请日	2009-03-18
[标]申请(专利权)人(译)	友达光电股份有限公司		
申请(专利权)人(译)	友达光电股份有限公司		
当前申请(专利权)人(译)	友达光电股份有限公司		
[标]发明人	WANG CHING YI		
发明人	WANG, CHING-YI		
IPC分类号	G02F1/1333 G02F1/1335		
CPC分类号	G02F1/133345 G02F1/133504 G02F1/133555 G02F1/1362 G02F2202/02 G02F2202/104		
优先权	093140408 2004-12-24 TW		
其他公开文献	US20090174850A1		
外部链接	Espacenet USPTO		

摘要(译)

提供一种透反像素结构，包括扫描线，数据线，薄膜晶体管，像素电极和有机材料层。扫描线和数据线设置在衬底上。薄膜晶体管设置在基板上方并电连接到扫描线和数据线。像素电极设置在基板上并电连接到薄膜晶体管。像素电极具有反射区域和透射区域。有机材料层覆盖薄膜晶体管和像素电极。相应地设置在像素电极的透射区域上方的有机材料层在其上表面上具有多个折射图案。折射图案将外部光折射到反射区域中。

