



(19) **United States**

(12) **Patent Application Publication**

(10) **Pub. No.: US 2004/0041970 A1**

Lee et al.

(43) **Pub. Date:**

Mar. 4, 2004

(54) **IN-PLANE SWITCHING MODE LIQUID CRYSTAL DISPLAY DEVICE AND METHOD OF FABRICATING THE SAME**

(30) **Foreign Application Priority Data**

Aug. 27, 2002 (KR)..... 50964/2002

(75) **Inventors: Joun-Ho Lee, Gyoungsangnam-Do (KR); Chung-Sun Lim, Seoul (KR)**

Publication Classification

(51) **Int. Cl.⁷ G02F 1/1343**

(52) **U.S. Cl. 349/141**

Correspondence Address:

**MORGAN LEWIS & BOCKIUS LLP
1111 PENNSYLVANIA AVENUE NW
WASHINGTON, DC 20004 (US)**

(57) **ABSTRACT**

An in-plane switching liquid crystal display device includes a first substrate and a second substrate, a gate line and a data line on the first substrate to define a pixel region, a floating line adjacent to a lower portion of the data line, a thin film transistor at an intersection between the gate and data lines, a passivation layer on the thin film transistor and the pixel region, a common electrode overlapping the data line, a pixel electrode separated from the common electrode at a predetermined interval, and a liquid crystal layer between the first and second substrates.

(73) **Assignee: LG.Philips LCD Co., Ltd.**

(21) **Appl. No.: 10/646,727**

(22) **Filed: Aug. 25, 2003**




FIG. 1
RELATED ART




FIG. 2
RELATED ART




FIG. 3
RELATED ART




FIG. 4
RELATED ART




FIG. 5




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D





FIG. 8E



IN-PLANE SWITCHING MODE LIQUID CRYSTAL DISPLAY DEVICE AND METHOD OF FABRICATING THE SAME

[0001] The present invention claims the benefit of Korean Patent Application No. 50964/2002 filed in Korea on Aug. 27, 2002, which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to a liquid crystal display device and a method of fabricating a liquid crystal display device, and more particularly, to an in-plane switching mode liquid crystal display device and a method of fabricating an in-plane switching mode liquid crystal display device.

[0004] 2. Description of the Related Art

[0005] In general, a liquid crystal display (LCD) device is capable of adjusting light transmission ratios of liquid crystal cells to display image data by individually supplying data signals corresponding to the image data to the liquid crystal cells. Accordingly, the LCD device includes a liquid crystal display panel in which liquid crystal cells are aligned in a matrix configuration and a driver integrated circuit (IC).

[0006] The liquid crystal display panel includes a color filter substrate and a thin film transistor (TFT) array substrate that oppose each other and a liquid crystal layer between the color filter substrate and the TFT array substrate. The TFT array substrate includes data lines for transmitting data signals supplied from a data driver IC to the liquid crystal cells and orthogonal gate lines for transmitting scan signals supplied from a gate driver IC, wherein the liquid crystal cells are defined at intersections of the data lines and gate lines. The gate driver IC sequentially supplies scan signals to the gate lines to sequentially select liquid crystal cells on a one by one basis. In addition, the data driver IC supplies data signals to the liquid crystal cells of selected gate lines.

[0007] Although twisted nematic mode LCD devices are commonly used as high definition display devices having low power consumption, they have a narrow viewing angle. This is due to refractive anisotropy of liquid crystal molecules, wherein the liquid crystal molecules aligned in parallel to the substrate are aligned almost vertically to the substrate when a voltage is supplied to the LCD panel. Accordingly, in-plane switching mode LCD devices have been developed to overcome this disadvantage.

[0008] Generally, the in-plane switching mode LCD devices include an upper substrate having color filters, a lower substrate having TFTs, a common electrode, pixel electrodes, and a liquid crystal layer formed between the upper and lower substrates.

[0009] FIG. 1 is a plan view of an in-plane switching mode liquid crystal display (LCD) device according to the related art. In FIG. 1, a pixel region is defined by arranging a plurality of gate lines 1 along a first direction and a plurality of data lines 2 along a second direction perpendicular to the first direction. In general, an N×M matrix of pixels are formed such that an N-number of gate lines 1 and an M-number of data lines 2 are provided on a substrate. A TFT composed of a gate electrode 5, a semiconductor layer

15, and source/drain electrodes 6a and 6b is disposed at each intersection between the gate and data lines 1 and 2, and a common line 3 is arranged in the pixel region approximately parallel to the gate line 1. In addition, pixel and common electrodes 8 and 9 are arranged in parallel to each other for switching the liquid crystal molecules of the LCD device. The pixel electrode 8 is connected to the drain electrode 6b of the TFT and the common electrode 9 is connected to the common line 3. Accordingly, a voltage is supplied through the TFT and a lateral electric field is generated between the pixel electrode 8 and the common electrode 9.

[0010] FIG. 2 is a cross sectional view along I-I' of FIG. 1 according to the related art. In FIG. 2, the LCD device includes a TFT substrate 10 having the TFT formed on a transparent substrate 7, the common electrode 9, and the pixel electrode 8, and a color filter substrate 20 having a light-shielding layer (i.e., black matrix) 21, a color filter 23, and an overcoat layer 25. In addition, a liquid crystal layer 30 is formed between the TFT substrate 10 and the color filter substrate 20, and a spacer 31 is positioned in the liquid crystal layer 30 to maintain a uniform cell gap between the TFT and color filter substrates 10 and 20.

[0011] The TFT includes a gate electrode 5, source/drain electrodes 6a and 6b, a semiconductor layer 15, and an ohmic contact layer 14. In addition, a gate insulating layer 11 is formed between the gate electrode 5 and the semiconductor layer 15.

[0012] Within the pixel region, the common electrode 9, which is formed together with the gate electrode 5 of the TFT, and a pixel electrode 8, which is formed together with the source/drain electrodes 6a and 6b, are formed at a predetermined interval, and a passivation layer 13 is formed over an entire surface of the TFT and an upper portion of the pixel region. However, since the pixel electrode 8 and the common electrode 9 are formed on the same substrate, an aperture ratio of the LCD device is degraded. For example, since the pixel electrode 8 and the common electrode 9 are made of opaque metal materials, light is not transmitted from a backlight device within a region where the pixel and common electrodes 8 and 9 are formed. Accordingly, an area of the opening portion is reduced by an area corresponding to the pixel and common electrodes 8 and 9. In order to solve the problem, the aperture ratio is improved by forming the common electrode 9 and the pixel electrode 8 of transparent materials.

[0013] FIG. 3 is a plan view of another in-plane switching mode liquid crystal display device according to the related art, and FIG. 4 is a cross sectional view along II-II' of FIG. 3 according to the related art. In FIGS. 3 and 4, an aperture ratio can be improved by forming pixel and common electrodes 18 and 19 positioned within a pixel region of transparent materials. In addition, a passivation layer 13 may be formed of organic materials having low dielectric constants between the data line 2 and the common electrode 19. Accordingly, the common electrode 19 is formed along a boundary of two adjacent pixel electrodes 18, such as an upper portion of the data line 2, and generates a lateral electric field (solid line) between the two adjacent pixel electrodes 18.

[0014] However, as shown in FIG. 4, the data line 2 positioned in a lower portion of the common electrode 19 generates another electric field (dotted line) with the pixel

electrode **18** that is adjacent to the common electrode **19**. Accordingly, the data line distorts the lateral electric field between the common electrode **19** and the pixel electrode **18**. Thus, light leaks along a marginal region of the pixel electrode **18** between the data line **2** and the adjacent pixel electrode **18**, thereby generating cross-talk on a display screen.

SUMMARY OF THE INVENTION

[**0015**] Accordingly, the present invention is directed to an in-plane switching mode liquid crystal display device and a method of fabricating an in-plane switching mode liquid crystal display device that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

[**0016**] An object of the present invention is to provide an in-plane switching liquid crystal display device capable of forming a uniform lateral electric field between a common electrode and a pixel electrode.

[**0017**] Another object of the present invention is to provide a method of fabricating an in-plane switching liquid crystal display device capable of forming a uniform lateral electric field between a common electrode and a pixel electrode.

[**0018**] Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

[**0019**] To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described herein, an in-plane switching liquid crystal display device includes a first substrate and a second substrate, a gate line and a data line on the first substrate to define a pixel region, a floating line adjacent to a lower portion of the data line, a thin film transistor at an intersection between the gate and data lines, a passivation layer on the thin film transistor and the pixel region, a common electrode overlapping the data line, a pixel electrode separated from the common electrode at a predetermined interval, and a liquid crystal layer between the first and second substrates.

[**0020**] In another aspect, an in-plane switching liquid crystal display device includes a first substrate and a second substrate, a gate line and a data line on the first substrate to define a pixel region, a common line parallel to the gate line, a floating line overlapping the data line and formed on a same plane as the gate line, a thin film transistor at an intersection between the gate and data lines, an organic passivation layer on the thin film transistor and the pixel region, a common electrode on the passivation layer overlapping the data line, a pixel electrode on the passivation layer to cross the common electrode, and a liquid crystal layer between the first and second substrates.

[**0021**] In another aspect, a method of fabricating an in-plane switching liquid crystal display device includes providing first and second substrates having pixel regions, forming a gate line and a floating line on a first substrate,

forming a data line to overlap the floating line, forming a thin film transistor at an intersection of the gate and data lines, forming a passivation layer on the thin film transistor and the pixel region, forming a common electrode to overlap the data line and a pixel electrode on the passivation layer, and forming a liquid crystal layer between the first and second substrates.

[**0022**] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

[**0023**] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention. In the drawings:

[**0024**] **FIG. 1** is a plan view of an in-plane switching mode liquid crystal display device according to the related art;

[**0025**] **FIG. 2** is a cross sectional view along I-I' of **FIG. 1** according to the related art;

[**0026**] **FIG. 3** is a plan view of another in-plane switching mode liquid crystal display device according to the related art;

[**0027**] **FIG. 4** is a cross sectional view along II-II' of **FIG. 3** according to the related art;

[**0028**] **FIG. 5** is a plan view of an exemplary in-plane switching mode liquid crystal display device according to the present invention;

[**0029**] **FIG. 6** is a cross sectional view along III-III' of **FIG. 5** according to the present invention;

[**0030**] **FIG. 7** is a cross sectional view another exemplary in-plane switching mode liquid crystal display device according to the present invention; and

[**0031**] **FIGS. 8A to 8E** are cross sectional views of an exemplary method of fabricating an in-plane switching mode liquid crystal display device according to the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

[**0032**] Reference will now be made in detail to the embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

[**0033**] **FIG. 5** is a plan view of an exemplary in-plane switching mode liquid crystal display device according to the present invention. In **FIG. 5**, an in-plane switching mode LCD device may include a plurality of pixel regions defined by a plurality of gate lines **101** arranged along a first direction, a plurality of data lines **102** arranged along a second direction perpendicular to the first direction, and a common line **103** disposed in parallel to the gate lines **101**.

[**0034**] In addition, one or more common electrodes **119** may be electrically connected to the common line **103** through a first contact hole **112a**. Accordingly, the common

electrode **119** may be formed to overlap the data line **102**, thereby generating a lateral electric field between two adjacent pixel electrodes **118**, which may be positioned at a predetermined interval from the common electrode **119**.

[0035] A thin film transistor composed of a gate electrode **105** that diverges from the gate line **101**, a source electrode **106a** that diverges from the data line **102**, a drain electrode **106b**, and a semiconductor layer **115** may be positioned at an intersection between the gate and data lines **101** and **102**, wherein the drain electrode **106b** may be connected with the pixel electrode **118** through a second contact hole **108a**. Accordingly, the pixel electrode **118** may be connected with source/drain electrode lines **112** that are formed to overlap the common line **103** through a third contact hole **118a**. Thus, the source/drain electrode line **112** and the common line **103**, which is formed at a lower portion thereof, may form a capacitor using a gate insulating layer (not shown) disposed therebetween.

[0036] A floating line **150** of two stems may be formed in the lower portion of the data line **102** on the gate insulating layer (not shown). The floating line **150** may be formed together with the gate line **101** in order to uniformly form a lateral electric field between pixel electrode **118** and the common electrode **119** that overlaps the data line **102**. Accordingly, a data signal passing through the data line **102** may be coupled with the pixel electrode **118** that is adjacent to the common electrode **119**. Thus, the floating line **150** can intercept the data signal to prevent any adverse effects.

[0037] FIG. 6 is a cross sectional view along III-III' of FIG. 5 according to the present invention. In FIG. 6, the floating line **150** and the data line **102** may be formed in parallel on a transparent substrate **107** over the gate insulating layer **111**, wherein the floating line **150** may prevent signals transmitted along the data line **102** from interfering with the pixel electrode **118** adjacent to the common electrode **119**, which is at an upper portion of the data line **102**. In addition, a passivation layer **113** may be disposed between the data line **102** and the common electrode **119**, wherein the passivation layer **113** may be formed of organic materials having low dielectric constants. The floating line **150** may be formed along an inner portion of the common electrode **119** to intercept the signals transmitted along the data line **102**.

[0038] The common electrode **119** and the pixel electrode **118**, which are formed on the passivation layer **113**, may be formed of transparent materials, such as indium tin oxide (ITO) or indium zinc oxide (IZO). In addition, the floating line **150** may be formed with gate electrode materials, and may be formed with two lines along both sides of a lower portion of the data line **102** to couple the signals transmitted along the data line **102**.

[0039] FIG. 7 is a cross sectional view another exemplary in-plane switching mode liquid crystal display device according to the present invention. In FIG. 7, a floating line **150** may be formed along a lower portion of a data line **102** and may be formed as a single conductive line. Accordingly, the signals transmitted along the data line **102** may be intercepted by increasing a width of the common electrode **119** that overlaps the data line **102** instead of forming the floating line **150**. In addition, the data line **102** may have a first width, the floating line may have a second width larger than the first width, and the common electrode **119** may have a third width larger than the first and second widths.

[0040] FIGS. 8A to 8E are cross sectional views of an exemplary method of fabricating an in-plane switching mode liquid crystal display device according to the present invention. In FIG. 8A, a metal material, such as Al, Mo, Ti, Cu, Ta, or an Al alloy, may be deposited onto a transparent substrate **107** using a sputtering method. Then, a gate electrode **105** of a TFT within a TFT region and a floating line **150** may be formed by patterning the metal material within data line region. Accordingly, a gate line **101** and the common line **103** may be formed simultaneously, as shown in FIG. 5.

[0041] In FIG. 8B, SiNx and/or SiOx may be deposited over the gate electrode **105** and an entire surface of the substrate **107** using a plasma chemical vapor deposition (CVD) method, thereby forming a gate insulating layer **111**. Then, a semiconductor layer **115** and an ohmic contact layer **114** may be formed by depositing and patterning amorphous silicon and n+ amorphous silicon formed over the gate insulating layer **111**.

[0042] In FIG. 8C, metal material(s), such as Al, Mo, Ti, Cu, Ta, or an Al alloy, may be deposited on the transparent substrate **107** using a sputtering method. Then, the metal material(s) may be patterned to form source/drain electrodes **106a** and **106b** of the TFT and a data line **102**. Next, the ohmic contact layer **114** formed between the source electrode **106a** and the drain electrode **106b** may be removed by using the source/drain electrodes **106a** and **106b** as masks, thereby exposing a portion of the semiconductor layer **115**.

[0043] In FIG. 8D, a passivation layer **113** may be formed by depositing organic material(s), such as benzocyclobutene (BCB) or acryl, over an entire surface of the upper portion of the gate insulating layer **111** of the source/drain electrodes **106a** and **106b** and the data line **102**.

[0044] FIG. 8E, indium tin oxide (ITO) and/or indium zinc oxide (IZO) may be deposited on the passivation layer **113** using a sputtering method. Then, a common electrode **119** connected to the common line and a pixel electrode **118** connected to the drain electrode **106b** of the TFT may be formed by patterning. Accordingly, the common electrode **119** and the pixel electrode **118** may be formed to cross each other at a predetermined interval, and the common electrode **119** may be formed to overlap the data line **102**. Then, a black matrix **121** and a color filter **123** may be formed on a transparent substrate **126**, and an over-coating layer **125** may be formed thereon and attached with the TFT substrate. Accordingly, the black matrix **121** may be formed within a region corresponding to the TFT, the gate line, and the data line **102** formed on the TFT substrate.

[0045] It will be apparent to those skilled in the art that various modifications and variations can be made in the in-plane switching mode liquid crystal display device and a method of fabricating an in-plane switching mode liquid crystal display device of the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. An in-plane switching liquid crystal display device, comprising:

- a first substrate and a second substrate;
- a gate line and a data line on the first substrate to define a pixel region;
- a floating line adjacent to a lower portion of the data line;
- a thin film transistor at an intersection between the gate and data lines;
- a passivation layer on the thin film transistor and the pixel region;
- a common electrode overlapping the data line;
- a pixel electrode separated from the common electrode at a predetermined interval; and
- a liquid crystal layer between the first and second substrates.

2. The device according to claim 1, wherein the thin film transistor includes:

- a gate electrode on the first substrate;
- a gate insulating layer on the gate electrode;
- a semiconductor layer on the gate insulating layer;
- an ohmic contact layer on the semiconductor layer; and
- source and drain electrodes on the ohmic contact layer.

3. The device according to claim 1, further comprising a common line positioned in parallel to the gate line.

4. The device according to claim 1, wherein the common electrode and the pixel electrode are formed on a same plane.

5. The device according to claim 1, wherein the common electrode and the pixel electrode are formed on the passivation layer.

6. The device according to claim 1, wherein the common electrode and the pixel electrode include transparent materials.

7. The device according to claim 6, wherein the transparent materials include at least one of indium tin oxide (ITO) and indium zinc oxide (IZO).

8. The device according to claim 1, wherein the passivation layer includes at least one of benzocyclobutene (BCB) and acryl.

9. The device according to claim 1, wherein the floating line includes at least two conductive lines.

10. The device according to claim 1, wherein the floating line includes a single conductive line.

11. The device according to claim 10, wherein a width of the floating line is larger than a width of the data line.

12. The device according to claim 11, wherein a width of the common electrode is larger than the width of the floating line.

13. The device according to claim 1, wherein the floating line and the gate line are simultaneously formed.

14. The device according to claim 1, further comprising a black matrix and a color filter on the second substrate.

15. An in-plane switching liquid crystal display device, comprising:

- a first substrate and a second substrate;
- a gate line and a data line on the first substrate to define a pixel region;
- a common line parallel to the gate line;
- a floating line overlapping the data line and formed on a same plane as the gate line;
- a thin film transistor at an intersection between the gate and data lines;
- an organic passivation layer on the thin film transistor and the pixel region;
- a common electrode on the passivation layer overlapping the data line;
- a pixel electrode on the passivation layer to cross the common electrode; and
- a liquid crystal layer between the first and second substrates.

16. A method of fabricating an in-plane switching liquid crystal display device, comprising:

- providing first and second substrates having pixel regions;
- forming a gate line and a floating line on the first substrate;
- forming a data line to overlap the floating line;
- forming a thin film transistor at an intersection of the gate and data lines;
- forming a passivation layer on the thin film transistor and the pixel regions;
- forming a common electrode to overlap the data line and a pixel electrode on the passivation layer; and
- forming a liquid crystal layer between the first and second substrates.

17. The method according to claim 16, wherein the forming of the thin film transistor includes:

- forming a gate electrode on the first substrate;
- forming a gate insulating layer on the gate electrode;
- forming an active layer on the gate insulating layer;
- forming an ohmic contact layer on the active layer to expose a center portion of the active layer; and
- forming source and drain electrodes on the ohmic contact layer.

18. The method according to claim 16, further comprising forming a black matrix and a color filter on the second substrate.

19. The method according to claim 16, wherein a width of the floating line is larger than a width of the data line.

20. The method according to claim 19, wherein a width of the common electrode is larger than the width of the floating line.

* * * * *

| | | | |
|----------------|---|---------|------------|
| 专利名称(译) | 面内切换模式液晶显示装置及其制造方法 | | |
| 公开(公告)号 | US20040041970A1 | 公开(公告)日 | 2004-03-04 |
| 申请号 | US10/646727 | 申请日 | 2003-08-25 |
| [标]申请(专利权)人(译) | 乐金显示有限公司 | | |
| 申请(专利权)人(译) | LG.PHILIPS LCD CO. , LTD. | | |
| 当前申请(专利权)人(译) | LG DISPLAY CO. , LTD. | | |
| [标]发明人 | LEE JOUN HO LIM CHUNG SUN | | |
| 发明人 | LEE, JOUN-HO LIM, CHUNG-SUN | | |
| IPC分类号 | G02F1/1343 G02F1/1362 | | |
| CPC分类号 | G02F1/136213 G02F1/134363 | | |
| 优先权 | 1020020050964 2002-08-27 KR | | |
| 其他公开文献 | US7061566 | | |
| 外部链接 | Espacenet USPTO | | |

摘要(译)

面内切换液晶显示装置包括第一基板和第二基板，栅极线和数据线在第一基板上以限定像素区域，浮置线与数据线的下部相邻，薄栅极和数据线交叉处的薄膜晶体管，薄膜晶体管和像素区域上的钝化层，与数据线重叠的公共电极，以预定间隔与公共电极隔开的像素电极，以及液晶第一和第二基板之间的层。

