



US 20050253985A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2005/0253985 A1****Ham et al.**(43) **Pub. Date: Nov. 17, 2005**(54) **LIQUID CRYSTAL DISPLAY DEVICE**(30) **Foreign Application Priority Data**(76) Inventors: **Yong Sung Ham**, Anyang-shi (KR);
Yun Bok Lee, Seoul (KR)

Aug. 28, 2002 (KR) 2002-51103

Publication Classification

Correspondence Address:

MCKENNA LONG & ALDRIDGE LLP**1900 K STREET, NW****WASHINGTON, DC 20006 (US)**(51) **Int. Cl.⁷** **G02F 1/1335**(52) **U.S. Cl.** **349/106**(21) Appl. No.: **11/185,875**(22) Filed: **Jul. 21, 2005****Related U.S. Application Data**

(62) Division of application No. 10/608,561, filed on Jun. 30, 2003, now Pat. No. 6,940,571.

(57) **ABSTRACT**

A liquid crystal display (LCD) device is disclosed, in which a hole or groove is formed at the same direction as the axis of polarization of first and second polarizers for improving the luminance, and an electric field inducing window or a dielectric protrusion is formed corresponding to the center of the hole or groove to stabilize the texture of liquid crystal layer.




FIG.1
Related Art




FIG.2
Related Art




FIG. 3
Related Art




FIG. 4
Related Art




FIG.5
Related Art




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 9C




FIG.10




FIG.11




FIG.12





FIG.13



LIQUID CRYSTAL DISPLAY DEVICE

[0001] This application claims the benefit of the Korean Application No. P2002-51103 filed on Aug. 28, 2002, which is hereby incorporated by reference for all purposes as if fully set forth herein.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to a liquid crystal display (LCD) device, and more particularly, to an LCD device for stabilizing a texture of liquid crystal molecules, and maximizing luminance.

[0004] 2. Discussion of the Related Art

[0005] In recent years, the development of information society increases demands for various display devices, so that many efforts have been made to research and develop various flat display devices such as liquid crystal display (LCD), plasma display panel (PDP), electroluminescent display (ELD), and vacuum fluorescent display (VFD). Some types of the flat display devices are already used as displays of various equipment.

[0006] Among the various flat display devices, the liquid crystal display (LCD) device has been most widely used due to its advantageous characteristics of thinness, lightness in weight, and low power consumption, whereby the LCD device has come to replace Cathode Ray Tube (CRT). In addition to the mobile type LCD devices such as a display for notebook computers, LCD devices have been developed for computer monitors and televisions to receive and display broadcasting signals.

[0007] Despite various technical developments in the LCD technology, research in improving the picture quality of LCD devices has been in some respects lacking as compared to other features and advantages of the LCD devices. Therefore, in order to use LCD devices in various fields as general displays, it is preferable that the LCD device can implement a high quality picture, such as high resolution and high luminance with a large-sized screen, while still maintaining lightness in weight, thinness, and low power consumption.

[0008] The LCD device includes an LCD panel for displaying an image and a driving part for applying a driving signal to the LCD panel. The LCD panel includes first and second glass substrates bonded to each other at a predetermined interval and a liquid crystal layer injected between the first and second glass substrates. The liquid crystal layer is driven by an electric field generated between the first and second glass substrates, thereby controlling light transmittance by the liquid crystal layer. As a result, an image is displayed on the LCD panel.

[0009] Among the LCD devices, a Twisted Nematic (TN) mode LCD device, in which longitudinal directions of liquid crystal molecules between the lower and upper substrates are parallel with the lower and upper substrates, has been most generally used. In TN mode, the liquid crystal molecules are spirally twisted with a predetermined pitch.

[0010] The TN mode LCD device has characteristics of varying transmittance of light at each gray level depending on viewing angles. Specifically, the transmittance of light is

distributed symmetrically in right and left directions of the TN mode LCD device, but asymmetrically in lower and upper directions.

[0011] In order to overcome such a problem, a method is proposed to compensate for the viewing angle dependency by dividing pixels into multiple domains with each domain having a different alignment direction of the liquid crystal layer in a Vertical Alignment (VA) mode. In the VA mode, an auxiliary electrode or an electric field inducing window is formed on the upper substrate to distort an electric field, thereby obtaining a wide viewing angle.

[0012] A related art LCD device will be explained with reference to the accompanying drawings. FIG. 1 is an enlarged plan view illustrating a related art LCD device, and FIG. 2 is a cross-sectional view illustrating a related art LCD device taken along line I-I' of FIG. 1.

[0013] As shown in FIG. 1 and FIG. 2, the related art LCD device includes lower and upper substrates 1 and 10 facing each other, and a liquid crystal layer 16 between the lower and upper substrates 1 and 10.

[0014] The lower substrate 1 includes a plurality of gate and data lines 2 and 4 crossing each other to define a plurality of pixel regions. A gate electrode 2a extends from both sides of the gate line 2. The lower substrate 1 also includes a gate insulating layer (not shown); an active region 3 on the gate insulating layer above the gate electrode 2a; a pixel electrode 7 in the pixel region in the same layer as the active region; a source electrode 4a extending from the data line 4 and overlapping one portion of the active region 3; a drain electrode 4b spaced apart from the source electrode 4a and overlapping the other portion of the active region 3 and a predetermined portion of the pixel region; an interlayer insulation film 6 on the entire surface of the lower substrate 1 including the pixel electrode 7; an orientation control electrode 5 on the interlayer insulation film 6 overlapping the periphery of the pixel electrode 7; and a first alignment layer 8 on the lower substrate 1 including the orientation control electrode 5.

[0015] The upper substrate 10 includes a black matrix layer (not shown) that prevents light leakage at the regions other than the pixel regions of the lower substrate 1, a color filter layer (not shown) on the upper substrate 10 corresponding to the black matrix layer of the upper substrate 10 and the pixel regions of the lower substrate 1, a common electrode 13 on the color filter layer, the common electrode 13 having an X-shaped orientation control window 14, and a second alignment layer 15 on the upper substrate 10 including the common electrode 13.

[0016] Although not shown, first and second polarizing plates are formed on a lower surface of the lower substrate 1 and an upper surface of the upper substrate 10, respectively. The first and second polarizing plates have polarizers crossing each other.

[0017] At this time, the orientation control electrode 5 is connected to another orientation control electrode of an adjacent pixel. Also, the orientation control window 14 is used for distorting the vertical electric field formed between the pixel electrode 7 and the common electrode 13.

[0018] That is, when the electric field is generated between the pixel electrode 7 of the lower substrate 1 and the

common electrode **13** of the upper substrate **10**, as indicated by the arrows of **FIG. 2**, a fringe field is generated by the orientation control window **14** inside the common electrode **13**. Thus, liquid crystal molecules are differently oriented at both sides of the orientation control window **14** by the fringe field, thereby compensating a viewing angle.

[0019] Also, the liquid crystal layer **16** has a negative dielectric anisotropy. In the VA mode using the fringe field, if an additional structure for inducing a fringe field (such as a side electrode) is not formed, a texture of liquid crystal molecules varies at each pixel region, thereby deteriorating uniformity of the LCD device.

[0020] Meanwhile, as shown in **FIG. 3**, devices having a liquid crystal layer **16** (**FIG. 2**) having negative dielectric anisotropy between the lower and upper substrates can have black lines on the screen generated by longitudinal axes of the liquid crystal molecules **21** arranged in parallel to the optical axes of the first and second polarizing plates.

[0021] In order to solve such a problem, chiral dopant is added to the negative dielectric anisotropy liquid crystal (vertical alignment liquid crystal with chiral dopant, hereinafter, referred to as VAC) as illustrated in **FIG. 4**. That is, light is transmitted at the portion where the longitudinal axes of the liquid crystal molecules **21** are arranged in parallel (arrow direction) to the optical axes of the first and second polarizing plates. Thus, luminance is improved as compared with a case using the general liquid crystal layer having the negative dielectric anisotropy. Accordingly, if the general liquid crystal layer having the negative dielectric anisotropy is used, 'A' and 'B' portions of **FIG. 3** become black as a result of the liquid crystal molecules arranged parallel to the optical axes of the first and second polarizing plates.

[0022] Meanwhile, using the VAC, the liquid crystal molecules are arranged in a twisted structure, as illustrated in **FIG. 4** according to helical characteristics of the chiral dopant. Thus, the light is transmitted at 'C' and 'D' portions of **FIG. 4**, thereby improving luminance.

[0023] **FIG. 5** illustrates the luminance when a general liquid crystal layer having the negative dielectric anisotropy is used as compared to the luminance when the VAC is used. If the VAC (dotted line) is used for the related art LCD device, luminance is improved as compared with the case using the general liquid crystal layer having the negative dielectric anisotropy without chiral dopant (solid line).

[0024] However, the related art LCD device has the following disadvantages.

[0025] In the related art LCD device, the orientation control window is formed to obtain the wide viewing angle, whereby the texture of the liquid crystal molecules is stabilized. However, in case of using the liquid crystal layer having the negative dielectric anisotropy, luminance is deteriorated because the liquid crystal molecules are arranged in parallel with the first and second the polarizers.

[0026] In case of using the VAC having the liquid crystal layer of the twisted structure, luminance is improved. However, it is hard to maximize luminance due to the thin color filter layer on the upper substrate.

SUMMARY OF THE INVENTION

[0027] Accordingly, the present invention is directed to a liquid crystal display (LCD) device that substantially obviates one or more problems due to limitations and disadvantages of the related art.

[0028] An advantage of the present invention is to provide to an LCD device in which a hole is formed in the same direction as those of first and second polarizers, and an electric field inducing window or a dielectric protrusion is formed at the center of the hole, thereby maximizing the luminance of the LCD device.

[0029] Additional advantages, objects, and features of the invention will be set forth in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or may be learned from practice of the invention. The objectives and other advantages of the invention may be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

[0030] To achieve these and other advantages and in accordance with the purpose of the invention, as embodied and broadly described herein, an LCD device includes first and second substrates; gate and data lines crossing each other to define a pixel region on the first substrate; a pixel electrode on the pixel region; a color filter layer on the second substrate, the color filter layer having a hole; a common electrode on the color filter layer; a liquid crystal layer between the first and second substrates; and first and second polarizers on the first and second substrates, a direction of the polarizer having same direction of the hole.

[0031] It is to be understood that both the foregoing general description and the following detailed description of the present invention are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0032] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate embodiment(s) of the invention and together with the description serve to explain the principle of the invention.

[0033] In the drawings:

[0034] **FIG. 1** is an enlarged plan view illustrating a unit pixel of a related art LCD device;

[0035] **FIG. 2** is a cross-sectional view illustrating a unit pixel taken along line I-I' of a **FIG. 1** in a related art LCD device;

[0036] **FIG. 3** is a plan view illustrating an orientation of liquid crystal layer having negative dielectric anisotropy in a related art LCD device;

[0037] **FIG. 4** is a plan view illustrating an orientation of liquid crystal layer having chiral dopant in a related art LCD device;

[0038] **FIG. 5** is a graph illustrating luminance using a liquid crystal having negative dielectric anisotropy with a chiral dopant and without a chiral dopant according to voltage;

[0039] FIG. 6 is an enlarged plan view illustrating a unit pixel of an LCD device according to a first embodiment of the present invention;

[0040] FIG. 7 is a cross-sectional view illustrating a unit pixel taken along line II-II' of FIG. 6 according to the present invention;

[0041] FIG. 8A to FIG. 9C are enlarged plan views illustrating a unit pixel having a hole in an LCD device according to the first embodiment of the present invention;

[0042] FIG. 10 is a cross-sectional view illustrating an etching process of a color filter layer;

[0043] FIG. 11 is a graph comparing the luminance of an LCD device according to the first embodiment of the present invention with the luminance of a related art LCD device;

[0044] FIG. 12 is an enlarged plan view illustrating a unit pixel of an LCD device according to a second embodiment of the present invention; and

[0045] FIG. 13 is a cross-sectional view illustrating a unit pixel taken along line III-III' of FIG. 10 according to the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

[0046] Reference will now be made in detail to the embodiments of the present invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

[0047] In LCD devices according to the illustrated embodiments of the present invention, a hole or groove is formed inside a unit pixel region in parallel with a polarizer, a dielectric protrusion or an electric field inducing window is formed on the center of the hole or groove, and a liquid crystal layer having chiral dopant is formed, thereby maximizing luminance.

[0048] The LCD devices according to the illustrated embodiments of the present invention, in which the dielectric protrusion or the electric field inducing window is formed inside the unit pixel region, will be described as follows.

[0049] FIG. 6 is an enlarged plan view illustrating a unit pixel region of an LCD device according to a first embodiment of the present invention, and FIG. 7 is a cross-sectional view illustrating the unit pixel region taken along line II-II' of FIG. 6 in an LCD device according to the first embodiment of the present invention.

[0050] As illustrated in FIG. 6 and FIG. 7, the LCD device according to the first embodiment of the present invention includes lower and upper substrates 30 and 40 facing each other with a predetermined interval therebetween. A plurality of gate and data lines 31 and 33, a plurality of thin film transistors T, a pixel electrode 35, a common auxiliary electrode 37, a gate insulating layer 32, and a passivation layer 34 are on the lower substrate 30. A black matrix layer (not shown), a color filter layer 42, a common electrode 44, a dielectric protrusion 45 are on the upper substrate 40. A liquid crystal layer 46 fills the predetermined interval between the lower and upper substrates 30 and 40.

[0051] The plurality of gate lines 31 are formed on the lower substrate 30 substantially perpendicular to the plurality of data lines 33 for defining a plurality of pixel regions. Then, the plurality of thin film transistors T are formed at crossing points of the plurality of gate and data lines 31 and 33, and each pixel electrode 35 is formed on the pixel region. Also, the common auxiliary electrode 37 is formed on the same layer as the gate line 31 or the data line 33 overlapping the periphery of the pixel electrode, and the gate insulating layer 32 is formed on the entire surface of the lower substrate 30, including the gate lines 31. The passivation layer 34 is formed on the entire surface of the lower substrate 30, including the data lines 33.

[0052] The black matrix layer (not shown) is formed on the upper substrate 40 in areas corresponding to regions of the lower substrate 30 other than the pixel regions. The color filter layer 42 having a hole or groove 41 in the pixel region partially overlaps with the black matrix layer, and the common electrode 44 is formed on the entire surface of the upper substrate 40, including the color filter layer 42. Also, the dielectric protrusion 45 is formed on the common electrode 44 at the center of the hole or groove 41, and the liquid crystal layer 46 is formed between the lower and upper substrates 30 and 40.

[0053] Although not shown, an orientation layer is formed on the entire surface of at least one of the lower and upper substrates 30 and 40 to determine an initial alignment of the liquid crystal layer 46. Furthermore, first and second polarizers are formed on an upper surface of the upper substrate 40 and a lower surface of the lower substrate 30, the first and second polarizers having axes of polarization crossing each other.

[0054] Preferably, the liquid crystal layer 46 has a negative dielectric anisotropy. Also, the liquid crystal layer 46 includes vertical alignment liquid crystal with chiral dopant (hereinafter, referred to as VAC). That is, light is transmitted at a portion where longitudinal axes of the liquid crystal molecules are parallel with the first and second polarizers, whereby luminance is improved as compared with using general liquid crystal layer of negative dielectric anisotropy without chiral dopant.

[0055] The hole or groove 41 in the pixel region is formed in the same direction as those of the first and second polarizers, so that light transmittance is improved, thereby maximizing luminance.

[0056] That is, if axes of polarization of the first and second polarizers are parallel with the length and the width of the lower and upper substrates, the hole or groove may be formed in a cross-shape corresponding to the directions of the axes of polarization. Optionally, as illustrated in FIG. 8A or FIG. 8B, the hole or groove may be formed horizontally or vertically in the unit pixel region (in the context of the figure). Also, the hole or groove may be formed in the direction of the axes of polarization.

[0057] Referring to FIG. 9A to FIG. 9C, if the hole or groove is formed diagonally or in X-shape inside the unit pixel region, the first and second polarizers are diagonally formed to the lower and upper substrates 30 and 40. In addition, the shape of the hole or groove may vary in the direction of the polarizers.

[0058] At this time, the hole or groove 41 is formed by etching the color filter layer 42. That is, the color filter layer

42 may be over-etched as shown in **FIG. 10(a)**, or may be removed as shown in **FIG. 10(b)**.

[0059] In the LCD device according to the first embodiment of the present invention, the color filter layer **42** may be over-etched or removed to form the hole or groove **41**, whereby light is transmitted through the hole or groove **41**. Thus, luminance is improved since the light transmittance is irradiated in the hole or groove, as shown in **FIG. 11**.

[0060] The LCD device according to the first embodiment of the present invention uses the hole or groove and the VAC liquid crystal layer. Referring to **FIG. 11**, the luminance (c) of the LCD device using both the hole or groove and the VAC liquid crystal layer increases as voltage intensity applied to the pixel electrode increases, in comparison with a related art LCD device having liquid crystal layer without chiral dopant (a) of **FIG. 11** or a related art LCD device using the VAC liquid crystal layer of **FIG. 11**.

[0061] Meanwhile, the unit pixel region is divided into two domains according to the hole or groove **41** horizontally formed inside the unit pixel region, and then divided again according to the hole or groove **41** vertically formed inside the pixel region, thereby forming four domain regions in the unit pixel region. In this case, a fringe field is generated by the hole or groove **41** and the common auxiliary electrode **37**, whereby an electric field generated in the lower substrate spreads to the circumference of the pixel region.

[0062] The texture of the liquid crystal layer is stabilized by the electric field in the circumference of the pixel electrode, remaining parts of the unit pixel region except the hole or groove **41**. However, if the hole or groove **41** is wide, the texture of the liquid crystal may be caused to be unstable by the hole or groove **41**.

[0063] Accordingly, in the LCD device according to the first embodiment of the present invention, the hole or groove **41** is formed in the pixel region, and the dielectric protrusion **45** is formed at the center of the hole or groove **41**, thereby stabilizing the texture of the liquid crystal layer.

[0064] Next, an overcoat layer (not shown) may be formed on the color filter layer **22** for planarizing the upper substrate, and the common electrode **42** may be formed on the overcoat layer. In this case, even though it is hard to obtain electric field distortion effect by the hole or groove **41**, it is possible to improve luminance.

[0065] It will be apparent to those skilled in the art that various modifications and variations of the gate line **31**, the data line **33**, the gate insulating layer **32**, the black matrix layer and the color filter layer **42** can be made in the present invention. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

[0066] As mentioned above, the LCD device according to the first embodiment of the present invention is formed such that the hole or groove **41** is formed inside the unit pixel region TN in the same direction as that of the polarizer to improve the luminance, and the dielectric protrusion **45** is formed at the center of the hole or groove **41** to stabilize the texture of the liquid crystal layer.

[0067] In an LCD device according to the second embodiment of the present invention, a hole or groove is formed in

a pixel region on a color filter layer, and then an electric field inducing window is formed in the center of the hole or groove of the color filter layer.

[0068] **FIG. 12** is an enlarged plan view illustrating a unit pixel region of an LCD device according to the second embodiment of the present invention, and **FIG. 13** is a cross-sectional view illustrating a unit pixel region taken along line III-III' of **FIG. 10** in an LCD device according to the second embodiment of the present invention.

[0069] As shown in **FIG. 12** and **FIG. 13**, the LCD device according to the second embodiment of the present invention includes lower and upper substrates **30** and **40** facing each and spaced apart by a predetermined interval. The lower substrate **30** includes a plurality of gate and data lines **31** and **33**, a plurality of thin film transistors T, a pixel electrode **35**, a common auxiliary electrode **37**, a gate insulating layer **32**, and a passivation layer **34**. The upper substrate **40** includes a black matrix layer, a color filter layer **42**, an overcoat layer **47**, and a common electrode **44**. A liquid crystal layer **46** is interposed between the lower and upper substrates **30** and **40** in the predetermined interval.

[0070] The plurality of gate lines **31** are formed on the lower substrate **30** substantially perpendicular with the plurality of data lines **33**, thereby forming a plurality of pixel regions. Then, the thin film transistor T is formed at each crossing point of the gate and data lines **31** and **33**, and each pixel electrode **35** is formed in the pixel region. The common auxiliary electrode **37** is formed on the same layer as that of the gate line **31** or the data line **33** overlapping the periphery of the pixel electrode, and the gate insulating layer **32** is formed on the entire surface of the lower substrate **30** including the gate lines **31**. Also, the passivation layer **34** is formed on the entire surface of the lower substrate **30** including the data lines **33**.

[0071] Next, the black matrix layer is formed on the upper substrate **40** corresponding to regions of the lower substrate **30** except the pixel regions, and the color filter layer **42** is formed partially overlapping the black matrix layer, the color filter layer **42** having a hole or groove **41** in the pixel region. Then, the overcoat layer is formed on the entire surface of the upper substrate **40** including the color filter layer **42**, and the common electrode **44** is formed on the entire surface of the upper substrate **40** including the overcoat layer, the common electrode **44** having an electric field inducing window **48** in the center of the hole or groove **41**. After that, the liquid crystal layer **46** is formed between the lower and upper substrates **30** and **40**.

[0072] Although not shown, an orientation layer is formed on the entire surface of at least one of the lower and upper substrates **30** and **40** to determine an initial alignment of the liquid crystal layer **46**. Furthermore, first and second polarizers are formed on an upper surface of the upper substrate **40** and a lower surface of the lower substrate **30**, respectively, the first and second polarizers crossing each other.

[0073] The liquid crystal layer **46** may have a negative dielectric anisotropy. Also, the liquid crystal layer **46** includes vertical alignment liquid crystal with chiral dopant (hereinafter, referred to as VAC).

[0074] The overcoat layer is formed to easily form the electric field inducing window **48** of the common electrode **44** by planarizing the color filter layer **42**. That is, in forming

the electric field inducing window **48** by etching the common electrode **44** in a region corresponding to the center of the hole or groove **41** without forming the overcoat layer, there may be problems in etching the common electrode **44**.

[0075] The LCD device according to the second embodiment of the present invention is the same as the LCD device according to the first embodiment of the present invention except that the electric field inducing window (reference number **48** of FIG. 13) is formed on the upper substrate **40** instead of the dielectric protrusion (reference number **45** of FIG. 6) on the upper substrate. Thus, the same reference numbers will be used throughout the drawings to refer to the same except the electric field inducing window **48** on the upper substrate **40**.

[0076] In order to easily form the aforementioned electric field inducing window **48**, the overcoat layer is further formed to planarize the color filter layer **42**.

[0077] Meanwhile, the hole or groove **41** is planarized by the overcoat layer, and the common electrode **44** is formed on the overcoat layer, so that it is difficult to distort the electric field by the hole or groove **41**. That is, the hole or groove **41** is not for controlling the liquid crystal layer **46**, but for improving luminance by controlling light transmittance on the color filter layer **42** according to an area of the hole or groove.

[0078] Meanwhile, the electric field inducing window generates a fringe field with common auxiliary electrode overlapping the pixel electrode at the periphery of the pixel region. Thus, an electric field spreads to the circumference of the pixel region, thereby stabilizing the texture of the liquid crystal layer. At this time, the electric field inducing window **48** may be larger than the hole or groove **41** in the center of the pixel region.

[0079] In the LCD device according to the second embodiment of the present invention, the hole or groove **41** is formed in the same direction as that of the polarizer being crossed on the upper substrate **40** so as to improve the luminance. Also, the electric field inducing window **48** is formed in the center of the pixel region to stabilize the texture of the liquid crystal layer.

[0080] As mentioned above, the LCD device according to the present invention has the following advantages.

[0081] In the LCD device according to the present invention, the hole or groove is formed inside the pixel region, and chiral dopant is added to the liquid crystal layer, so that light transmittance is improved, thereby maximizing luminance.

[0082] Also, the dielectric protrusion or the electric field inducing window is formed in the center of the pixel region to stabilize the texture of the liquid crystal layer, thereby obtaining a uniform image.

[0083] It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

1-36. (canceled)

37. An LCD device comprising:

first and second substrates;

gate and data lines crossing each other to define a pixel region on the first substrate;

a pixel electrode on the pixel region;

a color filter layer on the second substrate, the color filter layer having a hole;

a common electrode on the color filter layer;

a liquid crystal layer between the first and second substrates;

first and second polarizers on the first and second substrates, a direction of the polarizer having same direction of the hole; and

an electric field inducing window on the center of the hole.

38. The device of claim 37, wherein the liquid crystal layer has a negative dielectric anisotropy.

39. The device of claim 38, wherein the liquid crystal layer further includes chiral dopant.

40. The device of claim 37, wherein the hole has a shape one of a cross-shape, horizontally, vertically, diagonally and in X-shape.

41. The device of claim 37, wherein the hole is formed by etching the color filter layer.

42. The device of claim 37, wherein the electric field inducing window is formed in the common electrode.

43. The device of claim 37, wherein the pixel electrode is overlapped with the data line.

44. The device of claim 37, further comprising an overcoat layer on the color filter layer.

45. The device of claim 37, further comprising a common auxiliary electrode at the periphery of the pixel electrode.

46. The device of claim 45, wherein the common auxiliary electrode overlaps with the pixel electrode.

47. A liquid crystal display device, comprising:

first and second substrates facing each other, at least one of the first and second substrates having a polarizer on an external surface thereof, wherein the polarizer has a first axis of polarization with a first direction;

gate and data lines crossing each other to define at least one pixel region on a surface of the first substrate;

a pixel electrode on the pixel region;

a color filter layer on a surface of the second substrate facing the first substrate, the color filter layer having a groove therein, wherein a long side of the groove extends in the first direction;

a common electrode on the color filter layer;

a liquid crystal layer between the first and second substrates; and

an electric field inducing window corresponding to the center of the groove.

48. The device of claim 47, wherein the electric field inducing window is formed in the common electrode.

49. The device of claim 47, wherein the pixel electrode is overlapped with the data line.

50. The device of claim 47, further comprising an overcoat layer on the color filter layer.

51. The device of claim 47, further comprising a common auxiliary electrode at the periphery of the pixel electrode.

52. The device of claim 51, wherein the common auxiliary electrode overlaps with the pixel electrode.

53. The device of claim 47, wherein the other of the first and second substrates has an additional polarizer on an external surface thereof, wherein the additional polarizer has a second axis of polarization in a second direction.

54. The device of claim 53, wherein the first direction and second direction are substantially parallel.

55. The device of claim 53, wherein the first direction and the second direction are substantially perpendicular.

56. The device of claim 53, wherein the color filter layer has an additional groove, wherein a long side of the additional groove extends in the second direction.

57. The device of claim 56, wherein the groove and the additional groove overlap.

58. The device of claim 57, wherein the groove and the additional groove overlap in a cross shape.

59. The device of claim 53, wherein the first direction is substantially parallel to the data lines and the second direction is substantially parallel to the gate lines.

60. The device of claim 53, wherein the first direction is substantially parallel to the gate lines and the second direction is substantially parallel to the data lines.

61. The device of claim 53, wherein the first direction is not parallel to the data lines or the gate lines and the second direction is not parallel to the gate lines or the data lines.

62. The device of claim 47, wherein the liquid crystal layer has a negative dielectric anisotropy.

63. The device of claim 62, wherein the liquid crystal layer further includes chiral dopant.

64. The device of claim 47, wherein the first direction is substantially parallel to the data lines.

65. The device of claim 47, wherein the first direction is substantially parallel to the gate lines.

66. The device of claim 47, wherein the first direction is at an angle with respect to the data lines.

67. The device of claim 47, wherein the first direction is not parallel to the gate lines or the data lines.

68. The device of claim 47, wherein the groove is formed by etching the color filter layer.

* * * * *

专利名称(译)	液晶显示装置		
公开(公告)号	US20050253985A1	公开(公告)日	2005-11-17
申请号	US11/185875	申请日	2005-07-21
[标]申请(专利权)人(译)	HAM YONG 小号 李润乙		
申请(专利权)人(译)	HAM YONG 小号 李润乙		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	HAM YONG SUNG LEE YUN BOK		
发明人	HAM, YONG SUNG LEE, YUN BOK		
IPC分类号	G02F1/1333 G02F1/1335 G02F1/137 G02F1/139		
CPC分类号	G02F1/133514 G02F1/133707 G02F2001/13712 G02F2001/133531 G02F1/1396		
优先权	1020020051103 2002-08-28 KR		
其他公开文献	US7307684		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种液晶显示 (LCD) 装置，其中在与第一和第二偏振器的偏振轴相同的方向上形成孔或凹槽以改善亮度，并且形成电场感应窗口或电介质突起对应于孔或槽的中心，以稳定液晶层的纹理。

