



US 20090046216A1

(19) **United States**(12) **Patent Application Publication**
Chen(10) **Pub. No.: US 2009/0046216 A1**(43) **Pub. Date: Feb. 19, 2009**(54) **LIQUID CRYSTAL DISPLAY HAVING
ELECTRICALLY FLOATING THIN FILM
TRANSISTOR WITHIN SUB PIXEL UNIT****Publication Classification**(51) **Int. Cl.****G02F 1/133** (2006.01)**G02F 1/1368** (2006.01)(52) **U.S. Cl. 349/48**(75) **Inventor: Hung-Yu Chen, Miao-Li (TW)**

Correspondence Address:

WEI TE CHUNG**FOXCONN INTERNATIONAL, INC.****1650 MEMOREX DRIVE****SANTA CLARA, CA 95050 (US)**(73) **Assignee: INNOLUX DISPLAY CORP.**(21) **Appl. No.: 12/228,709**(22) **Filed: Aug. 15, 2008**(30) **Foreign Application Priority Data**


Aug. 15, 2007 (CN) 200710075773.6

(57)

ABSTRACT

An LCD includes data lines, gate lines intersecting with the data lines, and pixel units. Each pixel unit is defined by a minimal area formed by two adjacent data lines and two adjacent gate lines. Each pixel unit includes a first sub pixel unit and a second sub pixel unit. The first sub pixel unit includes a first thin film transistor (TFT) and a first pixel electrode. The second sub pixel unit includes a second TFT and a second pixel electrode. A gate electrode of the first TFT is connected to the gate line, a source electrode of the first TFT is connected to the data line. A source electrode of the second TFT is connected to a same data line, and a gate electrode of the second TFT is electrically floating.

200






FIG. 1




FIG. 2




FIG. 3




FIG. 4
(RELATED ART)




FIG. 5
(RELATED ART)

LIQUID CRYSTAL DISPLAY HAVING ELECTRICALLY FLOATING THIN FILM TRANSISTOR WITHIN SUB PIXEL UNIT

FIELD OF THE INVENTION

[0001] The present invention relates to liquid crystal displays (LCDs), and particularly, to a multi-domain vertical alignment LCD having an electrically floating thin film transistor within a sub pixel unit.

GENERAL BACKGROUND

[0002] LCD devices have been widely used in various portable information products such as notebooks, personal digital assistants, and video cameras, because of its portability, low power consumption, and low radiation. LCD devices are poised to completely replace cathode ray tube monitors and televisions.

[0003] Referring to FIG. 4 and FIG. 5, a typical multi-domain vertical alignment mode LCD 100 includes a plurality of parallel gate lines 101, a plurality of parallel first data lines 103 intersecting with the gate lines 101, a plurality of second data lines 105 parallel to the first data lines 103, a plurality of first thin film transistors (TFTs) 111 positioned adjacent to the intersection of the gate lines 101 and the first data lines 103, a plurality of second TFTs 121 positioned adjacent to the intersection of the gate lines 101 and the second data lines 105, a plurality of first pixel electrodes 113, a plurality of second pixel electrodes 123, a plurality of common electrodes 107 corresponding to the first pixel electrodes 113 and the second pixel electrodes 123, a plurality of first storage capacitors 115, and a plurality of second storage capacitors 125.

[0004] Each first TFTs 111 includes a gate electrode (not labeled) connected to a corresponding gate line 101, a source electrode (not labeled) connected to a corresponding first data line 103, and a drain electrode (not labeled) connected to a corresponding first pixel electrode 113. Each second TFTs 121 includes a gate electrode (not labeled) connected to a corresponding gate line 101, a source electrode (not labeled) connected to a corresponding second data line 105, and a drain electrode (not labeled) connected to a corresponding second pixel electrode 123.

[0005] Each first pixel electrode 113 and the corresponding common electrode 107 constitute a first liquid crystal capacitor 117. Each second pixel electrode 123 and the corresponding common electrode 107 constitute a second liquid crystal capacitor 127. The first liquid crystal capacitor 117 and the first capacitor 115 are connected in parallel. The second liquid crystal capacitor 127 and the second capacitor 125 are connected in parallel.

[0006] Each first TFT 111, the corresponding first capacitor 115, and the corresponding first liquid crystal capacitor 117 cooperatively define a first sub pixel unit 110. Each second TFT 121, the corresponding second capacitor 125, and the corresponding second liquid crystal capacitor 127 cooperatively define a second sub pixel unit 120. The first and second sub pixel units 110, 120 cooperatively constitute a pixel 130. In another aspect, each pixel 130 is a region substantially defined by two adjacent gate lines 101 crossing over a first data line 103 and an adjacent second data line 105.

[0007] The gate lines 101 are configured for applying a plurality of scanning signals to the first and second TFTs 111, 121 in order to switch on or switch off the corresponding first and second TFTs 111, 121. The first data lines 103 are configured for applying a plurality of first gray scale voltages to the first TFTs 111. The second data lines 105 are configured

for applying a plurality of second gray scale voltages to the second TFTs 121. Display performance of the LCD 100 is enhanced by applying first gray scale voltages to the first sub pixel units 110 and applying second gray scale voltages to the second sub pixel units 120.

[0008] However, a layout of the first and second data lines 103, 105 is complicated because the first sub pixel unit 110 and the second sub pixel unit 120 are supplied with gray scale voltages from the first data line 103 and the second data lines 105, respectively. In addition, the LCD 100 needs more data driving chips, thereby driving the cost of the LCD 100.

[0009] What is needed, therefore, is an LCD that can overcome the above-described deficiencies.

SUMMARY

[0010] An LCD includes a plurality of data lines, a plurality of gate lines intersecting with the data lines, and a plurality of pixel units. Each pixel unit is surrounded by two data lines and two gate lines. Each pixel unit includes a first sub pixel unit and a second sub pixel unit. The first sub pixel unit includes a first thin film transistor (TFT) and a first pixel electrode. The second sub pixel unit includes a second TFT and a second pixel electrode. A gate electrode of the first TFT is connected to the gate line, a source electrode of the first TFT is connected to the data line, and a drain electrode of the first TFT is connected to the first pixel electrode. A source electrode of the second TFT is connected to a same data line, a drain electrode of the second TFT is connected to the second pixel electrode, and a gate electrode of the second TFT is electrically floating.

[0011] Other novel features and advantages of the present LCD will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] Many aspects can be better understood with reference to the following drawings. The components in the drawings are not necessarily drawn to scale, the emphasis instead being placed upon clearly illustrating the principles of the embodiments. Moreover, in the drawings, like reference numerals designate corresponding parts throughout the several views.

[0013] FIG. 1 is a circuit diagram of a first embodiment of an LCD, the LCD including a plurality of gate lines, a plurality of data lines, and a plurality of pixel units.

[0014] FIG. 2 is an enlarged circuit diagram of one pixel unit of the LCD of FIG. 1.

[0015] FIG. 3 is an enlarged circuit diagram of one pixel unit of a second embodiment of an LCD.

[0016] FIG. 4 is a circuit diagram of a typical multi-domain vertical alignment (MVA) mode LCD.

[0017] FIG. 5 is an enlarged circuit diagram of one pixel unit of FIG. 4.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0018] Reference will now be made to the figures to describe various embodiments of the invention in detail.

[0019] Referring to FIG. 1, a circuit diagram of a first embodiment of an LCD 200 includes a plurality of gate lines 201, a plurality of data lines 203, and a plurality of pixel units 230. The plurality of gate lines 201 are substantially parallel to each other. The plurality of data lines 203 are substantially parallel to each other, and substantially perpendicular to the

gate lines **201**. Two nearby gate lines **201** and two nearby data lines **203** surround each pixel unit **230**.

[0020] Referring also to FIG. 2, each pixel unit **230** includes a first sub pixel unit **210** and a second sub pixel unit **220**. Each first sub pixel unit **210** includes a first TFT **211**, a first storage capacitor **215** and a first liquid crystal capacitor **217** comprising a first pixel electrode **213**, a common electrode **207**, and a liquid crystal (not shown) sandwiched between the first pixel electrode **213** and the common electrode **207**. Each second sub pixel unit **220** includes a second TFT **221**, a second storage capacitor **225**, and a second liquid crystal capacitor **227** comprising a second pixel electrode **223**, the common electrode **207**, and a liquid crystal sandwiched between the second pixel electrode **223** and the common electrode **207**.

[0021] Each first TFT **211** includes a first gate electrode (not labeled), a first source electrode (not labeled), and a first drain electrode (not labeled). Each second TFT **221** includes a second gate electrode (not labeled), a second source electrode (not labeled), and a second drain electrode (not labeled). Each first gate electrode is connected to an adjacent gate line **201**. Each first source electrode is connected to an adjacent data line **203**. Each first drain electrode is connected to the corresponding first pixel electrode **213**. Each second source electrode is connected to the corresponding first drain electrode. In another embodiment, the second source electrode may be connected to the adjacent data line **201**. Each second drain electrode is connected to the corresponding second pixel electrode **223**. The second gate electrode is floating (i.e., the second gate electrode is not connected).

[0022] In operation, scanning signals are provided sequentially to the gate lines **201**. When one of the gate lines **201** is scanned, the first TFTs **211** connected thereto are turned on so that the data lines **203** provide gray scale voltages to the first pixels electrodes **213** via the first TFTs **211**. The first liquid crystal capacitor **217** and the first storage capacitor **215** are charged by the gray scale voltages.

[0023] Simultaneously, the gray scale voltage is applied to the second source electrode of the second TFT **221**. The second TFT **221** is turned off because the second gate electrode of the second TFT **221** is floating. Thus, an impedance value between the second source electrode and the second drain electrode of the second TFT **221** is much greater than an impedance value of the first TFT **211**. Hence, a charging current for the second liquid crystal capacitor **227** and the second storage capacitor **225** is much less than a charging current for the first liquid crystal capacitor **217** and the first storage capacitor **215**. After the gate line **201** is scanned, the second pixel electrode **223** gains a gray scale voltage less than that of the first pixel electrode **213**. The gray scale voltages are maintained to realize a display of images until the gate line **201** is scanned again at a next frame period.

[0024] Unlike conventional LCDs, one of the data lines **203** provides the gray scale voltage to the first pixel electrode **213** and the second electrode **223**. In other words, the first sub pixel unit **210** and the second sub pixel unit **220** are driven by a single data line **203**, thereby simplifying a layout of the data lines **203**. In addition, the second sub pixel unit **220** gains a gray scale voltage different from that of the first pixel unit **210** because the second TFT is floating. In another embodiment, the second source electrode of the second TFT **221** can be connected to the data line **203** other than the first drain electrode of the first TFT **211**.

[0025] A parasitical capacitor generally exists between the gate electrode and the source electrode of the TFTs **211**, **221**. A voltage potential of the gate electrode changes as the voltage potential of the source electrode changes. Accordingly, an impedance value between the source electrode and the drain electrode changes. In other words, the voltage potential of the source electrode is inversely proportional to the impedance value between the source electrode and the drain electrode.

[0026] The gray scale voltage provided to the source electrode of the second TFT **221** is high and the impedance value between the source electrode and the drain electrode is low when the pixel unit **230** is displaying a white image, for a normally-black LCD. A charging current for the second sub pixel unit **220** is relatively great, or even equal to a charging current for the first sub pixel unit **210**. The second sub pixel unit **220** can reach a gray scale voltage nearly equal to that of the first sub pixel unit **210**. Therefore, the pixel unit **230** can still display a complete white image.

[0027] The gray scale voltage provided to the source electrode of the second TFT **221** is low and the impedance value between the source electrode and the drain electrode is great when the pixel unit **230** displays a black image. A charging current for the second sub pixel unit **220** is relatively small, or even equal to 0 Ampere (A). Thus, the second sub pixel unit **220** may display a blacker image than the first sub pixel unit **210**. Therefore, the pixel unit **230** may display a relatively blacker image. In summary, the LCD **200** may have good performance in contrast ratio.

[0028] Referring to FIG. 3, a second embodiment of an LCD is similar to the LCD **200**, except a second sub pixel unit **320** further includes a third TFT **329**. A second source electrode of a second TFT **321** is connected to a third drain electrode of the third TFT **329**. A third gate electrode of the third TFT **329** is connected to a gate line **301**. A third source electrode of the third TFT **329** is connected to a data line **303**. The third TFT **329** is configured for controlling whether a gray scale voltage is provided to the second pixel electrode via the second TFT **321**. The embodiment of FIG. 3 has advantages similar to those of the LCD **200** of FIG. 1. In another embodiment, the third source electrode of the third TFT **329** can be connected to the drain electrode of the first TFT other than the data line **303**.

[0029] It is to be understood, however, that even though numerous characteristics and advantages of the present embodiments have been set out in the foregoing description, together with details of the structures and functions of the embodiments, the disclosure is illustrative only, and changes may be made in detail, especially in matters of shape, size, and arrangement of parts within the principles of the invention to the full extent indicated by the broad general meaning of the terms in which the appended claims are expressed.

What is claimed is:

1. A liquid crystal display (LCD), comprising:
 - a plurality of data lines;
 - a plurality of gate lines intersecting the data lines; and
 - a plurality of pixel units, each pixel unit being at least partially surrounded by an adjacent data line adjacent to a side of the pixel unit and an adjacent gate line adjacent to another side of the pixel unit, each pixel unit comprising:
 - a first sub pixel unit comprising:
 - a first pixel electrode; and
 - a first thin film transistor (TFT) having a first gate electrode connecting to the adjacent gate line, a first

- source electrode connecting to the adjacent data line, and a first drain electrode connecting to the first pixel electrode; and
- a second sub pixel unit comprising:
- a second pixel electrode; and
 - a second TFT having a second source electrode coupling to the adjacent data line, a second drain electrode connecting to the second pixel electrode, and a second gate electrode electrically floating
2. The LCD of claim 1, wherein each second sub pixel unit further comprises a third TFT having a third gate electrode connected to the adjacent gate line, a third source electrode connected to the adjacent data line, and a third drain electrode connected to the second source electrode.
3. The LCD of claim 1, wherein each first sub pixel unit further comprises a common electrode and a liquid crystal sandwiched between the common electrode and the first pixel electrode, wherein the common electrode, the liquid crystal, and the first pixel electrode constitute a first liquid crystal capacitor.
4. The LCD of claim 3, wherein each first sub pixel unit further comprises a first storage capacitor electrically connected to the first liquid crystal capacitor in parallel.
5. The LCD of claim 3, wherein each second sub pixel unit further comprises a common electrode, and a liquid crystal sandwiched between the common electrode and the second pixel electrode, wherein the common electrode, the liquid crystal, and the second pixel electrode constitute a second liquid crystal capacitor.
6. The LCD of claim 5, wherein each second sub pixel unit further comprises a second storage capacitor electrically connected to the second liquid crystal capacitor in parallel.
7. A liquid crystal display (LCD), comprising:
- a plurality of data lines;
 - a plurality of gate lines intersecting the data lines; and
 - a plurality of pixel units, each pixel unit being at least partially surrounded by an adjacent data line adjacent to a side of the pixel unit and an adjacent gate line adjacent to another side of the pixel unit, each pixel unit comprising:
- a first sub pixel unit comprising:
 - a first pixel electrode; and
 - a first thin film transistor (TFT) having a first gate electrode connecting to the adjacent gate line, a first source electrode connecting to the adjacent data line, and a first drain electrode connecting to the first pixel electrode; and

- a second sub pixel unit comprising:

 - a second pixel electrode; and
 - a second TFT having a second source electrode coupling to the first drain electrode, a second drain electrode connecting to the second pixel electrode, and a second gate electrode electrically floating.

8. The LCD of claim 7, wherein each second sub pixel unit further comprises a third TFT having a third gate electrode connected to the adjacent gate line, a source electrode connected to the first drain electrode; a third drain electrode connected to the second source electrode.

9. A liquid crystal display (LCD), comprising:

- a plurality of data lines;
- a plurality of gate lines intersecting the data lines; and
- a plurality of pixel units, each pixel unit being surrounded by two data lines and two gate lines, each pixel unit comprising two sub pixel units, each sub pixel unit comprising a TFT and a pixel electrode, each TFT comprising a gate electrode, a source electrode, and a drain electrode;

wherein each pixel electrode is connected to an adjacent data line via the corresponding TFT; the gate electrode of one of the plurality of TFTs is connected to an adjacent gate line; the gate electrode of the another one of the plurality of TFTs is electrically floating.

10. The LCD of claim 9, wherein each pixel unit comprises a first sub pixel unit and a second sub pixel unit, the first sub pixel unit comprising a first TFT and a first pixel electrode, the second sub pixel unit comprising a second TFT and a second pixel electrode.

11. The LCD of claim 10, wherein the first pixel electrode is connected to the adjacent data line via the first TFT; the second pixel electrode is coupled to the adjacent data line via the second TFT.

12. The LCD of claim 11, wherein a gate electrode of the first TFT is connected to the gate line; a gate electrode of the second TFT is electrically floating.

13. The LCD of claim 12, wherein the second sub pixel unit further comprises a third TFT; a gate electrode of the third TFT is connected to the adjacent gate line; a source electrode of the third TFT is connected to the adjacent data line; a drain electrode of the third TFT is connected to the source electrode of the second TFT.

* * * * *

专利名称(译)	液晶显示器在子像素单元内具有电浮动薄膜晶体管		
公开(公告)号	US20090046216A1	公开(公告)日	2009-02-19
申请号	US12/228709	申请日	2008-08-15
[标]申请(专利权)人(译)	群创光电股份有限公司		
申请(专利权)人(译)	群创光电股份有限公司.		
当前申请(专利权)人(译)	群创光电		
[标]发明人	CHEN HUNG YU		
发明人	CHEN, HUNG-YU		
IPC分类号	G02F1/133 G02F1/1368		
CPC分类号	G02F1/1368 G02F1/13306		
优先权	200710075773.6 2007-08-15 CN		
其他公开文献	US7800705		
外部链接	USPTO		

摘要(译)

LCD包括数据线，与数据线交叉的栅极线和像素单元。每个像素单元由两条相邻数据线和两条相邻栅极线形成的最小区域限定。每个像素单元包括第一子像素单元和第二子像素单元。第一子像素单元包括第一薄膜晶体管 (TFT) 和第一像素电极。第二子像素单元包括第二TFT和第二像素电极。第一TFT的栅极连接到栅极线，第一TFT的源极连接到数据线。第二TFT的源极连接到同一数据线，第二TFT的栅极电浮置。

