



US007289175B2

(12) **United States Patent**  
**Chuang**

(10) **Patent No.:** **US 7,289,175 B2**  
(45) **Date of Patent:** **Oct. 30, 2007**

(54) **TRANSFLECTIVE LIQUID CRYSTAL DISPLAY**

(58) **Field of Classification Search** ..... 349/114,  
349/129  
See application file for complete search history.

(75) Inventor: **Li-Sen Chuang**, Penghu (TW)

(56) **References Cited**

(73) Assignee: **TPO Displays Corp.**, Chu-Nan (TW)

U.S. PATENT DOCUMENTS

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 415 days.

6,750,932 B2\* 6/2004 Kim ..... 349/114

\* cited by examiner

(21) Appl. No.: **10/906,804**

*Primary Examiner*—David Nelms  
*Assistant Examiner*—Richard H Kim  
(74) *Attorney, Agent, or Firm*—Liu & Liu

(22) Filed: **Mar. 8, 2005**

(57) **ABSTRACT**

(65) **Prior Publication Data**  
US 2005/0140866 A1 Jun. 30, 2005

A transflective liquid crystal display comprising an active device array substrate, a facing substrate, a liquid crystal layer and a reflector. The liquid crystal molecules in the transparent area are driven by a potential between the transparent pixel electrode and the common electrode. The liquid crystal molecules in the reflective area are driven by a potential between the transparent pixel electrode and the active device array substrate or the auxiliary electrode on the facing substrate. Under the condition of a single cell gap, the electric field applied to the transparent area and the reflective area can control the change in effective phase so as to optimize the performance.

**Related U.S. Application Data**

(62) Division of application No. 10/250,288, filed on Jun. 20, 2003, now Pat. No. 6,985,197.


**Foreign Application Priority Data**

(30) Nov. 7, 2002 (TW) ..... 91132742 A

(51) **Int. Cl.**  
**G02F 1/1335** (2006.01)

**10 Claims, 11 Drawing Sheets**

(52) **U.S. Cl.** ..... 349/114; 349/129






FIG. 1A (PRIOR ART)




FIG. 1B (PRIOR ART)




FIG. 2A





FIG. 2B






FIG. 4A





FIG. 4B



302  
304  
402  
410  
412  
414  
420  
T  
R  
FIG. 5




FIG. 6A




FIG. 6B




FIG. 7

# TRANSFLECTIVE LIQUID CRYSTAL DISPLAY

## CROSS-REFERENCE TO RELATED APPLICATION

This application is a divisional of a prior application Ser. No. 10/250,288, filed Jun. 20, 2003 now U.S. Pat. No. 6,985,197, which claims the priority benefit of Taiwan application serial no. 91132742, filed Nov. 7, 2002.

## BACKGROUND OF THE INVENTION

### 1. Field of Invention

The present invention relates to a transflective liquid crystal display (LCD). More particularly, the present invention relates to a single cell gap transflective liquid crystal display.

### 2. Description of Related Art

Due to progress in the development of semiconductor devices or man-machine display interface, multimedia communication is almost a routine in everyday life. High-quality and economical displaying devices such as cathode ray tube (CRT) are in the market for some time. However, as a desktop terminal/display, CRT is rather bulky and occupies a lot of space, and from the standpoint of energy conservation, CRT consumes too much electrical energy. Hence, CRT can no longer meet our demands for a light, compact and energy efficient display. Since the recently developed thin film transistor liquid crystal display (TFT-LCD) has superior image quality, slim, low power consumption and radiation free characteristics, TFT-LCD is now a major sell in the market.

Most liquid crystal displays (LCD) can be categorized into the transparent type, the reflective type and the transflective type. The classification is based on the different light source utilization and array arrangements. The transparent LCD uses back light as a source of illumination and the pixel electrodes on the array are transparent to facilitate the penetration of back light. The reflective LCD uses front light or external light as a source of illumination and the pixel electrodes on the array are made from metal or other substances having good reflective properties so that the front or external light can be reflected. The transflective LCD uses both back light and external light as a source of illumination at the same time. Each pixel can be divided into a transparent area and a reflective area. The transparent area has a transparent electrode that facilitates the passage of back light and the reflective area has a reflective electrode capable of reflecting light from external light sources.

Using a normally black transflective LCD as an example, both the transparent area and the reflective area are in a dark state before the application of a voltage. When the transparent area and the reflective area change from a dark state to the brightest state, phase in the transparent area must differ by  $\pm\lambda/2$  and phase in the reflective area must differ by  $\pm\lambda/4$ . However, in a single cell gap LCD, the required phase differences are hard to secure at the same time. Thus, optimal utilization of light in both the transparent area and the reflective area is difficult to attain in practice. Due to intrinsic display limitations of a single cell gap transflective LCD, transflective LCD having dual cell gaps are developed. By designing the transparent area and the reflective area with different cell gaps, light from whatever sources is fully utilized.

FIG. 1A is a schematic cross-sectional view of a conventional dual cell gap transflective liquid crystal display. As shown in FIG. 1A, the dual cell gap transflective LCD 100 mainly comprises of a thin film transistor (TFT) array substrate 102, a facing substrate 104 and a liquid crystal

layer 106. The cell gap in the transmission region (T) of the transflective LCD is controlled to a distance  $d$  while the cell gap in the reflective area (R) of the transflective LCD is controlled to a distance  $d/2$ . Hence, the liquid crystal layer 106 within the transparent area (T) has a thickness  $d$  and the liquid crystal layer 106 within the reflective area (R) has a thickness  $d/2$ . In addition, the cell gap or the thickness  $d$  of the liquid crystal layer 106 must also meet the phase change relationship  $(\Delta n \cdot d) = \pm\lambda/2$ . Therefore, through a thickness variation ( $d$  to  $d/2$ ) of the liquid crystal layer 106, there is a phase change of  $\pm\lambda/2$  and  $\pm\lambda/4$  inside the respective cell gaps.

FIG. 1B is a schematic layout diagram of a conventional dual cell gap transflective LCD. As shown in FIG. 1B, the active device array substrate 102 has a plurality of scanning lines 200 and a plurality of data lines 202 thereon. Each pair of neighboring scanning lines 200 and each pair of neighboring data lines 202 constitute a pixel region 212. Each pixel region 212 has an active device 204, a transparent electrode 206 and a reflective electrode 208. The transparent electrode 206 is positioned over a portion of the pixel region 212 to form a transparent area (T). The reflective electrode 208 is positioned over a portion of the pixel region 212 outside the transparent area (T) to form a reflective area (R).

In general, the transparent electrode 206 and the reflective electrode 208 in the same pixel region 212 are electrically connected together. Hence, the transparent electrode 206 and the reflective electrode 208 within the same pixel region 212 are controlled by one active device 204. Furthermore, the active device 204 is, for example, a thin film transistor (TFT) or a diode that may switch state when driven voltages applied to the scanning line 200 and the data line 202.

Although the dual cell gap transflective LCD is able to optimize illumination, the substrate plates are difficult to fabricate.

## SUMMARY OF THE INVENTION

Accordingly, one object of the present invention is to provide a transflective liquid crystal display (LCD) having a single cell gap structure that uses an applied electric field to control phase changes within the reflective area and the transparent area of the LCD. Hence, the reflective area and the transparent area in the transflective LCD are optimally illuminated.

To achieve these and other advantages and in accordance with the purpose of the invention, as embodied and broadly described herein, the invention provides a transflective liquid crystal display. The transflective LCD mainly comprises of a thin film transistor (TFT) array, a facing substrate and a liquid crystal layer. The active device array substrate has a plurality of scanning lines and a plurality of data lines thereon. Each pair of neighboring scanning lines and each pair of neighboring data lines together constitute a pixel region. Each pixel region has an active device, a transparent electrode and a reflector. The active device is driven by voltage applied to the scan line and the data line. The transparent electrode is positioned in a portion of the pixel region to form a transparent area and the reflector is positioned in the pixel region but outside the transparent area to form a reflective area. The transparent electrode and the active device are electrically connected. The facing substrate has a plurality of common electrodes and a plurality of auxiliary electrodes. The common electrode is positioned above the transparent electrode and the auxiliary electrode is positioned above the reflector. The liquid crystal layer is positioned between the active device array substrate and the facing substrate. The transparent area and the reflective area have an identical thickness. Furthermore, a first alignment film is positioned between the liquid crystal layer and the

active device array substrate and a second alignment film is positioned between liquid crystal layer and the facing substrate. In addition, a top polarizing plate is positioned just outside the active device array substrate and a bottom polarizing plate is positioned just outside the facing substrate.

This invention also provides a second type of transfective liquid crystal display that comprises of an active device array substrate, a facing substrate, a liquid crystal layer and a reflector. The active device array substrate has a plurality of scan lines and a plurality of data lines thereon. Each pair of neighboring scan lines and each pair of neighboring data lines constitutes a pixel region. Each pixel region has an active device and a transparent electrode. The active device is driven by voltage applied to the scan line and the data line. The transparent electrode is positioned over the pixel region to form a transparent area. The transparent electrode and the active device are electrically connected together. The facing substrate has a plurality of common electrodes and a plurality of auxiliary electrodes thereon. The common electrode is positioned over the transparent electrode and the auxiliary electrode is positioned outside the transparent area. The reflector is positioned outside the active device array substrate to form a reflective area. The liquid crystal layer is positioned between the active device array substrate and the facing substrate. The transparent area and the reflective area have an identical thickness. Furthermore, a first alignment film is positioned between the liquid crystal layer and the active device array substrate and a second alignment film is positioned between liquid crystal layer and the facing substrate. In addition, a top polarizing plate is positioned just outside the active device array substrate and a bottom polarizing plate is positioned just outside the facing substrate.

This invention also provides a third type of transfective liquid crystal display comprising of an active device array substrate, a facing substrate and a liquid crystal layer. The active device array substrate has a plurality of scanning lines and a plurality of data lines thereon. Each pair of neighboring scan lines and each pair of neighboring data lines together constitutes a pixel region. Each pixel region has an active device, a reflective electrode and an auxiliary electrode. The active device is driven by voltage applied to the scanning line and the data line. The reflective electrode is positioned over a portion of the pixel region to form a reflective area. The pixel region outside the reflective area is a transparent area. The reflective electrode and the active device are electrically connected together. The facing substrate has a plurality of common electrodes thereon. The common electrodes are positioned over the reflective electrodes. The liquid crystal layer is positioned between the active device array substrate and the facing substrate. The transparent area and the reflective area have an identical thickness. Furthermore, a first alignment film is positioned between the liquid crystal layer and the active device array substrate and a second alignment film is positioned between liquid crystal layer and the facing substrate. In addition, a top polarizing plate is positioned just outside the active device array substrate and a bottom polarizing plate is positioned just outside the facing substrate.

In this invention, the active device array substrate is a thin film transistor (TFT) array substrate or a diode array substrate, for example. In addition, the LCD may also serve as a color display by adding a color filter on the facing substrate in a position that corresponds to the pixel region to form a color filtering plate.

This invention also permits the installation of a first delay plate between the top polarizing plate and the active device array substrate and a second delay plate between the bottom polarizing plate and the active device array substrate.

It is to be understood that both the foregoing general description and the following detailed description are exemplary, and are intended to provide further explanation of the invention as claimed.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings are included to provide a further understanding of the invention, and are incorporated in and constitute a part of this specification. The drawings illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention. In the drawings,

FIG. 1A is a schematic cross-sectional view of a conventional dual cell gap transfective liquid crystal display;

FIG. 1B is a schematic layout diagram of a conventional dual cell gap transfective LCD;

FIGS. 2A and 2B are schematic cross-sectional views of a transfective liquid crystal display according to a first embodiment of this invention;

FIG. 3 is a diagram showing the layout of a transfective LCD according the first embodiment of this invention;

FIGS. 4A and 4B are schematic cross-sectional views of a transfective liquid crystal display according to a second embodiment of this invention;

FIG. 5 is a diagram showing the layout of a transfective LCD according the second embodiment of this invention;

FIGS. 6A and 6B are schematic cross-sectional views of a transfective liquid crystal display according to a third embodiment of this invention; and

FIG. 7 is a diagram showing the layout of a transfective LCD according the third embodiment of this invention.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the present preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts.

FIGS. 2A and 2B are schematic cross-sectional views of a transfective liquid crystal display according to a first embodiment of this invention. As shown in FIG. 2A, the transfective liquid crystal display (LCD) mainly comprises of an active device array substrate **400**, a complementary panel **300** and a liquid crystal layer **500**. The Active device array substrate **400** has a plurality of pixel regions thereon. Each pixel region has an active device (not shown), a transparent electrode **402** and a reflector **404**. The active device (not shown) and the transparent electrode **402** are positioned over a portion of the pixel region to form a transparent area (T). The reflector **404** and the pixel region **212** outside the transparent area (T) form a reflective area (R). Note that the transparent electrode **402** and the reflector **404** have no electrical connection.

The facing substrate **300** has a plurality of common electrode **302** and a plurality of auxiliary electrodes **304** thereon. The common electrode **302** is positioned over the transparent electrode **402** and the auxiliary electrode **304** is positioned over the reflector **404**. In addition, the liquid crystal layer **500** is positioned between the active device array substrate **400** and the facing substrate **300**.

Aside from the active device array substrate **400**, the facing substrate **300** and the liquid crystal layer **500**, optical films such as a first delay plate **306** and a top polarizing plate **308** may be attached to the outer surface of the facing substrate **300**. In addition, optical films such as a second delay plate **406** and a bottom polarizing plate **408** are attached to the outer surface of the active device array substrate **400**. The first delay plate **306** is capable of delaying incoming light by  $\lambda/4$  phase. Similarly, the second delay plate **406** is capable of delaying incoming light by  $\lambda/4$  phase.

The liquid crystal layer **500** used in this embodiment is, for example, negative liquid crystals so that slow axis of the liquid crystal molecules is parallel to the electric field provided. Without the application of a voltage, the liquid crystal molecules are aligned in a manner as shown in FIG. 2A. Hence, overall effective phase difference of the liquid crystal layer **500** is zero and both the transparent area (T) and the reflective area (R) are in a dark state. The transparent area (T) and the reflective area (R) change from a dark state to the brightest state when an electric field perpendicular to the surface of the active device array substrate **400** is created between the transparent electrode **402** and the common electrode **302** in the liquid crystal layer **500** within the transparent area (T). The vertical electric field aligns the liquid crystal molecules in a direction shown on the left side of FIG. 2B such that the transparent area (T) has an effective phase difference of  $\lambda/2$ .

Since the transparent electrode **402** and the reflector **404** have no electrical connection, the electric field in the reflective area (R) is created through the transparent electrode **402** and the auxiliary electrode **304**. In this embodiment, through the potential difference between the transparent electrode **402** and the auxiliary electrode **304**, an electric field forming an oblique angle with the surface of the active device array substrate **400** is created in the liquid crystal layer **500** within the reflective area (R). This oblique electric field aligns liquid crystal molecules in a direction as shown on the right side of FIG. 2B such that the reflective area (R) has an effective phase difference of  $\lambda/4$ .

Accordingly, phase variation in the transparent area (T) is  $(\lambda/2-0)=\lambda/2$  and thus the phase variation meets the demanded phase variation  $\pm\lambda/2$ . Similarly, phase variation in the reflective area (R) is  $(\lambda/4-0)=\lambda/4$  and hence the phase variation meets the demanded phase variation  $\pm\lambda/4$ . Ultimately, optimal utilization of light in both the transparent area and the reflective area is achieved.

FIG. 3 is a diagram showing the layout of a transfective LCD according to the first embodiment of this invention. As shown in FIG. 3, the active device array substrate has a plurality of scanning lines **410** and a plurality of data lines **412** thereon. Neighboring scanning lines **410** and neighboring data lines **412** together form a pixel region **420**. Each pixel region **420** has an active device **414**, a transparent electrode **402** and a reflector **404**. The active device **414** such as a thin film transistor or a diode is able to change state when driven by applied voltage at the scanning line **410** and the data line **412**. The transparent electrode **402** is positioned over a portion of the pixel region **212** to form a transparent area (T) and the reflector **404** is also positioned over a portion of the pixel region **212** to form a reflective area (R).

The transparent electrode **402** has no electrical connection with the reflector **404**. Hence, the liquid crystal molecules above the reflector **404** (the reflective area (R)) are driven by the oblique electric field between the transparent electrode **402** and the auxiliary electrode **304**. The liquid crystal molecules above the transparent electrode **402** (the trans-

parent area (T)) are driven by the vertical electric field between the transparent electrode **402** and the common electrode **302**.

FIGS. 4A and 4B are schematic cross-sectional views of a transfective liquid crystal display according to a second embodiment of this invention. In general, the reflector **404** in the first embodiment can be attached to the active device array substrate **400** in other ways. In the second embodiment, a reflector **416** is attached to the outer surface of the active device array substrate **400**. The reflector **416** is similarly capable of reflecting light from light sources (including front light and external light).

FIG. 5 is a diagram showing the layout of a transfective LCD according to the second embodiment of this invention. As shown in FIG. 5, the active device array substrate has a plurality of scanning lines **410** and a plurality of data lines **412** thereon. Neighboring scanning lines **410** and neighboring data lines **412** together form a pixel region **420**. Each pixel region **420** has an active device **414** and a transparent electrode **402**. The active device **414** such as a thin film transistor or a diode is able to change state when driven by applied voltage at the scanning line **410** and the data line **412**. The transparent electrode **402** is positioned over a portion of the pixel region **212** to form a transparent area (T) and the portion of the pixel region **212** outside the transparent area (T) is regarded as a reflective area (R).

In the second embodiment, the liquid crystal molecules above the reflective area (R) is driven by the oblique electric field between the transparent electrode **402** and the auxiliary electrode **304**. Similarly, the liquid crystal molecules above the transparent area (T) are driven by the vertical electric field between the transparent electrode **402** and the common electrode **302**.

FIGS. 6A and 6B are schematic cross-sectional views of a transfective liquid crystal display according to a third embodiment of this invention. As shown in FIGS. 6A and 6B, the transfective LCD mainly comprises of an active device array substrate **400**, a facing substrate **300** and a liquid crystal layer **500**. The active device array substrate **400** has a plurality of pixel regions thereon. Each pixel region has an active device (not shown), a reflective electrode **430** and an auxiliary electrode **418**. The active device (not shown) and the reflective electrode **430** are positioned over a portion of the pixel region to form a reflective area (R). The pixel region **212** outside the reflective area (R) is regarded as a transparent area (T). The facing substrate **300** has a plurality of common electrodes **302** thereon. The common electrodes **302** are positioned above the reflective electrode **430**. In addition, the liquid crystal layer **500** is positioned between the active device array substrate **400** and the facing substrate **300**.

The third embodiment is similar to the first embodiment of this invention in many ways. In the first embodiment, the auxiliary electrode **304** is positioned over the facing substrate **300** and the liquid crystal molecules above the reflective area (R) are driven by the oblique electric field between the auxiliary electrode **304** and the transparent electrode **402**. In the third embodiment, however, the auxiliary electrode **418** is positioned above the transparent area (T) of the active device array substrate **400**. Hence, the liquid crystal molecules above the transparent area (T) are driven by the lateral electric field between the reflective electrode **430** and the auxiliary electrode **418**. In addition, optical films such as a first delay plate **306** and a top polarizing plate **308** may be attached to the outer surface of the facing substrate **300**. Similarly, optical films such as a second delay plate **406** and a bottom polarizing plate **408** are attached to the outer

surface of the active device array substrate **400**. The first delay plate **306** is capable of delaying incoming light by  $\lambda/2$  phase and the second delay plate **406** is capable of delaying incoming light by  $\lambda/4$  phase.

The liquid crystal layer **500** in the third embodiment uses, for example, positive crystals that have a hybrid alignment or oblique alignment so that the fast axis of the liquid crystal molecules is parallel to the electric field provided. The liquid crystal molecules are aligned in a direction as shown in FIG. **6A** before the application of any voltage. Thus, the liquid crystal layer **500** produces an overall phase difference of  $\lambda/4$  and both the transparent area (T) and the reflective area (R) are in a dark state. To change the transparent area (T) and the reflective area (R) to a brightest state, the transparent electrode **430** and the common electrode **302** provide an electric field perpendicular to the surface of the active device array substrate **400** in the liquid crystal layer **500** within the reflective area (R). The vertical electric field aligns the liquid crystal molecules in a direction as shown on the left side of FIG. **6B** such that the effective phase difference in the transparent area (T) is zero.

In the third embodiment, the reflective electrode **430** and the auxiliary electrode **418** provides a lateral electric field parallel to the surface of the active device array substrate **400** in the liquid crystal layer **500** of the transparent area (T). The lateral electric field aligns the liquid crystal molecules in a direction as shown on the right side of FIG. **6B** so that the transparent area (T) has an effective phase difference of  $3\lambda/4$ .

Accordingly, phase variation in the transparent area (T) is  $(3\lambda/4 - \lambda/4) = \lambda/2$  and thus the phase variation meets the demanded phase variation  $\pm\lambda/2$ . Similarly, phase variation in the reflective area (R) is  $(0 - \lambda/4) = -\lambda/4$  and hence the phase variation meets the demanded phase variation  $\pm\lambda/4$ . Ultimately, optimal utilization of light in both the transparent area and the reflective area is achieved.

FIG. **7** is a diagram showing the layout of a transfective LCD according the third embodiment of this invention. As shown in FIG. **7**, the liquid crystal molecules above the reflective area (R) are driven by the vertical electric field between the reflective electrode **430** and the common electrode **302**. Similarly, the liquid crystal molecules above the transparent area (T) are driven by the lateral electric field between the reflective electrode **430** and the auxiliary electrode **418**.

In the aforementioned embodiments, the positioning of the transparent electrode, the reflective electrode, the common electrode and the auxiliary electrode relative to each other is utilized to provide an electric field having an appropriate direction and strength. Thus, the effective phase difference of liquid crystal molecules above the transparent area (T) and the reflective area (R) may vary in such a way that light utilization in the transmission region (T) and the reflective area (R) are optimized.

In summary, the transfective liquid crystal display has at least the following advantages:

1. The effective phase difference in the reflective area and the transparent area is controlled by the direction of an applied electric field so that light utilization in the reflective area and the transparent area is optimized.

2. In the third embodiment, there is no need to fabricate the transparent electrode. Nevertheless, the liquid crystal molecules above the transparent area (T) and the reflective area (R) are simultaneously driven. Hence, fabrication process is simplified.

3. Since the transparent electrode pattern on the active device array substrate and the common electrode pattern on

the facing substrate need to be modified, production is compatible with existing processes.

It will be apparent to those skilled in the art that various modifications and variations can be made to the structure of the present invention without departing from the scope or spirit of the invention. In view of the foregoing, it is intended that the present invention cover modifications and variations of this invention provided they fall within the scope of the following claims and their equivalents.

What is claimed is:

1. A transfective liquid crystal display (LCD), comprising:

an active device array substrate having a plurality of pixel regions, wherein each pixel region has an active device, a reflective electrode and an auxiliary electrode, the reflective electrode is positioned over a portion of the pixel region to form a reflective area and electrically connected to the active device, the pixel region outside the reflective area forms a transparent area, the auxiliary electrode is positioned over the transparent area; a facing substrate having a plurality of common electrodes thereon, wherein the common electrodes are positioned over the reflective electrode; and a liquid crystal layer positioned between the active device array substrate and the facing substrate.

2. The transfective LCD of claim 1, wherein the active device array substrate is either a thin film transistor array substrate or a diode array substrate.

3. The transfective LCD of claim 1, wherein the facing substrate further includes a plurality of color filter films positioned in areas corresponding to the pixel regions.

4. The transfective LCD of claim 1, wherein the LCD further includes:

a top polarizing plate positioned just outside the active device array substrate; and a bottom polarizing plate positioned just outside the facing substrate.

5. The transfective LCD of claim 4, wherein the LCD further includes:

a first delay plate between the top polarizing plate and the active device array substrate; and a second delay plate between the bottom polarizing plate and the active device array substrate.

6. The transfective LCD of claim 1, wherein a thickness of the liquid crystal layer in the transparent area is same as a thickness of the liquid crystal layer in the reflective area.

7. The transfective LCD of claim 1, wherein a first alignment film is positioned between the liquid crystal layer and the active device array substrate and a second alignment film is positioned between the liquid crystal layer and the facing substrate.

8. The transfective LCD of claim 1, wherein a plurality of liquid crystal molecules of the liquid crystal layer above the transparent area are driven by a lateral electric field between the auxiliary electrode and the reflective electrode.

9. The transfective LCD of claim 8, wherein the lateral electric field aligns the liquid crystal molecules in a direction of the transparent area is equivalent to phase difference of  $3\lambda/4$ .

10. The transfective LCD of claim 8, wherein the liquid crystal molecules above the reflective area are driven by a vertical electric field between the common electrode and the reflective electrode.

专利名称(译)	透反液晶显示器		
公开(公告)号	<a href="#">US7289175</a>	公开(公告)日	2007-10-30
申请号	US10/906804	申请日	2005-03-08
[标]申请(专利权)人(译)	庄立森		
申请(专利权)人(译)	庄礼SEN		
当前申请(专利权)人(译)	群创光电		
[标]发明人	CHUANG LI SEN		
发明人	CHUANG, LI-SEN		
IPC分类号	G02F1/1335 G02F1/1343 G02F1/1368		
CPC分类号	G02F1/134336 G02F1/133555		
审查员(译)	内尔姆斯, DAVID		
助理审查员(译)	KIM, RICHARD H		
优先权	091132742 2002-11-07 TW		
其他公开文献	US20050140866A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

一种半透半反液晶显示器，包括有源器件阵列基板，面对基板，液晶层和反射器。透明区域中的液晶分子由透明像素电极和公共电极之间的电位驱动。反射区域中的液晶分子由透明像素电极和有源器件阵列基板之间的电位或面对基板上的辅助电极驱动。在单个单元间隙的条件下，施加到透明区域和反射区域的电场可以控制有效相位的变化，从而优化性能。

