



US 20050157239A1

(19) **United States**

(12) **Patent Application Publication**
Yoo

(10) **Pub. No.: US 2005/0157239 A1**

(43) **Pub. Date: Jul. 21, 2005**

(54) **METHOD FOR FABRICATING AN ARRAY SUBSTRATE FOR IN-PLANE SWITCHING LIQUID CRYSTAL DISPLAY DEVICE HAVING MULTI-DOMAIN**

(30) **Foreign Application Priority Data**

Jul. 27, 2001 (KR)..... 2001-45473

Publication Classification

(76) **Inventor: Jang-Jin Yoo, Seoul (KR)**

(51) **Int. Cl.⁷ G02F 1/1343**

(52) **U.S. Cl. 349/141**

Correspondence Address:
MCKENNA LONG & ALDRIDGE LLP
1900 K STREET, NW
WASHINGTON, DC 20006 (US)

(57) **ABSTRACT**


A method for fabricating an array substrate for an in-plane switching liquid crystal display device includes forming a gate line and a data line on the substrate, the gate line and the data line crossing each other to define a pixel region, forming a thin film transistor that is electrically connected to the gate and data lines, and forming a common line parallel to the gate line. A plurality of common electrodes are formed to perpendicularly extend from the common line. A plurality of pixel electrodes are formed in an alternating pattern with the plurality of common electrodes, and an overcoat layer is formed over the plurality of common electrodes and the plurality of pixel electrodes, the overcoat layer having a plurality of holes.

(21) **Appl. No.: 11/081,671**

(22) **Filed: Mar. 17, 2005**

Related U.S. Application Data

(63) **Continuation of application No. 10/201,785, filed on Jul. 25, 2002, now Pat. No. 6,885,424.**






FIG. 1
(RELATED ART)




FIG. 2A
(RELATED ART)




FIG. 2B
(RELATED ART)




FIG. 3
(RELATED ART)




FIG. 4A
(RELATED ART)




FIG. 4B
(RELATED ART)




FIG. 5A
(RELATED ART)




FIG. 5B
(RELATED ART)





FIG. 6
(RELATED ART)



Inversion regions of gray level

FIG. 7
(RELATED ART)




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20

**METHOD FOR FABRICATING AN ARRAY
SUBSTRATE FOR IN-PLANE SWITCHING LIQUID
CRYSTAL DISPLAY DEVICE HAVING
MULTI-DOMAIN**

[0001] This application claims the benefit of Korean Patent Application No. 2001-45473, filed on Jul. 27, 2001, which is hereby incorporated by reference for all purposes as if fully set forth herein.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to a liquid crystal display (LCD) device and more particularly, to an array substrate for an in-plane switching liquid crystal display (IPS LCD) device.

[0004] 2. Discussion of the Related Art

[0005] In general, a liquid crystal display (LCD) device has an upper substrate and a lower substrate, which are spaced apart and face each other, and a liquid crystal layer disposed between the upper and lower substrates. Each of the substrates includes an electrode and the electrodes of each substrate also face each other. The LCD device uses an optical anisotropy of liquid crystal and produces an image by controlling light transmissivity by varying the arrangement of liquid crystal molecules, which are arranged by an electric field.

[0006] As it has a high resolution and can display an excellent moving image, an LCD device, which includes thin film transistors and pixel electrodes arranged in a matrix form, is widely used. The LCD device is referred to as an active matrix liquid crystal display (AMLCD).

[0007] A related art liquid crystal display (LCD) device will be described hereinafter more in detail with reference to FIG. 1. FIG. 1 is an exploded perspective view illustrating a conventional LCD device. The conventional LCD device 11 has upper and lower substrates 5 and 22, which are spaced apart and face each other, and also has a liquid crystal layer 14 to be interposed between the upper substrate 5 and the lower substrate 22.

[0008] A gate line 13 is formed horizontally in the context of the figure on the inside of the lower substrate 22 and a data line 15 is formed vertically in the context of the figure on the inside of the lower substrate 22. The gate line 13 and the data line 15 cross each other to define a pixel area "P". A thin film transistor "T" is situated at the crossing of the gate line 13 and the data line 15. A pixel electrode 17, which is electrically connected to the thin film transistor "T", is formed in the pixel area "P". The pixel electrode 17 is made of a transparent conductive material such as Indium-Tin-Oxide (ITO) or Indium Zinc Oxide (IZO).

[0009] Next, a black matrix 6, which has an opening corresponding to the pixel electrode 17, is formed on the inside of the upper substrate 5. A color filter 7 corresponding to the opening of the black matrix 6 is formed on the black matrix 6. The color filter 7 includes three colors: red (R), green (G) and blue (B). Each color corresponds to a respective pixel electrode 17. Subsequently, a transparent common electrode 18 is formed on the color filter 7.

[0010] In the related art LCD device of FIG. 1, when voltage is applied to the pixel electrode 17 and the common

electrode 18, an electric field is induced between the pixel electrode 17 and the common electrode 18 in a direction perpendicular to the upper and lower substrates 5 and 22. Molecules of the liquid crystal layer 14 are arranged by the electric field and light is emitted through the arranged liquid crystal layer 14 from a back light (not shown) disposed below the conventional LCD device, so that pictures are displayed.

[0011] The conventional LCD device having the above-mentioned structure, in which the liquid crystal layer is driven by the electric field perpendicular to the upper and lower substrates, has a high transmittance and a high aperture ratio, and the common electrode of the upper substrate is grounded so that breaking of the device due to static electricity is prevented.

[0012] The conventional LCD device, generally, uses twisted nematic (TN) mode liquid crystal, the orientation of which is parallel to substrates and is continuously twisted from one substrate to another substrate by 90 degrees.

[0013] FIGS. 2A and 2B are schematic views conceptually showing operation modes of a related art twisted nematic liquid crystal display (TNLCD) device. The liquid crystal has positive dielectric anisotropy, and is arranged in parallel to the direction of the electric field.

[0014] In FIG. 2A, when voltage is not applied, orientation of the long axis of the liquid crystal layer 14 is parallel to substrates 22 and 5, and molecules of the liquid crystal layer 14 are continuously twisted from the lower substrate 22 to the upper substrate 5 by 90 degrees.

[0015] In FIG. 2B, when voltage is applied to the pixel and common electrodes 17 and 18, the electric field, which is perpendicular to the lower and upper substrates 22 and 5, is induced between the lower and upper substrate 22 and 5, and molecules of the liquid crystal layer 14 are arranged in parallel to the electric field except for molecules of the liquid crystal layer 14 close to the pixel and common electrodes 17 and 18. At this time, the liquid crystal layer, generally, has molecules twisted at an extreme value of 90 degrees.

[0016] However, the above-mentioned liquid crystal display device, in which an electric field is induced perpendicular to the substrates and which includes molecules of the liquid crystal layer parallel to the electric field, has a disadvantage of a narrow viewing angle. To overcome the narrow viewing angle, an in-plane switching (IPS) LCD device was developed. The IPS LCD device implements an electric field that is parallel to the substrates, which is different from the TNLCD device. A detailed explanation of a conventional IPS LCD device and its operation modes will be provided with reference to the following figures.

[0017] FIG. 3 is a schematic cross-sectional view of a related art in-plane switching liquid crystal display device. As shown in FIG. 3, the upper and lower substrates 32 and 30 are spaced apart from each other, and a liquid crystal layer 33 is interposed there between. The upper and lower substrates 32 and 30 are referred to as a color filter substrate and an array substrate, respectively. Pixel and common electrodes 34 and 36 are disposed on the lower substrate 30. The pixel and common electrodes 34 and 36 are parallel with each other and spaced apart from each other. Molecules of the liquid crystal layer 33 are aligned by a lateral electric field between the pixel and common electrodes 34 and 36.

[0018] FIGS. 4A and 4B are views illustrating operations of the liquid crystal for IPS mode at on and off states of the applied voltage. FIG. 4A conceptually illustrates "off state" operation modes for a related art IPS LCD device. In the off state, the long axis of the liquid crystal layer 33 maintains an initial arrangement, which is made by a method such as a rubbing. The pixel and common electrodes 34 and 36 are parallel with each other.

[0019] FIG. 4B conceptually illustrates "on state" operation modes for a related art LPS LCD device. In the on state, an in-plane electric field 35, which is parallel to the surface of the lower substrate, is generated between the pixel and the common electrodes 34 and 36. The pixel electrode 34 and common electrode 36 are formed together on the lower substrate for this reason. Thereby, molecules of the liquid crystal layer 33 are aligned such that the long axes thereof are parallel to the substrates and perpendicular to the pixel and common electrodes 34 and 36.

[0020] FIGS. 5A and 5B are schematic plan views conceptually showing operation modes of a related art in-plane switching liquid crystal display device. Here, arrow 41 of FIGS. 5A and 41a of FIG. 5B show a direction of the long axis of the liquid crystal. In the off state of FIG. 5A, the long axis of the liquid crystal has a definite angle with respect to the pixel and common electrodes 34 and 36, and maintains the angle. On the other side, in the on state of FIG. 5B, electric field 35 is formed in a direction perpendicular to the pixel and common electrodes 34 and 36. Then, the liquid crystal (not shown) turns clockwise, so that the long axis thereof coincides with the direction of the electric field 35. Here, the extreme value of the liquid crystal in the IPS LCD device is smaller than that in the TNLCD device.

[0021] As stated above, the IPS LCD device uses the lateral electric field 35 because the pixel and common electrodes 34 and 36 are formed on the same substrate. The IPS LCD device has a wide viewing angle and low color dispersion. Specifically, the viewing angle of the IPS LCD device is about 70 degrees in the directions up, down, right, and left. In addition, the fabricating processes of this IPS LCD device are simpler than other various LCD devices.

[0022] However, the IPS LCD device has a disadvantage of color shift according to a viewing angle. FIG. 6 is a chromaticity diagram according to a viewing angle of a related art in-plane switching liquid crystal display (IPS LCD) device. In FIG. 6, standard white light has coordinate values of about 0.329 and 0.333. The color shift results from birefringence of the liquid crystal, and this is also discussed in "Advanced 18.1-inch Diagonal Super-TFT-LCDs with Mega Wide Viewing Angle and Fast Response Speed of 10 ms" of S. Endow et al., page 187, IDW 99'.

[0023] On the other hand, FIG. 7 shows a diagram of transmittance versus a viewing angle according to gray level of a related art liquid crystal display device. In FIG. 7, the gray level is divided into 8 levels. In a first level, while the transmittance at the front part, i.e. a viewing angle of 0 degrees, is zero percent, the transmittance of a viewing angle of ± 60 degrees is about 20 percent, which is larger than that of a fourth level. That is, when in the black mode of the first level, black shows at the viewing angle of 0 degrees, but white shows at the viewing angle of about ± 60 degrees. Therefore, gray inversion occurs.

SUMMARY OF THE INVENTION

[0024] Accordingly, the present invention is directed to an array substrate for an in-plane switching liquid crystal display device that substantially obviates one or more of problems due to limitations and disadvantages of the related art.

[0025] An advantage of the present invention is to provide an array substrate for an in-plane switching liquid crystal display device that has a wide viewing angle.

[0026] Another advantage of the present invention is to provide an array substrate for an in-plane switching liquid crystal display device that has low dependence on color shift and gray inversion.

[0027] Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

[0028] To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, an array substrate for an in-plane switching liquid crystal display device includes a substrate; a gate line and a data line on the substrate, wherein the gate line and the data line cross each other to define a pixel region; a thin film transistor being electrically connected to the gate line and the data line; a common line parallel to the gate line; a plurality of common electrodes perpendicularly extended from the common line; a plurality of pixel electrodes alternating with the plurality of common electrodes; and an overcoat layer over the plurality of common electrodes and the plurality of pixel electrodes, the overcoat layer having a plurality of holes.

[0029] In another aspect of the present invention, an array substrate for an in-plane switching liquid crystal display device includes a substrate; a gate line and a data line on the substrate, wherein the gate line and the data line cross each other to define a pixel region; a thin film transistor being electrically connected to the gate line and the data line; a common line parallel to the gate line; a plurality of common electrodes parallel to the common line; wherein the plurality of common electrodes are electrically connected to the common line, a plurality of pixel electrodes alternating with the plurality of common electrodes; and an overcoat layer over the plurality of common electrodes and the plurality of pixel electrodes, the overcoat layer having a plurality of holes.

[0030] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0031] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

[0032] In the drawings:

[0033] FIG. 1 is an exploded perspective view illustrating a related art liquid crystal display (LCD) device;

[0034] FIGS. 2A and 2B are schematic views conceptually showing operation modes of a related art twisted nematic (TN) mode liquid crystal display (LCD) device;

[0035] FIG. 3 is a schematic cross-sectional view of a related art in-plane switching liquid crystal display (IPS LCD) device;

[0036] FIGS. 4A and 4B are schematic views conceptually showing operation modes of a related art in-plane switching liquid crystal display (IPS LCD) device;

[0037] FIGS. 5A and 5B are schematic plan views conceptually showing operation modes of a related art in-plane switching liquid crystal display (IPS LCD) device;

[0038] FIG. 6 is a chromaticity diagram according to a viewing angle of a related art in-plane switching liquid crystal display (IPS LCD) device;

[0039] FIG. 7 is a diagram of transmittance versus a viewing angle according to gray level of a related art liquid crystal display (IPS LCD) device;

[0040] FIGS. 8A and 8B are schematic views showing path of light in single-domain and in multi-domain, respectively,

[0041] FIG. 9 is a plan view of an array substrate for a in-plane switching liquid crystal display (IPS LCD) device according to a first embodiment of the present invention;

[0042] FIG. 10 is a cross-sectional view along the line I-I of FIG. 9;

[0043] FIG. 11 is a plan view magnifying "K" of FIG. 9;

[0044] FIG. 12 is a schematic view showing the relationship between the electric field and the liquid crystal in a first embodiment of the present invention;

[0045] FIG. 13 is a schematic view showing the relationship between the electric field and the liquid crystal having negative dielectric anisotropy in a first embodiment of the present invention;

[0046] FIG. 14 is a plan view of an array substrate for an in-plane switching liquid crystal display (IPS LCD) device according to a second embodiment of the present invention;

[0047] FIG. 15 is a schematic view showing the relationship between the electric field and the liquid crystal of a second embodiment of the present invention;

[0048] FIG. 16 is a plan view of an array substrate for a in-plane switching liquid crystal display (LCD) device according to a third embodiment of the present invention;

[0049] FIG. 17 is a plan view magnifying "L" of FIG. 16;

[0050] FIG. 18 is a schematic view showing the relationship between the electric field and the liquid crystal of a third embodiment of the present invention;

[0051] FIG. 19 is a plan view of an array substrate for a in-plane switching liquid crystal display (LCD) device according to a fourth embodiment of the present invention; and

[0052] FIG. 20 is a schematic view showing the relationship between the electric field and the liquid crystal of a fourth embodiment of the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

[0053] Reference will now be made in detail to the illustrated embodiments of the present invention, which are illustrated in the accompanying drawings.

[0054] In an in-plane switching liquid crystal display device, the color shift or the gray inversion is caused by the birefringence of liquid crystal.

[0055] FIGS. 8A and 8B are schematic views showing the path of light in single-domain and in multi-domain, respectively. In single-domain shown in FIG. 8A, a liquid crystal molecule has different refractive indices according to each direction of a_1 , b_1 , and c_1 . Therefore, a birefringence phenomenon appears in the liquid crystal molecule, and the quality of display changes according to viewing angles.

[0056] Meanwhile, FIG. 8B shows the path of light in multi-domain, particularly two domains. In FIG. 8B, a first liquid crystal and a second liquid crystal are symmetric with respect to the vertical line to the substrates. Moreover, a_1 and a_2 directions parallel to each other are symmetric with respect to c_1 and c_2 directions parallel to each other with respect to the vertical line to the substrates. A refractive index of the first liquid crystal molecule to the a_1 direction has a negative value of a refractive index of the second liquid crystal molecule to the c_2 direction. Similarly, a refractive index of the first liquid crystal molecule to the c_1 direction has a negative value of a refractive index of the second liquid crystal molecule to the a_2 direction. Accordingly, the refractive indices of the a_1 and c_1 directions compensate the refractive indexes of the a_2 and c_2 directions, respectively. Therefore, there is no birefringence phenomenon in the LCD device of FIG. 8B.

[0057] An array substrate for an in-plane switching liquid crystal display (IPS LCD) device, which has the above-stated multi-domain structure, will be described hereinafter more in detail with reference to the following figures.

[0058] FIG. 9 is a plan view of an array substrate for an in-plane switching liquid crystal display (IPS LCD) device according to a first embodiment of the present invention. In FIG. 9, a gate line 150 and a common line 160 parallel to each other are formed horizontally in the context of the figure. A data line 170 extends vertically in the context of the figure and crosses the gate line 150 to define a pixel area "P". At the crossing of the gate line 150 and the data line 170, a thin film transistor "T" is formed, which includes a gate electrode 152, a source electrode 156, and a drain electrode 158. The gate electrode 152 is connected to the gate line 150 and the source electrode 156 is connected to the data line 170. An active layer 154 is formed at the crossing. In the pixel area "P", a plurality of common electrodes 162 are extended from the common line 160, and the plurality of common electrodes 162 are parallel to the data line 170. Also, a plurality of pixel electrodes 164 are formed vertically with an alternating arrangement with the plurality of the common electrodes 162 in the pixel area "P". The plurality of pixel electrodes 164 are connected to the drain electrode 158.

[0059] Next, an overcoat layer (not shown) covers the plurality of common electrodes 162 and the plurality of pixel electrodes 164. The overcoat layer has holes 192 of a hexagonal shape. The holes 192 may also take a shape such as a circle, a triangle, or a quadrangle. The overcoat layer may be made of a photosensitive material such as benzocyclobutene (BCB) or acrylic resin. The holes 192 are disposed over the common electrodes 162 or the pixel electrodes 164. The holes 192 over the common electrodes 162 make a first line and the holes 192 over the pixel electrodes 164 make a second line. The first line and the second line are spaced apart from each other. The holes 192 cause a fringe field between the common electrode 162 and the pixel electrode 164 when voltage is applied to the electrodes 162 and 164.

[0060] Subsequently, liquid crystal 194 is situated over the overcoat layer, and the liquid crystal 194 has positive dielectric anisotropy. The liquid crystal 194 was first arranged in a direction of the common electrode 162 and the pixel electrode 164, but it is not shown in FIG. 9.

[0061] On the other hand, the transmission axes of polarizers (not shown), which are arranged outside of the liquid crystal display device, are parallel and perpendicular to the electrodes 162 and 164, respectively.

[0062] In FIG. 9, when voltage is applied to the common and pixel electrodes 162 and 164, a fringe field is induced between the common and pixel electrodes 162 and 164, and the liquid crystal 194 is arranged in a direction parallel to the common and pixel electrodes 162 and 164.

[0063] FIG. 10 is a cross-sectional view along the line I-I of FIG. 9. As shown in the figure, the plurality of common electrodes 162 are formed on a substrate 100 and a gate insulator 163 covers the plurality of common electrodes 162. The plurality of pixel electrodes 164 are formed on the gate insulator 163, alternating with the plurality of the common electrodes 162. Next, an overcoat layer 165 is formed on the plurality of pixel electrodes 164 and covers the plurality of pixel electrodes 164. The overcoat layer 165 has holes 192, which are located over the common electrodes 164. The overcoat layer 165, desirably, has a smaller dielectric constant than the liquid crystal 194 of FIG. 9. Therefore, in the present invention, the dielectric constant of the overcoat layer 165 is less than about 5.

[0064] FIG. 11 is a plan view magnifying "K" of FIG. 9, and shows a fringe field formed by the holes of the overcoat layer. In FIG. 11, the overcoat layer (not shown) is divided into a first region "A" corresponding to the hole 192 and a second region "B" except for the first region "A". As the overcoat layer (not shown) has a smaller dielectric constant than the liquid crystal 194, electric lines of force in the second region "B" become denser than in the first region "A". Electric field 200 is bent according to the boundary of the hole 192, and distorted electric field 200, i.e. fringe field, is induced between the holes 192. The fringe field 200 centers the hole 192, and is substantially symmetric with respect to the common electrode 162 and a line perpendicular to the common electrode 162.

[0065] When the electric field 200 is induced, the liquid crystal 194 is rotated by the force of the electric field 200 to be parallel to the direction of the electric field 200. Accordingly, four domains, which include the liquid crystal 194 arranged differently from one another, are formed centering the hole 192.

[0066] FIG. 12 shows the relationship between the electric field and the liquid crystal in the first embodiment. FIG. 12 is similar to the upper region of the hole of FIG. 11. Here, a first arrow d_1 corresponds to a direction of the common electrode 162 or the pixel electrode 164 having a hole 192 of FIG. 11 thereon. A second arrow d_2 and a third arrow d_3 show directions of the electric field induced substantially symmetrically with respect to the first arrow d_1 . Therefore, when voltage is applied to the electrodes 162 and 164, the liquid crystal 194, which first is parallel to the first arrow d_1 , is arranged in a direction parallel to the second and third arrows d_2 and d_3 . At this time, the degree of freedom of the liquid crystal 194 is 2.

[0067] As stated above, in the present invention, a multi-domain is formed, in each of which the liquid crystal is arranged differently, and thus color shift and gray inversion according to the viewing angle decrease.

[0068] On the other hand, in the first embodiment, the liquid crystal may have negative dielectric anisotropy. FIG. 13 shows the relationship between the electric field and the liquid crystal having negative dielectric anisotropy in the first embodiment of the present invention. FIG. 13 also corresponds to the upper region of the hole of FIG. 11. First, the liquid crystal 195 is arranged in a direction perpendicular to the first arrow d_1 , respectively. When voltage is applied, the liquid crystal 195 is arranged in a direction perpendicular to the second and third arrows d_2 , and d_3 , respectively. The liquid crystal 195 is substantially symmetric with respect to the first arrow d_1 .

[0069] FIG. 14 is a plan view of an array substrate for an in-plane switching liquid crystal display (IPS LCD) device according to a second embodiment of the present invention. In FIG. 14, a gate line 250 is formed horizontally in the context of the figure. A data line 270 extends vertically in the context of the figure and crosses the gate line 250 to define a pixel area "P". At the crossing of the gate line 250 and the data line 270, a thin film transistor "T" is formed, which includes a gate electrode 252, a source electrode 256, and a drain electrode 258. Here, the gate electrode 252 is a part of the gate line 250 and the source electrode 256 is a part of the data line 270. An active layer 254 is formed at the crossing.

[0070] Next, a common line 260 parallel to the gate line 250 is formed, and a first vertical part 261a and a vertical second part 261b are extended vertically from the common line 260. In the pixel area "P", a plurality of common electrodes 262 are formed horizontally in the context of the figure spaced from each other. The plurality of common electrodes 262 are connected to the first and second vertical parts 261a and 261b. Also, a horizontal part 263, a plurality of pixel electrodes 264, a third vertical part 265a, and a fourth vertical part 265b are formed. The horizontal part 263 is parallel to the common line 260 and overlaps the common line 260. The third and fourth vertical parts 265a and 265b are extended from the common line 260, and the plurality of pixel electrodes 264, which are connected to the third and fourth vertical parts 265a and 265b, are formed horizontally in the context of the figure with an alternating arrangement with the plurality of the common electrodes 262. The third vertical part 265a is connected to the drain electrode 258.

[0071] Next, an overcoat layer (not shown) covers the plurality of common electrodes 262 and the plurality of pixel electrodes 264. The overcoat layer has holes 292 of a

hexagonal shape, and the holes 292 may take shapes such as a circle, a triangle, or a quadrangle. The overcoat layer may be made of a photosensitive material such as benzocyclobutene (BCB) or acrylic resin. The holes 292 are disposed over the common electrodes 262 or the pixel electrodes 264. The holes 292 over the common electrodes 262 make a first line and the holes 292 over the pixel electrodes 264 make a second line. The first line and the second line are spaced apart from each other. The holes 292 cause a fringe field to occur between the common electrode 262 and the pixel electrode 264 when voltage is applied to the electrodes 262 and 264.

[0072] Subsequently, liquid crystal 294 is situated over the overcoat layer, and the liquid crystal 294 has positive dielectric anisotropy. The liquid crystal 294 was first arranged in a direction of the common electrode 262 and the pixel electrode 264, but it is not shown in FIG. 14.

[0073] In FIG. 14, when voltage is applied to the common and pixel electrodes 262 and 264, a fringe field is induced between the common and pixel electrodes 262 and 264, and the liquid crystal 294 is arranged in a direction parallel to the common and pixel electrodes 262 and 264.

[0074] FIG. 15 shows the relationship between the electric field and the liquid crystal in the second embodiment. The liquid crystal 295 has a negative dielectric anisotropy. Here, a first arrow d_4 corresponds to the common electrode 262 or the pixel electrode 264 having a hole 292 of FIG. 14 thereon. A second arrow d_5 and a third arrow d_6 show directions of the electric field induced substantially symmetrically with respect to the first arrow d_4 . Therefore, when voltage is applied to the electrodes 262 and 264, the liquid crystal 294, which first is perpendicular to the first arrow d_4 , is arranged in a direction perpendicular to the second and third arrows d_5 and d_6 . At this time, the degree of freedom of the liquid crystal 294 is 2.

[0075] Next, FIG. 16 is a plan view of an array substrate for an in-plane switching liquid crystal display (LCD) device according to a third embodiment of the present invention. In FIG. 16, a gate line 350 and a common line 360 parallel to each other are formed horizontally in the context of the figure. A data line 370 extends vertically in the context of the figure and crosses the gate line 350 to define a pixel area "P". At the crossing of the gate line 350 and the data line 370, a thin film transistor "T" is formed, which includes a gate electrode 352, a source electrode 356, and a drain electrode 358. The gate electrode 352 is connected to the gate line 350 and the source electrode 356 is connected to the data line 370. An active layer 354 is formed at the crossing. In the pixel area "P", a plurality of common electrodes 362 are extended from the common line 360, and the plurality of common electrodes 362 are parallel to the data line 370. Also, a plurality of pixel electrodes 364 are formed vertically with an alternating arrangement with the plurality of the common electrodes 362 in the pixel area "P". The plurality of pixel electrodes 364 are connected to the drain electrode 358.

[0076] Next, an overcoat layer (not shown) covers the plurality of common electrodes 362 and the plurality of pixel electrodes 364. The overcoat layer has holes 392 of a shape such as a quadrangle. The overcoat layer may be made of a photosensitive material such as benzocyclobutene (BCB) or acrylic resin. The holes 392 are disposed between the

common electrodes 362 and the pixel electrodes 364, and have a length along a first direction and a width. Here, the first direction is inclined with respect to the common electrodes 362 and the pixel electrodes 364. The holes 392 are substantially symmetric with respect to the pixel electrodes 364 and the common electrodes 362.

[0077] Subsequently, liquid crystal 394 is situated over the overcoat layer, and the liquid crystal 394 has positive dielectric anisotropy. The liquid crystal 394 was first arranged in a direction of the common electrode 362 and the pixel electrode 364, but it is not shown in FIG. 16.

[0078] In FIG. 16, when voltage is applied to the common and pixel electrodes 362 and 364, electric field is induced in a direction parallel to the first direction between the common and pixel electrodes 362 and 364, and the liquid crystal 394 is arranged in a direction of the electric field, that is in the first direction.

[0079] FIG. 17 is a plan view magnifying "L" of FIG. 16, and shows the electric field induced by the holes of the overcoat layer. In FIG. 17, the overcoat layer (not shown) is divided into a first region "A" corresponding to the hole 392 and a second region "B" except for the first region "A". Here, electric lines of force in the first region "A" become denser than in the second region "B", and the electric lines of force in the first region "A" incline to the long direction of the hole 392. As the liquid crystal (not shown) has a positive dielectric anisotropy, the liquid crystal is arranged in a direction parallel to the electric field 300.

[0080] On the other hand, like the first embodiment, the liquid crystal may have negative dielectric anisotropy. FIG. 18 shows the relationship between the electric field and the liquid crystal having negative dielectric anisotropy in the third embodiment of the present invention. Here, a first arrow d_1 corresponds to the common electrode 362 or the pixel electrode 364 having a hole 392 of FIG. 16 thereon. A second arrow d_2 and a third arrow d_3 show directions of the electric field induced substantially symmetrically with respect to the first arrow d_1 . When voltage is applied, the liquid crystal 395, which first is perpendicular to the first arrow a_1 , is arranged in a direction perpendicular to the second and third arrows d_2 and d_3 , respectively. The liquid crystal 395 is substantially symmetric with respect to the first arrow d_1 .

[0081] In the third embodiment, as there is no disclination from a fringe field, and aperture ratio and brightness increase. Also, response time is short and force of restitution is large because of a strong fringe field.

[0082] FIG. 19 is a plan view of an array substrate for an in-plane switching liquid crystal display (IPS LCD) device according to a fourth embodiment of the present invention. In FIG. 19, a gate line 450 is formed horizontally in the context of the figure. A data line 470 extends vertically in the context of the figure and crosses the gate line 450 to define a pixel area "P". At the crossing of the gate line 450 and the data line 470, a thin film transistor "T" is formed, which includes a gate electrode 452, a source electrode 456, and a drain electrode 458. Here, the gate electrode 452 is a part of the gate line 450 and the source electrode 456 is a part of the data line 470. An active layer 454 is formed at the crossing.

[0083] Next, a common line 460 parallel to the gate line 450 is formed, and a first vertical part 461a and a vertical

second part **461b** are extended vertically from the common line **460**. In the pixel area "P", a plurality of common electrodes **462** is formed horizontally in the context of the figure spaced from each other. The plurality of common electrodes **462** are connected to the first and second vertical parts **461a** and **461b**. Also, a horizontal part **463**, a plurality of pixel electrodes **464**, a third vertical part **465a**, and a fourth vertical part **465b** are formed. The horizontal part **463** is parallel to the common line **460** and overlaps the common line **460**. The third and fourth vertical parts **465a** and **465b** are extended from the common line **460**, and the plurality of pixel electrodes **464**, which are connected to the third and fourth vertical parts **465a** and **465b**, are formed horizontally in the context of the figure with an alternating arrangement with the plurality of the common electrodes **462**. The third vertical part **465a** is connected to the drain electrode **458**.

[0084] Next, an overcoat layer (not shown) covers the plurality of common electrodes **462** and the plurality of pixel electrodes **464**. The overcoat layer has holes **492** of a shape such as a quadrangle. The overcoat layer may be made of a photosensitive material such as benzocyclobutene (BCB) or acrylic resin. The holes **492** are disposed with between the common electrodes **462** and the pixel electrodes **464**, and have a length along a first direction and a width. Here, the first direction is inclined with respect to the common electrodes **462** and the pixel electrodes **464**. The holes **492** are substantially symmetric with respect to the pixel electrodes **464** and the common electrodes **462**.

[0085] Subsequently, liquid crystal **494** is situated over the overcoat layer, and the liquid crystal **494** has positive dielectric anisotropy. The liquid crystal **494** was first arranged in a direction of the common electrode **462** and the pixel electrode **464**, but it is not shown in FIG. 19.

[0086] In FIG. 19, when voltage is applied to the common and pixel electrodes **462** and **464**, electric field is induced in a direction parallel to the first direction between the common and pixel electrodes **462** and **464**, and the liquid crystal **494** is arranged in a direction of the electric field, that is in the first direction.

[0087] FIG. 20 shows the relationship between the electric field and the liquid crystal in the fourth embodiment. Here, the liquid crystal has negative dielectric anisotropy. A first arrow d_4 corresponds to the common electrode **462** or the pixel electrode **464** having a hole **492** of FIG. 19 thereon. A second arrow d_5 and a third arrow d_6 show directions of the electric field induced substantially symmetrically with respect to the first arrow d_4 . Therefore, when voltage is applied to the electrodes **462** and **464**, the liquid crystal **495**, which first is perpendicular to the first arrow d_4 , is arranged in a direction perpendicular to the second and third arrows d_5 and d_6 .

[0088] It will be apparent to those skilled in the art that various modifications and variations can be made in the fabrication and application of the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

1-20. (canceled)

21. A method for fabricating an array substrate for an in-plane switching liquid crystal display device, comprising:

forming a gate line and a data line on a substrate, the gate line and the data line crossing each other to define a pixel region;

forming a thin film transistor on the substrate, the thin film transistor being electrically connected to the gate and data lines;

forming a plurality of common electrodes perpendicularly extended from the common line;

forming a gate insulator over the plurality of common electrodes;

forming a plurality of pixel electrodes on the gate insulator, wherein the plurality of pixel electrodes form an alternating pattern with the plurality of common electrodes; and

forming an overcoat layer over the plurality of common and pixel electrodes, the overcoat layer having a plurality of holes.

22. The method according to claim 21, further comprising forming a liquid crystal layer over the overcoat layer, the overcoat layer having a smaller dielectric constant than the liquid crystal layer.

23. The method according to claim 22, wherein each hole is formed in a shape of one of a circle, a triangle, a quadrangle, and a hexagon.

24. The method according to claim 21, wherein the plurality of holes are formed between each of the plurality of common electrodes or each of the plurality of pixel electrodes.

25. The method according to claim 24, wherein the plurality of holes have a length along a first direction and a width, the first direction being inclined with respect to the plurality of common and pixel electrodes.

26. The method according to claim 25, wherein the plurality of holes between each of the pixel electrodes are formed substantially symmetric with respect to each other.

27. The method according to claim 21, further comprising forming a liquid crystal layer over the overcoat layer, the liquid crystal layer having one of positive dielectric anisotropy and negative dielectric anisotropy.

28. The method according to claim 21, wherein the overcoat layer is formed of one of benzocyclobutene and acrylic resin.

29. The method according to claim 21, wherein the plurality of holes are formed over the plurality of common and pixel electrodes.

30. The method according to claim 29, wherein the plurality of holes over the plurality of common electrodes form a first line and the plurality of holes over the plurality of pixel electrodes form a second line.

31. The method according to claim 30, wherein the plurality of holes of the first line are spaced apart from the plurality of holes of the second line.

32. The method according to claim 21, further comprising forming a gate insulator on the plurality of common electrodes.

33. The method according to claim 32, wherein the plurality of holes expose a portion of the gate insulator.

34. A method for fabricating an array substrate for an in-plane switching mode liquid crystal display device, comprising:

forming a gate line and a data line on a substrate, the gate line and the data line crossing each other to define a pixel region;

forming a thin film transistor on the substrate, the thin film transistor being electrically connected to the gate and data lines;

forming a common line parallel to the gate line;

forming a plurality of common electrodes parallel to the common line, the plurality of common electrodes being electrically connected to the common line;

forming a plurality of pixel electrodes on the substrate in an alternating pattern with the plurality of common electrodes; and

forming an overcoat layer over the plurality of common and pixel electrodes, the overcoat layer having a plurality of holes.

35. The method according to claim 34, further comprising forming a liquid crystal layer over the overcoat layer, the overcoat layer having a smaller dielectric constant than the liquid crystal layer.

36. The method according to claim 34, wherein each hole is formed in a shape of one of a circle, a triangle, a quadrangle, and a hexagon.

37. The method according to claim 34, wherein the plurality of holes are formed between each of the plurality of common or each of the plurality of pixel electrodes.

38. The method according to claim 37, wherein the plurality of holes have a length along a first direction and a width, the first direction being inclined with respect to the plurality of common and pixel electrodes.

39. The method according to claim 38, wherein the plurality of holes between each of the pixel electrodes are formed substantially symmetric with respect to each other the plurality of common and pixel electrodes.

40. The method according to claim 34, further comprising forming a liquid crystal layer over the overcoat layer, the liquid crystal layer having one of positive dielectric anisotropy and negative dielectric anisotropy.

41. The method according to claim 34, wherein the overcoat layer is made of one of benzocyclobutene and acrylic resin.

42. The method according to claim 34, wherein the plurality of holes are formed over the plurality of common and pixel electrodes.

43. The method according to claim 42, wherein the plurality of holes over the plurality of common electrodes form a first line and the plurality of holes over the plurality of pixel electrodes form a second line.

44. The method according to claim 43, wherein the plurality of holes of the first line are spaced apart from the plurality of holes of the second line.

45. The method according to claim 34, further comprising forming a gate insulator on the plurality of common electrodes.

46. The method according to claim 34, wherein the plurality of holes expose a portion of the gate insulator.

* * * * *

专利名称(译)	制造具有多畴的面内切换液晶显示装置的阵列基板的方法		
公开(公告)号	US20050157239A1	公开(公告)日	2005-07-21
申请号	US11/081671	申请日	2005-03-17
[标]申请(专利权)人(译)	YOO张真		
申请(专利权)人(译)	YOO JANG-JIN		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	YOO JANG JIN		
发明人	YOO, JANG-JIN		
IPC分类号	G02F1/1333 G02F1/1343		
CPC分类号	G02F1/134363 G02F1/133707		
优先权	1020010045473 2001-07-27 KR		
其他公开文献	US7092060		
外部链接	Espacenet USPTO		

摘要(译)

一种制造面内切换液晶显示装置的阵列基板的方法，包括在基板上形成栅极线和数据线，栅极线和数据线彼此交叉以限定像素区域，形成薄膜晶体管电连接到栅极线和数据线，并形成与栅极线平行的公共线。形成多个公共电极以从公共线垂直延伸。多个像素电极与多个公共电极以交替图案形成，并且在多个公共电极和多个像素电极上形成外涂层，该外涂层具有多个孔。

