



US007929082B2

(12) **United States Patent**  
**Jang et al.**

(10) **Patent No.:** **US 7,929,082 B2**  
(45) **Date of Patent:** **\*Apr. 19, 2011**

(54) **TRANSMISSIVE AND REFLECTIVE TYPE LIQUID CRYSTAL DISPLAY**

(75) Inventors: **Yong-Kyu Jang**, Suwon-si (KR);  
**Hyung-Guel Kim**, Yongin-si (KR)

(73) Assignee: **Samsung Electronics, Co., Ltd.**,  
Suwon-Si (KR)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1154 days.  
  
This patent is subject to a terminal disclaimer.

(21) Appl. No.: **10/985,780**

(22) Filed: **Nov. 10, 2004**

(65) **Prior Publication Data**

US 2005/0062914 A1 Mar. 24, 2005

**Related U.S. Application Data**

(63) Continuation of application No. 10/183,143, filed on Jun. 26, 2002, now Pat. No. 6,831,719.

(30) **Foreign Application Priority Data**

Dec. 18, 2001 (KR) ..... 2001-80714

(51) **Int. Cl.**  
**G02F 1/1335** (2006.01)

(52) **U.S. Cl.** ..... **349/114**; 349/96

(58) **Field of Classification Search** ..... 349/114  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,882,774 A	3/1999	Jonza et al.	428/212
6,124,971 A *	9/2000	Ouderkirk et al.	359/487
6,262,842 B1	7/2001	Ouderkirk et al.	359/487
6,577,361 B1 *	6/2003	Sekiguchi et al.	349/96

6,831,719 B2 *	12/2004	Jang et al.	349/114
2001/0019385 A1	9/2001	Song et al.	
2001/0020990 A1	9/2001	Moon	349/96
2002/0030776 A1 *	3/2002	Khan et al.	349/114

**FOREIGN PATENT DOCUMENTS**

CN	1050939	4/1991
CN	1161106	10/1997
JP	9-507308	7/1997
KR	199983623	11/1999

**OTHER PUBLICATIONS**

PCT International Search Report dated Jun. 30, 2003.

\* cited by examiner

*Primary Examiner* — Richard H Kim

(74) *Attorney, Agent, or Firm* — F. Chau & Associates, LLC

(57) **ABSTRACT**

Disclosed is a transmissive and reflective type LCD. In the LCD, a second substrate faces a first substrate. A liquid crystal layer is formed between the first substrate and the second substrate. A first polarizing plate is formed on an outer surface of the first substrate. A second polarizing plate is formed on an outer surface of the second substrate. A backlight is arranged for irradiating incident light onto the polarizing plate. A transparent transfective film is arranged between the first polarizing plate and the backlight for partially reflecting and partially transmitting the incident light. The transparent transfective film includes at least a first layer and a second layer, the first and second layers having different refractivity indexes from each other and are alternatively stacked. By a restoring process occurring between the transfective film and the backlight, a predetermined amount of the incident light is transmitted through the transfective film repeatedly, so that transmissivity and light efficiency are enhanced.

**23 Claims, 17 Drawing Sheets**




FIG. 1  
(PRIOR ART)




FIG. 2A  
(PRIOR ART)





FIG. 2B  
(PRIOR ART)



ON

FIG. 3A  
(PRIOR ART)




FIG. 3B  
(PRIOR ART)




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B





FIG. 11



## TRANSMISSIVE AND REFLECTIVE TYPE LIQUID CRYSTAL DISPLAY

### CROSS-REFERENCE TO RELATED APPLICATION

This application is a Continuation of U.S. patent application Ser. No. 10/183,143, filed on Jun. 26, 2002, now U.S. Pat. No. 6,831,719 the contents of which are fully incorporated herein by reference.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates to a liquid crystal display, and more particularly, to a transmissive and reflective type liquid crystal display in which the display operation is carried out in reflection mode and transmission mode.

#### 2. Description of the Related Art

Liquid crystal displays (LCDs) have become displays of choice among the various developed flat panel type displays because they are much slimmer and lighter than other types of displays. They also require lower driving voltage and lower power consumption.

LCD displays are classified as transmission type which display images using an external light source such as a backlight, as reflection type which display an image using natural light, and transmissive and reflective type which display in a transmission mode using an internal light source provided in the display itself at indoors or a dark place where an external light source does not exist and the display operates in a reflection mode to display images by reflecting external incident light in a high brightness environment such as at outdoors.

LCDs can also be classified depending on the way they are driven. For example, In the passive matrix type, pixels in the LCDs are driven using a root-mean-square (rms) of a difference between voltages applied to signal lines and scanning lines, while a line addressing in which a signal voltage is applied to all of the pixels at the same time is carried out. In the active matrix type, pixels are driven by a switching element such as a MIM (Metal-insulator-metal) device or a thin film transistor.

FIG. 1 is a sectional view of a conventional transmissive and reflective type LCD, and shows an active matrix type LCD using the thin film transistor.

Referring to FIG. 1, the conventional transmissive and reflective type LCD includes a first substrate 10, a second substrate 40 arranged facing the first substrate 10, a liquid crystal layer 50 formed between the first substrate 10 and the second substrate 40, and a light source, i.e., a backlight assembly 60 disposed at a rear side of the first substrate 10.

The first substrate 10 includes a first insulating substrate 11, a thin film transistor 25 formed on the first insulating substrate 11, a passivation film 30 having a contact hole 32 for exposing a part of the thin film transistor 25, a transparent electrode 34, and a reflection electrode 36. The thin film transistor 25 includes a gate electrode 12, a gate insulating film 14, an active pattern 16, an ohmic contact pattern 18, a source electrode 20, and a drain electrode 22. The transparent electrode 34 functions as a pixel electrode for transmitting light that is generated from the backlight 60 and is then incident through the first substrate 10. The transparent electrode 34 is connected to the thin film transistor 25 formed on every unit pixel region on the first substrate 10. The reflection electrode 36 reflects external light that is incident through the second substrate 40 and at the same time functions as another

pixel electrode. The transparent electrodes 34 include regions of a transmission part T and a reflection part R for reflecting the external light incident through the second substrate 40.

The second substrate 40 includes a second insulating substrate 42, a color filter 44 comprised of RGB pixels for displaying colors while light is transmitted therethrough, a black matrix 46 for preventing the light from being leaked between the pixels, and a transparent common electrode 48.

The liquid crystal layer 50 is made of 90° twisted nematic (TN) liquid crystal, and has an approximately 0.24 of  $\Delta n d$  which is a product of anisotropy  $\Delta n$  in refractive index and thickness  $d$  of the liquid crystal layer 50.

Also, according to an alignment direction of the liquid crystal molecules, a first polarizing plate 54 and a second polarizing plate 58 are respectively attached to external surfaces of the first and second substrates 10 and 40 so as to transmit only polarized light in a specific direction. The first and second polarizing plates 54 and 58 are all linear polarizers in which each polarizing axis of the first and second polarizing plates 54 and 58 is orthogonal to each other.

Between the first substrate 10 and the first polarizing plate 54, and between the second substrate 40 and the second polarizing plate 58, there are respectively arranged a first  $\frac{1}{4}$  wavelength phase difference plate 52 and a second  $\frac{1}{4}$  wavelength phase difference plate 56. Each of the  $\frac{1}{4}$  wavelength phase difference plates 52 and 56 functions to convert linearly polarized light to circularly polarized light, or vice versa by causing a phase difference of  $\frac{1}{4}$  wavelength between two polarization components that are orthogonal to each other and are parallel to the optical axes of the  $\frac{1}{4}$  wavelength phase difference plates 52 and 56.

Hereinafter, there are respectively described operations in the reflection mode and the transmission mode in the conventional transmissive and reflective type LCD shown in FIG. 1.

FIGS. 2A and 2B are schematic views for illustrating an operation of the conventional LCD in the reflection mode.

First, when a pixel voltage is not applied (OFF), as shown in FIG. 2A, light that is incident from an outside is transmitted through the second polarizing plate 58, so that the light is linearly polarized in a direction parallel to the polarizing axis of the second polarizing plate 58. The linearly polarized light is transmitted through the second  $\frac{1}{4}$  wavelength phase difference plate 56, so that the linearly polarized light is converted onto left-handed circularly polarized light. The left-handed circularly polarized light is transmitted through the liquid crystal layer 50, so that the left-handed circularly polarized light is linearly polarized in a direction vertical to the polarizing axis of the second polarizing plate 58, and is then incident onto the reflection electrode 36. The linearly polarized light, which is reflected by the reflection electrode 36, is transmitted through the liquid crystal layer 50, so that the linearly polarized light is converted onto the left-handed circularly polarized light. The left-handed circularly polarized light is transmitted through the second  $\frac{1}{4}$  wavelength phase difference plate 56, so that the left-handed circularly polarized light is linearly polarized in a direction parallel to the polarizing axis of the second polarizing plate 58. And then, the linearly polarized light is transmitted through the second polarizing plate 58, so that a white image is displayed.

When a maximum pixel voltage is applied (ON), as shown in FIG. 2B, light that is incident externally is transmitted through the second polarizing plate 58, so that it is linearly polarized in a direction parallel to the polarizing axis of the second polarizing plate 58. The linearly polarized light is transmitted through the second  $\frac{1}{4}$  wavelength phase difference plate 56, so that it is converted onto left-handed circularly polarized light. The left-handed circularly polarized

light is transmitted through the liquid crystal layer 50 without variation in the polarization state, and is then incident onto the reflection electrode 36. The light, which is incident onto the reflection electrode 36, is reflected by the reflection electrode 36, so that it is converted to right-handed circularly polarized light and the converted right-handed circularly polarized light is transmitted through the liquid crystal layer 50. Thus, the right-handed circularly polarized light, which has been passed through the liquid crystal layer 50, is transmitted through the second ¼ wavelength phase difference plate 56, so that it is linearly polarized in a direction perpendicular to the polarizing axis of the second polarizing plate 58. The linearly polarized light is shielded by the second polarizing plate 58, so that a black image is displayed.

FIGS. 3A and 3B are schematic views for illustrating an operation mechanism of the transmission mode.

When a pixel voltage is not applied (OFF), as shown in FIG. 3A, light that is irradiated from a backlight disposed below the first polarizing plate 54 is incident onto the first polarizing plate 54, and only light propagating in a direction parallel to the polarizing axis of the first polarizing plate 54 is transmitted through the first polarizing plate 54. At this time, since the polarizing axis of the first polarizing plate 54 is perpendicular to that of the second polarizing plate 58, the light that has been passed through the first polarizing plate 54 is converted onto light linearly polarized in a direction perpendicular to the polarizing axis of the second polarizing plate 58. The linearly polarized light is converted onto a right-handed circularly polarized light by a first ¼-wavelength phase difference plate 52. The right-handed circularly polarized light is transmitted through a transparent electrode 34, and is then incident to a liquid crystal layer 50. The right-handed circularly polarized light is transmitted through the liquid crystal layer 50, so that it is linearly polarized in a direction parallel to the polarizing axis of the second polarizing plate 58. The linearly polarized light is transmitted through a second ¼-wavelength phase difference plate 56, so that it is converted onto the right-handed circularly polarized light. At this time, since only a light component propagating in a direction parallel to the polarizing axis of the second polarizing plate 58 can be transmitted through the second polarizing plate 58, only about 50% of the right-handed circularly polarized light is transmitted through the second polarizing plate 58. Accordingly, there is a light loss of about 50%, and an image having a moderate brightness is displayed.

Meanwhile, although not shown in the drawings, an optical path of the incident light becomes different at a region where a metal layer, such as the gate line, the data line, or the reflection electrode exists in the transmission mode. In other words, light that is incident from the backlight is transmitted through the first polarizing plate 54, so that it is linearly polarized in a direction parallel to the polarizing axis of the first polarizing plate 54. The linearly polarized light is transmitted through the first ¼ wavelength phase difference plate 52, so that it is right-handed circularly polarized. The right-handed circularly polarized light is reflected by metal layers, and become left-handed circularly polarized. Then, the left-handed circularly polarized light is transmitted through the first ¼ wavelength phase difference plate 52, so that it is linearly polarized in a direction parallel to the polarizing axis of the first polarizing plate 54. Accordingly, the linearly polarized light is absorbed in the first polarizing plate 54, and does not return to the backlight. Thus, the light reflected by the metal layers is not reproduced and disappears, so that an overall light efficiency is lowered.

When a maximum pixel voltage is applied (ON), as shown in FIG. 3B, light that is irradiated from a backlight disposed

below the first polarizing plate 54 is incident onto the first polarizing plate 54, so that only light propagating in a direction parallel to the polarizing axis of the first polarizing plate 54 is transmitted through the first polarizing plate 54. The light linearly polarized by the first polarizing plate 54 is converted into a right-handed circularly polarized light after being transmitted through the first ¼ wavelength phase difference plate 52. The right-handed circularly polarized light is transmitted through the transparent electrode 34, and is then incident onto the liquid crystal layer 50. The right-handed circularly polarized light is transmitted through the liquid crystal layer 50 without variation in the polarization state, and is linearly polarized in a direction orthogonal to the polarizing axis of the second polarizing plate 58 after being transmitted through the second ¼ wavelength phase difference plate 56. Afterwards, the light linearly polarized in the direction orthogonal to the polarizing axis of the second polarizing plate 58 is not transmitted to the second polarizing plate 58, so that a dark image is displayed.

As described above, since the conventional transmissive and reflective type LCD has to be provided with the wide band ¼ wavelength phase difference plates 52 and 56 covering an overall frequency band of the visible ray, as well as the first and second polarizing plates 54 and 58 with respect to each of the first and second substrates 10 and 40, manufacturing cost is increased as compared with the transmission type LCD. Also, since the polarization characteristic in the transmission mode causes light loss of about 50%, there are drawbacks in that a light transmissivity decreases by about 50% and contrast ratio (C/R) is lowered.

Further, since  $\Delta n_d$  of the liquid crystal layer 50 is only about 0.24  $\mu\text{m}$  which is a half of  $\Delta n_d$  (about 0.48  $\mu\text{m}$ ) of the conventional transmission type LCD, the cell gap of the liquid crystal cell should be decreased to a level of about 3  $\mu\text{m}$ , and the refractive anisotropy  $\Delta n$  of the liquid crystal also should be decreased. Accordingly, there is a need for a transmissive and reflective type LCD device and method which avoids aforementioned problems.

#### SUMMARY OF THE INVENTION

Accordingly, the present invention is to solve the aforementioned problems of the conventional art, and it is an object of the present invention to provide a transmissive and reflective type LCD capable of simplifying a structure of a liquid crystal cell and decreasing light loss in the transmission mode.

In one aspect, there is provided a transmissive and reflective type LCD comprising a first substrate, a second substrate, a liquid crystal layer, a first polarizing plate, a second polarizing plate, a backlight, and a transparent transfective film. In the transmissive and reflective type LCD, the second substrate has an inner surface that is arranged facing the first substrate, and the liquid crystal layer is formed between the first substrate and the second substrate. The first polarizing plate is formed on an outer surface of the first substrate. The second polarizing plate is formed on an outer surface of the second substrate, the outer surface being opposite to the inner surface of the second substrate. The backlight is arranged for irradiating incident light onto the first polarizing plate. The transparent transfective film is arranged between the first polarizing plate and the backlight for partially reflecting and partially transmitting the incident light. The transparent transfective film includes at least a first layer and a second layer having different refractivity indexes from each other and are alternatively stacked.

According to another aspect of the invention, there is provided a transmissive and reflective type LCD for partially reflecting and transmitting incident light, comprising an LC cell, a first polarizing plate, a second polarizing plate, a backlight and a transparent transfective film. The LC cell includes a first substrate, a second substrate having an inner surface that is arranged to face the first substrate, and a liquid crystal layer formed between the first substrate and the second substrate. The first polarizing plate is formed on an outer surface of the first substrate. The second polarizing plate is formed on an outer surface of the second substrate that oppositely faces the inner surface of the second substrate. The backlight is arranged at a rear side of the first polarizing plate. The transparent transfective film is arranged between the first polarizing plate and the backlight, and has a plurality of layers in which a first layer and a second layer having different refractivity indexes from each other. The transmissive and reflective type LCD has a reflection light path along which the incident light is incident onto the LC cell from a front side of the LC cell, is reflected by the transfective film, and is output through the front side of the LC cell. And, The transmissive and reflective type LCD has a transmission light path along which the incident light is incident onto the LC cell from a rear side of the LC cell, is transmitted through the transfective film, and is output through the front side of the LC cell.

The transmissive and reflective type LCD of the invention does not require a reflection electrode within LC cell or a  $\frac{1}{4}$ -wavelength phase difference plate on each of the upper substrate (second substrate) and the lower substrate (first substrate). Hence, compared with the conventional transmissive and reflective type LCD, the transmissive and reflective type LCD of the present invention is simpler and more easily made.

Further, it is possible that the transfective film of partially being transmitted and reflecting incident light performs both functions of the reflection electrode and the transparent electrode at the same time, and a recycling process of light is lastingly generated, so that light loss is not generated in the transmission mode. Accordingly, compared with the conventional transmissive and reflective type LCD, the transmissive and reflective type LCD of the invention has an enhanced transmissivity. Also, since the transmissive and reflective type LCD of the invention does not utilize the  $\frac{1}{4}$  wavelength phase difference plate, the light that is incident from the backlight and is then reflected by metal regions of LC cell is recycled and again used, so that it becomes possible to enhance an overall light efficiency.

Furthermore, since the optical conditions applied to the liquid crystal of the conventional transmissive and reflective type LCD can be identically applied to that of the transmissive and reflective type LCD of the present invention, there is no degradation in reliability.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The above objects and other advantages of the present invention will become more apparent by describing in detail exemplary embodiments thereof with reference to the attached drawings in which:

FIG. 1 is a sectional view of a conventional transmissive and reflective type LCD;

FIGS. 2A and 2B are schematic views for illustrating a conventional transmissive and reflective type LCD of FIG. 1 in a reflection mode;

FIGS. 3A and 3B are schematic views for illustrating a transmissive and reflective type LCD of FIG. 1 in a transmission mode;

FIG. 4 is a sectional view of a transmissive and reflective type LCD in accordance with an embodiment of the present invention;

FIG. 5 is a schematic view showing a structure of the transfective film shown in FIG. 4;

FIGS. 6A and 6B are sectional views for illustrating a light scattering layer that is applicable to the transmissive and reflective type LCD of FIG. 4;

FIGS. 7A and 7B are schematic views for illustrating the transmissive and reflective type LCD of FIG. 4 applied in a reflection mode;

FIGS. 8A and 8B are schematic views for illustrating the transmissive and reflective type LCD of FIG. 4 applied in a transmission mode;

FIGS. 9A and 9B are schematic views for illustrating the transmissive and reflective type LCD of FIG. 4 applied in a reflection mode;

FIGS. 10A and 10B are schematic views for illustrating the transmissive and reflective type LCD of FIG. 4 applied in a transmission mode; and

FIG. 11 is a sectional view of a transmissive and reflective type LCD in accordance with another embodiment of the present invention.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Now, exemplary embodiments of the present invention will be described in detail with reference to the annexed drawings.

FIG. 4 is a sectional view of a transmissive and reflective type LCD in accordance with an embodiment of the present invention.

Referring to FIG. 4, the transmissive and reflective type LCD includes a first substrate 110, a second substrate 130 of which an inner surface is arranged facing the first substrate 110, and a liquid crystal layer 150 formed between the first substrate 110 and the second substrate 130.

The first and second substrates 110 and 130 are preferably manufactured using a glass substrate.

A first transparent electrode 115 is formed on the inner surface of the first substrate 110. Preferably, the first transparent electrode 115 is formed of conductive oxide film such as indium tin oxide (ITO). Preferably, the first transparent electrode 115 is elongated in a first direction, and serves as a signal electrode that is repeatedly arranged in a second direction orthogonal to the first direction.

A first polarizing plate 155 is disposed on the outer surface of the first substrate 110. A second polarizing plate 165 is formed on an outer surface of the second substrate 130, opposite the inner surface of the second substrate 130. The first and second polarizing plates 155 and 165 function to absorb polarized light and to transmit other polarized light, thereby allowing incident light to be transmitted in a specific direction. The first and second polarizing plates 155 and 165 are linear polarizers of which polarizing axes are arranged to be orthogonal to each other.

A backlight 170 is installed at a rear side of the first polarizing plate 155.

A second transparent electrode 135 made of conductive oxide film such as ITO is formed on the inner surface of the second substrate 130 facing the first substrate 110. Preferably, the second transparent electrode 135 serves as a scanning electrode that is repeatedly arranged in a second direction and is elongated in the first direction. In other words, in a passive matrix type LCD, the first transparent electrode 115 of the first substrate 110 and the second transparent electrode 135 of the second substrate 130 are arranged to be orthogonal to each

other such that they are used as the signal electrode and scanning electrode, respectively.

The liquid crystal layer **150** is made of 270° super twisted nematic (STN) liquid crystal. Alternatively, the liquid crystal layer **150** can be made of 90° twisted nematic (TN) liquid crystal. One skilled in the art readily appreciates that the passive matrix type LCD uses STN liquid crystal while the active matrix type LCD uses TN liquid crystal.

According to an embodiment of the present embodiment, the liquid crystal layer **150** has an  $\Delta n$  of about 0.2  $\mu\text{m}$  to about 0.6  $\mu\text{m}$  that is a product of a refractive anisotropy  $\Delta n$  and a thickness  $d$  of the liquid crystal layer **150**, preferably about 0.48  $\mu\text{m}$ . The value of about 0.48  $\mu\text{m}$  allows the LCD of the present invention to identically use an LC optical condition of the conventional transmission type LCD without modification, thereby preventing the reliability of the liquid crystal from being lowered.

A transfective film **160** is disposed between the first polarizing plate **155** and the backlight **170**. The transfective film **160** includes at least two transparent layers having a different refractive index from each other. A first layer **161** and a second layer **162** are preferably alternatively stacked as shown in FIG. 5. The transparent transfective film **160** functions to partially reflect and transmit incident light. Accordingly, the transmissive and reflective type LCD in accordance with an embodiment of the invention has a reflection light path **180** and a transmission light path **185**. In the reflection light path, incident light is incident toward the second substrate **130**, is transmitted through the first substrate **110**, is reflected by the transfective film **160**, and is output through the second substrate **130**. In the transmission light path **185**, incident light is incident from the backlight onto the transfective film **160** and the first substrate **110**, and is output through the second substrate **130**.

Hereinafter, the structure and operations of the transfective film **160** are described.

Referring to FIG. 5, when it is assumed that the transfective film **160** has a film thickness direction of z-axis and a film plane of x-y plane, the transfective film **160** according to an aspect of the present invention is characterized in that the first layer **161** thereof has a refractive anisotropy within the film plane, e.g., x-y plane, and the second layer **162** does not have a refractive anisotropy within the film plane.

The transfective film **160** has various transmissivity and reflectivity characteristics depending on polarizing state and direction of the incident light. For instance, when it is assumed that a direction parallel to an elongated direction of the transfective film **160** is x-direction and a direction perpendicular to the elongated direction is y-direction, each of the first layer **161** having a high refractivity and refractive anisotropy within the film plane and the second layer **162** not having refractive anisotropy have three main refractive indexes of  $n_x$ ,  $n_y$ , and  $n_z$  that satisfy the following relationships (1):

$$\begin{aligned} n_{1x} &= n_{1z} \neq n_{1y}; \\ n_{2x} &= n_{2y} = n_{2z}; \\ n_{1x} &\neq n_{2x}; \\ n_{1y} &\neq n_{2y}; \text{ and} \\ |n_{1x} - n_{2x}| &< |n_{1y} - n_{2y}| \end{aligned} \quad (1).$$

( $n_{1x}$ ,  $n_{1y}$ , and  $n_{1z}$  denotes a main refractive index of the first layer in an x-axis, a y-axis, and a z-axis, respectively, and  $n_{2x}$ ,  $n_{2y}$ , and  $n_{2z}$  denotes a main refractive index of the second layer in an x-axis, a y-axis, and a z-axis, respectively)

Thus, if a refractivity difference in the x-direction between the first layer **161** and the second layer **162** is less than a refractivity difference in the y-direction between the first layer **161** and the second layer **162**, when a non-polarized light is incident in the direction perpendicular to the film plane, i.e., z-direction, a polarization component polarized parallel to the y-direction is mostly reflected due to a high difference in the refractivity based on Fresnel's equation, but a polarization component polarized parallel to the x-direction is partially transmitted and reflected due to a low difference in the refractivity.

There are disclosed methods for enhancing the display brightness by using a reflection type polarizing plate made of dielectric multilayered film having birefringence in Japanese Patent Laid Open Publication No. 9-506985 and International Patent Publication No. WO 97/01788. The dielectric multilayered film having birefringence has a structure in which two kinds of polymer layers are alternatively stacked. One of the two kinds of polymer layers is selected from a polymer group having a high refractivity and the other is selected from a polymer group having a low refractivity.

Hereinafter, the structure of the dielectric multilayered film is reviewed in an aspect of optical property.

For instance, when it is assumed that there is the following relationship between the first layer in which a material having a high refractivity is elongated, and a second layer in which a material having a low refractivity is elongated:

$$n_{1x} = n_{1z} = 1.57, n_{1y} = 1.86; \text{ and}$$

$$n_{2x} = n_{2y} = n_{2z} = 1.57.$$

Thus, in case that refractivities of the first and second layers in the x-direction and the z-direction are identical and refractivities of the first and second layers in the y-direction are different from each other, when non-polarized light is incident in the direction perpendicular to the film plane, i.e., z-direction, polarization components in the x-direction are all transmitted, polarization components in the y-direction are all reflected based on Fresnel's equation. A representative example of birefringence dielectric multilayered films having the above characteristics is DBEF (Dual brightness enhancement film). The DBEF has a multilayered structure in which two kinds of films made of different material are a few hundred layers stacked. In other words, poly(ethylene naphthalate) layer having a high birefringence and poly(methyl methacrylate) (PMMA) layer are alternatively stacked to form the DBEF layer. Since naphthalene groups of the poly(ethylene naphthalate) layer has a flat plane structure, when those groups are adjacently placed to each other, it is easy to stack the poly(ethylene naphthalate) layer and the DBEF layer, so that the refractivity in the stacking direction becomes considerably different from those in other directions. On the contrary, since the PMMA is an amorphous polymer and is isotropically aligned, the PMMA has an identical refractivity in all directions.

The DBEF transmits all x-directional polarization components and reflects all y-directional polarization components, while the transfective film **160** according to an aspect of the present invention mostly reflects a specific-directional (for instance, y-directional) polarization component, but partially reflects and transmits polarization component, which is polarized in a direction (for instance, x-direction) orthogonal to the specific direction. The transfective film can be made by vertically attaching two anisotropic transfective films having various transmissivity and reflectivity depending on polarizing state and direction of an incident light. Alternatively, the transfective film can be made by attaching an anisotropic

transflective film having various transmissivity and reflectivity depending on polarizing state and direction of incident light and a transflective film having isotropic reflection and transmission characteristics regardless of polarizing state and direction of incident light. The two transflective films can be made in an integrally formed structure, or made in a separately formed film structure.

Also, according to another preferred aspect of the invention, the transflective film 160 has isotropic reflection and transmission characteristics regardless of polarizing state and direction of incident light. For instance, if it is assumed that a direction parallel to an elongated direction of the film is in the x-direction and a direction perpendicular to the elongated direction of the film is in the y-direction, the first layer 161 having a high refractivity and the second layer 162 having a low refractivity both have a refractive isotropy within x-y planes of the film, and each of the first and second layers 161 and 162 have three main refractive indexes of  $n_x$ ,  $n_y$ , and  $n_z$  that satisfy the following relationships:

$$\begin{aligned} n_{1x} &= n_{1y} = n_{1z}; \text{ and} \\ n_{2x} &= n_{2y} = n_{2z} \neq n_{1z} \end{aligned} \quad (2).$$

Thus, in case that the first and second layers 161 and 162 have different refractivity indexes in the z-direction, when non-polarized light is incident in the direction (i.e., z-direction) perpendicular to the film, polarization components in the x-direction are partially transmitted and reflected according to Fresnel's equation, and polarization components in the y-direction are partially transmitted and reflected. At this time, the reflectivity of reflected light can be adjusted to match with characteristics of the transmissive and reflective type LCD by controlling the thickness or the refractivity of the first layer 161 or the second layer 162. In other words, a reflection characteristic-enhanced transmissive and reflective type LCD enhances the reflectivity, whereas a transmissive and reflective type LCD in which transmission characteristic is considered to be an important issue, lowers the reflectivity to thereby enhance the transmissivity.

As described above, the transflective film 160 of the present invention can be formed to have an anisotropy characteristic in which transmissivity and reflectivity of the film 160 varies with polarizing state and direction of incident light, or can be formed to have an isotropy characteristic in which transmissivity and reflectivity of the film 160 do not depend on polarizing state and direction of the incident light. In any case, it is desirable that the transflective film 160 has a reflectivity of no less than about 4% with respect to polarization component in all directions when light is incident in a direction perpendicular to the film plane.

According to an embodiment of the present invention, the transflective film 160 can be made in an integrally formed structure together with the first polarizing plate 155, or made in a separately formed film structure separated from the first polarizing plate 155. In case that the transflective film 160 is made in an integrally formed structure together with the first polarizing plate 155, it is possible to decrease the thickness of the LC cell, and the LCD has an advantage in an aspect of manufacturing cost.

In the above, there is explained a method of forming the transflective film 160 by depositing or coating a multilayered polymer film on a surface of the first polarizing plate 155. This method differs from an anti-reflection treatment in the polarizing plate. In other words, in the anti-reflection treatment, two kinds of transparent films having different refractivity are repeatedly deposited or coated in a constant thickness such that destructive interference occurs by multi-

reflection within the multilayered polymer film. However, to form a transflective film capable of partially transmitting and partially reflecting incident light, the film thickness should be adjusted such that constructive interference occurs.

FIGS. 6A and 6B are sectional views for illustrating a light scattering layer that is applicable to the transmissive and reflective type LCD of FIG. 4;

Referring to FIGS. 6A and 6B, the transmissive and reflective type LCD further includes a light scattering layer 168 formed on the first substrate 110 or the second substrate 130 to prevent specular reflection and to properly diffuse a reflected light in various angles. For instance, it is possible to form the light scattering layer 168 between the first substrate 110 and the first polarizing plate 155, between the second substrate 130 and the second polarizing plate 165, or between the first polarizing plate 155 and the transflective film 160. The light scattering layer 168 can be made in an integrally formed structure together with the first polarizing plate 155 or the second polarizing plate 165, or made in a separate film structure separated from the polarizing plates 155 and 165. Further, the light scattering layer 168 can be made in a form of a plastic film in which transparent beads are dispersed. Moreover, the light scattering layer 168 can be made in a state in which beads are added to an adhesive, which makes it possible to directly attach the first substrate 110 to the first polarizing plate 155.

Furthermore, to optimize light efficiency in the transmissive and reflective type LCD, it is possible to form a phase difference plate (not shown) on the first substrate 110 or the second substrate 130. For instance, the phase difference plate is formed in an integrally formed structure together with polarizing plate or a separate film structure separated from the polarizing plate between the first substrate 110 and the first polarizing plate 155, or between the second substrate 130 and the second polarizing plate 165.

Hereinafter, there is described in detail an operation mechanism of the transmissive and reflective type LCD having the above structure.

FIG. 7A through FIG. 8B are schematic views for illustrating operations in reflection mode and transmission mode in the transmissive and reflective type LCD in which the transflective film 160 is made an integrally formed structure together with the first polarizing plate 155. Here, polarization directions of the light are represented on the basis of a polarizing axis of the second polarizing plate 165, and a partially reflected light and a partially transmitted light by a dotted line.

First, when a pixel voltage is not applied (OFF) in the reflection mode, as shown in FIG. 7A, light that is incident from an outside is transmitted through the second polarizing plate 165, so that the light is linearly polarized in a direction parallel to the polarizing axis of the second polarizing plate 165. The linearly polarized light is transmitted through the liquid crystal layer 150 and the first transparent electrode 115, so that the linearly polarized light is linearly polarized in a direction perpendicular to the polarizing axis of the second polarizing plate 165 and is then incident onto the transflective film 160 made an integrally formed structure together with the first polarizing plate 155. At this time, since the polarizing axis of the first polarizing plate 155 is orthogonal to that of the second polarizing plate 165, the light that is incident onto the first polarizing plate 155 is parallel to the polarizing axis of the first polarizing plate 155. Accordingly, the light linearly polarized in the direction parallel to the polarizing axis of the first polarizing plate 155 is partially transmitted through the transflective film 160 and is partially reflected by the transflective film 160. In other words, in case that the transflective

film 160 has the refractivity characteristic of the relationship (1), a polarization component, which is polarized in the x-direction parallel to the elongated direction of the transfective film 160, in the lights that are incident onto the transfective film 160 is partially transmitted and reflected, whereas a polarization component which is polarized in the direction perpendicular to the elongated direction is mostly reflected. Further, in case that the transfective film 160 has the refractive characteristic of the relationship (2), in the lights that are incident onto the transfective film 160, the polarization components which is polarized in the x- and y-directions are partially transmitted and partially reflected.

Thus, the linearly polarized light reflected by the transfective film 160 is transmitted through the first transparent electrode 115 and the liquid crystal layer 150, so that it is linearly polarized in the direction parallel to the polarizing axis of the second polarizing plate 165. Afterwards, the light is transmitted through the second polarizing plate 165, so that a white image is displayed. Also, the lights that have been transmitted through the transfective film 160 are restored between the transfective film 160 and the backlight 170, and the restored lights repeatedly carry out a procedure of a partial reflection and a partial transmission. As a consequence, light loss is eliminated and reflectivity and light efficiency are enhanced.

When a maximum pixel voltage is applied (ON) in the reflection mode, as shown in FIG. 7B, light that is incident from an outside is transmitted through the second polarizing plate 165, so that the light is linearly polarized in a direction parallel to the polarizing axis of the second polarizing plate 165. Afterwards, the linearly polarized light is transmitted through the liquid crystal layer 150 without a variation in the polarizing state, and is then incident onto the transfective film 160 integrally formed with the first polarizing plate 155. At this time, since the linearly polarized light is perpendicular to the polarizing axis of the first polarizing plate 155, the light is all absorbed in the first polarizing plate 155. Thus, the linearly polarized light is not reflected by the transfective film 160, so that a black image is displayed.

When a pixel voltage is not applied (OFF) in the transmission mode, as shown in FIG. 8A, light that is irradiated from the backlight 170 is incident onto the transfective film 160 integrally formed with the first polarizing plate 155. In case that the transfective film 160 has the refractive characteristic of the relationship (1), a polarization component, which is polarized parallel to the x-direction in the lights that are parallel to the polarizing axis of the first polarizing plate 155, is partially transmitted and reflected, whereas a polarization component which is polarized parallel to the y-direction is mostly reflected. Also, in case that the transfective film 160 has the refractive characteristic of the relationship (2), lights which are parallel to the polarizing axis of the first polarizing plate 155 are partially transmitted and partially reflected because all polarization components which are polarized in the x-direction and y-direction is partially transmitted and reflected.

Thus, the light that has been transmitted through the transfective film 160 and the first polarizing plate 155 becomes a linearly polarized light having a propagating direction parallel to the polarizing axis of the first polarizing plate 155. The linearly polarized light is transmitted through the first transparent electrode 115 and the liquid crystal 150, so that it is linearly polarized in a direction parallel to the polarizing axis of the second polarizing plate 165. Accordingly, the light linearly polarized in the direction parallel to the polarizing axis of the second polarizing plate 165 is transmitted through the second polarizing plate 165, so that a white image is displayed. Also, light reflected by the transfective film 160 is

restored between the backlight 170 and the transfective film 160, and then repeats to carry out the above steps. Thus, polarization components parallel to the x-direction or polarization components parallel to the x- and y-directions are continuously transmitted through the transfective film 160 and are used, so that light loss is eliminated and transmissivity and light efficiency are enhanced.

When a maximum pixel voltage is applied (ON) in the transmission mode, as shown in FIG. 8B, light that is irradiated from the backlight 170 is incident onto the transfective film 160 integrally formed with the first polarizing plate 155, so that the light parallel to the polarizing axis of the first polarizing plate 155 is partially transmitted and reflected. The light that has been transmitted through the transfective film 160 and the first polarizing plate 155, is converted onto light linearly polarized in the direction parallel to the polarizing axis of the first polarizing plate 155, i.e., in the direction perpendicular to the polarizing axis of the second polarizing plate 165. The linearly polarized light is transmitted through the first transparent electrode 115 and the liquid crystal layer 150 without a variation in the polarizing state. Accordingly, the light linearly polarized in the direction perpendicular to the polarizing axis of the second polarizing plate 165 is not transmitted through the second polarizing plate 165, so that a black image is displayed.

FIG. 9A through FIG. 10B are schematic views for illustrating the transmission mode and the reflection mode of a transmissive and reflective type LCD in which the transfective film 160 is separated from the first polarizing plate 155 and is made in a film structure. Here, polarization directions of the light are represented on the basis of a polarizing axis of the second polarizing plate 165, and partially reflected light and partially transmitted light by a dotted line.

First when a pixel voltage is not applied (OFF) in the reflection mode, as shown in FIG. 9A, light that is incident from an outside is transmitted through the second polarizing plate 165, so that the light is linearly polarized in a direction parallel to the polarizing axis of the second polarizing plate 165. The linearly polarized light is transmitted through the liquid crystal layer 150 and the first transparent electrode 115, so that the linearly polarized light is linearly polarized in a direction perpendicular to the polarizing axis of the second polarizing plate 165 and is then incident onto the first polarizing plate 155. At this time, since the polarizing axis of the first polarizing plate 155 is orthogonal to that of the second polarizing plate 165, the light that has been linearly polarized in a direction perpendicular to the polarizing axis of the second polarizing plate 155 is transmitted through the first polarizing plate 155 and is then incident onto the transfective film 160. In case that the transfective film 160 has the refractivity characteristic defined in equation (1), a polarization component, which is polarized in the x-direction parallel to the elongated direction of the transfective film 160, light rays directed incident to the transfective film 160 is partially transmitted and reflected, whereas a polarization component, which is polarized in the y-direction perpendicular to the elongated direction, is mostly reflected. Further, in case that the transfective film 160 has the refractive characteristic of the relationship (2), light rays that are incident to the transfective film 160, the polarization components polarized in the x- and y-directions are partially transmitted and partially reflected.

Thus, since the linearly polarized light reflected by the transfective film 160 is parallel to the polarizing axis of the first polarizing plate 155, it is transmitted through the first polarizing plate 155, and is incident onto the liquid crystal layer 150 via the transparent electrode 115. The linearly

polarized light is transmitted through the liquid crystal layer **150**, whereby it is linearly polarized in the direction parallel to the polarizing axis of the second polarizing plate **165**. Afterwards, the light is transmitted through the second polarizing plate **165**, so that a white image is displayed. Also, the light rays that have been transmitted through the transmissive film **160** are restored between the transmissive film **160** and the backlight **170**, and the restored light repeatedly carry out a procedure of a partial reflection and a partial transmission. As a consequence, light loss is eliminated and reflectivity and light efficiency are enhanced.

When a maximum pixel voltage is applied (ON) in the reflection mode as shown in FIG. **9B**, light that is incident from an outside is transmitted through the second polarizing plate **165**, so that the light is linearly polarized in a direction parallel to the polarizing axis of the second polarizing plate **165**. Afterwards, the linearly polarized light is transmitted through the liquid crystal layer **150** without a variation in the polarizing state, and is then incident onto the first polarizing plate **155**. At this time, since the linearly polarized light is perpendicular to the polarizing axis of the first polarizing plate **155**, the light is all absorbed in the first polarizing plate **155**. Thus, since the linearly polarized light is not reflected by the transmissive film **160**, a black image is displayed.

When a pixel voltage is not applied (OFF) in the transmission mode, as shown in FIG. **10A**, light that is irradiated from the backlight **170** is incident onto the transmissive film **160**, so that the light is partially transmitted and reflected. In case that the transmissive film **160** has the refractive characteristic of the relationship (1), polarization components, which is polarized in the x-direction parallel to the elongated direction of the transmissive film **160** in the lights that have been incident onto the transmissive film **160** is partially transmitted and reflected, whereas polarization components, which is polarized in the y-direction perpendicular to the elongated direction, are mostly reflected. Also, in case that the transmissive film **160** has the refractive characteristic of the relationship (2), polarization components, which is polarized in the x- and y-directions, in the lights that have been incident onto the transmissive film **160** are partially transmitted and reflected.

Thus, the light that has been transmitted through the transmissive film **160** and the first polarizing plate **155** is linearly polarized in a direction parallel to the polarizing axis of the first polarizing plate **155**. Afterwards, the linearly polarized light is transmitted through the first transparent electrode **115** and the liquid crystal **150**, so that it is linearly polarized in a direction parallel to the polarizing axis of the second polarizing plate **165**. Accordingly, the light linearly polarized in the direction parallel to the polarizing axis of the second polarizing plate **165** is transmitted through the second polarizing plate **165**, so that a white image is displayed. Also, light reflected by the transmissive film **160** is restored between the backlight **170** and the transmissive film **160**, and then repeats to carry out the above steps. Thus, polarization components polarized parallel to the x-direction or polarization components polarized parallel to the x- and y-directions continuously is transmitted through the transmissive film **160** and are used, so that light loss is eliminated and transmissivity and light efficiency are enhanced.

When a maximum pixel voltage is applied (ON) in the transmission mode, as shown in FIG. **10B**, light that is irradiated from the backlight **170** is incident onto the transmissive film **160**, so that the incident light is partially transmitted through the transmissive film **160** and is partially reflected by the transmissive film **160**. The light that has been transmitted through the transmissive film **160** is transmitted through the first polarizing plate **155**, so that it is converted onto light

linearly polarized parallel to the polarizing axis of the first polarizing plate **155**, i.e., a direction perpendicular to the polarizing axis of the second polarizing plate **165**. Afterwards, the linearly polarized light is transmitted through the first transparent electrode **115** and the liquid crystal layer **150** without a variation in the polarizing state. Accordingly, the light linearly polarized in the direction perpendicular to the polarizing axis of the second polarizing plate **165** cannot be transmitted through the second polarizing plate **165**, so that a black image is displayed.

FIG. **11** is a sectional view of a transmissive and reflective type LCD in accordance with another embodiment of the present invention.

Referring to FIG. **11**, a transmissive and reflective type LCD includes a first substrate **200**, a second substrate **250** arranged facing the first substrate **200**, a liquid crystal layer **260** formed between the first substrate **200** and the second substrate **250**, and a backlight **270** arranged at a rear side of the first substrate **200**.

The first substrate **200** includes a first insulating substrate **210**. A plurality of gate lines (not shown) and a plurality of data lines (not shown) are formed on the first insulating substrate **210** in a matrix configuration. A pixel electrode **234** and a thin film transistor **225** are formed at a region defined by a pair of gate line and a pair of data lines. The second substrate **250** includes a second insulating substrate **252**, a color filter **254** of RGB pixels, for displaying colors while light is transmitted therethrough, a black matrix **256** for preventing light from being leaked between pixels, and a transparent common electrode **258**.

A thin film transistor **225** includes a gate electrode **212** formed on the first insulating substrate **210**, a gate insulating film **214** formed on the gate electrode **212** and the first insulating substrate **210**, an active pattern **216** and an ohmic contact pattern **218** both formed on the gate insulating film **214** on the gate electrode **212**, and source and drain electrodes **220** and **222** formed apart from each other on the ohmic contact pattern **218**. A passivation film **230** made of organic or inorganic substance is formed on the first insulating substrate **210** including the thin film transistor **225**. A contact hole **232** penetrating the passivation film **230** is formed in the passivation film **230** to expose the drain electrode **222**. The pixel electrode **234** is made of transparent conductive oxide such as ITO (Indium tin oxide).

The liquid crystal layer **260** is made of 90° twisted nematic (TN) liquid crystal, and has a  $\Delta n d$  of about 0.2  $\mu\text{m}$  to about 0.6  $\mu\text{m}$  that is a product of a refractive anisotropy  $\Delta n$  and a thickness  $d$  of the liquid crystal layer **260**, preferably about 0.48  $\mu\text{m}$ . Thus, the value on the refractivity anisotropy allows the LCD of the present invention to use the LC optical condition of the conventional transmission type LCD without any modification, thereby preventing the reliability of the liquid crystal from being lowered.

Depending on alignment direction of the liquid crystal layer **260**, first and second polarizing plates **262** and **266** for transmitting only light propagating in a specific direction are respectively attached on outer surfaces of the first and second substrates **210** and **252**. Preferably, the first and second polarizing plates **262** and **266** are linear polarizers of which polarizing axes are arranged perpendicular to each other.

The gate electrode **212** of the thin film transistor **225** is connected to the gate line, the source electrode **220** is connected to the data line, and the drain electrode **222** is connected to the pixel electrode **234** through the contact hole **232**. Accordingly, as a scanning voltage is applied to the gate electrode **212**, a signal voltage flowing through the data line is applied to the drain electrode **222** through the active pattern

216 from the source electrode 220. If the signal voltage is applied to the drain electrode 222, there is generated a voltage difference between the pixel electrode 234 connected to the drain electrode 222 and the common electrode 258 of the second substrate 252. As a consequence, molecular arrangement of the liquid crystal layer 260 injected between the pixel electrode 234 and the common electrode 258 varies, and thereby light transmissivity through the liquid crystal layer 260 varies. Thus, the thin film transistor 225 performs the role as switching element for turning on or turning off pixels of the LC cell.

According to an embodiment of the present invention, a transfective film 264 is formed between the first polarizing plate 262 and the backlight 270. The transfective film 264 is formed of a plurality of transparent layers in which first and second layers (not shown) having different refractivity are alternatively stacked. As described in the above embodiment, the transfective film 264 functions to partially transmit and reflect the incident light. In other words, the transfective film 264 can be formed in a structure having anisotropy characteristic in which degrees of the transmissivity and the reflectivity vary with polarizing state and direction of the incident light, or in a structure having isotropy characteristic in which degrees of the transmissivity and the reflectivity do not vary with polarizing state and direction of the incident light. In any cases, it is desirable that the transfective film 264 is formed to have about 4% or more in the reflectivity with respect to polarization components in all directions. The transfective film 264 is formed in an integrally formed structure with the first polarizing plate 262 or in a structure separated from the first polarizing plate 262.

Further, to prevent specular reflection and properly diffuse reflected lights in several directions, the transmissive and reflective type LCD in accordance with the present embodiment can further include a light scattering layer (not shown) on either the first substrate 200 or the second substrate 250. For instance, the light scattering layer can be formed between the first substrate 200 and the first polarizing plate 262, between the second substrate 250 and the second polarizing plate 266, or between the first polarizing plate 262 and the transfective film 264. The light scattering layer is formed in an integrally formed structure with the first polarizing plate 262 or the second polarizing plate 266, or in a structure separated from the first polarizing plate 262 or the second polarizing plate 266. Also, the light scattering layer can be made by mixing adhesive and beads.

Moreover, to optimize light efficiency in the transmissive and reflective type LCD of the present embodiment, a phase differential plate (not shown) can be further formed on either the first substrate 200 or the second substrate 250. For instance, the phase differential plate is formed between the first substrate 200 and the first polarizing plate 262 or between the second substrate 250 and the second polarizing plate 266. Also, the phase difference plate is formed in an integrally formed structure with the first polarizing plate 262 or the second polarizing plate 266, or in a structure separated from the first polarizing plate 262 or the second polarizing plate 266.

According to the transmissive and reflective type LCD of the present embodiment, a reflection electrode is not formed within the LC cell, but the transfective film 264 substitutes for the reflection electrode, and performs the role of the reflection electrode. Accordingly, light that is incident toward the second substrate 252 from an outside has a reflection light path 280 in which the light is transmitted through the first substrate 210, is reflected by the transfective film 264, and is output through the second substrate 252. Also, light that is

incident toward the first substrate 200 from the backlight 270 has a transmission light path 285 in which the light is transmitted through the transfective film 264 and then is output through the second substrate 250.

The transmissive and reflective type LCD shown in FIG. 11 has the same operation mechanism in the reflection mode and the transmission mode as those described with reference to FIG. 7A through FIG. 10B. In other words, by using the transfective film 264 which partially transmits and reflects the incident light, light loss is not generated in the reflection mode and the transmission mode, so that it is possible to enhance both of the reflectivity and transmissivity. Also, compared with the conventional transmissive and reflective type LCD of FIG. 1, the transmissive and reflective type LCD of the present invention does not require a  $\frac{1}{4}$ -wavelength phase difference plate on the lower substrate, i.e., the first substrate 210. Further, light that is incident from the backlight 270 and is reflected from regions where a metal layer, such as the gate line or data line, exists within the LC cell, are restored between the transfective film 264 and the backlight 270 and the restored lights are used, so that it increases overall light efficiency.

As described above, according to a preferred embodiment of the present invention, between the first polarizing plate attached on the outer surface of the lower substrate (i.e., first substrate) and the backlight is formed an anisotropy transfective film having an optical characteristic in which light components in a specific direction are strongly reflected and polarization components in a direction perpendicular to the specific direction are partially transmitted and reflected depending on polarizing state and direction of an incident light, or an isotropy transfective film having an optical characteristic in which light components are partially transmitted and reflected regardless of polarizing state and direction of the incident light. As a result, by a restoring process of light occurring between the transfective film and the backlight, the restored light is transmitted through the transfective film repeatedly, so that transmissivity and light efficiency are enhanced.

Further, the transmissive and reflective type LCD according to a preferred embodiment of the present invention does not require a reflection electrode within LC cell or a  $\frac{1}{4}$ -wavelength phase difference plate on each of the upper substrate (second substrate) and the lower substrate (first substrate). Accordingly, compared with the conventional transmissive and reflective type LCD, the transmissive and reflective type LCD of the present invention is simpler and can be more easily made.

Furthermore, since the optical conditions applied to the liquid crystal of the conventional transmissive and reflective type LCD can be identically applied to that of the transmissive and reflective type LCD of the present invention, there is no degradation in reliability.

While the present invention has been described in detail, it should be understood that various changes, substitutions and alterations can be made hereto without departing from the spirit and scope of the invention as defined by the appended claims.

What is claimed is:

1. A transmissive and reflective type LCD comprising:
  - an array substrate;
  - a counter substrate having an inner surface facing the array substrate;
  - a liquid crystal layer formed between the array substrate and the counter substrate;
  - a first polarizing plate formed on an outer surface of the array substrate;

a second polarizing plate formed on an outer surface of the counter substrate;  
 a backlight for irradiating incident light onto the first polarizing plate; and

a transfective film arranged between the first polarizing plate and the backlight, the transfective film reflecting a first polarization component of the incident light in a first direction, and partially reflecting and transmitting a second polarization component of the incident light in a second direction,

wherein the transfective film is deposited or coated on a surface of the first polarizing plate, so that the transfective film is integrally formed with the first polarizing plate,

wherein the transfective film includes at least a first layer and a second layer, and each of the first layer and the second layer has three main refractive indexes of  $n_x$ ,  $n_y$ , and  $n_z$  that satisfy the following relationships:

$$n1_x = n1_z \neq n1_y;$$

$$n2_x = n2_y = n2_z;$$

$$n1_x \neq n2_x;$$

$$n1_y \neq n2_y; \text{ and}$$

$$|n1_x - n2_x| < |n1_y - n2_y|$$

wherein the transfective film has a thickness direction of z-axis and a film plane of x-y plane, wherein  $n1_x$ ,  $n1_y$ ,  $n1_z$  denotes a main refractive index of the first layer in an x-axis, y-axis, z-axis, respectively, and  $n2_x$ ,  $n2_y$ ,  $n2_z$  denotes a main refractive index of the second layer in an x-axis, y-axis, z-axis, respectively.

2. The transmissive and reflective type LCD of claim 1, wherein the first and second layers are alternately stacked.

3. The transmissive and reflective type LCD of claim 1, wherein the transfective film has a reflectivity of no less than about 4% with respect to any direction of polarization components when the incident light is incident onto the transfective film with an angle perpendicular to a surface thereof.

4. The transmissive and reflective type LCD of claim 1, further comprising a light scattering layer formed on the array substrate or the counter substrate, wherein the light scattering layer is formed between the array substrate and the first polarizing plate, between the counter substrate and the second polarizing plate, or between the first polarizing plate and the transfective film.

5. The transmissive and reflective type LCD of claim 1, further comprising a phase difference plate formed on the array substrate or the counter substrate wherein the phase difference plate is formed between the array substrate and the first polarizing plate, or between the counter substrate and the second polarizing plate.

6. The transmissive and reflective type LCD of claim 1, wherein the liquid crystal layer has a  $\Delta n d$  of about 0.2-0.6  $\mu\text{m}$  that is a product of a refractive anisotropy  $\Delta n$  and a thickness  $d$  of the liquid crystal layer.

7. The transmissive and reflective type LCD of claim 1, wherein a transmitting direction of the incident light at the first polarizing plate is the same direction as a partially reflecting and transmitting direction of the incident light at the transfective film.

8. The transmissive and reflective type LCD of claim 1, wherein the transfective film comprises at least two transfective films having a varying transmissivity and reflectivity

depending on polarizing state and direction of the incident light, the at least two transfective films being disposed one on top of the other.

9. The transmissive and reflective type LCD of claim 8, wherein the transfective film comprises a first transfective film and a second transfective film, and the first transfective film having a transmissivity and a reflectivity that vary according to polarizing state and direction of the incident light, and the second transfective film having isotropic transmission and reflection characteristics independent of the polarizing state and the direction of the incident light.

10. The transmissive and reflective type LCD of claim 9, wherein the transfective film has a reflectivity of no less than about 4% with respect to any direction of polarization components when the incident light is incident onto the transfective film with an angle perpendicular to a surface thereof.

11. The transmissive and reflective type LCD of claim 9, further comprising a light scattering layer formed on the array substrate or the counter substrate, wherein the light scattering layer is formed between the array substrate and the first polarizing plate, between the counter substrate and the second polarizing plate, or between the first polarizing plate and the transfective film.

12. The transmissive and reflective type LCD of claim 9, further comprising a phase difference plate formed on the array substrate or the counter substrate wherein the phase difference plate is formed between the array substrate and the first polarizing plate, or between the counter substrate and the second polarizing plate.

13. The transmissive and reflective type LCD of claim 9, wherein the liquid crystal layer has a  $\Delta n d$  of about 0.2-0.6  $\mu\text{m}$  that is a product of a refractive anisotropy  $\Delta n$  and a thickness  $d$  of the liquid crystal layer.

14. The transmissive and reflective type LCD of claim 9, wherein a transmitting direction of the incident light at the first polarizing plate is the same direction as a partially reflecting and transmitting direction of the incident light at the transfective film.

15. A transmissive and reflective type LCD comprising:  
 an array substrate on which a switching element and a first transparent electrode is formed;

a counter substrate of which an inner surface is arranged facing the array substrate, the inner surface of the counter substrate having a second transparent electrode thereon;

a liquid crystal layer formed between the array substrate and the counter substrate;

a first polarizing plate formed on an outer surface of the array substrate;

a second polarizing plate formed on an outer surface of the counter substrate, opposite the inner surface of the counter substrate;

a backlight arranged at a rear side of the first polarizing plate; and

a transparent transfective film arranged between the first polarizing plate and the backlight, the transfective film reflecting a first polarization component of incident light in a first direction, and partially reflecting and transmitting a second polarization of the incident light in a second direction,

wherein the transfective film is deposited or coated on a surface of the first polarizing plate, so that the transfective film is integrally formed with the first polarizing plate,

wherein the transfective film includes at least a first layer and a second layer, and each of the first layer and the

19

second layer has three main refractive indexes of  $n_x$ ,  $n_y$ , and  $n_z$ , that satisfy the following relationships:

$$n1_x = n1_z \neq n1_y;$$

$$n2_x = n2_y = n2_z;$$

$$n1_x \neq n2_x;$$

$$n1_y \neq n2_y; \text{ and}$$

$$|n1_x - n2_x| < |n1_y - n2_y|$$

wherein the transfective film has a thickness direction of z-axis and a film plane of x-y plane, wherein  $n1_x$ ,  $n1_y$ ,  $n1_z$  denotes a main refractive index of the first layer in an x-axis, y-axis, z-axis, respectively, and  $n2_x$ ,  $n2_y$ ,  $n2_z$  denotes a main refractive index of the second layer in an x-axis, y-axis, z-axis, respectively.

16. The transmissive and reflective type LCD of claim 15, wherein the first transparent electrode is a signal electrode and the second transparent electrode is a scanning electrode.

17. The transmissive and reflective type LCD of claim 16, wherein the switching element is a thin film transistor.

18. The transmissive and reflective type LCD of claim 15, wherein the first and second layers are alternately stacked.

19. The transmissive and reflective type LCD of claim 15, wherein the transfective film has a reflectivity of no less than

20

about 4% with respect to any direction of polarization components when the incident light is incident onto the transfective film with an angle perpendicular to a surface thereof.

20. The transmissive and reflective type LCD of claim 15, further comprising a light scattering layer formed on the array substrate or the counter substrate, wherein the light scattering layer is formed between the array substrate and the first polarizing plate, between the counter substrate and the second polarizing plate, or between the first polarizing plate and the transfective film.

21. The transmissive and reflective type LCD of claim 15, further comprising a phase difference plate formed on the array substrate or the counter substrate wherein the phase difference plate is formed between the array substrate and the first polarizing plate, or between the counter substrate and the second polarizing plate.

22. The transmissive and reflective type LCD of claim 15, wherein the liquid crystal layer has a  $\Delta nd$  of about 0.2-0.6  $\mu\text{m}$  that is a product of a refractive anisotropy  $\Delta n$  and a thickness  $d$  of the liquid crystal layer.

23. The transmissive and reflective type LCD of claim 15, wherein a transmitting direction of the incident light at the first polarizing plate is the same direction as a partially reflecting and transmitting direction of the incident light at the transfective film.

\* \* \* \* \*

专利名称(译)	透射和反射型液晶显示器		
公开(公告)号	<a href="#">US7929082</a>	公开(公告)日	2011-04-19
申请号	US10/985780	申请日	2004-11-10
[标]申请(专利权)人(译)	JANG YONG KYU 金亨GUEL		
申请(专利权)人(译)	JANG YONG-KYU 金亨GUEL		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	JANG YONG KYU KIM HYUNG GUEL		
发明人	JANG, YONG-KYU KIM, HYUNG-GUEL		
IPC分类号	G02F1/1335 G02F1/13357		
CPC分类号	G02F1/133536 G02F1/133555 G02F2001/133567 G02F2001/133545 G02F1/133615		
审查员(译)	KIM , RICHARD H		
优先权	1020010080714 2001-12-18 KR		
其他公开文献	US20050062914A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

公开了一种透射和反射型LCD。在LCD中，第二基板面向第一基板。在第一基板和第二基板之间形成液晶层。第一偏振板形成在第一基板的外表面上。在第二基板的外表面上形成第二偏振板。设置背光源以将入射光照射到偏振片上。透明半透半反膜设置在第一偏振板和背光之间，用于部分反射和部分透射入射光。透明半透半反膜包括至少第一层和第二层，第一层和第二层具有彼此不同的折射率，并且交替地堆叠。通过在透射反射膜和背光之间发生的恢复过程，预定量的入射光反复透射穿过透反射膜，从而提高透射率和光效率。

