



US008847877B2

(12) **United States Patent**
Den Boer et al.

(10) **Patent No.:** **US 8,847,877 B2**
(45) **Date of Patent:** **Sep. 30, 2014**

(54) **OUTDOOR READABLE LIQUID CRYSTAL
DISPLAY DEVICE**

(71) Applicant: **Shanghai Tainma Micro-Electronics
Co., Ltd.**, Shanghai (CN)

(72) Inventors: **Willem Den Boer**, Shanghai (CN);
Xuhui Peng, Shanghai (CN); **Zhihua
Ling**, Shanghai (CN); **Zhongshou
Huang**, Shanghai (CN)

(73) Assignee: **Shanghai Tianma Micro-Electronics
Co., Ltd.**, Shanghai (CN)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/132,828**

(22) Filed: **Dec. 18, 2013**

(65) **Prior Publication Data**

US 2014/0104254 A1 Apr. 17, 2014

Related U.S. Application Data

(62) Division of application No. 12/935,487, filed as
application No. PCT/CN2009/071111 on Mar. 31,
2009, now Pat. No. 8,624,826.

(30) **Foreign Application Priority Data**

Apr. 3, 2008 (CN) 2008 1 0043215

(51) **Int. Cl.**

G09G 3/36 (2006.01)

G09G 3/34 (2006.01)

G02F 1/1335 (2006.01)

(52) **U.S. Cl.**

CPC **G09G 3/36** (2013.01); **G09G 2320/0626**
(2013.01); **G09G 2310/0235** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC G02F 2203/34; G09G 3/34; G09G 3/3406;
G09G 3/3413; G09G 3/342; G09G 3/3426
USPC 345/102, 207; 349/68-69;
362/97.1-97.4

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,447,132 B1 9/2002 Harter, Jr.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1428630 A 7/2003

(Continued)

OTHER PUBLICATIONS

International Search Report regarding Application No. PCT/
CN2009/071111, mailed Jul. 16, 2009.

(Continued)


Primary Examiner — Gene W Lee

(74) *Attorney, Agent, or Firm* — Harness, Dickey & Pierce,
P.L.C.

(57) **ABSTRACT**

An outdoor readable liquid crystal display device (200) includes a liquid crystal panel (210), a backlight device (220) and a light source control device. The backlight device (220) includes a plurality of red light emitting diodes (220r), green light emitting diodes (220g) and blue light emitting diodes (220b). The light source control device is used to adjust the backlight device (220) based on the light intensity of ambient light. When the light intensity of ambient light is lower than a predetermined light intensity of the liquid crystal display device (200), the red light emitting diodes (220r), the green light emitting diodes (220g) and the blue light emitting diodes (220b) of the backlight device (220) are sequentially energized to emit lights at a predetermined time lag. When the light intensity of ambient light is higher than the predetermined light intensity, the red light emitting diodes (220r), the green light emitting diodes (220g) and the blue light emitting diodes (220b) of the backlight device (220) are energized to emit lights at the same time.

6 Claims, 6 Drawing Sheets



(52) U.S. Cl.

CPC *G09G 2360/144* (2013.01); *G09G 2330/021*
 (2013.01); *G02F 2001/133612* (2013.01);
G09G 3/3413 (2013.01); *G02F 2201/58*
 (2013.01); *G09G 3/3426* (2013.01)
 USPC 345/102; 345/207; 349/68; 362/97.1;
 362/97.2; 362/97.3

2003/0169226 A1 9/2003 Yamada
 2006/0256257 A1* 11/2006 Nakano et al. 349/80
 2006/0279507 A1* 12/2006 Nakao et al. 345/98
 2007/0081330 A1 4/2007 Lee et al.
 2007/0139352 A1* 6/2007 Pugh et al. 345/102
 2008/0001909 A1 1/2008 Lim
 2009/0033613 A1* 2/2009 Butterworth 345/102
 2010/0182294 A1* 7/2010 Roshan et al. 345/207

(56)

References Cited

U.S. PATENT DOCUMENTS

6,724,354 B1* 4/2004 Spitzer et al. 345/32
 6,909,419 B2 6/2005 Zavracky et al.
 7,242,383 B2 7/2007 Zavracky et al.
 7,295,180 B2* 11/2007 Ichikawa et al. 345/102
 7,333,165 B2 2/2008 Nakano et al.
 7,438,442 B2 10/2008 Lee et al.
 7,532,176 B2 5/2009 Imade
 7,580,023 B2* 8/2009 Pugh et al. 345/102
 7,733,336 B2 6/2010 Lim
 7,893,915 B2 2/2011 Woo et al.
 8,384,654 B2 2/2013 Fujine et al.
 2003/0117355 A1 6/2003 Yamauchi

FOREIGN PATENT DOCUMENTS

CN 1862647 A 11/2006
 CN 1949504 A 4/2007
 CN 101055370 A 10/2007
 CN 101097695 A 1/2008
 EP 1950731 A1 7/2008
 JP 2007155829 A 6/2007
 WO WO-2007055131 A1 5/2007

OTHER PUBLICATIONS

Notice of Allowance regarding U.S. Appl. No. 12/935,487, mailed
 Aug. 29, 2013.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6 (a)




FIG. 6 (b)




FIG. 7 (a)




FIG. 7 (b)




FIG. 8

OUTDOOR READABLE LIQUID CRYSTAL DISPLAY DEVICE

This application is a Divisional Application of U.S. patent application Ser. No. 12/935,487, filed on Sep. 29, 2010, which is a 371 U.S. National Stage of International Application No. PCT/CN2009/071111, filed Mar. 31, 2009, which claims the benefit of Chinese patent application No. 200810043215.6, titled "Outdoor-readable Liquid Crystal Display" and filed with the State Intellectual Property Office on Apr. 3, 2008, both of which are incorporated herein by reference in their entirety.

FIELD OF THE INVENTION

The present invention relates to a liquid crystal display and in particular to an outdoor-readable liquid crystal display.

BACKGROUND OF THE INVENTION

In recent years, Liquid Crystal Displays (LCDs) have been widely used in electronics for representation of information due to their lightness, thinness, low power consumption, etc.

Conventional LCDs are broadly classified as either reflective or transmissive. Unlike Cathode Ray Tube (CRT) displays and Electroluminescent (EL) displays, LCDs are not self-emissive. A transmissive LCD is illuminated by a light source situated behind the LCD panel, and a reflective LCD is illuminated by ambient light. As a result, transmissive LCDs are less subjected to the intensity of ambient light and the contrast of the displayed image is higher, but transmissive LCDs are less power efficient due to the presence of the light source. Reflective LCDs are more power efficient because they do not need an additional light source, but the brightness and contrast of the displayed image in reflective LCDs are more subjected to the intensity of ambient light and the like. Particularly, their ability to resolve detail is notably limited in a dark environment.

A Field-Sequential Color Liquid Crystal Display (FSC-LCD) is a display with many advantageous features. The display switches on red, green and blue (R, G, B) backlights in sequence, which illuminate the display panel in sequence. That is, red, green and blue lights are applied in each pixel in sequence. Due to image sticking, the red, green and blue images are perceived by the observer as a continuous image.

Now refer to FIG. 1, a sectional view of the structure of a conventional FSC-LCD 1. The FSC-LCD 1 includes a first upper substrate 10, a first lower substrate 11, a first liquid crystal layer 12 provided between the first upper substrate 10 and the first lower substrate 11, and a first backlight device 13 for providing the light source of the FSC-LCD 1. The first backlight device 13 including a plurality of red Light-Emitting Diodes (LEDs) 13r, green LEDs 13g and blue LEDs 13b. First pixel electrodes 111 and Thin-Film Transistors (TFTs) 112 used as switches are formed on the side of the first lower substrate 11 immediately adjacent to the first liquid crystal layer 12. The TFTs 112 are electrically connected to the first pixel electrodes 111. A first common electrode 101 facing the first pixel electrodes 111 is formed on the side of the first upper substrate 10 immediately adjacent to the first liquid crystal layer 12. A black base 102 is provided between the first common electrode 101 and the first upper substrate 10, and in correspondence with the TFTs 112 of the first lower substrate 11, for blocking light from the regions excluding the first pixel electrodes 111 of the first lower substrate 11.

FIG. 2 is a top view of the first lower substrate 11 of the conventional FSC-LCD 1. The TFTs 112 used as pixel

switches, data lines 113 for providing signals to the first pixel electrodes 111 of the first lower substrate 11, and gate lines 114 for providing switching signals to the TFTs 112 are provided on the first lower substrate 11. The data lines 113 and the gate lines 114 define multiple pixel regions 115. Each of the TFTs 112 is on the place in a pixel region 115, where a data line 113 and a gate line 114 meet, and is electrically connected to the data line 113 and the gate line 114.

FIG. 3 is a sequence diagram illustrating a method for driving the conventional FSC-LCD 1. The method for driving the FSC-LCD 1 includes: scanning each of the TFTs 112 according to the first backlight device 13, and realigning liquid crystal molecules in the first liquid crystal 12 to correspond to the lights emitted by the red LEDs 13r, green LEDs 13g and blue LEDs 13b of the first backlight device 13. Specifically, scanning of all of the TFTs (tTFT) 15, liquid crystal response (tLC) 16 and backlighting (tBL) 17 in the FSC-LCD 1 are performed in the period of a field 14.

FIG. 4 illustrates the principle of driving the conventional FSC-LCD 1. The FSC-LCD 1 further includes a first scanning driver 18 and a first data driver 19. With reference to FIG. 2, the first lower substrate 11 of the FSC-LCD 1 includes multiple pixel regions 115, and pixels in all the pixel regions 115 form an array. The first scanning driver 18 scans pixels in the pixel regions 115 row by row in sequence, and the first data driver 19 transmits the image data to a pixel column corresponding to the pixel regions 115.

However, for good outdoor readability of the conventional FSC-LCD 1 discussed-above, the brightness of light produced by the first backlight device 13 has to be elevated, resulting in increased power consumption.

In view of the problem in the prior art, the inventors conducted intensive studies with their vast experiences in the field, and invented the outdoor-readable LCD of the invention.

SUMMARY OF THE INVENTION

An object of the invention is to solve the drawback of the prior art, provide an outdoor-readable LCD, and realize high brightness for good outdoor readability.

To solve the problems above, the invention provides an outdoor-readable LCD, including: a liquid crystal panel, including an upper substrate, a lower substrate and a liquid crystal layer provided between the upper substrate and the lower substrate; a backlight device including a plurality of red LEDs, green LEDs and blue LEDs; and a light source control device adapted to adjust the backlight device based on the intensity of ambient light. When the intensity of ambient light is lower than a predetermined light intensity of the outdoor-readable LCD, the red LEDs, the green LEDs and the blue LEDs of the backlight device are switched on in sequence to emit lights with predetermined delays; and when the intensity of ambient light is higher than the predetermined light intensity, the red LEDs, the green LEDs and the blue LEDs of the backlight device are switched on at the same time.

As discussed above, the outdoor-readable LCD applies red, green and blue (R, G, B) lights in sequence on the same pixel, for the eyes of the observer mixing the successive images into a color picture due to the image sticking, so that the invention without an expensive color filter, can realize outdoor readability, lower costs, improved resolution and lower power consumption, and increase illumination utilization of the backlight device.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings include:

FIG. 1 is a sectional view of the structure of a conventional FSC-LCD;

FIG. 2 is a top view of the first lower substrate of the conventional FSC-LCD;

FIG. 3 is a sequence diagram of the conventional FSC-LCD;

FIG. 4 illustrates the principle of driving the conventional FSC-LCD;

FIG. 5 is an exploded view of an outdoor-readable LCD according to the invention;

FIG. 6(a) and FIG. 6(b) are sequence diagrams for backlight in an outdoor-readable LCD according to a first embodiment of the invention;

FIG. 7(a) and FIG. 7(b) are sequence diagrams for backlight in an outdoor-readable LCD according to a second embodiment of the invention; and

FIG. 8 is a sequence diagram for backlight in an outdoor-readable FSC-LCD according to a third embodiment of the invention.

Numerals for the elements in the drawings are listed below:

PRIOR ART

FSC-LCD	1	First common electrode	101
First upper substrate	10	First pixel electrode	111
First lower substrate	11	Data line	113
TFT	112	Pixel region	115
Gate line	114	First backlight device	13
First liquid crystal layer	12	Scanning of TFTs	15
Period	14	Backlighting	17
Liquid crystal response	16	First data driver	19
First scanning driver	18		

THE INVENTION

Outdoor-readable LCD	200	Second pixel electrode	211
Liquid crystal panel	210	Second upper substrate	213
Second low substrate	212	Second liquid crystal layer	215
Second common electrode	214	First polarizing plate	221a
Second backlight device	220	Green LED	220g
Red LED	220r	White LED	220w
Blue LED	220b	Second data driver	240
Second scanning driver	230		

DETAILED DESCRIPTION OF THE INVENTION

The technical solution, structural features, objects and effects of the invention are described hereinafter in connection with the embodiments and the figures.

First Embodiment

As shown in FIG. 5, an outdoor-readable LCD 200 of the invention includes: a liquid crystal panel 210, a second backlight device 220 adapted to illuminate the liquid crystal panel 210, a second scanning driver 230 adapted to provide a scanning signal to the liquid crystal panel 210, a second data driver 240 adapted to provide a data signal to the liquid crystal panel 210, and a light source control device (not shown) adapted to adjust the brightness of the second backlight device 220. The liquid crystal panel 210 includes: a second lower substrate

212 including second pixel electrodes 211, a second upper substrate 213 facing to the second lower substrate 212, a second common electrode 214 provided on the side of the second upper substrate 213 facing to the second lower substrate 212, and a second liquid crystal layer 215 provided between the second lower substrate 212 and the second upper substrate 213. The second backlight device 220 includes a plurality of red LEDs 220r, green LEDs 220g and blue LEDs 220b, and further includes a first polarizing plate 221a and a second polarizing plate (not shown). The first polarizing plate 221a is mounted on the side of the second lower substrate 212 opposite to the second pixel electrodes 211. The second polarizing plate is mounted on the side of the second upper substrate 213 opposite to the second common electrode 214. The red LEDs 220r, green LEDs 220g and blue LEDs 220b of the second backlight device 220 are provided facing to the first polarizing plate 221a with a certain distance between the second backlight device 220 and the first polarizing plate 221a. When the red LEDs 220r, green LEDs 220g and blue LEDs 220b of the second backlight device 220 are switched on in sequence, the red LEDs 220r, the green LEDs 220g and the blue LEDs 220b emit red, green and blue lights with predetermined delays; or, the red LEDs 220r, green LEDs 220g and blue LEDs 220b are switched on at the same time, and the red, green and blue lights emitted are superimposed, resulting in white light.

Particularly, the outdoor-readable LCD according to the invention may further include an ambient light sensor (not shown), adapted to sense the intensity of ambient light and output a sensing signal. The light source control device adjusts the second backlight device 220 based on the sensing signal.

Now refer to FIG. 6(a) and FIG. 6(b). When the intensity of ambient light detected by the ambient light sensor is lower than a predetermined light intensity of the outdoor-readable LCD 200, the light source control device switches on the red LEDs 220r, the green LEDs 220g and the blue LEDs 220b in sequence according to the sensing signal, and the red LEDs 220r, the green LEDs 220g and the blue LEDs 220b emit red, green and blue lights with predetermined delays. The red, green and blue lights enter the first polarizing plate 221a, and pass through the second lower substrate 212, to the second liquid crystal layer 215. Lights arrived at the second liquid crystal layer 215 pass through the second upper substrate 213, and leave from the second polarizing plate, to form a color image. When the intensity of ambient light detected by the ambient light sensor is higher than the predetermined light intensity of the outdoor-readable LCD 200, the light source control device switches on the red LEDs 220r, the green LEDs 220g and the blue LEDs 220b of the second backlight device 220 at the same time according to the sensing signal, and the red LEDs 220r, the green LEDs 220g and the blue LEDs 220b of the second backlight device 220 emit red, green and blue lights correspondingly. The red, green and blue lights are superimposed into white light. The white light enters the first polarizing plate 221a, and passes through the second lower substrate 212, to the second liquid crystal layer 215. Light arrived at the second liquid crystal layer 215 passes through the second upper substrate 213, and leaves from the second polarizing plate, to form a monochrome image with high brightness.

Second Embodiment

This embodiment differs from the first embodiment in the backlight device. Specifically, the second backlight device 220 of the outdoor-readable LCD 200 based on the first

embodiment is provided with additional white LEDs **220w** (shown in FIG. 5). For other arrangements regarding the outdoor-readable LCD **200**, one may refer to the first embodiment.

Now refer to FIG. 7(a) and FIG. 7(b). When the intensity of ambient light detected by the ambient light sensor is lower than a predetermined light intensity of the outdoor-readable LCD **200**, the light source control device switches off the white LEDs **220w**, and switches on the red LEDs **220r**, the green LEDs **220g** and the blue LEDs **220b** of the second backlight device **220** in sequence according to the sensing signal. The red LEDs **220r**, the green LEDs **220g** and the blue LEDs **220b** emit red, green and blue lights with predetermined delays. The red, green and blue lights enter the first polarizing plate **221a**, and pass through the second lower substrate **212**, to the second liquid crystal layer **215**. Lights arrived at the second liquid crystal layer **215** pass through the second upper substrate **213**, and leave from the second polarizing plate, to achieve color representation. When the detected intensity of ambient light is higher than the predetermined light intensity of the outdoor-readable LCD **200**, the white LEDs **220w** are switched on, meanwhile, the red LEDs **220r**, the green LEDs **220g** and the blue LEDs **220b** are switched on in sequence to emit red, green and blue lights. The red, green and blue lights enter the first polarizing plate **221a**, and pass through the second lower substrate **212**, to the second liquid crystal layer **215**. Lights arrived at the second liquid crystal layer **215** pass through the second upper substrate **213**, and leave from the second polarizing plate. By switching on the white LEDs **220w**, additional white back light is provided to the outdoor-readable LCD **200**, thereby enhancing its backlight and forming a color image with high brightness.

Third Embodiment

As shown in FIG. 5, an outdoor-readable LCD **200** of the invention includes: a liquid crystal panel **210**, a second backlight device **220** adapted to illuminate the liquid crystal panel **210**, a second scanning driver **230** adapted to provide a scanning signal to the liquid crystal panel **210**, a second data driver **240** adapted to provide a data signal to the liquid crystal panel **210**, and a light source control device (not shown) adapted to adjust the brightness of the second backlight device **220**. The liquid crystal panel **210** includes: a second lower substrate **212** including second pixel electrodes **211**, a second upper substrate **213** facing the second lower substrate **212**, a second common electrode **214** provided on the side of the second upper substrate **213** facing to the second lower substrate **212**, and a second liquid crystal layer **215** provided between the second lower substrate **212** and the second upper substrate **213**. The second backlight device **220** includes a number of red LEDs **220r**, green LEDs **220g** and blue LEDs **220b**, and further includes a first polarizing plate **221a** and a second polarizing plate. The first polarizing plate **221a** is mounted on the side of the second lower substrate **212** facing away from the second pixel electrodes **211**. The second polarizing plate is mounted on a side of the second upper substrate **213** facing away from the second common electrode **214**. The red LEDs **220r**, green LEDs **220g** and blue LEDs **220b** of the second backlight device **220** are provided facing the first polarizing plate **221a** from a certain distance away. When the red LEDs **220r**, green LEDs **220g** and blue LEDs **220b** of the second backlight device **220** are switched on in sequence, the red LEDs **220r**, the green LEDs **220g** and the blue LEDs **220b** emit red, green and blue lights with predetermined delays; or, the red LEDs **220r**, green LEDs **220g** and blue LEDs **220b** are

switched on at the same time, and the red, green and blue lights emitted are superimposed, resulting in white light.

Particularly, the outdoor-readable LCD according to the invention may further include an ambient light sensor (not shown), adapted to sense the intensity of ambient light and output a sensing signal. The light source control device adjusts the second backlight device **220** based on the sensing signal.

Now refer to FIG. 8. When the intensity of ambient light detected by the ambient light sensor is lower than a predetermined light intensity of the outdoor-readable LCD **200**, the light source control device adjusts a bias voltage *V* of the red LEDs **220r**, the green LEDs **220g** and the blue LEDs **220b** of the second backlight device **220** to be zero according to the sensing signal, and the red LEDs **220r**, the green LEDs **220g** and the blue LEDs **220b** are switched on in sequence to emit red, green and blue lights with predetermined delays. The red, green and blue lights enter the first polarizing plate **221a**, and pass through the second lower substrate **212**, to the second liquid crystal layer **215**. Lights arrived at the second liquid crystal layer **215** pass through the second upper substrate **213**, and leave from the second polarizing plate. When the intensity of ambient light detected by the ambient light sensor is higher than the predetermined light intensity of the outdoor-readable LCD **200**, the light source control device adjusts the bias voltage *V* of the red LEDs **220r**, the green LEDs **220g** and the blue LEDs **220b** of the second backlight device **220** according to the sensing signal, by setting the bias voltage *V* to a predetermined value according to the intensity of ambient light. Thereby the brightness of backlight provided by the second backlight device **220** are elevated, and the red LEDs **220r**, the green LEDs **220g** and the blue LEDs **220b** are switched on in sequence to emit red, green and blue lights with predetermined delays. The red, green and blue lights enter the first polarizing plate **221a**, and pass through the second lower substrate **212**, to the second liquid crystal layer **215**. Lights arrived at the second liquid crystal layer **215** pass through the second upper substrate **213**, and leave from the second polarizing plate, to form a color image with high brightness.

To sum up, the outdoor-readable LCD **200** applies red, green and blue (R, G, B) lights in sequence on the same pixel. The eyes of the observer mix the successive images into a color picture due to image sticking. The invention without an expensive color filter, can realize outdoor readability, lower costs, lower power consumption and improved resolution, and increase illumination utilization of the backlight device.

Those skilled in the art shall understand that various modifications and alternations of the invention can be made without deviation from the scope of the invention. Accordingly, the invention shall include those modifications and alternations within the scope defined by the appended claims.

The invention claimed is:

1. An outdoor-readable Liquid Crystal Display (LCD), comprising:
 - a liquid crystal panel without a color filter, the liquid crystal panel comprising an upper substrate, a lower substrate and a liquid crystal layer provided between the upper substrate and the lower substrate;
 - a backlight device, comprising a plurality of red Light-Emitting Diodes (LEDs), green LEDs, blue LEDs, and white LEDs; and
 - a light source control device, adapted to adjust the backlight device based on an intensity of ambient light, wherein, when the intensity of ambient light is lower than a predetermined light intensity of the outdoor-readable LCD, the red LEDs, the green LEDs and the blue

7

LEDs of the backlight device are switched on in sequence to emit lights with predetermined delays; and when the intensity of ambient light is higher than the predetermined light intensity, the red LEDs, the green LEDs, the blue LEDs, and the white LEDs of the backlight device are switched on at the same time to emit white light.

2. The outdoor-readable LCD according to claim 1, wherein the outdoor-readable LCD further comprises an ambient light sensor adapted to detect the intensity of ambient light and output a sensing signal; and wherein the light source control device is adapted to adjust the backlight device based on the sensing signal.

3. An outdoor-readable Liquid Crystal Display (LCD), comprising:

a liquid crystal panel without a color filter, the liquid crystal panel comprising an upper substrate, a lower substrate and a liquid crystal layer provided between the upper substrate and the lower substrate;

a backlight device, comprising a plurality of red Light-Emitting Diodes (LEDs), green LEDs, blue LEDs and white LEDs; and

a light source control device, adapted to adjust the backlight device based on an intensity of ambient light, wherein, when the intensity of ambient light is lower than a predetermined light intensity of the outdoor-readable LCD, the white LEDs are switched off, and the red LEDs, the green LEDs and the blue LEDs of the backlight device are switched on in sequence to emit lights with predetermined delays; and when the intensity of ambient light is higher than the predetermined light intensity, the white LEDs are switched on to emit light, meanwhile, the red LEDs, the green LEDs and the blue LEDs of the backlight device are switched on in sequence to emit lights with predetermined delays.

4. The outdoor-readable LCD according to claim 3, wherein the outdoor-readable LCD further comprises an ambient light sensor adapted to detect the intensity of ambient light and output a sensing signal; and wherein the light source control device is adapted to adjust the backlight device based on the sensing signal.

5. A method for driving an outdoor-readable Liquid Crystal Display (LCD), wherein the outdoor-readable LCD comprises:

8

a liquid crystal panel without a color filter, the liquid crystal panel comprising an upper substrate, a lower substrate and a liquid crystal layer provided between the upper substrate and the lower substrate;

a backlight device, comprising a plurality of red Light-Emitting Diodes (LEDs), green LEDs, blue LEDs, and white LEDs; and

a light source control device, adapted to adjust the backlight device based on an intensity of ambient light,

wherein the method for driving the outdoor-readable LCD comprises: when the intensity of ambient light is lower than a predetermined light intensity of the outdoor-readable LCD, switching on the red LEDs, the green LEDs and the blue LEDs of the backlight device in sequence to emit lights with predetermined delays; and when the intensity of ambient light is higher than the predetermined light intensity, switching on the red LEDs, the green LEDs, the blue LEDs, and the white LEDs of the backlight device at the same time to emit white light.

6. A method for driving an outdoor-readable Liquid Crystal Display (LCD), wherein the outdoor-readable LCD comprises:

a liquid crystal panel without a color filter, the liquid crystal panel comprising an upper substrate, a lower substrate and a liquid crystal layer provided between the upper substrate and the lower substrate;

a backlight device, comprising a plurality of red Light-Emitting Diodes (LEDs), green LEDs, blue LEDs and white LEDs; and

a light source control device, adapted to adjust the backlight device based on an intensity of ambient light, and wherein the method for driving the outdoor-readable LCD comprises: when the intensity of ambient light is lower than a predetermined light intensity of the outdoor-readable LCD, switching off the white LEDs, and switching on the red LEDs, the green LEDs and the blue LEDs of the backlight device in sequence to emit lights with predetermined delays; and when the intensity of ambient light is higher than the predetermined light intensity, switching on the white LEDs to emit light, meanwhile, switching on the red LEDs, the green LEDs and the blue LEDs of the backlight device in sequence to emit lights with predetermined delays.

* * * * *

专利名称(译)	户外可读液晶显示装置		
公开(公告)号	US8847877	公开(公告)日	2014-09-30
申请号	US14/132828	申请日	2009-03-31
[标]申请(专利权)人(译)	上海天马微电子有限公司		
申请(专利权)人(译)	上海天马微电子有限公司.		
当前申请(专利权)人(译)	上海天马微电子有限公司.		
[标]发明人	DEN BOER WILLEM PENG XUHUI LING ZHIHUA HUANG ZHONGSHOU		
发明人	DEN BOER, WILLEM PENG, XUHUI LING, ZHIHUA HUANG, ZHONGSHOU		
IPC分类号	G09G3/36 G02F1/1335 G09G3/34		
CPC分类号	G09G3/36 G09G3/3413 G09G3/3426 G09G2320/0626 G09G2310/0235 G09G2360/144 G09G2330/021 G02F2001/133612 G02F2201/58		
优先权	200810043215.6 2008-04-03 CN		
其他公开文献	US20140104254A1		
外部链接	Espacenet USPTO		

摘要(译)

室外可读液晶显示装置 (200) 包括液晶面板 (210), 背光装置 (220) 和光源控制装置。背光装置 (220) 包括多个红色发光二极管 (220r), 绿色发光二极管 (220g) 和蓝色发光二极管 (220b)。光源控制装置用于基于环境光的光强度调节背光装置 (220)。当环境光的光强度低于液晶显示装置 (200) 的预定光强度时, 红色发光二极管 (220r), 绿色发光二极管 (220g) 和蓝色发光二极管 (220b) 背光装置 (220) 依次通电以在预定的时间滞后发光。当环境光的光强度高于预定光强度时, 背光装置 (220) 的红色发光二极管 (220r), 绿色发光二极管 (220g) 和蓝色发光二极管 (220b) 通电同时发光。

