



US007212261B2

(12) **United States Patent**
Rho

(10) **Patent No.:** **US 7,212,261 B2**
(45) **Date of Patent:** **May 1, 2007**

(54) **COLOR FILTER PANEL AND LIQUID CRYSTAL DISPLAY INCLUDING THE SAME**

(75) Inventor: **Soo-Guy Rho**, Suwon-si (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.** (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 250 days.

(21) Appl. No.: **10/917,186**

(22) Filed: **Aug. 10, 2004**

(65) **Prior Publication Data**

US 2005/0083452 A1 Apr. 21, 2005

(30) **Foreign Application Priority Data**

Oct. 16, 2003 (KR) 10-2003-0072092

(51) **Int. Cl.**
G02F 1/1335 (2006.01)

(52) **U.S. Cl.** **349/106**

(58) **Field of Classification Search** 349/106,
349/109, 108, 114, 105, 78, 80, 96, 97, 113
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,335,774 B1* 1/2002 Ono 349/106

FOREIGN PATENT DOCUMENTS

EP 0271105 6/1988

* cited by examiner

Primary Examiner—Dung T. Nguyen

Assistant Examiner—Thoi V. Duong

(74) *Attorney, Agent, or Firm*—F. Chau & Associates, LLC

(57) **ABSTRACT**

An LCD comprising a first substrate having an inner surface and an outer surface; a green color filter formed on the outer surface of the first substrate; red, green, and blue color filters formed on the inner surface of the first substrate; a second substrate facing the first substrate and having an inner surface and an outer surface; a pixel electrode formed on the inner surface of the second substrate; a common electrode formed on the inner surface of one of the first and second substrates; and a liquid crystal layer disposed between the first substrate and the second substrate is provided. By this structure, a green light having high color purity is produced. The manufacturing method of an LCD is simplified by replacing the black matrix with the overlapped color filters.

10 Claims, 3 Drawing Sheets




FIG.1




FIG.2




FIG.3




FIG. 4





FIG. 5



COLOR FILTER PANEL AND LIQUID CRYSTAL DISPLAY INCLUDING THE SAME

BACKGROUND OF THE INVENTION

(a) Field of the Invention

The present disclosure relates to liquid crystal displays (LCDs), and in detail, to a method for improving display quality and viewing angle of LCDs.

(b) Description of the Related Art

An LCD includes two panels provided with field-generating electrodes, and a liquid crystal (LC) layer interposed therebetween. The LCD displays images by applying voltages to the field-generating electrodes to generate an electric field in the LC layer, which determines orientations of LC molecules in the LC layer to adjust polarization of incident light.

In an LCD, usually, red, green, and blue color filters are sequentially disposed. Color images are displayed by controlling intensity of light which passes through the color filters.

However, there are limitations in displaying full colors by using three color filters.

Recently, as LCDs have been gaining popularity as multimedia displays, the need for good color reproducibility has increased. Especially, when an LCD is used as a television, good color reproducibility is extremely important.

When color reproducibility is discussed, the green color is most important. The green color of the National Television Standards Committee (NTSC) is marked at $x=0.21$, $y=0.70$ on color coordinates of the International Commission of Illumination (CIE). However, the green light from the conventional green color filter of an LCD television having a thickness of $1.9\text{ }\mu\text{m}$ is marked at $x=0.275$, $y=0.60$ on the CIE color coordinate system.

When the conventional green color filter is used, the color reproducibility reaches only up to 72% of natural color. If one wishes to make a green color filter producing green color of NTSC which allows color reproducibility of 80% to 100%, one of the following two methods may be used. The first is increasing the dispersion density of pigments in the color filter, and the second is increasing the thickness of the color filter. However, when the dispersion density of pigments in the color filter is increased, stability of the photoresist of the color filter is degraded. When the thickness of the color filter is increased, the color filter needs to have a thickness of about $7.6\text{ }\mu\text{m}$, which is four times thicker than that of the normal color filter. This causes difficulty in forming the color filter.

SUMMARY OF THE INVENTION

To solve such a problem, the present invention comprises a color filter panel having green color filters on both sides thereof.

In more detail, a liquid crystal display comprising a first substrate having an inner surface and an outer surface; a green color filter formed on the outer surface of the first substrate; red, green, and blue color filters formed on the inner surface of the first substrate; a second substrate facing the first substrate and having an inner surface and an outer surface; a pixel electrode formed on the inner surface of the second substrate; a common electrode formed on the inner surface of one of the first and second substrates; and a liquid crystal layer disposed between the first substrate and the second substrate is provided.

The green color filter formed on the outer surface of the first substrate may be disposed on the whole display area except at red and blue pixel areas, the green and blue color filters formed on the inner surface of the first substrate are respectively disposed on green and blue pixel areas, and the red color filter formed on the inner surface of the first substrate is disposed on the whole display area except at the green and blue pixel areas.

The green color filter formed on the outer surface of the first substrate may be at least 2.5 times the thickness of the green color filter formed on the inner surface of the first substrate.

A color filter panel comprising a transparent insulating substrate having two surfaces; a green color filter formed on a first surface of the insulating substrate; and red, green, and blue color filters formed on a second surface of the insulating substrate, wherein the green color filter formed on the first surface is removed in predetermined areas to expose part of the first surface of the insulating substrate, the red color filter formed on the second surface is disposed on the area except at the areas that the green and blue color filters are disposed, and the red and blue color filters formed on the second surface are seen through the predetermined areas exposing the first surface of the insulating substrate is provided.

The color filter panel may further include a transparent electrode formed on the red, green, and blue color filters. The thickness of the green color filter formed on the first surface may be 2.5 times the thickness of the green color filter formed on the second surface.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other advantages of the present invention will become more apparent by describing preferred embodiments thereof in detail with reference to the accompanying drawings, in which:

FIG. 1 is a sectional view of a liquid crystal display (LCD) according to an exemplary embodiment of the present invention;

FIG. 2 is a layout view of the color filter panel of the LCD according to the exemplary embodiment of the present invention shown from the top side;

FIG. 3 is a layout view of the color filter panel of the LCD according to the exemplary embodiment of the present invention shown from the bottom side;

FIG. 4 shows spectrum graphs of a light passing through a $1.9\text{ }\mu\text{m}$ green color filter and a light passing through a green color filter according to an exemplary embodiment of the present invention; and

FIG. 5 shows spectrum graphs of three kinds of light respectively passing through three kinds of color filters according to an exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. The present invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein.

In the drawings, the thickness of layers, films, and regions are exaggerated for clarity. Like numerals refer to like elements throughout. It will be understood that when an

element such as a layer, film, region, or substrate is referred to as being "on" another element, it can be directly on the other element or intervening elements may also be present. In contrast, when an element is referred to as being "directly on" another element, there are no intervening elements present.

Now, liquid crystal displays according to embodiments of the present invention will be described with reference to the accompanying drawings.

FIG. 1 is a sectional view of a liquid crystal display (LCD) according to an exemplary embodiment of the present invention. FIG. 2 is a layout view of the color filter panel of the LCD according to the exemplary embodiment of the present invention shown from the top side. FIG. 3 is a layout view of the color filter panel of the LCD according to the exemplary embodiment of the present invention shown from the bottom side.

An LCD according to an exemplary embodiment includes a thin film transistor (TFT) array panel 100, a color filter panel 200 facing the TFT array panel 100, a liquid crystal layer disposed between the two panels 100 and 200, a pair of compensation films 11 and 21 respectively disposed on the outside of the two panels 100 and 200, and a pair of polarizing films 12 and 22 respectively disposed on outside of the two compensation films 11 and 12.

The TFT array panel 100 will now be described in detail.

A plurality of pixel electrodes 190 made of indium tin oxide (ITO) or indium zinc oxide (IZO) are formed on a transparent substrate such as glass. Each pixel electrode 190 is connected to a TFT which is a switching element and is applied an image signal voltage through the TFT. Here, the TFT has a gate electrode connected to a gate line (not illustrated) transmitting scanning signals, a source electrode connected to a data line (not illustrated) transmitting image signals, and a drain electrode connected to the pixel electrode 190 that switches the image signals according to the scanning signals.

For a reflective LCD, the pixel electrode 190 is formed of a reflective metal instead of a transparent material, and the lower polarizing film 12 and the lower compensation film 11 are omitted.

Next, the color filter panel 200 will be described in detail.

Red, green, and blue color filters 230R, 230G, and 230B and a common electrode 270 made of a transparent conductive material such as indium tin oxide (ITO) or indium zinc oxide (IZO) are formed on the lower surface of an upper substrate 210 made of a transparent insulating material such as glass.

Here, the green color filter 230G and the blue color filter 230B are respectively formed on the corresponding pixel areas. The red color filter 230R is formed on the whole display area except at the areas of the green and blue color filters 230G and 230B, but including the red pixel area.

The thicknesses of the color filters 230R, 230G, and 230B are about 1.9 μm .

A green color filter 230G is formed on the upper surface of the upper substrate 210.

The green color filter 230G formed on the upper surface of the upper substrate 210 is disposed on the whole area of the display area except at the areas of the red and blue pixels.

Here, the display area means an area to display images in an LCD. The green color filter 230G formed on the upper surface of the upper substrate 210 has a thickness of about 5.7 μm .

The thickness of the color filters formed on the lower and upper surfaces of the upper substrate 210 may be modified according to their properties. However, under any circum-

stances, the thickness ratio of the green color filter on the lower surface to that on the upper surface is preferably over 1:2.5.

As described above, when the green color filter 230G is formed on the upper surface of the upper substrate 210, and the red, green, and blue color filters 230R, 230G, and 230B are formed on the lower surface of the upper substrate 210, a red light and a blue light are respectively produced by the red color filter 230R and the blue color filter 230B having thicknesses of about 1.9 μm in the red and blue pixels, and a green light having high color purity is produced by the green color filters 230G having a total thickness of about 7.6 μm in the green pixel. The red color filter 230R and the green color filter 230G overlap each other to block almost all of the light in the areas between the pixel areas and the area around the display area. The overlapped red and green color filters 230R and 230G play a role of a black matrix.

The lower polarizing film 12 and the upper polarizing film 22 are preferably disposed to make their polarizing axes perpendicular to each other. Under such polarizing films disposition, the LCD shows a normally black mode such that black is displayed when there is no electric field in the liquid crystal layer.

According to the present invention, the green color filter 230G can have sufficient thickness since the green color filters 230G are formed on both side of the color filter panel 200. Such a green color filter having sufficient thickness can produce a green light having high color purity.

FIG. 4 shows spectrum graphs of a light passing through a 1.9 μm green color filter and a light passing through a green color filter according to an exemplary embodiment of the present invention.

In FIG. 4, curve A represents a spectrum graph of a light passing through 1.9 μm green color filter, and curve B represents a spectrum graph of a light passing through a green color filter according to an exemplary embodiment of the present invention.

As shown in FIG. 4, the spectrum of the green light produced by the green color filter according to the present invention is distributed in a narrower wavelength range than that of the green light produced by a conventional green color filter having a thickness of 1.9 μm .

The overlapped red and green color filters 230R and 230G replace the black matrix in the exemplary embodiment of the present invention. The reason why the overlapped red and green color filters 230R and 230G can play a role of a black matrix will be described with reference to FIG. 5.

FIG. 5 shows spectrum graphs of three kinds of lights respectively passing through three kinds of color filters according to an exemplary embodiment of the present invention.

As shown in FIG. 5, the green color filter 230G of the exemplary LCD according to the present invention is a band pass filter of wavelengths ranging from 495~580 nm, and the red color filter 230R is a high pass filter of wavelengths of 580 nm or longer. According, when a white light passes through both the green and red color filters 230G and 230R, all the light will be blocked by the color filters 230G and 230G to display black.

As described above, in the present invention, a green light having high color purity is produced by forming the green color filters on both sides of the upper substrate 210. The manufacturing method of an LCD is simplified by replacing the black matrix with the overlapped color filters 230R and 230G.

Although preferred embodiments of the present invention have been described in detail hereinabove, it should be

5

clearly understood that many variations and/or modifications of the basic inventive concepts herein taught which may appear to those skilled in the present art will still fall within the spirit and scope of the present invention, as defined in the appended claims.

What is claimed is:

1. A liquid crystal display comprising:

a first substrate having an inner surface and an outer surface;

a green color filter formed on the outer surface of the first substrate, wherein the a green color filter is removed at predetermined areas to expose the outer surface of the first substrate:

red, green, and blue color filters formed on the inner surface of the first substrate;

a second substrate facing the first substrate and having an inner surface and an outer surface;

a pixel electrode formed on the inner surface of the second substrate;

a common electrode formed on the inner surface of one of the first and second substrates; and

a liquid crystal layer disposed between the first substrate and the second substrate.

2. The liquid crystal display of claim 1, wherein the green color filter formed on the outer surface of the first substrate is disposed on all the display area except at red and blue pixel areas, the green and blue color filters formed on the inner surface of the first substrate are respectively disposed on green and blue pixel areas, and the red color filter formed on the inner surface of the first substrate is disposed on all the display area except at the green and blue pixel areas.

3. The liquid crystal display of claim 2, wherein the green color filter formed on the outer surface of the first substrate is at least 2.5 times thicker than the green color filter formed on the inner surface of the first substrate.

4. A color filter panel comprising:

a transparent insulating substrate having two surfaces;

a green color filter formed on a first surface of the insulating substrate; and

red, green, and blue color filters formed on a second surface of the insulating substrate,

wherein the green color filter formed on the first surface is removed at predetermined areas to expose the first

6

surface of the insulating substrate, the red color filter formed on the second surface is disposed everywhere except at the areas where the green and blue color filters are disposed, and the red and blue color filters formed on the second surface are seen through the predetermined areas exposing the first surface of the insulating substrate.

5. The color filter panel of claim 4, further including a transparent electrode formed on the red, green, and blue color filters.

6. The color filter panel of claim 4, wherein the thickness of the green color filter formed on the first surface is 2.5 times the thickness of the green color filter formed on the second surface.

7. A color filter panel comprising:

a transparent insulating substrate having two surfaces;

a green color filter exclusively formed on a first surface of the first insulating; and

red, green, and blue color filters formed on a second surface of the insulating substrate,

wherein the green color filter formed on the first surface is removed at predetermined areas to expose the first surface of the insulating substrate.

8. The color filter panel of claim 7, further including a transparent electrode formed on the red, green, and blue color filters.

9. The color filter panel of claim 8, further including a transparent electrode formed on the red, green, and blue color filters.

10. A color filter panel comprising:

a transparent insulating substrate having two surfaces; red, green, and blue color filters formed on a second surface of the insulating substrate; and

a green color filter formed on a first surface of the insulating substrate and at least a portion of the green color filter overlaps a boundary of at least two different color filters,

wherein the green color filter formed on the first surface is removed at predetermined areas to expose the first surface of the insulating substrate.

* * * * *

专利名称(译)	滤色器面板和包括其的液晶显示器		
公开(公告)号	US7212261	公开(公告)日	2007-05-01
申请号	US10/917186	申请日	2004-08-10
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	RHO SOO GUY		
发明人	RHO, SOO-GUY		
IPC分类号	G02F1/1335 G02B5/20		
CPC分类号	G02F1/133514		
审查员(译)	NGUYEN , 龚便T.		
优先权	1020030072092 2003-10-16 KR		
其他公开文献	US20050083452A1		
外部链接	Espacenet USPTO		

摘要(译)

一种LCD，包括具有内表面和外表面的第一基板；在第一基板的外表面上形成绿色滤色器；红色，绿色和蓝色滤色器形成在第一基板的内表面上；第二基板，面向第一基板并具有内表面和外表面；像素电极形成在第二基板的内表面上；公共电极形成在第一和第二基板之一的内表面上；并且，提供设置在第一基板和第二基板之间的液晶层。通过这种结构，产生具有高色纯度的绿光。通过用重叠的滤色器代替黑矩阵，简化了LCD的制造方法。

