



US007215405B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 7,215,405 B2**
(45) **Date of Patent:** **May 8, 2007**

(54) **DISPENSER SYSTEM FOR LIQUID CRYSTAL DISPLAY PANEL AND METHOD OF USING THE SAME**

(75) Inventors: **Sang-Hyun Kim**, Gyoungsangbuk-Do (KR); **Sung-Su Jung**, Daegu (KR)

(73) Assignee: **LG.Philips LCD Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 114 days.

(21) Appl. No.: **10/701,489**

(22) Filed: **Nov. 6, 2003**

(65) **Prior Publication Data**

US 2004/0114094 A1 Jun. 17, 2004

(30) **Foreign Application Priority Data**

Nov. 19, 2002 (KR) 2002/72101

(51) **Int. Cl.**

G02F 1/13 (2006.01)

G02F 1/1339 (2006.01)

(52) **U.S. Cl.** **349/187; 349/153; 349/190**

(58) **Field of Classification Search** 349/1, 349/153, 187, 190, 191; 427/8, 421, 64, 427/162, 163.1, 164, 165; 118/668, 669
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,978,580 A 9/1976 Leupp et al.
4,094,058 A 6/1978 Yasutake et al.
4,653,864 A 3/1987 Baron et al.

4,691,995 A 9/1987 Yamazaki et al.
4,775,225 A 10/1988 Tsuboyama et al.
5,247,377 A 9/1993 Omeis et al.
5,263,888 A 11/1993 Ishihara et al.
5,379,139 A 1/1995 Sato et al.
5,406,989 A 4/1995 Abe
5,499,128 A 3/1996 Hasegawa et al.
5,507,323 A 4/1996 Abe
5,511,591 A 4/1996 Abe
5,539,545 A 7/1996 Shimizu et al.
5,548,429 A 8/1996 Tsujita
5,642,214 A 6/1997 Ishii et al.
5,680,189 A 10/1997 Shimizu et al.
5,742,370 A 4/1998 Kim et al.
5,757,451 A 5/1998 Miyazaki et al.
5,852,484 A 12/1998 Inoue et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1 003 006 A1 5/2000

(Continued)

Primary Examiner—Toan Ton


Assistant Examiner—Tai Duong

(74) *Attorney, Agent, or Firm*—McKenna Long & Aldridge LLP

(57) **ABSTRACT**

A dispenser system for a liquid crystal display panel includes a table to overturn a substrate having at least one image display part on a first surface of the overturned substrate, and at least one syringe system to supply sealant onto a first surface of the overturned substrate to form a seal pattern along outer edges of the image display part on the first surface of the overturned substrate, wherein the at least one syringe system moves along horizontal directions.

33 Claims, 13 Drawing Sheets



US 7,215,405 B2

Page 2

U.S. PATENT DOCUMENTS

5,854,664	A	12/1998	Inoue et al.	
5,861,932	A	1/1999	Inata et al.	
5,875,922	A	3/1999	Chastine et al.	
5,952,676	A	9/1999	Sato et al.	
5,956,112	A	9/1999	Fujimori et al.	
6,001,203	A	12/1999	Yamada et al.	
6,011,609	A	1/2000	Kato et al.	
6,016,178	A	1/2000	Kataoka et al.	
6,016,181	A	1/2000	Shimada	
6,055,035	A	4/2000	von Gutfeld et al.	
6,163,357	A	12/2000	Nakamura	
6,219,126	B1	4/2001	Von Gutfeld	
6,226,067	B1	5/2001	Nishiguchi et al.	
6,236,445	B1	5/2001	Foschaar et al.	
6,304,306	B1	10/2001	Shiomi et al.	
6,304,311	B1	10/2001	Egami et al.	
6,337,730	B1	1/2002	Ozaki et al.	
6,414,733	B1	7/2002	Ishikawa et al.	
2001/0021000	A1	9/2001	Egami	
2004/0001177	A1 *	1/2004	Byun et al.	349/187
2004/0090591	A1 *	5/2004	Jung	349/187

FOREIGN PATENT DOCUMENTS

EP	1 003 066	5/2000
JP	51-65656	6/1976
JP	57-038414	3/1982
JP	57-38414	3/1982
JP	57-088428	6/1982
JP	57-88428	6/1982
JP	58-27126	2/1983
JP	58-0271296	2/1983
JP	59-057221	4/1984
JP	59-57221	4/1984
JP	59-195222	11/1984
JP	60-111221	6/1985
JP	60-164723	8/1985
JP	60-217343	10/1985
JP	61-7822	1/1986
JP	61-007822	1/1986
JP	61-055625	3/1986
JP	61-55625	3/1986
JP	S62-054225	3/1987
JP	S62-054228	3/1987
JP	62-89025	4/1987
JP	62-089025	4/1987
JP	62-90622	4/1987
JP	62-090622	4/1987
JP	62-205319	9/1987
JP	63-109413	5/1988
JP	63-110425	5/1988
JP	63-128315	5/1988
JP	63-311233	12/1988
JP	H03-009549	1/1991
JP	H05-036425	2/1993
JP	H05-036426	2/1993
JP	H05-107533	4/1993
JP	05-127179	5/1993
JP	5-127179	5/1993
JP	5-154923	6/1993
JP	05-154923	6/1993
JP	5-265011	10/1993
JP	05-265011	10/1993
JP	5-281557	10/1993
JP	05-281557	10/1993
JP	05-281562	10/1993
JP	5-281562	10/1993
JP	H06-018829	1/1994
JP	06-051256	2/1994
JP	6-51256	2/1994
JP	H06-064229	3/1994

JP	06-148657	5/1994
JP	6-148657	5/1994
JP	06-160871	6/1994
JP	6-160871	6/1994
JP	H06-194637	7/1994
JP	6-235925	8/1994
JP	06-235925	8/1994
JP	06-265915	9/1994
JP	6-265915	9/1994
JP	6-313870	11/1994
JP	06-313870	11/1994
JP	7-84268	3/1995
JP	07-084268	3/1995
JP	07-128674	5/1995
JP	7-128674	5/1995
JP	07-181507	7/1995
JP	7-181507	7/1995
JP	H07-275770	10/1995
JP	H07-275771	10/1995
JP	H08-073133	3/1996
JP	08-095066	4/1996
JP	8-95066	4/1996
JP	08-101395	4/1996
JP	8-101395	4/1996
JP	8-106101	4/1996
JP	08-106101	4/1996
JP	H08-110504	4/1996
JP	H08-136937	5/1996
JP	08-171094	7/1996
JP	8-171094	7/1996
JP	8-190099	7/1996
JP	08-190099	7/1996
JP	H08-173874	7/1996
JP	8-240807	9/1996
JP	08-240807	9/1996
JP	09-005762	1/1997
JP	9-5762	1/1997
JP	09-026578	1/1997
JP	9-26578	1/1997
JP	H09-001026	1/1997
JP	09-311340	2/1997
JP	09-61829	3/1997
JP	9-61829	3/1997
JP	9-73075	3/1997
JP	09-073075	3/1997
JP	09-073096	3/1997
JP	9-73096	3/1997
JP	H09-094500	4/1997
JP	09-127528	5/1997
JP	9-127528	5/1997
JP	9-230357	9/1997
JP	09-230357	9/1997
JP	9-281511	10/1997
JP	09-281511	10/1997
JP	9-311340	12/1997
JP	10-123537	5/1998
JP	10-123538	5/1998
JP	10-142616	5/1998
JP	10-177178	6/1998
JP	H10-174924	6/1998
JP	10-221700	8/1998
JP	10-282512	10/1998
JP	10-333157	12/1998
JP	10-333159	12/1998
JP	11-014953	1/1999
JP	11-14953	1/1999
JP	11-038424	2/1999
JP	11-38424	2/1999
JP	11-64811	3/1999
JP	11-064811	3/1999
JP	11-109388	4/1999
JP	11-133438	5/1999
JP	11-142864	5/1999

US 7,215,405 B2

Page 3

JP	11-174477	7/1999	JP	2001-264782	9/2001
JP	11-212045	8/1999	JP	2001-272640	10/2001
JP	11-248930	9/1999	JP	2001-281675	10/2001
JP	H11-262712	9/1999	JP	2001-281678	10/2001
JP	H11-264991	9/1999	JP	2001-282126	10/2001
JP	11-326922	11/1999	JP	2001-305563	10/2001
JP	11-344714	12/1999	JP	2001-330837	11/2001
JP	2000-002879	1/2000	JP	2001-330840	11/2001
JP	2000-2879	1/2000	JP	2001-356353	12/2001
JP	2000-29035	1/2000	JP	2001-356354	12/2001
JP	2000-029035	1/2000	JP	2002-14360	1/2002
JP	2000-056311	2/2000	JP	2002-014360	1/2002
JP	2000-56311	2/2000	JP	2002-23176	1/2002
JP	2000-66165	3/2000	JP	2002-023176	1/2002
JP	2000-066165	3/2000	JP	2002-49045	2/2002
JP	2000-066218	3/2000	JP	2002-049045	2/2002
JP	2000-093866	4/2000	JP	2002-079160	3/2002
JP	2000-137235	5/2000	JP	2002-080321	3/2002
JP	2000-147528	5/2000	JP	2002-082340	3/2002
JP	2000-193988	7/2000	JP	2002-82340	3/2002
JP	2000-241824	9/2000	JP	2002-090759	3/2002
JP	2000-284295	10/2000	JP	2002-90759	3/2002
JP	2000-292799	10/2000	JP	2002-090760	3/2002
JP	2000-310759	11/2000	JP	2002-90760	3/2002
JP	2000-310784	11/2000	JP	2002-107740	4/2002
JP	2000-338501	12/2000	JP	2002-122870	4/2002
JP	2001-5401	1/2001	JP	2002-122872	4/2002
JP	2001-005401	1/2001	JP	2002-122873	4/2002
JP	2001-5405	1/2001	JP	2002-131762	5/2002
JP	2001-005405	1/2001	JP	2002-139734	5/2002
JP	2001-013506	1/2001	JP	2002-156518	5/2002
JP	2001-13506	1/2001	JP	2002-169166	6/2002
JP	2001-033793	2/2001	JP	2002-169167	6/2002
JP	2001-33793	2/2001	JP	2002-182222	6/2002
JP	2001-42341	2/2001	JP	2002-202512	7/2002
JP	2001-042341	2/2001	JP	2002-202514	7/2002
JP	2001-51284	2/2001	JP	2002-214626	7/2002
JP	2001-051284	2/2001	JP	2002-229042	8/2002
JP	2001-62370 A	3/2001	JP	2002-236276	8/2002
JP	2001-066615	3/2001	JP	2002-258299	8/2002
JP	2001-66615	3/2001	JP	2002-236292	9/2002
JP	2001-91727	4/2001	JP	2002-277865	9/2002
JP	2001-091727	4/2001	JP	2002-277866	9/2002
JP	2001-117105	4/2001	JP	2002-277881	9/2002
JP	2001-117109	4/2001	JP	2002-287156	10/2002
JP	2001-133745	5/2001	JP	2002-296605	10/2002
JP	2001-133794	5/2001	JP	2002-311438	10/2002
JP	2001-133799	5/2001	JP	2002-311440	10/2002
JP	2001-142074	5/2001	JP	2002-311442	10/2002
JP	2001-147437	5/2001	JP	2002-323687	11/2002
JP	2001-154211	6/2001	JP	2002-323694	11/2002
JP	2001-166272	6/2001	JP	2002-333628	11/2002
JP	2001-166310	6/2001	JP	2002-333635	11/2002
JP	2001-166320	6/2001	JP	2002-333843	11/2002
JP	2001-183683	7/2001	JP	2002-341329	11/2002
JP	2001-201750	7/2001	JP	2002-341355	11/2002
JP	2001-209052	8/2001	JP	2002-341356	11/2002
JP	2001-209056	8/2001	JP	2002-341357	11/2002
JP	2001-209057	8/2001	JP	2002-341358	11/2002
JP	2001-209058	8/2001	JP	2002-341359	11/2002
JP	2001-209060	8/2001	JP	2002-341362	11/2002
JP	2001-215459	8/2001	KR	2000-0035302	6/2000
JP	2001-222017	8/2001			
JP	2001-235758	8/2001			
JP	2001-255542	9/2001			

* cited by examiner

FIG. 1
RELATED ART




FIG. 2A
RELATED ART




FIG. 2B
RELATED ART




FIG. 3
RELATED ART




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9A




FIG. 9B




FIG. 9C





FIG. 9D



DISPENSER SYSTEM FOR LIQUID CRYSTAL DISPLAY PANEL AND METHOD OF USING THE SAME

The present invention claims the benefit of Korean Patent Application No. P2002-072 101 filed in Korea on Nov. 19, 2002, which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a dispensing system and a method using a dispensing system, and more particularly, to a dispenser system for a liquid crystal display panel and a method of using a dispensing system.

2. Discussion of the Related Art

In general, a liquid crystal display panel is used to display images according to data signals supplied to individual liquid crystal cells arranged in a matrix configuration, wherein light transmittance of the individual liquid crystal cells is controlled to display the image. Accordingly, liquid crystal display (LCD) devices include a liquid crystal display panel where a driver integrated circuit (IC) drives the individual liquid crystal cells.

The liquid crystal display panel includes a color filter substrate and a thin film transistor array substrate attached to each other, wherein a liquid crystal layer is disposed between the color filter substrate and the thin film transistor array substrate. In addition, the thin film transistor array substrate includes data lines and gate lines to intersect at right angles, thereby defining liquid crystal cells at every intersection of the data lines and gate lines. The data lines transmit data signals supplied from a data driver integrated circuit to the individual liquid crystal cells, and the gate lines transmit scan signals supplied from the gate driver integrated circuit to the individual liquid crystal cells. Data pads and gate pads are provided at distal end portions of each of the data and gate lines, respectively, to supply data signals and scan signals from the data driver integrated circuit and the gate driver integrated circuit to the data and gate lines, respectively. The gate driver integrated circuit sequentially supplies the scan signals to the gate lines so that the individual liquid crystal cells arranged in the matrix configuration can be sequentially selected on a line-by-line basis. Similarly, a data driver integrated circuit supplies the data signals to the data lines so that selected ones of the individual liquid crystal cells arranged in the matrix configuration can be provided with the data signals.

A common electrode and a pixel electrode are formed along inner surfaces of the color filter substrate and the thin film transistor array substrate, respectively, thereby supplying an electric field to the liquid crystal layer. The pixel electrode is formed at each of the individual liquid crystal cells on the thin film transistor array substrate, whereas the common electrode is integrally formed along an entire surface of the color filter substrate. Thus, by controlling voltages supplied to the pixel electrode and the common electrode, light transmittance of the individual liquid crystal cells can be individually controlled. In order to control the voltage supplied to the pixel electrode, a thin film transistor, which is commonly used as a switching device, is formed at each of the individual liquid crystal cells.

FIG. 1 is a plan view of a liquid crystal display panel according to the related art. In FIG. 1, a liquid crystal display panel 100 includes an image display part 113 where individual liquid crystal cells are arranged in a matrix configuration, a gate pad part 114 connected to gate lines of the

image display part 113, and a data pad part 115 connected to data lines of the image display part 113. The gate pad part 114 and the data pad part 115 are formed along edge regions of a thin film transistor array substrate 101 that does not overlap with a color filter substrate 102. The gate pad part 114 supplies scan signals from a gate driver integrated circuit (not shown) to the gate lines of the image display part 113, and the data pad part 115 supplies image information from the data driver integrated circuit (not shown) to the data lines of the image display part 113.

The data lines and the gate lines are provided on the thin film transistor array substrate 101 to intersect each other, wherein a thin film transistor for switching the liquid crystal cells is provided at the intersection of the data lines and the gate lines. In addition, a pixel electrode for driving the individual liquid crystal cells is connected to the thin film transistor provided on the thin film transistor array substrate 101, and a passivation film for protecting the pixel electrode and the thin film transistor is formed along an entire surface of the thin film transistor array substrate 101.

Color filters are separately coated at cell regions defined by a black matrix formed on the color filter substrate 102. In addition, a common transparent electrode is provided on the color filter substrate 102.

A cell gap is formed by spacers disposed between the thin film transistor array substrate 101 and the color filter substrate 102, and the thin film transistor array substrate 101 and the color filter substrate 102 are attached together using a seal pattern 116 formed along an outer edge of the image display part 113, wherein a cell gap is formed by spacers disposed between the thin film transistor array substrate 101 and the color filter substrate 102.

During fabrication of the liquid crystal display panel, a process for simultaneous formation of a plurality of unit liquid crystal display panels on a single glass substrate is commonly used. Accordingly, the process requires dividing the plurality of unit liquid crystal display panels formed on the single glass substrate using a cutting process to produce a plurality of individual liquid crystal display panels. Next, liquid crystal material is injected through a liquid crystal injection opening of each of the individual liquid crystal display panels to form a liquid crystal layer within the cell-gap that separates the thin film transistor array substrate 101 and the color filter substrate 102. Then, the liquid crystal injection openings are sealed.

FIGS. 2A and 2B are schematic plan and cross sectional views of a process for formation of a seal pattern according to the related art. In FIGS. 2A and 2B, a screen printing method includes patterning a screen mask 206 so that a plurality of seal pattern forming regions are selectively exposed, and selectively supplying a sealant 203 to the substrate 200 through a screen mask 206 using a rubber squeegee 208 to simultaneously form a plurality of seal patterns 216A~216F. The plurality of seal patterns 216A~216F formed on the substrate 200 provide a gap into which a liquid crystal layer is formed, and prevent leakage of the liquid crystal material to an exterior of the plurality of seal patterns 216A~216F. Accordingly, the plurality of seal patterns 216A~216F are formed along outer edges of the image display parts 213A~213F of the substrate 200, and a plurality of liquid crystal injection openings 204A~204F are formed at each one side of the seal patterns 216A~216F.

The screen printing method includes applying the sealant 203 on the screen mask 206 with the seal pattern forming regions patterned thereon, forming the plurality of seal

patterns **216A~216F** on the substrate **200** through printing with the rubber squeegee **208**, and evaporating a solvent contained in the seal patterns **216A~216F** and leveling them. The screen printing method is advantageous because of its convenience, but it is disadvantageous because of excessive consumption of the sealant **203** since the sealant **203** is applied along an entire surface of the screen mask **206** and printed using the rubber squeegee **208** to simultaneously form the plurality of seal patterns **216A~216F**. In addition, the screen printing method is problematic since a rubbing process of an orientation film (not shown) formed on the substrate **200** is altered as the screen mask **206** and the substrate **200** contact each other, thereby degrading image quality of the liquid crystal display device. Thus, a seal dispensing method has been proposed.

FIG. 3 is a schematic plan view of a seal pattern according to the related art. In FIG. 3, a seal dispensing method includes forming a plurality of seal patterns **316A~316F** along outer edges of a plurality of image display parts **313A~313F** formed on a substrate **300** by applying a certain pressure to syringes **301A~301C** filled with a sealant as a table **310** moves along forward/backward and left/right directions. Accordingly, the plurality of seal patterns **316A~316F** are sequentially formed as single lines around the image display parts **313A~313F**. During the seal dispensing method, since the sealant is selectively supplied to regions where the seal patterns **316A~316F** are to be formed, sealant consumption may be reduced. In addition, since the syringes **301A~301C** do not contact an orientation film (not shown) of the image display part **313** of the substrate **300**, the alignment of the rubbed orientation film would not be damaged and image quality of the liquid crystal display device may be improved.

In order to form the seal patterns **316A~316F**, the table **210** may be fixed and the syringes **301A~301C** may be horizontally moved along the forward/backward and left/right directions around the image display parts **313A~313F**. Accordingly, a certain pressure is applied to the syringes **301A~301C** filled with the sealant to dispense the sealant onto the substrate **300**, and the syringes **301A~301C** are moved along the forward/backward and left/right directions. However, foreign material generated from moving the syringes **301A~301C** may be deposited onto the image display parts **313A~313C**, thereby contaminating the liquid crystal display panel. Thus, in order to avoid contamination, the syringes **301A~301C** remain fixed and the table **310** is moved along the forward/backward and left/right directions.

However, keeping the syringes **301A~301C** fixed and moving the table **310** may be problematic. As an overall size of the liquid crystal display panel is enlarged, a corresponding area of the substrate **300** for fabricating the large-scale liquid crystal display panel increases. Thus, in order to form the seal patterns **316A~316F** on the substrate **300**, a driving distance of the table **310** is doubled in accordance with a short side of the substrate **300**. Accordingly, if a length of the short side of the substrate **300** is doubled, then the driving distance of the table **310** is increased by at least a factor of four. Therefore, if the area of the substrate **300** is increased, the dispenser occupies more space, thereby degrading clean room efficiency. In addition, since the table **310** is moved horizontally along forward/backward and left/right directions, a total time for forming the plurality of seal patterns **316A~316F** increases, thereby degrading productivity and efficiency.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a dispenser system for liquid crystal display panels and method of using a dispenser system for liquid crystal display panels that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

An object of the present invention is to provide to a dispenser system for a liquid crystal display panel for increasing productivity.

Another object of the present invention is to provide a method of using a dispenser system for a liquid crystal display panel for increasing productivity.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended claims.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, a dispenser system for a liquid crystal display panel includes a table to overturn a substrate having at least one image display part on a first surface of the overturned substrate, and at least one syringe system to supply sealant onto a first surface of the overturned substrate to form a seal pattern along outer edges of the image display part on the first surface of the overturned substrate, wherein the at least one syringe system moves along horizontal directions.

In another aspect, a dispenser system for a liquid crystal display panel includes a table to load, fix, and vertically align a substrate having at least one image display part formed on a first surface of the substrate, and at least one syringe system to supply sealant onto the first surface of the vertically-aligned substrate to form a seal pattern along outer edges of the at least one image display part, wherein the at least one syringe system moves along a vertical direction relative to a position of the substrate.

In another aspect, a method of using a dispenser system for a liquid crystal display panel includes loading and fixing a substrate on a table, overturning the table and the substrate, and supplying sealant from the dispenser system onto a first surface of the overturned substrate to form at least one seal pattern.

In another aspect, a method of using a dispenser system for a liquid crystal display panel includes loading and fixing a substrate on a table, rotating the table to vertically align the substrate, and supplying sealant from the dispenser system onto a first surface of the vertically-aligned substrate to form at least one seal pattern.

In another aspect, a method of dispensing sealant for a liquid crystal display panel includes loading and fixing a substrate on a table, overturning the table and the substrate, and supplying sealant from a dispenser system onto a first surface of the overturned substrate to form at least one seal pattern.

In another aspect, a method of dispensing sealant for a liquid crystal display panel includes loading and fixing a substrate on a table, vertically aligning the substrate, and supplying sealant from a dispenser system onto a first surface of the vertically-aligned substrate to form at least one seal pattern.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention. In the drawings:

FIG. 1 is a plan view of a liquid crystal display panel according to the related art;

FIGS. 2A and 2B are schematic plan and cross sectional views of a process for formation of a seal pattern according to the related art;

FIG. 3 is a schematic plan view of a seal pattern according to the related art;

FIG. 4 is a perspective schematic view of an exemplary dispenser system for a liquid crystal display panel according to the present invention;

FIG. 5 is a flow chart of an exemplary method of using a dispenser system using the dispenser system of FIG. 4 according to the present invention;

FIG. 6 is a schematic plan view of another exemplary dispenser system for a liquid crystal display panel according to the present invention;

FIG. 7 is a schematic plan view of another exemplary dispenser system for a liquid crystal display panel according to the present invention;

FIG. 8 is a schematic plan view of another exemplary dispenser system for a liquid crystal display panel according to the present invention; and

FIGS. 9A to 9D are perspective schematic views of an exemplary method of using a dispensing system according to the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

Reference will now be made in detail to the illustrated embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

FIG. 4 is a perspective schematic view of an exemplary dispenser system for a liquid crystal display panel according to the present invention. In FIG. 4, a dispenser system may include a plurality of syringes 401A~401C for supplying a sealant along outer edges of image display parts 413A~413F of an overturned substrate 400 using a plurality of nozzles 402A~402C provided at end portions of the syringes 401A~401C to form a plurality of seal patterns 416A~416F. Accordingly, table 410 may remain fixed while the syringes 401A~401C may move along horizontal directions to form the plurality of seal patterns 416A~416F. In FIG. 4, the table 410 may be first loaded with the substrate 400, wherein the plurality of image display parts 413A~413F may have been previously formed thereon. The substrate 400 may be a large-scale first glass substrate formed upon which a plurality of thin film transistors may have been previously fabricated, or a large-scale second glass substrate upon which a plurality of color filters may have been previously fabricated.

The syringes 401A~401C may be provided to correspond to a total number to the image display parts 413A~413F formed on the substrate 400, thereby simultaneously forming the plurality of seal patterns 416A~416F along the outer

edges of the image display parts 413A~413F. For example, if the image display parts formed on the substrate 400 have a matrix configuration including an M-number of lines and an N-number of columns, a matrix array of syringes may be provided to have an M-number of line syringes and an N-number of column syringes to provide sealant around the M×N matrix of image display parts formed on the substrate 400. Alternatively, the syringes may be provided to correspond to at least one line or at least one column of the image display parts having the M×N matrix configuration. In addition, the syringes may be driven simultaneously, may be driven individually, or may be driven in groups.

FIG. 5 is a flow chart of an exemplary method of using a dispenser system using the dispenser system of FIG. 4 according to the present invention. In FIG. 5, the substrate 400 having the plurality of image display parts 413A~413F formed thereon may be loaded and fixed onto the table 410 during a step of loading and fixing. Next, the substrate 400 may overturned during a step of overturning. Then, the syringes 401A~401C, which have the nozzles 402A~402C provided end portions thereof, may supply sealant along outer edges of the image display parts 413A~413F of the overturned substrate 400 to form the seal patterns 416A~416F, while being moved horizontally along forward/backward and left/right directions during a step of moving syringes to form seal patterns. Accordingly, since the driving of the syringes 401A~401C may be performed within an area of the substrate 400, even though the area of the substrate 400 increases, a size of the dispenser system for forming the seal patterns 416A~416F on the substrate 400 may change (i.e., increase or decrease) according to the increased area to the substrate 400. In addition, since the syringes may be provided to correspond to the total number to the image display parts formed on the substrate 400 and may be simultaneously or individually driven to form the seal patterns, an overall time to form the seal patterns may be reduced as compared to driving the table.

The exemplary seal patterns 416A~416F (in FIG. 4) formed by the dispenser system may differ in their form according to the method in which the liquid crystal layer is formed for the liquid crystal display panel. For example, using the vacuum injection method may require formation of an injection port in the seal patterns 416A~416F (in FIG. 4). However, the vacuum injection method may be problematic. First, since a significant amount of time is required to fill the liquid crystal material into the liquid crystal display panel, overall fabrication time of the liquid crystal display panel may be significantly increased. For example, when fabricating a liquid crystal display panel of about 15 inches, about 8 hours are required to fill the liquid crystal display panel with the liquid crystal material. In addition, as an overall size of the liquid crystal display panel increases, time required for filling the liquid crystal material increases. Thus, the vacuum injection method may not be adequate for large-scale liquid crystal display panels.

Second, significant amounts of the liquid crystal material are wasted due to the inherent processes for the vacuum injection method. For example, actual amounts of the injected liquid crystal material is very small compared to amounts of the liquid crystal material filled in the container used to fill the liquid crystal display panels, and when the liquid crystal material is exposed to air or to specific gases, the liquid crystal material may react with the gases and be degraded. Thus, even if large amounts of the liquid crystal material filled in the container is used to fill a plurality of the liquid crystal display panels, a relatively significant amount of the liquid crystal material remaining in the container must

be discarded. Accordingly, a unit price of the liquid crystal display panel would increase.

In order to overcome the problems and disadvantages of the vacuum injection method, a dropping method has been developed. The dropping method includes dropping a liquid crystal material onto a plurality of thin film transistors fabricated on a first large-scale glass substrate or on a plurality of color filters fabricated on a second large-scale glass substrates may be attached together to uniformly distribute the liquid crystal material along an entire image display region by applying pressure to the first and second glass substrates, thereby forming a liquid crystal layer. Since the liquid crystal material may be directly dropped onto either of the first or second glass substrates, the seal patterns 416A~416F may be formed as a closed pattern encompassing each outer edge of the image display parts 413A~413F, as shown in FIG. 4, thereby preventing leakage of the liquid crystal material. An ultraviolet (UV) hardening sealant may be used to form the seal patterns 416A~416F. Alternatively, a mixture of the ultraviolet hardening sealant and a thermosetting sealant may be applied. In addition, the liquid crystal material may be dropped within a comparatively short amount of time as compared to the vacuum injection method. Moreover, although the liquid crystal display panel may have a large size, the liquid crystal layer may be formed quickly between the first and second glass substrates, thereby increasing productivity. Thus, an increase in unit price of the liquid crystal display panel may be prevented.

During the exemplary method of FIG. 5, liquid crystal material dropped onto the substrate 400 prior to the overturning of the substrate may result in a flow of the liquid crystal material. Accordingly, the seal patterns 416A~416F may be formed on the substrate 400 upon which liquid crystal material may not be dropped. Alternatively, by using of the ultraviolet hardening sealant to form the seal patterns 416A~416F, flow of the liquid crystal material may not occur although the substrate 400 is overturned. For example, the ultraviolet hardening sealant may have a viscosity of about 400,000 cP(centi-Poise), wherein sealants with viscosities of above 100,000 cP(centi-Poise) may not flow in spite of the overturning of the substrate 400.

FIG. 6 is a schematic plan view of another exemplary dispenser system for a liquid crystal display panel according to the present invention. In FIG. 6, a dispenser system for a liquid crystal display panel may include a table 510 to overturn a loaded substrate 500 having a plurality of image display parts 513A~513F formed thereon, and a plurality of syringes 501A~501C to supply a sealant along outer edges of the image display parts 513A~513F of the overturned substrate 500 through nozzles 502A~502C provided at end portions of the syringes 501A~501C. Accordingly, the syringes 501A~501C may be used to form the seal patterns 516A~516F, while the table 510 may remain fixed and the syringes 501A~501C may be moved along horizontal directions.

During a method of using the dispenser system of FIG. 6, the substrate 500 may be loaded and fixed onto the table 510, and the table 510 may be overturned and fixed. Then, the syringes 501A~501C may supply the sealant along the outer edges of the image display parts 513A~513F of the substrate 500 to form the seal patterns 516A~516F, while the syringes 501A~501C may be moved along horizontal forward/backward and left/right directions. Accordingly, since driving of the syringes 501A~501C may be performed within an area of the substrate 500, although the area of the substrate 500

increases, a size of the dispensing system for forming the seal patterns 516A~516F on the substrate 500 may increase in relation to the increased area of the substrate 500.

In FIG. 6, bodies of the syringes 501A~501C may be positioned below the substrate 500 along the horizontal direction parallel of the table 510. In addition, portions of the bodies of the syringes 501A~501C may be bent toward the substrate 500 so that the nozzles 502A~502C provided at the end portions may be positioned at the outer edges of the image display parts 513A~513F of the substrate 500. Accordingly, a pressure for supplying the sealant filled in the syringes 501A~501C onto the substrate 500 through the nozzles 502A~502C may be reduced, thereby improving control of the dispensing of the sealant onto the substrate 500.

FIG. 7 is a schematic plan view of another exemplary dispenser system for a liquid crystal display panel according to the present invention. In FIG. 7, a dispenser system may include a table 610 disposed along a vertical direction, in which a substrate 600 having image display parts 613A~613F formed thereon may be loaded and fixed thereupon. The system may further include a plurality of syringes 601A~601C to supply a sealant along outer edges of the image display parts 613A~613F of the substrate 600 through nozzles 602A~602C, which may be provided at ends of the plurality of syringes 601A~601C, while the plurality of syringes 601A~601C may be moved along vertical directions relative to the substrate 600. The substrate 600 may be a large-scale glass substrate having a plurality of thin film transistors formed thereon or may be a large-scale glass substrate having a plurality of color filters formed thereon.

The syringes 601A~601C may be provided to correspond to a total number of image display parts 613A~613F formed on the substrate 600, thereby simultaneously forming the plurality of seal patterns 616A~616F along the outer edges of the image display parts 613A~613F. For example, if the image display parts are formed having a matrix array of an M-number of lines and an N-number of columns on the substrate 600, an M×N number array of syringes may be provided to correspond to the image display parts. Alternatively, the syringes 601A~601C may be provided to correspond to at least one line or at least one column of the image display parts having a matrix array of an M-number of lines and an N-number of columns. In addition, the syringes 601A~601C may be driven simultaneously, individually, or in groups.

A method for using the dispenser system of FIG. 7 may include loading and fixing the substrate 600 onto the table 610, wherein the table 600 may be positioned along a vertical direction or may be transitioned from a horizontal direction to a vertical direction. Then, the syringes 601A~601C may supply the sealant to form the seal patterns 616A~616F along the outer-edges of the image display parts 613A~613F of the substrate 400 while the syringes 601A~601C are vertically moved along forward/backward and left/right directions. Accordingly, since driving of the syringes 601A~601C may be performed within an area of the substrate 600, although the area of the substrate 600 may increase, a size of the dispenser system for forming the seal patterns 616A~616F on the substrate 600 may increase in accordance with the increased area to the substrate 600.

In addition, since the syringes 601A~601C may be simultaneously, individually, group driven to form the seal patterns 616A~616M×N, an overall time taken for forming the seal patterns 616A~616E may be reduced. Moreover, although the area of the image display parts 613A~613E may change according to a change of the liquid crystal

display panel or according to an increase in the area of the substrate **600**, the dispenser system and method of using the dispenser system may effectively compensate for the changes and increases.

In FIG. 7, the syringes **601A~601C** are positioned along a horizontal direction at a right angle below a surface of the vertically-aligned substrate **600** so that the nozzles **602A~602C** provided at the end portions of the syringes **601A~601C** may be positioned along an outer edge of the image display parts **613A~613F** of the substrate **600**. Accordingly, since a relatively low amount of pressure may be required for supplying the sealant filled in the syringes **601A~601C** to the outer edges of the image display parts **613A~613F** of the substrate **600**, the sealant supplying pressure may be easily controlled.

In addition, the seal patterns **616A~616F** may be formed in accordance with a desired method of providing liquid crystal material, i.e., liquid crystal injection or dropping methods. Accordingly, the seal patterns **616A~616F** may have different configurations. For example, using the vacuum injection method may result in forming the seal patterns **616A~616F** to have partial openings, similar to the seal patterns **316A~316F** in FIG. 3. Conversely, using the dropping method may result in forming the seal patterns **616A~616F** having closed patterns encompassing each outer edge of the image display parts **613A~613F**, as shown in FIG. 7.

When using the dropping method, if the seal patterns **616A~616F** are formed with a thermosetting sealant, the sealant may flow out to contaminate the dropped liquid crystal material while being heated during subsequent processing of the glass substrates. Thus, the seal patterns **616A~616F** may be formed having an ultraviolet hardening sealant or a mixture of the ultraviolet hardening sealant and a thermosetting sealant.

In FIG. 7, when the substrate **600** is aligned along the vertical direction, the liquid crystal material dropped onto the substrate **600** using the dropping method may flow. Accordingly, the seal patterns **616A~616F** may be formed on the substrate **600** where liquid crystal material may not be dropped.

FIG. 8 is a schematic plan view of another exemplary dispenser system for a liquid crystal display panel according to the present invention. In FIG. 8, a dispenser system for a liquid crystal display panel may include a table **710**, which may vertically stand a substrate **700** having image display parts **713A~713F** formed thereon that have been loaded and fixed thereon. The system may also include a plurality of syringes **701A~701C** to supply a sealant along outer edges of the image display parts **713A~713F** of the substrate **700** through nozzles **702A~702C**, which may be provided at end portions of the plurality of syringes **701A~701C**, to form seal patterns **716A~716F**. In addition, the plurality of syringes **701A~701C** may be moved along vertical directions in relation to the vertically-aligned substrate **700**.

During a method of using the dispenser system, the substrate **700** may be loaded and fixed onto the table **710**, and the table **710** may be aligned along the vertical direction and fixed. Then, the syringes **701A~701C** may supply the sealant while being moved along the vertical forward/backward and left/right directions, thereby forming the seal patterns **716A~716F** along the outer edges of the image display parts **713A~713F** of the substrate **700**. Accordingly, since a driving of the syringes **701A~701C** may be performed within an area of the vertically-aligned substrate **700**, although the area of the substrate **700** may increase, a size of the dispenser system equipment for forming the seal

patterns **716A~716F** on the substrate **700** may change (i.e., increase or decrease) to correspond to the increased area to the substrate **700**.

In FIG. 8, bodies of the syringes **701A~701C** may be positioned below the substrate **700** along the vertical direction in parallel to the vertically-aligned substrate **700**. In addition, the syringes **701A~701C** may be partially bent toward the substrate **700** so that the nozzles **702A~702C** may be positioned at the outer edges of the image display parts **713A~713F** of the substrate **700**. Accordingly, a pressure supplying the sealant filled in the syringes **701A~701C** on the substrate **700** through the nozzles **702A~702C** may be reduced, thereby providing improved control of the supplied sealant pressure.

FIGS. 9A to 9D are perspective schematic views of an exemplary method of using a dispensing system according to the present invention. In FIG. 9A, a first plurality of image display parts **813A~813C** having a first size and a second plurality of image display parts **813D~813G** having a second size may be formed on a substrate **800**.

In FIG. 9B, the substrate **800**, upon which the first image display parts **813A~813C** having the first size and the second image display parts **813D~813G** having the second size have been formed, may be loaded and fixed on a table **810**, which may then be overturned.

In FIG. 9C, a first plurality of syringes **801A~801C** may supply sealant along outer edges of the first image display parts **813A~813C** having the first size of the overturned substrate **800** to form a plurality of first seal patterns **816A~816C**. In addition, the first plurality of syringes **801A~801C** may be moved along horizontal forward/backward and left/right directions.

In FIG. 9D, a second plurality of syringes **801D~801G** may supply sealant along outer edges of the second image display parts **813D~813G** to form a plurality of second seal patterns **816D~816G**. In addition, the second plurality of syringes **801D~801G** may be moved along the horizontal forward/backward and left/right directions.

In FIGS. 9A~9D, the substrate may be loaded and fixed onto a single table, which may then be overturned, and the first seal patterns may be formed along outer edges of the first image display parts having the first size. Then, the second seal patterns may be formed along outer edges of the second image display parts having the second size. However, two independently driven tables may be used. For example, the substrate may be first loaded and fixed onto a first table, which is then overturned, and first seal patterns may be formed along the outer edges of first image display parts having a first size. Then, the substrate may be loaded and fixed onto a second table, which is then overturned, and second seal patterns may be formed along outer edges of second image display parts having a second size.

It will be apparent to those skilled in the art that various modifications and variations can be made in the dispenser system for a liquid crystal display panel and method of using a dispenser system of the present invention without departing from the spirit or scope of the inventions. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A dispenser system for a liquid crystal display panel, comprising:
 - a table to overturn a substrate having at least one image display part on a first surface of the overturned substrate; and

11

at least one syringe system to supply sealant onto a first surface of the overturned substrate to form a seal pattern along outer edges of the image display part on the first surface of the overturned substrate, wherein the at least one syringe system moves along horizontal directions.

2. The system according to claim 1, wherein at least one thin film transistor array substrate is formed on the first surface of the substrate.

3. The system according to claim 1, wherein at least one color filter substrate is formed on the first surface of the substrate.

4. The system according to claim 1, wherein a matrix array of image display parts are formed on the first surface of the substrate and a matrix array of syringe systems are provided to correspond to the matrix array of image display parts.

5. The system according to claim 4, wherein the matrix array of syringe systems are provided to correspond to at least one line or one column of the matrix array of image display parts.

6. The system according to claim 4, wherein driving of the matrix array of syringe systems corresponding to the matrix array of image display parts includes one of simultaneous driving, individually driving, and grouped driving.

7. The system according to claim 4, wherein the matrix array of image display parts includes at least two different sizes.

8. The system according to claim 1, wherein the seal pattern includes a partial opening.

9. The system according to claim 1, wherein the seal pattern includes a closed pattern encompassing the outer edges of the at least one image display part.

10. The system according to claim 1, wherein the seal pattern includes an ultraviolet hardening sealant.

11. The system according to claim 1, wherein the seal pattern includes a mixture of an ultraviolet hardening sealant and a thermosetting sealant.

12. The system according to claim 1, wherein a body portion of the at least one syringe is positioned below the first surface of the substrate along a horizontal direction parallel to the table and includes a partially bent portion bent toward the first surface of the substrate.

13. A method of using a dispenser system for a liquid crystal display panel, comprising:

loading and fixing a substrate on a table;
overturning the table and the substrate; and
supplying sealant from the dispenser system onto a first surface of the overturned substrate to form at least one seal pattern.

14. The method according to claim 13, wherein the dispenser system includes a syringe system for supplying the sealant.

15. The method according to claim 14, further comprising moving the syringe system along horizontal directions parallel to the first surface of the overturned substrate during the supplying.

16. A method of dispensing sealant for a liquid crystal display panel, comprising:

loading and fixing a substrate on a table;
overturning the table and the substrate; and
supplying sealant from a dispenser system onto a first surface of the overturned substrate to form at least one seal pattern.

12

17. The method according to claim 16, wherein the dispenser system includes a syringe system for supplying the sealant.

18. The method according to claim 17, further comprising moving the syringe system along horizontal directions parallel to the first surface of the overturned substrate during the supplying.

19. A method for fabricating a liquid crystal display (LCD) device, comprising:

providing a first substrate and a second substrate;

loading and fixing the first substrate on a table;

overturning the first substrate;

supplying a sealant from a dispenser system onto a first surface of the overturned first substrate to form a seal pattern; and

attaching the first and second substrates to each other.

20. The method according to claim 19, wherein the dispenser system includes a syringe system.

21. The method according to claim 20, further comprising moving the syringe system along horizontal directions parallel to the first surface of the overturned substrate during the supplying.

22. The method according to claim 19, wherein at least one thin film transistor array is formed on the first surface of the first substrate.

23. The method according to claim 19, wherein at least one color filter layer is formed on the first surface of the substrate.

24. The method according to claim 19, further comprising forming a matrix array of image display parts on the first surface of the substrate and providing a matrix array of syringe systems to correspond to the matrix array of image display parts.

25. The method according to claim 24, wherein the matrix array of syringe systems are provided to correspond to at least one line or one column of the matrix array of image display parts.

26. The method according to claim 24, further comprising simultaneously driving the matrix array of syringe systems corresponding to the matrix array of image display parts.

27. The method according to claim 24, further comprising individually driving the matrix array of syringe systems corresponding to the matrix array of image display parts.

28. The method according to claim 24, further comprising group-driving the matrix array of syringe systems corresponding to the matrix array of image display parts.

29. The method according to claim 24, wherein the matrix array of image display parts includes at least two different sizes.

30. The method according to claim 19, wherein the seal pattern includes a partial opening.

31. The method according to claim 24, wherein the seal pattern includes a closed pattern encompassing outer edges of the at least one image display part.

32. The method according to claim 19, wherein the seal pattern includes an ultraviolet hardening sealant.

33. The method according to claim 19, wherein the seal pattern includes a mixture of an ultraviolet hardening sealant and a thermosetting sealant.

* * * * *

专利名称(译)	用于液晶显示板的分配器系统及其使用方法		
公开(公告)号	US7215405	公开(公告)日	2007-05-08
申请号	US10/701489	申请日	2003-11-06
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG.PHILIPS LCD CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	KIM SANG HYUN JUNG SUNG SU		
发明人	KIM, SANG-HYUN JUNG, SUNG-SU		
IPC分类号	G02F1/13 G02F1/1339		
CPC分类号	G02F1/1339		
优先权	1020020072101 2002-11-19 KR		
其他公开文献	US20040114094A1		
外部链接	Espacenet USPTO		

摘要(译)

一种用于液晶显示板的分配器系统，包括：翻转基板的台，其在翻转基板的第一表面上具有至少一个图像显示部分；以及至少一个注射器系统，用于将密封剂供应到翻转基板的第一表面上。沿着翻转基板的第一表面上的图像显示部分的外边缘形成密封图案，其中所述至少一个注射器系统沿水平方向移动。

