



US008085354B2

(12) **United States Patent**
Lo et al.

(10) **Patent No.:** **US 8,085,354 B2**
(45) **Date of Patent:** **Dec. 27, 2011**

(54) **PIXEL STRUCTURE WITH SEMICONDUCTOR OF TOP-GATE TFT EXTENDED OVER ELECTRODES AND LIQUID CRYSTAL DISPLAY PANEL**

(75) Inventors: **Cheng Lo**, Taipei (TW); **Shih-Chyuan Fan Jiang**, Taipei (TW); **Ching-Sheng Cheng**, Kaohsiung County (TW); **Ching-Huan Lin**, Tainan County (TW); **Chih-Jen Hu**, Hsinchu (TW); **Chih-Ming Chang**, Taoyuan County (TW)

(73) Assignee: **Au Optonics Corporation**, Hsinchu (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 418 days.

(21) Appl. No.: **12/368,966**

(22) Filed: **Feb. 10, 2009**

(65) **Prior Publication Data**
US 2010/0044716 A1 Feb. 25, 2010

(30) **Foreign Application Priority Data**
Aug. 19, 2008 (TW) 97131633 A

(51) **Int. Cl.**
G02F 1/136 (2006.01)
G09G 3/30 (2006.01)
H01L 29/04 (2006.01)

(52) **U.S. Cl.** **349/47**; 349/42; 349/43; 349/46; 345/92; 257/59; 257/72

(58) **Field of Classification Search** 349/42, 349/43, 46-48; 345/92; 257/59, 72
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,250,996 B2	7/2007	Yoshida et al.	
2005/0185120 A1	8/2005	Kitoh et al.	
2006/0091387 A1	5/2006	Yamazaki	
2006/0268186 A1	11/2006	Kamada et al.	
2008/0121893 A1 *	5/2008	Kim et al.	257/72
2008/0239227 A1 *	10/2008	Fan Jiang et al.	349/144
2009/0079892 A1 *	3/2009	Hsien et al.	349/47

* cited by examiner


Primary Examiner — Hoan Nguyen

(74) *Attorney, Agent, or Firm* — Jianq Chyun IP Office

(57) **ABSTRACT**

A pixel structure is disclosed. The pixel structure is suitable to be disposed on a substrate and includes a first pixel electrode, a second pixel electrode and a top gate TFT. The first pixel electrode and the second pixel electrode are disposed over the substrate, wherein the first pixel electrode and the second pixel electrode are separated from each other. The top gate TFT is disposed between the substrate and the first pixel electrode and includes a patterned semiconductor layer and a gate.

20 Claims, 13 Drawing Sheets







FIG. 1A






FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5A




Fig. 5B





FIG. 6A



PIXEL STRUCTURE WITH SEMICONDUCTOR OF TOP-GATE TFT EXTENDED OVER ELECTRODES AND LIQUID CRYSTAL DISPLAY PANEL

CROSS-REFERENCE TO RELATED APPLICATION

This application claims the priority benefit of Taiwan application serial no. 97131633, filed on Aug. 19, 2008. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of specification.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to a liquid crystal display panel (LCD panel), and more particularly, to a pixel structure in an LCD panel.

2. Description of Related Art

A thin film transistor liquid crystal display (TFT LCD) in the current market is being developed mainly focusing on high contrast ratio, no grayscale inversion, high brightness, high color saturation, fast response and wide-viewing angle. The common wide-viewing technique today includes twisted nematic liquid crystal display (TN LCD) with wide-viewing film, in-plane switching LCD (IPS LCD), fringe field switching LCD (FFS LCD) and multi-domain vertical alignment LCD (MVA LCD). In an MVA LCD, for example, a plurality of alignment patterns, for example, alignment protrusions or slits, are used so as to make the liquid crystal molecules in each pixel arranged in multi directions and thereby obtain different alignment domains. Since the alignment protrusions or the slits formed on a color filter substrate (CF substrate) or a thin film transistor array substrate (TFT array substrate) enable the liquid crystal molecules to be arranged in multi directions to obtain different alignment domains, therefore, a conventional MVA LCD panel achieves the required wide-viewing angle.

FIG. 1A is a top view diagram of a conventional LCD panel and FIG. 1B is a cross-sectional diagram of FIG. 1A along the line I-I'. In a conventional transmissive multi-domain vertical alignment liquid crystal display panel (transmissive MVA LCD) 100, a plurality of alignment protrusions P is disposed on the CF substrate thereof, wherein the alignment protrusions P are distributed over reflective electrodes 103 and transmissive electrodes 104. In addition, a main slit SS is disposed between each transmissive electrode 104 and each reflective electrode 103, so that the liquid crystals LC at the edges of the transmissive electrode 104 and the reflective electrode 103 tilt towards the alignment protrusion P. Since the alignment protrusion P is disposed between the reflective electrode 103 and the transmissive electrode 104 to change the electric field distribution; therefore, the crystals LC tilt towards the alignment protrusion P so that to the required wide-viewing angle is achieved. Besides, a connecting portion 105 is disposed between each reflective electrode 103 and each transmissive electrode 104, which makes the reflective electrode 103 and the transmissive electrode 104 electrically connected to each other, wherein the material of the connecting portion 105 may be the same with that of the reflective electrode 103 or the transmissive electrode 104.

However, the above-mentioned connecting portion 105 would influence the electric field distribution in the liquid crystal layer. Under a normal operation condition, the liquid crystal molecules still can be arranged stably, but once the

LCD panel is pressed and exerted by an external force, the connecting portion 105 may cause the liquid crystal molecules to be arranged in mess. That is, the liquid crystal molecules in an LCD panel are affected by the above-mentioned twisted electric field when an external force is exerted on the LCD panel and the liquid crystal molecules are unable to be quickly restored into the original arrangement, which results in apparent finger press mura and seriously affecting the quality of the LCD panel.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a pixel structure capable of effectively mitigating the finger press mura when the invented pixel structure is used in an LCD panel.

The present invention is also directed to an LCD panel, wherein the liquid crystal molecules can be quickly restored into the original arrangement after an external force is exerted on and presses the LCD panel.

As embodied and broadly described herein, the present invention provides a pixel structure disposed on a substrate. The pixel structure includes a first pixel electrode, a second pixel electrode and a top gate thin film transistor (top gate TFT). The first pixel electrode and the second pixel electrode are disposed over the substrate, wherein the first pixel electrode and the second pixel electrode are separated from each other. The top gate TFT is disposed between the substrate and the first pixel electrode, and the top gate TFT includes a patterned semiconductor layer disposed and a gate. The patterned semiconductor layer is disposed on the substrate and has a plurality of conductive doping regions and at least a channel region between the conductive doping regions, wherein one of the conductive doping regions extends from below the first pixel electrode to below the second pixel electrode and is electrically connected to the first pixel electrode and the second pixel electrode. The gate is disposed over the channel regions.

The present invention provides an LCD panel, which includes the above-mentioned TFT array substrate, an opposite substrate and a liquid crystal layer. The opposite substrate is disposed over the TFT array substrate. The liquid crystal layer is disposed between the TFT array substrate and the opposite substrate.

In an embodiment of the present invention, the above-mentioned first pixel electrode and the second pixel electrode are reflective or transmissive.

In an embodiment of the present invention, the above-mentioned patterned semiconductor layer is substantially of L-shape.

In an embodiment of the present invention, the above-mentioned patterned semiconductor layer has three conductive doping regions and two channel regions, and each of the channel regions is respectively connected between two of the conductive doping regions.

In an embodiment of the present invention, the above-mentioned gate is a conductive line with a branch and the conductive line is located over and covers all the channel regions.

In an embodiment of the present invention, the above-mentioned conductive doping region electrically connected to the first pixel electrode and the second pixel electrode includes a first type doping region and a second type doping region, wherein the second type doping region is connected to the first type doping region, the first pixel electrode is electrically connected to both the first type doping region and the

second type doping region, and the second pixel electrode is electrically connected to the second type doping region only.

In an embodiment of the present invention, the above-mentioned pixel structure further includes a buffer layer disposed between the substrate and the patterned semiconductor layer.

In an embodiment of the present invention, the above-mentioned pixel structure further includes a gate insulating layer, a first dielectric layer, a first contact conductor, a second contact conductor and a second dielectric layer. The gate insulating layer is disposed on the substrate to cover the patterned semiconductor layer, wherein the first dielectric layer is disposed on the gate insulating layer, a first contact hole and a second contact hole are formed within the first dielectric layer and the gate insulating layer to expose two portions of the patterned semiconductor layer, respectively. The first contact conductor is disposed on the first dielectric layer and electrically connected to the patterned semiconductor layer through the first contact hole. The second contact conductor is disposed on the first dielectric layer and electrically connected to the patterned semiconductor layer through the second contact hole. The second dielectric layer is disposed on the first dielectric layer, wherein the second dielectric layer has a third contact hole and a fourth contact hole to respectively expose the first contact conductor and the second contact conductor, the first pixel electrode is electrically connected to the first contact conductor through the third contact hole and the second pixel electrode is electrically connected to the second contact conductor through the fourth contact hole.

In an embodiment of the present invention, the above-mentioned pixel structure further includes a common electrode disposed on the gate insulating layer, wherein the common electrode is overlapped with a part of the conductive doping region.

In an embodiment of the present invention, the above-mentioned common electrode has an aperture located correspondingly to the first contact hole.

In an embodiment of the present invention, the above-mentioned common electrode is of cross-shape.

In an embodiment of the present invention, the above-mentioned pixel structure further includes a gate insulating layer, a first dielectric layer, a first contact conductor, a second contact conductor, a second dielectric layer and a padding layer. The gate insulating layer is disposed on the substrate to cover the patterned semiconductor layer, wherein the gate is disposed on the gate insulating layer, and the first dielectric layer is disposed on the gate insulating layer, a first contact hole and a second contact hole are formed within the first dielectric layer and the gate insulating layer to expose two portions of the patterned semiconductor layer, respectively. The first contact conductor is disposed on the first dielectric layer and electrically connected to the patterned semiconductor layer through the first contact hole. The second contact conductor is disposed on the first dielectric layer and electrically connected to the patterned semiconductor layer through the second contact hole. The second dielectric layer is disposed on at least a part of the second dielectric layer, wherein a third contact hole is formed within the padding layer and the second dielectric to expose the first contact conductor, and the second dielectric layer has a fourth contact hole to expose the second contact conductor. The first pixel electrode is electrically connected to the first contact conductor through the third contact hole and the second pixel electrode is electrically connected to the second contact conductor through the fourth contact hole.

In an embodiment of the present invention, the above-mentioned patterned semiconductor layer is comprised of poly-silicon, monocrystalline silicon, microcrystalline silicon or amorphous silicon.

Since the present invention adopts the patterned semiconductor layer to deliver image data to the first pixel electrode and the second pixel electrode, so that no connecting portion is required between the first pixel electrode and the second pixel electrode, which significantly mitigate the mura after the LCD panel is pressed by an external force.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings are included to provide a further understanding of the invention, and are incorporated in and constitute a part of this specification. The drawings illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention.

FIG. 1A is a top view diagram of a conventional LCD panel.

FIG. 1B is a cross-sectional diagram along the line I1-I1' of FIG. 1A.

FIG. 2A is a top view diagram of an LCD panel according to the first embodiment of the present invention.

FIG. 2B is a cross-sectional diagram along the line I2-I2' of FIG. 2A.

FIG. 2C is a localized enlargement diagram of FIG. 2B where a part of the first contact conductor and a part of the patterned semiconductor layer near the first contact hole are shown.

FIG. 3A is a top view diagram of an LCD panel according to the second embodiment of the present invention.

FIG. 3B is a cross-sectional diagram along the line I3-I3' of FIG. 3A.

FIG. 4A is a top view diagram of an LCD panel according to the third embodiment of the present invention.

FIG. 4B is a cross-sectional diagram along the line I4-I4' of FIG. 4A.

FIG. 5A is a top view diagram of an LCD panel according to the fourth embodiment of the present invention.

FIG. 5B is a cross-sectional diagram along the line I5-I5' of FIG. 5A.

FIG. 6A is a top view diagram of an LCD panel according to the fifth embodiment of the present invention.

FIG. 6B is a cross-sectional diagram along the line I6-I6' of FIG. 6A.

DESCRIPTION OF THE EMBODIMENTS

Reference will now be made in detail to the present preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts.

The First Embodiment

FIG. 2A is a top view diagram of an LCD panel according to the first embodiment of the present invention and FIG. 2B is a cross-sectional diagram along the line I2-I2' of FIG. 2A. Referring to FIGS. 2A and 2B, an LCD panel 200 of the embodiment includes a TFT array substrate 201, an opposite substrate 202 and a liquid crystal layer 203. The TFT array substrate 201 has a plurality of pixel structures 204. Note that in FIG. 2A, only a pixel structure 204 of the TFT array substrate 201 and the opposite substrate 202 thereof are shown.

The opposite substrate **202** is disposed over the TFT array substrate **201**, and the liquid crystal layer **203** is disposed between the TFT array substrate **201** and the opposite substrate **202**. The opposite substrate **202** has a plurality of alignment protrusions **P** so as to make the liquid crystal molecules in the liquid crystal layer **203** tilt towards the alignment protrusions **P**, which enables the liquid crystal molecules in each pixel arranged in multi directions and thereby obtains a plurality of different alignment domains. Moreover, a black matrix **BM** is disposed over the alignment protrusions **P** and on the opposite substrate **202**, wherein the black matrix **BM** has a single layer structure or multi-layers structure and is made of, for example, metal, organic material, color photoresist material or a combination of the above-mentioned materials. For example, the black matrix **BM** is formed by stacking a plurality of color photoresist layers.

As shown in FIG. 2B, the TFT array substrate **201** includes a pixel structure **204**, and the pixel structure **204** includes a first pixel electrode **205**, a second pixel electrode **206** and a top gate TFT **207**. In the embodiment, the pixel structure **204** has a reflective region **R** and a transmissive region **T**. The first pixel electrode **205** is a reflective pixel electrode located in the reflective region **R** and the second pixel electrode **206** is a transmissive pixel electrode located in the transmissive region **T**. In addition, the alignment protrusions **P** of the opposite substrate **202** are respectively located over the first pixel electrode **205** and the second pixel electrode **206**.

When images are displayed by the transfective pixel structure of the embodiment, the pixel electrode **206** within the transmissive region **T** serves as a transparent electrode, so that the light emitted from a backlight source can pass through the pixel electrode **206**. On the other hand, the pixel electrode **205** located in the reflective region **R** is a metal reflective electrode or other reflective electrodes made of materials with good reflectivity so as to achieve the displaying effect by reflecting the light emitted from a front-light source and/or an environmental light source. In the embodiment, the first pixel electrode **205** is an aluminium electrode, for example, with bumps formed on the surface thereof, and the second pixel electrode **206** serving as a transmissive pixel electrode is made of indium-tin oxide (ITO) or indium-zinc oxide (IZO), for example.

Note that a continuous main slit **SS** is located between the first pixel electrode **205** and the second pixel electrode **206** to physically separate the two pixel electrodes **205** and **206** from each other. The present invention is not limited to the material and the number of the above-mentioned pixel electrode of the embodiment. For example, when the transmissive region **T** requires a larger area, the number of the transmissive region **T** can be two or more than two. In addition, the pixel structure **204** can further include a gate insulating layer **209**, a buffer layer **210**, a first dielectric layer **211**, a first contact conductor **M1**, a second contact conductor **M2**, a second dielectric layer **212** and a common electrode **COM**.

The top gate TFT **207** is disposed between the TFT array substrate **201** and the first pixel electrode **205** and includes a patterned semiconductor layer **208** and a gate **G**. The patterned semiconductor layer **208** herein extends from below the first pixel electrode **205** to below the second pixel electrode **206** and is electrically connected to the first pixel electrode **205** and the second pixel electrode **206**. In the embodiment, the patterned semiconductor layer **208** is comprised of poly-silicon, monocrystalline silicon, microcrystalline silicon or amorphous silicon, for example. The buffer layer **210** is optionally disposed between the substrate **201** and the patterned semiconductor layer **208**, as shown in FIG. 2B.

The gate insulating layer **209** is disposed on the substrate **201** to cover the patterned semiconductor layer **208**, wherein the gate **G** is disposed on the gate insulating layer **209**. The first dielectric layer **211** is disposed on the gate insulating layer **209**, wherein a first contact hole **W1** and a second contact hole **W2** are formed within the first dielectric layer **211** and the gate insulating layer **209** to expose two portions of the patterned semiconductor layer **208**, respectively. The first contact conductor **M1** is disposed on the first dielectric layer **211** and is electrically connected to the patterned semiconductor layer **208** through the first contact hole **W1**. The second contact conductor **M2** is disposed on the first dielectric layer **211** and is electrically connected to the patterned semiconductor layer **208** through the second contact hole **W2**. The second dielectric layer **212** is disposed on the first dielectric layer **211** and has a third contact hole **W3** and a fourth contact hole **W4** to respectively expose the first contact conductor **M1** and the second contact conductor **M2**. The first pixel electrode **205** is electrically connected to the first contact conductor **M1** through the third contact hole **W3**, and the second pixel electrode **206** is electrically connected to the second contact conductor **M2** through the fourth contact hole **W4**.

As shown in FIG. 2B, the positions of the second contact hole **W2**, the fourth contact hole **W4** and the second contact conductor **M2** are corresponding to the positions of the alignment protrusions **P** of the opposite substrate **202**. In this way, the black matrix **BM** over the alignment protrusions **P** can effectively shield the leakage light around the fourth contact hole **W4** and the second contact conductor **M2** can effectively shield the leakage light around the alignment protrusions **P**. In some of the embodiments, the second contact hole **W2** can be aligned with or staggered from the fourth contact hole **W4** according to different panel processes. Similarly, the first contact hole **W1** can be aligned with or staggered from the third contact hole **W3**. In the embodiment, the common electrode **COM** is disposed on the gate insulating layer **209** and overlapped with the patterned semiconductor layer **208**. More specifically, the common electrode **COM** is overlapped with a part of the patterned semiconductor layer **208**, and the gate insulating layer **209** is located between the common electrode **COM** and the part of the patterned semiconductor layer **208**, such that the common electrode **COM** together with the part of the patterned semiconductor layer **208** forms a storage capacitor **Cst**.

Referring to FIGS. 2A and 2B, when a turn-on signal is transmitted from a scan line **GL** to the gate **G** of the top gate TFT **207**, the top gate TFT **207** is turned on and an image signal is transmitted from a data line **DL** to the contact hole **W** in the first dielectric layer **211**. Then, the image signal transmitted by the data line **DL** is transmitted to the patterned semiconductor layer **208** through the contact hole **W**. Next, the image signal is transmitted to the second contact conductor **M2** formed in the second contact hole **W2** and the first contact conductor **M1** formed in the first contact hole **W1** through the patterned semiconductor layer **208**. As shown in FIGS. 2A and 2B, since the first pixel electrode **205** is electrically connected to the first contact conductor **M1** via the third contact hole **W3** and the second pixel electrode **206** is electrically connected to the second contact conductor **M2** via the fourth contact hole **W4**, the patterned semiconductor layer **208** can transmit the image signals from the data line **DL** to the first pixel electrode **205** and the second pixel electrode **206**. In the embodiment, the patterned semiconductor layer **208** directly transmits the image signal from the data line **DL** to the electrodes **206** and **205** respectively located in the transmissive region **T** and the reflective region **R** through the

contact holes W1-W4 and the contact conductors M1 and M2, which is different from the prior art where a connecting portion 105 (as shown in FIG. 1B) is used to transmit the image signals.

As shown in FIG. 2A, the patterned semiconductor layer 208 is substantially of L-shape and has a plurality of conductive doping regions 208a, 208b and 208c and two channel regions 208' and 208" between the conductive doping regions, wherein the conductive doping region 208c extends from below the first pixel electrode 205 to below the second pixel electrode 206 and is electrically connected to the first pixel electrode 205 and the second pixel electrode 206. In addition, the gate G is, for example, a conductive line with a branch, which is located over the above-mentioned channel regions 208' and 208" to cover channel regions 208' and 208" so as to form a plurality of top gates TFT 207.

FIG. 2C is a localized enlargement diagram of FIG. 2B where a part of the first contact conductor and a part of the patterned semiconductor layer near the first contact hole are shown. Referring to FIG. 2C, the first contact conductor M1 is disposed on the first dielectric layer 211 and is electrically connected to the patterned semiconductor layer 208 through the first contact hole W1. The conductive doping region 208c electrically connected to both the first pixel electrode 205 and the second pixel electrode 206 includes a first type doping region D1 and a second type doping region D2. The second type doping region D2 is connected to the first type doping region D1, wherein the first pixel electrode 205 is electrically connected to both the first type doping region D1 and the second type doping region D2, and the second pixel electrode 206 is electrically connected to second type doping region D2 only.

The conductive doping region 208c of the storage capacitor Cst has, for example, both N-type doped sub-region and P-type doped sub-region. The two different doping sub-regions share a border right below the first contact hole W1, for example, first type doping region D1 and the second type doping region D2. Since the junction (i.e., the above-mentioned border) between the first type doping region D1 and the second type doping region D2 is a P-N junction J, so that a depletion region L is formed at the junction which is unfavourable to conduct current. Therefore, the embodiment utilizes the first contact conductor M1 electrically connected to the conductive doping region 208c through the first contact hole W1 to provide another current conductive path. In this way, when the patterned semiconductor layer 208 transmits the image signals to the first pixel electrode 205 and the second pixel electrode 206, the possible negative impact by the depletion region L of the p-n junction J can be avoided.

The embodiment uses the patterned semiconductor layer 208 to transmit image signals to the first pixel electrode 205 and the second pixel electrode 206, which effectively avoids the serious twist of the electric field occurred near the connecting portion 105 and mitigates the finger press mura.

The Second Embodiment

In the following embodiments and figures, all the same or similar parts are represented by the same marks for depiction simplicity.

FIG. 3A is a top view diagram of an LCD panel according to the second embodiment of the present invention and FIG. 3B is a cross-sectional diagram along the line I3-I3' of FIG. 3A. Referring to FIGS. 3A and 3B, an LCD panel 200b of the embodiment is similar to the LCD panel 200 of the first embodiment except that an alignment pattern SCF is disposed over the first pixel electrode 205 in the LCD panel 200b. The

alignment pattern SCF is disposed on the opposite substrate 202 and an alignment protrusion P is disposed below the alignment pattern SCF. In the MVA LCD panel of the present embodiment, the liquid crystal molecules in each pixel are arranged in multi directions by using an alignment pattern SCF together with a plurality of alignment protrusions P and thereby a plurality of different alignment domains is obtained so as to achieve the required wide-viewing angle.

Accordingly, by disposing an alignment pattern SCF over the first pixel electrode 205 of the first embodiment, the cell-gaps of the liquid crystal layer 203 within the reflective region R can be changed so that the transmissive pixel structure 204 of the embodiment is modified into a dual cell-gaps structure; that is, the transmissive region T and the reflective region R respectively have a liquid crystal layer 203 having different thicknesses. For example, the cell gap of the liquid crystal layer 203 within the transmissive region T is G1 and the cell gap of the liquid crystal layer 203 within the reflective region R in the first embodiment is also G1 before disposing the alignment pattern SCF. After disposing the alignment pattern SCF, the cell gap of the liquid crystal layer 203 within the reflective region R in the second embodiment is changed to G2, wherein G2 is a half of G1.

The dual cell-gaps structure provided by the embodiment enables the transmissive region T and the reflective region R to have substantially the same phase retardation, which further enhances the display quality of the transmissive LCD panel 200b.

The Third Embodiment

FIG. 4A is a top view diagram of an LCD panel according to the third embodiment of the present invention and FIG. 4B is a cross-sectional diagram along the line I4-I4' of FIG. 4A. Referring to FIGS. 4A and 4B, an LCD panel 200c of the embodiment is similar to the LCD panel 200b of the second embodiment except that a padding layer 213 located in the reflective region R of the LCD panel 200c is disposed on a part of the second dielectric layer 212.

In more detail, the pixel structure 204 of the embodiment further includes a gate insulating layer 209, a first dielectric layer 211, a first contact conductor M1, a second contact conductor M2, a second dielectric layer 212 and a padding layer 213. The gate insulating layer 209 covers the patterned semiconductor layer 208, wherein the gate G is disposed on the gate insulating layer 209. The first dielectric layer 211 is disposed on the gate insulating layer 209, wherein a first contact hole W1 and a second contact hole W2 are formed within the first dielectric layer 211 and the gate insulating layer 209 to expose two portions of the patterned semiconductor layer 208, respectively. The first contact conductor M1 is disposed on the first dielectric layer 211 and is electrically connected to the patterned semiconductor layer 208 through the first contact hole W1. The second contact conductor M2 is disposed on the first dielectric layer 211 and is electrically connected to the patterned semiconductor layer 208 through the second contact hole W2. The second dielectric layer 212 is disposed on the first dielectric layer 211. The padding layer 213 is disposed on a part of the second dielectric layer 212, wherein a third contact hole W3 is formed within the padding layer 213 and the second dielectric layer 212 to expose the first contact conductor M1. The second dielectric layer 212 has a fourth contact hole W4 to expose the second contact conductor M2. The first pixel electrode 205 is electrically connected to the first contact conductor M1 through the third contact hole W3, and the second pixel electrode 206 is elec-

trically connected to the second contact conductor M2 through the fourth contact hole W4.

The padding layer 213 functions similarly to the alignment pattern SCF of the second embodiment. In other words, the cell gap G2' of the liquid crystal layer within the reflective region R is adjusted by the padding layer 213, wherein G2' is a half of cell gap G1 of the liquid crystal layer within the transmissive region T, so that the display quality of the transmissive LCD panel 200c is further promoted.

The Fourth Embodiment

FIG. 5A is a top view diagram of an LCD panel according to the fourth embodiment of the present invention and FIG. 5B is a cross-sectional diagram along the line 15-15' of FIG. 5A. Referring to FIGS. 5A and 5B, an LCD panel 200d of the embodiment is similar to the LCD panel 200 of the first embodiment except that both the first pixel electrode 205 and the second pixel electrode 206 of the LCD panel 200d are transmissive pixel electrodes. In other words, the pixel structure 204 of the LCD panel 200d has two transmissive regions T1 and T2. Note that in other embodiments, both the first pixel electrode 205 and the second pixel electrode 206 of the LCD panel can be reflective pixel electrodes as well.

As shown in FIG. 5B, another difference of the LCD panel 200d from the LCD panel 200 of the first embodiment rests in that the common electrode COM of the embodiment is disposed on the gate insulating layer 209 and has an aperture 214 at the position of the first contact hole W1, wherein the common electrode COM is overlapped with a part of the conductive doping region 208 to form a storage capacitor Cst.

The Fifth Embodiment

FIG. 6A is a top view diagram of an LCD panel according to the fifth embodiment of the present invention and FIG. 6B is a cross-sectional diagram along the line 16-16' of FIG. 6A. Referring to FIGS. 6A and 6B, an LCD panel 200e of the embodiment is similar to the LCD panel 200d of the fourth embodiment except that the common electrode COM of the pixel structure 204 in the embodiment is of cross-shape. In more detail, the common electrode COM is distributed not only below the main slit SS between the first transmissive region T1 and the second transmissive region T2, but also on the linking line between the third contact hole W3 and the fourth contact hole W4, wherein the common electrode COM in cross-shape is able to increase the capacitance of the storage capacitor Cst.

In summary, the LCD panel of the present invention has at least following advantages:

1. Since the present invention adopts the patterned semiconductor layer to transmit image signal to the first pixel electrode and the second pixel electrode without using a connecting portion; therefore, the liquid crystal molecules are not affected by twist electric field caused by the conventional connecting portion, which is favourable to mitigate the finger press mura after the LCD panel is pressed by an external force.

2. In some of the embodiments of the present invention, the pixel structure can be changed into a dual cell-gaps structure by design depending on the application requirement, which promotes the display quality of the transmissive LCD panel.

3. In some of the embodiments of the present invention, a common electrode in cross-shape is used to increase the capacitance of the storage capacitor Cst, so as to reduce the voltage variation caused by a capacitor coupling effect, which further enhances the display quality of the panel.

It will be apparent to those skilled in the art that various modifications and variations can be made to the structure of the present invention without departing from the scope or spirit of the invention. In view of the foregoing, it is intended that the present invention cover modifications and variations of this invention provided they fall within the scope of the following claims and their equivalents.

What is claimed is:

1. A pixel structure disposed on a substrate, comprising:
 - a first pixel electrode disposed over the substrate;
 - a second pixel electrode disposed over the substrate, wherein the first pixel electrode and the second pixel electrode are separated from each other; and
 - a top gate thin film transistor disposed between the substrate and the first pixel electrode, wherein the top gate thin film transistor comprises:
 - a patterned semiconductor layer disposed on the substrate, wherein the patterned semiconductor layer has a plurality of conductive doping regions and at least a channel region between the conductive doping regions, one of the conductive doping regions extends from below the first pixel electrode to below the second pixel electrode and is electrically connected to the first pixel electrode and the second pixel electrode; and
 - a gate disposed over the channel regions.
2. The pixel structure according to claim 1, wherein the first pixel electrode and the second pixel electrode are reflective or transmissive.
3. The pixel structure according to claim 1, wherein the patterned semiconductor layer is substantially of L-shape.
4. The pixel structure according to claim 3, wherein the patterned semiconductor layer has three conductive doping regions and two channel regions, and each of the channel regions is respectively connected between two of the conductive doping regions.
5. The pixel structure according to claim 4, wherein the gate is a conductive line with a branch and the conductive line is located over and covers all the channel regions.
6. The pixel structure according to claim 1, further comprising:
 - a gate insulating layer disposed on the substrate to cover the patterned semiconductor layer, wherein the gate is disposed on the gate insulating layer;
 - a first dielectric layer disposed on the gate insulating layer, wherein a first contact hole and a second contact hole are formed within the first dielectric layer and the gate insulating layer to expose two portions of the patterned semiconductor layer, respectively;
 - a first contact conductor disposed on the first dielectric layer and electrically connected to the patterned semiconductor layer through the first contact hole;
 - a second contact conductor disposed on the first dielectric layer and electrically connected to the patterned semiconductor layer through the second contact hole; and
 - a second dielectric layer disposed on the first dielectric layer, wherein the second dielectric layer has a third contact hole and a fourth contact hole to respectively expose the first contact conductor and the second contact conductor, the first pixel electrode is electrically connected to the first contact conductor through the third contact hole and the second pixel electrode is electrically connected to the second contact conductor through the fourth contact hole, the conductive doping region electrically connected to both the first pixel electrode and the second pixel electrode comprises:
 - a first type doping region; and

11

a second type doping region connected to the first type doping region, wherein the first contact conductor contacts the first type doping region and the second type doping region, and the second contact conductor electrically contacts the second type doping region only.

7. The pixel structure according to claim 1, further comprising:

a gate insulating layer disposed on the substrate to cover the patterned semiconductor layer, wherein the gate is disposed on the gate insulating layer;

a first dielectric layer disposed on the gate insulating layer, wherein a first contact hole and a second contact hole are formed within the first dielectric layer and the gate insulating layer to expose two portions of the patterned semiconductor layer, respectively;

a first contact conductor disposed on the first dielectric layer and electrically connected to the patterned semiconductor layer through the first contact hole;

a second contact conductor disposed on the first dielectric layer and electrically connected to the patterned semiconductor layer through the second contact hole; and

a second dielectric layer disposed on the first dielectric layer, wherein the second dielectric layer has a third contact hole and a fourth contact hole to respectively expose the first contact conductor and the second contact conductor, the first pixel electrode is electrically connected to the first contact conductor through the third contact hole and the second pixel electrode is electrically connected to the second contact conductor through the fourth contact hole.

8. The pixel structure according to claim 7, further comprising a common electrode disposed on the gate insulating layer, wherein the common electrode is overlapped with a part of the conductive doping region.

9. The pixel structure according to claim 8, wherein the common electrode has an aperture located correspondingly to the first contact hole and is of cross-shape.

10. The pixel structure according to claim 1, further comprising:

a gate insulating layer disposed on the substrate to cover the patterned semiconductor layer, wherein the gate is disposed on the gate insulating layer;

a first dielectric layer disposed on the gate insulating layer, wherein a first contact hole and a second contact hole are formed within the first dielectric layer and the gate insulating layer to expose two portions of the patterned semiconductor layer, respectively;

a first contact conductor disposed on the first dielectric layer and electrically connected to the patterned semiconductor layer through the first contact hole;

a second contact conductor disposed on the first dielectric layer and electrically connected to the patterned semiconductor layer through the second contact hole;

a second dielectric layer disposed on the first dielectric layer; and

a padding layer disposed on at least a part of the second dielectric layer, wherein a third contact hole is formed within the padding layer and the second dielectric layer to expose the first contact conductor, the second dielectric layer has a fourth contact hole to expose the second contact conductor, the first pixel electrode is electrically connected to the first contact conductor through the third contact hole and the second pixel electrode is electrically connected to the second contact conductor through the fourth contact hole.

12

11. The pixel structure according to claim 1, wherein the patterned semiconductor layer is comprised of poly-silicon, monocrystalline silicon, microcrystalline silicon or amorphous silicon.

12. A liquid crystal display panel, comprising:

a thin film transistor array substrate having a plurality of pixel structures, each of the pixel structures comprising:

a first pixel electrode disposed over the substrate;

a second pixel electrode disposed over the substrate, wherein the first pixel electrode and the second pixel electrode are separated from each other;

a top gate thin film transistor disposed between the substrate and the first pixel electrode, wherein the top gate thin film transistor comprises:

a patterned semiconductor layer disposed on the substrate, wherein the patterned semiconductor layer has a plurality of conductive doping regions and at least a channel region between the conductive doping regions, one of the conductive doping regions extends from below the first pixel electrode to below the second pixel electrode and is electrically connected to the first pixel electrode and the second pixel electrode; and

a gate disposed over the channel regions;

an opposite substrate disposed over the thin film transistor array substrate; and

a liquid crystal layer disposed between the thin film transistor array substrate and the opposite substrate.

13. The liquid crystal display panel according to claim 12, wherein the first pixel electrode and the second pixel electrode are reflective or transmissive.

14. The liquid crystal display panel according to claim 12, wherein the patterned semiconductor layer is substantially of L-shape.

15. The liquid crystal display panel according to claim 12, wherein the pixel structure further comprises:

a gate insulating layer, disposed on the substrate to cover the patterned semiconductor layer, wherein the gate is disposed on the gate insulating layer;

a first dielectric layer disposed on the gate insulating layer, wherein a first contact hole and a second contact hole are formed within the first dielectric layer and the gate insulating layer to expose two portions of the patterned semiconductor layer, respectively;

a first contact conductor, disposed on the first dielectric layer and electrically connected to the patterned semiconductor layer through the first contact hole;

a second contact conductor, disposed on the first dielectric layer and electrically connected to the patterned semiconductor layer through the second contact hole; and

a second dielectric layer, disposed on the first dielectric layer, wherein the second dielectric layer has a third contact hole and a fourth contact hole to respectively expose the first contact conductor and the second contact conductor, the first pixel electrode is electrically connected to the first contact conductor through the third contact hole and the second pixel electrode is electrically connected to the second contact conductor through the fourth contact hole.

16. The liquid crystal display panel according to claim 15, wherein the pixel structure further comprises a common electrode disposed on the gate insulating layer, wherein the common electrode is overlapped with a part of the conductive doping region.

17. The liquid crystal display panel according to claim 16, wherein the common electrode has an aperture located correspondingly to the first contact hole.

13

18. The liquid crystal display panel according to claim 16, wherein the common electrode is of cross-shape.

19. The liquid crystal display panel according to claim 12, wherein the pixel structure further comprises:

a gate insulating layer, disposed on the substrate to cover the patterned semiconductor layer, wherein the gate is disposed on the gate insulating layer;

a first dielectric layer disposed on the gate insulating layer, wherein a first contact hole and a second contact hole are formed within the first dielectric layer and the gate insulating layer to expose two portions of the patterned semiconductor layer, respectively;

a first contact conductor, disposed on the first dielectric layer and electrically connected to the patterned semiconductor layer through the first contact hole;

a second contact conductor, disposed on the first dielectric layer and electrically connected to the patterned semiconductor layer through the second contact hole;

14

a second dielectric layer, disposed on the first dielectric layer; and

a padding layer, disposed on at least a part of the second dielectric layer, wherein a third contact hole is formed within the padding layer and the second dielectric layer to expose the first contact conductor, the second dielectric layer has a fourth contact hole to expose the second contact conductor, the first pixel electrode is electrically connected to the first contact conductor through the third contact hole and the second pixel electrode is electrically connected to the second contact conductor through the fourth contact hole.

20. The liquid crystal display panel according to claim 12, wherein the opposite substrate has a plurality of alignment protrusions, and the alignment protrusions are located over the first pixel electrodes and the second pixel electrodes.

* * * * *

专利名称(译)	具有顶栅TFT半导体的像素结构在电极和液晶显示面板上延伸		
公开(公告)号	US8085354	公开(公告)日	2011-12-27
申请号	US12/368966	申请日	2009-02-10
[标]申请(专利权)人(译)	友达光电股份有限公司		
申请(专利权)人(译)	友达光电股份有限公司		
当前申请(专利权)人(译)	友达光电股份有限公司		
[标]发明人	LO CHENG FAN JIANG SHIH CHYUAN CHENG CHING SHENG LIN CHING HUAN HU CHIH JEN CHANG CHIH MING		
发明人	LO, CHENG FAN JIANG, SHIH-CHYUAN CHENG, CHING-SHENG LIN, CHING-HUAN HU, CHIH-JEN CHANG, CHIH-MING		
IPC分类号	G02F1/136 G09G3/30 H01L29/04		
CPC分类号	G02F1/133555 G02F1/133371 G02F1/133707 G02F1/136227 G02F2001/13685 H01L27/12		
审查员(译)	阮HOAN		
优先权	097131633 2008-08-19 TW		
其他公开文献	US20100044716A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种像素结构。像素结构适于设置在基板上，并包括第一像素电极，第二像素电极和顶栅TFT。第一像素电极和第二像素电极设置在基板上，其中第一像素电极和第二像素电极彼此分离。顶栅TFT设置在基板和第一像素电极之间，并包括图案化的半导体层和栅极。

