



US 20060092361A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2006/0092361 A1**
(43) **Pub. Date: May 4, 2006**
Kim et al.(54) **MULTI-DOMAIN LIQUID CRYSTAL
DISPLAY AND A THIN FILM TRANSISTOR
SUBSTRATE OF THE SAME****Publication Classification**(51) **Int. Cl.**
G02F 1/1343 (2006.01)(52) **U.S. Cl.** **349/139**(76) Inventors: **Hee-Seob Kim**, Hwasung-kun (KR);
Young-Chol Yang, Kunpo-city (KR);
Jong-Lae Kim, Seoul (KR); **Kyong-Ju
Shin**, Yongin-city (KR)Correspondence Address:
MACPHERSON KWOK CHEN & HEID LLP
1762 TECHNOLOGY DRIVE, SUITE 226
SAN JOSE, CA 95110 (US)(21) Appl. No.: **10/527,042**(22) PCT Filed: **Oct. 10, 2002**(86) PCT No.: **PCT/KR02/01893**(30) **Foreign Application Priority Data**

Sep. 9, 2002 (KR) 2002/54277

(57) **ABSTRACT**

A thin film transistor array panel is provided, which includes; an insulating substrate; a plurality of gate lines formed on the insulating substrate; a plurality of data lines formed on the insulating substrate, insulated from the gate lines, and intersecting the gate lines; a plurality of storage electrode lines formed on the insulating substrate, insulated from the data lines, and intersecting the data lines; a plurality of pixel electrodes provided on the respective pixel areas defined by the intersections of the gate lines and the data lines, each pixel electrode having a cutout; a plurality of direction control electrodes provided on the respective pixel areas defined by the intersections of the gate lines and the data lines; a first thin film transistor connected to a relevant one of the gate lines, a relevant one of the data lines and a relevant one of the gate lines, a relevant one of the data lines and a relevant one of the pixel electrodes; a second thin film transistor connected to a previous one of the gate lines, a previous one of the data lines and a relevant one of the direction control electrodes; an a third thin film transistor connected to the previous gate line, the relevant data line and the relevant pixel electrode.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8A




FIG. 9




FIG. 10




FIG. 11A




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16





FIG. 17



MULTI-DOMAIN LIQUID CRYSTAL DISPLAY AND A THIN FILM TRANSISTOR SUBSTRATE OF THE SAME

BACKGROUND OF THE INVENTION

[0001] (a) Field of the Invention

[0002] The present invention relates to a liquid crystal display, and in particular, vertically-aligned liquid crystal display having a pixel region including a plurality of domains for wide viewing angle.

[0003] (b) Description of the Related Art

[0004] A typical liquid crystal display ("LCD") includes an upper panel provided with a common electrode and an array of color filters, a lower panel provided with a plurality of thin film transistors ("TFTs") and a plurality of pixel electrodes, and a liquid crystal layer is interposed therebetween. The pixel electrodes and the common electrode are applied with electric voltages and the voltage difference therebetween causes electric field. The variation of the electric field changes the orientations of liquid crystal molecules in the liquid crystal layer and thus the transmittance of light passing through the liquid crystal layer. As a result, the LCD displays desired images by adjusting the voltage difference between the pixel electrodes and the common electrode.

[0005] The LCD has a major disadvantage of its narrow viewing angle, and several techniques for increasing the viewing angle have been developed. Among these techniques, the provision of a plurality of cutouts or a plurality of projections on the pixel electrodes and the common electrode opposite each other along with the vertical alignment of the liquid crystal molecules with respect to the upper and the lower panels is promising.

[0006] The cutouts provided both at the pixel electrodes and the common electrode give wide viewing angle by generating fringe field to adjust the tilt directions of the liquid crystal molecules.

[0007] The provision of the projections both on the pixel electrode and the common electrode distorts the electric field to adjust the tilt directions of the liquid crystal molecules.

[0008] The fringe field for adjusting the tilt directions of the liquid crystal molecules to form a plurality of domains is also obtained by providing the cutouts at the pixel electrodes on the lower panel and the projections on the common electrode on the upper panel.

[0009] Among these techniques for widening the viewing angle, the provision of the cutouts has problems that an additional mask for patterning the common electrode is required, an overcoat is required for preventing the effect of the pigments of the color filters on the liquid crystal material, and severe disclination is generated near the edges of the patterned electrode. The provision of the projections also has a problem that the manufacturing method is complicated since it is required an additional process step for forming the projections or a modification of a process step. Moreover, the aperture ratio is reduced due to the projections and the cutouts.

SUMMARY OF THE INVENTION

[0010] It is an object of the present invention to provide a liquid crystal display manufactured by simple process and ensuring stable multi-domains.

[0011] These and other objects may be achieved by providing a pixel thin film transistor for a pixel electrode and first and second direction-control-electrode thin film transistors for a direction control electrode. The pixel thin film transistor transmits signals from a relevant data line to a pixel electrode in response to a signal from a relevant gate line, the first direction-control-electrode thin film transistor transmits signals from a previous data line to a direction control electrode in response to a signal from a previous gate line, and the second direction-control-electrode thin film transistor transmits signals from the relevant data line to the pixel electrode in response to a signal from the previous gate line.

[0012] A thin film transistor array panel is provided, which includes: an insulating substrate; a plurality of first signal lines formed on the insulating substrate; a plurality of second signal lines formed on the insulating substrate, insulated from the first signal lines, and intersecting the first signal lines; a plurality of pixel electrodes provided on the respective pixel areas defined by the intersections of the first and the second signal lines, each pixel electrode having a cutout; a plurality of direction control electrodes provided on the respective pixel areas defined by the intersections of the first and the second signal lines; a first thin film transistor connected to a relevant one of the first signal lines, a relevant one of the second signal lines and a relevant one of the pixel electrodes; a second thin film transistor connected to a previous one of the first signal lines, a previous one of the second signal lines and a relevant one of the direction control electrodes; and a third thin film transistor connected to the previous first signal line, the relevant second signal line and the relevant pixel electrode.

[0013] The thin film transistor array panel may further include a third signal line insulated from the second signal lines and intersecting the second signal lines, the third signal line including a portion overlapping the cutout of the pixel electrode.

[0014] A thin film transistor array panel is provided, which includes: an insulating substrate; a gate wire formed on the insulating substrate and including first to third gate electrodes and a plurality of gate lines; a gate insulating layer formed on the gate wire; a semiconductor layer formed on the gate insulating layer; a data wire formed on the semiconductor layer and including a plurality of data lines intersecting the gate lines, first to third source electrodes connected to the data lines, and first to third drain electrodes opposite the first to the third source electrodes with respect to the first to the third gate electrodes; a direction control electrode connected to the second drain electrode; a protective layer formed on the data wire and the direction control electrode and having a plurality of contact holes; and a pixel electrode formed on the protective layer, having a plurality of cutouts, and electrically connected to the first and the third drain electrodes through the contact holes.

[0015] It is preferable that the first and the third source electrodes are connected to a relevant one of the data lines, the second source electrode is connected to a previous one of the data lines, the first and the second gate electrodes are connected to a previous one of the gate lines, and the third gate electrode is connected to a relevant one of the gate lines. The cutouts of the pixel electrode preferably include a transverse cutout bisecting the pixel electrode 190 into upper

and lower halves and a plurality of oblique cutouts having inversion symmetry with respect to the transverse cutout. Preferably, the direction control electrode overlaps at least one of the cutouts of the pixel electrode and has inversion symmetry with respect to a transverse one of the cutouts of the pixel electrode.

[0016] The thin film transistor array panel may further include a storage electrode wire including substantially the same layer as the gate wire and having a portion overlapping at least one of the cutouts of the pixel electrode. The direction control electrode may include substantially the same layer and material as the data wire.

[0017] The contact holes preferably have rectangular shapes having an edge parallel to or perpendicular to the oblique cutouts. The data wire and the direction control electrode may include double layers of a semiconductor layer and a metal layer. The semiconductor layer may include double films of an amorphous silicon film and an ohmic contact layer.

[0018] A liquid crystal display is provided, which includes: a first insulating substrate; a plurality of first signal lines formed on the first insulating substrate; a plurality of second signal lines formed on the first insulating substrate, insulated from the first signal lines, and intersecting the first signal lines; a plurality of pixel electrodes provided on the respective pixel areas defined by the intersections of the first and the second signal lines, the pixel electrodes having cutouts; a plurality of direction control electrodes provided on the respective pixel areas defined by the intersections of the first and the second signal lines; a first thin film transistor connected to a relevant one of the first signal lines, a relevant one of the second signal lines and a relevant one of the pixel electrodes; a second thin film transistor connected to a previous one of the first signal lines, a previous one of the second signal lines and a relevant one of the direction control electrodes; a third thin film transistor connected to the previous first signal line, the relevant second signal line and the relevant pixel electrode; a second insulating substrate opposite the first insulating substrate; a common electrode formed on the second insulating substrate; and a liquid crystal layer interposed between the first and the second substrates.

[0019] It is preferable that the liquid crystal layer has negative dielectric anisotropy and major axes of liquid crystal molecules in the liquid crystal layer are aligned vertical to the first and the second substrates.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] **FIG. 1** is an equivalent circuit diagram of an LCD according to an embodiment of the present invention;

[0021] **FIG. 2A** is a layout view of a TFT array panel for an LCD according to a first embodiment of the present invention;

[0022] **FIGS. 2B and 2C** are sectional views of the TFT array panel shown in **FIG. 2A** taken along the lines IIb-IIb' and IIc-IIc', respectively;

[0023] **FIGS. 3A to 3D** are sectional views of a TFT array panel for an LCD sequentially illustrating a manufacturing method thereof according to a first embodiment of the present invention;

[0024] **FIG. 4** is a layout view of a TFT array panel for an LCD according to a second embodiment of the present invention;

[0025] **FIG. 5** is a sectional view of the TFT array panel shown in **FIG. 4** taken along the lines V-V' and V'-V'';

[0026] **FIGS. 6A to 11B** are layout views and sectional views of a TFT array panel for an LCD sequentially illustrating a manufacturing method thereof according to a second embodiment of the present invention;

[0027] **FIG. 12** is a schematic diagram of TFT array panels for an LCD according to first and second embodiments of the present invention;

[0028] **FIG. 13** is an equivalent circuit diagram of an LCD according to a third embodiment of the present invention;

[0029] **FIG. 14** is a layout view of an LCD according to a third embodiment of the present invention;

[0030] **FIG. 15** is a sectional view of the LCD shown in **FIG. 14** taken along the line XV-XV';

[0031] **FIG. 16** is a sectional view of the LCD shown in **FIG. 14** taken along the line XVI-XVI'; and

[0032] **FIG. 17** is a sectional view of the LCD shown in **FIG. 14** taken along the lines XVII-XVII' and XVII'-XVII''.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0033] The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the inventions are shown. The present invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein.

[0034] In the drawings, the thickness of layers and regions are exaggerated for clarity. Like numerals refer to like elements throughout. It will be understood that when an element such as a layer, region or substrate is referred to as being "on" another element, it can be directly on the other element or intervening elements may also be present. In contrast, when an element is referred to as being "directly on" another element, there are no intervening elements present.

[0035] Now, LCDs according to embodiments of this invention will be described in detail with reference to the accompanying drawings.

[0036] **FIG. 1** is an equivalent circuit diagram of an LCD according to an embodiment of the present invention.

[0037] An LCD according to an embodiment of the present invention includes a TFT array panel, a color filter array panel opposite the TFT array panel, and a liquid crystal layer interposed therebetween. The TFT array panel is provided with a plurality of gate lines and a plurality of data lines intersecting each other to define a plurality of pixel areas, and a plurality of storage electrode lines extending parallel to the gate lines. The gate lines transmit scanning signals and the data lines transmit image signals. A common voltage Vcom is applied to the storage electrode lines. Each pixel area is provided with a pixel TFT for a pixel electrode and a direction-control-electrode TFT DCETFT for a direction control electrode ("DCE"). The pixel TFT includes a

gate electrode connected to one of the gate lines, a source electrode connected to one of the data lines, and a drain electrode connected to one of a plurality of pixel electrodes, while the DCE TFT includes a gate electrode connected to a previous gate line, a source electrode connected to one of the storage electrode lines, and a drain electrode connected to one of a plurality of direction control electrodes.

[0038] The DCE and the pixel electrode are capacitively coupled, and the capacitor therebetween or its capacitance is represented by C_{DP} . The pixel electrode and a common electrode provided on the color filter array panel form a liquid crystal capacitor, and the liquid crystal capacitor or its capacitance is represented by C_{LC} . The pixel electrode and a storage electrode connected to one of the storage electrode lines form a storage capacitor, and the storage capacitor or its capacitance is represented by C_{ST} .

[0039] Although it is not shown in the circuit diagram, the pixel electrode according to an embodiment of the present invention has an aperture overlapping the DCE such that the electric field due to the DCE flows out through the aperture. The electric field flowing out through the aperture makes the liquid crystal molecules have pretilt angles. The pretilted liquid crystal molecules are rapidly aligned without dispersion along predetermined directions upon the application of the electric field due to the pixel electrode.

[0040] In order to obtain the pretilted liquid crystal molecules using the electric field generated by the DCE, the potential of the DCE relative to the potential of the common electrode (referred to as the "DCE voltage" hereinafter) is larger than the potential of the pixel electrode relative to the potential of the common electrode (referred to as the "pixel voltage" hereinafter) by a predetermined value. The LCD according to an embodiment of the present invention easily satisfies this requirement by isolating the DCE after applying the potential applied to the storage electrode lines to the DCE. The reason will be described now.

[0041] Consider a moment that a given pixel electrode having a negative potential is refreshed by a positive potential. The application of a gate-on signal to the previous gate line turns on the DCE TFT to make the DCE have a potential higher than the pixel electrode. This changes the potential of the pixel electrode capacitively coupled with the DCE. In this case, the capacitor C_{DP} between the DCE and the pixel electrode and the capacitor C_{LC} between the pixel electrode and the common electrode are connected in series. Since the pixel electrode had the negative potential, its potential is lower than that of the DCE, i.e., $V_{DCE} > V_p$ during the charging of the serially-connected capacitors C_{DP} and C_{LC} . When the DCE TFT is turned off after charging, the DCE floats. Accordingly, the potential of the DCE is always larger than the potential of the pixel electrode irrespective of the potential change of the pixel electrode. For example, when the potential of the pixel electrode is increased to a positive value when the pixel TFT is turned on, the potential of the DCE follows the potential increase of the pixel electrode in order to maintain the potential difference between the DCE and the pixel electrode.

[0042] This is described in terms of an electrical circuit.

$$V_C = V_0 + \frac{1}{C} \int_0^{t_1} i d(t) \quad \text{A voltage across} \quad (1)$$

a capacitor in an electrical circuit is given by

[0043] A floating electrode is equivalent to an electrode connected to a resistor having infinite resistance ($R=\infty$). Therefore, $i=0$ and $V_C=V_0$, that is, the initial voltage across the capacitor is maintained. In other words, the potential of a floating electrode increases or decreases coupled with the potential of the other electrode.

[0044] On the contrary, when refreshing with a negative potential, the potential of the DCE is always lower than the potential of the pixel electrode by a predetermined value.

[0045] According to an embodiment of the present invention, the DCE TFT is connected to the storage electrode lines such that the common voltage is applied to the DCE. Hence, the potentials of the two electrodes increases or decreases to have substantially the same polarity irrespective of the polarity of the potential applied to the pixel electrode in the next frame. As a result, the present invention is applied any inversion type such as line inversion and dot inversion.

[0046] For the same gray, there is no variation of the potential difference between the DCE and the pixel electrode irrespective of the grays of previous and next frames, thereby ensuring stability of image quality.

[0047] The disconnection of the DCE TFTs from the data lines prevents the increase of the load of the data lines.

[0048] Now, a detailed embodiment of the present invention is described with reference to **FIGS. 2A to 2C**.

[0049] **FIG. 2A** is a layout view of an LCD according to an embodiment of the present invention, and **FIGS. 2B and 2C** are sectional views of the LCD shown in **FIG. 2A** taken along the lines IIb-IIb'.

[0050] An LCD according to a first embodiment of the present invention includes a lower panel, an upper panel facing the lower panel, and a vertically (or homeotropically) aligned liquid crystal layer interposed between the lower panel and the upper panel.

[0051] The lower panel will now be described more in detail.

[0052] A plurality of gate lines **121** are formed on an insulating substrate **110** and a plurality of data lines **171** are formed thereon. The gate lines **121** and the data lines **171** are insulated from each other and intersect each other to define a plurality of pixel areas.

[0053] Each pixel area is provided with a pixel TFT, a DCE TFT, a DCE and a pixel electrode. The pixel TFT has three terminals, a first gate electrode **123a**, a first source electrode **173a** and a first drain electrode **175a** while the DCE TFT has three terminals, a second gate electrode **123b**, a second source electrode **173b** and a second drain electrode **175b**. The pixel TFT is provided for switching the signals transmitted to the pixel electrode **190** while the DCE TFT is provided for switching the signals entering the DCE **178**. The gate electrode **123a**, the source electrode **173a** and the

drain electrode **175** of the pixel TFT are connected to corresponding one of the gate lines **121**, one of the data lines **171** and the pixel electrode **190**, respectively. The gate electrode **123b**, the source electrode **173b** and the drain electrode **175b** of the DCE TFT are connected to previous one of the gate lines **121**, corresponding one of the storage electrode lines **131** and the DCE **178**, respectively. The DC **178** is applied with a direction-controlling voltage for controlling the pre-tilts of the liquid crystal molecules to generate a direction-controlling electric field between the DCE **178** and the common electrode **270**. The DCE **178** is formed in a step for forming the data lines **171**.

[0054] The layered structure of the lower panel will be described in detail.

[0055] A plurality of gate lines **121** extending substantially in a transverse direction are formed on an insulating substrate **110**, and a plurality of first and second gate electrodes **123a** and **123b** are connected to the gate lines **121**. A plurality of storage electrode lines **131** and a plurality of sets of first to fourth storage electrodes **133a-133d** are also formed on the insulating substrate **110**. The storage electrode lines **131** extend substantially in the transverse direction, and the first and the second storage electrodes **133a** and **133b** extend from the storage electrode line **131** in a longitudinal direction. The third and the fourth storage electrodes **133c** and **133d** extend in the transverse direction and connect the first storage electrode **133a** and the second storage electrode **133b**.

[0056] The gate wire **121**, **123a** and **123b** and the storage electrode wire **131** and **133a-133d** are preferably made of Al, Cr or their alloys, Mo or Mo alloy. If necessary, the gate wire **121**, **123a** and **123b** and the storage electrode wire **131** and **133a-133d** include a first layer preferably made of Cr or Mo alloys having excellent physical and chemical characteristics and a second layer preferably made of Al or Ag alloys having low resistivity.

[0057] A gate insulating layer **140** is formed on the gate wire **121**, **123a** and **123b** and the storage electrode wire **131** and **133a-133d**.

[0058] A semiconductor layer **151**, **154a**, **154b** and **155** preferably made of amorphous silicon is formed on the gate insulating layer **140**. The semiconductor layer **151**, **154a**, **154b** and **155** includes a plurality of first and second channel semiconductors **154a** and **154b** forming channels of TFTs, a plurality of data-line semiconductors **151** located under the data lines **171**, and a plurality of intersection semiconductors **155** located near the intersections of DCEs **178** and the storage electrodes **133c** and **133d** for ensuring insulation therebetween.

[0059] An ohmic contact layer **161**, **163a**, **163b**, **165a** and **165b** preferably made of silicide or n+ hydrogenated amorphous silicon heavily doped with n type impurity is formed on the semiconductor layer **151**, **154a**, **154b** and **155**.

[0060] A data wire **171**, **173a**, **173b**, **175a** and **175b** is formed on the ohmic contact layer **161**, **163a**, **163b**, **165a** and **165b** and the gate insulating layer **140**. The data wire **171**, **173a**, **173b**, **175a** and **175b** includes a plurality of data lines **171** extending in the longitudinal direction and intersecting the gate lines **121** to form a plurality of pixels, a plurality of first source electrodes **173a** branched from the data lines **171** and extending onto portions **163a** of the

ohmic contact layer, a plurality of first drain electrodes **175a** disposed on portions **165a** of the ohmic contact layer, located opposite the first source electrodes **173a** with respect to the first gate electrodes **123a** and separated from the first source electrodes **173a**, a plurality of second source electrodes **173b** and a plurality of second drain electrodes **175b** disposed on respective portions **163b** and **165b** opposite each other with respect to the second gate electrodes **123b**, and a plurality of data pads (not shown) connected to one ends of the data lines **171** to receive image signals from an external device.

[0061] A plurality of DCEs **178** are formed in the pixel areas defined by the intersections of the gate lines **121** and the data lines **171**. Each DCE **178** includes a plurality of X-shaped metal pieces connected to one another and is connected to the second drain electrode **175b**. The data wire **171**, **173a**, **173b**, **175a** and **175b** and the DCEs **178** are preferably made of Al, Cr or their alloys, Mo or Mo alloy. If necessary, the data wire **171**, **173a**, **173b**, **175a** and **175b** and the DCEs **178** include a first layer preferably made of Cr or Mo alloys having excellent physical and chemical characteristics and a second layer preferably made of Al or Ag alloys having low resistivity.

[0062] A passivation layer **180** preferably made of silicon nitride or organic insulator is formed on the data wire **171**, **173a**, **173b**, **175a** and **175b**.

[0063] The passivation layer **180** is provided with a plurality of contact holes **181** exposing the first drain electrodes **175a**, a plurality of contact holes **182** extending to the gate insulating layer **140** and exposing the storage electrode lines **131**, a plurality of contact holes **183** exposing the second source electrodes **173b**, a plurality of contact holes (not shown) exposing the data pads, and a plurality of contact holes (not shown) extending to the gate insulating layer **140** exposing the gate pads. The contact holes exposing the pads may have various shapes such as polygon or circle. The area of the contact hole is preferably equal to or larger than 0.5 mm×15 μm and not larger than 2 mm×60 μm.

[0064] A plurality of pixel electrodes **190** are formed on the passivation layer **180**. Each pixel electrode **190** is connected to the first drain electrode **175a** through the contact hole **181** and has a plurality of X-shaped cutouts **191** and a plurality of linear cutouts **192**. The X-shaped cutouts **191** overlap the X-shaped portions of the DCE **178** while the linear cutouts **192** overlap the third and the fourth storage electrodes **133c** and **133d**. The DCE **178** broadly overlaps peripheries of the cutouts **191** as well as the cutouts **191** themselves to form a storage capacitance along with the pixel electrode **190**.

[0065] A plurality of bridges **92** connecting the storage electrode lines **131** and the second source electrodes **173b** through the contact holes **182** and **183** are also formed on the passivation layer. Furthermore, a plurality of subsidiary gate pads (not shown) and a plurality of subsidiary data pads (not shown) are formed on the passivation layer **180**. The subsidiary gate pads and the subsidiary data pads are connected to the gate pads and the data pads through the contact holes. The pixel electrodes **190**, the bridges **92**, the subsidiary gate pads and the subsidiary data pads are preferably formed of indium zinc oxide ("IZO"). Alternatively, the pixel electrodes **190**, the bridges **92** and the subsidiary pads are preferably made of indium tin oxide ("ITO").

[0066] To summarize, each pixel electrode **190** has the plurality of cutouts **191** and **192** for partitioning a pixel region into a plurality of domains, and the first cutouts **191** overlap the DCE **178** while the second cutouts **192** overlap the storage electrodes **133c** and **133d**. The DCE **178** and the first cutouts **191** are aligned such that the DCE **178** is exposed through the first cutouts **191** to be seen in front view. The storage electrode line **131** and the DCE **178** are connected via the DCE TFT while the data line **171** and the pixel electrode **190** are connected via the pixel TFT, and the pixel electrode **190** and the DCE **178** are aligned to form a storage capacitance.

[0067] According to another embodiment of the present invention, the DCEs **178** include substantially the same layer as the gate wire **121**, **123a** and **123b**. The portions of the passivation layer **180** on the DCEs **178** may be removed to form a plurality of openings.

[0068] The upper substrate **210** will not be described in detail.

[0069] A black matrix **220** for preventing light leakage, a plurality of red, green and blue color filters **230**, and a common electrode **270** preferably made of a transparent conductor such as ITO or IZO are formed on an upper substrate **210** preferably made of transparent insulating material such as glass.

[0070] A plurality of liquid crystal molecules contained in the liquid crystal layer **3** is aligned such that their director is perpendicular to the lower and the upper substrates **110** and **210** in absence of electric field. The liquid crystal layer **3** has negative dielectric anisotropy.

[0071] The lower substrate **110** and the upper substrate **210** are aligned such that the pixel electrodes **190** exactly match and overlap the color filters **230**. In this way, a pixel region is divided into a plurality of domains by the cutouts **191** and **192**. The alignment of the liquid crystal layer **3** in each domain is stabilized by the DCE **178**.

[0072] This embodiment illustrates the liquid crystal layer **3** having negative dielectric anisotropy and homeotropic alignment with respect to the substrates **110** and **210**. However, the liquid crystal layer **3** may have positive dielectric anisotropy and homogeneous alignment with respect to the substrates **110** and **210**.

[0073] A method of manufacturing a TFT array panel for an LCD having the above-described structure will be described.

[0074] FIGS. **3A** to **3D** are sectional views of a TFT array panel for an LCD sequentially illustrating a manufacturing method thereof according to a first embodiment of the present invention.

[0075] First, as shown in FIG. **3A**, a conductive layer preferably made of metal is deposited by sputtering and either dry-etched or wet-etched by a first photo-etching step using a mask to form a gate wire and a storage electrode wire on a substrate **110**. The gate wire includes a plurality of gate lines **121**, a plurality of gate pads (not shown) and a plurality of gate electrodes **123**, and the storage wire includes a plurality of storage electrode lines **131** and a plurality of storage electrodes **133a-133d**.

[0076] As shown in FIG. **3B**, a gate insulating layer **140** with 1,500-5,000 Å thickness, a hydrogenated amorphous

silicon layer with 500-2,000 Å thickness, and a doped amorphous silicon layer with 300-600 Å thickness are sequentially deposited by chemical vapor deposition ("CVD"). The doped amorphous silicon layer and the amorphous silicon layer are patterned by a photo-etching step using a mask to form an ohmic contact layer **160a**, **160b** and **161** and an amorphous silicon layer **151**, **154a** and **154b**.

[0077] Thereafter, as shown in FIG. **3C**, a conductive layer with 1,500-3,000 Å thickness preferably made of metal is deposited by sputtering and patterned by a photo-etching step using a mask to form a data wire and a plurality of DCEs **178**. The data wire includes a plurality of data lines **171**, a plurality of source electrodes **173a** and **173b**, a plurality of drain electrodes **175a** and **175b**, and a plurality of data pads (not shown).

[0078] Then, portions of the ohmic contact layer **160a** and **160b**, which are not covered by the source electrodes **173a** and **173b** and the drain electrodes **175a** and **175b**, are removed such that an ohmic contact layer **163a**, **163b**, **165a** and **165b** including a plurality of separated portions is formed and portions of the semiconductor layer **151** between the source electrodes **173a** and **173b** and the drain electrodes **175a** and **175b** are exposed.

[0079] As shown in FIG. **3D**, a passivation layer **180** is formed by coating an organic insulating material having low dielectric constant and good planarization characteristic or by CVD of low dielectric insulating material such as SiOF or SiOC having a dielectric constant equal to or less than 4.0. The passivation layer **180** together with the gate insulating layer **140** is patterned by a photo-etching step using a mask to form a plurality of contact holes **181**, **182** and **183**.

[0080] Finally, as shown in FIG. **2A**, an ITO layer or an IZO layer with thickness of 1500-500 Å is deposited and photo-etched using a mask to form a plurality of pixel electrodes **190**, a plurality of connecting bridges **92**, a plurality of subsidiary gate pads (not shown) and a plurality of subsidiary data pads (not shown).

[0081] This technique is applied to a manufacturing method using five masks as described above. However, the technique may be well adapted for a method of a TFT array panel for an LCD using four masks. It is described in detail with reference to the drawings.

[0082] FIG. **4** is a layout view of a TFT array panel for an LCD according to a second embodiment of the present invention, and FIG. **5** is a sectional view of the TFT array panel shown FIG. **4** taken along the lines V-V' and V'-V''.

[0083] A TFT array panel for an LCD according to a second embodiment of the present invention is manufactured by using four masks and has a feature compared with a TFT array panel manufactured by using five masks, which will be described now.

[0084] An ohmic contact layer **161**, **163a**, **163b**, **165a** and **165b** formed under a plurality of DCEs **178** and a data wire including a plurality of data lines **171**, a plurality of source electrodes **173a** and **173b**, a plurality of the drain electrodes **175a** and **175b** and a plurality of data pads **179** has substantially the same shape as the data wire **171**, **173a**, **173b**, **175a**, **175b** and **179** and the DCEs **178**. An amorphous silicon layer **151**, **154a**, **154b** and **158** has substantially the same shape as the data wire and the DCEs **178** except that

channel portions between the source electrodes **173a** and **173b** and the drain electrodes **175a** and **175b** are connected. Remaining structure is substantially the same as a TFT array panel manufactured by a five-mask process.

[0085] **FIG. 4** illustrates a gate pad **125**, a storage pad **135** and a data pad **179** as well as a subsidiary gate pad **95**, a subsidiary storage pad **99** and a subsidiary data pad **97**.

[0086] A method of manufacturing a TFT array panel will be now described.

[0087] **FIGS. 6A to 11B** are layout views and sectional views of a TFT array panel for an LCD sequentially illustrating a manufacturing method thereof.

[0088] First, as shown in **FIGS. 6A and 6B**, Al, Ag, their alloys or the like is deposited and photo-etched to form a gate wire including a plurality of gate lines **121**, a plurality of gate pads **125** and a plurality of gate electrodes **123**, and a storage electrode wire **131** and **133a-133d**. (First Mask)

[0089] As shown in **FIG. 7**, a silicon nitride gate insulating layer **140** with 1,500-5,000 Å thickness, an amorphous silicon layer **150** with 500-2,000 Å thickness, and a contact layer **160** with 300-600 Å thickness are sequentially deposited by CVD. A conductive layer **170** preferably made of Al, Ag or their alloys is deposited by preferably sputtering, and a photoresist film PR with thickness of 1-2 microns is coated thereon.

[0090] Thereafter, the photoresist film PR is exposed to light through a mask and is developed to form a photoresist pattern PR as shown in **FIGS. 8A and 8B**. Each portion of the photoresist pattern PR located on a channel area C of a TFT, which is placed between a source electrode **173a** or **173b** and a drain electrode **175a** or **175b**, is thicker than each portion of the photoresist pattern PR located on a data area A where a data wire will be formed. All portions of the photoresist film PR on the remaining areas B are removed. Here, the ratio of the thickness of the photoresist pattern PR on the channel area C and on the data area A is adjusted depending on process conditions of subsequent etching steps described later, and it is preferable that the thickness of the former is equal to or less than a half of that of the latter, for example, equal to or less than 4,000 Å. (Second Mask)

[0091] The position-dependent thickness of the photoresist pattern is obtained by several techniques. A slit pattern, a lattice pattern or a translucent film is provided on the mask in order to adjust the light transmittance in the area C.

[0092] When using a slit pattern, it is preferable that width of the slits and a gap between the slits is smaller than the resolution of an exposer used for the photolithography. In case of using a translucent film, thin films with different transmittances or different thickness may be used to adjust the transmittance on the masks.

[0093] When a photoresist film is exposed to light through such a mask, polymers of a portion directly exposed to the light are almost completely decomposed, and those of a portion exposed to the light through a slit pattern or a translucent film are not completely decomposed because the amount of a light irradiation is small. The polymers of a portion of the photoresist film blocked by a light-blocking film provided on the mask are hardly decomposed. After the photoresist film is developed, the portions containing the polymers, which are not decomposed, is left. At this time, the

thickness of the portion with less light exposure is thinner than that of the portion without light exposure. Since too long exposure time decomposes all the molecules, it is necessary to adjust the exposure time.

[0094] The small thickness of the photoresist film may be obtained using reflow. That is, the photoresist film is made of a reflowable material and exposed to light through a normal mask having opaque and transparent portions. The photoresist film is then developed and subject to reflow such that portions of the photoresist film flows down onto areas without photoresist, thereby forming thin portions.

[0095] Next, the photoresist pattern PR and the underlying layers including the conductive layer **170**, the contact layer **160** and the semiconductor layer **150** are etched such that the data wire and the underlying layers are left on the data areas A, only the semiconductor layer is left on the channel areas C, and all the three layers **170**, **160** and **150** are removed to expose the gate insulating layer **140** on the remaining areas B.

[0096] First, as shown in **FIG. 9**, the exposed portions of the conductive layer **170** on the other areas B are removed to expose the underlying portions of the contact layer **160**. Both dry etch and wet etch are selectively used in this step and preferably performed under the condition that the conductive layer **170** is easily etched and the photoresist pattern PR are hardly etched. However, since it is hard to identify the above-described condition for dry etch, and the dry etch may be performed under the condition that the photoresist pattern PR and the conductive layer **170** are etched simultaneously. In this case, the portions of the photoresist pattern PR on the channel areas C for dry etch are preferably made to be thicker than those for the wet etch to prevent the removal of the portions of the photoresist pattern PR on the channel areas C and thus the exposure of the underlying portions of the conductive layer **170**.

[0097] As a result, as shown in **FIG. 9**, only the portions **171**, **170a** and **170b** of the conductive layer **170** on the channel areas C and the data areas A are left and the portions of the conductive layer **170** on the remaining areas B are removed to expose the underlying portions of the contact layer **160**. Here, the data-wire conductors **171**, **170a** and **170b** have substantially the same planar shapes as the data wire **171**, **173a**, **173b**, **175a**, **175b** and **179** except that the source electrodes **173a** and **173b** and the drain electrodes **175a** and **175b** are not disconnected from but connected to each other. When using dry etch, the thickness of the photoresist pattern PR is reduced to an extent.

[0098] Next, as shown in **FIG. 9**, the exposed portions of the contact layer **160** and the underlying portions of the amorphous silicon layer **150** on the areas B as well as the portions of the photoresist pattern PR on the channel areas C are removed by dry etch. The etching is performed under the condition that the photoresist pattern PR, the contact layer **160** and the semiconductor layer **150** are easily etched and the gate insulating layer **140** is hardly etched. (It is noted that etching selectivity between the intermediate layer and the semiconductor layer is nearly zero.) In particular, it is preferable that the etching ratios for the photoresist pattern PR and the semiconductor layer **150** are nearly the same. For instance, the etched thicknesses of the photoresist pattern PR and the semiconductor layer **150** can be nearly the same by using a gas mixture of SF₆ and HCl, or a gas mixture of SF₆,

and O₂. When the etching ratios for the photoresist pattern PR and for the semiconductor pattern 150 are the same, the initial thickness of the portions of the photoresist pattern PR on the channel areas C is equal to or less than the sum of the thickness of the semiconductor layer 150 and the thickness of the contact layer 160.

[0099] Consequently, as shown in FIG. 10, the portions of the photoresist pattern PR on the channel areas C are removed to expose the underlying portions of source/drain ("S/D") conductors 170a and 170b, and the portions of the contact layer 160 and the semiconductor layer 150 on the remaining areas B are removed to expose the underlying portions of the gate insulating layer 140. In the meantime, the portions of the photoresist pattern PR on the data areas A are also etched to become thinner. Moreover, the semiconductor pattern 151, 154a, 154b and 158 is completed in this step. A plurality of ohmic contacts 161, 160a, 160b and 168 are formed on the semiconductor pattern 151, 154a, 154b and 158.

[0100] Then, photoresist remnants left on the surface of the S/D conductors 170a and 170b on the channel areas C are removed by ashing.

[0101] Next, as shown in FIGS. 11A and 11B, portions of the S/D conductors 170a and 170b and the underlying portions of the S/D ohmic contacts 160a and 160b on the channel areas C are etched to be removed. Here, the etching of both the S/D conductors 170a and 170b and the S/D ohmic contacts 160a and 160b may be done using only dry etching. Alternatively, the S/D conductors 170a and 170b are etched by wet etching and the S/D ohmic contacts 160a and 160b are etched by dry etching. In the former case, it is preferable to perform the etching under the condition that etching selectivity between the S/D conductors 170a and 170b and the S/D ohmic contacts 160a and 160b is high. It is because the low etching selectivity makes the determination of the etching finish point difficult, thereby causing the adjustment of the thickness of the portions of the semiconductor pattern 154a and 154b left on the channel areas C to be difficult. In the latter case alternately applying wet etching and dry etching, a stepwise lateral sidewall is formed since the wet etch etches the lateral sides of the S/D conductors 170a and 170b, while the dry etch hardly etches the lateral sides of the S/D ohmic contacts 160a and 160b. Examples of etching gases used for etching the S/D ohmic contacts 160a and 160b are a gas mixture of CF₄ and HCl and a gas mixture of CF₄ and O₂. Use of the gas mixture of CF₄ and O₂ enables to obtain uniform thickness of etched portions of the semiconductor pattern 154a and 154b. In this regard, the exposed portions of the semiconductor pattern 154a and 154b are etched to have a reduced thickness, and the portions of the photoresist pattern PR on the data-wire areas A are also etched to have a reduced thickness. This etching is performed under the condition that the gate insulating layer 140 is not etched, and it is preferable that the photoresist pattern PR is thick enough to prevent the portions of the photoresist pattern PR on the data-wire areas A from being removed to expose the underlying portions of the data wire 171, 173a, 173b, 175a, 175b and 179.

[0102] Accordingly, the source electrodes 173a and 173b and the drain electrodes 175a and 175b are separated from each other, and, simultaneously, the data wire 171, 173a, 173b, 175a, 175b and 179 and the ohmic contact pattern 161, 163a, 163b, 165a and 165b thereunder are completed.

[0103] Finally, the portions of the photoresist pattern PR left on the data areas A are removed. Alternatively, the portions of the photoresist pattern PR on the data areas A are removed after the portions of the S/D conductors 170a and 170b on the channel areas C are removed and before the underlying portions of the S/D ohmic contacts 160a and 160b are removed.

[0104] As described above, wet etching and dry etching may be performed one after the other, but only dry etching may be used. The latter is relatively simple but it is not easy to find a proper etching condition compared with the former. On the contrary, it is easy to find a proper etching condition for the former case but the former is relatively complicated compared with the latter.

[0105] Thereafter, as shown in FIGS. 4 and 5, a passivation layer 180 is formed by growing a-Si:C:O or a-Si:O:F by CVD, by depositing silicon nitride, or by coating an organic insulating material such as acrylic-based material. When forming an a-Si:C:O layer, SiH(CH₃)₃, SiO₂(CH₃)₄, (SiH)₄O₄(CH₃)₄, Si(C₂H₅O)₄ or basic source, oxidant such as N₂ or O₂, and Ar or He are mixed in gaseous states to flow for the deposition. For an a-Si:O:F layer, the deposition is performed with flowing a gas mixture including SiH₄, SiF₄ or the like and an additional gas of O₂. CF₄ may be added as a secondary source of fluorine.

[0106] As shown in FIGS. 4 and 5, the passivation layer 180 together with the gate insulating layer 140 is photo-etched to form a plurality of contact holes 181, 182, 183, 184, 185 and 186 exposing the first drain electrodes 175a, the second source electrodes 173b, the storage electrode lines 131, the gate pads 125, the storage pads 135 and the data pads 179. It is preferable that the area of the contact holes 184, 185 and 186 exposing the pads 125, 179 and 135 is equal to or larger than 0.5 mm×15 μm and not larger than 2 mm×60 μm. (Third Mask)

[0107] Finally, an ITO layer or an IZO layer with a thickness of 1500-500 Å is deposited and photo-etched to form a plurality of pixel electrodes 190 connected to the drain electrodes 175, a plurality of subsidiary gate pads 95 connected to the gate pads 125, a plurality of subsidiary data pads 97 connected to the data pads 179, and a plurality of bridges 92 connecting the second source electrodes 173b and the storage electrode lines 131. (Fourth Mask)

[0108] Since Cr etchant can be used as an etchant for an IZO layer, the exposed portions of the metal for the data wire and the gate wire through the contact holes are not corroded in the photo-etching step for forming the pixel electrodes 190, the subsidiary gate pads 95, the subsidiary data pads 97 and the bridges 92 from the IZO layer. An example of the Cr etchant is (HNO₃)/(NH₄)₂Ce(NO₃)₆/H₂O. The IZO layer is deposited at temperature preferably in a range from a room temperature to 200° C. for minimizing the contact resistance at the contacts. A preferred example of a target for the IZO layer includes In₂O₃ and ZnO. The content of ZnO is preferably in a range between 15 atm % and 20 atm %.

[0109] Meanwhile, nitrogen gas is preferably used for the pre-heating process before the deposition of the ITO layer or the IZO layer. This is to prevent the formation of metal oxides on portions of the metallic layers exposed through the contact holes 181, 182, 183, 184, 185 and 186.

[0110] FIG. 12 is a schematic diagram of the TFT array panels for an LCD shown in FIGS. 2A and 4 according to an embodiment of the present invention.

[0111] A TFT T1 connected to a data line 171 switches signals transmitted to a pixel electrode 190 while a TFT T2 connected to a storage electrode line switches signals entering a DCE 178. The pixel electrode 190 and the DCE 178 is capacitively coupled. For the same gray, there is no variation of the potential difference between the DCE 178 and the pixel electrode 190. Therefore, stability of image quality is ensured irrespective of inversion types such as line inversion, dot inversion or the like.

[0112] A source electrode of a DCE TFT according to the first and the second embodiments of the present invention is connected to a storage electrode line. However, the source electrode may be connected to a previous data line, which has some problems.

[0113] First, the application of the gate-on voltage to a previous gate line (represented as Gate N-1 in FIG. 1) causes a pixel electrode located diagonal to a relevant pixel applied with a gray voltage and a DCE of the relevant pixel applied with an initial voltage. The initial voltage of the DCE is equal to the gray voltage of the diagonally-located pixel electrode. Accordingly, the potential difference V_{DP} between the DCE and a pixel electrode of the relevant pixel is determined by the gray voltage of the diagonally-located pixel electrode. For example, a low gray voltage such as a black voltage applied to the diagonally-located pixel electrode causes the low initial voltage of the DCE, thereby resulting in a low V_{DP} . A low V_{DP} means that the potential difference between the DCE and the pixel electrode is small, and thus lateral field due to the DCE is weak. Accordingly, the arrangement of the liquid crystal molecules is unstable, thereby causing texture.

[0114] Next, the VDP is defined by a voltage across a capacitor CDP, which is serially connected to an equivalent capacitor of C_{LC} and C_{ST} . Accordingly, the value of V_{DP} increases as the capacitance C_{DP} decreases. For reducing the capacitance CDP, the overlapping area between the pixel electrode and the DCE is designed to be minimized. However, this may cause image quality to be sensitively varied by misalignment of a mask during a manufacturing process and light leakage near the DCE. For the former case, the mask misalignment changes the overlapping area of the pixel electrode and the DCE, and this directly affect on the image quality. The latter case occurs when the initial voltage of the DCE is high (that is, the gray voltage applied to the diagonally-located pixel electrode is high) and a black voltage is applied to the relevant pixel. The high voltage of the DCE forces to move the liquid crystal molecules to yield light leakage, which may not be blocked by the narrow DCE. The light leakage decreases contrast ratio.

[0115] A third embodiment for solving these problems will be described now.

[0116] FIG. 13 is an equivalent circuit diagram of an LCD according to a third embodiment of the present invention.

[0117] An LCD according to an embodiment of the present invention includes a TFT array panel, a color filter array panel opposite the TFT array panel, and a liquid crystal layer interposed therebetween. The TFT array panel is provided with a plurality of gate lines and a plurality of data

lines intersecting each other to define a plurality of pixel areas, and a plurality of storage electrode lines extending parallel to the gate lines. The gate lines transmit scanning signals and the data lines transmit image signals. A common voltage V_{com} is applied to the storage electrode lines. Each pixel area is provided with a pixel TFT for a pixel electrode and first and second DCE TFTs DCETFT1 and DCETFT2 for a DCE. The pixel TFT includes a gate electrode connected to a relevant gate line, a source electrode connected to a relevant data line, and a drain electrode connected to a relevant pixel electrode. The first DCE TFT includes a gate electrode connected to a previous gate line, a source electrode connected to a previous data line, and a drain electrode connected to a relevant DCE, while the second DCE TFT includes a gate electrode connected to the previous gate line, a source electrode connected to the relevant data line, and a drain electrode connected to the relevant pixel electrode.

[0118] The DCE is capacitively coupled with the pixel electrode, and the capacitor therebetween or its capacitance is represented by C_{DP} . The pixel electrode and a common electrode provided on the color filter array panel form a liquid crystal capacitor, and the liquid crystal capacitor or its capacitance is represented by C_{LC} . The pixel electrode and a storage electrode connected to one of the storage electrode lines form a storage capacitor, and the storage capacitor or its capacitance is represented by C_{ST} .

[0119] Although it is not shown in the circuit diagram, the pixel electrode according to an embodiment of the present invention has an aperture overlapping the DCE such that the electric field due to the DCE flows out through the aperture. The electric field flowing out through the aperture makes the liquid crystal molecules have pretilt angles. The pretilted liquid crystal molecules are rapidly aligned without dispersion along predetermined directions upon the application of the electric field due to the pixel electrode.

[0120] The LCD is assumed to be subject to dot inversion. The application of a gate-on signal to the previous gate line Gate N-1 turns on both the DCE TFTs DCETFT1 and DCETFT2 to make the DCE have a (+) gray voltage and to make the pixel electrode have a (-) gray voltage. The initial voltage of the DCE is the difference between the positive gray voltage and the negative gray voltage from the data lines Data A and Data B, respectively, which is twice or more the initial voltage of the DCE without the second DCE TFT DCETFT2. When the pixel TFT is turned on and the DCE TFTs DCETFT1 and DCETFT2 are turned off upon application of the gate-on signal to the relevant gate line Gate N, the DCE floats and thus the potential of the DCE also increases with maintaining the potential difference VDP from the potential of the pixel electrode. Accordingly, the structure according to the third embodiment ensures higher VDP to enhance the stability of the arrangement of the liquid crystal molecules, thereby stabilizing the texture.

[0121] Furthermore, since the V_{DP} is determined by the gray voltages of two adjacent previous pixels and is rarely affected by the capacitance C_{DP} , the capacitance C_{DP} need not be reduced to allow the DCE to have a sufficient width for overlapping the pixel electrode. Accordingly, the light leakage near the DCE is blocked and the image quality is not considerably affected by the mask misalignment.

[0122] In addition, the high VDP improves the response time and the afterimage.

[0123] The structure shown in FIG. 13 is suitable for dot inversion and line inversion, while other structures having modified connections of three TFTs may be adapted for other types of inversion.

[0124] Now, an exemplary TFT array panel for an LCD according to the third embodiment of the present invention is described in detail with reference to FIGS. 14 to 17.

[0125] FIG. 14 is a layout view of an LCD according to the third embodiment of the present invention, FIG. 15 is a sectional view of the LCD shown in FIG. 14 taken along the line XV-XV', FIG. 16 is a sectional view of the LCD shown in FIG. 14 taken along the line XVI-XVI', FIG. 17 is a sectional view of the LCD shown in FIG. 14 taken along the lines XVII-XVII' and XVII'-XVII''.

[0126] An LCD according to a third embodiment of the present invention includes a lower panel, an upper panel facing the lower panel, and a vertically aligned liquid crystal layer interposed between the lower panel and the upper panel.

[0127] The lower panel will now be described more in detail.

[0128] A plurality of gate lines 121 are formed on an insulating substrate 110 and a plurality of data lines 171 are formed thereon. The gate lines 121 and the data lines 171 are insulated from each other and intersect each other to define a plurality of pixel areas.

[0129] Each pixel area is provided with a pixel TFT, a first DCE TFT, a second DCE TFT, a DCE and a pixel electrode. The pixel TFT has three terminals, a first gate electrode 123a, a first source electrode 173ab and a first drain electrode 175a. The first DCE TFT has three terminals, a second gate electrode 123b, the first source electrode 173ab and a second drain electrode 175b while the second DCE TFT has three terminals, a third gate electrode 123c, a second source electrode 173c and a third drain electrode 175c. The first source electrode 173ab is used both for the pixel TFT and the first DCE TFT. The pixel TFT and the first DCE TFT are provided for switching the signals transmitted to the pixel electrode 190 while the second DCE TFT is provided for switching the signals entering the DCE 178. The gate electrode 123a, the source electrode 173a and the drain electrode 175 of the pixel TFT are connected to relevant one of the gate lines 121, relevant one of the data lines 171 and the pixel electrode 190, respectively. The gate electrode 123b, the source electrode 173b and the drain electrode 175b of the first DCE TFT are connected to previous one of the gate lines 121, the relevant data line 171 and the pixel electrode 190, respectively. The gate electrode 123c, the source electrode 173c and the drain electrode 175c of the second DCE TFT are connected to the previous gate line 121, previous one of the data lines 171 and the DCE 178, respectively. The DCE 178 is applied with a direction-controlling voltage for controlling the pre-tilts of the liquid crystal molecules to generate a direction-controlling electric field between the DCE 178 and the common electrode 270. The DCE 178 is formed in a step for forming the data lines 171.

[0130] The layered structure of the lower panel will be described in detail.

[0131] A plurality of gate lines 121 extending substantially in a transverse direction are formed on an insulating

substrate 110, and a plurality of first to third gate electrodes 123a-123c are connected to the gate lines 121. A plurality of gate pads 125 are connected to one ends of the gate lines 121.

[0132] A plurality of first and second storage electrode lines 131a and 131b and a plurality of sets of first to fourth storage electrodes 133a, 133b, 133c and 133d are also formed on the insulating substrate 110. The first and the second storage electrode lines 131a and 131b extend substantially in the transverse direction. The first and the second storage electrodes 133a and 133b extend from the first and the second storage electrode lines 131a and 131b in a longitudinal direction and are curved to extend in an oblique direction while the third and the fourth storage electrodes 134a and 134b extend in the longitudinal direction. A first storage wire including the first storage electrode lines 131a and the first and the third electrodes 133a and 134a and a second storage wire including the second storage electrode lines 131b and the second and the fourth electrodes 133b and 134b have inversion symmetry.

[0133] The gate wire 121, 123a-123c and 125 and the storage electrode wire 131, 133a, 133b, 134a and 134b are preferably made of Al, Cr or their alloys, Mo or Mo alloy. If necessary, the gate wire 121, 123a and 123b and the storage electrode wire 131 and 133a-133d include a first layer preferably made of Cr or Mo alloys having excellent physical and chemical characteristics and a second layer preferably made of Al or Ag alloys having low resistivity.

[0134] A gate insulating layer 140 is formed on the gate wire 121, 123a-123c and 125 and the storage electrode wire 131, 133a, 133b, 134a and 134b.

[0135] A semiconductor layer 151, 15ab and 154c preferably made of amorphous silicon is formed on the gate insulating layer 140. The semiconductor layer 151, 154ab and 154c includes a plurality of first and second channel semiconductors 154ab and 154c forming channels of TFTs and a plurality of data-line semiconductors 151 located under the data lines 171.

[0136] An ohmic contact layer 161, 163ab, 163c and 165a-165c preferably made of silicide or n+ hydrogenated amorphous silicon heavily doped with n type impurity is formed on the semiconductor layer 151, 154ab and 154c.

[0137] A data wire 171, 173ab, 173c, 175a-175c and 179 is formed on the ohmic contact layer 161, 163ab, 163c and 165a-165c and the gate insulating layer 140. The data wire 171, 173ab, 173c, 175a-175c and 179 includes a plurality of data lines 171 extending in the longitudinal direction and intersecting the gate lines 121 to form a plurality of pixels, a plurality of first source electrodes 173ab branched from the data lines 171 and extending onto portions 163ab of the ohmic contact layer, a plurality of first and second drain electrodes 175a and 175b disposed on portion 165a and 165b of the ohmic contact layer, located opposite the first source electrodes 173ab and separated from the first source electrodes 173ab, a plurality of second source electrodes 173c and a plurality of third drain electrodes 175c disposed on respective portions 163c and 165c opposite each other with respect to the third gate electrodes 123c, and a plurality of data pads 179 connected to one ends of the data lines 171 to receive image signals from an external device.

[0138] A plurality of DCEs 178 and 178a-178c are formed in the pixel areas defined by the intersections of the gate

lines 121 and the data lines 171. Each DCE 178 and 178a-178c includes a V-shaped stem 178 and a chevron-shaped branch 178a-178c and is connected to the third drain electrode 175c. The data wire 171, 173ab, 173c, 175a-175c and 179 and the DCEs 178 and 178a-178c are preferably made of Al, Cr or their alloys, Mo or Mo alloy. If necessary, the data wire 171, 173ab, 173c, 175a-175c and 179 and the DCEs 178 and 178a-178c include a first layer preferably made of Cr or Mo alloys having excellent physical and chemical characteristics and a second layer preferably made of Al or Ag alloys having low resistivity.

[0139] A passivation layer 180 preferably made of silicon nitride or organic insulator is formed on the data wire 171, 173ab, 173c, 175a-175c and 179.

[0140] The passivation layer 180 is provided with a plurality of first and second contact holes 181 and 182 exposing the first and the second drain electrodes 175a and 175b, a plurality of third contact holes 183 extending to the gate insulating layer 140 exposing the gate pads 125, and a plurality of fourth contact holes 184 exposing the data pads 179. The contact holes exposing the pads 125 and 179 may have various shapes such as polygon or circle. The area of the contact hole is preferably equal to or larger than 0.5 mm×15 μm and not larger than 2 mm×60 μm.

[0141] A plurality of pixel electrodes 190 are formed on the passivation layer 180. Each pixel electrode 190 is connected to the first and the second drain electrode 175a and 175b through the first and the second contact holes 181 and 182, respectively. The pixel electrode 190 has a transverse cutout 191 and a plurality of oblique cutouts 192a, 192b, 193a, 193b, 194a, 194b, 195a and 195b. The transverse cutout 191 bisects the pixel electrode 190 into upper and lower halves, and the oblique cutouts 192a, 192b, 193a, 193b, 194a, 194b, 195a and 195b have inversion symmetry with respect to the transverse cutout 191. Some cutouts 191, 192a, 192b, 194a, 194b, 195a and 195b overlap the DCE 178 and 178a-178c while the other cutouts 193a and 193b overlap the storage electrodes 133a and 133b.

[0142] Furthermore, a plurality of subsidiary gate pads 95 and a plurality of subsidiary data pads 97 are formed on the passivation layer 180. The subsidiary gate pads 95 and the subsidiary data pads 97 are connected to the gate pads 125 and the data pads 179 through the contact holes 183 and 184. The pixel electrodes 190, the subsidiary gate pads 95 and the subsidiary data pads 97 are preferably formed of IZO. Alternatively, the pixel electrodes 190 and the subsidiary pads 95 and 97 are preferably made of ITO.

[0143] To summarize, each pixel electrode 190 has the plurality of cutouts 191, 192a, 192b, 193a, 193b, 194a, 194b, 195a and 195b for partitioning a pixel region into a plurality of domains, and the cutouts 191, 192a, 192b, 194a, 194b, 195a and 195b overlap the DCE 178 and 178a-178c. The DCE 178 and 178a-178c and the cutouts 191, 192a, 192b, 194a, 194b, 195a and 195b are aligned such that the DCE 178 and 178a-178c is exposed through the cutouts 191, 192a, 192b, 194a, 194b, 195a and 195b to be seen in front view. The DCE 178 and 178a-178c is connected to the second DCE TFT while the pixel electrode 190 is connected to the first DCE TFT the pixel TFT, and the pixel electrode 190 and the DCE 178 are aligned to form a storage capacitance.

[0144] According to another embodiment of the present invention, the DCEs 178 and 178a-178c include substantially the same layer as the gate wire 121, 123a-123c and

125. The portions of the passivation layer 180 on the DCEs 178 and 178a-178c may be removed to form a plurality of openings.

[0145] The upper substrate 210 will not be described in detail.

[0146] A black matrix 220 for preventing light leakage, a plurality of red, green and blue color filters 230, and a common electrode 270 preferably made of a transparent conductor such as ITO or IZO are formed on an upper substrate 210 preferably made of transparent insulating material such as glass.

[0147] A plurality of liquid crystal molecules contained in the liquid crystal layer 3 is aligned such that their director is perpendicular to the lower and the upper substrates 110 and 210 in absence of electric field. The liquid crystal layer 3 has negative dielectric anisotropy.

[0148] The lower substrate 110 and the upper substrate 210 are aligned such that the pixel electrodes 190 exactly match and overlap the color filters 230. In this way, a pixel region is divided into a plurality of domains by the cutouts 191, 192a, 192b, 193a, 193b, 194a, 194b, 195a and 195b. The alignment of the liquid crystal layer 3 in each domain is stabilized by the DCE 178 and 178a-178c.

[0149] This embodiment illustrates the liquid crystal layer 3 having negative dielectric anisotropy and homeotropic alignment with respect to the substrates 110 and 210. However, the liquid crystal layer 3 may have positive dielectric anisotropy and homogeneous alignment with respect to the substrates 110 and 210.

[0150] A TFT array panel according to the third embodiment of the present invention may be manufactured using four photo-etching steps. In this case, a data wire and DCEs have a triple-layered structure including an amorphous silicon layer, an ohmic contact layer and a metal layer, and the triple layers have substantially the same planar shape, which is resulted from the patterning of the amorphous silicon layer, the ohmic contact layer and the metal layer using a photoresist film. Since such a manufacturing method is described in detail in the description about the second embodiment of the present invention, the manufacturing method is understood in view of the fact that the patterns made of the same layer(s) are formed in the same step and thus the detailed description thereof is omitted.

[0151] Although preferred embodiments of the present invention have been described in detail hereinabove, it should be clearly understood that many variations and/or modifications of the basic inventive concepts herein taught which may appear to those skilled in the present art will still fall within the spirit and scope of the present invention, as defined in the appended claims.

[0152] As described above, first and second DCE TFTs switching the signals transmitted to a DCE and a pixel electrode to generate initial direction-control voltage VDP, thereby ensuring stable brightness.

What is claimed is:

1. A thin film transistor array panel comprising:
 - an insulating substrate;
 - a plurality of first signal lines formed on the insulating substrate;

a plurality of second signal lines formed on the insulating substrate, insulated from the first signal lines, and intersecting the first signal lines;

a plurality of pixel electrodes provided on the respective pixel areas defined by the intersections of the first and the second signal lines, each pixel electrode having a cutout;

a plurality of direction control electrodes provided on the respective pixel areas defined by the intersections of the first and the second signal lines;

a first thin film transistor connected to a relevant one of the first signal lines, a relevant one of the second signal lines and a relevant one of the pixel electrodes;

a second thin film transistor connected to a previous one of the first signal lines, a previous one of the second signal lines and a relevant one of the direction control electrodes; and

a third thin film transistor connected to the previous first signal line, the relevant second signal line and the relevant pixel electrode.

2. The thin film transistor array panel of claim 1, further comprising a third signal line insulated from the second signal lines and intersecting the second signal lines, the third signal line including a portion overlapping the cutout of the pixel electrode.

3. A thin film transistor array panel comprising:

an insulating substrate;

a gate wire formed on the insulating substrate and including first to third gate electrodes and a plurality of gate lines;

a gate insulating layer formed on the gate wire;

a semiconductor layer formed on the gate insulating layer;

a data wire formed on the semiconductor layer and including a plurality of data lines intersecting the gate lines, first to third source electrodes connected to the data lines, and first to third drain electrodes opposite the first to the third source electrodes with respect to the first to the third gate electrodes;

a direction control electrode connected to the second drain electrode;

a protective layer formed on the data wire and the direction control electrode and having a plurality of contact holes; and

a pixel electrode formed on the protective layer, having a plurality of cutouts, and electrically connected to the first and the third drain electrodes through the contact holes.

4. The thin film transistor array panel of claim 3, wherein the first and the third source electrodes are connected to a relevant one of the data lines, the second source electrode is connected to a previous one of the data lines, the first and the second gate electrodes are connected to a previous one of the gate lines, and the third gate electrode is connected to a relevant one of the gate lines.

5. The thin film transistor array panel of claim 4, wherein the cutouts of the pixel electrode comprise a transverse cutout bisecting the pixel electrode 190 into upper and lower

halves and a plurality of oblique cutouts having inversion symmetry with respect to the transverse cutout.

6. The thin film transistor array panel of claim 4, wherein the direction control electrode overlaps at least one of the cutouts of the pixel electrode and has inversion symmetry with respect to a transverse one of the cutouts of the pixel electrode.

7. The thin film transistor array panel of claim 4, further comprising a storage electrode wire including substantially the same layer as the gate wire and having a portion overlapping at least one of the cutouts of the pixel electrode.

8. The thin film transistor array panel of claim 4, wherein the direction control electrode includes substantially the same layer and material as the data wire.

9. The thin film transistor array panel of claim 4, wherein the contact holes have rectangular shapes having an edge parallel to or perpendicular to the oblique cutouts.

10. The thin film transistor array panel of claim 4, wherein the data wire and the direction control electrode include double layers of a semiconductor layer and a metal layer.

11. The thin film transistor array panel of claim 4, wherein the semiconductor layer includes double films of an amorphous silicon film and an ohmic contact layer.

12. A liquid crystal display comprising:

a first insulating substrate;

a plurality of first signal lines formed on the first insulating substrate;

a plurality of second signal lines formed on the first insulating substrate, insulated from the first signal lines, and intersecting the first signal lines;

a plurality of pixel electrodes provided on the respective pixel areas defined by the intersections of the first and the second signal lines, the pixel electrodes having cutouts;

a plurality of direction control electrodes provided on the respective pixel areas defined by the intersections of the first and the second signal lines;

a first thin film transistor connected to a relevant one of the first signal lines, a relevant one of the second signal lines and a relevant one of the pixel electrodes;

a second thin film transistor connected to a previous one of the first signal lines, a previous one of the second signal lines and a relevant one of the direction control electrodes;

a third thin film transistor connected to the previous first signal line, the relevant second signal line and the relevant pixel electrode;

a second insulating substrate opposite the first insulating substrate;

a common electrode formed on the second insulating substrate; and

a liquid crystal layer interposed between the first and the second substrates.

13. The liquid crystal display of claim 12, wherein the liquid crystal layer has negative dielectric anisotropy and major axes of liquid crystal molecules in the liquid crystal layer are aligned vertical to the first and the second substrates.

专利名称(译)	多畴液晶显示器和它的薄膜晶体管基板		
公开(公告)号	US20060092361A1	公开(公告)日	2006-05-04
申请号	US10/527042	申请日	2002-10-10
[标]申请(专利权)人(译)	基姆熙燮 杨YOUNG CHOL 金正日LAE SHIN KYONG JU		
申请(专利权)人(译)	金喜善SEOB 杨YOUNG-CHOL 金正LAE SHIN KYONG-JU		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KIM HEE SEOB YANG YOUNG CHOL KIM JONG LAE SHIN KYONG JU		
发明人	KIM, HEE-SEOB YANG, YOUNG-CHOL KIM, JONG-LAE SHIN, KYONG-JU		
IPC分类号	G02F1/1343 G02F1/1333 G02F1/1337 G02F1/1362 G02F1/1368 G02F1/139		
CPC分类号	G02F1/133707 G02F1/133753 G02F2001/133757 G02F1/1393 G02F1/13624		
优先权	1020020054277 2002-09-09 KR		
其他公开文献	US7333171		
外部链接	Espacenet USPTO		

摘要(译)

提供一种薄膜晶体管阵列面板，其包括：绝缘基板；形成在绝缘基板上的多条栅极线；多条数据线形成在绝缘基板上，与栅极线绝缘，并与栅极线交叉；多条存储电极线，形成在绝缘基板上，与数据线绝缘，并与数据线交叉；多个像素电极设置在由栅极线和数据线的交叉点限定的各个像素区域上，每个像素电极具有切口；多个方向控制电极设置在由栅极线和数据线的交叉点限定的各个像素区域上；第一薄膜晶体管，连接到相关的一条栅极线，相关的一条数据线和相关的一条栅极线，相关的一条数据线和相关的一条像素电极；第二薄膜晶体管，连接到前一条栅极线，前一条数据线和相关的一条方向控制电极；第三薄膜晶体管，连接到前一栅极线，相关数据线和相关像素电极。

