



US 20090310052A1

(19) **United States**(12) **Patent Application Publication**
Huang et al.(10) **Pub. No.: US 2009/0310052 A1**(43) **Pub. Date: Dec. 17, 2009**(54) **LIQUID CRYSTAL DISPLAY PANEL**(30) **Foreign Application Priority Data**(75) Inventors: **Chun-Kang Huang**, Taichung City
(TW); **Chun-Chieh Wu**, Kaohsiung
County (TW); **Chia-Li Su**,
Taichung County (TW)


Jun. 16, 2008 (TW) 97122411

Publication Classification(51) **Int. Cl.**
G02F 1/1333 (2006.01)(52) **U.S. Cl.** **349/40**(57) **ABSTRACT**

Correspondence Address:

THOMAS, KAYDEN, HORSTEMEYER & RIS-
LEY, LLP**600 GALLERIA PARKWAY, S.E., STE 1500**
ATLANTA, GA 30339-5994 (US)(73) Assignee: **WINTEK CORPORATION**,
Taichung (TW)(21) Appl. No.: **12/485,203**(22) Filed: **Jun. 16, 2009**

A liquid crystal display (LCD) panel including a first substrate, a second substrate, a liquid crystal layer, a sealant and an electrostatic protection structure is provided. The first substrate and the second substrate are disposed in parallel. The sealant is for sealing the liquid crystal layer between the first substrate and the second substrate. The electrostatic protection structure is disposed within a non-display area outside the sealant. The electrostatic protection structure includes a first line disposed on the first substrate and surrounding the edge of the first substrate.

100'




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

500




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

LIQUID CRYSTAL DISPLAY PANEL

[0001] This application claims the benefit of Taiwan application Serial No. 97122411, filed Jun. 16, 2008, the subject matter of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The invention relates in general to a liquid crystal display (LCD) panel, and more particularly to an LCD panel with an electrostatic protection structure.

[0004] 2. Description of the Related Art

[0005] Nowadays, electronic products are very popular and widely used in people's everyday life. However, static electricity is everywhere in the environment, so that almost all electronic products are subject to the interference of electrostatic discharge or even damaged by electrostatic discharge.

[0006] Conventionally, electrostatic charges are accumulated at two substrates of the LCD panel. When too many electrostatic charges are accumulated, the internal circuits of the substrates would malfunction or even be damaged. Although an electrostatic discharge circuit is designed in the internal circuit of the substrate of the conventional LCD panel, the electrostatic discharge circuit can only protect the internal circuits from the static electricity less than 2 KV, so the reliability for the electrostatic protection of the LCD panel is not well. Therefore, how to design a quality discharge structure capable of effectively resolving the static electricity problem to avoid the malfunction of the LCD panel and prolong the lifespan of the LCD panel has become an imminent issue to manufacturers.

SUMMARY OF THE INVENTION

[0007] The invention is directed to a liquid crystal display (LCD) panel. A ring-type electrostatic protection structure is disposed at the gap between two substrates of the LCD panel. The electrostatic protection of the LCD panel is enhanced with the disposition of the electrostatic protection structure. In addition, the electrostatic protection structure can be simultaneously formed in the step of forming the ITO structure of the LCD panel without incurring additional manufacturing cost, so as to increase the product competitiveness.

[0008] According to the present invention, a liquid crystal display (LCD) panel including a first substrate, a second substrate, a liquid crystal layer, a sealant and an electrostatic protection structure is provided. The first substrate and the second substrate are disposed in parallel to each other. The sealant is for sealing the liquid crystal layer between the first substrate and the second substrate. The electrostatic protection structure is disposed within a non-display area outside the sealant. The electrostatic protection structure includes a first line disposed on the first substrate and surrounding the inner edge of the first substrate.

[0009] The invention will become apparent from the following detailed description of the preferred but non-limiting embodiments. The following description is made with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 shows a partial diagram of an LCD panel according to a first embodiment of the invention;

[0011] FIG. 2 shows a cross-section view of the LCD panel in FIG. 1 along the cross-sectional line 2-2';

[0012] FIG. 3 shows an example of an LCD panel with a first line being electrically connected to a grounding lead;

[0013] FIG. 4 shows a partial diagram of an LCD panel whose first line is saw-toothed at the side facing the sealant;

[0014] FIG. 5 shows a cross-section view of an LCD panel according to a second embodiment of the invention;

[0015] FIG. 6 shows a cross-section view of an LCD panel according to a third embodiment of the invention;

[0016] FIG. 7 shows a cross-section view of an LCD panel according to a fourth embodiment of the invention;

[0017] FIG. 8 shows a cross-section view of an LCD panel according to a fifth embodiment of the invention;

[0018] FIG. 9 shows a cross-section view of an LCD panel according to a sixth embodiment of the invention;

[0019] FIG. 10 shows a cross-section view of an LCD panel according to a seventh embodiment of the invention;

[0020] FIG. 11 shows a cross-section view of an LCD panel according to an eighth embodiment of the invention; and

[0021] FIG. 12 shows a cross-section view of an LCD panel according to a ninth embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0022] A liquid crystal display (LCD) panel is provided in following embodiments of the invention. The LCD panel includes a first substrate, a second substrate, a liquid crystal layer, a sealant and an electrostatic protection structure. The electrostatic protection structure includes a first line disposed on the first substrate and surrounding the inner edge of the first substrate for discharging accumulated electrostatic charges, such that the LCD panel has excellent electrostatic protection effect. The above-mentioned first substrate can be a thin film transistor (TFT) substrate or a color filter substrate.

[0023] Nine embodiments are disclosed below, so that anyone who is skilled in the related art of the invention can distinctly understand the scope of the invention. The first embodiment is illustrated by accompanying with FIGS. 1~4, and the second embodiment to the ninth embodiment are illustrated by accompanying with FIGS. 5~12, respectively. The embodiments of the invention are used for exemplifying the invention only not for limiting the scope of the invention. Furthermore, some components are omitted in the drawings to highlight the features of the invention.

First Embodiment

[0024] In the first embodiment, the electrostatic protection structure includes a first line. The first substrate is a TFT substrate, the second substrate is a color filter substrate, and the first line is disposed on the TFT substrate and surrounds the edge of the TFT substrate.

[0025] Referring to both FIG. 1 and FIG. 2, a partial diagram of an LCD panel according to a first embodiment of the invention is shown in FIG. 1, and a cross-section view of the LCD panel in FIG. 1 along the cross-sectional line 2-2' is shown in FIG. 2. The LCD panel 100 includes a TFT substrate 110, a color filter substrate 120, a liquid crystal layer 130, a sealant 140 and an electrostatic protection structure 150. The TFT substrate 110 and the color filter substrate 120 are disposed in parallel to each other. The sealant 140 seals the liquid crystal layer 130 between the TFT substrate 110 and the color filter substrate 120. The inner area of the sealant 140 is a display area of the LCD panel 100. The display area is sub-

stantially the part of the liquid crystal layer **130** sealed by the sealant **140** as indicated in FIG. 1. The electrostatic protection structure **150** is disposed within a non-display area outside the sealant **140**. The TFT substrate **110** includes a transparent substrate **111**, a common electrode line **112**, an insulating layer **114**, an ITO electrode layer **116** and an electric conductor **118**. The color filter substrate **120** includes a transparent substrate **121**, a black matrix layer **123** and a common electrode **126**. The electric conductor **118** is electrically connected to the ITO electrode layer **116** of the TFT substrate **110** and the common electrode **126** of the color filter substrate **120**.

[0026] In the present embodiment of the invention, the first line **151** of the electrostatic protection structure **150** is disposed on the insulating layer **114** of the TFT substrate **110** and surrounds the inner edge of the TFT substrate **110**.

[0027] The first line **151** can be floating or grounded. Preferably, the first line **151** is grounded. Referring to FIG. 3, an example of an LCD panel with a first line being electrically connected to a grounding lead is shown. The components in FIG. 3 which are the same as those in FIG. 1 and have the same functions are designated with the same numbers, and the components are not repeatedly described herein. As indicated FIG. 3, the LCD panel **100'** further includes an integrated circuit chip **160** and a flexible circuit board **170**. The flexible circuit board **170** has at least one grounding lead **172** disposed thereon. In FIG. 3, the integrated circuit chip **160** and the flexible circuit board **170** are both disposed on the TFT substrate **110**, for example. The first line **151'** exemplified by being grounded can be electrically connected to the grounding lead **172** of the flexible circuit board **170**.

[0028] The experimental results show that electrostatic discharge normally occurs at the gap between the TFT substrate **110** and the color filter substrate **120**. When a high voltage static electricity is discharged, an electric arc may even generate between the first substrate **110** and the second substrate **120**. In the present embodiment of the invention, with the electrostatic protection structure **150** being disposed between the first substrate **110** and the second substrate **120** and surrounding the inner edge of the substrate, the electrostatic charges accumulated on the first substrate **110** and the second substrate **120** and between the first substrate **110** and the second substrate **120** can be efficiently discharged, so as to achieve excellent electrostatic protection effect.

[0029] Moreover, the side of the first line facing the sealant is preferably saw-toothed. Referring to FIG. 4, a partial diagram of an LCD panel whose first line is saw-toothed at the side facing the sealant is shown. The components in FIG. 4 which are the same as those in FIG. 1 and have the same functions are designated with the same numbers, and the components are not repeatedly described herein. As indicated in FIG. 4, the first line **151''** of the electrostatic protection structure **150''** of the LCD panel **100''** has many sharp ends **151s''** for increasing the possibility of point discharge, such that the electrostatic charges are more easily to be transmitted to the first line **151''** and be discharged from the first line **151''** accordingly. Preferably, the first line **151''** and the ITO electrode layer of the TFT substrate are made of the same material, such as indium tin oxide (ITO). Thus, the first line can be simultaneously formed in the step of forming the ITO structure of the TFT substrate without incurring additional manufacturing cost.

Second Embodiment

[0030] The second embodiment differs from the first embodiment in the disposition relationship between the com-

mon electrode line and the electrostatic protection structure. In the second embodiment, the electrostatic protection of the LCD panel is further enhanced by changing the disposition relationship between the common electrode line and the electrostatic protection structure. Referring to FIG. 5, a cross-section view of an LCD panel according to a second embodiment of the invention is shown. As FIG. 5 can be viewed as a modification of FIG. 2, similar components in FIG. 5 are designated with similar numbers and are not repeatedly described herein.

[0031] In FIG. 5, the first line **251** is partially overlapped and electrically insulated from the common electrode line **212**, so as to form a capacitor structure at the overlapped part between the first line **251** and the common electrode line **212**. When electrostatic discharge occurs, the capacitor structure generates capacitor coupling effect for discharging the electrostatic charges of the common electrode line **212** via the first line **251**. Thus, the electrostatic charges accumulated at the common electrode line **212** can be quickly discharged via the first line **251**.

Third Embodiment

[0032] The third embodiment differs from the second embodiment in that a metal layer is disposed between the first line and the common electrode line. In the present embodiment of the invention, the metal layer is used for increasing the equivalent capacitance of the capacitor structure so as to further enhance the electrostatic protection of the LCD panel. Referring to FIG. 6, a cross-section view of an LCD panel according to a third embodiment of the invention is shown. As FIG. 6 can be viewed as a modification of FIG. 5, similar components in FIG. 6 are designated with similar numbers and are not repeatedly described herein.

[0033] In FIG. 6, the electrostatic protection structure **350** further includes a metal layer **353** positioned between the first line **351** and the common electrode line **312**, and a part of the metal layer **353** is covered by the insulating layer **314**. The metal layer **353** is electrically connected to the first line **351** and is partially overlapped and electrically insulated from the common electrode line **312** so as to form a capacitor structure at the overlapped part between the metal layer **353** and the common electrode line **312**. As the distance between the metal layer **353** and the common electrode line **312** in the present embodiment is shorter than the distance between the first line **251** and the common electrode line **212** in the second embodiment, the equivalent capacitance of the capacitor structure in the present embodiment is larger than that in the second embodiment. Thus, when electrostatic charges are accumulated at the common electrode line **312**, the electrostatic charges can be quickly and easily discharged via the metal layer **353** and the first line **351**.

Fourth Embodiment

[0034] The fourth embodiment is similar to the first embodiment. The difference between the two embodiments is that the first line of the fourth embodiment is disposed on the color filter substrate and surrounds the edge of the color filter substrate. The components and the functions which are similar to those in the first embodiment are not repeatedly described in the following.

[0035] Referring to FIG. 7, a cross-section view of an LCD panel according to a fourth embodiment of the invention is shown. As indicated in FIG. 7, the LCD panel **400** includes a

TFT substrate **410**, a color filter substrate **420**, a liquid crystal layer **430**, a sealant **440** and an electrostatic protection structure **450**. The electrostatic protection structure **450** includes a first line **451**. The TFT substrate **410** includes a transparent substrate **411**, a common electrode line **412**, an insulating layer **414**, an ITO electrode layer **416** and an electric conductor **418**. The color filter substrate **420** includes a transparent substrate **421**, a black matrix layer **423** and a common electrode **426**. The electric conductor **418** is coupled to the ITO electrode layer **416** and the common electrode **426**. The first line **451** of the present embodiment is disposed on the color filter substrate **420** and surrounds the inner edge of the color filter substrate **420**. Likewise, the first line **451** can be floating or grounded.

[0036] The first line **451** of the present embodiment which is disposed on and surrounds the color filter substrate **420** has the same function as the first line in the first embodiment. That is, the first line **451** can discharge the accumulated electrostatic charges so as to achieve excellent electrostatic protection effect. In addition, the inner side of the first line **451** can also be saw-toothed for increasing the possibility of point discharge, such that the electrostatic charges are more easily to be transmitted to the first line **451** and be discharged from the first line **451** accordingly. Moreover, the first line **451** and the common electrode **426** of the color filter substrate **420** can be made of the same material, such that the first line **451** can be simultaneously formed in the step of forming the ITO structure of the color filter substrate without incurring additional manufacturing cost.

Fifth Embodiment

[0037] The fifth embodiment differs from the fourth embodiment in the disposition relationship between the common electrode line and the electrostatic protection structure. In the present embodiment of the invention, the electrostatic protection of the LCD panel is further enhanced by changing the disposition relationship between the common electrode line and the electrostatic protection structure. Referring to FIG. 8, a cross-section view of an LCD panel according to a fifth embodiment of the invention is shown. As FIG. 8 can be viewed as a modification of FIG. 7, similar components in FIG. 8 are designated with similar numbers and are not repeatedly described herein.

[0038] In FIG. 8, the first line **551** is partially overlapped and electrically insulated from the common electrode line **512**, so as to form a capacitor structure at the overlapped part between the first line **551** and the common electrode line **512**. When electrostatic discharge occurs, the capacitor structure generates capacitor coupling effect for discharging the static electricity of the common electrode line **512** via the first line **551**. Thus, when static electricity is generated at the common electrode line **512**, the static electricity can be quickly discharged via the first line **551**.

Sixth Embodiment

[0039] The sixth embodiment differs from the fifth embodiment in that a metal layer is disposed between the first line and the common electrode line. In the present embodiment of the invention, the electrostatic protection of the LCD panel is further enhanced by increasing the equivalent capacitance of the capacitor structure. Referring to FIG. 9, a cross-section view of an LCD panel according to a sixth embodiment of the invention is shown. As FIG. 9 can be viewed as a modification

of FIG. 8, similar components in FIG. 9 are designated with similar numbers and are not repeatedly described herein.

[0040] In FIG. 9, the electrostatic protection structure **650** further includes a metal layer **653** positioned between the first line **651** and the common electrode line **612**, and a part of the metal layer **653** is covered by the insulating layer **614**. The metal layer **653** is partially overlapped and electrically insulated from the first line **651**, so as to form a capacitor structure at the overlapped part between the metal layer **653** and the first line **651**. The metal layer **653** is partially overlapped and electrically insulated from the common electrode line **612**, so as to form another capacitor structure at the overlapped part between the metal layer **653** and the common electrode line **612**, such that static electricity at the common electrode line **612** can be easily and quickly discharged via the metal layer **653** and the first line **651**.

Seventh Embodiment

[0041] The design of the seventh embodiment is a combination of the first embodiment and the fourth embodiment. In the present embodiment of the invention, except the first line is disposed on the TFT substrate and surrounds the inner edge of the TFT substrate, a second line is disposed on the color filter substrate and surrounds the edge of the color filter substrate. The components and the functions of the present embodiment which are similar to those in the first embodiment are not repeatedly described in the following.

[0042] Referring to FIG. 10, a cross-section view of an LCD panel according to a seventh embodiment of the invention is shown. As indicated in FIG. 10, the LCD panel **700** includes a TFT substrate **710**, a color filter substrate **720**, a liquid crystal layer **730**, a sealant **740** and an electrostatic protection structure **750**. The electrostatic protection structure **750** includes a first line **751** and a second line **752**. The TFT substrate **710** includes a transparent substrate **711**, a common electrode line **712**, an insulating layer **714**, an ITO electrode layer **716** and an electric conductor **718**. The color filter substrate **720** includes a transparent substrate **721**, a black matrix layer **723** and a common electrode **726**. The electric conductor **718** is coupled to the ITO electrode layer **716** and the common electrode **726**. The first line **751** of the present embodiment is disposed on the insulating layer **714** of the TFT substrate **710** and surrounds the inner edge of the TFT substrate **710**. The second line **752** is disposed on the color filter substrate **720** and surrounds the inner edge of the color filter substrate **720**, and the second line **752** is opposite to the first line **751**.

[0043] Likewise, the first line **751** and the second line **752** can be floating or grounded. Preferably, the first line **751** and the second line **752** are grounded. In the present embodiment of the invention, the electrostatic protection structure **750** may further include one or several electric conductor **754**. The electric conductors **754**, **718** can be made of the same material, such as conductive glue or silver conductive adhesive, and the electric conductors **754**, **718** can be simultaneously formed in the same manufacturing step. The electric conductor **754** is for coupling the first line **751** to the second line **752**, such that the second line **752** is grounded via the electric conductor **754** and the first line **751**.

[0044] The functions of the first line **751** and the second line **752** of the present embodiment are similar to those of the first embodiment and the fourth embodiment. That is, the first line **751** and the second line **752** are capable of discharging accumulated electrostatic charges so as to achieve excellent elec-

trostatic protection effect. The inner sides of the first line **751** and the second line **752** can be saw-toothed for increasing the possibility of point discharge, such that the electrostatic charges can be more easily to be transmitted to the first line **751** and the second line **752** and be discharged from the first line **751** and the second line **752** accordingly. The first line **751** and the second line **752** can be made of the same material as that of the ITO electrode layer **716** and the common electrode **726**. Therefore, the first line **751** can be simultaneously formed in the step of forming the ITO structure of the TFT substrate, and the second line **752** can be simultaneously formed in the step of forming the ITO structure of the color filter substrate without incurring additional manufacturing cost.

Eighth Embodiment

[0045] The eighth embodiment differs from the seventh embodiment in the disposition relationship between the common electrode line and the electrostatic protection structure. In the present embodiment of the invention, the electrostatic protection of the LCD panel is further enhanced by changing the disposition relationship between the common electrode line and the electrostatic protection structure. Referring to FIG. 11, a cross-section view of an LCD panel according to a eighth embodiment of the invention is shown. As FIG. 11 can be viewed as a modification of FIG. 10, similar components in FIG. 11 are designated with similar numbers and are not repeatedly described herein.

[0046] In FIG. 11, the first line **851** is partially overlapped and electrically insulated from the common electrode line **812**, such that a capacitor structure is formed at the overlapped part between the first line **851** and the common electrode line **812**. The second line **852** is also partially overlapped and electrically insulated from the common electrode line **812**. When electrostatic discharge occurs, the capacitor structure generates capacitor coupling effect for discharging the static electricity of the common electrode line **812** via the first line **851**. Thus, when static electricity is generated at the common electrode line **812**, the static electricity can be quickly discharged via the first line **851**.

Ninth Embodiment

[0047] The ninth embodiment differs from the eighth embodiment in that a metal layer is disposed between the first line and the common electrode line. In the present embodiment of the invention, the electrostatic protection of the LCD panel is further enhanced by increasing the equivalent capacitance of the capacitor structure. Referring to FIG. 12, a cross-section view of an LCD panel according to a ninth embodiment of the invention is shown. As FIG. 12 can be viewed as a modification of FIG. 11, similar components in FIG. 12 are designated with similar numbers and are not repeatedly described herein.

[0048] In FIG. 12, the electrostatic protection structure **950** further includes a metal layer **953** positioned between the first line **951** and the common electrode line **912**, and a part of the metal layer **953** is covered by the insulating layer **914**. The metal layer **953** is electrically connected to the first line **951** and is partially overlapped and electrically insulated from the common electrode line **912**, so as to form a capacitor structure at the overlapped part between the metal layer **953** and the first line **951**. The second line **952** is partially overlapped and electrically insulated from the common electrode line **912**.

Thus, the static electricity accumulated at the common electrode line **912** can be more quickly and easily discharged via the metal layer **953** and the first line **951**.

[0049] According to the results of electrostatic discharge test, the electrostatic protection of each of the LCD panels of the above embodiments is more than 8 KV and thus far outdoes that of the conventional LCD panel which is only 2 KV. Meanwhile, the manufacturing process of the electrostatic protection structure of each above embodiment can be integrated with the original manufacturing process of LCD panels without incurring more manufacturing cost, hence greatly increasing product competitiveness.

[0050] While the invention has been described by way of example and in terms of a preferred embodiment, it is to be understood that the invention is not limited thereto. On the contrary, it is intended to cover various modifications and similar arrangements and procedures, and the scope of the appended claims therefore should be accorded the broadest interpretation so as to encompass all such modifications and similar arrangements and procedures.

What is claimed is:

1. A liquid crystal display (LCD) panel, comprising:
 - a first substrate and a second substrate disposed in parallel to each other;
 - a liquid crystal layer;
 - a sealant for sealing the liquid crystal layer between the first substrate and the second substrate; and
 - an electrostatic protection structure disposed within a non-display area outside the sealant, wherein the electrostatic protection structure comprises:
 - a first line disposed on the first substrate and surrounding the edge of the first substrate.
2. The LCD panel according to claim 1, wherein the first substrate is a thin film transistor (TFT) substrate.
3. The LCD panel according to claim 2, wherein the first substrate has at least one common electrode line partially overlapped and electrically insulated from the first line.
4. The LCD panel according to claim 3, wherein the first substrate further has an insulating layer which covers the common electrode line, and the electrostatic protection structure further comprises:
 - a metal layer positioned between the first line and the common electrode line, wherein a part of the metal layer is covered by the insulating layer, and the metal layer is electrically connected to the first line and is partially overlapped and electrically insulated from the common electrode line.
5. The LCD panel according to claim 1, wherein the first substrate is a color filter substrate.
6. The LCD panel according to claim 5, wherein the second substrate has at least one common electrode line partially overlapped and electrically insulated from the first line.
7. The LCD panel according to claim 6, wherein the second substrate further has an insulating layer which covers the common electrode line, and the electrostatic protection structure further comprises:
 - a metal layer positioned between the first line and the common electrode line and covered by the insulating layer, wherein the metal layer is partially overlapped and electrically insulated from the first line and the common electrode line.
8. The LCD panel according to claim 1, wherein the side of the first line facing the sealant is saw-toothed.

9. The LCD panel according to claim 1, wherein the first line is made of indium tin oxide (ITO).

10. The LCD panel according to claim 1, wherein the first line is grounded.

11. The LCD panel according to claim 1, wherein the first line is floating.

12. The LCD panel according to claim 1, wherein the electrostatic protection structure further comprises a second line disposed on the second substrate and surrounding the inner edge of the second substrate, and the second line is opposite to the first line.

13. The LCD panel according to claim 12, wherein the first substrate has at least one common electrode line, the first line is partially overlapped and electrically insulated from the common electrode line, and the second line is partially overlapped and electrically insulated from the common electrode line.

14. The LCD panel according to claim 13, wherein the first substrate further has an insulating layer which covers the common electrode line, and the electrostatic protection structure further comprises:

a metal layer positioned between the first line and the common electrode line, wherein a part of the metal layer is covered by the insulating layer, the metal layer is electrically connected to the first line and is partially overlapped and electrically insulated from the common electrode line, and the second line is partially overlapped and electrically insulated from the common electrode line.

15. The LCD panel according to claim 12, wherein the second line is floating.

16. The LCD panel according to claim 12, wherein the second line is grounded.

17. The LCD panel according to claim 12, wherein the first line is grounded, and the electrostatic protection structure further comprises:

an electric conductor for electrically connecting to the first line and the second line, such that the second line is grounded.

* * * * *

专利名称(译)	液晶显示面板		
公开(公告)号	US20090310052A1	公开(公告)日	2009-12-17
申请号	US12/485203	申请日	2009-06-16
[标]申请(专利权)人(译)	胜华科技股份有限公司		
申请(专利权)人(译)	胜华科技股份有限公司		
当前申请(专利权)人(译)	胜华科技股份有限公司		
[标]发明人	HUANG CHUN KANG WU CHUN CHIEH SU CHIA LI		
发明人	HUANG, CHUN-KANG WU, CHUN-CHIEH SU, CHIA-LI		
IPC分类号	G02F1/1333		
CPC分类号	G02F2202/22 G02F1/13452		
优先权	097122411 2008-06-16 TW		
其他公开文献	US8018543		
外部链接	Espacenet USPTO		

摘要(译)

提供一种液晶显示 (LCD) 面板，包括第一基板，第二基板，液晶层，密封剂和静电保护结构。第一基板和第二基板平行设置。密封剂用于密封第一基板和第二基板之间的液晶层。静电防护结构设置在密封剂外部的非显示区域内。静电保护结构包括第一线，第一线设置在第一基板上并围绕第一基板的边缘。

