



US007034905B2

(12) **United States Patent**  
**Sah et al.**

(10) **Patent No.:** **US 7,034,905 B2**  
(45) **Date of Patent:** **Apr. 25, 2006**

(54) **LIQUID CRYSTAL DISPLAY PANEL HAVING  
A REPAIR LINE POSITIONED ONLY  
UNDERNEATH THE SECOND PORTION OF  
THE NON-DISPLAY AREA**

(75) Inventors: **Wen-Jyh Sah**, Tai-Nan Hsien (TW);  
**Chin-Cheng Chien**, Tai-Nan Hsien  
(TW)

(73) Assignee: **Chi Mei Optoelectronics Corporation**,  
Tainan (TW)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 16 days.

(21) Appl. No.: **10/463,553**

(22) Filed: **Jun. 18, 2003**

(65) **Prior Publication Data**  
US 2004/0070700 A1 Apr. 15, 2004

(30) **Foreign Application Priority Data**  
Oct. 9, 2002 (TW) ..... 91123367 A

(51) **Int. Cl.**  
**G02F 1/1333** (2006.01)

(52) **U.S. Cl.** ..... **349/54; 349/42; 349/139;**  
349/149; 349/152

(58) **Field of Classification Search** ..... 349/54,  
349/11, 42, 139, 110, 111, 149-152  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,600,460 A \* 2/1997 Yamamoto et al. .... 349/54  
6,639,634 B1 \* 10/2003 Zhang et al. .... 349/54

\* cited by examiner

*Primary Examiner*—Andrew Schechter


*Assistant Examiner*—George Y. Wang

(74) *Attorney, Agent, or Firm*—Winston Hsu

(57) **ABSTRACT**

A liquid crystal display panel is provided. The LCD panel has a first substrate having at least a conductive material layer thereon, a second substrate having at least a repair line positioned in a predetermined area, and a liquid crystal layer positioned between the first substrate and the second substrate. The predetermined area is underneath the first substrate excluding the portions having the conductive material layer, thus reducing RC delay of the repair line.

**16 Claims, 4 Drawing Sheets**






Fig. 1 Prior art




Fig. 2 Prior art




Fig. 3




Fig. 4

1

# LIQUID CRYSTAL DISPLAY PANEL HAVING A REPAIR LINE POSITIONED ONLY UNDERNEATH THE SECOND PORTION OF THE NON-DISPLAY AREA

## BACKGROUND OF INVENTION

### 1. Field of the Invention

The invention relates to a liquid crystal display (LCD) panel, and more particularly, to an LCD panel with at least 10 a repair line structure.

### 2. Description of the Prior Art

A traditional LCD panel comprises a thin-film transistor (TFT) substrate, a color filter (CF) substrate, and a liquid crystal layer positioned between the TFT substrate and the CF substrate. The TFT substrate contains a plurality of matrix pixels, which consist of a plurality of datalines and a plurality of scan lines, and a plurality of pixel driving circuits consisting of a plurality of electric components, such as thin-film transistors and capacitors. The pixel driving circuits are positioned on the intersections of each data line and each scan line for receiving an image data signal transmitted by the data line and a switching/addressing signal transmitted by the scan line to control operation of each pixel. For avoiding disconnection of data lines or scan lines which cause the failure of signal transmission, the method according to the prior art is to set a plurality of repair lines in the area around the LCD panel. Thus external image data signals or switching/addressing signals are capable of passing through the repair lines to control operation of pixels, and this will avoid the defects of the LCD panel caused by disconnecting data lines.

Please refer to FIG. 1, which is a structure of a prior-art LCD panel 10. As shown in FIG. 1, an LCD panel 10 contains a display area 12 and a non-display area 14 surrounding the display area 12. The display area 12 contains a plurality of matrix pixels 16, which consist of a plurality of data lines 20 and a plurality of scan lines 30, and a plurality of pixel driving circuits consisting of a plurality of electric components, such as thin-film transistors and capacitors. The pixel driving circuits are positioned on the intersections of each data line 20 and each scan line 30. The non-display area 14 contains some package testing materials, such as main sealants, electric components, and repair lines.

Please refer to FIG. 2, which is a section view of the prior-art LCD panel 10. As shown in FIG. 2, the prior-art LCD panel 10 contains a lower substrate (often called a TFT substrate) 40, an upper substrate (often called a CF substrate) 46 covering the lower substrate 40, a liquid crystal layer (not shown in FIG. 2) positioned between the lower substrate 40 and the upper substrate 46 in the display area 12, and a main sealant 52 positioned between the lower substrate 40 and the upper substrate 46 in the non-display area 14 for binding the two substrates. On the lower substrate 40 are a plurality of repair lines 42 in the non-display area 14 and a passivation layer 44, such as a silicon nitride layer, covers on the display area 12 and the non-display area 14. On the surface of the upper substrate 46 are a black matrix 48 in the non-display area 14 and a conductive material layer 50, such as an indium tin oxide (ITO) layer, in both display area 12 and non-display area 14 for being a transparent electrode.

In the structure of the prior-art LCD panel, the conductive material layer 50 completely covers the surface of the upper substrate 46, including the display area 12 and the non-display area 14, and therefore the conductive material layer

2

50 in the non-display area 14, the repair lines 42 underneath the conductive material layer 50, and the liquid crystal will form a capacitance. The formation of the capacitance causes an RC delay effect to the repair line, and the RC delay decreases the successful rate of using a repair line to repair a disconnecting wire. As the large size LCD panels are developed, to efficiently decrease the RC delay on the repair lines has become an important issue for increasing the yield of the production.

## SUMMARY OF INVENTION

It is therefore an objective of the present invention to provide an LCD panel that can decrease the RC delay of the repair lines and increase the successful rate of utility of the repair lines.

According to the claimed invention, the LCD panel contains a first substrate having at least a conductive material layer thereon, a second substrate having at least a repair line thereon, and a liquid crystal layer positioned between the first substrate and the second substrate. The repair line is positioned in a predetermined area underneath the first substrate excluding portions having the conductive material layer, and the repair line repairs a disconnecting line on the second substrate so that an external signal, which is predetermined to transmit to the line, is capable of passing through the repair line to the line.

It is an advantage of the claimed invention that the repair line of the LCD panel is positioned in the area underneath the first substrate excluding portions having the conductive material layer so that it avoids the liquid crystal to form the capacitances between the repair line and the conductive material layer, which decreases the RC delay on the repair line and further increase the successful rate of utility of the repair line and the yield of the LCD panel.

These and other objectives of the present invention will no doubt become obvious to those of ordinary skill in the art after reading the following detailed description of the preferred embodiment that is illustrated in the various figures and the drawings.

## BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a structure of a prior-art LCD panel.

FIG. 2 is a section view of the prior-art LCD panel shown in FIG. 1.

FIG. 3 is a section view of an LCD panel according to a first preferred embodiment of the present invention.

FIG. 4 is a section view of an LCD panel according to a second preferred embodiment of the present invention.

## DETAILED DESCRIPTION

Please refer to FIG. 3. FIG. 3 is a section view of an LCD panel according to the first preferred embodiment of the present invention. The LCD panel of the present invention contains a lower substrate (often called a TFT substrate) 60, an upper substrate (often called a CF substrate) 66 covering the lower substrate 60, a liquid crystal layer (not shown in FIG. 3) positioned between the lower substrate 60 and the upper substrate 66 in a display area 12, and a main sealant 72 positioned between the lower substrate 60 and the upper substrate 66 in a non-display area 14 for binding the two substrates.

On the lower substrate 60 are formed a plurality of matrix pixels, which consist of a plurality of data lines and a plurality of scan lines, in the display area 12, and a plurality

of pixel driving circuits positioned on the intersections of each data line and each scan line for controlling the operation of pixels of the LCD panel. The pixel driving circuits consist of a plurality of electric components, such as thin-film transistors and capacitances. In addition, the lower substrate **60** further comprises a plurality of repair lines **62** in the non-display area **14**, and the repair lines **62** enclose the TFT pixels in the display area **12** for repairing a disconnecting line, such as a data line, on the lower substrate **60** to transmit an external signal passing through the repair lines **62** to the corresponding pixels. A passivation layer **64**, such as a silicon nitride layer, covers the pixel driving circuits and repair lines **62**.

The surface of the upper substrate **66** has a black matrix **68** in the non-display area **14** and a conductive material layer **70** covering the display area **12** and portions of the non-display area **14**. The black matrix **68** is an opaque layer made by an insulating material. The conductive material layer **70** serves as a transparent electrode, which is formed by a transparent conductive material, such as ITO. It should be noted that the conductive material layer **70** should not be positioned in an area over portions of the lower substrate **60** where the repair lines **62** are. For the reason of avoiding liquid crystal capacitances, as well as the RC delay, formed by the conductive material layer **70** and the repair lines **62**, one can use a shadow mask or a photolithography process to define at least a pattern of the conductive material in the area on the surface of the upper substrate **66** excluding portions right over the repair lines **62**. A main sealant **72** is positioned outside of the repair lines **62** or covers some repair lines **62**.

Please refer to FIG. 4, which is a section view of an LCD panel according to the second preferred embodiment of the present invention. As shown in FIG. 4, the LCD panel of the present invention contains a lower substrate (often called a TFT substrate) **80**, an upper substrate (often called a CF substrate) **86** covering the lower substrate **80**, a liquid crystal layer (not shown in FIG. 4) positioned in a display area **12** between the lower substrate **80** and the upper substrate **86**, and a main sealant **92** positioned in a non-display area **14** between the lower substrate **80** and the upper substrate **86** for binding the two substrates.

On the lower substrate **80** are formed matrix pixels, which consist of a plurality of data lines and a plurality of scan lines, in the display area **12** and a plurality of pixel drivers positioned on the intersections of each data line and each scan line for controlling operation of pixels of the LCD panel, wherein the pixel drivers consist of a plurality of electric components, such as thin-film transistors and capacitances. In addition, the lower substrate **80** further comprises a plurality of repair lines **82** in the non-display area **14**, and the repair lines **82** surround the TFT pixels in the display area **12** for repairing a disconnecting line, such as a data line, on the lower substrate **80** to transmit an external signal passing through the repair lines **82** to corresponding pixels. A passivation layer **84**, such as a silicon nitride layer, covers the pixel driving circuits and repair lines **82**.

The surface of the upper substrate **86** has a black matrix **88** in the non-display area **14** and a conductive material layer **90** covering the display area **12** and portions of the non-display area **14**. The black matrix **88** is an opaque layer and made by an insulating material or a conductive material, such as chromium,  $\text{Cr}_2\text{O}_3$ , or CrN. The conductive material layer **90** serves as a transparent electrode and made by transparent conductive materials, for example by ITO. The conductive material layer **90** should not be positioned in an

area over portions of the lower substrate **80** where the repair lines **82** are. For the reason of avoiding the formation of the liquid crystal capacitances, formed by the black matrix **88**, the conductive material layer **90**, and the repair lines **82**, and of the RC delay on the repair lines, one can use a shadow mask or a photolithography process to define at least a pattern of the conductive material in the area on the surface of the upper substrate **86** excluding portions right over the repair lines **82**. A main sealant **92** is positioned in the non-display area **14**, for example outside of the black matrix **88**, and covers the surface of the lower substrate **80** outside of the repair lines **82** or covers some repair lines **82**.

For saving the lead time of injecting liquid crystal when fabricating large size LCD panels, currently the liquid crystal layer is filled between the upper substrate and lower substrate by the way of One Drop Filling (ODF), and a main sealant UV exposure area is set on the edge of the upper and lower substrate in advance. Then ultraviolet light is used to solidify the main sealant, which is positioned in the main sealant UV exposure area, for binding and fixing the two substrates. In the second preferred embodiment of the present invention, the black matrix **88** avoids the area right over the repair line **82** so that the main sealant **92** and repair lines **82** are set in a transparent area. More specifically, the fabrication of the LCD panel of the present invention is capable of applying to ODF method, setting the black matrix and the transparent electrode on the surface of the upper substrate outside of the main sealant transparent area, and positioning repair lines on the lower substrate in the main sealant transparent area. As a result, the conductive materials, such as the black matrix and the transparent electrode, are not positioned above the repair lines so that the RC delay caused by the formation of liquid crystal capacitances, formed between the conductive materials and repair lines, can be avoided effectively.

In contrast to the prior art, the present invention LCD panel provides a pattern of the conductive materials, such as the black matrix and the transparent electrode, on the surface of the upper substrate avoiding portions right over repair lines. Thus the liquid crystal capacitances between the repair lines and the conductive material patterns will be avoided, and it will avoid the RC delay interfering with the signals transmitted by repair lines. Furthermore, the present invention improves the successful rate of the utility of repair lines and the yield of the LCD panel.

Those skilled in the art will readily observe that numerous modifications and alterations of the device may be made while retaining the teachings of the invention. Accordingly, the above disclosure should be construed as limited only by the mate and bounds of the appended claims.

What is claimed is:

1. An LCD panel comprising:

- a first substrate comprising a display area and a non-display area including a first portion and a second portion;
- at least a conductive material pattern positioned in the display area and only in the first portion, excluding the second portion, of the non-display area of the first substrate;
- a second substrate having at least a repair line thereon, positioned in a predetermined area underneath the second portion of the non-display area of the first substrate, wherein the repair line repairs a disconnecting wire on the second substrate so that an external signal, which is predetermined to transmit to the wire, is capable of passing through the repair line to the wire,

5

the repair line being positioned only underneath the second portion of the non-display area; and  
a liquid crystal layer positioned between the first substrate and the second substrate.

2. The LCD panel of claim 1 wherein the first substrate is a CF substrate. 5

3. The LCD panel of claim 1 wherein the conductive material pattern is a transparent electrode.

4. The LCD panel of claim 3 wherein the conductive material pattern is defined by a shadow mask.

5. The LCD panel of claim 3 wherein the conductive material pattern is defined by a photolithography process.

6. The LCD panel of claim 1 wherein the first substrate further comprises a black matrix positioned in the first portion of the non-display area.

7. The LCD panel of claim 1 wherein the first substrate further comprises a main sealant positioned in the second portion of the non-display area for binding the first substrate and the second substrate.

8. The LCD panel of claim 7 wherein the main sealant covers the repair line. 20

6

9. The LCD panel of claim 7 wherein the main sealant covers a surface of the second substrate adjacent to the repair line.

10. The LCD panel of claim 1 wherein the second substrate is a TFT substrate.

11. The LCD panel of claim 1 wherein the second substrate has a plurality of thin-film transistors thereon for controlling operation of the pixels of the LCD panel.

12. The LCD panel of claim 11 wherein the predetermined area encloses the thin-film transistors. 10

13. The LCD panel of claim 1 wherein the line is a data line, and the external signal is a data signal.

14. The LCD panel of claim 1 wherein the liquid crystal layer is filled between the first substrate and the second substrate by the way of ODF (One Drop Filling). 15

15. The LCD panel of claim 6 wherein the conductive material pattern covers at least a portion of the black matrix.

16. The LCD panel of claim 9 wherein the repair line is positioned between the main sealant and the display area.

\* \* \* \* \*

|                |                                                                            |         |            |
|----------------|----------------------------------------------------------------------------|---------|------------|
| 专利名称(译)        | 液晶显示面板具有仅位于非显示区域的第二部分下方的修复线                                                |         |            |
| 公开(公告)号        | <a href="#">US7034905</a>                                                  | 公开(公告)日 | 2006-04-25 |
| 申请号            | US10/463553                                                                | 申请日     | 2003-06-18 |
| [标]申请(专利权)人(译) | SAH文JYH<br>简锦成                                                             |         |            |
| 申请(专利权)人(译)    | 看到文志<br>简锦诚                                                                |         |            |
| 当前申请(专利权)人(译)  | 奇美电子股份有限公司                                                                 |         |            |
| [标]发明人         | SAH WEN JYH<br>CHIEN CHIN CHENG                                            |         |            |
| 发明人            | SAH, WEN-JYH<br>CHIEN, CHIN-CHENG                                          |         |            |
| IPC分类号         | G02F1/1333 G02F1/1339 G02F1/13 G02F1/1335 G02F1/1343 G02F1/1362 G02F1/1368 |         |            |
| CPC分类号         | G02F1/1309 G02F2001/136272                                                 |         |            |
| 代理机构(译)        | HSU , WINSTON                                                              |         |            |
| 助理审查员(译)       | 王 , GEORGE Y.                                                              |         |            |
| 优先权            | 091123367 2002-10-09 TW                                                    |         |            |
| 其他公开文献         | US20040070700A1                                                            |         |            |
| 外部链接           | <a href="#">Espacenet</a> <a href="#">USPTO</a>                            |         |            |

#### 摘要(译)

提供一种液晶显示面板。LCD面板具有：第一基板，其上至少具有导电材料层；第二基板，至少具有位于预定区域中的修复线；以及液晶层，位于第一基板和第二基板之间。除了具有导电材料层的部分之外，预定区域位于第一基板下方，因此减少了修复线的RC延迟。

