



US007872622B2

(12) **United States Patent**
Kim

(10) **Patent No.:** **US 7,872,622 B2**
(45) **Date of Patent:** **Jan. 18, 2011**

- (54) **LIQUID CRYSTAL DISPLAY**
- (75) Inventor: **Dong-kyu Kim, Yongin-si (KR)**
- (73) Assignee: **Samsung Electronics Co., Ltd., Suwon Si (KR)**
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1267 days.

2004/0070713	A1 *	4/2004	Song	349/129
2004/0233343	A1 *	11/2004	Baek	349/38
2004/0257519	A1 *	12/2004	Jun et al.	349/155
2005/0140908	A1 *	6/2005	Song	349/146
2006/0146241	A1 *	7/2006	Choi et al.	349/129

FOREIGN PATENT DOCUMENTS

WO WO2004010212 1/2001

* cited by examiner

Primary Examiner—Sumati Lefkowitz

Assistant Examiner—Charles Hicks

(74) *Attorney, Agent, or Firm*—F. Chau & Associates, LLC

(21) Appl. No.: **11/444,185**

(22) Filed: **May 31, 2006**

(65) **Prior Publication Data**
US 2007/0018927 A1 Jan. 25, 2007

(30) **Foreign Application Priority Data**
Jul. 20, 2005 (KR) 10-2005-0066014

(51) **Int. Cl.**
G09G 3/36 (2006.01)
G02F 1/1343 (2006.01)
G02F 1/1337 (2006.01)

(52) **U.S. Cl.** **345/87; 345/92; 349/38; 349/125; 349/129; 349/130**

(58) **Field of Classification Search** **345/55, 345/84, 87, 90, 92; 349/129, 155, 108, 144, 349/146**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,331,845	B1 *	12/2001	Kitajima et al.	345/88
7,119,870	B1 *	10/2006	Nishikawa et al.	349/125

(57) **ABSTRACT**

A liquid crystal display (LCD) which can provide uniform vertical and horizontal visibility while improving lateral visibility is provided. The LCD includes a first insulating substrate, first and second gate lines which are formed on the first insulating substrate, and a data line which is insulated from the first and second gate lines and intersects the first and second gate lines. The LCD also includes first and second thin film transistors (TFTs) which are formed in each pixel and are connected to the first and second gate lines, respectively, and to the data line, first sub-pixel electrodes which are connected to the first TFT, and a second sub-pixel electrode which is separated from the first sub-pixel electrodes by predetermined gaps and is connected to the second TFT. The LCD includes a second insulating substrate which faces the first insulating substrate, a common electrode which is formed on the second insulating substrate and comprises a plurality of domain dividers, and a liquid crystal layer which is interposed between the first and second insulating substrates, wherein a display region of the second sub-pixel electrode is divided into 4 domain groups by the domain dividers, and the 4 domain groups have substantially the same area.

16 Claims, 11 Drawing Sheets




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5




FIG. 6A




FIG. 6B





FIG. 7



LIQUID CRYSTAL DISPLAY**CROSS-REFERENCE TO RELATED APPLICATION**

This application claims priority from Korean Patent Application No. 10-2005-0066014 filed on Jul. 20, 2005 in the Korean Intellectual Property Office, the disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION**1. Technical Field**

The present disclosure relates to a display device, and more particularly, to a liquid crystal display (LCD).

2. Discussion of the Related Art

A liquid crystal display (LCD) is one of the most widely used flat panel displays. An LCD includes two panels provided with field-generating electrodes such as pixel electrodes and a common electrode and a liquid crystal (LC) layer interposed therebetween. The LCD displays images by applying voltages to the field-generating electrodes to generate an electric field in the LC layer, which determines orientations of LC molecules in the LC layer to adjust polarization of incident light.

Among the LCDs, a vertical alignment (VA) mode LCD, which aligns LC molecules such that the long axes of the LC molecules are perpendicular to the panels in the absence of an electric field, exhibits a high contrast ratio and wide reference viewing angle. The reference viewing angle is defined as a viewing angle resulting in a contrast ratio equal to 1:10 or as a limit angle for the inversion in luminance between the grays.

The wide viewing angle of the VA mode LCD can be realized through the use of cutouts in the field-generating electrodes and/or protrusions on the field-generating electrodes. Since the cutouts and the protrusions influence the tilt directions of the LC molecules, the tilt directions can be distributed into several directions by using the cutouts and the protrusions such that the reference viewing angle is widened.

However, the VA mode LCD has relatively poor lateral visibility compared with front visibility. For example, a patterned VA (PVA) mode LCD having the cutouts can result in an image that becomes bright as a viewer moves away from the front vantage point, and in the worse case, the luminance difference between high grays vanishes such that the images cannot be perceived.

In addition, in LCDs, a pixel region is divided into a plurality of domains by cutouts or protrusions formed in or on a pixel electrode and a common electrode. However, the domains are likely to have different areas, and thus, it is difficult to provide uniform vertical and horizontal visibility.

SUMMARY OF THE INVENTION

Embodiments of the present invention provide an LCD which can provide uniform vertical and horizontal visibility while improving lateral visibility.

According to an embodiment of the present invention, there is provided a liquid crystal display (LCD) including a first insulating substrate, first and second gate lines which are formed on the first insulating substrate, a data line which is insulated from the first and second gate lines and intersects the first and second gate lines, first and second thin film transistors (TFTs) which are formed in each pixel and are connected to the first and second gate lines, respectively, and to the data line, first sub-pixel electrodes which are connected to the first TFT, a second sub-pixel electrode which is sepa-

rated from the first sub-pixel electrodes by predetermined gaps and is connected to the second TFT, a second insulating substrate which faces the first insulating substrate, a common electrode which is formed on the second insulating substrate and comprises a plurality of domain dividers, and a liquid crystal layer which is interposed between the first and second insulating substrates, wherein a display region of the second sub-pixel electrode is divided into 4 domain groups by the domain dividers, and the 4 domain groups have substantially the same area.

According to another embodiment of the present invention, a liquid crystal display (LCD) device comprises a first substrate, a first gate line and a second gate line formed on the first substrate, a data line intersecting the first and second gate lines, a first thin film transistor and a second thin film transistor formed in each pixel of a plurality of pixels and connected to the first and second gate lines, respectively, and to the data line, a first sub-pixel electrode connected to the first thin film transistor, a second sub-pixel electrode separated from the first sub-pixel electrode by a predetermined gap and connected to the second thin film transistor, a second substrate facing the first substrate, and a common electrode formed on the second substrate and comprising a plurality of domain dividers, wherein a display region of the second sub-pixel electrode is divided into a plurality of domain groups according to a shape of the second sub-pixel electrode and the domain dividers, and each of the plurality of domain groups have substantially the same area.

BRIEF DESCRIPTION OF THE DRAWINGS

Exemplary embodiments of the invention can be understood in more detail from the following descriptions taken in conjunction with the accompanying drawings in which:

FIGS. 1A through 1C are block diagrams of an LCD according to an exemplary embodiment of the present invention;

FIG. 2 is an equivalent circuit diagram of a pixel of an LCD according to an exemplary embodiment of the present invention;

FIG. 3 is an equivalent circuit diagram of a sub-pixel of an LCD according to an exemplary embodiment of the present invention;

FIG. 4A is a layout view of a lower display panel of an LCD according to an exemplary embodiment of the present invention;

FIG. 4B is a layout view of an upper display panel of an LCD according to an exemplary embodiment of the present invention;

FIG. 4C is a layout view of an LCD including the display panel of FIG. 4A and the display panel of FIG. 4B according to an exemplary embodiment of the present invention;

FIG. 5 is an enlarged layout view of a sub-pixel electrode of FIG. 4C;

FIG. 6A is a layout view of a lower display panel of an LCD according to another exemplary embodiment of the present invention;

FIG. 6B is a layout view of an LCD including an upper display panel and the display panel of FIG. 6A according to another exemplary embodiment of the present invention; and

FIG. 7 is an enlarged layout view of a sub-pixel electrode of FIG. 6B.

DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

Exemplary embodiments of the present invention will be described below in more detail with reference to the accom-

panying drawings. The present invention may, however, be embodied in many different forms and should not be construed as being limited to the embodiments set forth herein.

FIGS. 1A through 1C are block diagrams of an LCD according to an exemplary embodiment of the present invention. FIG. 2 is an equivalent circuit diagram of a pixel of an LCD according to an exemplary embodiment of the present invention. FIG. 3 is an equivalent circuit diagram of a sub-pixel of an LCD according to an exemplary embodiment of the present invention.

Referring to FIGS. 1A through 1C, an LCD according to an exemplary embodiment of the present invention includes a liquid crystal panel assembly 300, a data driving unit 500 and a gate driving unit 400 (or a pair of gate driving units 400a and 400b) which are connected to the liquid crystal panel assembly 300. A gray-scale voltage generation unit 800 is connected to the data driving unit 500. A signal control unit 600 controls the gate driving unit 400 (or the gate driving units 400a and 400b) and the data driving unit 500.

The liquid crystal panel assembly 300 includes a plurality of display signal lines and a plurality of pixels PX which are connected to the display signal lines and are arranged in a matrix format. Referring to FIG. 3, the liquid crystal panel assembly 300 may include a lower display panel 100 and an upper display panel 200 which face each other and a liquid crystal layer 3 which is interposed between the lower and upper display panels 100 and 200.

The display signal lines are formed on the lower display panel 100 and include a plurality of gate lines G_{1a} through G_{na} and G_{1b} through G_{nb} , which transmit gate signals, and a plurality of data signals D_1 through D_m which transmit data signals. The gate lines G_{1a} through G_{na} and G_{1b} through G_{nb} substantially extend in a transverse direction and are parallel to one another, while the data lines D_1 through D_m substantially extend in a longitudinal direction and are parallel to one another.

FIG. 2 is an equivalent circuit diagram of a pixel PX of an LCD according to an exemplary embodiment of the present invention including gate lines GLa and GLb, a data line DL, and a storage electrode line SL, which is substantially parallel to the gate lines GLa and GLb.

Referring to FIG. 2, the pixel PX comprises a pair of sub-pixels PXa and PXb. The sub-pixels PXa and PXb include switching devices Qa and Qb, respectively, liquid crystal capacitors Clca and Clcb, respectively, and storage capacitors Csta and Cstb, respectively. The switching devices Qa and Qb are connected to the gate lines GLa and GLb, respectively, and are connected to the data line DL. The liquid crystal capacitors Clca and Clcb are connected to the switching devices Qa and Qb, respectively. The storage capacitors Csta and Cstb are connected to the switching devices Qa and Qb, respectively, and are connected to the storage electrode line SL. The pixel PX may optionally include the storage capacitors Csta and Cstb. If the pixel PX does not include the storage capacitors Csta and Cstb, the storage electrode line SL can be omitted.

Referring to FIG. 3, a switching device Q of a sub-pixel PE includes a thin film transistor (TFT) formed on the lower display panel 100 and is a three-end portion device including a control end portion connected to a gate line GL, an input end portion connected to a data line DL, and an output end portion connected to a liquid crystal capacitor C_{lc} and a storage capacitor C_{st} .

The sub-pixel electrode PE of the lower display panel 100 and a common electrode CE of an upper display panel 200 function as two terminals of the liquid crystal capacitor C_{lc} , and the liquid crystal layer 3 interposed between the sub-pixel

electrode PE and the common electrode CE serves as a dielectric material. The sub-pixel electrode PE is connected to the switching device Q. The common electrode CE is formed on a surface of the upper display panel 200, for example, a front surface, and a common voltage V_{com} is applied to the common electrode CE. The common electrode CE may be formed on the lower display panel 100, in which case, the sub-pixel electrode PE or the common electrode CE may be shaped as a line or a strip.

The storage capacitor C_{st} is an auxiliary capacitor for the LC capacitor C_{lc} . The storage capacitor C_{st} includes the pixel electrode PE and a separate signal line (not shown), which is provided on the lower panel 100. The separate signal line overlaps the pixel electrode PE via an insulator, and is supplied with a predetermined voltage such as the common voltage V_{com} . Alternatively, the storage capacitor C_{st} includes the pixel electrode PE and an adjacent gate line called a previous gate line, which overlaps the pixel electrode PE via an insulator.

For a color display, each pixel represents one of three primary colors such as red, green and blue (R, G and B) colors (spatial division) or sequentially represents the three primary colors in time (temporal division), so as to obtain a desired color. FIG. 3 shows an example of the spatial division in which each pixel includes a color filter CF representing one of the three primary colors in an area of the upper panel 200. The color filter CF may also be provided on or under the pixel electrode PE of the lower panel 100.

Referring to FIGS. 1A through 1C, the gate driving unit 400 (or the gate driving units 400a and 400b) is connected to the gate lines G_{1a} through G_{na} and G_{1b} through G_{nb} and applies gate signals consisting of a gate-on voltage V_{on} and a gate-off voltage V_{off} applied from an external circuit to the gate lines G_{1a} through G_{na} and G_{1b} through G_{nb} . In detail, referring to FIG. 1A, the gate driving units 400a and 400b are located on the left and right sides, respectively, of the liquid crystal panel assembly 300 and are connected to the odd-numbered gate lines G_{1a} through G_{na} and the even-numbered gate lines G_{1b} through G_{nb} , respectively. Referring to FIGS. 1B and 1C, the gate driving unit 400 is located on one side of the liquid crystal panel assembly 300 and is connected to all of the gate lines G_{1a} through G_{na} and G_{1b} through G_{nb} . Referring to FIG. 1C, the gate driving unit 400 includes two driving circuits 401 and 402 which are connected to the odd-numbered gate lines and the even-numbered gate lines, respectively.

The gray-scale voltage generation unit 800 generates two sets of gray-scale voltages (or reference gray-scale voltage sets) which are related to the transparencies of the pixels PX. The two gray-scale voltage sets are independently provided to a pair of sub-pixels of each pixel PX. Each of the two gray-scale voltage sets includes positive polarity level and negative polarity level with respect to the common voltage V_{com} , but the embodiments of the present invention are not restricted thereto. Alternatively, the gray-scale voltage generation unit 800 may generate only one gray-scale voltage set, rather than generating two gray-scale voltage sets.

The data driving unit 500 is connected to the data lines D_1 through D_m of the liquid crystal panel assembly 300, selects one of the two gray-scale voltage sets generated by the gray-scale voltage generation unit 800, and applies one of a plurality of gray-scale voltages included in the selected gray-scale voltage set to the pixels PX as a data voltage. If the gray-scale voltage generation unit 800 provides only a reference gray-scale voltage, instead of providing a set of voltages for all gray scales, the data driving unit 500 generates a

plurality of reference voltages for all gray scales by dividing the reference gray scale and selects one of the reference voltages as a data voltage.

The gate driving unit **400** (or the gate driving units **400a** and **400b**) and/or the data driving unit **500** may be formed as an integrated chip on which a plurality of driving circuits are integrated. The gate driving unit **400** (or the gate driving units **400a** and **400b**) and/or the data driving unit **500** may be directly mounted on the liquid crystal panel assembly **300**. Alternatively, the gate driving unit **400** (or the gate driving units **400a** and **400b**) and/or the data driving unit **500** may be mounted on a flexible printed circuit film (not shown), and then the resulting structure may be mounted on the liquid crystal panel assembly **300** as a tape carrier package. Alternatively, the gate driving unit **400** (or the gate driving units **400a** and **400b**) and/or the data driving unit **500** may be integrated on the liquid crystal panel assembly **300** together with the display signal lines G_{1a} through G_{na} , G_{1b} through G_{nb} and D_1 through D_m and a switching device Q of a TFT.

The signal control unit **600** controls the gate driving unit **400** (or the gate driving units **400a** and **400b**) and the data driving unit **500**.

LCDs according to exemplary embodiments of the present invention will now be described in detail with reference to FIGS. **4A** through **7**.

First, FIGS. **4A** through **4C** and **5** are diagrams illustrating an LCD according to an exemplary embodiment of the present invention. The LCD includes a lower display panel, an upper display panel, which faces the lower display panel, and a liquid crystal layer which is interposed between the lower and upper display panels.

A lower display panel of the LCD according to an exemplary embodiment of the present invention will now be described in detail with reference to FIGS. **4A** through **4C**.

Referring to FIGS. **4A** through **4C**, a pair of gate lines, e.g., first and second gate lines **22a** and **22b**, and a storage electrode line **28**, are formed on an insulating substrate, which is formed of a transparent material, such as glass.

The first and second gate lines **22a** and **22b** extend substantially in a transverse direction to transmit gate signals and are physically and electrically spaced apart from each other. The first and second gate lines **22a** and **22b** are located on opposite sides of a pixel, for example, the upper and lower sides, respectively, of a pixel. A pair of electrodes, e.g., first and second gate electrodes **26a** and **26b**, are formed as branches of the first and second gate lines **22a** and **22b**, respectively. A first gate line end portion **24a** is formed at one end of the first gate line **22a**, and a second gate line end portion **24b** is formed at one end of the second gate line **22b**. The first and second gate line end portions **24a** and **24b** receive gate signals from another layer or from external circuits and transmit the gate signals to the first and second gate lines **22a** and **22b**, respectively. The first and second gate line end portions **24a** and **24b** are formed wider than the first and second gate lines **22a** and **22b** so as to effectively connect the first and second gate lines **22a** and **22b** to external circuits. The first and second gate line end portions **24a** and **24b** are located on the left and right sides, respectively, of a pixel region, as illustrated in FIG. **4A**. Alternatively, for example, the first and second gate line end portions **24a** and **24b** may be all located on one side of a pixel region, for example, on either the left or right sides of the pixel region.

As shown in FIGS. **4A** and **4C**, the storage electrode line **28** extends along a horizontal direction. A storage electrode **29** is formed on the storage electrode line **28** and is wider than the storage electrode line **28**. In the present embodiment, the storage electrode line **28** crosses the middle of the pixel

region. The shapes and arrangement of the storage electrode line **28** and the storage electrode **29** may vary.

The first and second gate lines **22a** and **22b** and the storage electrode line **28** are preferably made of Al containing metal such as Al and Al alloy, Ag containing metal such as Ag and Ag alloy, Cu containing metal such as Cu and Cu alloy, Mo containing metal such as Mo and Mo alloy, Cr, Ti and/or Ta. In addition, the first and second gate lines **22a** and **22b** and the storage electrode line **28** may have a multi-layered structure including two conductive films (not shown) having different physical characteristics. One of the two conductive films is preferably made of a low resistivity metal including Al containing metal, Ag containing metal, and/or Cu containing metal for reducing signal delay or voltage drop in the first and second gate lines **22a** and **22b** and the storage electrode line **28**. The other conductive film is preferably made of material such as a Mo containing metal, Cr, Ta and/or Ti, which have good physical, chemical, and electrical contact characteristics with other materials such as indium tin oxide (ITO) or indium zinc oxide (IZO). A good exemplary combination is a lower Cr film and an upper Al film or a lower Al film and an upper Mo film. However, the first and second gate lines **22a** and **22b** and the storage electrode line **28** may be made of various metals or conductors.

A gate insulation layer (not shown) formed of, for example, silicon nitride (SiN_x), is formed on the first and second gate lines **22a** and **22b** and the storage electrode line **28**.

Semiconductor layers **40a** and **40b** formed of, for example, hydrogenated amorphous silicon or porous silicon, are formed on the gate insulation layer. The semiconductor layers **40a** and **40b** may have various shapes such as island shapes or line shapes. In an illustrative embodiment, for example, the semiconductor layers **40a** and **40b** may be formed in an island shape. When the semiconductor layers **40a** and **40b** are formed in a line shape, they may be disposed under the data line **62** and extended.

An ohmic contact layer (not shown) formed of, for example, silicide or n+hydrogenated amorphous silicon doped with a high concentration of n-type impurities, is formed on the semiconductor layers **40a** and **40b**. Ohmic contacts are provided on the semiconductor layers **40a** and **40b** in pairs.

The data line **62** and first and second drain electrodes **66a** and **66b** are formed on the ohmic contact layer and the gate insulation layer.

The data line **62** extends substantially along a longitudinal direction, intersects the first and second gate lines **22a** and **22b** and the storage electrode line **28**, and transmits a data voltage. First and second source electrodes **65a** and **65b** are formed on the data line **62** and extend toward the first and second drain electrodes **66a** and **66b**, respectively. In addition, a data line end portion **68** is formed at one end of the data line **62**. The data line end portion **68** receives a data signal from another layer or an external source and transmits the data signal to the data line **62**. The data line end portion **68** is formed wider than the data line **62** so as to effectively connect the data line **62** to an external circuit.

The data line **62**, the first and second source electrodes **65a** and **65b** and the first and second drain electrodes **66a** and **66b** are preferably made of refractory metal such as Cr, a metal containing Mo, Ta, and/or Ti. Also, the data line **62**, the first and second source electrodes **65a** and **65b** and the first and second drain electrodes **66a** and **66b** may have a multilayered structure including a lower refractory metal film and a low-resistivity upper film (not shown). Examples of the multi-layered structure include a double-layered structure having an upper Cr film and an upper Al film or a lower Al film and

an upper Mo film, and a triple-layered structure having a lower Mo film, an intermediate Al film, and an upper Mo film.

The first and second source electrodes **65a** and **65b** at least partially overlap the semiconductor layers **40a** and **40b**, respectively. The first and second drain electrodes **66a** and **66b** are opposite to and face the first and second source electrodes **65a** and **65b**, with respect to the gate electrodes **26a** and **26b**, respectively, and at least partially overlap with the semiconductor layers **40a** and **40b**, respectively. The ohmic contacts are interposed between the underlying semiconductor layers **40a**, **40b** and the overlying first and second source electrodes **65a**, **65b** and first and second drain electrodes **66a**, **66b** to reduce the contact resistance between semiconductor layers and the source and drain electrodes.

The first and second drain electrodes **66a** and **66b** include strip-type end portions overlapping with the semiconductor layers **40a** and **40b**. Drain electrode extensions **67a** and **67b** extend from the strip-type end portions, are wider than the strip-type end portions, and overlap the storage electrode **29**.

Each of the first and second source electrodes **65a** and **65b** are separated into two branches and surround the strip-type end portions of the first and second drain electrodes **66a** and **66b**, respectively.

A passivation layer (not shown) is formed on the data line **62**, the first and second drain electrodes **66a** and **66b**, and exposed portions of the semiconductor layers **40a** and **40b**. The passivation layer is preferably made of an inorganic insulator such as silicon nitride or silicon oxide, a flat photosensitive organic material, or a low dielectric insulating material such as a-Si:C:O and a-Si:O:F formed by plasma enhanced chemical vapor deposition (PECVD). In addition, the passivation layer may be formed as a double layer including a lower inorganic layer and an upper organic layer so as to provide organic layer characteristics and effectively protect the exposed portions of the semiconductor layers **40a** and **40b**.

Contact holes **78**, **76a**, and **76b** are formed through the passivation layer so that the data line end portion **68** and the drain electrode extensions **67a** and **67b** can be exposed through the contact holes **78**, **76a**, and **76b**, respectively. Contact holes **74a** and **74b** are formed through the passivation layer and the gate insulation layer so that the first and second gate line end portions **24a** and **24b** can be exposed through the contact holes **74a** and **74b**, respectively. First and second sub-pixel electrodes **82a** and **82b** are formed to be electrically connected to the first and second drain electrodes **66a** and **66b**, respectively, through the contact holes **76a** and **76b**, respectively. Auxiliary gate line end portions **86a** and **86b** and an auxiliary data line end portion **88** are formed on the passivation layer and are connected to the first and second gate line end portions **24a** and **24b** and the data line end portion **68**, respectively, through the contact holes **74a**, **74b**, and **78**, respectively. The first and second sub-pixel electrodes **82a** and **82b** and the auxiliary gate and data line end portions **86a**, **86b**, **88** are preferably made of a transparent conductor such as ITO or IZO and/or a reflective conductor such as Al.

The first and second sub-pixel electrodes **82a**, **82b** are physically and electrically connected to the first and second drain electrodes **66a**, **66b** through the contact holes **76a**, **76b** such that the first and second sub-pixel electrodes **82a**, **82b** receive the data voltages from the first and second drain electrodes **66a**, **66b**.

Electric fields are generated between the first and second sub-pixel electrodes **82a**, **82b** supplied with the data voltages and the common electrode of the upper display panel. The electric fields influence an orientation of liquid crystal mol-

ecules in the LC layer between the first and second sub-pixel electrodes **82a**, **82b** and the common electrode.

As described above, the first sub-pixel electrode **82a** forms the liquid crystal capacitor Clca with the common electrode CE, and the second sub-pixel electrode **82b** forms the liquid crystal capacitor Clcb with the common electrode CE. Accordingly, even after the switching devices Qa and Qb are turned off, the first and second sub-pixel electrodes **82a** and **82b** can maintain a predetermined voltage level.

In order to enhance storage capacity, the storage capacitor Csta and the liquid crystal capacitor Clca are connected in parallel to each other, and the storage capacitor Cstb and the liquid crystal capacitor Clcb are connected in parallel to each other. The storage capacitors Csta and Cstb are formed by arranging the first and second sub-pixel electrodes **82a** and **82b** or the first and second drain electrodes **66a** and **66b** connected to the first and second sub-pixel electrodes **82a** and **82b**, respectively, to overlap the storage electrode line **28**.

The first and second sub-pixel electrodes **82a** and **82b** are separated from each other by gaps **83**. The gaps **83** may have a rectangular shape. The second sub-pixel electrodes **82b** are V-shaped and are located in the middle of a pixel region. The first sub-pixel electrodes **82a** are formed in portions of the pixel region where the second sub-pixel electrode **82b** is not formed. The gaps **83** include a gap that forms an angle of about 45 degrees with a transmission axis **1** of a polarizing plate and a gap that forms an angle of about -45 degrees with the transmission axis **1** of the polarizing plate. Therefore, upper oblique portions of the second sub-pixel electrode **82b** form an angle of -45 degrees with the transmission axis **1** of the polarizing plate, and lower oblique portions of the second sub-pixel electrode **82b** form an angle of 45 degrees with the transmission axis **1** of the polarizing plate. A plurality of cutouts **84** may be formed in the first sub-pixel electrodes **82a** in the longitudinal directions of the respective gaps **83**. Alternatively to, or in addition to the cutouts **84**, a plurality of protrusions may be formed on the first sub-pixel electrodes **82a** in the longitudinal directions of the respective gaps **83** (hereinafter referred to as oblique directions). The sizes and shapes of the first and second sub-pixel electrodes **82a** and **82b** and the cutouts **84** (or the protrusions) may vary in a variety of manners according to design factors.

Different gray-scale voltages are applied to the first and second sub-pixel electrodes **82a** and **82b**. For example, a gray-scale voltage which is lower than a reference gray-scale voltage may be applied to the first sub-pixel electrodes **82a**, and a gray-scale voltage which is higher than the reference gray-scale voltage may be applied to the second sub-pixel electrode **82b**. Assuming that a ratio of an area of the first sub-pixel electrodes **82a** to an area of the second sub-pixel electrodes **82b** is about 2:1, the lateral visibility of an LCD including the first and second sub-pixel electrodes **82a** and **82b** can be considerably improved by applying different gray-scale voltages to the first and second sub-pixel electrodes **82a** and **82b** in the above-described manner.

The auxiliary gate line end portions **86a** and **86b** and the data line end portion **88** are connected to the first and second gate line end portions **24a** and **24b** and the data line end portion **68**, respectively, through the contact holes **74a**, **74b**, and **78**, respectively. The auxiliary gate line end portions **86a** and **86b** and the data line end portion **88** are used for connecting external devices to the gate line end portions **24a** and **24b** and the data line end portion **68**.

An alignment layer (not shown) for aligning a liquid crystal layer is formed on the first and second sub-pixel electrodes **82a** and **82b**, the auxiliary gate line end portions **86a** and **86b**, and the data line end portion **88**.

An upper display panel of the LCD according to an exemplary embodiment of the present invention will now be described in detail with reference to FIGS. 4B and 4C.

Referring to FIGS. 4B and 4C, a black matrix (not shown), color filters (not shown), e.g., red, green, and blue filters, and a common electrode 90 are formed on an insulating substrate, which is formed of a transparent material, such as glass. The common electrode 90 is formed of a transparent material, such as ITO or IZO. The black matrix corresponds to the first and second gate lines 22a and 22b, the data line 62, and the switching devices Qa and Qb. The black matrix may be formed in various shapes. The black matrix prevents light leakage from occurring near the first and second sub-pixel electrodes 82a and 82b and the switching devices Qa and Qb.

The common electrode 90 corresponds to the first and second sub-pixel electrodes 82a and 82b and includes a plurality of cutouts 92 (and/or a plurality of protrusions). Here, the cutouts 92 (or the protrusions) comprise oblique portions which form an angle of -45 degrees or 45 degrees with the transmission axis 1 of the polarizing plate. As described above, the first and second sub-pixel electrodes 82a and 82b, like the common electrode 90, include the cutouts 84 (or the protrusions).

An alignment layer (not shown) for aligning a liquid crystal layer may be formed on the common electrode 90.

FIG. 4C is a layout view of an LCD including the lower display panel of FIG. 4A and the upper display panel of FIG. 4B. Referring to FIG. 4C, the oblique portions of the cutouts 92 of the common electrode 90 are arranged among the gaps 83 and the cutouts 84 (or the protrusions) of the first sub-pixel electrodes 82a. The relationship between the cutouts 92 of the common electrode 90 and the second sub-pixel electrode 82b will be described in detail with reference to FIG. 5.

An architecture for the LCD according to an exemplary embodiment of the present invention can be formed by vertically aligning the lower display panel of FIG. 4A and the upper display panel of FIG. 4B with each other and coupling them with liquid crystal material interposed therebetween. When the lower display panel of FIG. 4A and the upper display panel of FIG. 4B are vertically aligned with each other, a display region of a pixel is divided into a plurality of domains by the gaps 83, the cutouts 84 of the first sub-pixel electrodes 82a, and the cutouts 92 of the common electrode 90. As a result, a reference viewing angle is widened and lateral visibility is improved. The gaps and the cutouts 94 and 92 (or the protrusions) may be referred to as domain dividers.

The LCD according to an exemplary embodiment of the present invention can include the architecture illustrated in FIG. 4B, and also include other elements, such as a polarizing plate and a backlight assembly. A polarizing plate may be installed on either side of the architecture in such a manner that a first transmission axis is parallel to the gate line 22 and a second transmission axis is perpendicular to the gate line 22.

In the LCD according to an exemplary embodiment of the present invention, a liquid crystal in each of a plurality of domains of a pixel tilts perpendicularly to the gaps 83 or the cutouts 92 when an electric field is applied thereto. Thus, the liquid crystal in each of the domains forms an angle of about 45 degrees or -45 degrees with a transmission axis of a polarizing plate. A lateral electric field formed in each of the gaps 83 or the cutouts 92 facilitates the alignment of liquid crystal molecules in each domain.

A plurality of domains can be divided into, for example, 4 domain groups according to the direction in which a liquid crystal in each of the domains tilts. If the domain groups have the same area, it is possible to provide uniform vertical and horizontal visibility. The display characteristics of an LCD

are determined mainly based on the second sub-pixel electrode 82b to which a voltage higher than a reference gray-scale voltage is applied. Therefore, if 4 domain groups constituting the second sub-pixel electrode 82b have substantially the same area, it is possible to provide uniform vertical and horizontal visibility. An LCD according to an exemplary embodiment of the present invention, which is capable of providing uniform vertical and horizontal visibility, will be described in detail with reference to FIG. 5.

FIG. 5 is an enlarged layout view of a second sub-pixel electrode of FIG. 4C.

Referring to FIG. 5, portions of a second sub-pixel electrode 82b are symmetrical with respect to a storage electrode line 28 which runs across the middle of the second sub-pixel electrode 82b. The second sub-pixel electrode 82b is separated from the first sub-pixel electrodes 82a of FIG. 4C by the gaps 83 of FIG. 4C. The second sub-pixel electrode 82b is V-shaped and is located in the middle of a pixel region. A cutout 92 is formed in a portion of the common electrode corresponding to the second sub-pixel electrode 82b. In other words, as shown in FIG. 5, the cutout 92 overlaps with the second sub-pixel electrode 82b, is V-shaped, and is narrower than the second sub-pixel electrode 82b. Therefore, the second sub-pixel electrode 82b can be divided into 4 domain groups, i.e., A, B, C, and D, by the storage electrode line 28, the gaps 83 and a domain divider, such as the cutout 92.

If the second sub-pixel electrode 82b is formed such that upper and lower oblique portions of the second sub-pixel electrode 82b are symmetrical with respect to the storage electrode line 28, the domain groups A and C may have substantially the same area, and the domain groups B and D may have substantially the same area. The upper oblique portions of the second sub-pixel electrode 82b form an angle of -45 degrees with a transmission axis of a polarizing plate, and the lower oblique portions of the second sub-pixel electrode 82b form an angle of 45 degrees with the transmission axis of the polarizing plate. Thus, in order to result in the domain groups A and B having the same area, the width Wa of the domain group A must be larger than the width Wb of the domain group B. Likewise, in order to result in the domain groups C and D having the same area, the width Wc of the domain group C must be larger than the width Wd of the domain group D. Here, the domain groups A and C of the second sub-pixel electrode 82b are arranged between the cutout 92 of the common electrode and the center of the pixel region. In this manner, the domain groups A, B, C, and D have the same area.

In order to achieve a predetermined response speed when aligning liquid crystal molecules using domain dividers and a lateral field formed along a predetermined direction, the domain group A or C may be formed to have a width of about 28 μm or less.

In addition, the domain group B or D may be formed to have a width of about 14 μm . or larger in consideration of alignment margins for upper and lower display panels.

The operation of the LCD according to an exemplary embodiment of the present invention will now be described in detail with reference to FIGS. 1A through 4C.

Referring to FIGS. 1A through 4C, the signal control unit 600 receives input image signals (R, G, B) and input control signals to control the display of the input image signals. The input control signals include, for example, a vertical synchronization signal Vsync, a horizontal synchronization signal Hsync, a main clock signal MCLK, and a data enable signal DE. The input image signals and the input control signals are received from an external graphic controller (not shown). The signal control unit 600 appropriately processes the input

image signals and the input control signals according to the operating conditions of the liquid crystal panel assembly 300, and generates a gate control signal CONT1 and a data control signal CONT2. The signal control unit 600 transmits the gate control signal CONT1 to the gate driving unit 400 (or the gate driving units 400a and 400b), and transmits the data control signal CONT2 to the data driving unit 500.

The gate control signal CONT1 comprises a scanning initiation signal STV for initiating scanning and at least one clock signal for controlling when to output the gate-on voltage Von. The gate control signal CONT1 may also include an output enable signal OE for defining the duration of the gate-on voltage Von. Here, the clock signal included in the gate control signal CONT1 may be used as a selection signal SE.

The data control signal CONT2 comprises a horizontal synchronization signal STH for informing the data driver 500 of a start of data transmission for a group of pixels, a load signal LOAD for instructing the data driver 500 to apply the data voltages to the data lines D_i through D_m, and a data clock signal HCLK. The data control signal CONT2 may also include an inversion signal RVS for reversing the polarity of the data voltages with respect to the common voltage Vcom.

In response to the data control signal CONT2 transmitted by the signal control unit 600, the data driving unit 500 receives image data DAT for a pair of sub-pixels PXa and PXb, selects a gray-scale voltage for the image data DAT, converts the image data DAT into a data voltage, and applies the data voltage to one of the data lines D_i through D_m corresponding to the sub-pixels PXa and PXb.

The gate driving unit 400 (or the gate driving units 400a and 400b) applies the gate-on voltage Von to one of the gate lines G_{ia} through G_{na} and G_{ib} through G_{nb} corresponding to the sub-pixels PXa and PXb, so that switching devices Qa and Qb connected to the gate line to which the gate-on voltage Von is applied are turned on. Accordingly, the data voltage applied via the data line corresponding to the sub-pixels PXa and PXb is applied to the sub-pixels PXa and PXb via the switching devices Qa and Qb.

A difference between the data voltage applied to the sub-pixels PXa and PXb and the common voltage Vcom is represented as a voltage across the LC capacitor Clca, which is referred to as a pixel voltage. Liquid crystal molecules in the LC capacitor Clca have orientations depending on a magnitude of the pixel voltage, and molecular orientations of the LC molecules determine a polarization of light passing through the LC layer. A polarizer(s) converts light polarization into a light transmittance.

In the LCD according to an exemplary embodiment of the present invention, a gate voltage is transmitted to the sub-pixels PXa and PXb by a pair of gate lines 22a and 22b. A pair of gray-scale voltage sets, which have different gamma curves for the sub-pixels PXa and PXb obtained from a piece of image information, are applied to the sub-pixels PXa and PXb. Thus, a gamma curve for a pixel PX comprising the sub-pixels PXa and PXb can be obtained by synthesizing the gamma curves for the sub-pixels PXa and PXb. It is possible to improve lateral visibility by determining gray-scale voltages for the respective sub-pixels PXa and PXb so that a synthesized gamma curve obtained from the front of an LCD is similar to a reference gamma curve for the front of the LCD and a synthesized gamma curve obtained from either side of the LCD is as close as possible to the reference gamma curve.

In addition, as described above, 4 domain groups constituting the second sub-pixel electrode 82b are formed to have substantially the same area, thereby resulting in uniform vertical and horizontal visibility.

An LCD according to another exemplary embodiment of the present invention will now be described in detail with reference to FIGS. 6A through 7. Components having the same function as described in connection with the embodi-

ments shown in FIGS. 1 through 5 are respectively identified by the same reference numerals, and their further description will be omitted. FIG. 6A is a layout view of a lower display panel of an LCD according to another exemplary embodiment of the present invention. FIG. 6B is a layout view of an LCD including an upper display panel and the lower display panel of FIG. 6A according to another exemplary embodiment of the present invention. FIG. 7 is an enlarged layout view of a second sub-pixel electrode of FIG. 6B.

Referring to FIG. 7, the LCD is substantially the same as the LCD according to the embodiment of the present invention described in connection with FIGS. 4A-4C and 5, except that, 4 domain groups constituting a second sub-pixel electrode 82b, i.e., domain groups A, B, C, and D, are formed to have substantially the same width. Accordingly, the area of domain group B or D is larger than the area of domain groups A or C. Therefore, in order to make the domain groups A, B, C, and D have substantially the same area, a storage electrode extension 29' may be formed such that it extends from the storage electrode 29 in directions of the domain groups B and D. In other words, the storage electrode extension 29' extends toward the domain groups B and D adjacent to the storage electrode 29 so as to be overlapped with the second sub-pixel electrode 82b, thereby reducing the areas of the domain groups B and D.

In the present embodiment, the storage electrode 29 having the storage electrode extension 29' is formed as a rotated 'T' shape. However, the shape formed by the storage electrode 29 and the storage electrode extension 29' is not restricted to the shape shown. In other words, the storage electrode 29 and the storage electrode extension 29' may be formed in various shapes as long as the domain groups A, B, C, and D have the same area.

As described above, it is possible to provide uniform vertical and horizontal visibility by forming the 4 domain groups of the second sub-pixel electrode 82b divided according to orientations of liquid crystal molecules so as to have the same area.

Accordingly, the embodiments of the present invention provide uniform visibility in horizontal and vertical directions while improving lateral visibility.

Although the illustrative embodiments have been described herein with reference to the accompanying drawings, it is to be understood that the present invention is not limited to those precise embodiments, and that various other changes and modifications may be affected therein by one of ordinary skill in the related art without departing from the scope or spirit of the invention. All such changes and modifications are intended to be included within the scope of the invention as defined by the appended claims.

What is claimed is:

1. A liquid crystal display device comprising:
 - a first insulating substrate comprising a pixel region;
 - a second insulating substrate comprising a common electrode, the common electrode having domain dividers;
 - a liquid crystal layer interposed between the first and the second insulating substrates;
 wherein the pixel region is to be divided into first to fourth domains by at least one of the domain dividers, the first and the third domains have first width and first length, and the second and the fourth domains have second width different from the first width and second length different from the first length, and wherein the first to fourth domains have same area with one another.
2. The LCD of claim 1, wherein the first insulating substrate further comprising:
 - a storage electrode line passing through the pixel region; and

13

a storage electrode connected to the storage electrode line, wherein, the first and the third domains are symmetrical with respect to the storage electrode, and the second and the fourth domains are symmetrical with respect to the storage electrode.

3. The LCD of claim 1, wherein each of the domains has a width of 28 μm or less.

4. The LCD of claim 1, wherein each of the domains has a width of 14 μm or more.

5. A liquid crystal display device comprising:
 a first insulating substrate comprising a pixel region;
 a second insulating substrate comprising a common electrode, the common electrode having domain dividers;
 a liquid crystal layer interposed between the first and the second insulating substrates;
 a storage electrode line disposed on the first insulating substrate, and passing through the pixel region;
 a storage electrode electrically connected to the storage electrode line,
 wherein the pixel region is to be divided into first to fourth domains by at least one of the domain dividers, the first to fourth domains have same area with one another, and wherein the first and the third domains are symmetrical with respect to the storage electrode, and the second and the fourth domains are symmetrical with respect to the storage electrode.

6. The liquid crystal display device of claim 5, wherein the storage electrode has an extension overlapping portions of the second and the fourth domains

7. The LCD of claim 5, wherein each of the domains has a width of 28 μm or less.

8. The LCD of claim 5, wherein each of the domains has a width of 14 μm or more.

9. A liquid crystal display device comprising:
 a first insulating substrate comprising a first pixel region and a second pixel region, the first insulating substrate further comprising:
 a first gate line extended in a first direction;
 a second gate line parallel to the first gate line;
 a data line extended in a second direction perpendicular to the first direction, and insulated from the first and the second gate lines;
 a first switching element electrically connected to the first gate line and the data line respectively;
 a second switching element electrically connected to the second gate line and the data line respectively;
 a first pixel electrode electrically connected to the first switching element, and corresponding to the first pixel region; and
 a second pixel electrode electrically connected to the second switching element, and corresponding to the second pixel region;
 a second insulating substrate comprising a common electrode, the common electrode having domain dividers, at least one of the domain dividers overlapping the second pixel electrode;
 a liquid crystal layer interposed between the first and the second insulating substrates,
 wherein the second pixel region is to be divided into at least a first domain and a second domain by the at least one domain divider, the first and second domains have different widths and lengths from each other, and have same area with each other,

14

wherein the second pixel region is to be divided into first to fourth domain dividers by the at least one domain divider, the first and the third domains have first width and first length, and the second and the fourth domains have second width different from the first width and second length different from the first length,
 and wherein the first to fourth domains have same area with one another.

10. The LCD of claim 9, wherein the first insulating substrate further comprising:
 a storage electrode line passing through the pixel region; and
 a storage electrode connected to the storage electrode line, wherein, the first and the third domains are symmetrical with respect to the storage electrode, and the second and the fourth domains are symmetrical with respect to the storage electrode.

11. The LCD of claim 9, wherein each of the domains has a width of 28 μm or less.

12. The LCD of claim 9, wherein each of the domains has a width of 14 μm or more.

13. A liquid crystal display device comprising:
 a first insulating substrate comprising a first pixel region and a second pixel region, the first insulating substrate further comprising:
 a first gate line extended in a first direction;
 a second gate line parallel to the first gate line;
 a data line extended in a second direction perpendicular to the first direction, and insulated from the first and the second gate lines;
 a first switching element electrically connected to the first gate line and the data line respectively;
 a second switching element electrically connected to the second gate line and the data line respectively;
 a storage electrode line passing through the first and second pixel regions;
 a storage electrode connected to the storage electrode line;
 a first pixel electrode electrically connected to the first switching element, and corresponding to the first pixel region; and
 a second pixel electrode electrically connected to the second switching element, and corresponding to the second pixel region;
 a second insulating substrate comprising a common electrode, the common electrode having domain dividers, at least one of the domain dividers overlapping the second pixel electrode;
 a liquid crystal layer interposed between the first and the second insulating substrates,
 wherein the pixel region is to be divided into first to fourth domains by at least one of the domain dividers, the first to fourth domains have same area with one another, and wherein the first and the third domains are symmetrical with respect to the storage electrode, and the second and the fourth domains are symmetrical with respect to the storage electrode.

14. The liquid crystal display device of claim 13, wherein the storage electrode has an extension overlapping portions of the second and the fourth domains

15. The LCD of claim 13, wherein each of the domains has a width of 28 μm or less.

16. The LCD of claim 14, wherein each of the domains has a width of 14 μm or more.

专利名称(译)	液晶显示器		
公开(公告)号	US7872622	公开(公告)日	2011-01-18
申请号	US11/444185	申请日	2006-05-31
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KIM DONG KYU		
发明人	KIM, DONG-KYU		
IPC分类号	G09G3/36 G02F1/1343 G02F1/1337		
CPC分类号	G02F1/13624 G09G3/3659 G02F1/1393 G02F2001/134345 G09G3/3696 G09G2300/0443 G09G2320/028		
助理审查员(译)	希克斯, CHARLES		
优先权	1020050066014 2005-07-20 KR		
其他公开文献	US20070018927A1		
外部链接	Espacenet USPTO		

摘要(译)

提供了一种能够提供均匀的垂直和水平可见度同时改善侧向可见度的液晶显示器 (LCD)。 LCD 包括第一绝缘基板，形成在第一绝缘基板上的第一和第二栅极线以及与第一和第二栅极线绝缘并与第一和第二栅极线交叉的数据线。 LCD 还包括形成在每个像素中并且分别连接到第一和第二栅极线以及数据线的的第一和第二薄膜晶体管 (TFT)，连接到第一 TFT 的第一子像素电极以及与第一子像素电极隔开预定间隙并连接到第二 TFT 的第二子像素电极。 LCD 包括：第二绝缘基板，面对第一绝缘基板；公共电极，形成在第二绝缘基板上并且包括多个域分离器；以及液晶层，插入在第一和第二绝缘基板之间，其中第二子像素电极的显示区域被畴分隔物划分为4个畴组，并且4个畴组具有基本相同的面积。

