



US007894006B2

(12) **United States Patent**
Choi et al.

(10) **Patent No.:** **US 7,894,006 B2**
(45) **Date of Patent:** **Feb. 22, 2011**

(54) **LIQUID CRYSTAL DISPLAY WITH M X 1
INVERSION DRIVE**

(75) Inventors: **Jin-Young Choi**, Seoul (KR); **Seok-Je
Seong**, Yongin-si (KR); **Jin Jeon**,
Suwon-si (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.** (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 465 days.

(21) Appl. No.: **11/774,716**

(22) Filed: **Jul. 9, 2007**

(65) **Prior Publication Data**

US 2008/0018815 A1 Jan. 24, 2008

(30) **Foreign Application Priority Data**

Jul. 24, 2006 (KR) 10-2006-0068931

(51) **Int. Cl.**

G02F 1/141 (2006.01)

G02F 1/1335 (2006.01)

G09G 3/18 (2006.01)

G09G 3/36 (2006.01)

(52) **U.S. Cl.** **349/37; 345/54; 349/137**

(58) **Field of Classification Search** **349/37,**
349/107, 109, 54; 345/54

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,038,002 A 3/2000 Song
6,249,326 B1 * 6/2001 Hebiguchi 349/42
2003/0043328 A1 3/2003 Hayashi

2004/0109122 A1 * 6/2004 Kumagawa et al. 349/143
2004/0233343 A1 * 11/2004 Baek 349/38
2005/0036091 A1 * 2/2005 Song 349/129
2005/0041006 A1 2/2005 Lee et al.
2005/0068281 A1 * 3/2005 Shin et al. 345/88
2005/0167669 A1 8/2005 Kim et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0752611 A2 1/1997

(Continued)

OTHER PUBLICATIONS

European Search Report for Application No. EP07013180; Search
Completion Date: Sep. 11, 2007.

Primary Examiner—Mark A Robinson


Assistant Examiner—Michael Inadomi

(74) *Attorney, Agent, or Firm*—Cantor Colburn LLP

(57) **ABSTRACT**

A liquid crystal display (LCD) includes a substrate, gate lines, data lines, thin film transistors and pixel electrodes. The gate lines are formed on the substrate and cross the data lines. The thin film transistors are connected to the gate and data lines, and each thin film transistor includes a drain electrode. The pixel electrodes are connected to the thin film transistors and are arranged in a matrix, and each of the pixel electrodes has a first side disposed in parallel with the gate lines and a second side adjacent to the first side and shorter than the first side. In the LCD, the predetermined portion of each of the drain electrodes is overlapped with only one of two adjacent pixel electrodes if the polarities of the adjacent pixel electrodes are different, and the predetermined portion of each of the drain electrodes is overlapped with both of the adjacent pixel electrodes if the polarities are the same.

15 Claims, 9 Drawing Sheets



US 7,894,006 B2

Page 2

U.S. PATENT DOCUMENTS				JP	2002303873	10/2002
				JP	2003330037	11/2003
2006/0061700	A1 *	3/2006	Chung et al. 349/38	JP	2006017897	1/2006
2006/0061711	A1 *	3/2006	Lee et al. 349/106	KR	1020020056675	7/2002
2006/0066797	A1 *	3/2006	Back 349/139	KR	1020030029218	4/2003
2006/0131585	A1	6/2006	Kim et al.	KR	1020040006554	1/2004
2007/0263134	A1 *	11/2007	Kim et al. 349/54	KR	1020040031370	4/2004
				KR	1020040076721	9/2004
FOREIGN PATENT DOCUMENTS				KR	1020060023699	3/2006
JP	2001222027	8/2001		* cited by examiner		

FIG. 1




FIG. 2




FIG.3




FIG.4




FIG. 5




FIG. 6




FIG. 7




FIG.8





FIG. 9



LIQUID CRYSTAL DISPLAY WITH M X 1 INVERSION DRIVE

This application claims priority to Korean Patent Application No. 10-2006-0068931, filed on Jul. 24, 2006, and all the benefits accruing therefrom under 35 U.S.C. §119, the contents of which in its entirety are herein incorporated by reference.

BACKGROUND OF THE INVENTION

(a) Field of the Invention

The present invention relates to a liquid crystal display. More particularly, the present invention relates to a liquid crystal display having fewer data driving circuits, and which prevents cross-talk, generated during column inversion driving.

(b) Description of the Related Art

A liquid crystal display is one of the most widely used flat panel displays. The liquid crystal display includes two display panels each having field-generating electrodes such as a pixel electrode and a common electrode, and a liquid crystal layer interposed therebetween. The liquid crystal display induces an electric field in the liquid crystal layer by applying a voltage to the field generating electrodes, and determines the alignment of liquid crystal molecules of the liquid crystal layer to control polarization of incident light through the display panels, thereby displaying an image.

The liquid crystal display also includes a plurality of signal lines such as gate lines and data lines in order to supply a voltage to a respective pixel electrode by controlling a switching element connected to the respective pixel electrode. The gate line transfers a gate signal generated from a gate driving circuit, and the data line transfers a data voltage generated from a data driving circuit. The switching element transfers a data voltage to the respective pixel electrode according to the gate signal.

The gate driving circuit and data driving circuit are directly mounted on one of the two display panels in the form of a plurality of integrated circuit ("IC") chips. Alternatively, the gate driving circuit and data driving circuit are mounted on a flexible circuit layer and the flexible circuit layer is attached to one of the display panels. Such an IC chip is responsible for a large percentage of a manufacturing cost of a liquid crystal display. Particularly, since the data driver IC chip is much more expensive than a gate driving circuit IC chip, it is necessary to reduce the number of IC chips for a high resolution and large-sized liquid crystal display. The manufacturing cost of the gate driving circuit can be reduced by integrating the gate driving circuit with the display panel having the gate lines, data lines and switching elements. However, it is very difficult to integrate the data driving circuit with the display panel because the data driving circuit has a complicated structure. Therefore, a reduction of the number of data driver ICs is required.

BRIEF SUMMARY OF THE INVENTION

The present invention has been made in an effort to provide a liquid crystal display having features, aspects and advantages of reducing the number of data driving circuit IC chips and preventing cross-talk generated during column inversion driving.

An exemplary embodiment of the present invention provides a liquid crystal display including: a substrate, a plurality of gate lines, a plurality of data lines, a plurality of thin film transistors and a plurality of pixel electrodes. The gate lines

are formed on the substrate, and the data lines cross the gate lines. The thin film transistors are connected to the gate lines and the data lines, and each thin film transistor includes a drain electrode. The pixel electrodes are connected to the thin film transistors and arranged in a matrix, and each of the pixel electrodes includes a first side disposed in parallel with the gate lines and a second side adjacent to the first side and shorter than the first side. In the liquid crystal display, a predetermined portion of each the drain electrodes are disposed between adjacent pixel electrodes. The predetermined portion of the drain electrodes are overlapped with only one of the adjacent pixel electrodes if the polarities of the adjacent pixel electrodes are different, and the predetermined portion of the drain electrodes are overlapped with both of the adjacent pixel electrodes if the polarities of the adjacent pixel electrodes are the same.

The polarity of the pixel electrodes may be driven in an $m \times 1$ inversion-drive manner.

In exemplary embodiments, the m may be 3.

The liquid crystal display further includes a storage electrode line overlapped with respective pixel drain electrodes.

A predetermined portion of each of the drain electrodes and the storage electrode lines may be disposed between adjacent pixel electrodes in a column direction.

Each of the pixel electrodes may cover a previous gate line.

The liquid crystal display may further include an organic layer formed between the pixel electrodes and the data lines, and between the pixel electrodes and the gate lines.

The length of the first side may be three times longer than that of the second side.

The liquid crystal display may further include a gate driver connected to the gate lines, wherein the gate driver may be placed at the same layer as the gate lines, the data lines and the thin film transistors.

Another exemplary embodiment of the present invention provides a liquid crystal display which includes a substrate, a plurality of gate lines, a plurality of data lines, a plurality of thin film transistors, and first, second and third pixel electrodes. The gate lines are formed on the substrate, and the data lines cross the gate lines. The thin film transistors are connected to the gate lines and the data lines. The first, second, and third pixel electrodes are connected to the thin film transistors, respectively, and are adjacent in a column direction. Each of the first to third pixel electrodes has a first side disposed in parallel with the gate lines and a second side adjacent to and shorter than the first side. Polarities of the second and third pixel electrodes are the same, and the polarity of the first pixel electrode is opposite to the polarity of the second and third pixel electrodes. A first drain electrode is disposed between the first and second pixel electrodes, and a second drain electrode is disposed between the second and third pixel electrodes. The first drain electrode is overlapped only with the first pixel electrode of the first, second and third pixel electrodes, and the second drain electrode is overlapped with both of the second and third pixel electrodes.

The liquid crystal display may further include a storage electrode line overlapped with corresponding pixel and drain electrodes.

Each of the pixel electrodes may cover a previous gate line.

The liquid crystal display may further include an organic layer formed between the pixel electrodes and the data lines, and between the pixel electrodes and the gate lines.

The length of the first side is three times longer than the length of the second side.

The liquid crystal display may further include a gate driver connected to the gate lines, and the gate driver may be placed at the same layer as the gate lines, the data lines and the thin film transistors.

BRIEF DESCRIPTION OF THE DRAWINGS

Features aspects and advantages of the present invention will be made apparent by describing exemplary embodiments of the present invention with reference to the accompanying drawings, in which:

FIG. 1 is a block diagram illustrating a liquid crystal display according to an exemplary embodiment of the present invention;

FIG. 2 is an equivalent circuit diagram of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention;

FIG. 3 is a plan view layout of a thin film transistor array panel for a liquid crystal panel assembly according to an exemplary embodiment of the present invention;

FIG. 4 is a plan view layout of a common electrode panel for a liquid crystal panel assembly according to an exemplary embodiment of the present invention;

FIG. 5 is a plan view layout of a liquid crystal panel assembly including a thin film transistor array panel shown in FIG. 3 and a common electrode panel shown in FIG. 4;

FIG. 6 and FIG. 7 are cross-sectional views of the liquid crystal display shown in FIG. 5 taken along lines VI-VI and VII-VII, respectively;

FIG. 8 is a plan view layout of a liquid crystal display according to another exemplary embodiment of the present invention; and

FIG. 9 is a cross-sectional view of the liquid crystal display shown in FIG. 8 taken along line IX-IX.

DETAILED DESCRIPTION OF THE INVENTION

The present invention will be described more fully herein-after with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown. As those skilled in the art would realize, the described exemplary embodiments may be modified in various different ways, all without departing from the spirit or scope of the present invention.

In the drawings, the thickness of layers, films, panels, regions, etc., are exaggerated for clarity. Like reference numerals designate like elements throughout the specification. It will be understood that when an element such as a layer, film, region, or substrate is referred to as being "on" another element, it can be directly on the other element or intervening elements may also be present. In contrast, when an element is referred to as being "directly on" another element, there are no intervening elements present. As used herein, the term "and/or" includes any and all combinations of one or more of the associated listed items.

It will be understood that, although the terms first, second, third etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer or section from another element, component, region, layer or section. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the present invention.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprises" and/or "comprising," or "includes" and/or "including" when used in this specification, specify the presence of stated features, regions, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, regions, integers, steps, operations, elements, components, and/or groups thereof.

Spatially relative terms, such as "beneath", "below", "lower", "above", "upper" and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as "below" or "beneath" other elements or features would then be oriented "above" the other elements or features. Thus, the exemplary term "below" can encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and the present disclosure, and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

Embodiments of the present invention are described herein with reference to cross section illustrations that are schematic illustrations of idealized embodiments of the present invention. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, embodiments of the present invention should not be construed as limited to the particular shapes of regions illustrated herein but are to include deviations in shapes that result, for example, from manufacturing. For example, a region illustrated or described as flat may, typically, have rough and/or nonlinear features. Moreover, sharp angles that are illustrated may be rounded. Thus, the regions illustrated in the figures are schematic in nature and their shapes are not intended to illustrate the precise shape of a region and are not intended to limit the scope of the present invention.

Hereinafter, a liquid crystal display according to an exemplary embodiment of the present invention will be described with reference to FIG. 1 and FIG. 2.

FIG. 1 is a block diagram illustrating a liquid crystal display according to an exemplary embodiment of the present invention. FIG. 2 is an equivalent circuit diagram illustrating a pixel of a liquid crystal display according to an exemplary embodiment of the present invention.

Referring to FIG. 1 and FIG. 2, the liquid crystal display according to an exemplary embodiment of the present invention includes a liquid crystal panel assembly **300**, a gate driver **400** and data driver **500** connected to the liquid crystal panel

assembly **300**, a gray voltage generator **800** connected to the data driver **500**, and a signal controller **600** for controlling the drivers **400** and **500**.

The liquid crystal panel assembly **300** includes a plurality of display signal lines and a plurality of pixels PX1, PX2 and PX3 connected to display signal lines and arranged in a matrix shape. Further, the liquid crystal panel assembly **300** includes a liquid crystal layer **3** interposed between lower and upper panels **100** and **200** facing each other as shown in FIG. 1.

The signal lines G_1 - G_m , D_1 - D_m include a plurality of gate lines G_1 - G_m transferring a gate signal (or a scanning signal) and a plurality of data lines D_1 - D_m transferring a data signal.

The gate lines G_1 - G_m extend substantially in a row direction in parallel with each other, and the data lines D_1 - D_m extend substantially in a column direction in parallel with each other, as illustrated in FIG. 1.

Each of the pixels PX1, PX2 and PX3 has a longitudinal structure in the row direction. For example, the pixels PX1, PX2, and PX3 connected to the gate line GL and the data line DL include a switching element Q connected to signal lines GL and DL, and a liquid crystal capacitor Clc and a storage capacitor Cst connected thereto. However, the storage capacitor Cst can be omitted according to need in alternative exemplary embodiments.

The switching element Q is a three-terminal element such as a thin film transistor disposed at the lower panel **100**. The switching element Q includes a control terminal connected to the gate line GL, an input terminal connected to a data line DL and an output terminal connected to a liquid crystal capacitor Clc and a storage capacitor Cst.

The liquid crystal capacitor Clc uses a pixel electrode **191** at the lower panel **100** and a common electrode **270** at the upper panel **200** as two terminals, and a liquid crystal layer **3** between two electrodes **191** and **270** functions as a dielectric material. The pixel electrode **191** is connected to the switching element Q. The common electrode **270** is formed on the entire surface of the upper panel **200** and receives a common voltage Vcom. Unlike FIG. 2, a common electrode **270** can be formed at the lower panel **100**. In this case, at least one of the two electrodes **191** and **270** can be made in a line shape or a rod shape.

A storage capacitor Cst functioning as a subsidiary of the liquid crystal capacitor Clc is formed of a sustaining electrode line SL overlapping a pixel electrode **191** with an insulator interposed therebetween. A predetermined voltage such as a common voltage Vcom is applied to the additional signal line. The storage capacitor Cst can be formed of a pixel electrode **191** overlapping a previous gate line with an insulator as a medium.

In order to embody color display, each of the pixels PX1-PX3 displays a unique primary color (spatial division), or alternatively, each of the pixels PX1-PX3 displays different primary colors according to time (temporal division), thereby displaying desired colors through a spatial or temporal sum of these primary colors. For example, the primary colors are three primary colors, red, green and blue. FIG. 2 shows a color filter **230** displaying one of the primary colors on a region of an upper panel **200** corresponding to the pixel electrode **191** by each of the pixels PX1-PX3 as an example of spatial division. Unlike that shown in FIG. 2, a color filter **230** can be formed below a pixel electrode **191** of the lower panel **100**. Color filters **230** for one primary color of pixels PX1-PX3 adjacent in a row direction extend in a row direction and are connected to one another, and color filters **230** for different colors are alternately arranged in a column direction.

It is assumed that each color filter **230** uniquely displays one of a red, green and blue color throughout the specification. A red pixel is a pixel with a red color filter **230**, a green pixel is a pixel with a green color filter **230** and a blue pixel is a pixel with a blue color filter **230**. The red pixel, blue pixel and green pixel are sequentially and alternately arranged in a column direction.

As described above, the pixels PX1-PX3 of three primary colors form one dot (DT) as a basic unit of an image (see FIG. 1).

Referring to FIG. 1 again, the gate driver **400** is integrated with the liquid crystal panel assembly **300** along with the signal lines G_1 - G_m , D_1 - D_m and the thin film transistor switching elements Q. The gate driver **400** is formed at the left side and the right side of the liquid crystal panel assembly **300** (only the left side gate driver **400** shown in FIG. 1). The gate driver **400** applies a gate signal formed of a combination of a gate-on voltage Von and a gate-off voltage Voff. The gate driver **400** can be mounted directly on the liquid crystal panel assembly **300** as an IC chip. Alternatively, the gate driver **400** can be mounted on the liquid crystal panel assembly **300** in a tape carrier package ("TCP") type by being mounted on a flexible printed circuit film, or can be mounted on an additional printed circuit board ("PCB").

At least one polarizer (not shown) is attached at the outer surface of the liquid crystal panel assembly **300** for polarizing the light.

The gray voltage generator **800** generates two gray voltage sets (or reference gray voltage sets) related to a transmittance of a pixel PX. One of the two sets has a positive value and the other has a negative value relative to a common voltage Vcom.

The data driver **500** is connected to data lines D_1 - D_m of the liquid crystal panel assembly **300**, selects a gray voltage from the gray voltage generator **800**, and supplies the selected gray voltage to the data lines D_1 - D_m as a data signal. When the gray voltage generator **800** only provides a predetermined number of reference gray voltages instead of supplying gray voltages for all grays, the data driver **500** generates a gray voltage for all grays by dividing the reference gray voltage and selects one among them. The data driver **500** can be mounted directly on a liquid crystal panel assembly **300** as an IC chip. Alternatively, the data driver **500** can be attached on the liquid crystal panel assembly **300** as a TCP by being mounted on a flexible printed circuit film (not shown), or mounted on an additional PCB. However, the data driver **500** can be integrated with the liquid crystal panel assembly **300** with the signal lines G_1 - G_m and D_1 - D_m and the thin film transistor switching elements Q.

The signal controller **600** controls the gate driver **400** and the data driver **500**.

Hereinafter, the operation of such a liquid crystal display according to the present exemplary embodiment will be described in more detail.

The signal controller **600** receives an input control signal from an external graphics controller (not shown) for controlling display of input image signals R, G and B. The input image signals R, G and B have information about luminance of each pixel PX. The luminance has a predetermined number of grays, for example, 1024 ($=2^{10}$), 256 ($=2^8$) or 64 ($=2^6$). For example, the input control signal includes a vertical synchronization signal Vsync, a horizontal synchronizing signal Hsync, a main clock signal MCLK, a data enable signal DE, etc.

The signal controller **600** receives an input control signal from the external graphics controller (not shown) for controlling the display of input image signals R, G and B, and

processes the received input control signal to be suitable to an operating condition of the liquid crystal panel assembly 300. Then, the signal controller 600 generates a gate control signal CONT1 and a data control signal CONT2, and outputs them to the gate driver 400 and data driver 500, respectively. The image signal processing of the signal controller 600 includes an operation for rearranging the input image signals R, G and B according to the arrangement of the pixels.

The gate control signal CONT1 includes a scanning start signal STV for ordering start of scanning and at least one clock signal for controlling the output cycle of the gate-on voltage (Von). The gate control signal CONT1 can further include an output enable signal OE that limits a time duration of the gate-on voltage Von.

The data control signal CONT2 includes a horizontal synchronization start signal STH for notifying beginning of digital image signal DAT transmission to one column of pixels, and a load signal LOAD and a data clock signal HCLK for ordering load of an analog data signal to the data lines D₁-D_m. The data control signal CONT2 can further include an inversion signal RVS which inverts a voltage polarity of an analog data signal for a common voltage Vcom. Hereinafter, the data signal polarity denotes the voltage polarity of a data signal for a common voltage.

The data driver 500 receives a digital image signal DAT for a column of pixels, and converts the digital image signal DAT to an analog data signal by selecting a gray voltage corresponding to each digital image signal DAT according to the data control signal CONT2 from the signal controller 600. Then, the analog data signal is supplied to corresponding data lines D1-Dm.

The gate driver 400 supplies a gate-on voltage Von to gate lines G₁-G_n according to a gate control signal CONT1 from the signal controller 600, thereby turning on a switching element Q connected to the gate lines G₁-G_n. Then, the data signal supplied to the data lines D₁-D_m is supplied to a corresponding pixel PX through the turned-on switching element Q.

The difference between a voltage of a data signal supplied to a pixel PX and a common voltage Vcom is shown as a charge voltage of a liquid crystal capacitor Clc, that is, a pixel voltage. Liquid crystal molecules vary their arrangement according to the level of the pixel voltage, and vary the polarization of light passing through the liquid crystal layer 3 according to the variation of the liquid crystal molecule arrangement. Such a polarization variation is shown as a transmittance variation of light by a polarizer attached to the display panel assembly 300, and the pixel PX displays luminance expressing the gray of the image signal DAT.

By repeating the above described operation in a unit of 1 horizontal period ("1H") which is equivalent to one cycle of a horizontal synchronizing signal Hsync and a data enable signal DE, the gate-on voltage Von is sequentially provided to all of the gate lines G₁-G_n, and an image of one frame is displayed by supplying the data signals to all of the pixels PX.

After displaying the image of one frame, the next frame starts and the state of the inversion signal RVS supplied to the data driver 500 is controlled to invert the polarity of the data signal from the previous frame ("frame inversion"). Herein, the polarity of a data signal flowing through a data line can be inverted according to a characteristic of the inversion signal RVS even within one frame (for example, row inversion, dot inversion), or the polarity of the data signal supplied to one pixel can be different (for example column inversion, dot inversion).

Hereinafter, the liquid crystal panel assembly 300 according to an embodiment of the present invention will be described with reference to FIGS. 3 to 7.

FIG. 3 is a plan view layout illustrating a thin film transistor array panel for a liquid crystal panel assembly according to an exemplary embodiment of the present invention. FIG. 4 is a plan view layout illustrating a common electrode panel for a liquid crystal panel assembly according to an exemplary embodiment of the present invention. FIG. 5 is a plan view layout view illustrating a liquid crystal panel assembly formed of a thin film transistor array panel shown in FIG. 3 and a common electrode panel shown in FIG. 4. FIGS. 6 and 7 are cross-sectional views of a liquid crystal panel assembly shown in FIG. 5 taken along lines VI-VI and VII-VII, respectively.

First, a thin film transistor array panel for a liquid crystal panel assembly according to an exemplary embodiment of the present invention will be described with reference to FIGS. 3, 5, 6 and 7.

A plurality of gate lines 121 and storage electrode lines 131 are formed on an insulation substrate 110 made of transparent glass or plastic.

The gate lines 121 transfer a gate signal and basically extend in a horizontal direction, as illustrated in FIGS. 3 and 5. Each gate line 121 includes a plurality of gate electrodes 124 protruding upwardly and downwardly, and a wide end 129 for contacting other layers or an external driving circuit (not shown).

Each storage electrode line 131 receives a predetermined voltage such as a common voltage, and extends in parallel with the gate lines 121. The storage electrode line 131 includes a storage electrode 137. However, the shape and arrangement of the storage electrode lines 131 can be modified.

The gate lines 121 and the storage electrode lines 131 can be made of an aluminum group metal such as aluminum (Al) and an aluminum alloy, a silver group metal such as silver (Ag) and a silver alloy, a copper group metal such as copper (Cu) and a copper alloy, a molybdenum group metal such as molybdenum (Mo) and a molybdenum alloy, chromium (Cr), tantalum (Ta), or titanium (Ti). However, they can have a multilayer structure having two conductive layers (not shown) with different physical properties. A conductive layer among them can be made of a metal having low resistivity, for example an aluminum group metal, a silver group metal, or a copper group metal in order to reduce signal delay or voltage drop. On the contrary, the other conductive layer can be made of a different material having excellent physical, chemical and electrical contact characteristics to indium tin oxide ("ITO") and indium zinc oxide ("IZO"), for example a molybdenum group metal, chromium, tantalum, or titanium. For example, such a composition can be a chromium lower layer and an aluminum (alloy) upper layer, or an aluminum (alloy) lower layer and a molybdenum (alloy) upper layer. However, the gate line 121 and storage electrode line 131 can be made of various metals or conductors besides the materials described above.

It is desirable that the sides of the gate lines 121 and storage electrode lines 131 are inclined relative to the substrate 110, and the inclination angle is about 30° to about 80°.

A gate insulating layer 140 made of silicon nitride ("SiN_x") or silicon oxide ("SiO_x") is formed on the gate lines 121 and the storage electrode lines 131.

A plurality of semiconductor islands 154 made of hydrogenated amorphous silicon ("a-Si") or polysilicon are formed

on the gate insulating layer **140**. A semiconductor **154** is formed on the gate electrode **124**, as illustrated in FIGS. 3, 5 and 6.

A plurality of ohmic contact islands (ohmic contacts) **163** and **165** are formed on the semiconductor **154**. The ohmic contacts **163** and **165** are made of n+ hydrogenated amorphous silicon doped with a highly concentrated n-type impurity such as phosphor, or of silicide. The ohmic contacts **163** and **165** are paired on the semiconductor **154**.

The sides of the semiconductor **154** and the ohmic contacts **163** and **165** are also inclined relative to the substrate **110**, and the inclination angle therebetween is about 30° to about 80°.

A plurality of data lines **171** and a plurality of drain electrodes **175** are formed on the ohmic contacts **163** and **165** and the gate insulating layer **140**.

The data lines **171** transfer a data signal and basically extend in a vertical direction, thereby intersecting the gate lines **121**, as illustrated in FIGS. 3 and 5. Each data line **171** includes a plurality of source electrodes **173** extending toward the gate electrode **124** and a wide end **179** for contacting another layer or an external driving circuit (not shown). A data driving circuit (not shown) generating a data signal can be mounted on a flexible printed circuit film (not shown) attached to the substrate **110**, directly on the substrate **110**, or integrated with the substrate **110**. When the data driving circuit is integrated with the substrate **110**, the data line **171** can extend to directly connect thereto.

The drain electrodes **175** are separated from the data lines **171** and face a source electrode **173** interposing the gate electrode **124** therebetween. Each drain electrode **175** includes one wide end **177** and one rod-shaped end. The wide end **177** is overlapped with a storage electrode **137**, and the rod-shaped end is partially surrounded by the U shaped source electrode **173**.

One gate electrode **124**, one source electrode **173** and one drain electrode **175** form a thin film transistor ("TFT") with a semiconductor **154**, and the channel of the thin film transistor is formed between the source electrode **173** and the drain electrode **175** on the semiconductor **154**.

It is desirable that the data lines **171** and drain electrodes **175** are made of a refractory metal such as molybdenum, chromium, tantalum, titanium, or alloys comprising at least one of the foregoing metals, and have a multilayer structure made of a refractory metal layer (not shown) and a conductive layer (not shown). For example, the multilayer structure may be a dual-layer structure made of a chromium or molybdenum (alloy) lower layer and an aluminum (alloy) upper layer, or a triple-layer structure made of a molybdenum (alloy) lower layer, an aluminum (alloy) middle layer, and a molybdenum (alloy) upper layer. However, the data lines **171** and drain electrodes **175** can be made of various metals or conductors besides the materials described above.

It is desirable that the data line **171** and drain electrode **175** are also inclined relative to the substrate **110**, and the inclination angle is about 30° to about 80°.

The ohmic contacts **163** and **165** are only present between the semiconductors **154** disposed thereunder and the data lines **171** and drain electrodes **175** disposed thereabove, and reduce the contact resistive therebetween. Each semiconductor **154** includes an exposed region which is not covered by a data line **171** and a drain electrode **175**, such as a region between the source electrode **173** and the drain electrode **175**.

A passivation layer **180** is formed on the data line **171**, the drain electrode **175** and the exposed portion of the semiconductor **154**. The passivation layer **180** is made of an inorganic insulator such as silicon nitride or silicon oxide. The passivation layer **180** can be made of an organic insulator, and the

surface thereof can be flat. In the case of the organic insulator, the passivation layer **180** can have photosensitivity, and it is desirable that the dielectric constant thereof is less than about 4.0. The passivation layer **180** can have a dual-layer structure made of a lower inorganic layer and an upper organic layer at the exposed region of the semiconductor **154** in order to sustain the inorganic layer's excellent insulating characteristic and to not damage the exposed region of the semiconductor **154**.

A plurality of contact holes **182** and **185** are formed in the passivation layer **180** to expose the ends **179** of the data lines **171**, and the drain electrodes **175**, and a plurality of contact holes **181** are formed in the passivation layer **180** and the gate insulating layer **140** to expose the ends **129** of the gate lines **121**.

A plurality of pixel electrodes **191**, a plurality of connecting members **81** and a plurality of contact assistants **82** are formed on the passivation layer **180**. They can be made of a transparent conductive material such as ITO or IZO, or a reflective metal such as aluminum, silver, chromium, or alloys comprising at least one of the foregoing metals.

Each pixel electrode **191** has four sides disposed substantially in parallel with the gate line **121** or the data line **171**. Among them, the two vertical sides **1911** parallel with the gate line **121** are longer than the two horizontal sides **191s**, and the two vertical sides **1911** are three times longer than the two horizontal sides **191s**, as best seen with reference to FIGS. 3 and 5. Therefore, compared to a case having a vertical side shorter than a horizontal side, the number of pixel electrodes **191** disposed at each column is smaller than the number of pixel electrodes **191** disposed at each row. Therefore, since the overall number of data lines **171** is reduced, the material cost can be reduced by reducing the number of IC chips for the data driver **500**. Although the number of gate lines **121** increases, the increase of the gate lines **121** does not become a major problem because the gate driver **400** can be integrated with the assembly **300** having the gate lines **121**, data lines **171**, and thin film transistors. Although the gate driver **400** is mounted as an IC chip, it is more cost effective to reduce the number of IC chips for data driver **500** because the price of the IC chips for the gate driver **400** is comparatively cheaper.

The pixel electrode **191** is physically and electrically connected to the drain electrode **175** through the contact hole **185**, and receives a data voltage from the drain electrode **175** (FIG. 6). The pixel electrode **191** receiving a data voltage induces an electric field with the common electrode **270** of the common electrode panel **200**. Thereby, the electric field determines the direction of the liquid crystal molecules of the liquid crystal layer **3** between the two electrodes **191** and **270**. The polarization of the light passing through the liquid crystal layer **3** varies according to the determined direction of the liquid crystal molecules. The pixel electrode **191** and common electrode **270** sustain the supplied voltage by forming a liquid crystal capacitor after the respective thin film transistor is turned off.

The pixel electrode **191** forms a storage capacitor which enhances the voltage sustaining capability of the liquid crystal capacitor by being overlapped with the storage electrode line **131** and the storage electrode **137**. In more detail, the storage electrode **137** of the storage electrode line **131** horizontally crosses two adjacent pixel electrodes **191n** and **191p**, and overlaps two pixel electrodes **191n** and **191p**, as best seen with reference to FIGS. 3 and 5. The storage electrode **137** blocks light leakage between the pixel electrodes **191**.

Referring to FIGS. 3 and 5, the pixel electrodes **191** also overlap the gate lines **121**. In more detail, a gate line **121p**

connected to a gate electrode **124** of a thin film transistor Qp connected to the first pixel electrode **191p** which is placed on the top between two pixel electrodes **191n** and **191p** adjacent in a column direction does not overlap the first pixel electrode **191n**. The gate line **121p** is overlapped with the second pixel electrode **191n**. A gate line **121n** connected to a gate electrode **124** of a thin film transistor (Qn) connected to the lower pixel electrode **191n** is overlapped by the third pixel electrode **191m** adjacent to and under the second pixel electrode **191n**.

As described above, a storage electrode line **131** is formed between pixel electrodes **191**, and the gate line **121** is overlapped with the adjacent pixel electrodes **191**, thereby reducing a kickback voltage and increasing an aperture ratio.

Contact assistants **82** are connected to the ends **179** of the data lines **171** through contact holes **182**. The contact assistants **82** complement adhesion between the ends **179** of the data lines **171** and an external device (not shown) and protect them.

A connecting member **81** is connected to the wide end **129** of the gate line **121** through the contact hole **181**. The connecting member **81** connects the wide end **129** of the gate line **121** and the gate driver **400**. If the gate driver **400** is of the IC chip type, the connecting member **81** can have a shape and function similar to those of the contact assistants **82**.

Hereinafter, a common electrode panel **200** will be described with reference to FIGS. **4** to **6**.

A light blocking member **220** is formed on an insulation substrate **210** made of transparent glass or plastic. The light blocking member **220** is also called a black matrix, and blocks light leakage.

A plurality of color filters **230** are formed on the substrate **210** and light blocking member **220**. The color filters **230** are mostly formed in a region surrounded by the light blocking member **220**, and extend along the line of the pixel electrode **191**. Each of the color filters **230** can display one of three primary colors, such as, red, green and blue, for example, but is not limited thereto.

An overcoat **250** is formed on the color filters **230** and the light blocking member **220**. The overcoat **250** can be made of an organic insulator. Such an overcoat **250** prevents the color filters **230** from being exposed and provides a flat surface. A common electrode **270** is formed on the overcoat **250**. The overcoat **250** can be omitted in alternative exemplary embodiments.

Alignment layers **11** and **21** are coated on the inside surfaces of the display panels **100** and **200**, and they can be vertical alignment layers. Polarizers **12** and **22** are provided at the outer surface of the display panels **100** and **200**, respectively, and the polarization axis of the two polarizers can be in parallel with or cross each other. In the case of a reflective liquid crystal display, one of the two polarizers can be omitted.

The liquid crystal display according to the present exemplary embodiment can further include a phase retardation film (not shown) to correct the delay of the liquid crystal layer **3**. The liquid crystal display can include the polarizers **12** and **22**, a phase retardation film, the display panels **100** and **200**, and a lighting unit for providing light to a liquid crystal layer **3**.

The liquid crystal layer **3** has positive or negative dielectric anisotropy, so the liquid crystal molecules of the liquid crystal layer **3** are arranged to have a longitudinal axis which is parallel with or vertical to the surface of the two display panels **100** and **200** in a state of no electric field being applied.

Hereinafter, a liquid crystal panel assembly according to another exemplary embodiment of the present invention will be described with reference to FIGS. **8** and **9**.

FIG. **8** is a plan view layout illustrating a liquid crystal panel assembly according to another exemplary embodiment of the present invention. FIG. **9** is a cross-sectional view illustrating a liquid crystal panel assembly shown in FIG. **8** taken along line IX-IX.

The liquid crystal panel assembly according to the present alternative exemplary embodiment includes a thin film transistor array panel **100**, a common electrode panel **200** facing the thin film transistor array panel **100** and a liquid crystal layer **3** interposed between the two display panels **100** and **200**.

The layered structure of the liquid crystal panel assembly according to the present alternative exemplary embodiment is approximately identical to the layered structure of the liquid crystal panel assembly shown in FIGS. **3** to **6**.

The lower panel **100** will be described hereinafter. A plurality of gate conductors having a plurality of gate lines **121** and storage electrode lines **131a** and **131b** are formed on an insulation substrate **110**. Each gate line **121** includes a wide end **129** of the gate electrode **124**, and each storage electrode line **131a** and **131b** includes a storage electrode **137a** and **137b**, respectively. A gate insulating layer **140** is formed on a gate conductor **121**. A semiconductor island **154** is formed on the gate insulating layer **140**, and a plurality of ohmic contacts **163** and **165** are formed thereon. A data conductor having a plurality of data lines **171** and a plurality of drain electrodes **175** is formed on the ohmic contacts **163** and **165** and gate insulating layer **140**. Each data line **171** includes an end **179** of a plurality of source electrodes **173**. A passivation layer **180** is formed on the data conductors **171** and **175** and the exposed region of the semiconductor **154**, and a plurality of contact holes **181**, **182** and **185** are formed on the passivation layer **180** and gate insulating layer **140**. A plurality of pixel electrodes **191** and a plurality of contact assistants **81** and **82** are formed on the passivation layer. An alignment layer **11** is formed on the pixel electrode **191**, the contact assistants **81** and **82**, and the passivation layer **180**.

Hereinafter, the upper panel will be described. A light blocking member **220**, a plurality of color filters **230**, an overcoat **250**, a common electrode **270** and an alignment layer **21** are formed on an insulation substrate **210**.

The liquid crystal panel assembly shown in FIG. **8** inversely drives a data voltage supplied from the data driver **500** to the data line **171** in a 3×1 manner. If three pixel electrodes adjacent in a row direction are the first pixel electrode **191a**, the second pixel electrode **191b** and the third pixel electrode **191c**, and if a pixel electrode adjacent to the upper region of the first pixel electrode **191a** is the fourth pixel electrode **191d**, the voltage polarities of the first to third pixel electrodes **191a**, **191b** and **191c** are positive (+) and the voltage polarity of the fourth pixel electrode **191d** is negative (−).

A drain electrode **177a** overlapping a storage electrode line **131a** between the first pixel electrode **191a** and the fourth pixel electrode **191d** is overlapped with only one of the first and fourth pixel electrode **191a** and **191d**. That is, if the voltage polarities of the adjacent two pixel electrodes **191a** and **191d** are different, the drain electrode **177a** is overlapped with only one of two pixel electrodes **191a** and **191d**.

On the contrary, the drain electrode **177b** overlapping a storage electrode line **131b** formed between the first pixel electrode **191a** and the second pixel electrode **191b** is overlapped with both of the first and second pixel electrodes **191a** and **191b**. A drain electrode **177c** overlapping a storage electrode line **131c** formed between the second pixel electrode **191b** and the third pixel electrode **191c** is also overlapped with both of the second and third pixel electrodes **191b** and **191c**. That is, if the voltage polarity of two adjacent pixel

electrodes **191a** and **191b**, or **191b** and **191c**, are the same, the drain electrodes **177b** and **177c** are overlapped with both of two pixel electrodes (**191a** and **191b**, or **191b** and **191c**).

When the voltage polarities of two adjacent pixel electrodes **191** are opposite, the voltage difference between two pixel electrodes **191** is large. If the drain electrode **177** is overlapped with both of two adjacent pixel electrodes **191**, in this case, a parasitic capacitance is induced between each pixel electrode **191** and the drain electrode **177**. The parasitic capacitance influences the voltages of the two adjacent pixel electrodes, thereby causing pixel quality deterioration. Accordingly, if the polarities of two adjacent pixel electrodes **191** are identical as in the present invention, an aperture ratio can be secured by overlapping the drain electrode **177** with two pixel electrodes **191**. If polarities of two adjacent pixel electrodes **191** are opposite, the pixel quality deterioration can be prevented by overlapping the drain electrode **177** with one of the pixel electrodes **191**.

The liquid crystal panel assembly according to the present alternative exemplary embodiment was described on a basis of a 3×1 inversion drive. However, the present invention is not limited thereto. The present invention can be applied to an m×1 inversion drive, where m is an integer greater than 2. That is, if the polarities of adjacent pixel electrodes **191** are opposite in the case of an m×1 inversion drive, the drain electrode **177** is overlapped with only one of the pixel electrodes **191**. If the polarities of adjacent pixel electrodes **191** are the same, the drain electrode **177** is overlapped with both of two pixel electrodes **191**.

According to the present invention, the number of data driving circuit chips disposed on the liquid crystal display can be reduced, cross-talk can be prevented and the aperture ratio can be secured.

While this invention has been described in connection with what is presently considered to be practical exemplary embodiments, it is to be understood that the present invention is not limited to the disclosed exemplary embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

What is claimed is:

1. A liquid crystal display comprising: a substrate; a plurality of gate lines formed on the substrate; a plurality of data lines crossing the gate lines; a plurality of thin film transistors connected to the gate lines and the data lines, and each thin film transistor including a drain electrode; a plurality of pixel electrodes connected to the thin film transistors, arranged in a matrix, and each pixel electrode having a first side disposed in parallel with the gate lines and a second side shorter than the first side and adjacent to the first side; and a data driver coupled to the data lines applies a voltage having positive polarity or negative polarity to the pixel electrodes, wherein a predetermined portion of each of the drain electrodes is disposed between adjacent pixel electrodes and the drain electrodes include a first drain electrode and second drain electrode, the predetermined portion of the first drain electrode is overlapped with only one of the adjacent pixel electrodes if the polarities of the adjacent pixel electrodes are different, and the predetermined portion of the second drain electrode is overlapped with both of the adjacent pixel electrodes if the polarities of the adjacent pixel electrodes are the same,

wherein the polarities of the pixel electrodes are driven in an m×1 inversion-drive manner, and

wherein the m is an integer greater than 2.

2. The liquid crystal display of claim 1 wherein the m is 3.

3. The liquid crystal display of claim 1, further comprising a storage electrode line overlapped with a respective pixel electrode and drain electrode.

4. The liquid crystal display of claim 3, wherein predetermined portions of each of the drain electrodes and the storage electrode line are disposed between adjacent pixel electrodes in a column direction.

5. The liquid crystal display of claim 1, wherein each pixel electrode covers a previous gate line.

6. The liquid crystal display of claim 1, further comprising an organic layer formed between each pixel electrode and the data lines, and between each pixel electrode and the gate lines.

7. The liquid crystal display of claim 1, wherein the length of the first side is three times longer than that of the second side.

8. The liquid crystal display of claim 1, further comprising a gate driver connected to the gate lines, wherein the gate driver is placed on the substrate on which the gate lines, the data lines and the thin film transistors are formed.

9. A liquid crystal display comprising: a substrate; a plurality of gate lines formed on the substrate; a plurality of data lines crossing the gate lines; a plurality of thin film transistors connected to the gate lines and the data lines; and

first, second and third pixel electrodes, which are connected to the thin film transistors, respectively, each of the first, second and third pixel electrodes having a first side disposed in parallel with the gate lines and a second side adjacent to and shorter than the first side, and are adjacent in a column direction, wherein polarities of the second and third pixel electrodes are the same, and the polarity of the first pixel electrode is opposite to the polarity of the second and third pixel electrodes, wherein a first drain electrode is disposed between the respective first sides of the first and second pixel electrodes, and a second drain electrode is disposed between the respective first sides of the second and third pixel electrodes, and wherein the first drain electrode is overlapped only with the first pixel electrode of the first, second and third pixel electrodes, and the second drain electrode is overlapped with both of the second and third pixel electrodes.

10. The liquid crystal display of claim 9, further comprising a storage electrode line overlapped with corresponding pixel and drain electrodes.

11. The liquid crystal display of claim 9, wherein each of the first, second and third pixel electrodes covers a previous gate line.

12. The liquid crystal display of claim 9, further comprising an organic layer formed between each of the first, second and third pixel electrodes and the data lines, and between each of the first, second and third pixel electrodes and the gate lines.

13. The liquid crystal display of claim 9, wherein the length of the first side is three times longer than that of the second side.

14. The liquid crystal display of claim 9, further comprising a gate driver connected to the gate lines, wherein the gate driver is placed on the substrate on which the gate lines, the data lines and the thin film transistors are formed.

15. The liquid crystal display of claim 1, wherein the first drain electrode overlaps only one pixel electrode of a pair of adjacent pixel electrodes being driven with different polarities and the second drain electrode overlaps both pixel electrodes of a pair of adjacent pixel electrodes being driven with same polarities.

专利名称(译)	具有m×1反转驱动的液晶显示器		
公开(公告)号	US7894006	公开(公告)日	2011-02-22
申请号	US11/774716	申请日	2007-07-09
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	CHOI JIN YOUNG SEONG SEOK JE JEON JIN		
发明人	CHOI, JIN-YOUNG SEONG, SEOK-JE JEON, JIN		
IPC分类号	G02F1/141 G09G3/36 G09G3/18 G02F1/1335		
CPC分类号	H01L27/124 G02F1/136286 G02F1/134309 G02F1/136213		
代理机构(译)	康托科尔伯恩LLP		
优先权	1020060068931 2006-07-24 KR		
其他公开文献	US20080018815A1		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示器 (LCD) 包括基板，栅极线，数据线，薄膜晶体管和像素电极。栅极线形成在基板上并与数据线交叉。薄膜晶体管连接到栅极线和数据线，并且每个薄膜晶体管包括漏电极。像素电极连接到薄膜晶体管并且布置成矩阵，并且每个像素电极具有与栅极线平行设置的第一侧和与第一侧相邻且比第一侧短的第二侧。在LCD中，如果相邻的像素电极的极性不同，则每个漏电极的预定部分仅与两个相邻的像素电极中的一个重叠，并且每个漏电极的预定部分与两个相邻的像素电极的预定部分重叠。如果极性相同，则相邻的像素电极。

