



US 20070126944A1

(19) **United States**(12) **Patent Application Publication****Kim et al.**(10) **Pub. No.: US 2007/0126944 A1**(43) **Pub. Date:****Jun. 7, 2007**(54) **LIQUID CRYSTAL DISPLAY****Publication Classification**(76) Inventors: **Dong-Gyu Kim**, Yongin-si (KR);
Back-Won Lee, Cheonan-si (KR);
Seung-Soo Back, Seoul (KR)(51) **Int. Cl.****G02F 1/136** (2006.01)(52) **U.S. Cl.** **349/43**

Correspondence Address:

Frank Chau, Esq.**F. CHAU & ASSOCIATES, LLC****130 Woodbury Road****Woodbury, NY 11797 (US)**

(57)

ABSTRACT(21) Appl. No.: **11/565,837**(22) Filed: **Dec. 1, 2006**(30) **Foreign Application Priority Data**

Dec. 2, 2005 (KR) 10-2005-0116790

A liquid crystal display includes a substrate, a plurality of pixel electrodes formed on the substrate wherein each of the pixel electrodes includes first and second sub-pixel electrodes, and a plurality of first data lines formed on the substrate, wherein a first data line of the plurality of first data lines does not overlap a first sub-pixel electrode and partially overlaps a second sub-pixel electrode of a pixel electrode of the plurality of pixel electrodes.




FIG. 1




FIG. 2




FIG.3




FIG.5




FIG.6




FIG. 7a




FIG. 7b




FIG. 8




FIG. 9




FIG.10




FIG. 11




FIG. 14




FIG.15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG.20




FIG. 21




FIG. 22




FIG. 23




FIG.24




FIG.25





FIG.27



LIQUID CRYSTAL DISPLAY

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to Korean Patent Application No. 10-2005-0116790 filed in the Korean Intellectual Property Office on Dec. 02, 2005, the disclosure of which is incorporated by reference herein in its entirety.

BACKGROUND OF THE INVENTION

[0002] 1. Technical Field

[0003] The present invention relates to a liquid crystal display.

[0004] 2. Discussion of the Related Art

[0005] Liquid crystal displays (LCDs) are among the most widely used flat panel displays. For example, liquid crystal displays are commonly found in a variety of electronic devices such as televisions, laptop computers, personal digital assistants, cell phones and digital cameras.

[0006] An LCD includes a pair of panels provided with field-generating electrodes such as pixel electrodes and a common electrode and a liquid crystal (LC) layer interposed between the panels. The LCD displays images by applying voltages to the electrodes to generate an electric field in the LC layer, and regulates the strength of the electric field to vary the transmittance of light passing through the LC layer.

[0007] An LCD also includes switching elements connected to respective pixel electrodes and a plurality of signal lines such as gate lines and data lines for controlling the switching elements and applying voltages to the pixel electrodes.

[0008] In such an LCD, to prevent the LC layer from deteriorating due to a one-directional electric field applied for a long time, the polarity of a data voltage is reversed for each frame, for each row, or for each pixel with respect to a common voltage.

[0009] Meanwhile, a parasitic capacitance is generated between a data line and a pixel electrode of the LCD. The parasitic capacitance affects the pixel electrode voltage by changing the voltage of a sub-pixel electrode applied with a high voltage, thereby changing the luminance of the sub-pixel electrode. Consequently, vertical cross-talk is generated, which deteriorates the image quality of the LCD. Such vertical cross-talk can be particularly pronounced when a column inversion driving is performed.

[0010] Accordingly, there is a need for an LCD that has a minimized occurrence of vertical cross-talk as well as a sufficient aperture ratio.

SUMMARY OF THE INVENTION

[0011] An exemplary embodiment of the present invention provides a liquid crystal display including a substrate, a plurality of pixel electrodes formed on the substrate wherein each of the pixel electrodes includes a first and a second sub-pixel electrode, and a plurality of first data lines formed on the substrate, wherein a first data line of the plurality of first data lines does not overlap a first sub-pixel electrode and partially overlaps a second sub-pixel electrode of a pixel electrode of the plurality of pixel electrodes.

[0012] The first data line may include a first portion not overlapping the first sub-pixel electrode and a second portion partially overlapping the second sub-pixel electrode, and the first and second portions may be curved to each other.

[0013] The second portion of the first data line may include a third portion overlapping the second sub-pixel electrode and a fourth portion not overlapping the second sub-pixel electrode.

[0014] The third and the fourth portions of the first data line may be curved to each other.

[0015] The first data line may be connected to the first sub-pixel electrode.

[0016] The liquid crystal display may further include a second data line that is adjacent to the first data line.

[0017] The second data line may be disposed apart from the pixel electrode.

[0018] The second data line may not overlap the pixel electrode.

[0019] The second data line may include a first portion adjacent to the first sub-pixel electrode and a second portion adjacent to the second sub-pixel electrode.

[0020] A part of the second portion of the second data line may overlap the second sub-pixel electrode.

[0021] The second data line may be connected to the pixel electrode.

[0022] The second data line may include a first portion adjacent to the first sub-pixel electrode and a second portion adjacent to the second sub-pixel electrode, and a part of the second portion may overlap the second sub-pixel electrode.

[0023] The second data line may not overlap the pixel electrode.

[0024] Each of the first and second sub-pixel electrodes may include at least one parallelogrammic electrode piece, each parallelogrammic electrode piece having lengthwise edges and oblique edges that are adjacent to the lengthwise edges.

[0025] At least one lengthwise edge of the parallelogrammic electrode pieces of the first and second sub-pixel electrodes may adjoin each other.

[0026] At least one oblique edge of each of the parallelogrammic electrode pieces of the first and second sub-pixel electrodes may meet each other at right angles.

[0027] The liquid crystal display may further include a tilt direction determining member formed at the first and second sub-pixel electrodes.

[0028] The tilt direction determining member may include a plurality of cutouts that have oblique edges which are substantially parallel to the oblique edges of the parallelogrammic electrode pieces.

[0029] Each of the first and the second sub-pixel electrodes may include a first and a second edge that are substantially parallel to the first data line, and a third and a fourth edge that are perpendicular to the first and second edges.

[0030] A height of the first sub-pixel electrode may be different from a height of the second sub-pixel electrode.

[0031] The first sub-pixel electrode and the second sub-pixel electrode may be adjacent to each other.

[0032] A transverse center-line of the first sub-pixel electrode and a transverse center-line of the second sub-pixel electrode may be aligned with each other.

[0033] A voltage of the first sub-pixel electrode and a voltage of the second sub-pixel electrode may be different from each other.

[0034] An area of the first sub-pixel electrode may be smaller than an area of the second sub-pixel electrode, and a voltage of the first sub-pixel electrode may be higher than a voltage of the second sub-pixel electrode.

[0035] The first sub-pixel electrode and the second sub-pixel electrode may be applied with different data voltages, the different data voltages may be obtained from the same image information.

[0036] The liquid crystal display may further include a first thin film transistor connected to the first sub-pixel electrode and a second thin film transistor connected to the second sub-pixel electrode, and a gate line connected to the first and second thin film transistors.

[0037] The liquid crystal display may further include a first storage electrode line and a second storage electrode line that are parallel to the gate line.

[0038] The first thin film transistor may include a first drain electrode overlapping the first storage electrode line and the second thin film transistor may include a second drain electrode overlapping the second storage electrode line.

[0039] The liquid crystal display may further include a first thin film transistor connected to the first sub-pixel electrode, a second thin film transistor connected to the second sub-pixel electrode, a first gate line connected to the first thin film transistor, and a second gate line connected to the second thin film transistor.

[0040] The first and second thin film transistors may be turned on in response to signals from the first and second gate lines, respectively, and transmit signals from the first data line.

[0041] The liquid crystal display may further include a first thin film transistor connected to the first sub-pixel electrode and the first data line, a second thin film transistor connected to the second sub-pixel electrode, a second data line connected to the second thin film transistor, and a gate line connected to the first and second thin film transistors and intersecting the first and second data lines.

[0042] The first and second thin film transistors may be turned on in response to signals from the gate line, and transmit signals from the first and second data lines, respectively.

[0043] The liquid crystal display may further include a first storage electrode line and a second storage electrode line that are parallel to the gate line.

[0044] The first thin film transistor may include a first drain electrode overlapping the first storage electrode line,

and the second thin film transistor includes a second drain electrode overlapping the second storage electrode line.

BRIEF DESCRIPTION OF THE DRAWINGS

[0045] FIG. 1 is a block diagram of a liquid crystal display (LCD) according to an exemplary embodiment of the present invention;

[0046] FIG. 2 is an equivalent circuit diagram of two sub-pixels of an LCD according to an exemplary embodiment of the present invention;

[0047] FIG. 3 is an equivalent circuit diagram of a pixel of a liquid crystal (LC) panel assembly according to an exemplary embodiment of the present invention;

[0048] FIG. 4 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention;

[0049] FIG. 5 and FIG. 6 are cross-sectional views of the LC panel assembly illustrated in FIG. 4 taken along line V-V' and line VI-VI', respectively;

[0050] FIG. 7A and FIG. 7B are plan views of a pixel electrode of an LCD according to an exemplary embodiment of the present invention;

[0051] FIG. 8 is a graph illustrating a gamma curve of an LCD according to an exemplary embodiment of the present invention;

[0052] FIG. 9 is a graph illustrating luminance change ratios according to grays when a voltage is changed by a predetermined amount at a first sub-pixel electrode of an LCD according to an exemplary embodiment of the present invention;

[0053] FIG. 10 is a graph illustrating luminance change ratios according to grays when a voltage is changed by a predetermined amount at a second sub-pixel electrode of an LCD according to an exemplary embodiment of the present invention;

[0054] FIG. 11 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention;

[0055] FIG. 12 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention;

[0056] FIG. 13 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention;

[0057] FIG. 14 is a cross-sectional view of the LC panel assembly illustrated in

[0058] FIG. 13 taken along line X IV- X IV';

[0059] FIG. 15 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention;

[0060] FIG. 16 is an equivalent circuit diagram of a pixel of an LC panel assembly according to an exemplary embodiment of the present invention;

[0061] FIG. 17 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention;

[0062] FIG. 18 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention;

[0063] FIG. 19 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention;

[0064] FIG. 20 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention;

[0065] FIG. 21 is a block diagram of an LCD according to an exemplary embodiment of the present invention;

[0066] FIG. 22 is an equivalent circuit diagram of a pixel of an LC panel assembly according to an exemplary embodiment of the present invention;

[0067] FIG. 23 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention;

[0068] FIG. 24 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention;

[0069] FIG. 25 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention;

[0070] FIG. 26 is a cross-sectional view of the LC panel assembly illustrated in FIG. 25 taken along line X X VI-X X VI; and

[0071] FIG. 27 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

[0072] The present invention will be described more fully hereinafter with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown. The present invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein.

[0073] It will be understood that when an element such as a layer, film, region, or substrate is referred to as being “on” another element, it can be directly on the other element or intervening elements may also be present.

[0074] A liquid crystal display (LCD) according to an exemplary embodiment of the present invention will be described in detail with reference to FIG. 1 and FIG. 2.

[0075] FIG. 1 is a block diagram of an LCD according to an exemplary embodiment of the present invention, and FIG. 2 is an equivalent circuit diagram of two sub-pixels of an LCD according to an exemplary embodiment of the present invention.

[0076] As shown in FIG. 1, the LCD includes an LC panel assembly 300, a gate driver 400 and a data driver 500 that are connected to the LC panel assembly 300, a gray voltage generator 800 connected to the data driver 500, and a signal controller 600 for controlling the gate driver 400 and the data driver 500.

[0077] The LC panel assembly 300 includes a plurality of signal lines (not shown), and a plurality of pixels PX connected to the signal lines and arranged substantially in a matrix. The LC panel assembly 300 includes lower and upper panels 100 and 200 that face each other with an LC layer 3 interposed therebetween, as shown in FIG. 2.

[0078] The signal lines include a plurality of gate lines (not shown) for transmitting gate signals (also referred to as “scanning signals”) and a plurality of data lines (not shown) for transmitting data signals. The gate lines extend substantially in a row direction and are substantially parallel to each other, and the data lines extend substantially in a column direction and are substantially parallel to each other.

[0079] Each pixel PX includes a pair of sub-pixels, and each sub-pixel includes an LC capacitor Clca or Clcb. At least one of the two sub-pixels includes a switching element (not shown) connected to a gate line, a data line, and the LC capacitor Clca or Clcb.

[0080] The LC capacitor Clca/Clcb includes a sub-pixel electrode PEa/PEb provided on the lower panel 100 and a common electrode CE provided on the upper panel 200 as its two terminals, and the LC layer 3 disposed between the sub-pixel electrode PEa/PEb and the common electrode CE functions as a dielectric of the LC capacitor Clca/Clcb. The sub-pixel electrodes PEa and PEb are separated from each other and together form a pixel electrode PE. The common electrode CE is supplied with a common voltage Vcom and covers an entire surface of the upper panel 200. The LC layer 3 has negative dielectric anisotropy, and LC molecules in the LC layer 3 may be oriented so that long axes of the LC molecules are substantially perpendicular to the two panels 100 and 200 in the absence of an electric field.

[0081] To implement color display, each pixel PX uniquely displays one of the primary colors (e.g., spatial division) or each pixel PX sequentially displays the primary colors in time (e.g., temporal division) such that the spatial or temporal sum of the primary colors is recognized as a desired color. An example of a set of the primary colors includes red, green, and blue colors. FIG. 2 shows an example of the spatial division in which each pixel PX includes a color filter CF representing one of the primary colors in an area of the upper panel 200. Unlike that shown in FIG. 2, the color filter CF may be provided on or under the sub-pixel electrode PEa/PEb provided on the lower panel 100.

[0082] Polarizers (not shown) are provided on the outer surface of the panels 100 and 200, and polarization axes of two polarizers may be perpendicular to each other. One of the two polarizers may be omitted when the LCD is a reflective LCD. In the case of perpendicular polarizers, light that is incident to the LC layer 3 in the absence of an electric field cannot pass through the polarizer.

[0083] Referring to FIG. 1 again, the gray voltage generator 800 generates a plurality of gray voltages (or reference gray voltages) related to the transmittance of the pixels PX. However, the gray voltage generator 800 may generate only a given number of gray voltages instead of generating all of the gray voltages.

[0084] The gate driver 400 is connected to the gate lines of the LC panel assembly 300 and synthesizes a gate-on

voltage V_{on} and a gate-off voltage V_{off} from an external device to generate gate signals V_g for application to the gate lines.

[0085] The data driver **500** is connected to the data lines of the LC panel assembly **300**, and applies data voltages V_d , which are selected from the gray voltages supplied from the gray voltage generator **800**, to the data lines. However, in the case when the gray voltage generator **800** supplies only reference gray voltages of a predetermined number instead of supplying voltages for all grays, the data driver **500** divides the reference gray voltages to generate gray voltages for all grays, from which data signals are selected.

[0086] Each of the elements **400**, **500**, **600**, and **800** mentioned above may be directly mounted on the LC panel assembly **300** in the form of at least one integrated circuit (IC) chip. The IC chip may be mounted on a flexible printed circuit film (not shown) in a tape carrier package (TCP) type that is attached to the LC panel assembly **300**, or the IC chip may be mounted on a separate printed circuit board (not shown). On the other hand, each of the elements **400**, **500**, **600**, and **800** may be integrated into the LC panel assembly **300**. Also, the elements **400**, **500**, **600**, and **800** may be integrated into a single chip, and in this case, at least one thereof or at least one circuit element forming them may be located outside of the single chip.

[0087] Now, the operation of the LCD will be described in further detail.

[0088] The signal controller **600** is supplied with input image signals R, G, and B and input control signals for controlling the display thereof from an external graphics controller (not shown). The input image signals R, G and B include luminance information of each pixel PX, and the luminance information has a predetermined number of, for example, 1024 ($=2^{10}$), 256 ($=2^8$), or 64 ($=2^6$) grays. The input control signals include, for example, a vertical synchronization signal V_{sync} , a horizontal synchronization signal H_{sync} , a main clock signal MCLK, and a data enable signal DE.

[0089] On the basis of the input control signals and the input image signals R, G, and B, the signal controller **600** processes the input image signals R, G, and B for operating the LC panel assembly **300** and generates gate control signals CONT1 and data control signals CONT2. Then, the signal controller **600** transmits the gate control signals CONT1 to the gate driver **400** and transmits the processed image signals DAT and the data control signals CONT2 to the data driver **500**. The output image signals DAT are digital signals having a predetermined number of values (or grays).

[0090] The gate control signals CONT1 include a scanning start signal STV for instructing scanning to start and at least one clock signal for controlling the output time of the gate-on voltage V_{on} . The gate control signals CONT1 may further include an output enable signal OE for defining the duration of the gate-on voltage V_{on} .

[0091] The data control signals CONT2 include a horizontal synchronization start signal STH for indicating a start of image data transmission for a packet of sub-pixels, a load signal LOAD for instructing the data signals to be applied to the LC panel assembly **300**, and a data clock signal HCLK. The data control signal CONT2 may further include an

inversion signal RVS for reversing the polarity of the data signals with respect to the common voltage V_{com} (hereinafter, "polarity of the data signals with respect to the common voltage V_{com} " is referred to as "polarity of the data signals").

[0092] Responding to the data control signals CONT2 from the signal controller **600**, the data driver **500** sequentially receives the digital image signals DAT for the packet of sub-pixels, selects gray voltages corresponding to respective digital image signals DAT, converts the digital image signals DAT into analog data signals, and applies the analog data signals to corresponding data lines.

[0093] The gate driver **400** applies the gate-on voltage V_{on} to the gate lines in response to the gate control signals CONT1 from the signal controller **600**, thereby turning on the switching elements connected to the gate lines. Then, data signals applied to the data lines are applied to corresponding sub-pixels through the turned-on switching elements.

[0094] Here, when a first sub-pixel electrode **191a** and a second sub-pixel electrode **191b** forming a pixel electrode **191** are coupled to respective switching elements, in other words, each sub-pixel has its own switching element, the two sub-pixels may be supplied with respective data voltages V_d at different times through the same data line or through different data lines or at the same time through different data lines. On the other hand, when the first sub-pixel electrode **191a** is connected to a switching element (not shown) and the second sub-pixel electrode **191b** is capacitively coupled to the first sub-pixel electrode **191a**, only the first sub-pixel electrode **191a** is supplied with data voltages V_d through the switching element, and the second sub-pixel electrode **191b** is supplied with voltages that are dependent on the voltages supplied to the first sub-pixel electrode **191a**. Here, the voltage of the first sub-pixel electrode **191a** having a relatively small area is higher than the voltage of the second sub-pixel electrode **191b** having a relatively large area.

[0095] In this way, when the voltage difference is generated across the first or second LC capacitor C_{lca} or C_{lcb} , a primary electric field that is substantially perpendicular to the surfaces of the panels **100** and **200** is generated in the LC layer **3**. The pixel electrode **191** and a common electrode **270** may be together referred to as "field generating electrodes". Then, the LC molecules in the LC layer **3** tilt in response to the electric field such that their long axes become perpendicular to the electric field direction, and the degree of the tilt of the LC molecules determines the change of the polarization of light that is incident to the LC layer **3**. This change of the light polarization causes a change of light transmittance through the polarizers, and thus, the LCD displays images.

[0096] The tilt angle of the LC molecules depends on the strength of the electric field. Since the voltages of the two LC capacitors C_{lca} and C_{lcb} are different from each other, the tilt angles of the LC molecules are also different from each other, and thus, the luminances of the two sub-pixels are different from each other. Therefore, the voltage of the first LC capacitor C_{lca} and the voltage of the second LC capacitor C_{lcb} can be adjusted so that an image viewed from a lateral side is similar to an image viewed from the front,

in other words, a lateral gamma curve can be made to be similar to a frontal gamma curve, thereby improving the lateral visibility.

[0097] Also, when the area of the first sub-pixel electrode **191a** applied with a higher voltage is formed to be smaller than the area of the second sub-pixel electrode **191b**, the lateral gamma curve further approaches the frontal gamma curve. Particularly, when the area ratio of the first and the second sub-pixel electrodes **191a** and **191b** is approximately 1:2 to 1:3 as illustrated in FIG. 4 to FIG. 7B, the lateral gamma curve is much more similar to the frontal gamma curve, thereby further improving the lateral visibility.

[0098] By repeating this procedure for a horizontal period (which is denoted as “1H” and is equal to one period of the horizontal synchronization signal Hsync and the data enable signal DE), all pixels PX are applied with data signals, thereby displaying an image for a frame.

[0099] When the next frame starts after one frame is finished, the inversion signal RVS applied to the data driver **500** is controlled such that the polarity of the data signals applied to each pixel PX is reversed to be opposite to the polarity in the previous frame (which is referred to as “frame inversion”). Here, even during one frame, the polarity of the data signal flowing in a data line may vary in accordance with the characteristics of the inversion signal RVS (which is referred to as “row inversion” and/or “dot inversion”), or the polarities of the data signals applied to a packet of pixels may be different from each other (which is referred to as “column inversion” and/or “dot inversion”).

[0100] Now, a structure of an LC panel assembly according to an exemplary embodiment of the present invention will be described in detail with reference to FIG. 3 to FIG. 15 along with FIG. 1 and FIG. 2 described above.

[0101] FIG. 3 is an equivalent circuit diagram of a pixel of an LC panel assembly according to an exemplary embodiment of the present invention.

[0102] Referring to FIG. 3, an LC panel assembly includes signal lines including a plurality of gate lines GL, a plurality of pairs of data lines DL_a and DL_b, and a plurality of storage electrode lines SL and a plurality of pixels PX connected to the signal lines.

[0103] Each pixel PX includes a pair of sub-pixels PX_a and PX_b, and each sub-pixel PX_a/PX_b includes a switching element Ga/Gb that is respectively connected to a corresponding gate line GL and a data line DL_a/DL_b, an LC capacitor Cl_{ca}/Cl_{cb} that is connected to the switching element Q_a/Q_b, and a storage capacitor C_{sta}/C_{stb} that is connected to the switching element Q_a/Q_b and the storage electrode line SL.

[0104] Each switching element Q_a/Q_b including a thin film transistor (TFT) is a three-terminal element provided on the lower panel **100**, and it has a control terminal connected to a gate line GL, an input terminal connected to a data line DL_a/DL_b, and an output terminal connected to an LC capacitor Cl_{ca}/Cl_{cb} and a storage capacitor C_{sta}/C_{stb}.

[0105] The storage capacitor C_{sta}/C_{stb} that functions as an auxiliary capacitor for the LC capacitor Cl_{ca}/Cl_{cb} is formed by overlapping a storage electrode line SL that is provided on the lower panel **100** with a sub-pixel electrode PX_a/PX_b via an insulator disposed therebetween, and the

storage electrode line SL is supplied with a predetermined voltage such as the common voltage V_{com}. Alternatively, the storage capacitors C_{sta} and C_{stb} may be formed by overlapping the sub-pixel electrodes PX_a and PX_b with a previous gate line directly thereabove via an insulator.

[0106] Here, a detailed description of the LC capacitors Cl_{ca} and Cl_{cb}, which were described above, will be omitted.

[0107] In an LCD including this LC panel assembly, the signal controller **600** may receive input image signals R, G and B for a pixel PX and convert them into output image signals DAT for two sub-pixels PX_a and PX_b, which are transmitted to the data driver **500**. On the other hand, separate sets of gray voltages for the two sub-pixels PX_a and PX_b may be generated by the gray voltage generator **800**, wherein the sets of gray voltages are alternately applied to the data driver **500** or alternately selected by the data driver **500**, thereby applying different voltages to the two sub-pixels PX_a and PX_b. However, it is preferable to compensate the image signals or generate sets of gray voltages such that the merged gamma curve of the two sub-pixels PX_a and PX_b is close to the frontal reference gamma curve. For example, the frontal merged gamma curve is made to accord with the frontal reference gamma curve that is determined to be appropriate for the LC panel assembly, and the lateral merged gamma curve is made to be similar to the frontal reference gamma curve.

[0108] Now, an example of the LC panel assembly illustrated in FIG. 3 will be described in detail with reference to FIG. 4 to FIG. 10 along with FIG. 1 and FIG. 2 described above.

[0109] FIG. 4 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention, FIG. 5 and FIG. 6 are cross-sectional views of the LC panel assembly illustrated in FIG. 4 taken along line V-V and line VI-VI respectively, and FIG. 7A and FIG. 7B are top plan views of an electrode piece of the respective sub-pixel electrodes illustrated in FIG. 4 to FIG. 6.

[0110] Referring to FIG. 4 to FIG. 6, the LC panel assembly includes a lower panel **100** and an upper panel **200** opposing each other and an LC layer **3** interposed between the two panels **100** and **200**.

[0111] First, the lower panel **100** will be described in detail.

[0112] A plurality of gate conductors including a plurality of gate lines **121** and a plurality of pairs of first and second storage electrode lines **131a** and **131b** are formed on an insulating substrate **110** that is preferably made of transparent glass or plastic.

[0113] The gate lines **121** for transmitting gate signals extend substantially in a transverse direction. Each of the gate lines **121** includes a plurality of pairs of first and second gate electrodes **124a** and **124b** protruding upward and downward and an end portion **129** having a large area for connection with another layer or the gate driver **400**. When the gate driver **400** is integrated into the substrate **110**, the gate lines **121** may be extended to be directly connected to the gate driver **400**.

[0114] The storage electrode lines **131a** and **131b** are supplied with a predetermined voltage such as a common voltage V_{com} and extend substantially in a transverse direc-

tion. The first and the second storage electrode lines **131a** and **131b** are disposed above and below the gate line **121**, respectively. Each storage electrode line **131a** and **131b** includes a plurality of pairs of first and second storage electrodes **137a** and **137b** extending upward and downward. However, the shape and arrangement of the storage electrode lines **131a** and **131b** including the storage electrodes **137a** and **137b** may be modified in various ways.

[0115] The gate conductors **121**, **131a**, and **131b** may be made of an aluminum (Al) containing metal such as Al and an Al alloy, a silver (Ag) containing metal such as Ag and a Ag alloy, a copper (Cu) containing metal such as Cu and a Cu alloy, a molybdenum (Mo) containing metal such as Mo and a Mo alloy, chromium (Cr), tantalum (Ta), and titanium (Ti). Alternatively, the gate conductors **121**, **131a**, and **131b** may have a multi-layered structure including two conductive layers (not shown) having different physical properties. One of the two conductive layers is preferably made of a low resistivity metal such as an Al-containing metal, a Ag-containing metal, or a Cu-containing metal for reducing signal delay or voltage drop. On the other hand, the other conductive layer is preferably made of a material such as a Mo-containing metal, Cr, Ti, and Ta, which has good physical, chemical, and electrical contact characteristics with other materials such as indium tin oxide (ITO) and indium zinc oxide (IZO). Examples of the combination of two layers include a pair of a lower Cr layer and an upper Al (alloy) layer and a pair of a lower Al (alloy) layer and an upper Mo (alloy) layer. However, the gate conductors **121**, **131a**, and **131b** may be made of many various metals or conductors.

[0116] The lateral sides of the gate conductors **121**, **131a**, and **131b** are inclined relative to a surface of the substrate **110**, and the preferable inclination angle thereof ranges from about 30 degrees to about 80 degrees.

[0117] A gate insulating layer **140** preferably made of silicon nitride (SiNx) or silicon oxide (SiOx) is formed on the gate conductors **121**, **131a**, and **131b**.

[0118] A plurality of first and second semiconductor islands **154a** and **154b** preferably made of hydrogenated amorphous silicon (a-Si) or polysilicon are formed on the gate insulating layer **140**. The first and second semiconductor islands **154a** and **154b** are disposed on the first and second gate electrodes **124a** and **124b**, respectively.

[0119] A pair of ohmic contact islands (not shown) is formed on each of the first semiconductor islands **154a**, and a pair of ohmic contact islands **163b** and **165b** are formed on each of the second semiconductor islands **154b**. The ohmic contacts **163b** and **165b** are preferably made of n⁺hydrogenated a-Si heavily doped with an n-type impurity such as phosphorus (P) or silicide.

[0120] The lateral sides of the semiconductors **154a** and **154b** and the ohmic contacts **163b** and **165b** are also inclined relative to a surface of the substrate **110**, and the preferable inclination angle thereof ranges from about 30 degrees to about 80 degrees.

[0121] A plurality of data conductors including a plurality of pairs of data lines **171a** and **171b** and a plurality of pairs of first and second drain electrodes **175a** and **175b** are formed on the ohmic contacts **163b** and **165b** and the gate insulating layer **140**.

[0122] The first and the second data lines **171a** and **171b** for transmitting data signals extend substantially in the longitudinal direction, and intersect the gate lines **121** and the storage electrode lines **131a** and **131b**. Each data line **171a** and **171b** is curved once midway. Each of the data lines **171a** and **171b** includes a plurality of pairs of first and second source electrodes **173a** and **173b** branched out toward the first and second gate electrodes **124a** and **124b** and an end portion **179a** and **179b** having a large area for connection with another layer or a data driver **500**. When the data driver **500** is integrated into the substrate **110**, the data lines **171a** and **171b** may be extended to be directly connected to the data driver **500**.

[0123] The first and the second drain electrodes **175a** and **175b** are separated from each other and are also separated from the data lines **171a** and **171b**. The first/second drain electrode **175a/175b** opposes the first/second source electrode **173a/173b** with respect to the first/second gate electrode **124a/124b** and includes an end portion **177a/177b** having a large area and another stick-shaped end portion. The two end portions **177a** and **177b** having a large area overlap the first and second storage electrodes **137a** and **137b**, respectively, and the stick-shaped end portions are partially surrounded by the first and second source electrodes **173a** and **173b** that are curved. Also, each of the first and the second drain electrode **175a** and **175b** includes a branch **178a** and **178b** extending parallel to the gate line **121**, respectively. The branches **178a** and **178b** maintain the symmetry of the pixel PX.

[0124] The first/second gate electrode **124a/124b**, the first/second source electrode **173a/173b**, and the first/second drain electrode **175a/175b**, along with the first/second semiconductor **154a/154b**, form a first/second TFT Qa/Qb having a channel formed in the first/second semiconductor **154a/154b** disposed between the first/second source electrode **173a/173b** and the first/second drain electrode **175a/175b**. The first/second TFT Qa/Qb is disposed on the left/right side of the data line **171a/171b**, respectively.

[0125] The data conductors **171a**, **171b**, **175a**, and **175b** are preferably made of a refractory metal such as Mo, Cr, Ta, and Ti or an alloy thereof. Also, the data line **171** and the drain electrode **175** may have a multi-layered structure including a refractory metal layer (not shown) and a conductive layer (not shown) having low resistivity. An example of the multi-layered structure includes double layers of a lower Cr or Mo (alloy) layer and an upper Al (alloy) layer, and triple layers of a lower Mo (alloy) layer, an intermediate Al (alloy) layer, and an upper Mo (alloy) layer. However, the data conductors **171a**, **171b**, **175a**, and **175b** may be made of many various metals or conductive materials.

[0126] The lateral sides of the data conductors **171a**, **171b**, **175a**, and **175b** are also inclined relative to a surface of the substrate **110**, and the inclination angles thereof are preferably in a range of about 30 degrees to about 80 degrees.

[0127] The ohmic contacts **163b** and **165b** are interposed only between the underlying semiconductors **154a** and **154b** and the overlying data conductors **171a**, **171b**, **175a**, and **175b** thereon and reduce the contact resistance therebetween. The semiconductors **154a** and **154b** include exposed portions that are not covered with the data conductors **171a**, **171b**, **175a**, and **175b** such as portions located between the source electrodes **173a** and **173b** and the drain electrodes **175a** and **175b**.

[0128] A passivation layer 180 is formed on the data conductors 171a, 171b, 175a, 175b and the exposed portions of the semiconductors 154a and 154b. The passivation layer 180 is preferably made of an inorganic insulator or an organic insulator and the surface thereof may be flat. The organic insulator may have photosensitivity and the preferable dielectric constant thereof is lower than about 4.0. However, the passivation layer 180 may have a double-layered structure including a lower inorganic layer and an upper organic layer so as not to harm the exposed portions of the semiconductors 154a and 154b and to take advantage of the excellent insulating characteristics of an organic layer.

[0129] The passivation layer 180 has a plurality of contact holes 182, 185a, and 185b respectively exposing the end portions 179a and 179b of the data lines 171a and 171b and the large end portions 177a and 177b of the first and second drain electrodes 175a and 175b and the passivation layer 180 and the gate insulating layer 140 have a plurality of contact holes 181 respectively exposing the end portions 129 of the gate lines 121.

[0130] A plurality of pixel electrodes 191 and a plurality of contact assistants 81, 82a, and 82b are formed on the passivation layer 180. These may be made of a transparent conductor such as ITO or IZO, or a reflective metal such as Al, Ag, Cr, or an alloy thereof.

[0131] Each of the pixel electrodes 191 opposes a color filter CF that is formed on the upper panel 200 and represents one of the primary colors such as the three primary colors of red (R), green (G), and blue (B), respectively. Each pixel electrode 191 includes a pair of first and second sub-pixel electrodes 191a and 191b that are separated from each other.

[0132] Each of the first and the second sub-pixel electrode 191a and 191b includes at least one parallelogrammic electrode piece 196 as illustrated in FIG. 7A and one parallelogrammic electrode piece 197 as illustrated in FIG. 7B.

[0133] As shown in FIG. 7A and FIG. 7B each of the electrode pieces 196 and 197 has a pair of oblique edges 196o and 197o and a pair of lengthwise edges 196t and 197t and substantially has a shape of a parallelogram. Each oblique edge 196o and 197o forms an oblique angle with the lengthwise edges 196t and 197t, and the preferable oblique angle ranges from about 45 degrees to about 135 degrees. Hereinafter, for convenience sake, the shape of the electrode piece 196 and 197 is classified according to its direction of inclination (e.g. an "inclination direction") from a perpendicular state with respect to the lengthwise edges 196t and 197t, and it is referred to as "right-inclined" when the inclination direction is rightward as shown in FIG. 7A and as "left-inclined" when the inclination direction is leftward as shown in FIG. 7B.

[0134] The distance between the lengthwise edges 196t and 197t of the electrode pieces 196 and 197, in other words, the width W, and the distance between the oblique edges 196o and 197o, in other words, the height H, may be determined in accordance with the size of the LC panel assembly 300. Also, the lengthwise edges 196t and 197t of each electrode piece 196 and 197 may be modified, for example, to be curved or projected, when considering their relationships with other parts.

[0135] Each of the first and the second sub-pixel electrode 191a and 191b has a shape formed by connecting parallelogrammic electrode pieces 196 and 197 having different inclination directions from each other in a row direction. One lengthwise edge 196t or 197t of each of the parallelogrammic electrode pieces 196 and 197 adjoins each other. One oblique edge 196o or 197o of each of the parallelogrammic electrode pieces 196 and 197 meets each other making an oblique angle with each other, and the oblique angle thereof is preferably about 90 degrees.

[0136] The first and second sub-pixel electrodes 191a and 191b are adjacent to each other in a column direction. The height H2 of the second sub-pixel electrode 191b is more than the height H1 of the first sub-pixel electrode 191a by about 1.1 times to about 2 times. The width W2 of the second sub-pixel electrode 191b is a little more than the width W1 of the first sub-pixel electrode 191a. Accordingly, the area of the second sub-pixel electrode 191b is larger than the area of the first sub-pixel electrode 191a by about 1.5 times to about 2 times. However, the present invention is not limited to this size, and the height H1 and H2 and the width W1 and W2 of the first and second sub-pixel electrodes 191a and 191b may be adjusted to obtain a desired area ratio, preferably about 1:1.1 to 1:3.

[0137] In this way, each of the first and the second sub-pixel electrode 191a and 191b has a shape that is curved in the horizontal direction once. As a result, it becomes easier to form a region for three pixel electrodes 191 corresponding to color filters CF representing the three primary colors of red (R), green (G), and blue (B), respectively. Also, it is easy to adjust the overlapped area with the data lines 171a and 171b.

[0138] The first sub-pixel electrode 191a has a cutout 91, and the second sub-pixel electrode has cutouts 92 and 93. Each of the cutouts 91, 92, and 93 includes two oblique edges that are substantially parallel to the oblique edges 196o and 197o of the parallelogrammic electrode pieces 196 and 197 forming the first and second sub-pixel electrodes 191a and 191b. The number, shape, and arrangement of the cutouts 91, 92, and 93 may be modified in various ways.

[0139] The first and second sub-pixel electrodes 191a and 191b are divided into a plurality of sub-regions with respect to the cutouts 91, 92, and 93. Each of the sub-regions includes two primary edges defined by the oblique edges of the cutouts 91, 92, and 93 and the oblique edges 196o and 197o of the electrode pieces 196 and 197.

[0140] The edges of the sub-pixel electrodes 191a and 191b and the cutouts 91, 92, and 93 of the electric field-generating electrodes 191 and 270 distort the primary electric field and give it a horizontal component, which initially determines the tilt directions of the LC molecules. The horizontal component of the primary electric field is perpendicular to the edges of the sub-pixel electrodes 191a and 191b and the edges of the cutouts 91, 92, and 93.

[0141] Since the LC molecules on each sub-area divided by the cutouts 91, 92, 93 substantially tilt vertically to the primary edges, the azimuthal distribution of the tilt directions is localized to four directions. In this way, if tilt directions of the LC molecules are numerous, the reference viewing angle of the LCD is increased.

[0142] Meanwhile, the direction of a secondary electric field that is generated due to the voltage difference between

the sub-pixel electrodes **191a** and **191b** is perpendicular to each of the primary edges of the sub-areas. Accordingly, the direction of the secondary electric field coincides with that of the horizontal component of the primary electric field. Consequently, the secondary electric field between the sub-pixel electrodes **191a** and **191b** enhances the determination of the tilt directions of the LC molecules.

[0143] The first sub-pixel electrodes **191a** are connected to each of the first drain electrodes **175a** through the contact holes **185a**, and the second sub-pixel electrodes **191b** are connected to each of the second drain electrodes **175b** through the contact holes **185b**.

[0144] The first sub-pixel electrode **191a** does not overlap the first and second data lines **171a** and **171b**, and the second sub-pixel electrode **191b** overlaps the first and second data lines **171a** and **171b** via the passivation layer **180** interposed therebetween. Each of the first and the second data line **171a** and **171b** includes a first portion **171a1** and **171b1** that is adjacent to but does not overlap the first sub-pixel electrode **191a** and a second portion **171a2** and **171b2** overlapping the second sub-pixel electrode **191b**. The first portion **171a1/171b1** and the second portion **171a2/171b2** are curved to each other.

[0145] Hereinafter, the overlapping relationship between the data lines **171a** and **171b** and the pixel electrode **191** will be described in detail with reference to FIG. 8 to FIG. 10.

[0146] FIG. 8 is a graph illustrating a gamma curve of a pixel electrode for each gray. FIG. 9 is a graph illustrating total luminance change ratios according to voltage changes of a first sub-pixel electrode **191a**, and FIG. 10 is a graph illustrating total luminance change ratios according to voltage changes of a second sub-pixel electrode **191b**.

[0147] Parasitic capacitances are generated between the data lines **171a** and **171b** and the pixel electrode **191**. The pixel electrode voltage is affected by varying parasitic capacitances. Since the first sub-pixel electrode **191a** and the second sub-pixel electrode **191b** are applied with different voltages, the luminance change ratios of the first sub-pixel electrode **191a** and the second sub-pixel electrode **191b** are different even though the pixel electrode voltage is varied by the same amount according to the parasitic capacitances.

[0148] Referring to FIG. 8, a gamma curve **31** of a first sub-pixel electrode, a gamma curve **32** of a second sub-pixel electrode, and an average gamma curve **30** of a pixel electrode for each gray are illustrated. In the low grays where luminance varies sensitively in response to a small change of voltage, the voltage change ratio of the first sub-pixel electrode is great while the voltage change ratio of the second sub-pixel electrode is almost zero. In the high grays where luminance does not vary sensitively in response to a voltage change, the voltage change ratio of the first sub-pixel electrode is small while the voltage change ratio of the second sub-pixel electrode is great.

[0149] When described again referring to FIG. 9 and FIG. 10, the luminance change ratio of the first sub-pixel electrode **191a** in the low grays comes up to about 9%. On the other hand, the luminance change ratio of the second sub-pixel electrode **191b** in the low grays is nearly 0% since it is in an off state while the luminance change ratio thereof increases when going up to the high grays. However, the luminance change ratio of the second sub-pixel electrode

191b in the high grays is maximally about 0.45%, which is very small compared to the luminance change ratio of the first sub-pixel electrode **191a**.

[0150] Therefore, like that shown in FIG. 4 the first sub-pixel electrode **191a**, which has a sensitive luminance change ratio, does not overlap the data lines **171a** and **171b**, thereby preventing a luminance change due to a parasitic capacitance. Also, the data lines **171a** and **171b** overlap the second sub-pixel electrode **191b**, which has a relatively insensitive luminance change ratio, thereby ensuring a sufficient aperture ratio.

[0151] Referring to FIG. 4 again, the storage electrode lines **131a** and **131b**, the large end portions **177a** and **177b** of the drain electrodes **175a** and **175b**, and the contact holes **185a** and **185b** are located on the transverse center-line of the sub-pixel electrodes **191a** and **191b**. A straight line connecting the curve points of the sub-pixel electrodes **191a** and **191b** is the boundary of the sub-areas described above, where the arrangements of the LC molecules are disordered to yield texture. Therefore, the aperture ratio can be improved while blocking the texture.

[0152] The first/second sub-pixel electrode **191a/191b** and the common electrode **270** provided on the upper panel **200** along with the LC layer **3** disposed therebetween form a first/second LC capacitor **Clca/Clcb** respectively to store applied voltages even after the TFT **Qa/Qb** is turned off.

[0153] A first/second sub-pixel electrode **191a/191b** and a first/second drain electrode **175a/175b** connected thereto overlap a storage electrode **137a/137b** via the gate insulating layer **140** interposed therebetween to form a first/second storage capacitor **Csta/Cstb**, and the first/second storage capacitor **Csta/Cstb** enhances the voltage storing capacity of the first/second LC capacitor **Clca/Clcb**.

[0154] The contact assistants **81** and **82** are connected to the end portion **129** of the gate line **121** and the end portion **179** of the data line **171** through the contact holes **181** and **182**, respectively. The contact assistants **81** and **82** supplement the adhesive property of the end portions **129** of the gate lines **121** and the end portions **179** of the data lines **171** to exterior devices, and protect them.

[0155] Next, the description of the upper panel **200** follows.

[0156] A light blocking member **220** is formed on an insulating substrate **210** that is preferably made of transparent glass or plastic. The light blocking member **220** includes curved portions facing the curved edges of the pixel electrodes **191** and quadrilateral portions facing the TFTs, and the light blocking member **220** defines opening areas opposed to the pixel electrodes **191a** and also prevents the leakage of light between the pixel electrodes **191**.

[0157] A plurality of color filters **230** are also formed on the substrate **210** and the light blocking member **220**. The color filters **230** are disposed substantially in the areas enclosed by the light blocking member **220** and may extend in a longitudinal direction substantially along the pixel electrodes **191**. Each of the color filters **230** may represent one of the primary colors such as red, green, and blue.

[0158] An overcoat **250** is formed on the color filters **230** and the light blocking member **220**. The overcoat **250** is preferably made of an organic insulator and it prevents the

color filters **230** from being exposed and also provides a flat surface. The overcoat **250** may be omitted.

[0159] A common electrode **270** is formed on the overcoat **250**. The common electrode **270** is preferably made of a transparent conductive material such as ITO and IZO, and it may have a plurality of cutouts (not shown).

[0160] Alignment layers **11** and **21** are coated on inner surfaces of the panels **100** and **200**, and they may be homeotropic.

[0161] Polarizers **12** and **22** are provided on outer surfaces of the panels **100** and **200** and their polarization axes may be perpendicular to each other, with one of the polarization axes preferably parallel to the gate lines **121**. One of the polarizers **12** and **22** may be omitted when the LCD is a reflective LCD.

[0162] The LCD may include a backlight unit (not shown) for supplying light to the polarizers **12** and **22**, a retardation film, the panels **100** and **200**, and the LC layer **3**.

[0163] The LC layer **3** is in a state of negative dielectric anisotropy, and the LC molecules in the LC layer **3** are aligned such that their long axes are substantially vertical to the surfaces of the panels **100** and **200** in the absence of an electric field.

[0164] Cutouts **91**, **92**, and **93** may be substituted by protrusions (not shown) or depressions (not shown).

[0165] The protrusions may be made of an organic or inorganic material and may be disposed on or under the field-generating electrodes **191** and **270**.

[0166] Next, another example of the LC panel assembly illustrated in FIG. 3 will be described in detail with reference to FIG. 11.

[0167] FIG. 11 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention.

[0168] Referring to FIG. 11, the LC panel assembly includes a lower panel (not shown), an upper panel (not shown), and an LC layer (not shown) interposed therebetween.

[0169] The layered structure of the LC panel assembly according to the present exemplary embodiment is similar to the layered structure of the LC panel assembly illustrated in FIG. 4 to FIG. 6.

[0170] Regarding the lower panel, a plurality of gate conductors including a plurality of gate lines **121** and a plurality of pairs of storage electrode lines **131a** and **131b** are formed on an insulating substrate (not shown). Each of the gate lines **121** includes first and second gate electrodes **124a** and **124b** and an end portion **129**. A gate insulating layer (not shown) is formed on the gate conductors **121**, **131a**, and **131b**. A plurality of semiconductors **154a** and **154b** are formed on the gate insulating layer, and a plurality of ohmic contacts (not shown) are formed thereon. Data conductors including a plurality of data lines **171a** and **171b** and a plurality of first and second drain electrodes **175a** and **175b** are formed on the ohmic contacts. Each of the data lines **171a** and **171b** includes a plurality of first and second source electrodes **173a** and **173b** and an end portion **179a** and **179b**, and the drain electrodes **175a** and **175b** include

end portions **177a** and **177b** having a large area. A passivation layer (not shown) is **5,0** formed on the data conductors **171a**, **171b**, **175a**, and **175b** and exposed portions of the semiconductors **154a** and **154b**, and the passivation layer and the gate insulating layer have a plurality of contact holes **181**, **182a**, **182b**, **185a**, and **185b**. A plurality of pixel electrodes **191** including first and second sub-pixel electrodes **191a** and **191b** and a plurality of contact assistants **81**, **82a** and **82b** are formed on the passivation layer. An alignment layer (not shown) is formed on the pixel electrodes **191**, the contact assistants **81**, **82a**, and **82b**, and the passivation layer.

[0171] Regarding the upper panel, a light blocking member, a common electrode, and an alignment layer are formed on an insulating substrate.

[0172] However, in the LC panel assembly according to the present exemplary embodiment, unlike the LC panel assembly illustrated in FIG. 4 to FIG. 6, the shape of the first and second data lines **171a** and **171b** are different from each other. The first data line **171a** is curved once so that a portion thereof does not overlap the first sub-pixel electrode **191a** and another portion thereof does overlap the second sub-pixel electrode **191b**, like the LC panel assembly illustrated in FIG. 4. However, the second data line **191b** extends straight to overlap neither of the first and second sub-pixel electrodes **191a** and **191b**.

[0173] In this way, by overlapping only one of a pair of data lines **171a** and **171b** with the second sub-pixel electrode **191b**, the luminance change ratio according to a voltage change of a pixel electrode **191** is further minimized, thereby preventing vertical cross-talk.

[0174] Numerous characteristics of the LC panel assembly illustrated in FIG. 4 to FIG. 6 may also be applied to the LC panel assembly illustrated in FIG. 11.

[0175] Next, another example of the LC panel assembly illustrated in FIG. 3 will be described in detail with reference to FIG. 12.

[0176] FIG. 12 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention.

[0177] Referring to FIG. 12, the LC panel assembly includes a lower panel (not shown) and an upper panel (not shown) and an LC layer (not shown) interposed therebetween.

[0178] The layered structure of the LC panel assembly according to the present exemplary embodiment is similar to the layered structure of the LC panel assembly illustrated in FIG. 4 to FIG. 6.

[0179] Regarding the lower panel, a plurality of gate conductors including a plurality of gate lines **121** and a plurality of pairs of storage electrode lines **131a** and **131b** are formed on an insulating substrate (not shown). Each of the gate lines **121** includes first and second gate electrodes **124a** and **124b** and an end portion **129**. A gate insulating layer (not shown) is formed on the gate conductors **121**, **131a**, and **131b**. A plurality of semiconductors **154a** and **154b** are formed on the gate insulating layer, and a plurality of ohmic contacts (not shown) are formed thereon. Data conductors including a plurality of data lines **171a** and **171b** and a plurality of first and second drain electrodes **175a** and

175b are formed on the ohmic contacts. Each of the data lines **171a** and **171b** includes a plurality of first and second source electrodes **173a** and **173b** and an end portion **179a** and **179b**, and the drain electrodes **175a** and **175b** include end portions **177a** and **177b** having a large area. A passivation layer (not shown) is formed on the data conductors **171a**, **171b**, **175a**, and **175b** and exposed portions of the semiconductors **154a** and **154b**, and the passivation layer and the gate insulating layer have a plurality of contact holes **181**, **182a**, **182b**, **185a**, and **185b**. A plurality of pixel electrodes **191** including first and second sub-pixel electrodes **191a** and **191b** and a plurality of contact assistants **81**, **82a**, and **82b** are formed on the passivation layer. An alignment layer (not shown) is formed on the pixel electrodes **191**, the contact assistants **81**, **82a**, and **82b**, and the passivation layer.

[**0180**] Regarding the upper panel a light blocking member, a common electrode **270**, and an alignment layer are formed on an insulating substrate.

[**0181**] However, the shape of the pixel electrode **191** of the LC panel assembly according to the present exemplary embodiment is different from that of the LC panel assembly illustrated in FIG. 4 to FIG. 6.

[**0182**] Each of the first and the second sub-pixel electrode **191a** and **191b** includes a pair of first edges **191a1** and **191b1** that are substantially parallel to the gate line **121** and a pair of second edges **191a2** and **191b2** that are substantially parallel to the data lines **171a** and **171b**. In other words, each of the first and the second sub-pixel electrode **191a** and **191b** has a substantially quadrangular shape.

[**0183**] The height of the first sub-pixel electrode **191a** is less than that of the second sub-pixel electrode **191b**, and the width of the first sub-pixel electrode **191a** is a little less than that of the second sub-pixel electrode **191b**. The height and the width of the first and second sub-pixel electrodes **191a** and **191b** may be adjusted to obtain a desired area ratio. Also, the first and second sub-pixel electrodes **191a** and **191b** are adjacent to each other in the column direction.

[**0184**] In the LC panel assembly in FIG. 12, the LC layer **3** has positive dielectric anisotropy, and the LC molecules in the LC layer **3** are aligned such that their major axes are substantially parallel to the two panels in the absence of an electric field. When an electric field is generated between the pixel electrode **191** and the common electrode **270** that are applied with voltages, the LC molecules in the LC layer **3** are aligned parallel to the electric field.

[**0185**] Numerous characteristics of the LC panel assembly illustrated in FIG. 4 to FIG. 6 may be also applied to the LC panel assembly illustrated in FIG. 12.

[**0186**] Next, another example of the LC panel assembly illustrated in FIG. 3 will be described in detail with reference to FIG. 13 and FIG. 14.

[**0187**] FIG. 13 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention, and FIG. 14 is a cross-sectional view of the LC panel assembly illustrated in FIG. 13 taken along line X-IV-X IV.

[**0188**] Referring to FIG. 13 and 14, the LC panel assembly includes a lower panel **100**, an upper panel **200**, and an LC layer **3** interposed therebetween.

[**0189**] The layered structure of the LC panel assembly according to the present exemplary embodiment is similar to the layered structure of the LC panel assembly illustrated in FIG. 4 to FIG. 6.

[**0190**] Regarding the lower panel **100**, a plurality of gate conductors including a plurality of gate lines **121** and a plurality of pairs of storage electrode lines **131a** and **131b** are formed on an insulating substrate **110**. Each of the gate lines **121** includes first and second gate electrodes **124a** and **124b** and an end portion **129**. A gate insulating layer **140** is formed on the gate conductors **121**, **131a**, and **131b**. A plurality of semiconductors **154a** and **154b** are formed on the gate insulating layer **140**, and a plurality of ohmic contacts **163a** and **165a** are formed thereon. Data conductors including a plurality of data lines **171a** and **171b** and a plurality of first and second drain electrodes **175a** and **175b** are formed on the ohmic contacts. Each of the data lines **171a** and **171b** includes a plurality of first and second source electrodes **173a** and **173b** and an end portion **179a** and **179b**, and the drain electrodes **175a** and **175b** include end portions **177a** and **177b** having a large area. The shape of the data line **171a** and **171b** is the same as that of the data lines **171a** and **171b** of the LC panel assembly illustrated in FIG. 11. A passivation layer **180** is formed on the data conductors **171a**, **171b**, **175a**, and **175b** and exposed portions of the semiconductors **154a** and **154b**, and the passivation layer **180** and the gate insulating layer **140** have a plurality of contact holes **181**, **182a**, **182b**, **185a**, and **185b**. A plurality of pixel electrodes **191** including first and second sub-pixel electrodes **191a** and **191b** and a plurality of contact assistants **81**, **82a**, and **82b** are formed on the passivation layer **180**. The shape of the pixel electrode **191** in the LC panel assembly according to the present exemplary embodiment is the same as that of the pixel electrode **191** in the LC panel assembly illustrated in FIG. 12. An alignment layer **11** is formed on the pixel electrodes **191**, the contact assistants **81**, **82a**, and **82b**, and the passivation layer **180**.

[**0191**] Regarding the upper panel **200**, a light blocking member **220**, a common electrode **270**, and an alignment layer **21** are formed on an insulating substrate **210**.

[**0192**] However, in the LC panel assembly according to the present exemplary embodiment, unlike the LC panel assembly illustrated in FIG. 4 to FIG. 6, there is no color filter on the upper panel **200**, and instead, a plurality of color filters **230** are formed under the passivation layer **180** in the lower panel **100**.

[**0193**] The color filters **230** are periodically curved along the column of the pixel electrodes **191** and extend in the longitudinal direction, and they do not exist in peripheral regions where the end portions **129** of the gate lines **121** and the end portions **179** of the data lines **171** are disposed. A contact hole **185a** passes through a color filter **230** and a penetrating hole **235** that is bigger than the contact hole **185a** is formed in the color filter **230**.

[**0194**] Adjacent color filters **230** may overlap each other on the data line **171** to function as a light blocking member that blocks light leakage between adjacent pixel electrodes **191**. In this case, the light blocking member on the upper panel **200** may be omitted.

[**0195**] A passivation layer (not shown) may be also provided under the color filters **230**.

[0196] Also, the semiconductors **154a** and **154b** in the LC panel assembly according to the present exemplary embodiment are extended along the data lines **171a** and **171b** to form semiconductor stripes (not shown), and the ohmic contacts **163a** and **165a** are extended along the data lines **171a** and **171b** to form ohmic contact stripes **161**.

[0197] Numerous characteristics of the LC panel assembly illustrated in FIG. 4 to FIG. 6 may be also applied to the LC panel assembly illustrated in FIG. 13 and FIG. 14.

[0198] Next, another example of the LC panel assembly illustrated in FIG. 3 will be described in detail with reference to FIG. 15.

[0199] FIG. 15 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention.

[0200] Referring to FIG. 15, the LC panel assembly includes a lower panel (not shown) and an upper panel (not shown) and an LC layer (not shown) interposed therebetween.

[0201] The layered structure of the LC panel assembly according to the present exemplary embodiment is similar to the layered structure of the LC panel assembly illustrated in FIG. 4 to FIG. 6.

[0202] Regarding the lower panel, a plurality of gate conductors including a plurality of gate lines **121** and a plurality of pairs of storage electrode lines **131a** and **131b** are formed on an insulating substrate (not shown). Each of the gate lines **121** includes first and second gate electrodes **124a** and **124b** and an end portion **129**. A gate insulating layer (not shown) is formed on the gate conductors **121**, **131a**, and **131b**. A plurality of semiconductors **154a** and **154b** are formed on the gate insulating layer, and a plurality of ohmic contacts (not shown) is formed thereon. Data conductors including a plurality of data lines **171a** and **171b** and a plurality of first and second drain electrodes **175a** and **175b** are formed on the ohmic contacts. Each of the data lines **171a** and **171b** includes a plurality of first and second source electrodes **173a** and **173b** and an end portion **179a** and **179b**, and the drain electrodes **175a** and **175b** include end portions **177a** and **177b** having a large area. A passivation layer (not shown) is formed on the data conductors **171a**, **171b**, **175a**, and **175b** and exposed portions of the semiconductors **154a** and **154b**, and the passivation layer and the gate insulating layer have a plurality of contact holes **181**, **182a**, **182b**, **185a**, and **185b**. A plurality of pixel electrodes **191** including first and second sub-pixel electrodes **191a** and **191b** and a plurality of contact assistants **81**, **82a**, and **82b** are formed on the passivation layer. An alignment layer (not shown) is formed on the pixel electrodes **191**, the contact assistants **81**, **82a**, and **82b**, and the passivation layer.

[0203] Regarding the upper panel, a light blocking member, a common electrode, and an alignment layer are formed on an insulating substrate.

[0204] However, in the LC panel assembly according to the present exemplary embodiment, auxiliary electrodes **191** are formed on both sides of the first sub-pixel electrode **191a**. A pair of data lines **171a** and **171b** extend along gaps **195** between the auxiliary electrode **191a** and the first

sub-pixel electrode **191a**, so the first sub-pixel electrode **191a** and a pair of data lines **171a** and **171b** do not overlap each other.

[0205] Accordingly, even when the first sub-pixel electrode **191a** shifts to the left or right, there is no difference between the parasitic capacitances generated between a pair of data lines **171a** and **171b** and the first sub-pixel electrode **191a**. Therefore, there is no need to accurately adjust the distances between the first sub-pixel electrode **191a** and a pair of data lines **171a** and **171b**. Next, an LC panel assembly according to an exemplary embodiment of the present invention will be described in detail with reference to FIG. 16 to FIG. 20 along with FIG. 1 and FIG. 2 described above.

[0206] FIG. 16 is an equivalent circuit diagram of a pixel of an LC panel assembly according to an exemplary embodiment of the present invention.

[0207] Referring to FIG. 16, an LC panel assembly includes signal lines including a plurality of pairs of gate lines GLa and GLb, a plurality of data lines DL, and a plurality of storage electrode lines SL, and a plurality of pixels PX connected to the signal lines.

[0208] Each pixel PX includes a pair of sub-pixels PXa and PXb, and each sub-pixel PXa/PXb includes a switching element Qa/Qb that is respectively connected to a corresponding gate line GLa/GLb and a data line DL, an LC capacitor Clca/Clcb that is connected to the switching element Qa/Qb, and a storage capacitor Csta/Cstb that is connected to the switching element Qa/Qb and the storage electrode line SLa/SLb.

[0209] Each switching element Qa/Qb including a TFT is also a three-terminal element provided on the lower panel **100**, and it has a control terminal connected to a gate line GLa/GLb, an input terminal connected to a data line DL, and an output terminal connected to an LC capacitor Clca/Clcb and a storage capacitor Csta/Cstb.

[0210] The LC capacitors Clca and Clcb, the storage capacitors Csta and Cstb, and the operation of an LCD including the above LC panel assembly are substantially the same as those of FIG. 3, so detailed descriptions thereof will be omitted. However, in the LC panel assembly illustrated in FIG. 3, two sub-pixels PXa and PXb forming a pixel PX are applied with data voltages at the same time, but in the present exemplary embodiment, the two sub-pixels PXa and PXb are applied with data voltages at a different time.

[0211] Now, an example of the LC panel assembly illustrated in FIG. 16 will be described in detail with reference to FIG. 17.

[0212] FIG. 17 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention.

[0213] Referring to FIG. 17, the LC panel assembly includes a lower panel (not shown) and an upper panel (not shown) opposing each other and an LC layer (not shown) interposed between the two panels.

[0214] The layered structure of the LC panel assembly according to the present exemplary embodiment is similar to the layered structure of the LC panel assembly illustrated in FIG. 4 to FIG. 6.

[0215] Regarding the lower panel, a plurality of gate conductors including a plurality of pairs of gate lines **121a** and **121b** and a plurality of storage electrode lines **131** are formed on an insulating substrate (not shown). The gate lines **121a** and **121b** include first and second gate electrodes **124a** and **124b** and end portions **129a** and **129b**, respectively. A gate insulating layer (not shown) is formed on the gate conductors **121a**, **121b**, and **131**. A plurality of semiconductors **154a** and **154b** are formed on the gate insulating layer, and a plurality of ohmic contacts (not shown) are formed thereon. Data conductors including a plurality of data lines **171** and a plurality of first and second drain electrodes **175a** and **175b** are formed on the ohmic contacts. Each data line **171** includes a plurality of first and second source electrodes **173a** and **173b** and an end portion **179**, and the drain electrodes **175a** and **175b** respectively include end portions **177a** and **177b** having a large area. A passivation layer (not shown) is formed on the data conductors **171**, **175a**, and **175b** and exposed portions of the semiconductors **154a** and **154b**, and the passivation layer and the gate insulating layer have a plurality of contact holes **181a**, **181b**, **182**, **185a**, and **185b**. A plurality of pixel electrodes **191** including first and second sub-pixel electrodes **191a** and **191b** and a plurality of contact assistants **81a**, **81b**, and **82** are formed on the passivation layer. An alignment layer (not shown) is formed on the pixel electrodes **191**, the contact assistants **81a**, **81b**, and **82**, and the passivation layer.

[0216] Regarding the upper panel, a light blocking member, a common electrode, and an alignment layer are formed on an insulating substrate.

[0217] However in the LC panel assembly according to the present exemplary embodiment, the number of gate lines **121a** and **121b** is twice and the number of data lines **171** is half compared to the LC panel assembly illustrated in FIG. 4 to FIG. 6. Here a pair of gate lines **121a** and **121b** is repeatedly disposed in the same manner.

[0218] In addition, the first and second TFTs Qa and Qb connected to the first and second sub-pixel electrodes **191a** and **191b** forming a pixel electrode **191** are connected to the same data line **171** and different gate lines **121a** and **121b**.

[0219] The first and second TFTs Qa and Qb are located on the left side of the data line **171**, respectively,

[0220] The data lines **171** of the LC panel assembly illustrated in FIG. 17 are the same as the data lines **171a** and **171b** of the LC panel assembly illustrated in FIG. 4. The data lines **171** includes a data line **171m** (referred to as a "self data line") connected to the first and second sub-pixel electrodes **191a** and **191b** via the TFTs Qa and Qb, and a data line **171o** (referred to as an "adjacent data line") not connected to the first and second sub-pixel electrodes **191a** and **191b** but connected to the adjacent pixel electrode **191**. The self data line **171m** includes a first portion **171m1** not overlapping the first sub-pixel electrode **191a** and a second portion **171m2** overlapping the second sub-pixel electrode **191b**. The adjacent data line **171o** includes a first portion **171o1** and a second portion **171o2** that are curved to each other, and neither of these portions **171o1** and **171o2** overlap the first and second sub-pixel electrodes **191a** and **191b**.

[0221] Numerous characteristics of the LC panel assembly illustrated in FIG. 4 to FIG. 6 may also be applied to the LC panel assembly illustrated in FIG. 17.

[0222] Now, other examples of the LC panel assembly illustrated in FIG. 16 will be described in detail with reference to FIG. 18 to FIG. 20.

[0223] FIG. 18 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention. FIG. 19 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention, and FIG. 20 is a layout view of an LC panel assembly according to an exemplary embodiment of the present invention.

[0224] Referring to FIG. 18, FIG. 19, and FIG. 20, respectively, the LC panel assembly includes a lower panel (not shown) and an upper panel (not shown) opposing each other and an LC layer (not shown) interposed between the two panels.

[0225] The layered structure of the LC panel assembly according to the present exemplary embodiments is similar to the layered structure of the LC panel assembly illustrated in FIG. 4 to FIG. 6.

[0226] Regarding the lower panel, a plurality of gate conductors including a plurality of pairs of gate lines **121a** and **121b** and a plurality of storage electrode lines **131** are formed on an insulating substrate (not shown). The gate lines **121a** and **121b** include first and second gate electrodes **124a** and **124b** and end portions **129a** and **129b**, respectively. A gate insulating layer (not shown) is formed on the gate conductors **121a**, **121b**, and **131**. A plurality of semiconductors **154a** and **154b** are formed on the gate insulating layer, and a plurality of ohmic contacts (not shown) is formed thereon. Data conductors including a plurality of data lines **171** and a plurality of first and second drain electrodes **175a** and **175b** are formed on the ohmic contacts. Each data line **171** includes a plurality of first and second source electrodes **173a** and **173b** and an end portion **179**, and the drain electrodes **175a** and **175b** respectively include end portions **177a** and **177b** having a large area. A passivation layer (not shown) is formed on the data conductors **171**, **175a**, and **175b** and exposed portions of the semiconductors **154a** and **154b**, and the passivation layer and the gate insulating layer have a plurality of contact holes **181a**, **181b**, **182**, **185a**, and **185b**. A plurality of pixel electrodes **191** including first and second sub-pixel electrodes **191a** and **191b** and a plurality of contact assistants **81a**, **81b**, and **82** are formed on the passivation layer. An alignment layer (not shown) is formed on the pixel electrodes **191**, the contact assistants **81a**, **81b**, and **82**, and the passivation layer.

[0227] Regarding the upper panel a light blocking member, a common electrode, and an alignment layer are formed on an insulating substrate.

[0228] However, in the LC panel assembly illustrated in FIG. 18, unlike the LC panel assembly of FIG. 17, the self data line **171m** is curved twice where it is adjacent to a pixel electrode **191**. In other words, the self data line **171m** includes a first portion **171m1** that is adjacent to but does not overlap the first sub-pixel electrode **191a** and a second portion **171m2** that is adjacent to the second sub-pixel electrode **191b**. The second portion **171m2** includes a third portion **171m3** overlapping the second sub-pixel electrode **191b** and a fourth portion **171m4** not overlapping the second sub-pixel electrode **191b**.

[0229] The adjacent data line **171o** is also curved twice where it is adjacent to a pixel electrode **191**. In other words,

the adjacent data line **171o** includes a first portion **171o1** that is adjacent to but does not overlap the first sub-pixel electrode **191a** and a second portion **171o2** that is adjacent to the second sub-pixel electrode **191b**. The second portion **171o2** also includes a third portion **171o3** and a fourth portion **171o4** that are curved to each other. The fourth portion **171o4** overlaps the second sub-pixel electrode **191b**.

[0230] In this way, data lines **171** are curved twice through a pixel electrode **191**, thereby minimizing occurrence of vertical cross-talk.

[0231] In the LC panel assembly illustrated in FIG. **19**, unlike the LC panel assembly of FIG. **17**, the shape of the pixel electrode **191** is the same as that of the pixel electrode **191** in the LC panel assembly of FIG. **12**. The shape of the data lines **171** is the same as that of the data lines **171** in the LC panel assembly illustrated in FIG. **17**.

[0232] In the LC panel assembly illustrated in FIG. **20**, the shape of the data lines **171** is the same as that of the data lines **171** in the LC panel assembly of FIG. **18**, and the shape of the pixel electrode **191** is the same as that of the pixel electrode **191** in the LC panel assembly of FIG. **12**.

[0233] Numerous characteristics of the LC panel assembly illustrated in FIG. **4** to FIG. **6** may be also applied to the LC panel assembly illustrated in FIG. **18** to FIG. **20**.

[0234] Now, an LCD according to an exemplary embodiment of the present invention will be described in detail with reference to FIG. **21** and FIG. **22**.

[0235] FIG. **21** is a block diagram of an LCD according to an exemplary embodiment of the present invention, and FIG. **22** is an equivalent circuit diagram of a pixel of an LC panel assembly according to an exemplary embodiment of the present invention.

[0236] Referring to FIG. **21** and FIG. **22**, the LCD includes an LC panel assembly **300**, a gate driver **400**, a data driver **500**, and a storage electrode driver **700** that are connected to the LC panel assembly **300**, a gray voltage generator **800** connected to the data driver **500**, and a signal controller **600** controlling the gate driver **400**, the data driver **500** and the storage electrode driver **700**.

[0237] The LC panel assembly **300** includes a plurality of signal lines G_1 - G_n and D_1 - D_m , and a plurality of pixels PX connected thereto and arranged in approximately a matrix. The LC panel assembly **300** includes lower and upper panels **100** and **200** opposing each other and an LC layer **3** interposed therebetween, as shown in FIG. **2**.

[0238] The signal lines G_1 - G_n and D_1 - D_m include a plurality of gate lines G_1 - G_n for transmitting gate signals (also referred to as "scanning signals"), a plurality of data lines D_1 - D_m for transmitting data signals, and a plurality of pairs of first and second storage electrode lines SLa and SLb for transmitting storage electrode signals. The gate lines G_1 - G_n extend substantially in the row direction and are substantially parallel to each other, and the data lines D_1 - D_m extend substantially in the column direction and are substantially parallel to each other.

[0239] The LC panel assembly **300** includes signal lines including a plurality of gate lines GL, a plurality of data lines DL, and a plurality of pairs of storage electrode lines SLa and SLb and a plurality of pixels PX connected to the signal lines.

[0240] Each pixel PX includes a pair of sub-pixels PXa and PXb, and each sub-pixel PXa/PXb includes a switching element Q that is connected to a corresponding gate line GL and data line DL, a first/second LC capacitor Clca/Clcb connected to the switching element Q and a first/second storage capacitor Csta/Cstb connected to the switching element Q and the storage electrode line SLa/SLb, respectively.

[0241] The switching element Q including a TFT is also a three-terminal element provided on the lower panel **100**, and it has a control terminal connected to a gate line GL, an input terminal connected to a data line DL, and an output terminal connected to an LC capacitor Clca/Clcb and a storage capacitor Csta/Cstb.

[0242] The first LC capacitor Clca includes a first sub-pixel electrode **191a** provided on a lower panel **100** and a common electrode **270** provided on an upper panel **200** as its two terminals, and the second LC capacitor Clcb includes a second sub-pixel electrode **191b** provided on the lower panel **100** and the common electrode **270** provided on the upper panel **200** as its two terminals. An LC layer **3** disposed between the electrodes **191** and **270** functions as a dielectric of the LC capacitors Clca and Clcb. The first and second sub-pixel electrodes **191a** and **191b** are connected to the TFT Q in common. The common electrode **270** is formed on the entire surface of the upper panel **200** and is supplied with a common voltage Vcom.

[0243] The first storage capacitor Csta is formed by overlapping a first storage electrode line SLa provided on the lower panel **100** with a first sub-pixel electrode **191a** via an insulator disposed therebetween, and the second storage capacitor Cstb is formed by overlapping a second storage electrode line SLb provided on the lower panel **100** with a second sub-pixel electrode **191b** via an insulator disposed therebetween. The first and second storage electrode lines SLa and SLb are supplied with storage electrode signals Vsta and Vstb.

[0244] Now, this LC panel assembly **300** will be described in detail with reference to FIG. **23**.

[0245] Referring to FIG. **23**, the LC panel assembly according to an exemplary embodiment of the present invention also includes a lower panel (not shown) and an upper panel (not shown) opposing each other and an LC layer (not shown) interposed between the two panels.

[0246] The layered structure of the LC panel assembly according to the present exemplary embodiment is similar to the layered structure of the LC panel assembly illustrated in FIG. **4** to FIG. **6**.

[0247] Regarding the lower panel, a plurality of gate conductors including a plurality of gate lines **121** and a plurality of pairs of storage electrode lines **131a** and **131b** are formed on an insulating substrate (not shown). Each gate line **121** includes gate electrodes **124** and an end portion **129**. A gate insulating layer (not shown) is formed on the gate conductors **121**, **131a** and **131b**. A plurality of semi-conductors **154** are formed on the gate insulating layer, and a plurality of ohmic contacts (not shown) are formed thereon. Data conductors including a plurality of data lines **171** and a plurality of first and second drain electrodes **175a** and **175b** are formed on the ohmic contacts. Each data line **171** includes a plurality of source electrodes **173** and an end portion **179**, and the drain electrodes **175a** and **175b** include

end portions **177a** and **177b** having a large area. A passivation layer (not shown) is formed on the data conductors **171**, **175a**, and **175b** and exposed portions of the semiconductors **154**, and the passivation layer and the gate insulating layer have a plurality of contact holes **181**, **182**, **185a**, and **185b**. A plurality of pixel electrodes **191** including first and second sub-pixel electrodes **191a** and **191b** and a plurality of contact assistants **81** and **82** are formed on the passivation layer. An alignment layer (not shown) is formed on the pixel electrodes **191**, the contact assistants **81** and **82**, and the passivation layer.

[0248] Regarding the upper panel, a light blocking member, a common electrode, and an alignment layer are formed on an insulating substrate.

[0249] The LCD according to the present exemplary embodiment, unlike the LCD illustrated in FIG. 4 and FIG. 16, includes a gate line **121** and a data line **171** for each pixel, and a gate electrode **124**, a source electrode **173**, and a first drain electrode **175a**, along with a projection **154** of a semiconductor stripe, form a portion of a TFT Q having a channel formed in the projection **154** disposed between the source electrode **173** and the first drain electrode **175a**. Also, a gate electrode **124**, a source electrode **173**, and a second drain electrode **175b**, along with a projection **154** of a semiconductor stripe, form a portion of a TFT Q having a channel formed in the projection **154** disposed between the source electrode **173** and the second drain electrode **175b**.

[0250] Referring to FIG. 21 again, the gray voltage generator **800** generates two sets of a plurality of gray voltages (or reference gray voltages) related to the transmittance of the pixels PX. The gray voltages in one set have positive polarity with respect to the common voltage Vcom, while those in the other set have negative polarity with respect to the common voltage Vcom.

[0251] The gate driver **400** is connected to the gate lines G_1 - G_n of the LC panel assembly **300** and synthesizes a gate-on voltage Von and a gate-off voltage Voff to generate gate signals, which are applied to the gate lines G_1 - G_n .

[0252] The data driver **500** is connected to the data lines D_1 - D_m of the LC panel assembly **300** and selects gray voltages supplied from the gray voltage generator **800** and then applies the selected gray voltages to the data lines D_1 - D_m as data signals. However, in the case when the gray voltage generator **800** supplies only reference gray voltages of a predetermined number instead of supplying voltages for all grays, the data driver **500** divides the reference gray voltages to generate gray voltages for all grays, from which data signals are selected.

[0253] The storage electrode driver **700** is connected to the first and second storage electrode lines SLa and SLb, and applies a pair of storage electrode signals Vsta and Vstb having opposite phases to the first and second storage electrode lines SLa and SLb, respectively.

[0254] Each of the elements **400**, **500**, **600**, **700** and **800** mentioned above may be directly mounted on the LC panel assembly **300** in the form of at least one **20** integrated circuit (IC) chip. The IC chip may be mounted on a flexible printed circuit film (not shown) in a tape carrier package (TCP) type which is attached to the LC panel assembly **300**, or the IC chip may be mounted on a separate printed circuit board (not shown). On the other hand, the elements **400**, **500**, **600**, and

800 may be integrated into the LC panel assembly **300** along with the **27**, signal lines G_1 - G_n , D_1 - D_m , SLa, and SLb, and the TFT switching elements Q. Also, the elements **400**, **500**, **600**, and **800** may be integrated into a single chip, and in this case, at least one thereof or at least one circuit element forming these may be located outside of the single chip.

[0255] Now, the operation of the LCD will be described in further detail.

[0256] The signal controller **600** is supplied with input image signals R, G, and B and input control signals for controlling the display thereof from an external graphics controller (not shown). The input control signals include, for example, a vertical synchronization signal Vsync, a horizontal synchronization signal Hsync, a main clock signal MCLK, and a data enable signal DE.

[0257] On the basis of the input control signals and the input image signals R, G, and B, the signal controller **600** processes the input image signals R, G, and B for operating the LC panel assembly **300** and generates gate control signals CONT1, data control signals CONT2, and storage electrode control signals CONT3.

[0258] Then, the signal controller **600** transmits the gate control signals CONT1 to the gate driver **400**, the processed image signals DAT and the data control signals CONT2 to the data driver **500**, and the storage electrode control signals CONT3 to the storage electrode driver **700**.

[0259] The gate control signals CONT1 include a scanning start signal STV for instructing scanning to start and at least one clock signal for controlling the output time of the gate-on voltage Von. The gate control signals CONT1 may further include an output enable signal OE for defining the duration of the gate-on voltage Von.

[0260] The data control signals CONT2 include a horizontal synchronization start signal STH for indicating a start of image data transmission for a row of pixels PX, a load signal LOAD for instructing the data voltages to be applied to the data lines D_1 - D_m , and a data clock signal HCLK. The data control signal CONT2 may further include an inversion signal RVS for reversing the polarity of the data signals with respect to the common voltage Vcom.

[0261] The storage electrode driver **700** applies the first and second storage electrode signals Vsta and Vstb to the first and second storage electrode lines SLa and SLb respectively according to the storage electrode control signals CONT3 from the signal controller **600**. The first and second storage electrode signals Vsta and Vstb reverse periodically with respect to the common voltage Vcom and their phases are opposite to each other.

[0262] Responding to the data control signals CONT2 from the signal controller **600**, the data driver **500** sequentially receives the digital image signals DAT for a row of pixels PX, selects gray voltages corresponding to respective digital image signals DA, converts the digital image signals DAT into analog data signals, and applies the analog data signals to corresponding data lines D_1 - D_m .

[0263] The gate driver **400** applies the gate-on voltage Von to the gate lines G_1 - G_n in response to the gate control signals CONT1 from the signal controller **600**, thereby turning on the switching elements Q connected to the gate lines G_1 - G_n .

Then, the data signals applied to the data lines D_1 - D_m are applied to corresponding pixels PX through the turned-on switching elements Q.

[0264] The difference between the voltage of the data signal applied to a first sub-pixel electrode 191a and the common voltage Vcom appears as a charge voltage of the first LC capacitor Clc1, in other words, a first sub-pixel electrode voltage. Also, the difference between the voltage of the data signal applied to a second sub-pixel electrode 191b and the common voltage Vcom appears as a charge voltage of the second LC capacitor Clc2, in other words, a second sub-pixel electrode voltage.

[0265] When the switching element Q is turned off, the first and second sub-pixel electrodes 191a and 191b are in a floating state. However, since the first and second sub-pixel electrodes 191a and 191b form capacitors Csta and Cstb along with the first and second storage electrode lines 131a and 131b, respectively, the voltages of the first and second sub-pixel electrodes 191a and 191b vary according to a voltage change of the first and second storage electrode lines 131a and 131b. The average voltage of the second sub-pixel electrode 191b with respect to the common voltage Vcom may be higher than the average voltage of the first sub-pixel electrode 191a with respect to the common voltage Vcom by adjusting the polarities of the first and second storage electrode signals Vsta and Vstb.

[0266] Now, another example of the LC panel assembly of FIG. 21 will be described in detail with reference to FIG. 24 to FIG. 27.

[0267] FIG. 24, FIG. 25, and FIG. 27 are layout views illustrating an LC panel assembly according to various exemplary embodiments of the present invention, and FIG. 26 is a cross-sectional view of the LC panel assembly illustrated in FIG. 25 taken along line X X VI-X X VI.

[0268] Referring to FIG. 24, FIG. 25, FIG. 26, and FIG. 27, the LC panel assembly includes a lower panel 100 and an upper panel 200 opposing each other and an LC layer 3 interposed between the two panels 100 and 200.

[0269] The layered structure of the LC panel assembly according to the present exemplary embodiments is similar to the layered structure of the LC panel assembly illustrated in FIG. 4 to FIG. 6.

[0270] Regarding the lower panel 100, a plurality of gate conductors including a plurality of gate lines 121 and a plurality of pairs of storage electrode lines 131a and 131b are formed on an insulating substrate 110. Each gate line 121 includes gate electrodes 124 and an end portion 129. A gate insulating layer 140 is formed on the gate conductors 121, 131a and 131b. A plurality of semiconductors 154 are formed on the gate insulating layer 140, and a plurality of ohmic contacts 163a and 165a are formed thereon. Data conductors including a plurality of data lines 171 and a plurality of first and second drain electrodes 175a and 175b are formed on the ohmic contacts 163a and 165a. Each data line 171 includes a plurality of source electrodes 173 and an end portion 179, and the drain electrodes 175a and 175b respectively include end portions 177a and 177b having a large area. A passivation layer 180 is formed on the data conductors 171, 175a, and 175b and exposed portions of the semiconductors 154, and the passivation layer 180 and the gate insulating layer 140 have a plurality of contact holes

181, 182, 185a, and 185b. A plurality of pixel electrodes 191 including first and second sub-pixel electrodes 191a and 191b and a plurality of contact assistants 81 and 82 are formed on the passivation layer 180. An alignment layer 11 is formed on the pixel electrodes 191, the contact assistants 81 and 82, and the passivation layer 180.

[0271] Regarding the upper panel 200, a light blocking member 220, color filters 230, a common electrode 270, and an alignment layer 21 are formed on an insulating substrate 210.

[0272] However, in the LC panel assembly illustrated in FIG. 24, unlike the LC panel assembly of FIG. 23, the shape of the data lines 171 is the same as that of the data lines 171 of the LC panel assembly illustrated in FIG. 18.

[0273] In the LC panel assembly illustrated in FIG. 25 and FIG. 26, unlike the LC panel assembly of FIG. 23, the semiconductors 154 are extended along the data lines 171 and the drain electrodes 175a and 175b to form semiconductor stripes 151, and the ohmic contacts 163, 165a, and 165b are extended along the data lines 171 to form ohmic contact stripes 161. The semiconductor stripes 151 have substantially the same planar shapes as the data lines 171 and the drain electrodes 175a and 175b as well as the underlying ohmic contacts 163, 165a, and 165b.

[0274] In a manufacturing method of the LC panel assembly according to an exemplary embodiment of the present invention, the data lines 171, the drain electrodes 175a and 175b, the semiconductor stripes 151, and the ohmic contacts 163, 165a, and 165b are formed simultaneously using a photolithography process.

[0275] The photosensitive film used in the photolithography process has position-dependent thickness, and particularly, it includes first and second portions having thicknesses decreasing in sequence. The first portions of the photosensitive film are located on wiring regions occupied by the data lines 171 and the drain electrodes 175a and 175b, and the second portions are located on the channel regions of the TFTs.

[0276] The position-dependent thickness of the sensitive film is obtained by several techniques, for example, by providing translucent areas on an exposure mask as well as light transmitting areas and light blocking areas. The translucent areas may have a slit pattern, a lattice pattern, or a thin film(s) with intermediate transmittance or intermediate thickness. When using a slit pattern, it is preferable that the width of the slits or the distance between the slits is smaller than the resolution of a light exposer used for the photolithography process. Another example is to use a reflowable photosensitive film. In detail, after a photosensitive film pattern made of a reflowable material is formed by using a normal exposure mask with only light transmitting areas and light blocking areas, it is subjected to a reflow process to flow onto areas without the photosensitive film, thereby forming thin portions.

[0277] In this way, the manufacturing method is simplified because one photolithography process is omitted.

[0278] In the LC panel assembly of FIG. 27, unlike the LC panel assembly of FIG. 23, the shape of the pixel electrodes 191 and the shape of the data lines 171 are the same as those of the LC panel assembly of FIG. 20.

[0279] Numerous characteristics of the LC panel assembly illustrated in FIG. 4 to FIG. 6 may also be applied to the LC panel assembly illustrated in FIG. 24 to FIG. 27.

[0280] As described above, according to exemplary embodiments of the present invention, data lines partially overlap pixel electrodes, thereby preventing occurrence of vertical cross-talk by minimizing parasitic capacitances generated between the data lines and the pixel electrodes as well as ensuring a sufficient aperture ratio. Therefore the display quality of display devices can be improved.

[0281] While the present invention has been described in detail with reference to the exemplary embodiments, those skilled in the art will appreciate that various modifications and substitutions can be made thereto without departing from the spirit and scope of the present invention as set forth in the appended claims.

What is claimed is:

1. A liquid crystal display comprising:
 - a substrate;
 - a plurality of pixel electrodes formed on the substrate, each of the pixel electrodes including a first and a second sub-pixel electrode; and
 - a plurality of first data lines formed on the substrate, wherein a first data line of the plurality of first data lines does not overlap a first sub-pixel electrode and partially overlaps a second sub-pixel electrode of a pixel electrode of the plurality of pixel electrodes.
2. The liquid crystal display of claim 1, wherein the first data line includes a first portion not overlapping the first sub-pixel electrode and a second portion partially overlapping the second sub-pixel electrode, and
 - the first and the second portions are curved to each other.
3. The liquid crystal display of claim 2, wherein the second portion of the first data line includes a third portion overlapping the second sub-pixel electrode and a fourth portion not overlapping the second sub-pixel electrode.
4. The liquid crystal display of claim 3, wherein the third and fourth portions of the first data line are curved to each other.
5. The liquid crystal display of claim 1, wherein the first data line is connected to the first sub-pixel electrode.
6. The liquid crystal display of claim 1, further comprising an organic layer formed between the first data lines and the pixel electrodes.
7. The liquid crystal display of claim 1, further comprising a second data line that is adjacent to the first data line.
8. The liquid crystal display of claim 7, wherein the second data line is disposed apart from the pixel electrode.
9. The liquid crystal display of claim 8, wherein the second data line does not overlap the pixel electrode.
10. The liquid crystal display of claim 8, wherein the second data line includes a first portion adjacent to the first sub-pixel electrode and a second portion adjacent to the second sub-pixel electrode, and
11. The liquid crystal display of claim 10, wherein at least a part of the second portion of the second data line overlaps the second sub-pixel electrode.
12. The liquid crystal display of claim 7, wherein the second data line is connected to the pixel electrode.
13. The liquid crystal display of claim 12, wherein the second data line includes a first portion adjacent to the first sub-pixel electrode and a second portion adjacent to the second sub-pixel electrode, and
 - a part of the second portion overlaps the second sub-pixel electrode.
14. The liquid crystal display of claim 12, wherein the second data line does not overlap the pixel electrode.
15. The liquid crystal display of claim 7, further comprising an organic layer formed between the second data line and the pixel electrode.
16. The liquid crystal display of claim 1, wherein each of the first and the second sub-pixel electrodes includes at least one parallelogrammic electrode piece, the parallelogrammic electrode piece having lengthwise edges and oblique edges that are adjacent to the lengthwise edges.
17. The liquid crystal display of claim 16, wherein at least one lengthwise edge of each of the parallelogrammic electrode pieces of the first and second sub-pixel electrodes adjoin each other.
18. The liquid crystal display of claim 17, wherein at least one oblique edge of each of the parallelogrammic electrode pieces of the first and second sub-pixel electrodes meet each other at right angles.
19. The liquid crystal display of claim 18, further comprising a tilt direction determining member formed at the first and the second sub-pixel electrodes.
20. The liquid crystal display of claim 19, wherein the tilt direction determining member includes a plurality of cutouts that have oblique edges which are substantially parallel to the oblique edges of the parallelogrammic electrode pieces.
21. The liquid crystal display of claim 16, wherein a height of the first sub-pixel electrode is different from a height of the second sub-pixel electrode.
22. The liquid crystal display of claim 16, wherein the first sub-pixel electrode and the second sub-pixel electrode are adjacent to each other.
23. The liquid crystal display of claim 22, wherein a transverse center-line of the first sub-pixel electrode and a transverse center-line of the second sub-pixel electrode are aligned with each other.
24. The liquid crystal display of claim 1, wherein each of the first and second sub-pixel electrodes includes a first and a second edge that are substantially parallel to the first data line and a third and a fourth edge that are perpendicular to the first and second edges.
25. The liquid crystal display of claim 24, wherein a height of the first sub-pixel electrode is different from a height of the second sub-pixel electrode.
26. The liquid crystal display of claim 24, wherein the first sub-pixel electrode and the second sub-pixel electrode are adjacent to each other.
27. The liquid crystal display of claim 26, wherein a transverse center-line of the first sub-pixel electrode and a transverse center-line of the second sub-pixel electrode are aligned with each other.
28. The liquid crystal display of claim 1, wherein a voltage of the first sub-pixel electrode and a voltage of the second sub-pixel electrode are different.
29. The liquid crystal display of claim 28, wherein an area of the first sub-pixel electrode is smaller than an area of the second sub-pixel electrode, and a voltage of the first sub-pixel electrode is higher than a voltage of the second sub-pixel electrode.

30. The liquid crystal display of claim 29, wherein the first sub-pixel electrode and the second sub-pixel electrode are applied with different data voltages, and the different data voltages are obtained from the same image information.

31. The liquid crystal display of claim 30, further comprising:

- a first thin film transistor connected to the first sub-pixel electrode and a second thin film transistor connected to the second sub-pixel electrode; and

- a gate line connected to the first and second thin film transistors.

32. The liquid crystal display of claim 31, further comprising a first storage electrode line and a second storage electrode line that are parallel to the gate line.

33. The liquid crystal display of claim 32, wherein the first thin film transistor includes a first drain electrode overlapping the first storage electrode line and the second thin film transistor includes a second drain electrode overlapping the second storage electrode line.

34. The liquid crystal display of claim 31, further comprising:

- a first thin film transistor connected to the first sub-pixel electrode;

- a second thin film transistor connected to the second sub-pixel electrode;

- a first gate line connected to the first thin film transistor; and

- a second gate line connected to the second thin film transistor.

35. The liquid crystal display of claim 34, wherein the first and second thin film transistors are respectively turned on in response to signals from the first and second gate lines, and transmit signals from the first data line.

36. The liquid crystal display of claim 34, further comprising:

- a first thin film transistor connected to the first sub-pixel electrode and the first data line;

- a second thin film transistor connected to the second sub-pixel electrode;

- a second data line connected to the second thin film transistor; and

- a gate line connected to the first and second thin film transistors, the gate line intersecting the first and second data lines.

37. The liquid crystal display of claim 36, wherein the first and second thin film transistors are turned on in response to signals from the gate line, and respectively transmit signals from the first and second data lines.

38. The liquid crystal display of claim 36, further comprising a first storage electrode line and a second storage electrode line that are parallel to the gate line.

39. The liquid crystal display of claim 38, wherein the first thin film transistor includes a first drain electrode overlapping the first storage electrode line, and the second thin film transistor includes a second drain electrode overlapping the second storage electrode line.

* * * * *

专利名称(译)	液晶显示器		
公开(公告)号	US20070126944A1	公开(公告)日	2007-06-07
申请号	US11/565837	申请日	2006-12-01
[标]申请(专利权)人(译)	金东GYU LEE BACK WON 比克升洙		
申请(专利权)人(译)	金东GYU LEE背景 BAEK SEUNG-SOO		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KIM DONG GYU LEE BACK WON BAEK SEUNG SOO		
发明人	KIM, DONG-GYU LEE, BACK-WON BAEK, SEUNG-SOO		
IPC分类号	G02F1/136		
CPC分类号	G02F1/136286 G02F2001/134345		
优先权	1020050116790 2005-12-02 KR		
其他公开文献	US7705926		
外部链接	Espacenet USPTO		

摘要(译)

一种液晶显示器，包括基板，形成在基板上的多个像素电极，其中每个像素电极包括第一和第二子像素电极，以及形成在基板上的多条第一数据线，其中第一数据线为多条第一数据线不与第一子像素电极重叠，并且与多个像素电极的像素电极的第二子像素电极部分重叠。

