



US007436461B2

(12) **United States Patent**
Choi et al.

(10) **Patent No.:** **US 7,436,461 B2**
(45) **Date of Patent:** **Oct. 14, 2008**

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

(75) Inventors: **Woo Hyuk Choi**, Kyungsangbuk-do
(KR); **Kwang Seop Park**,
Kyungsangbuk-do (KR)

(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 113 days.

(21) Appl. No.: **09/739,825**

(22) Filed: **Dec. 20, 2000**

(65) **Prior Publication Data**

US 2001/0024245 A1 Sep. 27, 2001

(30) **Foreign Application Priority Data**

Dec. 30, 1999 (KR) 10-1999-65977

(51) **Int. Cl.**

G02F 1/136 (2006.01)

G02F 1/1343 (2006.01)

(52) **U.S. Cl.** **349/42; 349/139; 349/143**

(58) **Field of Classification Search** **349/42-43,**
349/143, 139; 257/59, 72
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,416,619 A * 5/1995 Koike 349/42

5,585,951 A * 12/1996 Noda et al. 349/122
6,087,730 A * 7/2000 McGarvey et al. 257/766
6,508,686 B2 * 1/2003 Adachi 445/24
6,556,264 B1 * 4/2003 Hirakata et al. 349/110
6,900,854 B1 * 5/2005 Kim et al. 349/43
2001/0024245 A1 * 9/2001 Choi et al. 349/43
2004/0174482 A1 * 9/2004 Oke et al. 349/139

* cited by examiner

Primary Examiner—Dung T. Nguyen

(74) *Attorney, Agent, or Firm*—Birch, Stewart, Kolasch &
Birch, LLP

(57) **ABSTRACT**

A liquid crystal display device is formed wherein pattern defects generated during the process are eliminated to reduce the need for repairs. In the device, a trench-shaped hole is defined by patterning a passivation layer and a gate-insulating layer at the peripheries of a gate line and a data line to expose a transparent substrate. Accordingly, a protruding defect portion at the pixel area caused by pattern defects in the semiconductor layer and the gate line is removed by the trench-shaped holes defined by patterning the passivation layer and the gate insulating layer at the peripheries of the gate line and the data line, so that a separate repair process is not required.

29 Claims, 4 Drawing Sheets




FIG. 1
RELATED ART




FIG. 2
RELATED ART




FIG. 3




FIG. 4




FIG. 5





FIG. 6



1

LIQUID CRYSTAL DISPLAY DEVICE**BACKGROUND OF THE INVENTION****1. Field of the Invention**

This invention relates to a liquid crystal display, and more particularly, to a liquid crystal display device wherein pattern defects generated during the formation process are eliminated to reduce the need for repairs.

2. Description of the Related Art

Generally, a liquid crystal display (LCD) has a structure in which unit pixels are arranged horizontally and vertically each of the unit pixels includes a switching device consisting of a thin film transistor (TFT) and a pixel electrode for controlling a liquid crystal injected between substrates to transmit or reflect an incident light.

In the LCD, N×M unit pixels (wherein N and M are integers), each of which consists of a thin film transistors as a switching device and a pixel electrode coupled with the thin film transistor, are vertically and horizontally arranged in a matrix. N gate lines and M data lines transmitting signals to the gate electrodes and the source electrodes of the thin film transistors, respectively, are formed in such a manner to cross each other.

FIG. 1 is a plan view showing a structure of an LCD of the related art, and FIG. 2 is a section view of the related art LCD taken along the II-II' line in FIG. 1. Referring to FIG. 1 and FIG. 2, in the related art LCD, N gate lines 13 and M data lines 21 are formed on a transparent substrate 11 in such a manner to cross each other, thereby defining N×M pixel areas. The gate lines 13 and the data lines 21 are made from a metal and have a gate insulating layer 17 therebetween to be electrically insulated from each other. The N×M pixel areas include N×M pixels, each of which is driven with a TFT as a switching device connected electrically to the gate line 13 and the data line 21.

The TFT consists of a gate electrode 15, a source electrode 23, a drain electrode 25, and a semiconductor layer 19 including an ohmic contact layer (not shown) and an active layer (not shown). The gate electrode 15 is connected to the gate line 13 while the source electrode 23 is connected to the data line 21. The drain electrode 25 is opposed to the source electrode 23 with the gate electrode 15 therebetween. The semiconductor layer 19 is formed on the gate insulating layer 17 in such a manner as to overlap the gate electrode 15 and the source and drain electrodes 23 and 25 of the TFT as well as the data line 21.

A passivation layer 26 is provided to cover the TFT having the structure as mentioned above. A transparent pixel electrode 29 electrically connected to the drain electrode 25 via a contact hole 27 is provided at a pixel area on the passivation layer 26.

However, the related art LCD has a problem in that, since it must be repaired upon the generation of pattern defects in the gate line and the semiconductor line, its process time is increased.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide a liquid crystal display device wherein pattern defects in a gate line and a semiconductor layer can be eliminated.

In order to achieve these and other objects of the invention, a liquid crystal display device according to an embodiment of the present invention includes a trench-shaped hole defined

2

by patterning a passivation layer and a gate insulating layer at the peripheries of a gate line and a data line to expose a transparent substrate.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects of the invention will be apparent from the following detailed description of the embodiments of the present invention with reference to the accompanying drawings, in which:

FIG. 1 is a plan view showing a structure of a related art liquid crystal display device;

FIG. 2 is a section view of the related art liquid crystal display device taken along the II-II' line in FIG. 1;

FIG. 3 is a plan view showing a structure of a liquid crystal display device according to an embodiment of the present invention;

FIG. 4 is a section view of the liquid crystal display device taken along the IV-IV' line in FIG. 3;

FIG. 5 is a section view of the liquid crystal display device taken along the V-V' line in FIG. 3; and

FIG. 6 is a section view of the liquid crystal display device taken along the VI-VI' line in FIG. 3.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to FIGS. 3-6, there is shown a liquid crystal display device according to an embodiment of the present invention. In the liquid crystal display device, N gate lines 33 and M data lines 41 are formed on a transparent substrate 31 in such a manner to cross each other, thereby defining N×M pixel areas. The gate lines 33 and the data lines 41 are made from a conductive metal and have a gate insulating layer 37 made from an insulating material such as silicon oxide or silicon nitride therebetween to be electrically insulated from each other. The N×M pixel areas includes N×M pixels, each of which is driven with a TFT as a switching device connected electrically to the gate line 33 and the data line 41.

The TFT consists of a gate electrode 35, a source electrode 43, a drain electrode 45, and a semiconductor layer 39 including an ohmic contact layer (not shown) and an active layer (not shown). The gate electrode 35 is connected to the gate line 33 while the source electrode 43 is connected to the data line 41. The drain electrode 45 is opposed to the source electrode 43 with the gate electrode 35 therebetween.

The semiconductor layer 39 has an active layer (not shown) made from polycrystalline silicon or amorphous silicon that is not doped with an impurity, and an ohmic contact layer (not shown) made from polycrystalline silicon or amorphous silicon doped with a n-type or p-type impurity. The active layer (not shown) constituting the semiconductor layer 39 between the drain electrode 45 and the source electrode 43 makes a channel. The semiconductor layer 39 is formed on the gate insulating layer 37 in such a manner as to overlap the gate electrode 35 and the source and drain electrodes 43 and 45 of the TFT as well as the data line 41. A passivation layer 46 is provided to cover the TFT having the structure as mentioned above.

French-shaped holes 47 are provided at the peripheries of the gate line 33 and the data line 41. The trench-shaped holes 47 expose the drain electrode 45 and are defined by patterning the passivation layer 46 and the gate insulating film 37 by photolithography including a dry etching to expose the transparent substrate 31. When the trench-shaped holes 47 are formed, a protruding defect portion at the pixel area caused by

pattern defects in the semiconductor layer 39 and the gate line 33 is also thereby removed, so that a separate repair process is not required.

A transparent pixel electrode 49 electrically connected, via the trench-shaped holes 47, to the exposed drain electrode 45, is provided at the pixel area on the passivation layer 46.

As described above, according to the present invention, a protruding defect portion at the pixel area caused by pattern defects in the semiconductor layer and the gate line is removed by the trench-shaped holes defined by patterning the passivation layer and the gate insulating layer at the peripheries of the gate line and the data line, so that a separate repair process is not required.

Although the present invention has been explained by the embodiments shown in the drawings described above, it should be understood to the ordinary skilled person in the art that the invention is not limited to the embodiments, but rather that various changes or modifications thereof are possible without departing from the spirit of the invention. Accordingly, the scope of the invention shall be determined only by the appended claims and their equivalents.

What is claimed is:

1. A liquid crystal display device comprising:

a transparent substrate, at least one thin film transistor having a gate electrode, a gate insulating layer over the gate electrode, a semiconductor layer, a source electrode and a drain electrode, a passivation layer located on the at least one thin film transistor, a pixel electrode connected to the drain electrode of the at least one thin film transistor, a gate line connected to the gate electrode of the at least one thin film transistor, a data line connected to the source electrode of the at least one thin film transistor;

a first trench-shaped hole formed in the passivation layer and the gate insulating layer along a first side of at least one of the data line and the gate line between the pixel electrode and the at least one of the data line and the gate line to expose the transparent substrate, the pixel electrode in the first trench exposing the transparent substrate; and

a second trench-shaped hole formed in the passivation layer and the gate insulating layer along a second, opposite side of the at least one of the data line and the gate line,

wherein the first and second trench-shaped holes expose the substrate.

2. The liquid crystal display device according to claim 1, wherein the drain electrode is exposed by the first trench-shaped hole.

3. The liquid crystal display device according to claim 1, wherein the first and second trench-shaped holes are formed by patterning the passivation layer and the gate insulating layer.

4. The liquid crystal display device according to claim 1, wherein the first and second trench-shaped holes extend along a majority of the at least one of the gate line and the data line.

5. The liquid crystal display device according to claim 1, wherein the first and second trench-shaped holes extend parallel to the at least one of the gate line and the data line.

6. The liquid crystal display device according to claim 1, wherein the second trench-shaped hole is formed between an adjacent pixel electrode and the second, opposite side of the at least one of the data line and the gate line.

7. The liquid crystal display device according to claim 1, wherein the first trench-shaped hole exposes a portion of the

transparent substrate, and the portion of the transparent substrate exposed to the first trench-shaped hole is free of contact with the pixel electrode.

8. A liquid crystal display structure, comprising:

a substrate;

a gate line formed on the substrate and connected to a thin film transistor;

a data line formed on the substrate and crossing the gate line and connected to the thin film transistor;

a pixel electrode located adjacent to the gate line and the data line and connected to the thin film transistor;

a first trench located along a first side of at least one of the data line and the gate line between the pixel electrode and the at least one of the data line and the gate line, the pixel electrode in the first trench exposing the substrate; and

a second trench located along a second, opposite side of the at least one of the data line and the gate line.

9. The liquid crystal display structure according to claim 8, further comprising a gate insulating layer formed over the gate line, wherein the first and second trenches extend through the gate insulating layer and expose the substrate.

10. The liquid crystal display structure according to claim 8, wherein the first and second trenches extend along a majority of the at least one of the gate line and the data line.

11. The liquid crystal display structure according to claim 8, wherein the first and second trenches extend parallel to the at least one of the gate line and the data line.

12. The liquid crystal display structure according to claim 8, wherein the thin film transistor is located on the substrate.

13. The liquid crystal display structure according to claim 12, wherein the thin film transistor comprises:

a gate electrode connected with the gate line;

a source electrode connected with the data line; and

a drain electrode connected with the pixel electrode.

14. The liquid crystal display structure according to claim 8, wherein the second trench is located between an adjacent pixel electrode and the second, opposite side of the at least one of the data line and the gate line.

15. A liquid crystal display device, comprising:

a substrate;

a thin film transistor located on the substrate;

a bus line formed on the substrate and connected with the thin film transistor;

a pixel electrode located adjacent to the bus line and connected with the drain electrode of the thin film transistor;

a first trench extending along a first side of the bus line and between the pixel electrode and the bus line, the pixel electrode in the first trench exposing the substrate; and

a second trench extending along a second, opposite side of the bus line.

16. The liquid crystal display device according to claim 15, wherein the bus line comprises a gate line, and further comprising a gate insulating layer formed over the gate line, wherein the first trench and the second trench extend through the gate insulating layer and expose the substrate.

17. The liquid crystal display device according to claim 16, further comprising:

a data line formed on the substrate and connected with the thin film transistor;

a third trench extending along a first side of the data line and between the pixel electrode and the data line; and

a fourth trench extending along a second, opposite side of the data line.

18. The liquid crystal display device according to claim 17, wherein the thin film transistor comprises:

the gate electrode being connected with the gate line;

5

the source electrode being connected with the data line;
and
a drain electrode connected with the pixel electrode.

19. The liquid crystal display device according to claim 15,
wherein the second trench is located between an adjacent
pixel electrode and the second, opposite side of the bus line.

20. The liquid crystal display device according to claim 15,
wherein the first and second trenches extend along a majority
of the bus line.

21. A method of making a liquid crystal display structure,
comprising the following steps:

providing a substrate;

forming a gate line on the substrate to be connected to a thin
film transistor;

forming a data line on the substrate which crosses the gate
line and is connected to the thin film transistor;

forming a pixel electrode adjacent to the gate line and the
data line to be connected to the thin film transistor;

forming a first trench along a first side of at least one of the
data line and the gate line and between the pixel elec-
trode and the at least of the data line and gate line, the
pixel electrode in the first trench exposing the substrate;
and

forming a second trench along a second, opposite side of
the at least one of the data line and the gate line.

22. The method according to claim 21, further comprising
the step of forming the thin film transistor on the substrate.

6

23. The method according to claim 22, wherein the step of
forming the thin film transistor further comprises the follow-
ing substeps:

forming a gate electrode connected with the gate line;

forming a source electrode connected with the data line;
and

forming a drain electrode with the pixel electrode.

24. The method according to claim 23, further comprising
the step of forming a contact hole to expose the drain elec-
trode for contact with the pixel electrode.

25. The method according to claim 24, wherein the first and
second trenches are formed during the step of forming the
contact hole.

26. The method according to claim 21, wherein the first
trench and the second trench exposing the substrate.

27. The method according to claim 21, wherein the step of
forming the second trench includes forming the second trench
between an adjacent pixel electrode and the second, opposite
side of the at least one of the data line and the gate line.

28. The method according to claim 21, wherein the step of
forming the first trench includes forming the first trench to
expose the substrate, and the step of forming the pixel elec-
trode includes exposing at least a portion of the substrate
exposed in the step of forming the first trench.

29. The method according to claim 21, wherein the steps of
forming the first and second trenches include forming the first
and second trenches extending along a majority of the at least
one of the gate line and the data line.

* * * * *

专利名称(译)	液晶显示装置		
公开(公告)号	US7436461	公开(公告)日	2008-10-14
申请号	US09/739825	申请日	2000-12-20
[标]申请(专利权)人(译)	崔佑赫 PARK KWANG燮		
申请(专利权)人(译)	崔佑赫 PARK KWANG燮		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	CHOI WOO HYUK PARK KWANG SEOP		
发明人	CHOI, WOO HYUK PARK, KWANG SEOP		
IPC分类号	G02F1/136 G02F1/1343 G02F1/1335 G02F1/1333 G02F1/1362 G02F1/1368		
CPC分类号	G02F1/133345 G02F1/136259 G02F1/136286 G02F1/1368 G02F2001/133337		
审查员(译)	NGUYEN , 龚便T.		
优先权	1019990065977 1999-12-30 KR		
其他公开文献	US20010024245A1		
外部链接	Espacenet USPTO		

摘要(译)

形成液晶显示装置，其中消除了在处理过程中产生的图案缺陷，以减少修理的需要。在该器件中，通过在栅极线和数据线的外围处图案化钝化层和栅极绝缘层来限定沟槽形孔，以暴露透明衬底。因此，由在半导体层和栅极线中的图案缺陷引起的像素区域处的突出缺陷部分被通过在栅极线的周边处图案化钝化层和栅极绝缘层而限定的沟槽形状的孔去除。数据线，因此不需要单独的修复过程。

