



US007852450B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 7,852,450 B2**
(45) **Date of Patent:** **Dec. 14, 2010**

(54) **LIQUID CRYSTAL DISPLAY DEVICE AND
METHOD OF FABRICATING THE SAME**

6,411,360 B1 6/2002 Matsuyama et al. 349/156
6,597,425 B2 7/2003 Kadota et al. 349/156
7,126,662 B2 * 10/2006 Choi et al. 349/155

(75) Inventors: **Jeom Jae Kim**, Seoul (KR); **Sang Yoon Paik**, Seoul (KR)

(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 375 days.

JP 11-084386 3/1999

(21) Appl. No.: **10/981,429**

OTHER PUBLICATIONS

(22) Filed: **Nov. 4, 2004**

Office Action dated Sep. 29, 2006 for corresponding Chinese Patent Application No. 200410088628.8.

(65) **Prior Publication Data**

US 2005/0099578 A1 May 12, 2005

* cited by examiner

(30) **Foreign Application Priority Data**

Nov. 8, 2003 (KR) 10-2003-0078853

Primary Examiner—Dung T. Nguyen

(74) *Attorney, Agent, or Firm*—Brinks Hofer Gilson & Lione

(57) **ABSTRACT**

(51) **Int. Cl.**

G02F 1/1339 (2006.01)

G02F 1/1333 (2006.01)

G02F 1/1335 (2006.01)

(52) **U.S. Cl.** 349/156; 349/106; 349/110

(58) **Field of Classification Search** 349/155–156,
349/106, 110, 139

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,097,467 A 8/2000 Fujimaki et al. 349/155

6,111,624 A * 8/2000 Matsuoka et al. 349/106

A liquid crystal display device is disclosed that is capable of preventing poor alignment caused by a column spacer to improve the contrast ratio. The liquid crystal display device includes a color filter and column spacers located between a first substrate and a second substrate. The column spacers maintain the cell gap between the first and second substrates. The color filter contains pixels having multiple sub-pixels of different colors. The column spacers in regions of sub-pixels of the same color are randomly formed within the regions.

8 Claims, 12 Drawing Sheets




FIG. 1
RELATED ART




FIG. 2
RELATED ART




FIG. 3
RELATED ART




FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 7E





FIG. 7F



LIQUID CRYSTAL DISPLAY DEVICE AND METHOD OF FABRICATING THE SAME

This application claims the benefit of Korean Patent Application No. P2003-78853 filed in Korea on Nov. 8, 2003, which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display device, and more particularly, to a liquid crystal display device capable of preventing poor alignment caused by a column spacer to improve a contrast ratio.

2. Description of the Related Art

In general, a liquid crystal display (LCD) device controls the light transmittance of liquid crystal cells in response to video signals to thereby display pictures corresponding to the video signals on a liquid crystal display panel. To this end, the LCD device includes a liquid crystal display panel having liquid crystal cells arranged in an active matrix form, and driving circuits for driving the liquid crystal display panel.

Depending on a direction of an electric field driving a liquid crystal material, the LCD device is generally classified into two modes—a twisted nematic (TN) mode using a vertical electric field and an in-plane switching (IPS) mode using a horizontal electric field.

The TN mode LCD device drives the liquid crystal material using a vertical electric field formed between a common electrode and an opposing pixel electrode. The TN mode LCD device has high aperture ratios, but narrow viewing angles. The IPS mode LCD device drives the liquid crystal material using a horizontal electric field formed between the pixel electrode and the common electrode located in parallel on one substrate. The IPS mode LCD device has wide viewing angles, but low aperture ratios.

FIG. 1 is a plan view illustrating a related art IPS mode liquid crystal display panel.

Referring to FIG. 1, the IPS mode liquid crystal display panel includes: a color filter array substrate having a black matrix, a color filter, a planarization layer, a column spacer 13, and an upper alignment layer, which are sequentially formed on an upper substrate whose rear surface is covered with materials (not shown) for a transparent electrode for preventing static electricity; a thin film transistor array substrate having a thin film transistor (TFT), a common electrode, a pixel electrode, and a lower alignment layer, all of which are formed on a lower substrate; and a liquid crystal material (not shown) injected in the inner space between the color array substrate and the thin film transistor array substrate.

The column spacer 13 is regularly formed at a defined location on a red sub-pixel R region within one pixel having red, green and blue sub-pixels to serve to maintain a cell gap between the color filter array substrate and the thin film transistor array substrate. Also, the column spacer 13 may be regularly formed at a defined location on a green sub-pixel G region within one pixel and may be regularly formed at a defined location on a blue sub-pixel B region within one pixel.

Meanwhile, a rubbing process is performed on the upper and the lower alignment films in order to control initial alignment of the liquid crystal disposed therebetween. In the rubbing process, a rubbing roller rolls up a rubbing material. The surface of the alignment film is rubbed using the rubbing roller with the rubbing material in a direction defined from

upward to downward such as in a direction parallel to an alignment direction A of the column spacer 13 as shown in FIG. 2.

However, if the rubbing process is performed, then the rubbing material passes by the column spacer 13 regularly formed on the defined location, to thereby cause sectional damage at a particular portion of the rubbing material.

In other words, a rubbing scratch S, representing uneven alignment concentrated along the column spacer 13 arranged in a line as shown in FIG. 2, occurs, to thereby generate light leakage. As a result, a black brightness is increased, to thereby deteriorate the contrast ratio.

Meanwhile, in order to prevent the sectional damage in the rubbing material, as shown in FIG. 3, there has been proposed a structure, in which the column spacer 13 is formed within the other sub-pixels in one pixel. However, the red, green and blue color filters have different thicknesses due to process deviations. Accordingly, the cell gap is uneven.

SUMMARY

By way of introduction only, a liquid crystal display device according to an embodiment includes column spacers located between a first substrate and a second substrate to maintain a cell gap. The column spacers are randomly formed in sub-pixels of the same color.

The display device has pixels of multiple sub-pixels including red, green, and blue sub-pixels. A column spacer is located in each pixel.

The first substrate includes a black matrix, a color filter formed on the black matrix, and a common electrode formed on the color filter.

The first substrate includes a black matrix, a color filter formed on the black matrix, and a planarization layer formed to cover the color filter.

A method of fabricating a liquid crystal display device includes forming first and second substrates and forming column spacers maintaining a cell gap between the first and the second substrate. The column spacers in regions of sub-pixels of the same color are randomly formed within the sub-pixel regions.

Each pixel includes red, green, and blue sub-pixels and has a column spacer located therein.

Forming the first substrate includes: forming a black matrix; forming a color filter on the black matrix; and forming a common electrode on the color filter.

Forming the first substrate includes: forming a black matrix; forming a color filter on the black matrix; and forming a planarization layer to cover the color filter.

BRIEF DESCRIPTION OF THE DRAWINGS

The following detailed description of the embodiments of the present invention reference the accompanying drawings, in which:

FIG. 1 is a plan view illustrating a related art IPS mode liquid crystal display panel;

FIG. 2 is a diagram representing a scratch made during a rubbing process of the related liquid crystal display panel;

FIG. 3 is a plan view illustrating the liquid crystal display panel having a structure in which a related art column spacer is formed within the other sub-pixels in one pixel;

FIG. 4 is a plan view illustrating a liquid crystal display panel according to one embodiment of the present invention;

FIG. 5 is a sectional view showing a portion of the liquid crystal display panel shown in FIG. 4;

FIG. 6 shows randomly formed column spacers on the sub-pixel in the pixel shown in FIG. 3; and

FIGS. 7A to 7F are sectional views sequentially illustrating a method of fabricating a color filter array substrate of the liquid crystal display panel of FIG. 5.

DETAILED DESCRIPTION

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

Hereinafter, the preferred embodiments of the present invention will be described in detail with reference to FIGS. 4 to 7.

FIG. 4 is a plan view illustrating an IPS mode liquid crystal display panel according to an embodiment of the present invention, and FIG. 5 is a sectional view showing a portion of the liquid crystal display panel shown in FIG. 4.

Referring to FIGS. 4 and 5, the IPS mode liquid crystal display panel includes: a color filter array **100** substrate having a black matrix **104**, a color filter **106**, a planarization layer **108**, a column spacer **113**, and an upper alignment layer **110**, all of which are sequentially formed on an upper substrate **102** whose rear surface is covered with materials (not shown) for a transparent electrode to prevent static electricity; a thin film transistor array substrate **120** having a thin film transistor (TFT) **130**, a common electrode **124**, a pixel electrode **134**, and a lower alignment layer **142**, all of which are formed on a lower substrate **122**; and liquid crystal material (not shown) injected in the inner space between the color filter array substrate **100** and the thin film transistor array substrate **120**.

In the color filter array substrate **100**, the black matrix **104** is formed so as to overlap the area of the TFT **130** on the lower substrate **122** and with the area (not shown) of gate and data lines, and partitions the cell regions at which the color filter **106** is to be formed. The black matrix **104** serves to prevent light leakage and absorb external light, to thereby improve the contrast ratio. The color filter **106** is formed at the cell region partitioned by the black matrix **104**. The color filter **106** is formed by separate red (R), green (G), and blue (B) filters and represents red, green, and blue colors. The planarization layer **108** is formed to cover the color filter **106** and planarizes the upper substrate **102**. The column spacer **113** maintains the cell gap between the upper substrate **102** and the lower substrate **122**.

The column spacer **113** is formed on a red sub-pixel R region in one pixel including red, green, blue color filter **106**. Each column spacer **113** is randomly formed on each red sub-pixel R region irrespective of a defined regulation. Accordingly, when a rubbing process for aligning a liquid crystal material is performed, sectional damage of the rubbing material is prevented.

In the thin film transistor array substrate **120**, the TFT **130** includes: a gate electrode **132** along with a gate line **135** formed on the lower substrate **122**; a semiconductor layer **140** formed to overlap the gate electrode **132** with a gate insulating layer **126** positioned therebetween; and source/drain electrodes **168** and **170** formed along with a data line **164** with the semiconductor layer **140** positioned therebetween.

The TFT supplies pixel signals from the data line to the pixel electrode **134** in response to scan signals from the gate line **135**.

The pixel electrode **134** is made of a transparent conductive material with a high light transmittance, and contacts a drain electrode **170** of the TFT **130** with a passivation film **144** positioned therebetween. The common electrode **124** is formed in a stripe form so as to alternate with the pixel

electrode **134**. A common voltage to drive the liquid crystal material is applied to the common electrode **124**.

A horizontal electric field formed by the common voltage and a pixel voltage supplied to the pixel electrode **134** makes the liquid crystal material rotate in a horizontal direction.

As set forth above, according to the embodiment of the liquid crystal display panel, the column spacer **113** is randomly formed on the red sub-pixel R region in one pixel region without having a defined regulation. Accordingly, when a rubbing process is performed, sectional damage caused by the column spacer **113** is prevented and the alignment becomes uniform. Thus, the contrast ratio is improved.

More specifically, a rubbing process is performed on the upper and the lower alignment films **110** and **142** in order to control the initial alignment of the liquid crystal material. In the rubbing process, a rubbing roller rolls up a rubbing material. The surface of the alignment film is rubbed by using the rubbing roller with the rubbing material in a direction defined from upward to downward. When the rubbing process is performed, as shown in FIG. 6, the column spacer **113** is randomly formed on the sub-pixel providing equal color in each pixel irrespective of the particular regulation. Thus, the sectional damage of the rubbing material is prevented.

Accordingly, it is possible to prevent unevenness of the alignment occurring when the related art column spacer is regularly arranged. As a result, the light leakage is remarkably reduced. Hereby, the black brightness is decreased and thus, the contrast ratio is improved.

FIGS. 7A to 7F are sectional views sequentially illustrating a method of fabricating the color filter array substrate of the IPS mode liquid crystal display panel according to an embodiment of the present invention.

First of all, an opaque material such as a nontransparent metal or a nontransparent resin is deposited on the upper substrate **102**. Then, the nontransparent material is patterned by photolithography using a mask and etching. Consequently, the black matrix **104** is formed as shown in FIG. 7A.

A red resin is deposited on the upper substrate **102** having the black matrix formed thereon. Then, the red resin is patterned by photolithography using a mask and etching. Consequently, a red color filter R is formed as shown in FIG. 7B.

A green resin is deposited on the upper substrate **102** having the red color filter R formed thereon. Then, the green resin is patterned by photolithography using a third mask and etching. Consequently, a green color filter G is formed as shown in FIG. 7C.

A blue resin is deposited on the upper substrate **102** having the green color filter G formed thereon. Then, the blue resin is patterned by photolithography using a mask and etching. Consequently, a blue color filter B is formed as shown in FIG. 7D.

A planarization material is deposited on the entire surface of the upper substrate **102** having the red, green, and blue color filters **106** formed thereon. Consequently, the planarization layer **108** is formed as shown in FIG. 7E.

A spacer material is deposited on the upper substrate **102** having the planarization layer **108** formed thereon. Then, the spacer material is patterned by photolithography using a mask and etching. Consequently, the column spacer **113** is formed as shown in FIG. 7F. The column spacer **113** is randomly formed on the sub-pixel R region providing a red color in each pixel having the red, green and blue filters **106** without having a particular regulation.

Meanwhile, the column spacer **113** may be formed on the thin film transistor array substrate to overlap the TFT, the gate line and the data line formed on the thin film transistor array substrate.

5

As set forth above, the upper alignment film **110** is applied on the upper substrate **102** in which the column spacer **113** is randomly formed. The lower alignment film **142** is applied on the lower substrate **122** in which the pixel electrode **134** is formed. Thereafter, the rubbing process for aligning the liquid crystal material is performed.

A method randomly forming a column spacer without having a particular regulation in a sub-pixel representing an equal color is easily applicable to not only a liquid crystal display panel of an in-plane-switching IPS mode but also a liquid crystal display of a twisted nematic TN mode and a vertical alignment VA mode.

As described above, according to the liquid crystal display device and the method of fabricating the liquid crystal display device herein, the column spacer is randomly formed without having a particular regulation in the sub-pixel providing the equal color. As a result, when the rubbing process is performed, sectional damage of the rubbing material and the light leakage caused by the scratch by the uneven alignment of the alignment film are prevented. Accordingly, the black brightness is decreased, to thereby improve the contrast ratio.

Although the present invention has been explained by the embodiments shown in the drawings described above, it should be understood to the ordinary skilled person in the art that the invention is not limited to the embodiments, but rather that various changes or modifications thereof are possible without departing from the spirit of the invention. Accordingly, the scope of the invention shall be determined only by the appended claims and their equivalents.

What is claimed is:

1. An IPS mode display device comprising:

a first substrate containing a plurality of column spacers; and

a second substrate, the column spacers maintaining a cell gap between the first and second substrates,

wherein one of the first and second substrates includes a color filter having sub-pixels of different colors,

a first column spacer being randomly positioned on a first gate line between first and second data lines and within a first sub-pixel of the sub-pixels, and

a second column spacer being randomly positioned on a second gate line between the first and second data lines and within a second sub-pixel of the sub-pixels,

6

the first and second column spacers arranged in different positions of the first sub-pixel and second sub-pixel respectively and the first sub-pixel being the same color as the second sub-pixel, and

wherein one of the first and second substrates includes a black matrix, and the column spacers are covered by the black matrix.

2. The display device according to claim 1, wherein a pixel contains red, green, and blue sub-pixels and at least one column spacer is located in each pixel.

3. The display device according to claim 1, wherein the first substrate includes a black matrix, the color filter formed on the black matrix, and a common electrode formed on the color filter.

4. The display device according to claim 1, wherein the first substrate includes a black matrix, the color filter formed on the black matrix, and a planarization layer formed to cover the color filter.

5. The display device according to claim 1, wherein the sub-pixel regions of the same color are formed in a substantially vertical direction.

6. The display device according to claim 1, wherein one of the first and second substrates includes both pixel and common electrodes.

7. The display device according to claim 1, further comprising an alignment layer disposed on the column spacers.

8. An IPS mode display device comprising:

a first substrate containing a plurality of column spacers; and

a second substrate, the column spacers maintaining a cell gap between the first and second substrates,

wherein one of the first and second substrates includes a color filter having sub-pixels of different colors, the column spacers being randomly disposed in regions of sub-pixels of the same color,

wherein the column spacers are only formed on the sub-pixel providing equal color, and

wherein one of the first and second substrates includes a black matrix, and the column are covered by the black matrix,

wherein the column spacers arranged in different positions of the same color sub-pixels.

* * * * *

专利名称(译)	液晶显示装置及其制造方法		
公开(公告)号	US7852450	公开(公告)日	2010-12-14
申请号	US10/981429	申请日	2004-11-04
[标]申请(专利权)人(译)	KIM观选团J PAIK桑Y		
申请(专利权)人(译)	KIM观选团J. PAIK桑Y.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	KIM JEOM JAE PAIK SANG YOON		
发明人	KIM, JEOM JAE PAIK, SANG YOON		
IPC分类号	G02F1/1339 G02F1/1333 G02F1/1335 G02F1/133 G02F1/1337 G02F1/1343 G02F1/136 H01L21/00		
CPC分类号	G02F1/13394 G02F1/134363		
代理机构(译)	BRINKS霍费尔GILSON & LIONE		
审查员(译)	NGUYEN , 粪便T.		
优先权	1020030078853 2003-11-08 KR		
其他公开文献	US20050099578A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种液晶显示装置，其能够防止由柱状间隔物引起的不良对准，从而提高对比度。液晶显示装置包括滤色器和位于第一基板和第二基板之间的柱状衬垫料。柱状衬垫料保持第一和第二衬底之间的盒间隙。滤色器包含具有不同颜色的多个子像素的像素。在该区域内随机形成相同颜色的子像素区域中的列间隔物。

