



US008054398B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 8,054,398 B2**
(45) **Date of Patent:** **Nov. 8, 2011**

(54) **LIQUID CRYSTAL DISPLAY AND PANEL THEREFOR**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(75) Inventors: **Hee-Seob Kim**, Gyeonggi-do (KR);
Jong-Lae Kim, Seoul (KR);
Young-Chol Yang, Kunpo-si (KR);
Sung-Kyu Hong, Seongnam-si (KR)

4,840,460 A 6/1989 Bernot et al.
5,283,566 A * 2/1994 Mimura et al. 345/211
5,709,308 A 1/1998 Gics
5,777,700 A 7/1998 Kaneko et al.
6,104,450 A * 8/2000 Hiraishi 349/48
6,473,142 B2 * 10/2002 Kim et al. 349/84

(Continued)

(73) Assignee: **Samsung Electronics Co., Ltd.** (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 235 days.

FOREIGN PATENT DOCUMENTS

CN 1290920 4/2001

(Continued)

(21) Appl. No.: **10/550,598**

OTHER PUBLICATIONS

(22) PCT Filed: **Mar. 26, 2004**

Written Opinion of the International Searching Authority for International Application No. PCT/KR2004/000685. Mailed May 29, 2004.

(86) PCT No.: **PCT/KR2004/000685**

§ 371 (c)(1),

(2), (4) Date: **Jul. 24, 2006**

(Continued)

(87) PCT Pub. No.: **WO2004/086129**

Primary Examiner — Michael Caley

(74) *Attorney, Agent, or Firm* — Cantor Colburn LLP

PCT Pub. Date: **Oct. 7, 2004**

(57)

ABSTRACT

(65) **Prior Publication Data**

US 2007/0177067 A1 Aug. 2, 2007

The present invention provides a liquid crystal display having excellent visibility. A thin film transistor array panel is provided, which includes: gate lines formed on an insulating substrate; data lines insulated from the gate lines and intersecting the gate lines; first pixel electrodes disposed on pixel areas defined by intersections of the gate lines and the data lines; first thin film transistors, each having three terminals connected to one of the gate lines, one of the data lines, and one of the first pixel electrodes; second pixel electrodes disposed on the pixel areas and capacitively coupled to the first pixel electrodes; and second thin film transistors, each having three terminals connected to a previous gate line, a storage electrode line or one of the data lines, and one of the second pixel electrodes.

(30) **Foreign Application Priority Data**

Mar. 26, 2003 (KR) 10-2003-0018787

(51) **Int. Cl.**

G02F 1/136 (2006.01)


G02F 1/1343 (2006.01)

(52) **U.S. Cl.** **349/48**; 349/39; 349/144

(58) **Field of Classification Search** 349/48,
349/144, 39

See application file for complete search history.

22 Claims, 15 Drawing Sheets



US 8,054,398 B2

Page 2

U.S. PATENT DOCUMENTS

6,724,359	B2 *	4/2004	Yamamoto et al.	345/92
6,760,082	B2 *	7/2004	Lee	349/42
6,922,183	B2 *	7/2005	Ting et al.	345/87
7,034,789	B2	4/2006	Takeuchi et al.	
7,113,159	B2	9/2006	Sawabe	
7,460,191	B2 *	12/2008	Song	349/48
2002/0089813	A1 *	7/2002	Yamamoto et al.	361/328

FOREIGN PATENT DOCUMENTS

CN	1346450	4/2002
JP	07-013191 A	1/1995
JP	7-98461	4/1995

JP	9-96835	4/1997
JP	10142577	5/1998
JP	10-161084	6/1998
JP	10-268349 A	10/1998
JP	2000-19559	1/2000
JP	2000195559	7/2000
JP	2001-235752 A	8/2001
JP	2002-258307 A	9/2002

OTHER PUBLICATIONS

International Preliminary Report for International Application No. PCT/KR2004/000685. Mailed Oct. 13, 2005.

* cited by examiner

FIG. 1




FIG. 2





FIG. 3

FIG. 4




FIG. 5





FIG. 6





FIG. 8

FIG. 9





FIG. 10






FIG. 12

FIG. 13








FIG. 15*FIG. 16*

LIQUID CRYSTAL DISPLAY AND PANEL THEREFOR

TECHNICAL FIELD

The present invention relates to a liquid crystal display and a panel therefor.

BACKGROUND ART

A typical liquid crystal display ("LCD") includes an upper panel provided with a common electrode and color filters, a lower panel provided with thin film transistors ("TFTs") and pixel electrodes, and a liquid crystal layer is interposed therebetween. The pixel electrodes and the common electrode are applied with different electric voltages to generate electric field, thereby changing the orientations of liquid crystal molecules and thus the transmittance of light passing through the liquid crystal layer. As a result, the LCD displays desired images.

However, the LCD has gray inversion that the luminances between grays are reversed and lateral gamma curve distortion that a lateral gamma curve does not coincide with a front gamma curve, thereby exhibiting inferior visibility at left and right view. For example, the luminance increases and the color moves into white as goes toward the lateral side. In particular, the luminance difference between bright grays disappears such that the image is not clear. In the meantime, the recent employment of the LCD at multimedia increasingly requires good visibility for viewing pictures and moving pictures.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will become more apparent by describing embodiments thereof in detail with reference to the accompanying drawings in which:

FIG. 1 is a layout view of a TFT array panel for an LCD according to a first embodiment of the present invention;

FIG. 2 is a sectional view of the TFT array panel shown in FIG. 1 taken along the line II-II';

FIG. 3 is an equivalent circuit diagram of an LCD according to the first embodiment of the present invention;

FIG. 4 is a layout view of a TFT array panel for an LCD according to the second embodiment of the present invention;

FIG. 5 is a sectional view of the TFT array panel shown in FIG. 4 taken along the line V-V';

FIG. 6 is an equivalent circuit diagram of an LCD according to the second embodiment of the present invention;

FIG. 7 is a layout view of an LCD according to the third embodiment of the present invention;

FIG. 8 is an equivalent circuit diagram of an LCD according to the third embodiment of the present invention.

FIG. 9 is a layout view of an LCD according to the fourth embodiment of the present invention;

FIG. 10 is an equivalent circuit diagram of an LCD according to the fourth embodiment of the present invention;

FIG. 11 is a layout view of a TFT array panel for an LCD according to the fifth embodiment of the present invention;

FIG. 12 is a layout view of a color filter panel for an LCD according to the fifth embodiment of the present invention;

FIG. 13 is a layout view of an LCD the fifth embodiment of the present invention;

FIG. 14 is a sectional view of the LCD shown in FIG. 13 taken along the line XIV-XIV';

FIG. 15 is an equivalent circuit diagram of an LCD according to the sixth embodiment of the present invention; and

FIG. 16 is an equivalent circuit diagram of an LCD according to the seventh embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Technical Problem

A motivation of the present invention is to provide a liquid crystal display having excellent visibility.

Technical Solution

Based on the motivation, the present invention divides a pixel electrode into two sub-electrodes and applies different voltages to the sub-electrodes.

In detail, a thin film transistor array panel according to an embodiment of the present invention includes a plurality of first signal lines and a plurality of second signal lines insulated from the first signal lines and intersecting the first signal lines formed on the insulating substrate. A plurality of first pixel electrodes are disposed on pixel areas defined by intersections of the first signal lines and the second signal lines and arranged in a matrix and a plurality of first thin film transistors, each having three terminals connected to one of the first signal lines, one of the second signal lines, and one of the first pixel electrodes, are formed thereon. A plurality of second pixel electrodes are disposed on the pixel areas and capacitively coupled to the first pixel electrodes, and a plurality of second thin film transistors are formed thereon. Each of the second thin film transistors have a terminal connected to one of the second pixel electrodes and another terminal connected to one of the first signal lines that is connected to one of the first pixel electrodes in a pixel area in an adjacent row.

The thin film transistor array panel may further include a plurality of coupling electrodes that are connected to or overlapping the first pixel electrodes and overlap the second pixel electrodes with being insulated therefrom. The coupling electrodes are preferably connected to drain electrodes of the first thin film transistors connected to the first pixel electrodes.

The thin film transistor array panel may further include a plurality of third signal lines intersecting the second signal lines, wherein a final terminal of each of the second thin film transistors is connected to one of the third signal lines and the second signal lines.

The final terminal of each of the second thin film transistors may be connected to one of the third signal lines, and the thin film transistor array panel may further include a plurality of third thin film transistors, each having three terminal connected to one of the second signal lines, one of the second pixel electrodes, and one of the first signal lines connected to a pixel area in an adjacent row.

At least one of the first pixel electrodes and the second pixel electrodes includes at least one domain partitioning member. The thin film transistor array panel may further include a gate insulating layer disposed between the first signal lines and the second signal lines, and a passivation layer disposed between the second signal lines and the first and the second pixel electrodes, wherein the coupling electrodes are preferably connected to the first pixel electrodes through contact holes at the passivation layer.

The thin film transistor array panel according to embodiments of the present invention is used for a panel for a liquid crystal display.

A viewing angle of an LCD is enlarged by improving lateral visibility.

BEST MODE OF EMBODIMENTS

The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which embodiments of the inventions invention are shown. The present invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein.

In the drawings, the thickness of layers and regions are exaggerated for clarity. Like numerals refer to like elements throughout. It will be understood that when an element such as a layer, region or substrate is referred to as being "on" another element, it can be directly on the other element or intervening elements may also be present. In contrast, when an element is referred to as being "directly on" another element, there are no intervening elements present.

Then, liquid crystal displays and thin film transistor panels therefor according to embodiments of this invention will be described in detail with reference to the accompanying drawings.

FIG. 1 is a layout view of a TFT array panel for an LCD according to a first embodiment of the present invention, FIG. 2 is a sectional view of the TFT array panel shown in FIG. 1 taken along the line II-II', and FIG. 3 is an equivalent circuit diagram of an LCD according to the first embodiment of the present invention.

An LCD according to an embodiment of the present invention includes a lower panel (i.e., a TFT array panel), an upper panel (i.e., an opposite panel) facing the lower panel, and a liquid crystal layer interposed between the two panels and including liquid crystal molecules aligned in a twisted nematic mode such that they are twisted from the lower panel to the upper panel.

First, the lower panel is described.

A plurality of first and second pixel electrodes **190a** and **190b** preferably made of transparent conductive material such as ITO (indium tin oxide) and IZO (indium zinc oxide) are formed on an insulating substrate **110** preferably made of transparent insulating material such as glass. Each of the first pixel electrodes **190a** is connected to a first thin film transistor TFT1 and receives image signal voltages therefrom, and each of the second pixel electrodes **190b** is connected to a second thin film transistor TFT2 that is electrically connected to a previous gate line **121** for transmitting gate signals or scanning signals to a previous pixel row and to a storage electrode line **131**. The second pixel electrode **190b** overlaps a coupling electrode **176** connected to the first pixel electrode **190a** to be electromagnetically (capacitively) coupled therewith. The first thin film transistor TFT1 is connected to a gate line **121** transmitting scanning signals and a data line **171** transmitting image voltages and switches on or off the image signals to be supplied to the first pixel electrode **190a** in response to the scanning signals. Here, the first and the second pixel electrodes **190a** and **190b** for a reflective LCD may not include transparent material.

In the meantime, although it is not shown in the figures, the upper panel is described now.

A black matrix for blocking light leakage between pixels, a plurality of red, green, and blue color filters, and a common electrode preferably made of transparent conductive material such as ITO and IZO for generating an electric field along with the pixel electrodes **190a** and **190b** are formed a surface

of an insulating substrate preferably made of transparent insulating material such as glass, which faces the TFT array panel. The black matrix and the color filters may be provided on the TFT array panel.

Now, a TFT array panel for an LCD according to the first embodiment is described more in detail.

A plurality of gate lines **121** and a plurality of storage electrode lines **131** extending in a transverse direction are formed on a lower insulating substrate **110**.

A plurality of portions of each gate line **121** expand upward and downward to a plurality of gate electrodes **123a** of first thin film transistors TFT1, and each gate lines **121** includes an end portion **125** having a large area for connection with an external circuit.

In the meantime, a gate line **121** transmitting gate signals or scanning signals to a previous pixel row has a plurality of portions forming gate electrodes **123b** of second thin film transistors TFT2.

Each pixel electrode **131** includes a plurality of sets of storage electrodes **133a** and **133b** branched therefrom. Two storage electrodes **133a** and **133b** in a set of storage electrodes **133a** and **133b** are branched out in a longitudinal direction and extend to edges of a pixel area.

The gate lines **121** and the storage electrode lines **131** is preferably made of metal such as Al, Al alloy, Ag, Ag alloy, Cr, Ti, Ta and Mo. As shown in FIG. 2, the gate lines **121** and the storage electrode lines **131** according to this embodiment including a single layer. However, they may have a dual-layered structure including a metal layer preferably made of Cr, Mo, Ti and Ta having excellent physical and chemical characteristics and another metal layer preferably containing Al or Ag having low resistivity. The gate lines **121** and the storage electrode lines **131** may be made of various metal or conductors other than those described above.

The gate lines **121** and the storage electrode lines **131** have inclined side surfaces and the inclination angle relative to a horizontal surface is preferably 30-80°.

A gate insulating layer **140** preferably made of silicon nitride SiNx is formed on the gate lines **121** and the storage electrode lines **131**.

On the gate insulating layer **140**, a plurality of the data lines **171** and a plurality of drain electrodes **175** of the first thin film transistors TFT1, a plurality of coupling electrodes **176**, and a plurality of under-bridge metal pieces **172** are formed. Each data line **171** extends substantially in the longitudinal direction, and it includes a plurality of branches extending to the drain electrodes **175** to form source electrodes **173a** of the first thin film transistors TFT1. The under-bridge metal pieces **172** are disposed on previous gate lines **121** and include a plurality portions forming drain electrodes **175b** of the second thin film transistors TFT2. A plurality of source electrodes **173b** of the second thin film transistors TFT2 are formed on the previous gate lines **121** and they are disposed opposite to the drain electrodes **175b** of the second thin film transistors TFT2 with respect to the previous gate lines **121**. The coupling electrodes **176** are connected to the drain electrodes **175a** of the first thin film transistors TFT1 and disposed near the pixel areas to overlap the storage electrode lines **131**.

The data lines **171**, the drain electrodes **175a** and **175b**, the coupling electrodes **176**, the source electrodes **173a** and **173b**, and the under-bridge metal pieces **172** are preferably made of Cr or Al like the gate lines **121**, and they may include a single layer or multiple layers.

A plurality of semiconductor stripes **151** are formed under the data lines **171** and the drain electrodes **175a** and they extend substantially in the longitudinal direction along the

data lines 171. Each semiconductor stripe 151 preferably made of amorphous silicon has a plurality of branches extending toward the gate lines 123a, the source electrodes 173a, and the drain electrodes 175a and forming channel portions 154 of the first thin film transistors TFT1. In addition, a plurality of semiconductor islands 155 forming channel portions of the second thin film transistors TFT2 are formed on the previous gate lines 121.

A plurality of ohmic contacts 161 are disposed between the semiconductors 151 and the data lines 171 and the drain electrodes 175a for reducing the contact resistance therebetween. The ohmic contacts 161 are preferably made of silicide or amorphous silicon heavily doped with n type impurity. The ohmic contacts 161 include a plurality of ohmic contacts 163a and 165a for the first thin film transistors TFT1 disposed under the source electrodes 173a and the drain electrodes 175a, and a plurality of ohmic contacts 163b and 165b for the second thin film transistors TFT2 are formed under the source electrodes 173b and the drain electrodes 175b of the second thin film transistors TFT2.

A passivation layer 180 made of an inorganic insulator such as silicon nitride or an organic insulator such as resin is formed on the data lines 171, the drain electrodes 175a and 175b, the coupling electrodes 176, and the under-bridge metal pieces 172.

The passivation layer 180 has a plurality of contact holes 181a, 181b and 183 exposing at least a portion of the drain electrodes 175a and 175b and the end portions 179 of the data lines 171, respectively. In addition, a plurality of contact holes 182, 184 and 185 exposing the end portions 125 of the gate lines 121 and portions of the storage electrode lines 131, respectively, penetrate the gate insulating layer 140 and the passivation layer 180. In addition, the passivation layer 180 has a plurality of contact holes 186 exposing the source electrodes of the second thin film transistors TFT2.

A plurality of pixel electrodes the pixel electrodes 190a and 190b, a plurality of contact assistants 95 and 97, and a plurality of storage bridges 91 are formed on the passivation layer 180. The pixel electrodes 190a and 190b, the contact assistants 95 and 97, and the storage bridges 91 is preferably made of a transparent conductor such as ITO (indium tin oxide) and IZO (indium zinc oxide) or an opaque conductor such as Al having excellent light reflectance.

The pixel electrodes 190a and 190b includes first pixel electrodes 190a and second pixel electrodes 190b. The first pixel electrodes 190a are connected to the drain electrodes 175a of the first thin film transistors TFT1 through the contact holes 181a, and the second pixel electrodes 190b are connected to the drain electrodes 175b of the second thin film transistors TFT2 through the contact holes 181b and overlap the coupling electrodes 176. Accordingly, the second pixel electrodes 190b are electromagnetically (capacitively) coupled to the first pixel electrodes 190a.

The storage bridges 91 connect two storage electrode lines 131 disposed opposite each other with respect to the gate lines 121. The storage bridges 91 contact the storage electrodes 133a and the storage electrode lines 131 through the contact holes 184 and 185 penetrating the passivation layer 180 and the gate insulating layer 140. The storage bridges 91 are connected to the under-bridge metal pieces 172 through the contact holes 186. Accordingly, when the second thin film transistors operate responsive to gate-on signals applied to the previous gate lines 121, the second pixel electrodes 190b are supplied with a common voltage or a reference voltage applied to the storage electrode lines 131. The storage bridges 91 electrically connect all the storage electrode lines 131 on the lower substrate 110. The storage electrode lines 131 are

used for repairing the defects in the gate lines 121 or the data lines 171, if necessary, and the under-bridge metal pieces 172 enhance the electrical connection between the gate lines 121 and the storage bridges 91 when a laser beam is illuminated for repairing.

The contact assistants 95 and 97 are connected to the end portions 125 of the gate lines 121 and the end portions 179 of the data lines 171 through the contact holes 182 and 183, respectively.

In the above-described LCD, the first pixel electrodes 190a receive the image signal voltages through the first thin film transistors TFT1, while the second pixel electrodes 190b have changing voltages dependent on the capacitive coupling with the storage electrode lines 131. Therefore, absolute values of the voltages of the second pixel electrodes 190b are always higher than those of the first pixel electrodes 190a. In this way, two pixel electrodes disposed in a pixel area but having different voltages compensate their voltages to reduce the distortion of a gamma curve.

Then, a reason why the voltage of a second pixel electrode 190b is maintained higher than that of a first pixel electrode 190a is described with reference to FIG. 3.

In FIG. 3, C_{LCA} indicates a liquid crystal capacitance between a first pixel electrode 190a and a common electrode of an opposite panel, and C_{STA} indicates a storage capacitance between the first pixel electrode 190a and a storage electrode line 131. C_{LCB} indicates a liquid crystal capacitance between a second pixel electrode 190b and the common electrode of the opposite panel, C_{STB} indicates a storage capacitance between the second pixel electrode 190b and the storage electrode line 131, and C_{CPB} indicates a coupling capacitance between a coupling electrode 176 and the second pixel electrode 190b.

The voltage of the first pixel electrode 190a with respect to a common voltage or a reference voltage applied to the common electrode of the opposite panel is denoted by V_a (V_{d1}), and the voltage of the second pixel electrode 190b is denoted by V_b . The voltage distribution law results in:

$$V_b \approx 1 / (C_1 + 2C_2) \times [(2 - C_3/C_2) \times (C_1 + C_2) \times V_{d1}].$$

The voltage V_b can be controlled such that the voltage V_b approaches the voltage V_a but always higher than the voltage V_a by adjusting the capacitances. Here, $C_1 = C_{LCA} + C_{STA}$, $C_2 = C_{CPB}$, and $C_3 = C_{LCB} + C_{STB}$. A parasitic capacitance between a gate electrode and a source electrode is neglected since it is trivial.

The arrangements of the first or the second thin film transistor TFT1 or TFT2 or the connection between the first and the second pixel electrodes 190a and 190b can be variously modified, which will be described in second to seventh embodiments.

Hereinafter, only the features distinguished from the first embodiment will be described and remaining features that is the same as those of the first embodiment will be omitted.

FIG. 4 is a layout view of a TFT array panel for an LCD according to the second embodiment of the present invention, FIG. 5 is a sectional view of the TFT array panel shown in FIG. 4 taken along the line V-V', and FIG. 6 is an equivalent circuit diagram of an LCD according to the second embodiment of the present invention.

In the TFT array panel for an LCD according to the second embodiment, a second thin film transistor TFT2 is driven through a previous gate line 121 like the first embodiment, but it owns a gate electrode 123 commonly with a first thin film transistor TFT1 and the first and the second thin film transistors TFT1 and TFT2 are disposed opposite with respect to a gate line 121. A source electrode 173b of the second thin film

transistor TFT2 and a source electrode 173a of the first thin film transistor TFT1 extend from a data line 171, a drain electrode 175b of the second thin film transistor TFT2 extends opposite a drain electrode 175a of the first thin film transistor TFT1 with respect to the gate electrode 123.

In the TFT array panel for an LCD according to the second embodiment of the present invention, although a second pixel electrode 190b is initially supplied with a pixel voltage supplied with a first pixel electrode 190a of a previous pixel row, it is supplied with a voltage Vb close to a voltage Va (Vd1) of the first pixel electrode 190a when the pixels in a corresponding pixel row are driven since it is capacitively coupled with the first pixel electrode 190a. The voltage Vb is given from the voltage distribution law by:

$$Vb \approx 1/(C_1 + 2C_2) \times [(2 - C_3/C_2) \times (C_1 + C_2) \times Vd1 + (C_1 + C_3) \times Vd2].$$

The voltage Vb can be controlled such that the voltage Vb approaches the voltage Va but always higher than the voltage Va by adjusting the capacitances and the TFT array panel according to the second embodiment of the present invention is preferably subject to column inversion therefor. Here, the voltage Vd2 is the voltage initially supplied to the second pixel electrode 190b when the second thin film transistor TFT2 turns on.

The first and the second embodiments according to the present invention the second relates to the control of an effective driving voltage supplied to the pixel electrode 190b. However, the TFT array panel may be modified such that the first pixel electrode 190a is supplied with a voltage lower than a driving voltage transmitted by a data line, while the second pixel electrode 190b is supplied with a voltage higher than the driving voltage, which will be described in detail with reference to the figures.

FIG. 7 is a layout view of an LCD according to the third embodiment of the present invention and FIG. 8 is an equivalent circuit diagram of an LCD according to the third embodiment of the present invention.

Most of the configuration is the same as those shown in FIGS. 1 and 3.

However, a first pixel electrode 190a is not connected to a first thin film transistor TFT1 through a contact hole in a passivation layer (indicated by 180 in FIG. 2), and it overlaps a coupling electrode 176 such that it is electromagnetically (capacitively) coupled with the first thin film transistors TFT1.

In the TFT array panel for an LCD according to the third embodiment of the present invention, an effective pixel voltage supplied to a first pixel electrode 190a is smaller than a voltage Vd1 supplied through a data line 171. It is because that the first pixel electrode 190a is capacitively coupled with the coupling electrodes 176 connected to a drain electrode 175a, the effective pixel voltage Va of the first pixel electrode 190a with respect to the common voltage is given from the voltage distribution law by:

$$Va = Vd1 \times [C_{CPA} / (C_{CPA} + C_{LCB})].$$

Since $C_{CPA} / (C_{CPA} + C_{LCB})$ is always lower than one, the voltage Va is always smaller than the voltage Vd1. Here, C_{CPA} indicates a coupling capacitance between the coupling electrodes 176 and the first pixel electrode. 190a.

The effective driving voltage Vb supplied to the second pixel electrode 190b is determined in the same way as the first embodiment.

FIG. 9 is a layout view of an LCD according to the fourth embodiment of the present invention and FIG. 10 is an equivalent circuit diagram of an LCD according to the fourth embodiment of the present invention.

Most of the configuration is the same as those shown in FIGS. 4 and 6.

However, the connection relation between first and second thin film transistors TFT1 and TFT2 and the first and the second pixel electrodes 190a and 190b is substantially the same as that shown in FIGS. 7 and 8.

In this case, an effective driving voltage Vb supplied to the first pixel electrode 190a is smaller than a voltage Vd1 transmitted by a data line 171 and an effective driving voltage Vb supplied to the second pixel electrode 190b is determined in the same way as the second embodiment.

The LCD has a major disadvantage of its narrow viewing angle, and several suggestions increasing the viewing angle for overcoming the disadvantage have been developed.

Among these techniques, a method provides a plurality of cutouts or a plurality of protrusions on pixel electrodes and a common electrode opposite each other and aligns liquid crystal molecules vertical to upper and lower panels. The cutouts or the protrusions can be applied to TFT array panels according to embodiments of the present invention.

The cutouts provided both at the pixel electrodes and the common electrode give wide viewing angle by generating fringe field to adjust the tilt directions of the liquid crystal molecules.

The provision of the protrusions both on the pixel electrode and the common electrode in the lower and upper panels distorts the electric field to adjust the tilt directions of the liquid crystal molecules.

The fringe field for adjusting the tilt directions of the liquid crystal molecules to form a plurality of domains is also obtained by providing the cutouts at the pixel electrodes on the lower panel and the protrusions on the common electrode on the upper panel.

The fifth embodiment of the present invention relates to a configuration having cutouts is described in detail.

FIG. 11 is a layout view of a TFT array panel for an LCD according to the fifth embodiment of the present invention, FIG. 12 is a layout view of a color filter panel for an LCD according to the fifth embodiment of the present invention, FIG. 13 is a layout view of an LCD the fifth embodiment of the present invention, and FIG. 14 is a sectional view of the LCD shown in FIG. 13 taken along the line XIV-XIV'.

An LCD according to the fifth embodiment of the present invention includes a lower panel, an upper panel facing the lower panel, and a liquid crystal layer interposed between the two panels and including liquid crystal molecules aligned vertical to surfaces of the panels.

First, the lower panel is described.

A plurality of first and second pixel electrodes 190a and 190b preferably made of transparent conductive material such as ITO (indium tin oxide) and IZO (indium zinc oxide) are formed on an insulating substrate 110 preferably made of transparent insulating material such as glass. The first and the second pixel electrodes 190a and 190b are connected to first and second thin film transistors TFT1 and TFT2, respectively, like the first embodiment. Each of the second pixel electrodes 190b overlaps a coupling electrode 176 connected to a first pixel electrode 190a to be electromagnetically (capacitively) coupled therewith. The second pixel electrode 190b has a cutout 192. A lower polarizing plate 12 is attached to an outer surface of the insulating substrate 110. Here, the first and the second pixel electrodes 190a and 190b for a reflective LCD may not include transparent material, and in this case, the lower polarizing plate 12 is unnecessary.

The upper panel is described now.

A black matrix 220 for blocking light leakage between pixels, a plurality of red, green, and blue color filters 230, and

a common electrode **270** preferably made of transparent conductive material such as ITO and IZO are formed on an inner surface of an insulating substrate **210** preferably made of transparent insulating material such as glass. The common electrode **270** has a plurality of cutouts **271**, **272** and **273**. The black matrix **220** is disposed around pixel areas and it may overlap the cutouts **271**, **272** and **273** of the common electrode **270** for blocking light leakage near edges of the cutouts **271**, **272** and **273**.

Now, a TFT array panel for an LCD according to the first embodiment is described more in detail.

A pair of a first pixel electrode **190a** and a second pixel electrode **190b** is divided by a gap that includes a pair of portions **191** and **193** making 45 degrees with gate line **121** and a portion perpendicular to the gate lines **121**. Each of the 45-degree portions **191** and **193** is longer than the perpendicular portion. In addition, the 45-degree portions are perpendicular to each other.

A second pixel electrode **190b** has a cutout **192** that extends from a right edge of the second pixel electrode **190b** toward a left edge thereof and has an expanded inlet.

The first pixel electrode **190a** and the second pixel electrode **190b** have inversion symmetry with respect to a line that bisects a pixel area defined by intersections of the gate lines **121** and data lines **171** (and extends parallel to the gate lines **121**).

A black matrix **220** for blocking light leakage is formed on an upper insulating substrate **210** and a plurality of red, green, and blue color filters **230** are formed on the black matrix **220**. A common electrode **270**, which is preferably made of transparent conductive material such as ITO and IZO and includes a plurality of sets of cutouts **271-273** are formed on the color filters **230**.

A set of the cutouts **271**, **272** and **273** in the common electrode **270** interpose the 45-degree portions of the gap between the pixel electrodes **190a** and **190b** and they include oblique portions parallel to the 45-degree portions and end portions overlapping edges of the pixel electrodes **190a** and **190b**. The end portions of the cutouts **271-273** include longitudinal end portions and transverse end portions.

The above-described TFT array panel and color filter panel are aligned and assembled and a liquid crystal material is injected therebetween and vertically aligned, thereby preparing a basic structure of the LCD according to an embodiment of the present.

When the TFT array panel and the color filter panel are aligned with each other, a set of the cutouts **271**, **272** and **273** in the common electrode **270** partition each of the pixel electrodes **190a** and **190b** into a plurality of subareas, according to this embodiment, four subareas as shown in FIG. **13**. As shown in FIG. **13**, each subarea is elongated to have a width direction and a length direction.

Portions of a liquid crystal layer **3** disposed between the subareas of the pixel electrodes **190a** and **190b** and the subareas of the common electrode **270** corresponding thereto are referred to as subregions, and the subregions are classified into four kinds depending on average long-axis directions of liquid crystal molecules contained therein under the application of an electric field, which are referred to as domains.

In the meantime, although the first to the fifth embodiments connect a second pixel electrode **190b** to a second thin film transistor TFT2, the second pixel electrode **190b** may be connected to two thin film transistors.

FIG. **15** is an equivalent circuit diagram of an LCD according to the sixth embodiment of the present invention.

Referring to FIG. **15**, an LCD according to the sixth embodiment of the present invention adds the second thin

film transistor (TFT2 shown in FIG. **6**) of the second embodiment into the connection configuration of the first embodiment as a third thin film transistor TFT3.

FIG. **16** is an equivalent circuit diagram of an LCD according to the seventh embodiment of the present invention.

Referring to FIG. **16**, an LCD according to the sixth embodiment of the present invention adds the second thin film transistor (TFT2 shown in FIG. **10**) of the fourth embodiment into the connection configuration of the third embodiment as a third thin film transistor TFT3.

The above-described configuration improves lateral visibility of an LCD, thereby widening a viewing angle.

While the present invention has been described in detail with reference to the preferred embodiments, those skilled in the art will appreciate that various modifications and substitutions can be made thereto without departing from the spirit and scope of the present invention as set forth in the appended claims. In particular, the cutouts formed in the pixel electrodes and the common electrode have various modifications.

The invention claimed is:

1. A liquid crystal display comprising:

- a first insulating substrate;
 - a gate line formed on the first insulating substrate and including first and second gate electrodes;
 - a storage electrode line formed on the first insulating substrate;
 - a gate insulating layer covering the gate line and the storage electrode line;
 - first and second amorphous silicon layers formed on the gate insulating layer;
 - a data line formed on the gate insulating layer and including a first source electrode disposed on the first amorphous silicon layer at least in part;
 - a second source electrode disposed on the second amorphous silicon layer at least in part;
 - first and second drain electrodes formed on the first and the second amorphous silicon layers at least in part and disposed opposite the first and the second source electrodes, respectively;
 - a coupling electrode formed on the gate insulating layer;
 - a passivation layer formed on the data line, the first and the second drain electrodes, and the coupling electrode;
 - a first pixel electrode that is formed on the passivation layer and is connected to or overlaps the first drain electrode and the coupling electrode;
 - a second pixel electrode insulating from the first pixel electrode, connected to or overlaps the first drain electrode and the coupling electrode;
 - a second insulating layer facing the first insulating substrate; and
 - a common electrode formed on the second insulating substrate,
- wherein a portion of the coupling electrode extends parallel to one of the data lines and partially overlaps the storage electrode line.

2. The liquid crystal display of claim 1, wherein the second source electrode is connected to the storage electrode line or the data line.

3. The liquid crystal display of claim 2, wherein the second source electrode is connected to the storage electrode line, and the liquid crystal display further comprises a third gate electrode connected to the gate line, a third source electrode connected to the data line, and the third drain electrode connected to the second pixel electrode.

4. The liquid crystal display of claim 2 or 3, wherein the first drain electrode is connected to the coupling electrode.

11

5. The liquid crystal display of claim 3, wherein the coupling electrode is connected to the first pixel electrode through a contact hole at the passivation layer.

6. The liquid crystal display of claim 5, further comprising: a first domain partitioning member disposed on at least one of the first and the second substrates and partitioning a pixel area into a plurality of domains along with the first domain partitioning member.

7. A liquid crystal display, comprising:

a first substrate;

a plurality of pixels disposed in a matrix on the first substrate, the pixel comprising a first pixel electrode electrically connected to a first transistor and a second pixel electrode electrically connected to a second transistor, wherein the first pixel electrode and the second pixel electrode are separated from each other;

a second substrate facing the first substrate and having a common electrode; and

a liquid crystal layer interposed between the first substrate and the second substrate and comprising a plurality of liquid crystal molecules,

wherein the liquid crystal layer on at least one of the first pixel electrode and the second pixel electrode is divided into at least 4 domains, wherein the domain is defined by an orientation direction of liquid crystal molecules when a voltage is applied to at least one of the first pixel electrode and the second pixel electrode,

wherein an electric field generated between the first pixel electrode and the common electrode is different from an electric field generated between the second pixel electrode and the common electrode, and

wherein the liquid crystal molecules are vertically aligned with the first substrate in the absence of the electric field.

8. The liquid crystal display of claim 7, wherein the pixel comprises at least one of the first pixel electrode, the second pixel electrode and the common electrode further comprise at least one domain partitioning member forming the domain of the liquid crystal layer.

9. The liquid crystal display of claim 8, wherein the at least one domain partitioning member has at least one slit.

10. The liquid crystal display of claim 7, further comprising a coupling electrode which applies an electric field to one

12

of the first pixel electrode and the second pixel electrode, wherein the coupling electrode is connected to one of the first pixel electrode and the second pixel electrode.

11. The liquid crystal display of claim 10, wherein the coupling electrode contacts one of the first pixel electrode and the second pixel electrode via a contact hole through an insulating layer.

12. The liquid crystal display of claim 11, wherein the coupling electrode is overlapped with at least one of the first pixel electrode and the second pixel electrode and the insulating layer is disposed therebetween.

13. The liquid crystal display of claim 12, further comprises a storage capacitance line capacitatively coupled with one of the first pixel electrode and the second pixel electrode.

14. The liquid crystal display of claim 13, wherein the storage capacitance line is overlapped with a portion of one of the first pixel electrode and the second pixel electrode.

15. The liquid crystal display of claim 14, wherein the coupling electrode is overlapped with the storage capacitance line.

16. The liquid crystal display of claim 7, wherein a surface area of the first pixel electrode is different from a surface area of the second pixel electrode.

17. The liquid crystal display of claim 16, wherein a shape of a boundary of the first pixel electrode is different from a shape of a boundary of the second pixel electrode.

18. The liquid crystal display of claim 17, wherein the boundary of the first pixel electrode and the boundary of the second pixel electrode are both polygonal.

19. The liquid crystal display of claim 16, wherein the surface area of the first pixel electrode is 30% to 70% of a surface area of an individual pixel.

20. The liquid crystal display of claim 7, wherein a shape of a boundary of the first pixel electrode is different from a shape of a boundary of the second pixel electrode.

21. The liquid crystal display of claim 20, wherein the boundary of the first pixel electrode and the boundary of the second pixel electrode are both polygonal.

22. The liquid crystal display of claim 7, wherein the first pixel electrode and the second pixel electrode are disposed in a same layer on the first substrate.

* * * * *

专利名称(译)	液晶显示器及其面板		
公开(公告)号	US8054398	公开(公告)日	2011-11-08
申请号	US10/550598	申请日	2004-03-26
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
[标]发明人	KIM HEE SEOB KIM JONG LAE YANG YOUNG CHOL HONG SUNG KYU		
发明人	KIM, HEE-SEOB KIM, JONG-LAE YANG, YOUNG-CHOL HONG, SUNG-KYU		
IPC分类号	G02F1/136 G02F1/1343 G02F1/133 G02F1/1362		
CPC分类号	G02F1/13624 G02F2001/134354 G02F2001/134345 G02F1/136286 G02F1/133345 G02F1/136227 G02F1/1368		
代理机构(译)	康托科尔伯恩LLP		
优先权	1020030018787 2003-03-26 KR		
其他公开文献	US20070177067A1		
外部链接	Espacenet USPTO		

摘要(译)

本发明提供一种具有优异可视性的液晶显示器。提供一种薄膜晶体管阵列面板，包括：形成在绝缘基板上的栅极线；数据线与栅极线绝缘并与栅极线相交；第一像素电极设置在由栅极线和数据线的交叉点限定的像素区域上；第一薄膜晶体管，每个薄膜晶体管具有连接到其中一条栅极线，一条数据线和第一像素电极的三个端子；第二像素电极设置在像素区域上并且电容性地耦合到第一像素电极；第二薄膜晶体管，每个具有连接到前一栅极线，存储电极线或一条数据线的三个端子，以及第二像素电极之一。

