



US008390773B2

(12) **United States Patent**
Jeong et al.

(10) **Patent No.:** **US 8,390,773 B2**
(45) **Date of Patent:** **Mar. 5, 2013**

(54) **LIQUID CRYSTAL DISPLAY PANEL AND
METHOD OF MANUFACTURING THE SAME**

(75) Inventors: **Youn-Hak Jeong**, Cheonan-si (KR);
Keun-Chan Oh, Cheonan-si (KR);
Yeon-Sik Ham, Suwon-si (KR);
Dong-Gi Seong, Seongnam-si (KR);
Kang-Woo Kim, Seoul (KR);
Yeon-Mun Jeon, Iksan-si (KR);
Hee-Hwan Lee, Busan (KR)

(73) Assignee: **Samsung Display Co., Ltd.** (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 810 days.

(21) Appl. No.: **12/469,211**

(22) Filed: **May 20, 2009**

(65) **Prior Publication Data**

US 2010/0053518 A1 Mar. 4, 2010

(30) **Foreign Application Priority Data**

Aug. 27, 2008 (KR) 2008-83715

(51) **Int. Cl.**
G02F 1/1335 (2006.01)

(52) **U.S. Cl.** **349/114**; 349/144

(58) **Field of Classification Search** None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,643,115	B2 *	1/2010	Sato et al.	349/114
2007/0222925	A1 *	9/2007	Park et al.	349/114
2007/0268440	A1 *	11/2007	Nagano	349/141
2008/0002071	A1 *	1/2008	Park	349/33
2009/0262288	A1 *	10/2009	Tsuchiya	349/114

FOREIGN PATENT DOCUMENTS

JP	2004341524	A	12/2004
JP	2006153978	A	6/2006
KR	1020080003197	A	1/2008

* cited by examiner

Primary Examiner — Hemang Sanghavi

(74) *Attorney, Agent, or Firm* — Cantor Colburn LLP

(57) **ABSTRACT**

A liquid crystal display panel includes; an array substrate including a pixel electrode disposed in a pixel area, the pixel electrode including a reflective electrode disposed in a reflective area of the pixel area and a transparent electrode disposed in a transmissive area of the pixel area, at least one of the reflective electrode and the transparent electrode including a plurality of first slit electrodes, an opposite substrate including a first common electrode disposed in alignment with the reflective area, the first common electrode including a plurality of second slit electrodes each having a width wider than that of an individual first slit electrode of the plurality of first slit electrodes, and a liquid crystal layer interposed between the array substrate and the opposite substrate.

18 Claims, 24 Drawing Sheets




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10




FIG. 12A




FIG. 12B




FIG. 13




FIG. 14A




FIG. 14B




FIG. 15




FIG. 16




FIG. 17A




FIG. 17B




FIG. 18




FIG. 19A





FIG. 19B



LIQUID CRYSTAL DISPLAY PANEL AND METHOD OF MANUFACTURING THE SAME

This application claims priority to Korean Patent Application No. 2008-83715, filed on Aug. 27, 2008, and all the benefits accruing therefrom under 35 U.S.C. §119, the contents of which in its entirety are herein incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

Exemplary embodiments of the present invention relate to a liquid crystal display ("LCD") panel and a method of manufacturing the LCD panel. More particularly, exemplary embodiments of the present invention relate to an LCD panel used in a transmissive-type LCD device and a method of manufacturing the LCD panel.

2. Description of the Related Art

Generally, a liquid crystal display ("LCD") device may be classified as a transmissive-type LCD device, a reflective-type LCD device or a transmissive-type LCD device. Due to high visibility and color reproducibility of the transmissive-type LCD device in an indoor space, the transmissive-type LCD device has been widely used. However, the visibility of the transmissive-type LCD device is decreased outdoors, and power consumption of the transmissive-type LCD device is high.

On the other hand, the reflective-type LCD device has high visibility outdoors and does not employ an internal light source, for example, a backlight, so that the reflective-type LCD has the benefit of having low power consumption. However, the visibility of the reflective-type LCD device is decreased in a dark environment, such as an indoor space.

Thus, a transmissive-type LCD device has been developed, which has the merits of 75

both the transmissive-type LCD and the reflective-type LCD device. However, the transmissive-type LCD has detriments in its optical structure and manufacturing aspects as compared with the transmissive-type LCD and the reflective-type LCD device. That is, a light path passing through a liquid crystal layer only once in a transmissive area of the display; however, in a reflective area of the display incident light is reflected against a reflective plate back to the liquid crystal layer so that the light path in this part of the display passes through the liquid crystal layer at least twice. Thus, a difference of phase delay exists in the two areas.

In order to solve the above problems, the transmissive-type LCD is designed so that a cell gap of a liquid crystal layer corresponding to the transmissive area is twice as large as that of a liquid crystal layer corresponding to the reflective area by using a twisted nematic ("TN") mode. However, a liquid crystal film structure, which is used to adjust a light path of a reflective area and a transmissive area and narrow viewing angle of the TN mode, and a rubbing direction of an initial liquid crystal have a low-TN mode that is a TN mode of which an initial twist angle is small, so that transmissivity may be low. In order to overcome the above disadvantages, a vertical alignment mode may be used. However, transmittance versus applied voltage curve (V-T curve) characteristics and reflectivity versus applied voltage curve (V-R curve) characteristics corresponding to the reflective area and the transmissive area may need to be adjusted.

When thin-film transistors ("TFTs") that are independently employed in the reflective area and the transmissive area to adjust V-T curve characteristics and V-R curve characteristics of the reflective and the transmissive areas, an aperture ratio

may be decreased and manufacturing costs may be increased. Moreover, when an insulation layer is formed in the reflective area to decrease an electric field for driving liquid crystal molecules, a difference of threshold voltage may be generated at low gradation.

BRIEF SUMMARY OF THE INVENTION

Exemplary embodiments of the present invention provide a liquid crystal display ("LCD") panel capable of enhancing light efficiency and a viewing angle.

Exemplary embodiments of the present invention provide a method of manufacturing the above-mentioned LCD panel.

According to one exemplary embodiment of the present invention, an LCD panel includes; an array substrate including a pixel electrode disposed in a pixel area, the pixel electrode including a reflective electrode disposed in a reflective area of the pixel area and a transparent electrode disposed in a transmissive area of the pixel area, at least one of the reflective electrode and the transparent electrode including a plurality of first slit electrodes, an opposite substrate including a first common electrode disposed in alignment with the reflective area, the first common electrode includes a plurality of second slit electrodes each having a width substantially equal to or wider than that of an individual first slit electrode of the plurality of first slit electrodes, and a liquid crystal layer interposed between the array substrate and the opposite substrate.

According to another exemplary embodiment of the present invention, an LCD panel includes an array substrate including a pixel electrode disposed in a pixel area, the pixel electrode including a reflective electrode disposed in a reflective area of the pixel area and a transparent electrode disposed in a transmissive area of the pixel area, only one of the reflective electrode and the transparent electrode including a plurality of first slit electrodes, an opposite substrate including a first common electrode disposed in alignment with the reflective area, the first common electrode including a plurality of second slit electrodes, each having a width wider than that of an individual first slit electrode of the plurality of first slit electrodes, and a liquid crystal layer interposed between the array substrate and the opposite substrate.

According to still another exemplary embodiment of the present invention, an LCD panel includes; an array substrate including a pixel area which is divided into a reflective area and a transmissive area, the array substrate including a reflective electrode disposed in the reflective area, and a transmissive electrode disposed in substantially the entire pixel area in alignment with the reflective electrode, the transmissive electrode having a plurality of slit electrodes, an opposite substrate disposed substantially opposite to the transmissive electrode, and including a common electrode, and a liquid crystal layer interposed between the array substrate and the opposite substrate.

According to still another exemplary embodiment of the present invention, an LCD panel includes an array substrate, an opposite substrate and a liquid crystal layer. The array substrate includes a pixel electrode disposed in a pixel area. The pixel electrode includes a reflective electrode disposed in a reflective area of the pixel area and a transparent electrode disposed in a transmissive area of the pixel area. The opposite substrate includes a first common electrode and a second common electrode. The first common electrode is disposed in alignment with the reflective area. The first common electrode includes a plurality of first slit electrodes. The second common electrode is disposed in alignment with the transparent area. The second common electrode includes a plural-

ity of second slit electrodes. The liquid crystal layer is interposed between the array substrate and the opposite substrate.

According to further still another exemplary embodiment of the present invention, there is provided a method of manufacturing an LCD panel, the method including: providing an array substrate, providing an opposite substrate, disposing a liquid crystal layer having a reactive mesogenic monomer between the array substrate and the opposite substrate, forming a hardened layer having a pretilt angle corresponding to a reflective mode on each of alignment layers of the array substrate and the opposite substrate by irradiating light to the liquid crystal layer when the liquid crystal layer is activated by applying a first voltage to a first common electrode, and forming a hardened layer having a pretilt angle corresponding to a transmissive mode on each of alignment layers of the array substrate and the opposite substrate by irradiating light to the liquid crystal layer when the liquid crystal layer is activated by applying a second voltage to a second common electrode.

According to the above exemplary embodiments of the present invention, a pixel electrode and/or a common electrode having a plurality of slit electrodes formed thereon align liquid crystal in a long axis direction of the slit electrode, so that high transmissivity and high reflectivity may be obtained. Moreover, a wide viewing angle may be obtained.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other features and advantages of the present invention will become more apparent by describing in detail exemplary embodiments thereof with reference to the accompanying drawings, in which:

FIG. 1 is a cross-sectional view of an exemplary embodiment of a liquid crystal display ("LCD") panel according to a first exemplary embodiment of the present invention;

FIG. 2A is a top plan layout view illustrating an exemplary embodiment of an array substrate of FIG. 1;

FIG. 2B is a top plan layout view illustrating an exemplary embodiment of an opposite substrate of FIG. 1;

FIG. 3 is a flow chart illustrating an exemplary embodiment of a manufacturing method of an exemplary embodiment of an LCD panel of FIG. 1;

FIG. 4 is a cross-sectional view illustrating an exemplary embodiment of a liquid crystal distribution of the exemplary embodiment of an LCD panel of FIG. 1 when an electric field is not applied thereto;

FIG. 5 is a cross-sectional view illustrating an exemplary embodiment of a liquid crystal distribution of the exemplary embodiment of an LCD panel of FIG. 1 when an electric field is applied thereto;

FIGS. 6A and 6B are top plan layout views illustrating a liquid crystal distribution of the exemplary embodiment of an LCD panel of FIG. 1 when an electric field is applied thereto;

FIG. 7 is an exploded perspective view of an exemplary embodiment of a display assembly illustrating optical characteristics of the exemplary embodiment of an LCD panel of FIG. 1;

FIGS. 8A and 8B are Poincare spheres illustrating polarizing variations in a transmissive area of FIG. 1;

FIGS. 9A and 9B are Poincare spheres illustrating polarizing variation in a reflective area of FIG. 1;

FIG. 10 is a graph illustrating V-T curve and V-R curves of the exemplary embodiment of an LCD panel;

FIG. 11 is a cross-sectional view of an exemplary embodiment of an LCD panel according to a second exemplary embodiment of the present invention;

FIG. 12A is a top plan layout view illustrating an exemplary embodiment of an array substrate of FIG. 11;

FIG. 12B is a top plan layout view illustrating an exemplary embodiment of an opposite substrate of FIG. 11;

FIG. 13 is a cross-sectional view illustrating an exemplary embodiment of a liquid crystal distribution of the exemplary embodiment of an LCD panel of FIG. 11 when an electric field is applied thereto;

FIGS. 14A and 14B are top plan layout views illustrating a liquid crystal distribution of the exemplary embodiment of an LCD panel of FIG. 11 when an electric field is applied thereto;

FIG. 15 is a cross-sectional view of an exemplary embodiment of an LCD panel according to a third exemplary embodiment of the present invention;

FIG. 16 is a cross-sectional view of an exemplary embodiment of an LCD panel according to a fourth exemplary embodiment of the present invention;

FIG. 17A is a top plan layout view illustrating an exemplary embodiment of an array substrate of FIG. 16;

FIG. 17B is a top plan layout view illustrating an exemplary embodiment of an opposite substrate of FIG. 16;

FIG. 18 is a cross-sectional view illustrating an exemplary embodiment of a liquid crystal distribution of the exemplary embodiment of an LCD panel of FIG. 16 when an electric field is applied thereto; and

FIGS. 19A and 19B are top plan layout views illustrating a liquid crystal distribution of the exemplary embodiment of an LCD panel of FIG. 16 when an electric field is applied thereto.

DETAILED DESCRIPTION OF THE INVENTION

The invention now will be described more fully hereinafter with reference to the accompanying drawings, in which embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. In the drawings, the sizes and relative sizes of layers and regions may be exaggerated for clarity. Like reference numerals refer to like elements throughout.

It will be understood that when an element is referred to as being "on," "connected to" or "coupled to" another element, it can be directly on the other element or intervening elements may be present therebetween. In contrast, when an element is referred to as being "directly on" another element, there are no intervening elements present. As used herein, the term "and/or" includes any and all combinations of one or more of the associated listed items.

It will be understood that, although the terms first, second, third, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer or section from another region, layer or section. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the present invention.

Spatially relative terms, such as "beneath," "below," "lower," "above," "upper" and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation

depicted in the figures. For example, if the device in the figures is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the exemplary term “below” can encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

The terminology used herein is for the purpose of describing particular example embodiments only and is not intended to be limiting of the present invention. As used herein, the singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

Example embodiments of the invention are described herein with reference to cross-sectional illustrations that are schematic illustrations of idealized example embodiments (and intermediate structures) of the present invention. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, example embodiments of the present invention should not be construed as limited to the particular shapes of regions illustrated herein but are to include deviations in shapes that result, for example, from manufacturing. For example, an implanted region illustrated as a rectangle will, typically, have rounded or curved features and/or a gradient of implant concentration at its edges rather than a binary change from implanted to non-implanted region. Likewise, a buried region formed by implantation may result in some implantation in the region between the buried region and the surface through which the implantation takes place. Thus, the regions illustrated in the figures are schematic in nature and their shapes are not intended to illustrate the actual shape of a region of a device and are not intended to limit the scope of the present invention.

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein. All methods described herein can be performed in a suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g., “such as”), is intended merely to better illustrate the invention and does not pose a limitation on the scope of the invention unless otherwise claimed. No language in the specification should be construed as indicating any non-claimed element as essential to the practice of the invention as used herein.

Hereinafter, the present invention will be explained in detail with reference to the accompanying drawings.

Exemplary Embodiment 1

FIG. 1 is a cross-sectional view of an exemplary embodiment of a liquid crystal display (“LCD”) panel 400 according to a first exemplary embodiment of the present invention.

FIG. 2A is a top plan layout view illustrating an exemplary embodiment of an array substrate of FIG. 1. FIG. 2B is a top plan layout view illustrating an opposite substrate of FIG. 1.

Referring to FIGS. 1, 2A and 2B, an LCD panel 400 includes an array substrate 100, an opposite substrate 200 and a liquid crystal layer 300.

The array substrate 100 includes a first base substrate 101, a gate line 111, a storage line 115, a gate insulation layer 120, a data line 141, a switching element TR, an organic layer 150, a reflective electrode 160, a transparent electrode 170 and a first alignment layer 180.

In one exemplary embodiment, the first base substrate 101 includes an optically transparent and electrically conductive material. A plurality of pixel areas is defined on the first base substrate 101. Each of the pixel areas ‘P’ is divided into a reflective area RA and a transmissive area TA.

The gate line 111 is extended in a first direction D11, and the storage line 115 is disposed in the reflective area RA and extends substantially in parallel with the gate line 111.

The data line 141 extends in a second direction D12 substantially perpendicular to the first direction D11.

The gate insulation layer 120 is disposed on the gate line 111, the storage line 115 and a gate electrode 113 of the switching element TR.

In one exemplary embodiment, the switching element TR is disposed within the reflective area RA. The switching element TR includes the gate electrode 113, a source electrode 142, a channel portion 130 and a drain electrode 143. The gate electrode 113 is electrically connected to the gate line 111, and the source electrode 142 is electrically connected to the data line 141. The channel portion 130 includes a semiconductor layer 131 and an ohmic contact layer 132 that are disposed on the gate electrode 113. The drain electrode 143 is spaced apart from the source electrode 142.

The organic layer 150 is disposed within the reflective area RA of the first base substrate 101 where the switching element TR is formed. In one exemplary embodiment, a surface of the organic layer 150 may have an embossing pattern EB in order to enhance a reflection ratio thereof. The organic layer 150 may have a contact hole 155 exposing a connection electrode 145, which in the present exemplary embodiment may be extended from the drain electrode 143. In one exemplary embodiment, the contact hole 155 may be formed in an area where the reflective electrode 160 and the transparent electrode 170 are overlapped with each other. In the present exemplary embodiment, the organic layer 150 is disposed to form the embossing pattern EB. Alternative exemplary embodiments include configurations wherein the organic layer 150 may be omitted.

In the present exemplary embodiment the reflective electrode 160 is disposed on the organic layer 150. In one exemplary embodiment, the reflective electrode 160 may include an electrically conductive reflecting material which reflects light. The electrically conductive reflecting material may include an optically non-transparent metal material. The reflective electrode 160 is disposed within the pixel area ‘P’ to form a reflective area RA and a transmissive area TA. In the present exemplary embodiment, the reflective electrode 160 directly makes contact with the connection electrode 145 through the contact hole 155 to be electrically connected to the switching element TR. The reflective electrode 160 may be extended to an adjacent pixel area along the gate line 111, so that a peripheral area of the pixel area ‘P’ may be utilized as a reflective area. Thus, as the reflective area is increased, the LCD panel 400 may have increased reflection characteristics.

The transparent electrode **170** is electrically connected to the reflective electrode **160** and is disposed on the transmissive area TA. In the present exemplary embodiment, the transparent electrode **170** includes a plurality of first slit electrodes E1. According to the present exemplary embodiment, a width **W1** of the first slit electrode E1 may be no more than about 10 μm , and a distance **b1** between the first slit electrodes E1 adjacent to each other may be no more than about 10 μm . The first slit electrodes E1 are extended in at least two directions to form a plurality of domains. In the present exemplary embodiment, the first slit electrode E1 extends along the first direction D11 and has a long axis direction along a second direction D12. Alternative exemplary embodiments include configurations wherein the first slit electrode may have various directions of extension, sizes, shapes, etc. As a result, the reflective electrode **160** and the transparent electrode **170** may together form a pixel electrode PE formed in the pixel area 'P'.

The first alignment layer **180** is disposed on the reflective electrode **160** and the transparent electrode **170** to vertically arrange liquid crystal molecules of the liquid crystal layer **300** when an electric field is not applied thereto.

The opposite substrate **200** includes a second base substrate **201**, a light blocking pattern **210**, a color filter **220**, a first common electrode **231**, a second common electrode **233** and a second alignment layer **240**.

The second base substrate **201** includes an optically transparent and electrically conductive material. In the second base substrate **201**, a plurality of pixel areas is defined. Each of the pixel areas 'P' is divided into a reflective area RA and a transmissive area TA, similar to the array substrate **100** described above.

The light blocking pattern **210** is disposed on the second base substrate **201** to block light from passing through the liquid crystal layer **300**. In one exemplary embodiment, the light blocking pattern **210** may be disposed on the second base substrate **201** corresponding with an area where the gate line **111**, the data line **141** and the switching element TR are formed. In another exemplary embodiment, the light blocking pattern **210** may be disposed in a boundary area between the reflective area RA and the transmissive area TA. Alternative exemplary embodiments include configurations wherein the light blocking pattern **210** may be disposed on the second base substrate **201** corresponding with an area where the gate line **111**, the data line **141** and the switching element TR are formed and a boundary area between the reflective area RA and the transmissive area TA.

The color filter **220** is disposed on the second base substrate **201** corresponding with the pixel area 'P'.

The first common electrode **231** is disposed on the color filter **220** of the reflective area RA. The first common electrode **231** includes a plurality of second slit electrodes E2. In one exemplary embodiment, each width **W2** of the second slit electrode E2 is about 1.5 times a width **W1** of the first slit electrode E1, and a distance **s2** between adjacent second slit electrodes E2 is no more than about 10 μm . The second slit electrodes E2 are extended in at least two directions to define a plurality of domains. In the present exemplary embodiment, the second slit electrode has a first axis along the first direction D11 and a long axis direction along the second direction D12. Alternative exemplary embodiments include configurations wherein the second slit electrode may have various directions. The second common electrode **233** is spaced apart from the first common electrode **231** to be disposed on the color filter **220** corresponding to the transmissive area TA. In one exemplary embodiment, the second common electrode **233** may have a planar structure (or plate structure). The first

and second common electrodes **231** and **233** together form a common electrode CE facing the pixel electrode PE disposed in the array substrate **100**.

The second alignment layer **240** is disposed on the first and second common electrodes **231** and **233** to vertically arrange liquid crystal molecules of the liquid crystal layer **300** when an electric field is not applied thereto.

In the present exemplary embodiment, the liquid crystal layer **300** includes liquid crystal molecules of a vertically aligned ("VA") mode, a first hardened layer **310** and a second hardened layer **320**. For example, a multiplication of a cell gap 'dt' of the liquid crystal layer **300** by a refractive index Δn of liquid crystal molecules may be about 0.25 μm to about 0.6 μm in the transmissive area TA, and a multiplication of a cell gap 'dr' of the liquid crystal layer **300** by a refractive index Δn of liquid crystal molecules may be no more than about 0.3 μm in the reflective area RA.

The first and second hardened layers **310** and **320** are disposed on the first and second alignment layers **180** and **240** to have a pretilt angle. In one exemplary embodiment, the first hardened layer **310** corresponding to the reflective area RA has a first pretilt angle, and the first hardened layer **310** corresponding to the transmissive area TA has a second pretilt angle. The second hardened layer **320** corresponding to the reflective area RA has a third pretilt angle, and the second hardened layer **320** corresponding to the transmissive area TA has a fourth pretilt angle.

In one exemplary embodiment the first and second hardened layers **310** and **320** may be formed from a reactive mesogenic monomer. In one exemplary embodiment, a first common voltage is applied to the first common electrode **231** and a first pixel voltage is applied to the pixel electrode PE to rotate a liquid crystal, and then ultraviolet ("UV") light is irradiated to form the first and third pretilt angles by forming a reactive mesogenic polymer chain in a predetermined direction on the first and second alignment layers **180** and **240** corresponding to the reflective area RA. In one exemplary embodiment the first common voltage is a voltage corresponding to the maximum luminance of a V-R curve.

Then, a second common voltage is applied to the first common electrode **233** and a second pixel voltage is applied to the pixel electrode PE to rotate a liquid crystal, and then UV light is irradiated to form the second and fourth pretilt angles by forming a reactive mesogenic polymer chain in a predetermined direction on the first and second alignment layers **180** and **240** corresponding to the transmissive area TA. In one exemplary embodiment, the second common voltage is a voltage corresponding to the maximum luminance at a V-T curve. Thus, pretilt angles of the reflective area RA and the transmissive area TA are effectively controlled, so that V-R curve characteristics and V-T curve characteristics may be obtained.

FIG. 3 is a flow chart illustrating an exemplary embodiment of a manufacturing method of an LCD panel of FIG. 1.

Referring to FIGS. 1 to 3, the array substrate **100** is manufactured, which includes the reflective electrode **160** formed in the reflective area RA on the first base substrate **101** and the transparent electrode **170** formed in the transmissive area TA on the first base substrate **101** (step S110).

The opposite substrate **200** is manufactured, which includes the first common electrode **231** formed in the reflective area RA on the second base substrate **201** and the second common electrode **233** formed in the transmissive area TA on the second base substrate **201** (step S130). Alternative exemplary embodiments include configurations wherein the opposite substrate **200** may be manufactured before the array substrate **100**.

The array substrate **100** and the opposite substrate **200** are combined with each other by using a sealing member (not shown) (step **S150**).

Liquid crystal material is injected between the array substrate **100** and the opposite substrate **200** that are combined with each other (step **S170**). The liquid crystal material may include liquid crystal having a negative refractive index including a reactive mesogenic monomer. Alternative exemplary embodiments include configurations wherein the liquid crystal layer is deposited on the array substrate **100** or the opposite substrate **200** before the substrates are combined in step **S150**.

In the LCD panel having the liquid crystal material, a first pixel voltage is applied to a pixel electrode **PE** having the reflective electrode **160** and the transparent electrode **170** and a first common voltage is applied to the first common electrode **231** to drive the reflective area **RA** in a white mode of a reflective mode. When the reflective area **RA** is driven in the white mode, UV light is irradiated to form the first and second hardened layers **310** and **320** on the reflective area **RA**, which have the first and third pretilt angles corresponding to the reflective mode (step **S190**).

Then, a second pixel voltage is applied to the pixel voltage **PE** of the LCD panel and a second common voltage is applied to the second electrode **233** to drive the transmissive area **TA** in a white mode of a transmissive mode. When the transmissive area **TA** is driven in the white mode, UV light is irradiated to form the first and second hardened layers **310** and **320** on the transmissive area **TA**, which have the second and fourth pretilt angles in correspondence with the transmissive mode (step **S210**).

FIG. **4** is a cross-sectional view illustrating an exemplary embodiment of a liquid crystal distribution of the LCD panel of FIG. **1** when an electric field is not applied thereto. FIG. **5** is a cross-sectional view illustrating an exemplary embodiment of a liquid crystal distribution of the LCD panel of FIG. **1** when an electric field is applied thereto. FIGS. **6A** and **6B** are top plan layout views illustrating an exemplary embodiment of a liquid crystal distribution of the LCD panel of FIG. **1** when an electric field is applied thereto.

Referring to FIG. **4**, when a voltage is not applied to a pixel electrode **PE** and a common electrode **CE** of the LCD panel, liquid crystals **LC** of the liquid crystal layer are vertically aligned.

Referring to FIGS. **5**, **6A** and **6B**, when a voltage is applied to the pixel electrode **PE** and the common electrode **CE**, liquid crystals **LC** corresponding to the transmissive area **TA** are aligned along a long axis of the first slit electrode **E1**. Thus, a disclination line due to liquid crystal alignment defects is not generated in a middle area of a width **W1** of the first slit electrode **E1** and a distance **b1** between the first slit electrodes **E1**, that is, an edge area of the first slit electrode **E1**, so that the LCD panel may have high transmissivity.

A width **W2** of the second slit electrode **E2** corresponding to the reflective area **RA** is wider than a distance **b2** between the second slit electrodes **E2**, so that the liquid crystals **LC** are aligned to face with each other with respect to a distance **b2** between the second slit electrodes **E2**. Thus, a wide viewing angle due to a dual domain effect may be realized.

FIG. **7** is an exploded perspective view of an exemplary embodiment of a display assembly illustrating optical characteristics of the LCD panel of FIG. **1**.

The display assembly includes the LCD panel **400**, a polarizer **511**, an analyzer **513**, a lower $\frac{1}{4}\lambda$ compensation film **521** and an upper $\frac{1}{4}\lambda$ compensation film **523**.

The polarizer **511** has a first transmitting axis **511a** to be disposed below the liquid crystal layer **300**. The analyzer **513**

has a second transmitting axis **513a** substantially perpendicular to the first transmitting axis **511a** to be disposed on the liquid crystal layer **300**. The lower $\frac{1}{4}\lambda$ compensation film **521** is disposed between the liquid crystal layer **300** and the polarizer **511** to have a first optical axis **521a** which is crossed with the first transmitting axis **511a**. The upper $\frac{1}{4}\lambda$ compensation film **523** is disposed between the liquid crystal layer **300** and the analyzer **513** to have a second optical axis **523a** which is crossed with the second transmitting axis **513a** by about 45 degrees.

In one exemplary embodiment, a long axis of the first and second slit electrodes **E1** and **E2** may be substantially parallel with an extending direction (or a first direction **D11**) of the gate line **111**. Alternative exemplary embodiments include configurations wherein a long axis of the first and second electrode **E1** and **E2** may be parallel with an extending direction (or a second direction **D12**) of the data line **141**. That is, the long axis of the first and second slit electrodes **E1** and **E2** may be a horizontal direction (or a first direction **D11**) or a vertical direction (or a second direction **D12**). In exemplary embodiments wherein the lower and upper $\frac{1}{4}\lambda$ compensation films **521** and **523** are omitted, a first transmitting axis **511a** of the polarizer **511** and a second transmitting axis **513a** of the analyzer **513** may be crossed with a long axis of the first and second slit electrodes **E1** and **E2**, respectively, by about 45 degrees.

According to the present exemplary embodiment, the lower and upper $\frac{1}{4}\lambda$ compensation films **521** and **523** having the first and second optical axes **521a** and **523a** respectively, which are crossed with the first and second transmitting axis **511a** and **513a**, are disposed so that light characteristics may be obtained even though transmitting axes of the polarizer **511** and the analyzer **513** that are perpendicular to the first and second slit electrodes **E1** and **E2** are optionally disposed.

FIGS. **8A** and **8B** are Poincare spheres illustrating a polarizing variation in a transmissive area of FIG. **1**.

Referring to FIGS. **7**, **8A** and **8B**, when a voltage is not applied to the LCD panel **400**, liquid crystal molecules are vertically aligned with respect to a surface of the LCD panel **400**. Thus, light which transmits through the polarizer **511** passes the lower $\frac{1}{4}\lambda$ compensation film **521** at an **S1** axis to arrive at a lower vertex of a Poincare sphere. That is, light passes through the liquid crystal layer **300** without a polarizing variation, and then the light passes the upper $\frac{1}{4}\lambda$ compensation film **523** to be again moved to the **S1** axis. Therefore, light transmitting through the upper $\frac{1}{4}\lambda$ compensation film **523** corresponds to an absorbing axis of the analyzer **513**. Therefore, when a voltage is not applied, the display assembly displays black.

On the other hand, when a voltage is applied to the LCD panel **400**, liquid crystal molecules are aligned substantially parallel with a surface of the LCD panel **400**. Thus, light which transmits through the polarizer **511** is moved to an **S3** axis by the liquid crystal layer **300** performing a role of a half wave film, and then the light is moved to an opposite side of the **S1** axis by passing through the upper $\frac{1}{4}\lambda$ compensation film **523**. Therefore, light transmitting through the upper $\frac{1}{4}\lambda$ compensation film **523** corresponds to a second transmitting axis **513a** of the analyzer **513**. Therefore the display assembly emits light, e.g., the display is white.

FIGS. **9A** and **9B** are Poincare spheres illustrating a polarizing variation in a reflective area of FIG. **1**.

Referring to FIGS. **7**, **9A** and **9B**, when a voltage is not applied to the LCD panel **400**, light which transmits through the analyzer **513** is positioned at the **S1** axis, and then the light is delayed by about 45 degrees passing through the upper $\frac{1}{4}\lambda$ compensation film **523** to arrive at a lower vertex of a

Poincare sphere. Then, light passes through the liquid crystal layer **300** to be reflected by a reflective electrode **160**. The reflected light is again passed to the upper $\frac{1}{4}\lambda$ compensation film **523** to be moved to an opposite side of the S1 axis. Therefore, light transmitting through the upper $\frac{1}{4}\lambda$ compensation film **523** is corresponding to an absorbing axis of the analyzer **513**. The display assembly displays black.

On the other hand, when a voltage is applied to the LCD panel **400**, liquid crystal is aligned substantially in parallel with a surface of the LCD panel **400**. Thus, light which transmits through the upper $\frac{1}{4}\lambda$ compensation film **523** is moved to an opposite side of an S1 axis by the liquid crystal layer **300** performing a role of a half wave film, and then the reflected light by the reflective electrode **160** is again passed to the liquid crystal layer **300** to be moved to an upper vertex of a Poincare sphere. Then, the light passes the upper $\frac{1}{4}\lambda$ compensation film **523** to be moved to the S1 axis. Therefore, light transmitting through the upper $\frac{1}{4}\lambda$ compensation film **523** is corresponding to a second transmitting axis **513a** of the analyzer **513**. The display assembly emits light, e.g., the display is white.

FIG. **10** is a graph illustrating V-T curve and V-R curve of the LCD panel having various physical characteristics.

Referring to FIGS. **1** and **10**, a width **W1** of the first slit electrode **E1** disposed in the transmissive area **TA** and a distance **b1** between the first slit electrodes **E1** are $4\ \mu\text{m}$ and $2\ \mu\text{m}$, respectively, and a phase delay (or a retardation value) ($d\cdot\Delta n$) of liquid crystal is varied from $0.36\ \mu\text{m}$, $0.33\ \mu\text{m}$ and $0.30\ \mu\text{m}$, wherein d is the cell gap and Δn is the average birefringence of the liquid crystal within the cell gap. A width **W2** of the second slit electrode **E2** disposed in the reflective area **RA** and a distance **b2** between the second slit electrodes **E2** are $15\ \mu\text{m}$ and $2\ \mu\text{m}$, respectively, and a phase delay ($d\cdot\Delta n$) of liquid crystal is classified as $0.18\ \mu\text{m}$ and $0.20\ \mu\text{m}$.

As shown in the graph of FIG. **10**, it is recognized that a threshold voltage corresponding to the transmissive area **TA** is substantially equal to that of the reflective area **RA**. Moreover, it is recognized that a transmittance versus applied voltage curve (V-T curve) and a reflectivity versus applied voltage curve (V-R curve) are substantially matched at the transmissive area **TA** of which a phase delay is about $0.30\ \mu\text{m}$ and $0.18\ \mu\text{m}$. In other words, the transmittance and the reflectance are most evenly matched when the phase delay (or retardation value) of the transmissive area is about $0.30\ \mu\text{m}$ and the phase delay (or retardation value) of the reflective area is about $0.18\ \mu\text{m}$.

Exemplary Embodiment 2

FIG. **11** is a cross-sectional view of a second exemplary embodiment of an LCD panel according to the present invention. FIG. **12A** is a top plan layout view illustrating an array substrate of FIG. **11**. FIG. **12B** is a top plan layout view illustrating an opposite substrate of FIG. **11**. The LCD panels of the second exemplary embodiment is substantially the same as the LCD panels of the first exemplary embodiment except for at least a first common electrode disposed in a reflective area. Thus, the same reference numerals are used in FIG. **11** to refer to components that are the same or like those shown in the LCD panel of the first exemplary embodiment, and thus, a detailed description thereof will be omitted.

Referring to FIGS. **11**, **12A** and **12B**, the LCD panel **600** includes an array substrate **100**, an opposite substrate **200** and a liquid crystal layer **300**.

The array substrate **100** includes the reflective electrode **160** disposed in the reflective area **RA** and the transparent electrode **170** covering the reflective electrode **160** to be

disposed on the transmissive area **TA**. In the present exemplary embodiment, the transparent electrode **170** is disposed to cover the reflective electrode **160**, so that an etching solution for etching the transparent electrode **170** may prevent the reflective electrode **160** from being damaged. Alternatively, the transparent electrode **170** may be formed in the transparent area **TA** to be overlapped with a portion of the reflective electrode **160** as shown in the LCD panel **400** of the first exemplary embodiment.

The opposite substrate **200** includes a first common electrode **231** disposed in the reflective area **RA** and a second common electrode **233** disposed in the transmissive area **TA**. The first common electrode **231** includes a plurality of slit electrodes **E2**. In one exemplary embodiment, a width **W2** of each second slit electrode **E2** may be no more than about $10\ \mu\text{m}$, and a distance **b2** between the second slit electrodes **E2** may be no more than about $10\ \mu\text{m}$. In one exemplary embodiment, when the width **W1** of the first slit electrode **E1** is about $1\ \mu\text{m}$, the width **W2** of the second slit electrode **E2** may be about $0.5\ \mu\text{m}$ to about $2\ \mu\text{m}$. In the present exemplary embodiment, the second slit electrodes **E2** are extended in at least two directions to define a plurality of domains. In the present exemplary embodiment, the second common electrode **233** is spaced apart from the first common electrode **231** to be formed on the transmissive area **TA** in a planar structure.

The liquid crystal layer **300** includes a first hardened layer **310** and a second hardened layer **320**, exemplary embodiments of which may be formed from a reactive mesogenic monomer. In one exemplary embodiment, the first hardened layer **310** corresponding to the reflective area **RA** has a first pretilt angle, and the second hardened layer **320** corresponding to the transmissive area **TA** has a second pretilt angle. The second hardened layer **320** corresponding to the reflective area **RA** has a third pretilt angle, and the second hardened layer **320** corresponding to the transmissive area **TA** has a fourth pretilt angle. Thus, the pretilt angles of the reflective area **RA** and the transmissive area **TA** are effectively controlled using the reactive mesogenic monomer, so that a V-R curve and a V-T curve may be obtained.

An exemplary embodiment of a manufacturing method of the second exemplary embodiment of an LCD panel **600** is substantially the same as a manufacturing method of the first exemplary embodiment of an LCD panel **400**, which is described referring to FIG. **3**. Thus, a detailed description thereof will be omitted.

FIG. **13** is a cross-sectional view illustrating an exemplary embodiment of a liquid crystal distribution of the second exemplary embodiment of an LCD panel of FIG. **11** when an electric field is applied thereto. FIGS. **14A** and **14B** are top plan layout views illustrating a liquid crystal distribution of the exemplary embodiment of an LCD panel of FIG. **11** when an electric field is applied thereto.

Referring to FIGS. **13**, **14A** and **14B**, when a voltage is applied to the pixel electrode **PE** and the common electrode **CE**, liquid crystals **LC** corresponding to the transmissive area **TA** are aligned in a long axis of the first slit electrode **E1**. Thus, a disclination line due to liquid crystal alignment defects is not generated in a middle area of a width **W1** of the first slit electrode **E1** and a distance **b1** between the first slit electrodes **E1**, that is, an edge area of the first slit electrode **E1**, so that the LCD panel may have high transmissivity.

Moreover, liquid crystals **LC** corresponding to the reflective area **RA** are aligned along a long axis direction of the second slit electrode **E2** having a width **W2** and a distance **b2** that are substantially equal to a width **W1** and a distance **b1** of the first slit electrode **E1**, respectively, so that the LCD panel may have high reflectivity.

FIG. 15 is a cross-sectional view of a third exemplary embodiment of an LCD panel according to the present invention. The third exemplary embodiment of an LCD panel is substantially similar to the previous exemplary embodiments of LCD panels except for at least a common electrode disposed on the opposite substrate and a pixel electrode disposed on the array substrate. Thus, identical reference numerals are used in FIG. 15 to refer to components that are the same or similar to those shown in the first exemplary embodiment of an LCD panel, and thus, a detailed description thereof will be omitted.

The LCD panel 700 includes an array substrate 100, an opposite substrate 200 and a liquid crystal layer 300. The array substrate 100 includes a pixel electrode PE, and the pixel electrode PE includes a reflective electrode 160 disposed on the reflective area RA and a transparent electrode 170 disposed on the transmissive area TA. In the present exemplary embodiment, the reflective electrode 160 and the transparent electrode 170 may have a planar structure.

The opposite substrate 200 includes a common electrode CE, and the common electrode CE includes a first common electrode 231 disposed on the reflective area RA and a second common electrode 233 disposed on the transmissive area TA. The first common electrode 231 includes a plurality of first slit electrodes E1, and the second common electrode 233 includes a plurality of second slit electrodes E2.

In the present exemplary embodiment, a width W1 of the first slit electrode E1 is no more than about 10 μm , and a distance b1 between the first slit electrodes E1 is no more than about 10 μm . Also in the present exemplary embodiment, each of a width W2 and a distance b2 of the second slit electrode E2 is no more than about 10 μm .

When a voltage is applied to the pixel electrode PE and the common electrode CE, liquid crystals LC corresponding to the transmissive area TA and the reflective area RA are aligned in a long axis direction of the first and second slit electrodes E1 and E2. Thus, a disclination line due to liquid crystal alignment defects is not generated in a middle area of a width W1 of the first slit electrode E1 and a distance b1 between the first slit electrodes E1, that is, an edge area of the first slit electrode E1, and a middle area of a width W2 of the second slit electrode E2 and a distance b2 between the second slit electrodes E2, that is, an edge area of the second slit electrode E2, so that the LCD panel may have high transmissivity and high reflectivity.

The liquid crystal layer 300 includes a first hardened layer 310 and a second hardened layer 320, exemplary embodiments of which may be formed from a reactive mesogenic monomer. In the present exemplary embodiment, the first hardened layer 310 corresponding to the reflective area RA has a first pretilt angle, and the first hardened layer 310 corresponding to the transmissive area TA has a second pretilt angle. Also in the present exemplary embodiment, the second hardened layer 320 has a third pretilt angle, and the second hardened layer 320 corresponding to the transmissive area TA has a fourth pretilt angle.

Therefore, pretilt angles of the reflective area RA and the transmissive area TA are effectively controlled using the reactive mesogenic monomer, so that V-R curve characteristics and V-T curve characteristics may be obtained.

An exemplary embodiment of a manufacturing method of the third exemplary embodiment of an LCD panel 700 is substantially similar to a manufacturing method of the first

exemplary embodiment of an LCD panel 400 which is described referring to FIG. 3. Thus, a detailed description thereof will be omitted.

Exemplary Embodiment 4

FIG. 16 is a cross-sectional view of a fourth exemplary embodiment of an LCD panel according to the present invention. FIG. 17A is a top plan layout view illustrating an array substrate of FIG. 16. FIG. 17B is a top plan layout view illustrating an opposite substrate of FIG. 16. Hereafter, the same reference numerals will be used to refer to the same or like parts as in the previous exemplary embodiments, and any further explanation concerning the above elements will be omitted.

The LCD panel 800 includes an array substrate 100, an opposite substrate 200 and a liquid crystal layer 300.

The array substrate 100 includes a first base substrate 101, a gate line 111, a storage line 115, a gate insulation layer 120, a data line 141, a switching element TR, an organic layer 150, a reflective electrode 160, an insulation layer 165, a transparent electrode 170 and a first alignment layer 180.

The reflective electrode 160 is disposed on the organic layer 150. In one exemplary embodiment, the reflective electrode 160 may be electrically isolated from the switching element TR. When the reflective electrode 160 is expanded to an adjacent pixel area along the gate line 111, a peripheral area of the pixel area 'P' may be utilized as a reflective area. Thus, as the reflective area is increased, the LCD panel may have high reflecting characteristic.

The insulation layer 165 is disposed on the first base substrate 101 having the reflective electrode 160 disposed thereon to cover the reflective electrode 160. That is, the insulation layer 165 is disposed between the reflective electrode 160 and the transparent electrode 170, and is disposed between the gate insulation layer 120 and the transparent electrode 170 in an area corresponding with the transmissive area TA.

The transparent electrode 170 is formed on a pixel area 'P' including the transmissive area TA and the reflective area RA. The transparent electrode 170 is a pixel electrode formed on the pixel area 'P'. The transparent electrode 170 is electrically connected to the switching element TR through the contact hole 155. In one exemplary embodiment, the contact hole 155 may be formed by simultaneously etching the organic layer 150 and the insulation layer 165.

The transparent electrode 170 includes a plurality of slit electrodes E1. In one exemplary embodiment, a width 'w' of the slit electrodes E1 and a distance 'b' between the slit electrodes E1 may be no more than about 10 μm .

In one exemplary embodiment, a long axis direction of the slit electrode E1 may be a unit direction. Alternative exemplary embodiments include configurations wherein the long axis direction of the slit electrode E1 has at least two directions, so that a viewing angle may be increased. In the transmissive area TA, an electric field may be formed by the transparent electrode 170 having the slit electrode E1 and a second common electrode 233 having a planar structure.

In the reflective area RA, the transparent electrode 170 having a plurality of slit electrodes E1 is positioned between the reflective electrode 160 and the first common electrodes 231 having a planar structure, so that an effective fringe field is generated. Thus, when an electric field is applied in the reflective area RA, liquid crystal molecules which are arranged in a vertical direction are aligned uniformly, so that reflectivity of the LCD panel may be enhanced.

In addition, in the reflective area RA, the reflective electrode **160** having a planar structure is used as a counter electrode of the transparent electrode **170**, so that the reflective electrode **160** is extended to an adjacent pixel area along the gate line **111** so that a peripheral area of the pixel area P may be utilized as a reflective area. Thus, as the reflective area is wider, the LCD panel may have high reflectivity.

Additionally, as the storage line **115** is disposed in the reflective area RA substantially parallel with the gate line **111**, a decreasing of an aperture ratio due to the storage line **115** formed from a nontransparent metal material may be prevented. In one exemplary embodiment, the storage line **115** includes a nontransparent metal material, so that a resistance thereof may be small. Also, in the present exemplary embodiment the storage line **115** has a planar structure, so that the storage line **115** and the upper slit electrodes E1 may form a storage capacitor having a sufficient capacitance.

Moreover, the contact hole **155** is disposed in a boundary area between the reflective area RA and the transmissive area TA, so that a loss of an aperture ratio may be minimized.

The opposite substrate **200** includes a first common electrode **231** disposed on the reflective area RA and a second common electrode **233** disposed on the transmissive area TA. In one exemplary embodiment, the first and second common electrodes **231** and **233** may have a planar structure to be spaced apart from each other.

The liquid crystal layer **300** includes a first hardened layer **310** and a second hardened layer **320**, exemplary embodiments of which may be formed from a reactive mesogenic monomer. In one exemplary embodiment, the first hardened layer **310** corresponding to the reflective area RA has a first pretilt angle, and the second hardened layer **320** corresponding to the transmissive area TA has a second pretilt angle. In one exemplary embodiment, the second hardened layer **320** corresponding to the reflective area RA has a third pretilt angle, and the second hardened layer **320** corresponding to the transmissive area TA has a fourth pretilt angle.

Thus, the pretilt angles of the reflective area RA and the transmissive area TA are effectively controlled using the reactive mesogenic monomer, so that a V-R curve and a V-T curve may be obtained.

An exemplary embodiment of a manufacturing method of the fourth exemplary embodiment of an LCD panel **800** is substantially the same as an exemplary embodiment of a manufacturing method of the previous exemplary embodiment of an LCD panel **400** which is described referring to FIG. 3. Thus, a detailed description thereof will be omitted.

FIG. 18 is a cross-sectional view illustrating a liquid crystal distribution of the exemplary embodiment of an LCD panel of FIG. 16 when an electric field is applied thereto. FIGS. 19A and 19B are top plan layout views illustrating a liquid crystal distribution of the exemplary embodiment of an LCD panel of FIG. 1 when an electric field is applied thereto.

Referring to FIGS. 18, 19A and 19B, liquid crystals LC are initially aligned in a vertical direction at the reflective area RA and the transmissive area TA. When an electric field is formed, the liquid crystals LC are aligned along a long axis of the slit electrode E1. Thus, the LCD panel may have high transmissivity and high reflectivity.

Moreover, when an electric field is applied to the liquid crystals LC, fringe field electric fields that are symmetric to each other are generated at a corner portion of the slit electrode due to the slit electrode E1 in the transmissive area TA. Accordingly, the liquid crystals LC are initially aligned to face with each other with respect to a short axis direction of the slit electrode E1, and the liquid crystals LC are aligned along a long axis direction of the slit electrode E1 when an

electric field is applied to the liquid crystals LC. Thus, a disclination line due to liquid crystal alignment defects is not generated, so that the LCD panel may have high transmissivity.

Moreover, in the reflective area RA, the transparent electrode **170** having the slit electrode E1 is disposed between a first common electrode **231** of a planar structure and a reflective electrode **160** of a planar structure, so that a strong fringe field electric field is generated at an edge portion of the slit electrode E1. Accordingly, the liquid crystals LC are uniformly aligned along a long axis direction of the slit electrode E1, so that a reflectivity may be increased. In one exemplary embodiment, a width W1 of the slit electrode E1 and a distance b1 between the slit electrodes E1 are no more than about 10 μm .

Moreover, when an electric field is applied to the liquid crystals LC, the liquid crystals LC are aligned along a long axis direction in the reflective area RA and the transmissive area TA. Accordingly, the long axis direction of the slit electrode E1 may be at least two directions, so that alignment directions of the liquid crystals LC are symmetric to each other so that light viewing characteristics may be enhanced. The long axis direction of the slit electrode E1 may be formed in various directions.

Furthermore, in one exemplary embodiment a multiplication of a cell gap 'dt' of the liquid crystal layer **300** by a refractive index Δn of liquid crystal molecules may be about 0.25 μm to about 0.6 μm in the transmissive area TA, and a multiplication of a cell gap 'dr' of the liquid crystal layer **300** by a refractive index Δn of liquid crystal molecules may be no more than about 0.3 μm in the reflective area RA.

According to exemplary embodiments of the present invention, a pixel electrode and/or a common electrode having a plurality of slit electrodes formed thereon align liquid crystal in a long axis direction of the slit electrode, so that high transmissivity and high reflectivity may be obtained. Moreover, a wide viewing angle may be obtained.

Moreover, a reactive mesogenic hardened layer having a pretilt angle corresponding to the reflective mode is formed in the reflective area, and a reactive mesogenic hardened layer having a pretilt angle corresponding to the transmissive mode is formed in the transmissive area using the first and second common electrodes spaced apart from each other in correspondence with a reflective area and a transmissive area, so that a threshold voltage of a V-R curve and a threshold voltage of a V-T curve may be corresponding to each other.

The foregoing is illustrative of the present invention and is not to be construed as limiting thereof. Although a few example embodiments of the present invention have been described, those skilled in the art will readily appreciate that many modifications are possible in the example embodiments without materially departing from the novel teachings and advantages of the present invention. Accordingly, all such modifications are intended to be included within the scope of the present invention as defined in the claims. In the claims, means-plus-function clauses are intended to cover the structures described herein as performing the recited function and not only structural equivalents but also equivalent structures. Therefore, it is to be understood that the foregoing is illustrative of the present invention and is not to be construed as limited to the specific example embodiments disclosed, and that modifications to the disclosed example embodiments, as well as other example embodiments, are intended to be included within the scope of the appended claims. The present invention is defined by the following claims, with equivalents of the claims to be included therein.

What is claimed is:

1. A liquid crystal display panel comprising:
an array substrate comprising:
a pixel electrode disposed in a pixel area, the pixel electrode including a reflective electrode disposed in a reflective area of the pixel area and a transparent electrode disposed in a transmissive area of the pixel area, at least one of the reflective electrode and the transparent electrode including a plurality of first slit electrodes;
an opposite substrate comprising:
a first common electrode disposed in alignment with the reflective area, the first common electrode including a plurality of second slit electrodes having a width substantially equal to or wider than that of an individual first slit electrode of the plurality of first slit electrodes; and
a liquid crystal layer interposed between the array substrate and the opposite substrate,
wherein the reflective electrode is closer to the opposite substrate than the transparent electrode.
2. The liquid crystal display panel of claim 1, wherein a width of the individual first slit electrode is less than about 10 μm and a distance between adjacent first slit electrodes is less than about 10 μm .
3. The liquid crystal display panel of claim 1, wherein the plurality of first slit electrodes has a plurality of long axis directions and the plurality of second slit electrodes has a plurality of long axis directions.
4. The liquid crystal display panel of claim 1, further comprising a second common electrode spaced apart from the first common electrode and disposed in alignment with the transmissive area.
5. The liquid crystal display panel of claim 4, wherein the second common electrode has a planar structure.
6. The liquid crystal display panel of claim 1, wherein the liquid crystal layer comprises:
a first hardened layer including a reactive mesogenic monomer hardened on a first alignment layer of the array substrate; and
a second hardened layer including a reactive mesogenic monomer hardened on a second alignment layer of the opposite substrate.
7. The liquid crystal display panel of claim 6, wherein the first hardened layer has a first pretilt angle corresponding to the reflective area and a second pretilt angle corresponding to the transmissive area, and
the second hardened layer has a third pretilt angle corresponding to the reflective area and a fourth pretilt angle corresponding to the transmissive area.
8. The liquid crystal display panel of claim 1, wherein a width of the second slit electrode is about 0.5 μm to about 2 μm , when a width of the first slit electrode is about 1 μm .
9. The liquid crystal display panel of claim 1, wherein a multiplication of a cell gap of the liquid crystal layer by a refractive index Δn of liquid crystal molecules is about 0.25 μm to about 0.6 μm in the transmissive area, and a multiplication of a cell gap of the liquid crystal layer by a refractive index Δn of liquid crystal molecules is no more than about 0.3 μm in the reflective area.

10. A liquid crystal display panel comprising:
an array substrate having a pixel area which is divided into the reflective area and a transmissive area, the array substrate comprising:
a reflective electrode disposed in the reflective area; and
a transmissive electrode disposed in substantially the entire pixel area in alignment with the reflective electrode, the transmissive electrode having a plurality of slit electrodes;
an opposite substrate disposed substantially opposite to the transmissive electrode, and comprising a common electrode; and
a liquid crystal layer interposed between the array substrate and the opposite substrate,
wherein the reflective electrode is closer to the opposite substrate than the transmissive electrode disposed in the transmissive area.
11. The liquid crystal display panel of claim 10, wherein the array substrate further comprises an insulation layer disposed between the reflective electrode and the plurality of slit electrodes.
12. The liquid crystal display panel of claim 10, wherein a width of an individual slit electrode of the plurality of slit electrodes is less than about 10 μm and a distance between adjacent slit electrodes of the plurality of slit electrodes is less than about 10 μm .
13. The liquid crystal display panel of claim 10, wherein the plurality of slit electrodes has a plurality of long axis directions.
14. The liquid crystal display panel of claim 10, wherein the common electrode comprises:
a first common electrode disposed in alignment with the reflective area; and
a second common electrode spaced apart from the first common electrode and disposed in alignment with the transmissive area.
15. The liquid crystal display panel of claim 14, wherein the first and second common electrodes have a planar structure.
16. The liquid crystal display panel of claim 15, wherein the liquid crystal layer comprises:
a first hardened layer including a reactive mesogenic monomer hardened on a first alignment layer of the array substrate; and
a second hardened layer including a reactive mesogenic monomer hardened on a second alignment layer of the opposite substrate.
17. The liquid crystal display panel of claim 16, wherein the first hardened layer has a first pretilt angle corresponding to the reflective area and a second pretilt angle corresponding to the transmissive area, and
the second hardened layer has a third pretilt angle corresponding to the reflective area and a fourth pretilt angle corresponding to the transmissive area.
18. The liquid crystal display panel of claim 10, wherein a multiplication of a cell gap of the liquid crystal layer by a refractive index Δn of liquid crystal molecules is about 0.25 μm to about 0.6 μm in the transmissive area, and a multiplication of a cell gap of the liquid crystal layer by a refractive index Δn of liquid crystal molecules is no more than about 0.3 μm in the reflective area.

* * * * *

专利名称(译)	液晶显示面板及其制造方法		
公开(公告)号	US8390773	公开(公告)日	2013-03-05
申请号	US12/469211	申请日	2009-05-20
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	JEONG YOUN HAK OH KEUN CHAN HAM YEON SIK SEONG DONG GI KIM KANG WOO JEON YEON MUN LEE HEE HWAN		
发明人	JEONG, YOUN-HAK OH, KEUN-CHAN HAM, YEON-SIK SEONG, DONG-GI KIM, KANG-WOO JEON, YEON-MUN LEE, HEE-HWAN		
IPC分类号	G02F1/1335		
CPC分类号	G02F1/133371 G02F1/133555 G02F1/134309 G02F2001/134318 G02F1/133707		
代理机构(译)	康托科尔伯恩LLP		
优先权	1020080083715 2008-08-27 KR		
其他公开文献	US20100053518A1		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示面板包括：阵列基板，包括设置在像素区域中的像素电极，所述像素电极包括设置在所述像素区域的反射区域中的反射电极，以及设置在所述像素区域的透射区域中的透明电极，所述反射电极中的至少一个透明电极包括多个第一狭缝电极，相对基板包括与反射区域对齐设置的第一公共电极，第一公共电极包括多个第二狭缝电极，每个第二狭缝电极的宽度大于个体的宽度多个第一狭缝电极的狭缝电极，以及插入在阵列基板和相对基板之间的液晶层。

