



US007483114B2

(12) **United States Patent**
Lee et al.

(10) **Patent No.:** **US 7,483,114 B2**
(45) **Date of Patent:** **Jan. 27, 2009**

(54) **LIQUID CRYSTAL DISPLAY DEVICE,
SUBSTRATE BONDING APPARATUS, AND
METHOD FOR FABRICATING LIQUID
CRYSTAL DISPLAY DEVICE USING THE
SAME**

(75) Inventors: **Hyun Kyu Lee**, Seoul (KR); **Hyun Sang
Chung**, Kyonggi-do (KR); **Young Suk
Park**, Kyonggi-do (KR)

(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 419 days.

(21) Appl. No.: **10/967,263**

(22) Filed: **Oct. 19, 2004**

(65) **Prior Publication Data**

US 2005/0083478 A1 Apr. 21, 2005

(30) **Foreign Application Priority Data**

Oct. 20, 2003 (KR) 10-2003-0073056
Oct. 20, 2003 (KR) 10-2003-0073057

(51) **Int. Cl.**
G02F 1/1339 (2006.01)
G02F 1/1341 (2006.01)

(52) **U.S. Cl.** **349/187**; 349/110; 349/156;
349/190

(58) **Field of Classification Search** 349/42,
349/110, 155, 156, 157, 187, 188, 190
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,720,173 A * 1/1988 Okada et al. 349/156

5,684,556 A * 11/1997 Shimamune 349/158
5,726,728 A * 3/1998 Kondo et al. 349/156
5,852,487 A * 12/1998 Fujimori et al. 349/162
6,023,310 A 2/2000 Kawamoto et al. 349/54
6,067,144 A 5/2000 Murouchi 349/156
6,078,379 A 6/2000 Nagae et al. 349/155
6,115,098 A 9/2000 Kume et al. 349/156
2003/0128327 A1 * 7/2003 Noiri 349/156

FOREIGN PATENT DOCUMENTS

JP	05-203925	8/1993
JP	7-28071	1/1995
JP	07-28701	1/1995
JP	07-056154	3/1995
JP	2000-250049	9/2000
JP	2001-166317	6/2001
JP	2001-264740	9/2001
JP	2002-162633	6/2002
JP	2002-214626	7/2002
KR	10-0144896 B1	4/1998
KR	1998-042841	8/1998
KR	2002-0088447	11/2002
KR	10-20030021743 A	3/2003
TW	457386 B	10/2001
TW	466365	12/2001

* cited by examiner

Primary Examiner—Dung Nguyen

Assistant Examiner—Tai Duong

(74) *Attorney, Agent, or Firm*—Morgan, Lewis & Bockius
LLP

(57) **ABSTRACT**

A liquid crystal display device includes a plurality of guide walls formed at regular intervals on a first substrate, the guide walls extending lengthwise or widthwise within an active region of the first substrate, a liquid crystal material filled between the guide walls, and a second substrate being attached to the first substrate sandwiching the liquid crystal material therebetween.

4 Claims, 9 Drawing Sheets




FIG. 1
Related Art




FIG. 2
Related Art




FIG. 3A



FIG. 3B




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9A




FIG. 9B





FIG. 10



LIQUID CRYSTAL DISPLAY DEVICE, SUBSTRATE BONDING APPARATUS, AND METHOD FOR FABRICATING LIQUID CRYSTAL DISPLAY DEVICE USING THE SAME

The present invention claims the benefit of Korean Patent Application No. P2003-73056 filed in Korea on Oct. 20, 2003 and Korean Patent Application No. P2003-73057, which are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display device, and more particularly, to a liquid crystal display device and a method for fabricating the same using a liquid crystal dispensing method and a bonding apparatus for bonding substrates at an atmospheric pressure.

2. Discussion of the Related Art

Demands for display devices have increased with development of an information society. Accordingly, many efforts have been made to research and develop various flat display devices, such as liquid crystal display (LCD) devices, plasma display panel (PDP) devices, electro-luminescent display (ELD) devices, and vacuum fluorescent display (VFD) devices. In particular, liquid crystal display (LCD) devices have been most widely used as a substitute for a cathode ray tube (CRT) because of their advantageous characteristics of thin profile, lightness, and low power consumption. LCD devices have been implemented as display devices for notebook computers, desktop computers, televisions, and the like. One consideration in developing LCD devices is to develop LCD devices having a high quality picture, such as high resolution and high luminance with a large-sized screen, while maintaining lightness, thin profile, and low power consumption.

In general, the LCD device includes an LCD panel for displaying an image and a driver for supplying a driving signal to the LCD panel. In addition, the LCD panel includes first and second substrates attached to each other with a cell gap therebetween, and a liquid crystal layer formed in the cell gap. Further, alignment layers are respectively formed on facing surfaces of the first and second substrates, wherein the alignment layers are rubbed to align the liquid crystal layer. For maintaining fixed cell gaps between the first and second substrates, spacers are spread or fixed between the first and second substrates.

The first substrate or a thin film transistor array substrate includes a plurality of gate lines arranged along a first direction, a plurality of data lines arranged along a second direction perpendicular to the first direction, a plurality of pixel electrodes arranged in a matrix-type configuration within pixel regions defined by the crossings of the gate and data lines, and a plurality of thin film transistors for switching signals from the data lines to the pixel electrodes based on signals received from the gate lines.

Further, the second substrate or a color filter array substrate includes a black matrix layer, a color filter layer, and a common electrode. The color filter layer includes red, green, and blue color filters, wherein the color filter layer is formed by repetitively positioning the color filters in order of red(R), green(G), and blue(B) within regions corresponding to the pixel regions of the first substrate. Alternatively, in a liquid crystal display device of an In Plane Switching (IPS) mode, the common electrode may be formed on the first substrate.

Accordingly, the liquid crystal layer controls the intensity of light, and the light passes through the color filter layers of red(R), green(G), and blue(B) to represent color images.

In particular, the liquid crystal display layer is formed by a liquid crystal injection method or a liquid crystal dispensing method. In a liquid crystal injection method, two substrates are bonded to each other with an liquid crystal injection hole formed in the seal pattern, and a liquid crystal material is injected between the two substrates via the liquid crystal injection hole. In a liquid crystal dispensing method, an appropriate amount of the liquid crystal material is dispensed on one of the two substrates, and the two substrates are bonded to each other.

FIG. 1 illustrates a system for bonding substrates using a liquid crystal injection method according to the related art. As shown in FIG. 1, the two bonded substrates 10 are placed into a vacuum chamber 20 having a container 30 holding a liquid crystal material 31 therein. Then, a vacuum pump 25 evacuates the vacuum chamber 20, and the liquid crystal injection hole (not shown) in the bonded substrates 10 contacts the liquid crystal material 31 held in the container 30. Further, air or N₂ gas is supplied to the vacuum chamber 20 to bring the vacuum chamber 20 into an atmospheric pressure state. As a result, the liquid crystal material 31 is injected between the two bonded substrates 10 by the capillary tube phenomenon. When the liquid crystal material 31 is filled between the two bonded substrates fully, the liquid crystal injection hole is sealed.

FIG. 2 illustrates a system for bonding substrates using a liquid crystal dispensing method according to the related art. As shown in FIG. 2, a substrate bonding apparatus is placed inside a vacuum chamber 21. The substrate bonding apparatus includes an upper stage 40 for holding a first substrate 10a, a lower stage 41 for holding a second substrate 10b having the liquid crystal material 31 dispensed thereon, a vacuum pump 25 for evacuating the vacuum chamber 21, and a vent means 26 for injecting gas or air into the vacuum chamber 21. Although not shown, the upper, and lower stages 40 and 41 are provided with vacuum holes, and electrostatic chucks for adsorbing and holding the substrates 10a and 10b, respectively.

In addition, a seal pattern 27 is formed on a periphery of the second substrate 10b, and the liquid crystal material 30 is dispensed inside the seal pattern 27. Although not shown, column spacers are formed on one of the first and second substrates 10a and 10b, and an alignment film also is formed on one of the first and second substrates 10a and 10b.

In particular, the first substrate 10a having no liquid crystal material dispensed thereon is loaded on the vacuum chamber 21, and the upper stage 40 is moved down under the control of a moving means 42 to adsorb the first substrate 10a. Then, the second substrate 10b having the liquid crystal material 30 dispensed thereon is loaded on the vacuum chamber 21 and positioned on the lower stage 41, so that the lower stage 41 adsorbs the second substrate 10b by vacuum.

Then, the upper and lower stages 40 and 41 respectively hold the first and second substrates 10a and 10b using the electrostatic chucks for preventing the substrates 10a and 10b from falling off the respective stages 40 and 41 at the time of evacuation of the vacuum chamber 21.

After securing the first and second substrates 10a and 10b with the upper and lower stages 40 and 41, the vacuum pump 25 is turned on to evacuate the vacuum chamber 21. Then, the upper stage 40 is moved down to bond the first and second substrates 10a and 10b with the seal pattern, and air or gas is injected through the vent means 26 to bring the vacuum chamber 21 into an atmospheric state. Then, because an

inside of the two bonded substrates is in a vacuum state and the vacuum chamber **21** is in the atmospheric state, the two substrates are pressed and bonded by a pressure difference.

In particular, the bonding of the first and second substrates **10a** and **10b** are performed in a vacuum state for increasing fluidity of the dispensed liquid crystal material **31** to uniformly distribute the liquid crystal material. If the distribution of the liquid crystal material **31** is not uniform, bubbles may be formed in the resultant liquid crystal layer, thereby causing defects, such as picture distortion in the resultant liquid crystal display panel.

In addition, the apparatus and method for fabricating a liquid crystal display device according to the related art have the following problems. First, the related art liquid crystal injection method requires the vacuum chamber, the vacuum pump, and the like for injection of the liquid crystals in a vacuum state, thereby requiring complex system and increasing production cost. Further, the liquid crystal dispensing method according to the related art also requires the vacuum chamber, the vacuum pump, the electrostatic chucks, and the vent means to perform bonding of the first and second substrates in a vacuum state, thereby increasing production cost. Moreover, since the vacuum chamber needs to be evacuated, overall production time is prolonged, thereby reducing fabrication efficiency.

Furthermore, in the related art, smooth spread of the liquid crystals is achieved by creating a pressure state for the dispensed liquid crystals at a vacuum. However, to create the environment for the liquid crystals at a vacuum is complicated since vacuum suction is not applicable to the holding of the substrates at the stages due to the vacuum state of an inside of the vacuum chamber.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a liquid crystal display device, and a substrate bonding apparatus, and a method for fabricating the liquid crystal display device using the same that substantially obviate one or more of the problems due to limitations and disadvantages of the related art.

An object of the present invention is to provide a liquid crystal display device, and method and bonding apparatus for fabricating the liquid crystal display device using the same that perform a substrate bonding process in an atmospheric state, thereby simplifying a bonding apparatus, shortening a process time period, improving productivity, and reducing production cost.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described herein, a liquid crystal display device includes a plurality of guide walls formed at regular intervals on a first substrate, the guide walls extending lengthwise or widthwise within an active region of the first substrate, a liquid crystal material filled between the guide walls, and a second substrate being attached to the first substrate sandwiching the liquid crystal material therebetween.

In another aspect, a method for fabricating a liquid crystal display device includes providing first, and second substrates having a plurality of pixel regions, forming guide walls on the

second substrate between the pixel regions, dispensing a liquid crystal material on the second substrate having the guide walls formed thereon, and bonding the first and second substrates to each other.

In yet another aspect, a method for fabricating a liquid crystal display device includes dispensing a liquid crystal material on a first substrate, affixing the first substrate having the liquid crystal material dispensed thereon at a lower stage, affixing a second substrate at an upper stage, heating the liquid crystals dispensed on the second substrate to an isotropization temperature, and bonding the first and second substrates to each other.

In another aspect, a liquid crystal display device fabricated using a method including dispensing a liquid crystal material on a first substrate, affixing the first substrate having the liquid crystal material dispensed thereon at a lower stage, affixing a second substrate at an upper stage, heating the liquid crystals dispensed on the second substrate to an isotropization temperature, and bonding the first and second substrates to each other, the liquid crystal display device includes a seal pattern at a peripheral of one of the first and second substrates for bonding the first and second substrates to each other.

In yet another aspect, a substrate bonding apparatus for fabricating a liquid crystal display device includes an upper stage for holding a first substrate, a lower stage for holding a second substrate having a liquid crystal material dispensed thereon, and heating means for heating the liquid crystal material to an isotropization temperature.

In another aspect, a method for fabricating a liquid crystal display device using a substrate bonding apparatus including an upper stage for holding a first substrate, a lower stage for holding a second substrate having a liquid crystal material dispensed thereon, and heating means for heating the liquid crystal material to an isotropization temperature, includes dispensing the liquid crystal material from a dispenser onto the second substrate, and joining the first and second substrates by contacting an inner surface of the first substrate with the liquid crystal material dispensed on the second substrate.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention. In the drawings:

FIG. 1 illustrates a system for bonding substrates using a liquid crystal injection method according to the related art;

FIG. 2 illustrates a system for bonding substrates using a liquid crystal dispensing method according to the related art;

FIG. 3A is a cross-sectional view of a substrate in accordance with an embodiment of the present invention;

FIG. 3B is a planar view of the substrate shown in FIG. 3A;

FIG. 4 illustrates a layout of a liquid crystal display panel including the substrate shown in FIG. 3A;

FIG. 5 schematically illustrates a substrate bonding apparatus for fabricating a liquid crystal display device in accordance with an embodiment of the present invention;

FIG. 6 is a flow chart illustrating a method for forming a liquid crystal display panel in accordance with an embodiment of the present invention;

FIG. 7 schematically illustrates a substrate bonding apparatus for fabricating a liquid crystal display device in accordance with another embodiment of the present invention;

FIG. 8 schematically illustrates a process for dispensing a liquid crystal material in accordance with an embodiment of the present invention;

FIG. 9A schematically illustrates an arrangement of liquid crystal molecules at an atmospheric pressure and a room temperature in accordance with an embodiment of the present invention;

FIG. 9B schematically illustrates an arrangement of liquid crystal molecules at an atmospheric pressure and in a state heated at or over an isotropization temperature T_i in accordance with an embodiment of the present invention; and

FIG. 10 illustrates a planar view of a heating means in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

FIG. 3A is a cross-sectional view of a substrate in accordance with an embodiment of the present invention, and FIG. 3B is a planar view of the substrate shown in FIG. 3A. In FIG. 3A, a plurality of guide walls **160** are formed on a substrate **110b**. The substrate **110b** may be either an array substrate having thin film transistors formed thereon or a color filter substrate having color filters formed thereon. In addition, the guide walls **160** may be formed projecting from an upper surface of the substrate **110b** at regular intervals within a display area of the substrate **110b**. The guide walls **160** may include a transparent material, and a cross-section of the guide walls **160** may be rectangular, triangular, trapezoidal or curved. In particular, the guide walls **160** may have a height such that they also function to maintain a cell gap when the substrate **110b** is attached to a second substrate (not shown). In other words, the guide walls **160** may function as spacers. Further, as shown in FIG. 3B, the guide walls **160** may be formed parallel to one another in a length-wise direction.

FIG. 4 illustrates a layout of a liquid crystal display panel including the substrate shown in FIG. 3A. In FIG. 4, as an example, the substrate **110b** is shown to be a color filter substrate having a black matrix layer **150b** formed thereon. In addition, the guide walls **160** are formed at regular intervals corresponding to a plurality of pixel regions **150a**. The pixel regions **150a** may be defined by the crossing of a plurality of gate and data lines formed on a corresponding substrate (not shown), and the guide walls **160** may be formed in a vertical or horizontal direction of the pixel regions **150a** corresponding to the gate lines or the data lines. Alternatively, although not shown, the guide walls **160** also may be formed in both the vertical and horizontal directions similar to the black matrix layer **150b**.

Further, a plurality of color filters, R, G and B, may be formed within the pixel regions **150a**. In particular, the black matrix layer **150b** is a lattice formed on the substrate **110b** between the pixel regions **150a**. Thus, a liquid crystal material is kept within the pixel regions **150a** for selectively transmitting light to display a desired image, while the black matrix layer **150b** shield light from regions overlapping the black matrix layer **150b**. Therefore, it is preferable that the guide walls **160** are formed along the black matrix layer **150b** for not interfering light paths that display the image. Accord-

ingly, the guide walls **160** do not spread irregularly and do not interfere with light paths as the spacers according to the related art.

Since the pixel regions **150a** are micronite, the guide walls **160** at the micronite intervals hold the liquid crystal material dispensed on the substrate **110b** between the guide walls **160**. In particular, a surface tension of the liquid crystal material is formed by a cohesive force of the liquid crystal molecules, and a force between the guide walls **160** and the liquid crystal molecule is an adhesive force. If the cohesive force is greater than the adhesive force, the liquid crystals are filled between the guide walls **160** in a shape convex upward due to the surface tension.

FIG. 5 schematically illustrates a substrate bonding apparatus for fabricating a liquid crystal display device in accordance with an embodiment of the present invention. In FIG. 5, a substrate bonding apparatus includes an upper stage **140** and a lower stage **141**. In particular, the upper stage **140** may be vertically movable under the control of a stage moving means **142**, while the lower stage **141** may remain stationary. Alternatively, one of or both the upper and lower stages **140** and **141** may be movable vertically and/or horizontally.

A liquid crystal material **131** is dispensed on the first substrate **110b** which is placed on the lower stage **141**. In particular, the liquid crystal material **131** is filled between the guide walls **160** and may have a convex surface shape projecting upward between the guide walls **160** for the reasons described above with respect to FIG. 4.

In addition, a second substrate **110a** may be held by the upper stage **140**. As the upper stage **140** moves downward controlled by the stage moving means **142** to bond the first and second substrates **110b** and **110a**, the convex portion/surface of the liquid crystal material **131** is brought into close contact with an underside surface of the second substrate **110a**, thereby preventing formation of bubbles in the liquid crystal material **131** even in a non-vacuum environment. Accordingly, the substrate bonding apparatus according to an embodiment of the present invention does not require a vacuum state for operation, and can operate satisfactorily at an atmospheric pressure by using the guide walls **160**.

In particular, the first and second substrates **110b** and **110a** may be bonded to each other by a sealant **132** formed at a peripheral of one of the first and second substrates **110b** and **110a**. Further, a predetermined cell gap between the first and second substrates **110b** and **110a** is maintained by the guide walls **160**. Thus, the guide walls **160** prevent the liquid crystal material **131** from containing bubbles even if the first and second substrates **110b** and **110a** are bonded under the atmospheric pressure, and the guide walls **160** also function as spacers for maintaining a uniform cell gap.

Moreover, since the bonding is not performed in the vacuum state, the first and second substrates **110b** and **110a** can be respectively held at the upper and lower stages **140** and **141** and do not require a complicate electrostatic chuck of the related art. Alternatively, although not shown, a plurality of vacuum holes may be formed in a lower surface of the upper stage **140** and a vacuum pump may be connected to an upper surface of the lower stage **141**, thereby bonding the first and second substrates **110b** and **110a** at the vacuum holes.

The guide walls **160** may be formed of an acryl group material since the acryl group material has high light transmittivity and forms a strong adhesive force with the liquid crystal material **131**. In addition, the guide walls **160** may be formed in a desired shape by a photo-lithographic or printing method. Further, the guide walls **160** may be formed of any material that satisfies the above-discussed characteristics.

Alternatively, the first substrate **110b** may be an array substrate having a plurality of thin film transistors formed thereon. In particular, the thin film transistors may be formed on the first substrate **110b** and the guide walls **160** may subsequently be formed on the first substrate **110b**. However, an upper surface of the first substrate **110b** should be of a certain flatness after the formation of the thin film transistors, such that the guide walls **160** may be formed uniformly on the first substrate **110b**. Further, the guide walls **160** may be formed at positions opposite to the gate lines or the data lines.

FIG. 6 is a flow chart illustrating a method for forming a liquid crystal display panel in accordance with an embodiment of the present invention. As shown in FIG. 6, a method for forming a liquid crystal display panel includes forming a synthetic resin layer on a substrate at a first step **1S**. The substrate may be a thin film transistor substrate or a color filter substrate. Also, the transparent synthetic resin may include an acryl group material. Then, a photoresist is coated on an upper surface of the synthetic resin layer at a second step **2S**.

Further, light, e.g., an UV beam, is directed onto the photoresist through a mask at a third step **3S**, such that light is selectively irradiated on the photoresist. In particular, the photoresist may be a negative photoresist or a positive photoresist. Then, the substrate is developed at a fourth step **4S**, thereby patterning the photoresist. In addition, the synthetic resin is etched by using the patterned photoresist as a mask to form a plurality of guide walls. Subsequently, the photoresist is removed.

Moreover, a sealant is coated on the substrate having the guide walls formed thereon and an appropriate amount of a liquid crystal material is dispensed on the substrate at a fifth step **5S**. In particular, the sealant may be coated on a periphery of a display region of the substrate for preventing the liquid crystal material from flowing outwardly, and the liquid crystal material is dispensed between the guide walls at the display region within the sealant **132**. Then, the substrate is bonded to a corresponding substrate at a sixth step **S6**.

In particular, the substrates may be bonded using the substrate bonding apparatus shown in FIG. 5. For example, if the color filter substrate has the guide walls formed thereon and the liquid crystal material dispensed thereon, the color filter substrate is positioned on the lower stage **141** (shown in FIG. 5), the thin film transistor array substrate is positioned on the upper stage **140** (shown in FIG. 5), and the two substrates are bonded. Alternatively, if the thin film transistor array substrate has the guide walls formed thereon and the liquid crystal material dispensed thereon, the thin film transistor array substrate is positioned on the lower stage **141** (shown in FIG. 5), the color filter substrate is positioned on the upper stage **140** (shown in FIG. 5), and the two substrates are bonded. Then, the sealant is set or cured.

Since the above-described steps are susceptible to dust particles, and a defective pattern caused by the dust particles is liable to cause defects on the whole liquid crystal display panel, it is required that above steps are performed in a clean environment, and strict management of materials/equipment is important. Alternatively or in addition, a cleaning process may be additionally performed between steps to remove any dust particles.

FIG. 7 schematically illustrates a substrate bonding apparatus for fabricating a liquid crystal display device in accordance with another embodiment of the present invention. In FIG. 7, a substrate bonding apparatus includes an upper stage **140** and a lower stage **141**. In particular, the upper stage **140** may be vertically movable under the control of a stage moving means **142**, while the lower stage **141** may remain sta-

tionary. Alternatively, one of or both the upper and lower stages **140** and **141** may be movable vertically and/or horizontally.

In addition, a heating means **170** is placed under the lower stage **141**. The heating means **170** may be inside of the lower stage **141** or may be mounted separately from the lower stage **141**. As the liquid crystal material **131** is dispensed on an upper surface of the first substrate **110b** which is placed on the lower stage **141**, the liquid crystal material **131** is heated by the heating means **170**. In particular, the heating means **170** may heat the liquid crystal material **131** to an isotropization temperature T_i . The heating means **170** may be spaced from the lower surface of the first substrate **110b**, thereby forming a space for allowing the heat generated from the heating means **170** be uniformly distributed to the lower surface of the first substrate **110b**. Also, the first substrate **110b** may be a thin film transistor substrate but may more preferably be a color filter substrate, since a thin film transistor substrate may include heat sensitive circuits formed thereon.

Further, a heat pipe having a two-phase flow (not shown) may be provided between the heating means **170** and the first substrate **10b** to enhance the heat distribution. By injecting a liquid phase material into the heat pipe, and adjusting an inside pressure to set a temperature at which the two-phase flow starts in the neighborhood of the isotropization temperature T_i , a more uniform heat transfer between the heating means **170** and the lower stage **141** can be made by phase change and convection heat transfer of the two-phase flow at an elevated temperature. That is, as a higher density liquid phase working substance positions at a surface in contact with the heating means **170** by gravity, and a gas phase working substance positions at a surface in contact with the first substrate **110b** or the lower stage **141**, the heat transfer from a lower portion to an upper portion is made through phase change. In a process in which the gas phase working substance positioned at the upper portion of the heat pipe heat exchanges with the lower stage **141** or the first substrate **110b**, and condenses to move downward, the upper surface of the heat pipe can always have a uniform temperature distribution. Accordingly, the heat pipe can perform heat transfer to the first substrate **110b** at a uniform temperature, with a more heat transfer quantity. For example, a plurality of the heat pipes may be mounted in shapes of pipes and the heat pipes may have a flat hexahedral shape corresponding to a size of the first substrate **110b**.

In addition, a second heating means (not shown) may be provided on an upper side of the upper stage **140**. Thus, the second heating means may supplement the heating means **170** to heat the substrate held at the upper stage **140** to or over a predetermined temperature, such that the liquid crystal material **131** is at or above the isotropization temperature T_i at the moment of the bonding.

Moreover, a plurality of vacuum holes (not shown) may be formed in an underside surface of the upper stage **140** or in an upper surface of the lower stage **141**. In particular, the vacuum holes may be connected to a vacuum pumping device for holding the substrates **110a** and **110b** by vacuum.

FIG. 8 schematically illustrates a process for dispensing a liquid crystal material in accordance with an embodiment of the present invention. As shown in FIG. 8, the liquid crystal material **131** may be dispensed on the upper surface of the first substrate **110b** by dropping a plurality of dots of the liquid crystal material **131** via a nozzle **121** on the first substrate **110b**. To form an even layer of the liquid crystal material **131** across the upper surface of the first substrate **110b**, the lower stage **141** may be moved respective to the nozzle **121**.

In addition, the nozzle **121** may be connected to a syringe **120**. The syringe **120** may be connected to a reservoir storing the liquid crystal material **131**. Further, the syringe **120** may include a preheating means **120a** for heating the liquid crystal material **131** before dispensing/dropping the liquid crystal material **131** onto the first substrate **110b**. In particular, the preheating means **120a** may preheat the liquid crystal material **131** to a predetermined temperature, such that in combination with the heating means **170** (shown in FIG. 7), the liquid crystal material **131** reaches to the isotropization temperature T_i when the first and second substrates **110b** and **110a** are bonded to each other. Accordingly, the liquid crystal material **131** may be more easily spread across the upper surface of the first substrate **110b** for reasons which will be explained more in details with respect to FIGS. 9A and 9B.

FIG. 9A schematically illustrates an arrangement of liquid crystal molecules at an atmospheric pressure and a room temperature in accordance with an embodiment of the present invention, and FIG. 9B schematically illustrates an arrangement of liquid crystal molecules at an atmospheric pressure and in a state heated at or over an isotropization temperature T_i in accordance with an embodiment of the present invention.

As shown in FIG. 9A, at an atmospheric pressure and a room temperature, the liquid crystal material is in a liquid crystal phase, which is an intermediate phase between a liquid phase and a solid phase. When in the liquid crystal phase, the liquid crystal material has some fluidity but also has an orientation similar to a solid, thereby having a poor spreadability. In particular, liquid crystal molecules **131a** are oriented regularly, such that the liquid crystal molecules **131a** do not spread well due to an interference between the liquid crystal molecules **131a** and high viscosity after the liquid crystal molecules **131a** are dispensed on the substrate. Accordingly, if the substrates are bonded when the liquid crystal molecules **131a** do not spread well, air layers are formed between the liquid crystal molecules **131a**, thereby creating bubbles in the resultant liquid crystal layer and causing a defect in the resultant liquid crystal display panel.

As shown in FIG. 9B, when the liquid crystal material is heated to a temperature at or over the isotropization temperature T_i at an atmospheric pressure, the solid-like arrangement of the liquid crystal molecules **131a** (as shown in FIG. 9A) loosens and becomes less regular and less rigid. As a result, the interference between the liquid crystal molecules **131a** reduces, such that the liquid crystal molecules **131a** can be spread more smoothly to an even film shape. Accordingly, if the substrates are bonded after the liquid crystal material is heated to or over the isotropization temperature T_i , the evacuation of an inside of the bonding apparatus is not required to bond the substrates at the atmospheric pressure.

When a thermotropic liquid crystal material is heated to a temperature higher than the isotropization temperature T_i , the liquid crystal material undergoes a phase change and its molecular orientation/arrangement loosens. As a result, viscosity of the liquid crystal material reduces and fluidity of the liquid crystal material increases, such that the thermotropic liquid crystal material spreads well like a general fluid. In addition, the isotropization temperature T_i differs for various types of liquid crystal materials. For example, for nematic liquid crystals, the isotropization temperature T_i is in a range of about 70~80° C.

FIG. 10 illustrates a planar view of a heating means in accordance with an embodiment of the present invention. As shown in FIG. 10, the heating means **170** may include hot wires **170a** connected electrically for generating heat. Thus, when electricity is supplied to the hot wires **170a** from a

power source **170b**, the hot wires **170a** function as a resistor to generate heat at a desired temperature. Although not shown, the heating means **170** may include other types of heating devices to dispense heat onto the first substrate **110b** (shown in FIG. 7).

A method for bonding substrates by using the substrate bonding apparatus for fabricating a liquid crystal display in accordance with another embodiment of the present invention will be described in more detail by referring to FIG. 7. First, a sealant **132** is coated at a peripheral of the first substrate **110b**, and an appropriate amount of the liquid crystal material **131** is dispensed on the first substrate **110b** inside the sealant **132**. Of course, the sealant may be coated on the second substrate **110a**, and the liquid crystals may be dispensed on the first substrate **110b**.

Then, the second substrate **110a** is held by the upper stage **140**, and the first substrate **110b** having the liquid crystals dispensed thereon is held by the lower stage **141**. The first and second substrates **110b** and **110a** may be moved to the stages **140** and **141** by using a loader, a lift bar or the like. In addition, the stages **140** and **141** may generate a vacuum suction force to more securely hold the substrates.

Further, electricity is supplied to the heating means **170** to heat the liquid crystal material **131** dispensed on the first substrate **110b**. Upon heating the liquid crystal material **131** over the isotropization temperature T_i , arrangement of the liquid crystal molecules **131a** (shown in FIGS. 9A and 9B) loses orientation and improves fluidity of the liquid crystal material **131**. Accordingly, stable bonding of the substrates is possible because the liquid crystal material **131** can be spread evenly on the upper surface of the first substrate **110b** even under an atmospheric pressure. Therefore, different from the related art, it is not required to bond the substrates at a vacuum state.

If the liquid crystal material **131** is preheated before being dispensed, a time period for heating the liquid crystal material **131** to the isotropization temperature T_i can be shortened. In particular, the liquid crystal material **131** may be preheated by the preheating device **120a**.

Further, after the liquid crystal material **131** is heated over the isotropization temperature T_i , the first and second substrates **110b** and **110a** are bonded, and the sealant **132** is set. In particular, the temperature of the liquid crystal material **131** may be measured directly by placing a temperature sensor, such as a thermocouple, in direct contact with the liquid crystal material **131**.

Alternatively, the temperature of the liquid crystal material **131** may be estimated indirectly by measuring a temperature in the vicinity of the liquid crystal material **131**. For example, while maintaining the air temperature in the work room constant, a temperature of the heating means **170/120a** or the lower stage **141** is measured to estimate the temperature of the liquid crystal material **131**. In particular, a quantity of heat transfer from the heating means is reduced if the measured liquid crystal temperature is higher than the isotropization temperature T_i , or is increased if the measured liquid crystal temperature is lower than the isotropization temperature T_i . Such a process may be controlled by a control means, such as a microcomputer.

As a result, the liquid crystal display device, and substrate bonding apparatus and method for fabricating the same according to an embodiment of the present invention has the following advantages. First, the formation of the guide walls on the first or second substrate enables the liquid crystal

material be formed between the guide walls and prevents bubbles from occurring even if the bonding process is performed at an atmospheric pressure. Thus, extra units, such as the vacuum pump, the vacuum chamber, and the like, are not required, thereby simplifying the bonding apparatus. In addition, since the guide walls formed on the black matrix layer excluding the pixel regions also function to maintain a cell gap between the two substrates, no spacers are required additionally and light paths are not interfered.

Further, by bonding the substrates at an atmospheric pressure avoids evacuation of the work room, thereby significantly reducing processing time and improving productivity. Moreover, the present invention permits to make more stable and effective holding of the substrates at the stages by forming a plurality of vacuum holes in the stages, which provide vacuum suction force, without using the complicate electrostatic chucks for holding the substrates at the stages.

Furthermore, by heating the liquid crystal material to isotropization temperature T_i by using the heating means and/or the preheating means, an even film of the liquid crystal material is formed without having bubbles formed therein even if the bonding process is performed at an atmospheric pressure. Thus, extra units, such as the vacuum pump, the vacuum chamber, and the like, are not required, thereby simplifying the bonding apparatus and significantly improving productivity.

It will be apparent to those skilled in the art that various modifications and variations can be made in the liquid crystal display device, and substrate bonding apparatus and method for fabricating the same of the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A method for fabricating a liquid crystal display device, comprising:

providing first, and second substrates having a plurality of pixel regions;

forming guide walls on the second substrate between the pixel regions;

preheating of the liquid crystal material;

dispensing the preheated liquid crystal material on the second substrate having the guide walls formed thereon, wherein the liquid crystals are filled between the guide walls in a shape convex upward due to a surface tension of the liquid crystal material when a cohesive force of the liquid crystal molecules is greater than an adhesive force between the guide walls and the liquid crystal molecules; and

bonding the first and second substrates to each other at an atmospheric pressure, wherein the convex portion of the liquid crystal material is close contact with the first substrate, thereby preventing formation of bubbles in the liquid crystal material.

2. The method of claim 1, wherein the step of forming the guide walls includes coating and patterning an acryl group material.

3. The method of claim 1, wherein the second substrate is a thin film transistor substrate having gate lines and data lines formed thereon, and the guide walls are formed overlapping at least one of the gate lines and the data lines.

4. The method of claim 1, wherein the second substrates is a color filter substrate having a black matrix layer formed on regions except the pixel regions, and the guide walls are formed in a vertical or horizontal direction overlapping a portion of the black matrix layer.

* * * * *

专利名称(译)	液晶显示装置，基板贴合装置以及使用其制造液晶显示装置的方法		
公开(公告)号	US7483114	公开(公告)日	2009-01-27
申请号	US10/967263	申请日	2004-10-19
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG.飞利浦液晶CO. , LTD.		
当前申请(专利权)人(译)	LG显示器		
[标]发明人	LEE HYUN KYU CHUNG HYUN SANG PARK YOUNG SUK		
发明人	LEE, HYUN KYU CHUNG, HYUN SANG PARK, YOUNG SUK		
IPC分类号	G02F1/1339 G02F1/1341 G02F1/13 G02F1/1335 G02F1/1368		
CPC分类号	G02F1/13394 G02F1/1341 G02F2001/13415		
审查员(译)	NGUYEN , 龚便		
优先权	1020030073057 2003-10-20 KR 1020030073056 2003-10-20 KR		
其他公开文献	US20050083478A1		
外部链接	Espacenet USPTO		

摘要(译)

一种液晶显示装置，包括在第一基板上以规则间隔形成的多个引导壁，所述引导壁在所述第一基板的有源区域内纵向或横向延伸，液晶材料填充在所述引导壁之间，以及第二基板连接到第一基板上，将液晶材料夹在其间。

