



US 20070008475A1

(19) **United States**(12) **Patent Application Publication**
Tak et al.(10) **Pub. No.: US 2007/0008475 A1**(43) **Pub. Date: Jan. 11, 2007**(54) **LIQUID CRYSTAL DISPLAY**(30) **Foreign Application Priority Data**(75) Inventors: **Young-Mi Tak**, Seoul (KR); **Ae Shin**,
Cheongju-si (KR); **Dong-Gyu Kim**,
Yongin-si (KR); **Seung-Soo Baek**,
Seoul (KR)

May 13, 2003 (KR)..... 2003-30195

Publication Classification(51) **Int. Cl.**
G02F 1/1343 (2006.01)(52) **U.S. Cl.** 349/139(57) **ABSTRACT**

A liquid crystal display is provided, which includes: a first substrate; a first signal line formed on the first substrate; a second signal line formed on the first substrate and intersecting the first signal line; a pixel electrode including a plurality of partitions; a thin film transistor connected to the gate line, the data line, and the pixel electrode; a second substrate facing the second substrate; a common electrode formed on the second substrate and having an opening facing the first or the second signal line; and first and second domain defining members that define a plurality of domains in the liquid crystal display and are disposed on the first and the second substrates, respectively, the second domain defining member disposed on the second substrate and separated from the opening.

Correspondence Address:
F. CHAU & ASSOCIATES, LLC
130 WOODBURY ROAD
WOODBURY, NY 11797 (US)


(73) Assignee: **Samsung Electronics Co., Ltd.**(21) Appl. No.: **11/523,302**(22) Filed: **Sep. 19, 2006****Related U.S. Application Data**(63) Continuation of application No. 10/844,239, filed on
May 12, 2004, now Pat. No. 7,110,075.

FIG.1




FIG.2




FIG.3




FIG. 4




FIG.5





FIG.6



LIQUID CRYSTAL DISPLAY

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application is a continuation of application Ser. No. 10/844,239, filed on May 12, 2004, which claims priority to Korean Patent Application No. 2003-30195, filed on May 13, 2003, the disclosure of which in its entirety is incorporated by reference herein.

BACKGROUND OF THE INVENTION

[0002] (a) Field of the Invention

[0003] The present invention relates to a liquid crystal display.

[0004] (b) Description of the Related Art

[0005] A liquid crystal display (LCD) is one of the most widely used flat panel displays. An LCD includes two panels provided with field-generating electrodes such as pixel electrodes and a common electrode and a liquid crystal (LC) layer interposed therebetween. The LCD displays images by applying voltages to the field-generating electrodes to generate an electric field in the LC layer, which determines orientations of LC molecules in the LC layer to adjust polarization of incident light.

[0006] Among the LCDs, a vertical alignment (VA) mode LCD, which aligns LC molecules such that the long axes of the LC molecules are perpendicular to the panels in absence of electric field, is spotlighted because of its high contrast ratio and wide viewing angle.

[0007] The wide viewing angle of the VA mode LCD can be realized by cutouts in the field-generating electrodes and protrusions on the field-generating electrodes. Since the cutouts and the protrusions can determine the tilt directions of the LC molecules, the tilt directions can be distributed into several directions by using the cutouts and the protrusions such that the viewing angle is widened. In particular, a patterned VA (PVA) mode LCD employing the cutouts is preferred as a substitute of an in-plane switching (IPS) mode LCD.

[0008] The PVA mode LCD has a fast response time compared with a twisted nematic (TN) mode LCD since the motions of the LC molecules only include elastic splay or bend without twist.

[0009] In the meantime, the LCD also includes a plurality of switching elements for applying voltages to the field-generating electrodes and a plurality of signal lines such as gate lines and data lines connected to the switching elements. The signal lines make capacitive coupling with other signal lines and the common electrode, which serves as a load exerted on the signal lines to yield signal delay as well as their own resistances. In particular, the coupling between the data lines and the common electrode drives liquid crystal molecules disposed therebetween to cause light leakage near the data lines, thereby deteriorating the light leakage. In order to prevent the light leakage, a black matrix may be wide to reduce the aperture ratio.

SUMMARY OF THE INVENTION

[0010] A liquid crystal display is provided, which includes: a first substrate; a first signal line formed on the

first substrate; a second signal line formed on the first substrate and intersecting the first signal line; a pixel electrode including a plurality of partitions; a thin film transistor connected to the gate line, the data line, and the pixel electrode; a second substrate facing the second substrate; a common electrode formed on the second substrate and having an opening facing the first or the second signal line; and first and second domain defining members that define a plurality of domains in the liquid crystal display and are disposed on the first and the second substrates, respectively, the second domain defining member disposed on the second substrate and separated from the opening.

[0011] The first domain defining member may include a first cutout provided at the pixel electrode and the second domain defining member may include a second cutout provided at the common electrode.

[0012] A distance between the second cutout and the opening preferably ranges from about three to six microns.

[0013] A liquid crystal display is provided, which includes: a first substrate; a gate line formed on the first substrate; a gate insulating layer formed on the gate line; a semiconductor layer formed on the gate insulating layer; a data line formed on the gate insulating layer and intersecting the gate line; a drain electrode formed on the semiconductor layer at least in part; a pixel electrode connected to the drain electrode and having a first cutout; a second substrate facing the first substrate; and a common electrode formed on the second substrate and having a second cutout facing the pixel electrode and a first opening that faces the gate line or the data line.

[0014] The liquid crystal display may further include a storage electrode line located on the same plane as the gate line and overlapping the pixel electrode.

[0015] The common electrode may further have a second opening separated from the first opening along the gate lines or the data line.

[0016] Distances between the second cutout and the first and the second openings and between the first opening and the second opening may range from about three to six microns.

[0017] The liquid crystal display may further include a plurality of ohmic contacts disposed between the semiconductor layer and the data line and between the semiconductor layer and the drain electrode.

[0018] The ohmic contacts and the semiconductor layer may extend along the data line and the drain electrode.

[0019] The semiconductor layer may have substantially the same planar shape as the data line and the drain electrode except for a portion disposed between the data line and the drain electrode.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] The present invention will become more apparent by describing embodiments thereof in detail with reference to the accompanying drawings in which:

[0021] FIG. 1 is a layout view of a TFT array panel of an LCD according to an embodiment of the present invention;

[0022] FIG. 2 is a layout view of cutouts of a common electrode panel of an LCD according to an embodiment of the present invention;

[0023] FIG. 3 is a layout view of an LCD including the TFT array panel shown in FIG. 1 and the common electrode panel shown in FIG. 2;

[0024] FIG. 4 is a sectional view of the LCD shown in FIG. 3 taken along the line IV-IV';

[0025] FIG. 5 is a layout view of an LCD according to another embodiment of the present invention; and

[0026] FIG. 6 is a sectional view of the LCD shown in FIG. 5 taken along the line VI-VI'.

DETAILED DESCRIPTION OF EMBODIMENTS

[0027] The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which embodiments of the invention are shown. The present invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein.

[0028] In the drawings, the thickness of layers, films and regions are exaggerated for clarity. Like numerals refer to like elements throughout. It will be understood that when an element such as a layer, film, region or substrate is referred to as being "on" another element, it can be directly on the other element or intervening elements may also be present. In contrast, when an element is referred to as being "directly on" another element, there are no intervening elements present.

[0029] Now, liquid crystal displays according to embodiments of the present invention will be described with reference to the accompanying drawings.

[0030] FIG. 1 is a layout view of a TFT array panel of an LCD according to an embodiment of the present invention, FIG. 2 is a layout view of cutouts of a common electrode panel 200 of an LCD according to an embodiment of the present invention, FIG. 3 is a layout view of an LCD including the TFT array panel shown in FIG. 1 and the common electrode panel shown in FIG. 2, and FIG. 4 is a sectional view of the LCD shown in FIG. 3 taken along the line IV-IV'.

[0031] An LCD according to an embodiment of the present invention will be described in detail with reference to FIGS. 1-4.

[0032] FIG. 1 is a layout view of a TFT array panel of an LCD according to an embodiment of the present invention, FIG. 2 is a layout view of cutouts of a common electrode panel of an LCD according to an embodiment of the present invention, FIG. 3 is a layout view of an LCD including the TFT array panel shown in FIG. 1 and the common electrode panel shown in FIG. 2, and FIG. 4 is a sectional view of the LCD shown in FIG. 3 taken along the line IV-IV'.

[0033] An LCD according to an embodiment of the present invention includes a TFT array panel 100, a common electrode panel 200, and a LC layer 3 interposed between the panels 100 and 200 and containing a plurality of LC molecules aligned substantially vertical to surfaces of the panels 100 and 200.

[0034] The TFT array panel 100 is now described in detail with reference FIGS. 1, 3 and 4.

[0035] A plurality of gate lines 121 and a plurality of storage electrode lines 131 are formed on an insulating substrate 110 such as transparent glass.

[0036] The gate lines 121 extend substantially in a transverse direction and are separated from each other and transmit gate signals. Each gate line 121 includes a plurality of projections forming a plurality of gate electrodes 123 and an end portion having a large area for connection with an external driving circuit.

[0037] Each storage electrode line 131 extends substantially in the transverse direction and includes a plurality of sets of two longitudinal branches forming first and second storage electrodes 133a and 133b and a transverse branch forming a third storage electrode 133c connected between the first storage electrode 133a and the second storage electrode 133b. Each of the first storage electrodes 133a has a free end portion and a fixed end portion connected to the storage electrode line 131, and the fixed end portion has a projection. Each of the third storage electrodes 133c forms a mid-line between two adjacent gate lines 121. The storage electrode lines 131 are supplied with a predetermined voltage such as a common voltage, which is applied to a common electrode 270 on the common electrode panel 200 of the LCD. Each storage electrode line 131 may include a pair of stems extending in the transverse direction.

[0038] The gate lines 121 and the storage electrode lines 131 is preferably made of Al containing metal such as Al and Al alloy, Ag containing metal such as Ag and Ag alloy, Cu containing metal such as Cu and Cu alloy, Mo containing metal such as Mo and Mo alloy, Cr, Ti or Ta. The gate lines 121 and the storage electrode lines 131 may have a multi-layered structure including two films having different physical characteristics, a lower film (not shown) and an upper film (not shown). The upper film is preferably made of low resistivity metal including Al containing metal such as Al and Al alloy for reducing signal delay or voltage drop in the gate lines 121 and the storage electrode lines 131. On the other hand, the lower film is preferably made of material such as Cr, Mo and Mo alloy, which has good contact characteristics with other materials such as indium tin oxide (ITO) or indium zinc oxide (IZO). A good exemplary combination of the lower film material and the upper film material is Cr and Al—Nd alloy.

[0039] In addition, the lateral sides of the gate lines 121 and the storage electrode lines 131 are inclined relative to a surface of the substrate, and the inclination angle thereof ranges about 20-80 degrees.

[0040] A gate insulating layer 140 preferably made of silicon nitride (SiNx) is formed on the gate lines 121 and the storage electrode lines 131.

[0041] A plurality of semiconductor stripes 151 preferably made of hydrogenated amorphous silicon (abbreviated to "a-Si") or polysilicon are formed on the gate insulating layer 140. Each semiconductor stripe 151 extends substantially in the longitudinal direction and has a plurality of projections 154 branched out toward the gate electrodes 123.

[0042] A plurality of ohmic contact stripes and islands 161 and 165 preferably made of silicide or n+ hydrogenated a-Si

heavily doped with n type impurity such as phosphorous are formed on the semiconductor stripes **151**. Each ohmic contact stripe **161** has a plurality of projections **163**, and the projections **163** and the ohmic contact islands **165** are located in pairs on the projections **154** of the semiconductor stripes **151**.

[0043] The lateral sides of the semiconductor stripes **151** and the ohmic contacts **161** and **165** are inclined relative to a surface of the substrate, and the inclination angles thereof are preferably in a range between about 30-80 degrees.

[0044] A plurality of data lines **171**, a plurality of drain electrodes **175** separated from the data lines **171**, and a plurality of isolated metal pieces **172** are formed on the ohmic contacts **161** and **165** and the gate insulating layer **140**.

[0045] The data lines **171** for transmitting data voltages extend substantially in the longitudinal direction and intersect the gate lines **121** and the storage electrode lines **131**. Each data line **171** is disposed between the first and the second storage electrodes **133a** and **133b** in adjacent sets of the branches **133a-133c** of the storage electrode lines **131** and it includes an end portion **179** having a large area for contact with another layer or an external device. A plurality of branches of each data line **171**, which project toward the drain electrodes **175**, form a plurality of source electrodes **173**. Each drain electrode **175** includes an end portion **179** having a large area for contact with another layer and each source electrode **173** is curved to partly enclose another end portion of the drain electrode **175**. A gate electrode **123**, a source electrode **173**, and a drain electrode **175** along with a projection **154** of a semiconductor stripe **151** form a TFT having a channel formed in the projection **154** disposed between the source electrode **173** and the drain electrode **175**.

[0046] The metal pieces **172** are disposed on the gate lines **121** near the end portions of the storage electrodes **133a**.

[0047] The data lines **171**, the drain electrodes **175**, and the metal pieces **172** are preferably made of refractory metal such as Cr, Mo containing metal, Ti and Ti, or Al containing metal and they may also have a multilayered structure including a lower film (not shown) preferably made of Mo, Mo alloy or Cr and an upper film (not shown) located thereon and preferably made of Al containing metal.

[0048] Like the gate lines **121** and the storage electrode lines **131**, the data lines **171** and the drain electrodes **175** have tapered lateral sides, and the inclination angles thereof range about 30-80 degrees.

[0049] The ohmic contacts **161** and **165** are interposed only between the underlying semiconductor stripes **151** and the overlying data lines **171** and the overlying drain electrodes **175** thereon and reduce the contact resistance therebetween. The semiconductor stripes **151** include a plurality of exposed portions, which are not covered with the data lines **171** and the drain electrodes **175**, such as portions located between the source electrodes **173** and the drain electrodes **175**.

[0050] A passivation layer **180** is formed on the data lines **171**, the drain electrodes **175**, and the exposed portions of the semiconductor stripes **151**. The passivation layer **180** is preferably made of photosensitive organic material having a

good flatness characteristic, low dielectric insulating material having dielectric constant lower than 4.0 such as a-Si:C:O and a-Si:O:F formed by plasma enhanced chemical vapor deposition (PECVD), or inorganic material such as silicon nitride.

[0051] The passivation layer **180** has a plurality of contact holes **181** and **183** exposing the end portions of the drain electrodes **175** and the end portions **179** of the data lines **171**, respectively. The passivation layer **180** and the gate insulating layer **140** have a plurality of contact holes **182**, **184** and **185** exposing the end portions **125** of the gate lines **121**, the projections of the free end portions of the first storage electrodes **133a**, and portions of the storage electrode lines **131** near the fixed end portions of the first storage electrodes **133a**, respectively. The contact holes **181-185** have a shape of polygon or a circle, and sidewalls of the contact holes **181-185** are tapered. Each of the contact holes **182** and **183** exposing the end portions **125** and **179** preferably has an area ranging from about 0.5 mm $\times$ 15 μ m to about 2 mm $\times$ 60 μ m.

[0052] A plurality of pixel electrodes **190**, a plurality of contact assistants **95** and **97**, and a plurality of storage connections **91**, which are preferably made of ITO or IZO, are formed on the passivation layer **180**.

[0053] The pixel electrodes **190** are physically and electrically connected to the drain electrodes **175** through the contact holes **181** such that the pixel electrodes **190** receive the data voltages from the drain electrodes **175**.

[0054] The pixel electrodes **190** supplied with the data voltages generate electric fields in cooperation with the common electrode **270**, which reorient liquid crystal molecules in the liquid crystal layer **3**.

[0055] A pixel electrode **190** and the common electrode **270** form a liquid crystal capacitor, which stores applied voltages after turn-off of the TFT. An additional capacitor called a "storage capacitor," which is connected in parallel to the liquid crystal capacitor, is provided for enhancing the voltage storing capacity. The storage capacitors are implemented by overlapping the pixel electrodes **190** with the storage electrode lines **131** including the storage electrodes **133a-133c**.

[0056] Each pixel electrode **190** is chamfered at its four corners and the chamfered edges of the pixel electrode **190** make an angle of about 45 degrees with the gate lines **121**.

[0057] Each pixel electrode **190** has a lower cutout **191**, a center cutout **192**, and an upper cutout **193**, which partition the pixel electrode **190** into a plurality of partitions. The cutouts **191**, **192** and **193** substantially have an inversion symmetry with respect to a third storage electrode **133c**.

[0058] The lower and the upper cutouts **191** and **193** obliquely extend approximately from a right edge of the pixel electrode **190** approximately to a left edge of the pixel electrode **190**, and they are disposed at lower and upper halves of the pixel electrode **190**, respectively, which can be divided by the third storage electrode **133c**. The lower and the upper cutouts **191** and **193** make an angle of about 45 degrees to the gate lines **121**, and they extend perpendicular to each other. The center cutout **192** extends along the third storage electrode **133c** and has an inlet from the right edge

of the pixel electrode **190**, which has a pair of inclined edges substantially parallel to the lower cutout **191** and the upper cutout **193**, respectively.

[0059] Accordingly, the lower half of the pixel electrode **190** is also partitioned into two lower partitions by the lower cutout **191** and the upper half of the pixel electrode **190** is partitioned into two upper partitions by the upper cutout **193**. The number of partitions or the number of the cutouts is varied depending on the design factors such as the size of pixels, the ratio of the transverse edges and the longitudinal edges of the pixel electrodes, the type and characteristics of the liquid crystal layer **3**, and so on.

[0060] The contact assistants **95** and **97** are connected to the end portions **125** of the gate lines **121** and the end portions **179** of the data lines **171** through the contact holes **182** and **183**, respectively. The contact assistants **95** and **97** are not requisites but preferred to protect the end portions **125** and **179** and to complement the adhesiveness of the end portions **125** and **179** and external devices.

[0061] The storage connections **91** cross over the gate lines **121** and they are connected to the exposed projection of the fixed end portions of the first storage electrodes **133a** and the exposed portions of the storage electrode lines **131** respectively through the contact holes **184** and **185** opposite each other with respect to the gate lines **121**. The storage connections **91** overlaps the metal pieces **172** and they may be electrically connected to the metal pieces **172**. The storage electrode lines **131** including the storage electrodes **133a-133c** along with the storage connections **91** and the metal pieces **172** are used for repairing defects in the gate lines **121**, the data lines **171**, or the TFTs. The electrical connection between the gate lines **121** and the storage electrode lines **131** for repairing the gate lines **121** is obtained by illuminating the cross points of the gate lines **121** and the storage connections **91** by a laser beam to electrically connect the gate lines **121** to the storage connections **91**. In this case, the metal pieces **172** enhance the electrical connection between the gate lines **121** and the storage connections **91**.

[0062] The description of the common electrode panel **200** follows with reference to FIGS. 2-4.

[0063] A light blocking member **220** called a black matrix for preventing light leakage is formed on an insulating substrate **210** such as transparent glass. The light blocking member **220** may include a plurality of openings that face the partitions **191a** and **191b** of the pixel electrodes **191** and may have substantially the same shape as the partitions **191a** and **191b**. Otherwise, the light blocking member **220** may include oblique linear portions corresponding to the data lines **171** and other portions corresponding to the TFTs.

[0064] A plurality of red, green and blue color filters **230** are formed on the substrate **210** and they are disposed substantially in the areas enclosed by the light blocking member **220**. The color filters **230** may extend substantially along the longitudinal direction along the pixel electrodes **191**. The color filters **230** may represent one of the primary colors such as red, green and blue colors.

[0065] An overcoat **250** is formed on the color filters **230**.

[0066] A common electrode **270** preferably made of transparent conductive material such as ITO and IZO is formed on the overcoat **250**.

[0067] The common electrode **270** has a plurality of sets of cutouts **271-273** and a plurality of openings **279**.

[0068] A set of cutouts **271-273** face a pixel electrode **190** and include a lower cutout **271**, a center cutout **272**, and an upper cutout **273**. Each of the cutouts **271-273** is disposed between adjacent cutouts **191-193** of the pixel electrode **190** or between a cutout **191** or **193** and a chamfered edge of the pixel electrode **190**. In addition, each of the cutouts **271-273** has at least an oblique portion extending parallel to the lower cutout **191** or the upper cutout **193** of the pixel electrode **190**, and the distances between adjacent two of the cutouts **271-273** and **191-193**, the oblique portions thereof, the oblique edges thereof, and the chamfered edges of the pixel electrode **190**, which are parallel to each other, are substantially the same. The cutouts **271-293** substantially have an inversion symmetry with respect to a third storage electrode **133c**.

[0069] Each of the lower and upper cutouts **271** and **273** includes an oblique portion extending approximately from a left edge of the pixel electrode **190** approximately to a lower or upper edge of the pixel electrode **190**, and transverse and longitudinal portions extending from respective ends of the oblique portion along edges of the pixel electrode **190**, overlapping the edges of the pixel electrode **190**, and making obtuse angles with the oblique portion.

[0070] The center cutout **272** includes a central transverse portion extending approximately from the left edge along the third storage electrode **133c**, a pair of oblique portions extending from an end of the central transverse portion approximately to a right edge of the pixel electrode and making obtuse angles with the central transverse portion, and a pair of terminal longitudinal portions extending from the ends of the respective oblique portions along the right edge of the pixel electrode **190**, overlapping the right edge of the pixel electrode **190**, and making obtuse angles with the respective oblique portions.

[0071] The number of the cutouts **271-273** may be varied depending on the design factors, and the light blocking member **220** may also overlap the cutouts **271-273** to block the light leakage through the cutouts **271-273**.

[0072] Each opening **279** extends along a data line **171** to overlap the data line **171** and it is disposed between adjacent sets of the cutouts **271-278**. Some openings **279** meet the gate lines **121** while the other openings **279** do not meet the gate lines **121**. The number of the openings **279** that are disposed between adjacent two gate lines **121** is one but it may be at least two.

[0073] The openings **279** reduce the load exerted on the data lines **171** and thus the delay of the data voltages flowing in the data lines **171**, which is generated by the parasitic capacitance formed by the overlap of the common electrode **270** and the data lines **171**. The reduction of the load on the data lines **171** enlarges the freedom of the selection of the material for the data lines **171** and the resolution of the LCD.

[0074] The openings **279** also decrease the variation of the capacitance of the liquid crystal capacitor due to the data voltages carried by the data lines **171**, thereby decreasing vertical crosstalk that are firstly generated under the poor charging capacity of the liquid crystal capacitor. Accordingly, the charging capacity is improved.

[0075] In addition, the openings 279 reduce the lateral light leakage due to the lateral crosstalk of the data signals. The reduction of the lateral light leakage enables to decrease the width of the light blocking member 220, thereby increasing aperture ratio.

[0076] Referring to FIG. 2, the distance between the openings 279 denoted by (a) and the distance between the openings 279 and the cutouts 271-273 denoted by (b) are preferably larger than the resolution of an exposor used in photolithography process, and more preferably, they are equal to about 3-6 microns. The portions of the common electrode 270 between the openings 279 and between the openings 279 and the cutouts 271-273 form various signal paths for the common voltage.

[0077] Homeotropic alignment layers 21 and 22 are coated on inner surfaces of the panels 100 and 200, and polarizers 12 and 22 are provided on outer surfaces of the panels 100 and 200 such that their polarization axes may be crossed and one of the transmissive axes may be parallel to the gate lines 121. One of the polarizers may be omitted when the LCD is a reflective LCD.

[0078] The LCD may further include at least one retardation film for compensating the retardation of the LC layer 3.

[0079] The LC molecules in the LC layer 3 are aligned such that their long axes are vertical to the surfaces of the panels 100 and 200. The liquid crystal layer 3 has negative dielectric anisotropy.

[0080] The cutouts 191-193 and 271-273 controls the tilt directions of the LC molecules in the LC layer 3. That is, the liquid crystal molecules in each region called domain defined by adjacent cutouts 191-193 and 271-273 or by the cutout 272 or 273 and the chamfered edge of the pixel electrode 190 are tilted in a direction perpendicular to the extension direction of the cutouts 191-193 and 271-273. It is apparent that the domains have two long edges extending substantially parallel to each other and making an angle of about 45 degrees with the gate line 121.

[0081] At least one of the cutouts 191-193 and 271-273 can be substituted with protrusions or depressions.

[0082] The shapes and the arrangements of the cutouts 191-193 and 271-273 and the openings 279 may be modified. For example, the openings 279 may be formed along the gate lines 121 instead of the data lines 171.

[0083] A method of manufacturing the TFT array panel shown in FIGS. 1-4 according to an embodiment of the present invention will be now described in detail.

[0084] A conductive film preferably made of Cr or Mo alloy or Al are deposited and photo-etched to form a plurality of gate lines 121 including a plurality of gate electrodes 123 and end portions 125 and a plurality of storage electrode lines 131 including a plurality of storage electrodes 133a-133c.

[0085] After sequential deposition of a gate insulating layer 140, an intrinsic a-Si layer, and an extrinsic a-Si layer, the extrinsic a-Si layer and the intrinsic a-Si layer are photo-etched to form a plurality of extrinsic semiconductor stripes and a plurality of intrinsic semiconductor stripes 151 including a plurality of projections 154 on the gate insulating layer 140.

[0086] Subsequently, a conductive film preferably made of Cr or Mo alloy or Al are deposited and photo-etched to form a plurality of data lines 171 including a plurality of source electrodes 173 and end portions 179, a plurality of drain electrodes 175, and a plurality of metal pieces 172.

[0087] Thereafter, portions of the extrinsic semiconductor stripes, which are not covered with the data lines 171 and the drain electrodes 175, are removed to complete a plurality of ohmic contact stripes 161 including a plurality of projections 163 and a plurality of ohmic contact islands 165 and to expose portions of the intrinsic semiconductor stripes 151. Oxygen plasma treatment preferably follows in order to stabilize the exposed surfaces of the semiconductor stripes 151.

[0088] A passivation layer 180 is formed by chemical vapor deposition of a-Si:C:O or a-Si:O:F, by deposition of an inorganic insulator such as silicon nitride, or by coating of an organic insulator such as acrylic material. An a-Si:C:O film may be deposited by using a gas mixture containing source gases of $\text{SiH}(\text{CH}_3)_3$, $\text{SiO}_2(\text{CH}_3)_4$, $(\text{SiH})_4\text{O}_4(\text{CH})_4$ or $\text{Si}(\text{C}_2\text{H}_5\text{O})_4$, oxidants of N_2O or O_2 , and Ar or He. An a-Si:O:F film may be deposited by using a gas mixture of SiH_4 , SiF_4 , O_2 , etc., and CF_4 gas may be added as an additional source of fluorine.

[0089] The passivation layer 180 and the gate insulating layer 140 are photo-etched to form a plurality of contact holes 181-185 exposing the drain electrodes 175, the end portions 125 of the gate lines 121, the end portions 179 of the data lines 171, the storage electrodes 133a, and the storage electrode lines 131.

[0090] Finally, a plurality of pixel electrodes 190, a plurality of contact assistants 95 and 97, and a plurality of storage connections 91 are formed on the passivation layer 180 and on the exposed portions of the drain electrodes 175, the end portions 125 and 179, the storage electrodes 133a, and the storage electrode lines 131 by sputtering and photo-etching an IZO or ITO layer. The TFT array panel may be preheated with nitrogen gas before the IZO or ITO layer is deposited in order for preventing the formation of metal oxides on exposed portions of metal layers through the contact holes 181-185.

[0091] An LCD according to another embodiment of the present invention will be described in detail with reference to FIGS. 5 and 6.

[0092] FIG. 5 is a layout view of an LCD according to another embodiment of the present invention, and FIG. 6 is a sectional view of the LCD shown in FIG. 5 taken along the line VI-VI'.

[0093] Referring to FIGS. 5 and 6, an LCD according to this embodiment also includes a TFT array panel 100, a common electrode panel 200, and a LC layer 3 interposed therebetween.

[0094] Layered structures of the panels according to this embodiment are almost the same as those shown in FIGS. 1-4.

[0095] Regarding the TFT array panel, a plurality of gate lines 121 including a plurality of gate electrodes 123 and a plurality of storage electrode lines 131 including a plurality of storage electrodes 133a-133b are formed on a substrate 110, and a gate insulating layer 140, a plurality of semicon-

ductor stripes **151** including a plurality of projections **154**, and a plurality of ohmic contact stripes **161** including a plurality of projections **163** and a plurality of ohmic contact islands **165** are sequentially formed thereon. A plurality of data lines **171** including a plurality of source electrodes **173** and a plurality of drain electrodes **175** are formed on the ohmic contacts **161** and **165**, and a passivation layer **180** is formed thereon. A plurality of contact holes **181**, **184** and **185** are provided at the passivation layer **180** and the gate insulating layer **140**, and a plurality of pixel electrodes **190** and a plurality of storage connections **91** are formed on the passivation layer **180**. An alignment layer **11** is coated on an inner surface of the TFT array panel **100**, and a polarizer **12** is disposed on an outer surface of the TFT array panel **100**.

[0096] Regarding the common electrode panel, a light blocking member **220**, a plurality of color filters **230**, an overcoat **250**, and a common electrode **270** are formed on an insulating substrate **210**. An alignment layer **21** is coated on an inner surface of the common electrode panel **100**, and a polarizer **22** is disposed on an outer surface of the common electrode panel **100**.

[0097] Different from the LCD shown in FIGS. 1-4, the semiconductor stripes **151** have almost the same planar shapes as the data lines **171** and the drain electrodes **175** as well as the underlying ohmic contacts **161** and **165**. However, the projections **154** of the semiconductor stripes **151** include some exposed portions, which are not covered with the data lines **171** and the drain electrodes **175**, such as portions located between the source electrodes **173** and the drain electrodes **175**.

[0098] In addition, there is no storage electrode connecting the storage electrodes **133a** and **133b**.

[0099] Each pixel electrode **190** is chamfered at its left corners but not chamfered at its right corners and the chamfered edges of the pixel electrode **190** make an angle of about 45 degrees with the gate lines **121**.

[0100] Each pixel electrode **190** has a plurality of lower cutouts **191-193**, upper cutouts **196-198**, and center cutouts **194** and **195**, which partition the pixel electrode **190** into a plurality of partitions. The lower and the upper cutouts **191-193** and **196-198** are disposed at lower and upper halves of the pixel electrode **190**, respectively, and the center cutouts **194** and **195** is located between the lower cutouts **191-193** and the upper cutouts **196-198**. The cutouts **191-198** substantially have an inversion symmetry with respect to a transverse center line of the pixel electrode **190** that divides the lower and the upper halves of the pixel electrode **190**.

[0101] The lower and the upper cutouts **191-193** and **196-198** make an angle of about 45 degrees to the gate lines **121**, and the lower cutouts **191-193**, which extend substantially parallel to each other and to the chamfered lower edge of the pixel electrode **190**, extend substantially perpendicular to the upper cutouts **196-198**, which extend substantially parallel to each other and to the chamfered upper edge of the pixel electrode **190**.

[0102] The cutouts **191** and **198** extend approximately from a left longitudinal edge of the pixel electrode **190** approximately to transverse edges of the pixel electrode **190**. The cutouts **192** and **197** extend approximately from the left edge of the pixel electrode **190** approximately to the

unchamfered right corners of the pixel electrode **190**. The cutouts **193** and **196** extend approximately from left corners of the upper and lower halves of the pixel electrode **190** approximately to a right longitudinal edge of the pixel electrode **190**.

[0103] The center cutout **194** includes a transverse portion extending along the transverse center line of the pixel electrode **190** and a pair of oblique portions extending from the transverse portion to the right edge of the pixel electrode **190** and extending substantially parallel to the lower cutouts **191-193** and the upper cutouts **196-198**, respectively. The center cutout **195** extends along the transverse center line of the pixel electrode **190** and has an inlet from the right edge of the pixel electrode **190**, which has a pair of inclined edges substantially parallel to the lower cutouts **191-193** and the upper cutouts **196-198**, respectively.

[0104] Accordingly, the lower half of the pixel electrode **190** is partitioned into five lower partitions by the lower cutouts **191-193** and the center cutout **194** and the upper half of the pixel electrode **190** is also partitioned into five upper partitions by the upper cutouts **196-198** and the center cutout **194**.

[0105] The common electrode **270** has a plurality of sets of cutouts **271-278** and a plurality of openings **279**.

[0106] A set of cutouts **271-278** face a pixel electrode **190** and include a plurality of lower and upper cutouts **271-273** and **276-278** and center cutouts **274** and **275**. Each of the cutouts **271-278** is disposed between adjacent cutouts **191-198** of the pixel electrode **190** or between a cutout **191** or **198** and a chamfered edge of the pixel electrode **190**. In addition, each of the cutouts **271-278** has at least an oblique portion extending parallel to the lower cutouts **191-193** or the upper cutouts **196-198** of the pixel electrode **190**, and the distances between adjacent two of the cutouts **271-278** and **191-198**, the oblique portions thereof, the oblique edges thereof, and the chamfered edges of the pixel electrode **190**, which are parallel to each other, are substantially the same. The cutouts **271-278** substantially have an inversion symmetry with respect to a transverse center line of the pixel electrode **190**.

[0107] Each of the cutouts **271**, **272**, **278** and **277** has an oblique portion extending approximately from a left edge of the pixel electrode **190** approximately to a lower or upper edge of the pixel electrode **190** and transverse and longitudinal portions extending from respective ends of the oblique portion along edges of the pixel electrode **190**, overlapping the edges of the pixel electrode **190**, and making obtuse angles with the oblique portion. Each of the cutouts **273** and **276** has an oblique portion extending approximately from the left edge of the pixel electrode **190** approximately to a right edge of the pixel electrode **190** and a pair of longitudinal portions extending from respective ends of the oblique portion along the left and the right edges of the pixel electrode **190**, overlapping the left and the right edges of the pixel electrode **190**, and making obtuse angles with the oblique portion. Each of the cutouts **274** and **275** has a central transverse portion extending along the transverse center line of the pixel electrode **190**, a pair of oblique portions extending from the transverse portion approximately to the right edge of the pixel electrode **190** and making obtuse angles with the central transverse portion, and a pair of terminal transverse portions extending from the

respective oblique portions along the right edge of the pixel electrode 190, overlapping the right edge of the pixel electrode 190, and making an obtuse angle with the respective oblique portions.

[0108] Each opening 279 extends along a data line 171 to overlap the data line 171 and it is disposed between adjacent sets of the cutouts 271-278. Some openings 279 meet the gate lines 121 while the other openings 279 do not meet the gate lines 121. The number of the openings 279 that are disposed between adjacent two gate lines 121 is three.

[0109] The contact holes 182 and 183 and the contact assistants 95 and 97 shown in FIGS. 14 can be omitted when driving circuits for applying signals to the gate lines 121 or the data lines 171 are formed on the TFT panel 100 along with the TFTs.

[0110] A manufacturing method of the TFT array panel according to an embodiment simultaneously forms the data lines 171, the drain electrodes 175, the semiconductors 151, and the ohmic contacts 161 and 165 using one photolithography process.

[0111] A photoresist pattern for the photolithography process has position-dependent thickness, and in particular, it has first and second portions with decreased thickness. The first portions are located on wire areas that will be occupied by the data lines 171 and the drain electrodes 175 and the second portions are located on channel areas of TFTs.

[0112] The position-dependent thickness of the photoresist is obtained by several techniques, for example, by providing translucent areas on the exposure mask 300 as well as transparent areas and light blocking opaque areas. The translucent areas may have a slit pattern, a lattice pattern, a thin film(s) with intermediate transmittance or intermediate thickness. When using a slit pattern, it is preferable that the width of the slits or the distance between the slits is smaller than the resolution of a light exposer used for the photolithography. Another example is to use reflowable photoresist. In detail, once a photoresist pattern made of a reflowable material is formed by using a normal exposure mask only with transparent areas and opaque areas, it is subject to reflow process to flow onto areas without the photoresist, thereby forming thin portions.

[0113] As a result, the manufacturing process is simplified by omitting a photolithography step.

[0114] Many of the above-described features of the LCD shown in FIGS. 1-4 may be appropriate to the LCD shown in FIGS. 5 and 6.

[0115] As described above, the openings 279 reduce the delay of the data voltages flowing in the data lines 171, which is generated by the parasitic capacitance formed by the overlap of the common electrode 270 and the data lines 171. The openings 270 also decrease the variation of the capacitance of the liquid crystal capacitor due to the data voltages carried by the data lines 171 and lateral light leakage due to the crosstalk of the data signals. The reduction of the lateral light leakage enables to decrease the width of the light blocking member 220, thereby increasing the aperture ratio.

[0116] While the present invention has been described in detail with reference to the preferred embodiments, those skilled in the art will appreciate that various modifications

and substitutions can be made thereto without departing from the spirit and scope of the present invention as set forth in the appended claims.

[0117] For example, the arrangements of the cutouts and the openings of the pixel electrodes and the common electrode may be modified and protrusions are provided instead of the cutouts.

What is claimed is:

1. A liquid crystal display comprising:

a first substrate;

a first signal line formed on the first substrate;

a second signal line formed on the first substrate and intersecting the first signal line;

a pixel electrode including a plurality of partitions;

a thin film transistor connected to the gate line, the data line, and the pixel electrode;

a second substrate facing the first substrate;

a common electrode formed on the second substrate and having an opening facing the first or the second signal line; and

first and second domain defining members that define a plurality of domains in the liquid crystal display and are disposed on the first and the second substrates, respectively, the second domain defining member disposed on the second substrate and separated from the opening.

2. The liquid crystal display of claim 1, wherein the first domain defining member includes a first cutout provided at the pixel electrode and the second domain defining member includes a second cutout provided at the common electrode.

3. The liquid crystal display of claim 2, wherein a distance between the second cutout and the opening ranges from about three to six microns.

4. A liquid crystal display comprising:

a first substrate;

a gate line formed on the first substrate;

a gate insulating layer formed on the gate line;

a semiconductor layer formed on the gate insulating layer;

a data line formed on the gate insulating layer and intersecting the gate line;

a drain electrode formed on the semiconductor layer at least in part;

a pixel electrode connected to the drain electrode and having a first cutout;

a second substrate facing the first substrate; and

a common electrode formed on the second substrate and having a second cutout facing the pixel electrode and a first opening that faces the gate line or the data line.

5. The liquid crystal display of claim 4, further comprising a storage electrode line located on the same plane as the gate line and overlapping the pixel electrode.

6. The liquid crystal display of claim 4, wherein the common electrode further has a second opening separated from the first opening along the gate lines or the data line.

7. The liquid crystal display of claim 6, wherein distances between the second cutout and the first and the second openings and between the first opening and the second opening range from about three to six microns.

8. The liquid crystal display of claim 4, further comprising a plurality of ohmic contacts disposed between the semiconductor layer and the data line and between the semiconductor layer and the drain electrode.

9. The liquid crystal display of claim 8, wherein the ohmic contacts and the semiconductor layer extend along the data line and the drain electrode.

10. The liquid crystal display of claim 9, wherein the semiconductor layer has substantially the same planar shape as the data line and the drain electrode except for a portion disposed between the data line and the drain electrode.

* * * * *

专利名称(译)	液晶显示器		
公开(公告)号	US20070008475A1	公开(公告)日	2007-01-11
申请号	US11/523302	申请日	2006-09-19
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	TAK YOUNG MI SHIN AE KIM DONG GYU BAEK SEUNG SOO		
发明人	TAK, YOUNG-MI SHIN, AE KIM, DONG-GYU BAEK, SEUNG-SOO		
IPC分类号	G02F1/1343 G02F1/1337 G02F1/1333 G02F1/1368 G02F1/139		
CPC分类号	G02F1/133707 G02F1/1393 G02F1/134336		
优先权	1020030030195 2003-05-13 KR		
其他公开文献	US7379142		
外部链接	Espacenet USPTO		

摘要(译)

提供一种液晶显示器，包括：第一基板；形成在第一基板上的第一信号线；第二信号线，形成在第一基板上并与第一信号线交叉；像素电极，包括多个分区；薄膜晶体管，连接到栅极线，数据线和像素电极；面向第二基板的第二基板；公共电极形成在第二基板上并具有面向第一或第二信号线的开口；第一和第二畴限定构件，其在液晶显示器中限定多个畴并分别设置在第一和第二基板上，第二畴限定构件设置在第二基板上并与开口分离。

