



US007006186B2

(12) **United States Patent**
Chung

(10) **Patent No.:** **US 7,006,186 B2**
(45) **Date of Patent:** **Feb. 28, 2006**

(54) **IN-PLANE SWITCHING MODE LIQUID CRYSTAL DISPLAY DEVICE AND METHOD OF FABRICATING THE SAME**

5,838,037 A 11/1998 Masutani et al.
5,946,060 A 8/1999 Nishiki et al.
5,990,987 A 11/1999 Tanaka
6,028,653 A 2/2000 Nishida
6,097,454 A 8/2000 Zhang et al.
6,266,166 B1 7/2001 Katsumata et al.

(75) Inventor: **Jin-Youl Chung**, Seoul (KR)

(73) Assignee: **LG.Philips LCD Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 117 days.

FOREIGN PATENT DOCUMENTS

JP 9-5764 1/1997
JP 9-73101 3/1997

(21) Appl. No.: **10/670,424**

(22) Filed: **Sep. 26, 2003**

(65) **Prior Publication Data**

US 2004/0125303 A1 Jul. 1, 2004

(30) **Foreign Application Priority Data**

Dec. 31, 2002 (KR) 10-2002-0088443

(51) **Int. Cl.**

G02F 1/1368 (2006.01)
G02F 1/139 (2006.01)

(52) **U.S. Cl.** **349/141**; 349/43; 349/111;
349/187

(58) **Field of Classification Search** 349/43,
349/110, 111, 141, 187, 44, 122, 138; 257/59,
257/72; 345/92; 438/30

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,345,324 A * 9/1994 Koseki et al. 349/44
5,598,285 A 1/1997 Kondo et al.

OTHER PUBLICATIONS

M. Ohta et al., "Development of Super-TFT-LCDs with In-Plane Switching Display Mode", Asia Display '95, pp. 707-710.

(Continued)

Primary Examiner—Dung T. Nguyen


Assistant Examiner—Tai Duong

(74) *Attorney, Agent, or Firm*—McKenna Long & Aldridge LLP

(57) **ABSTRACT**

An in-plane switching mode liquid crystal display device includes first and second substrates, a gate line and a data line arranged along first and second directions on the first substrate to define a pixel area, a passivation layer on the first substrate except within the pixel area, a light blocking system on the first substrate and on a stepped portion of the passivation layer adjacent to the data line, a plurality of common electrodes disposed within the pixel area, at least one of the common electrodes overlap a portion of the data line, and a plurality of pixel electrodes disposed within the pixel area, wherein the pixel electrodes and the common electrodes form a lateral electric field.

22 Claims, 9 Drawing Sheets



OTHER PUBLICATIONS

M. Oh-e, et al., "Principles and Characteristics of Electro-Optical Behaviour with In-Plane Switching Mode", Asia Display '95, pp. 577-580.

S. Matsumoto et al., "Display Characteristics of In-Plane-Switching (IPS) LCDs and a Wide-Viewing-Angle", Euro Display '96, pp. 445-448.

H. Wakemoto et al., "An Advanced In-Plane-Switching Mode FTF-LCD", Sid 97 Digest, pp. 929-932.

S.H. Lee et al., "High-Transmittance, Wide-Viewing-Angle Nematic Liquid Crystal Display Controlled by Fringe-Field Switching", Asia Display 98, pp. 371-374.

* cited by examiner

FIG. 1A
RELATED ART




FIG. 1B
RELATED ART




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 6A




FIG. 6B




FIG. 6C





FIG. 6D



IN-PLANE SWITCHING MODE LIQUID CRYSTAL DISPLAY DEVICE AND METHOD OF FABRICATING THE SAME

The present invention claims the benefit of Korean Patent Application No. 88443/2002 filed in Korea on Dec. 31, 2002, which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display device, and particularly, to an in-plane switching mode liquid crystal display device and method of fabricating the same.

2. Description of the Related Art

In general, twisted nematic mode liquid crystal display (LCD) devices commonly used as flat panel display devices have advantages of high image quality and lower power consumption. However, twisted nematic mode LCD devices have disadvantages, such as narrow viewing angles, due to refractive anisotropy of liquid crystal molecules being oriented in parallel with a substrate along a nearly vertical direction to the substrate when the voltage is supplied to the liquid crystal display panel. Accordingly, in-plane switching mode LCD devices have been developed that can solve the viewing angle problems by orienting the liquid crystal molecules to be parallel with the substrate.

FIG. 1A is a plan view of a unit pixel of an in-plane switching mode LCD according to the related art, and FIG. 1B is a cross sectional view along I-I' of FIG. 1A according to the related art. In FIG. 1A, a gate line 1 and a data line 3 are arranged along transverse and longitudinal directions, respectively, on a transparent first substrate 10 (in FIG. 1B) to define a pixel area. In actuality, there are an n-number of nxm pixels by crossings of an n-number of gate lines 1 and an m-number of data lines 3 formed on the transparent first substrate 10. In addition, a thin film transistor 9 includes a gate electrode 1a, a semiconductor layer 5, and source and drain electrodes 2a and 2b disposed within the pixel area, wherein the gate electrode 1a is connected to the gate line 1, the source electrode 2a is connected to the data line 3, and the drain electrode 2b is connected to a pixel electrode 7. Moreover, a gate insulating layer 8 is formed on an entire surface of the transparent first substrate 10.

A common line 4 is arranged to be parallel with the gate line 1 within the pixel area, and at least a pair of common and pixel electrodes 6 and 7 for switching the liquid crystal molecules are arranged to be parallel with the data line 3. The common electrode 6 is simultaneously formed with the gate line 1 and is connected to the common line 4, whereas the pixel electrode 7 is simultaneously formed with the source and drain electrodes 2a and 2b and is connected to the drain electrode 2b of the thin film transistor 9.

In FIG. 1B, a passivation layer 11 and a first alignment layer 12a are formed along an entire surface of the transparent first substrate 10 including the source and drain electrodes 2a and 2b. It is desirable that the common electrode 6 is formed along an outer portion of the pixel area in order to shield any lateral electric fields generated between the pixel electrode 7 and the data line 3 formed along the outer portion of the pixel area. In addition, a pixel electrode line 14 is formed to overlap the common line 4 and is connected to the pixel electrode 7, thereby forming a storage capacitor with the gate insulating layer 8 therebetween.

A black matrix 21, which prevents light from leaking to the thin film transistor 9, the gate line 1, the data line 3, and a color filter 23 are formed on a second substrate 20, and a second alignment layer 12b is formed thereon. In addition, a liquid crystal layer 13 is formed between the first and second substrates 10 and 20. However, the in-plane switching mode LCD device of FIGS. 1A and 1B has a low aperture ratio since the common electrode 6 and the pixel electrode 7 are formed of opaque metals within the pixel area.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to an in-plane switching mode liquid crystal display device and method of fabricating an in-plane switching mode liquid crystal display device that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

An object of the present invention is to provide an in-plane switching mode liquid crystal display device having an improved aperture ratio.

Another object of the present invention is to provide a method of fabricating an in-plane switching mode liquid crystal display device having an improved aperture ratio.

Another object of the present invention is to provide an in-plane switching mode liquid crystal display device having an improved brightness.

Another object of the present invention is to provide a method of fabricating an in-plane switching mode liquid crystal display device having an improved brightness.

Another object of the present invention is to provide an in-plane switching mode liquid crystal display device having an ability to prevent light leakage.

Another object of the present invention is to provide a method of fabricating an in-plane switching mode liquid crystal display device having an ability to prevent light leakage.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, an in-plane switching mode liquid crystal display device includes first and second substrates, a gate line and a data line arranged along first and second directions on the first substrate to define a pixel area, a passivation layer on the first substrate except within the pixel area, a light blocking system on the first substrate and on a stepped portion of the passivation layer adjacent to the data line, a plurality of common electrodes disposed within the pixel area, at least one of the common electrodes overlap a portion of the data line, and a plurality of pixel electrodes disposed within the pixel area, wherein the pixel electrodes and the common electrodes form a lateral electric field.

In another aspect, a method of fabricating an in-plane switching mode liquid crystal display device includes forming a gate line and a light blocking line on a first substrate, forming a data line on the first substrate to define a pixel area, forming a plurality of pixel electrodes within the pixel area to be parallel with the data line, forming an organic layer along an entire surface of the first substrate, exposing the pixel electrodes by removing a portion of the organic

layer, and forming a plurality of common electrodes on the first substrate, wherein at least one of the common electrodes along an outer portion of the pixel area overlap the data line.

In another aspect, a method of fabricating an in-plane switching mode liquid crystal display device includes forming a gate line and a data line along first and second directions on a first substrate to define a pixel area, forming a passivation layer on the first substrate except within the pixel area, forming a light blocking system on the first substrate and on a stepped portion of the passivation layer adjacent to the data line, forming a plurality of common electrodes disposed within the pixel area, at least one of the common electrodes overlap a portion of the data line, and forming a plurality of pixel electrodes disposed within the pixel area, wherein the pixel electrodes and the common electrodes form a lateral electric field.

In another aspect, an in-plane switching mode liquid crystal display device includes a gate line and a light blocking line on a first substrate, a data line on the first substrate to define a pixel area, a plurality of pixel electrodes within the pixel area to be parallel with the data line, an organic layer along an entire surface of the first substrate except for the pixel electrodes, and a plurality of common electrodes on the first substrate, wherein at least one of the common electrodes is provided along an outer portion of the pixel area to overlap the data line.

The foregoing and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention. In the drawings:

FIG. 1A is a plan view of a unit pixel of an in-plane switching mode LCD according to the related art;

FIG. 1B is a cross sectional view along I-I' of FIG. 1A according to the related art;

FIG. 2A is a plan view of an exemplary unit pixel of an in-plane switching mode LCD device according to the present invention;

FIG. 2B is a cross sectional view along II-II' of FIG. 2A according to the present invention;

FIG. 3A is a plan view of another exemplary unit pixel of an in-plane switching mode LCD device according to the present invention;

FIG. 3B is a cross sectional view along III-III' of FIG. 3A according to the present invention;

FIG. 4A is a plan view of another exemplary unit pixel of an in-plane switching mode LCD device according to the present invention;

FIG. 4B is a cross sectional view along IV-IV' of FIG. 4A according to the present invention;

FIGS. 5A to 5D are plan views of an exemplary method of fabricating an in-plane switching mode LCD device according to the present invention;

FIGS. 6A to 6D are cross sectional views along V-V', VI-VI', VII-VII', and VIII-VIII' of FIGS. 5A to 5D, respectively, showing the exemplary method of fabricating an in-plane switching mode LCD device according to the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

Reference will now be made in detail to the illustrated embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

FIG. 2A is a plan view of an exemplary unit pixel of an in-plane switching mode LCD device according to the present invention, and FIG. 2B is a cross sectional view along II-II' of FIG. 2A according to the present invention. In FIG. 2A, a gate line **101** and a data line **103** may be arranged along transverse and longitudinal directions on a transparent first substrate **110** (in FIG. 2B) to define a pixel area, a common line **104** may be disposed to be parallel with the gate line **101**, and a pixel electrode line **114** may be provided to overlap the common line **104**. Accordingly, the common line **104** and the pixel electrode line **114** may form a storage capacitor using an organic passivation layer **111** (in FIG. 2B) applied along an entire surface of the transparent first substrate **110** as a capacitor dielectric. In addition, a thin film transistor **109** including a gate electrode **101a**, a semiconductor layer **105**, and source and drain electrodes **102a** and **102b** may be disposed at crossing area of the gate and data lines **101** and **103**. Moreover, the gate electrode **101a** may be connected to the gate line and the source electrode **102a** may be connected to the data line **103**, wherein the drain electrode **102b** may be connected to pixel electrodes **107** that vertically branch from the pixel electrode line **114**, and a gate insulating layer **108** (in FIG. 2B) may be deposited along an entire surface of the transparent first substrate **110**.

In FIGS. 2A and 2B, the pixel electrodes **107** and the common electrodes **106**, which may include transparent conductive material, such as ITO and IZO and may branch vertically from the common line **104**, may function to generate a lateral electric field within the pixel area, wherein each of the pixel electrodes **107** may be disposed to alternate with each of the common electrodes within the pixel area. Accordingly, portions of the common electrodes **106** disposed along outer portions of the pixel area may overlap with portions of the data line **103**. In addition, a first alignment layer **112a** may be formed along an entire surface of the transparent first substrate **110** including the common electrodes **106**.

In FIG. 2B, a black matrix **121**, which may prevent light from leaking into the thin film transistor **109** (in FIG. 2A), the gate line **101** (in FIG. 2A), the data line **103** (in FIG. 2A), and a color filter **123** may be formed on a transparent second substrate **120**. In addition, a second alignment layer **112b** may be formed on the color filter **123**, and a liquid crystal layer **113** may be provided between the transparent first and second substrates **110** and **120**.

Accordingly, since portions of the common electrode **106** may overlap portions of the data line **103** and may include the transparent conductive material, the light transmitting area of the pixel area may be increased. However, since the organic passivation layer **111** may overlap the common electrodes **106** and the data line **103**, the light produced by a backlight device may be absorbed in the organic passivation layer **111** and image brightness on the display screen may be lowered.

FIG. 3A is a plan view of another exemplary unit pixel of an in-plane switching mode LCD device according to the present invention, and FIG. 3B is a cross sectional view along III-III' of FIG. 3A according to the present invention. Since FIGS. 3A and 3B may include the same components as those of FIG. 2, except for the passivation layer, same reference numerals will be used to describe like components.

In FIG. 3A, a gate line **101** and a data line **103** may be arranged along transverse and longitudinal directions on a transparent first substrate **110** (in FIG. 3B) to define a pixel area, and a common line **104** may be disposed in parallel with the gate line **101**. In addition, a pixel electrode line **114** may be provided to overlap the common line **104**. Accordingly, the common line **104** and the pixel electrode line **114** may form a storage capacitor using an organic passivation layer **211** as a capacitor dielectric selectively formed on the transparent first substrate **110**. The organic passivation layer **211** may be selectively formed at an area where the gate line **101**, the data line **103**, the common line **104**, and the thin film transistor **109** may be disposed, and portions of the organic passivation layer **211** may be removed on the pixel area. Thus, image brightness on a display screen may be improved.

In FIG. 3A, common electrodes **206** may be formed to vertically branch from the common line **104** and the pixel electrodes **107** may be formed to vertically branch from the pixel electrode line **114**, wherein the common and pixel electrodes **206** and **107** may be alternately arranged within the pixel area.

In FIG. 3B, the common and pixel electrodes **206** and **107**, except for the common electrode **206** disposed along an outer portion of the pixel area, may be formed on the gate insulating layer **108** that may have been formed along an entire surface of the transparent first substrate **110**. Accordingly, the common and pixel electrodes **206** and **107** may generate a lateral electric field within the pixel area.

Portions of the common electrodes **206** formed along the outer portion of the pixel area that overlap with portions of the data line **103** may be formed on the organic passivation layer **211**, wherein the organic passivation layer **211** may electrically insulate the common electrode **206** and the data line **103**. In addition, a first alignment layer **112a** may be formed along an entire surface of the transparent first substrate **110** including the common and pixel electrodes **206** and **107**.

In FIG. 3B, a black matrix **121**, which may prevent light from leaking into the TFT **109**, a color filter **123**, and a second alignment layer **112b** may be formed on a transparent second substrate **120**. In addition, a liquid crystal layer **113** may be provided between the transparent first and second substrates **110** and **120**.

Accordingly, the organic passivation layer **211** may be formed only within areas exclusive of the pixel area (i.e., the gate line **101**, the data line **103**, the common line **104**, and the TFT **109**), wherein loss of light produced by a backlight device and generated onto a light transmission area (i.e., pixel area) may be prevented. However, as shown in FIG. 3B, since the organic passivation layer **211** may be selectively formed within the area of the gate line **101**, the data line **103**, the common line **104**, and the thin film transistor **109**, a stepped portion **200** may be formed along an edge portion of the pixel area. Accordingly, alignment of the liquid crystal molecules may not be properly achieved due to slanted surfaces of the stepped portion **200**. Thus, the light may leak along the stepped portion **200**, thereby lowering image quality.

FIG. 4A is a plan view of another exemplary unit pixel of an in-plane switching mode LCD device according to the present invention, and FIG. 4B is a cross sectional view along IV-IV' of FIG. 4A according to the present invention. In FIGS. 4A and 4B, since all components, except a light blocking system formed on a lower portion of a stepped portion **200** on the organic passivation layer **211**, may be the

same as those of FIGS. 3A and 3B, similar reference numerals may be used for the same components.

In FIG. 4A, a gate line **101** and a data line **103** may be disposed along transverse and longitudinal directions on a transparent first substrate **110** (in FIG. 4B) to define a pixel area, and a common line **104** may be disposed to be parallel with the gate line **101**.

In FIG. 4B, a pixel electrode line **114** may be provided to overlap the common line **104**, wherein the common line **104** and the pixel electrode lines **114** may form a storage capacitor using an organic passivation layer **211** as a capacitor dielectric. The organic passivation layer **211** may be selectively formed within an area where the gate line **101**, the data line **103**, the common line **104**, and the thin film transistor **109** are disposed, and may include a slanted stepped portion **200** along an edge portion of the pixel area. In addition, a light blocking line **350** may be formed along a portion of the transparent first substrate **110** that corresponds to the stepped portion **200** in order to block any light that may leak from the stepped portion **200** of the organic passivation layer **211**. The light blocking line **350** may be simultaneously with the gate line **101**.

In FIG. 4A, common electrodes **206** may be formed to vertically branch from the common line **104** and the pixel electrodes **107** may be formed to vertically branch from the pixel electrode line **114**, wherein the common and pixel electrodes **206** and **107** may be disposed to alternate within the pixel area. The common and pixel electrodes **206** and **107**, except for the common electrodes **206** disposed along an outer portion of the pixel area, may be formed on a gate insulating layer **108** that may be provided along an entire surface of the transparent first substrate **110**. Accordingly, the common and pixel electrodes **206** and **107** may function to generate a lateral electric field within the pixel area.

In FIG. 4A, portions of the common electrode **206** formed along the outer portion of the pixel area may overlap with portions of the data line **103** formed on the organic passivation layer **211**, wherein the organic passivation layer **211** may electrically insulate the common electrode **206** and the data line **103**. In addition, the first alignment layer **112a** is formed on the entire surface of substrate including the common electrode **206** and the pixel electrode **107**.

In FIG. 4B, a black matrix **121**, which may prevent light from leaking into the TFT **109**, a color filter **123**, and a second alignment layer **112b** may be formed on a transparent second substrate **120**. In addition, a liquid crystal layer **113** may be provided between the transparent first and second substrates **110** and **120**.

In FIG. 4B, a light blocking line **350** may be formed within an area corresponding to a stepped portion **200** of the organic passivation layer **211**, thereby preventing a light leakage on the stepped portion **200**. In addition, voltages equal to voltages supplied to the common electrode **206** may be supplied to the light blocking line **350** to form equivalent potentials therebetween. Accordingly, affects of data voltages supplied to the data line **103** toward the pixel electrodes **107** may be effectively shielded.

In general, in order to reduce affects of the data voltage supplied to the data line **103** toward the pixel electrodes **107** in the in-plane switching mode LCD device, the common electrodes **206** are disposed along outer portions of the pixel area adjacent to the data lines **103**. However, it may not be possible to completely shield the affects of the data voltages toward the pixel electrodes **107** adjacent to the data line **103**. Thus, vertical cross talk may be generated by the affects of

the electric field of the data voltages toward the pixel electrodes **107** during driving, thereby lowering image quality.

However, as shown in FIG. **4B**, since the light blocking line **350** may be formed on the stepped portion **200**, when voltages equal to voltages supplied to the common electrodes **206** are supplied, the common electrode **206** and the light blocking line **350** form equivalent potentials that block the affects of the data voltages supplied to the data line **103** toward the pixel electrodes **107**. Thus, a complete lateral electric field may be formed between the common electrodes **206** and the pixel electrodes **107**.

Moreover, the pixel electrodes **107** and the common electrodes **206** may be formed on a common plane (i.e., a gate insulating layer), thereby increasing an electric field supplied to the liquid crystal layer between the pixel and common electrodes **107** and **206**. Accordingly, the liquid crystal molecules of the liquid crystal layer may be switched more rapidly by the stronger electric field, and may produce moving images.

FIGS. **5A** to **5D** are plan views of an exemplary method of fabricating an in-plane switching mode LCD device according to the present invention, and FIGS. **6A** to **6D** are cross sectional views along V-V', VI-VI', VII-VII', and VIII-VIII' of FIGS. **5A** to **5D**, respectively, showing the exemplary method of fabricating an in-plane switching mode LCD device according to the present invention.

In FIGS. **5A** and **6A**, a metal, such as Cu, Ti, Cr, Al, Mo, Ta, and Al alloys, may be deposited and patterned on an insulating substrate **110**, such as glass, to form a gate line **101**, a gate electrode **101a**, and a light blocking line **350**, which may be disposed along a vertical direction normal to a direction of the gate line **101**. Then, SiNx or SiOx may be deposited using a plasma CVD method along an entire surface of the insulating substrate **110**, including the gate line **101** and the light blocking line **350**, to form a gate insulating layer **108**. Next, amorphous silicon and n⁺ amorphous silicon may be deposited and patterned on an upper part of the gate insulating layer **108** to form a semiconductor layer **105** on the gate electrode **101a**.

In FIGS. **5B** and **6B**, a metal, such as Cu, Mo, Ta, Al, Cr, Ti, and Al alloys, may be deposited using a sputtering method and patterned to form a data line **103** parallel with the light blocking line **350**, source and drain electrodes **102a** and **102b**, a pixel electrode line **114** disposed in parallel with the gate line **101**, and pixel electrodes **107** that may vertically branch from the pixel electrode line **114**, wherein the pixel electrodes **107** may include a portion that is connected to the drain electrode **102b**. The pixel area may be defined by cross regions of the gate and data lines **101** and **103** arranged along transverse and longitudinal directions, wherein a thin film transistor **109** including a gate electrode **101a**, the semiconductor layer **105**, and the source and drain electrodes **102a** and **102b** may be formed at the cross regions of the gate and data lines **101** and **103**.

In FIGS. **5C** and **6C**, an organic material, such as benzocyclobutene or acryl, may be formed along an entire upper portion of the gate insulating layer **108** of a pixel area upon which the thin film transistor **109** and the pixel electrode **107** are formed to form an organic material layer. Then, portions of the organic material layer may be removed to expose portions of the pixel electrodes **107** on the gate insulating layer **108**, wherein an organic passivation layer **211** may selectively remain on the gate line **101**, the data line **103**, the pixel electrode line **114**, and the thin film transistor **109**.

In FIGS. **5D** and **6D**, transparent material, such as ITO or IZO, may be deposited along an entire surface of the

insulating substrate **110** including the pixel electrodes **107**. Then, the transparent material may be patterned to form the common line **104** (in FIG. **5D**) to overlap with the pixel electrode line **114**, wherein common electrodes **206** may vertically branch from the common line **104** for generating a lateral electric field with the pixel electrodes **107** within the pixel area. In addition, portions of the common electrodes **206** disposed along outer portions of the pixel area may be formed to overlap portions of the data line **103**.

Then, the insulating substrate **110** and another substrate upon which color filters may be formed may be attached together, and a liquid crystal layer may be provided between the insulating substrate **110** and the another substrate, thereby forming an LCD device.

According to the present invention, an in-plane switching mode LCD device includes removal of a portion of an organic passivation layer formed within a pixel area in order to prevent a decrease in image brightness due to light absorption of the organic passivation layer. Accordingly, a high aperture ratio may be achieved. In addition, a light blocking system is provided at a stepped portion of the organic passivation layer in order to prevent light leakage generated on the stepped portion of the organic passivation layer. Thus, voltages equal to voltages supplied to a common electrode may be supplied to the light blocking system in order to block affects of data voltages supplied to data lines toward pixel electrodes, thereby improving image quality. Moreover, since pixel and common electrodes may be formed within a same plane, switching of liquid crystals may increase, thereby providing rapid display of images (i.e., moving images).

It will be apparent to those skilled in the art that various modifications and variations can be made in the in-plane switching mode liquid crystal display device and method of fabricating and in-plane switching mode liquid crystal display device of the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. An in-plane switching mode liquid crystal display device, comprising:

first and second substrates;

a gate line and a data line arranged along first and second directions on the first substrate to define a pixel area; a passivation layer on the first substrate except within the pixel area;

a light blocking system on the first substrate and under a stepped portion of the passivation layer adjacent to the data line;

a plurality of common electrodes disposed within the pixel area, at least one of the common electrodes overlap a portion of the data line; and

a plurality of pixel electrodes disposed within the pixel area, wherein the pixel electrodes and the common electrodes form a lateral electric field.

2. The device according to claim **1**, further comprising a thin film transistor at a cross portion of the gate and data lines.

3. The device according to claim **1**, wherein the thin film transistor includes:

a gate electrode on the first substrate;

a gate insulating layer on the gate electrode;

a semiconductor layer on the gate insulating layer;

an ohmic contact layer on the semiconductor layer; and

source and drain electrodes on the ohmic contact layer.

4. The device according to claim 3, wherein the gate insulating layer is formed along an entire surface of the first substrate.

5. The device according to claim 1, wherein the common electrodes and the pixel electrodes are formed on a common plane.

6. The device according to claim 5, wherein the common electrodes and the pixel electrodes are formed on the gate insulating layer.

7. The device according to claim 1, wherein the common electrodes include transparent conductive material.

8. The device according to claim 7, wherein the transparent conductive material includes at least one of indium tin oxide (ITO) and indium zinc oxide (IZO).

9. The device according to claim 1, wherein the light blocking system is formed with the gate electrode.

10. The device according to claim 1, wherein the passivation includes at least an organic material.

11. The device according to claim 10, wherein the organic material includes at least one of benzocyclobutene and photoacryl.

12. A method of fabricating an in-plane switching mode liquid crystal display device, comprising:

forming a gate line and a data line along first and second

directions on a first substrate to define a pixel area;

forming a passivation layer on the first substrate except within the pixel area;

forming a light blocking system on the first substrate and under a stepped portion of the passivation layer adjacent to the data line;

forming a plurality of common electrodes disposed within the pixel area, at least one of the common electrodes overlap a portion of the data line; and

forming a plurality of pixel electrodes disposed within the pixel area,

wherein the pixel electrodes and the common electrodes form a lateral electric field.

13. The method according to claim 12, further comprising forming a thin film transistor at a cross portion of the gate and data lines.

14. The method according to claim 12, wherein forming the thin film transistor includes:

forming a gate electrode on the first substrate;

forming a gate insulating layer on the gate electrode;

forming a semiconductor layer on the gate insulating layer;

forming an ohmic contact layer on the semiconductor layer; and

forming source and drain electrodes on the ohmic contact layer.

15. The method according to claim 14, wherein the gate insulating layer is formed along an entire surface of the first substrate.

16. The method according to claim 12, wherein the common electrodes and the pixel electrodes are formed on a common plane.

17. The method according to claim 16, wherein the common electrodes and the pixel electrodes are formed on the gate insulating layer.

18. The method according to claim 12, wherein the common electrodes include transparent conductive material.

19. The method according to claim 18, wherein the transparent conductive material includes at least one of indium tin oxide (ITO) and indium zinc oxide (IZO).

20. The method according to claim 12, wherein the light blocking system and the gate electrode are simultaneously formed.

21. The method according to claim 12, wherein the passivation includes at least an organic material.

22. The method according to claim 21, wherein the organic material includes at least one of benzocyclobutene and photoacryl.

* * * * *

专利名称(译)	面内切换模式液晶显示装置及其制造方法		
公开(公告)号	US7006186	公开(公告)日	2006-02-28
申请号	US10/670424	申请日	2003-09-26
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG.PHILIPS LCD CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	CHUNG JIN YOUL		
发明人	CHUNG, JIN-YOUL		
IPC分类号	G02F1/1368 G02F1/139 G02F1/1343		
CPC分类号	G02F1/134363 G02F1/136209		
审查员(译)	NGUYEN , 龚便T.		
优先权	1020020088443 2002-12-31 KR		
其他公开文献	US20040125303A1		
外部链接	Espacenet USPTO		

摘要(译)

面内切换模式液晶显示装置包括第一和第二基板，沿第一和第二方向布置在第一基板上的栅极线 and 数据线以限定像素区域，除了像素内的第一基板上的钝化层区域，第一基板上和与数据线相邻的钝化层的台阶部分上的挡光系统，设置在像素区域内的多个公共电极，至少一个公共电极与数据线的一部分重叠多个像素电极设置在像素区域内，其中像素电极和公共电极形成横向电场。

