



US007375785B2

(12) **United States Patent**
Lai et al.

(10) **Patent No.:** **US 7,375,785 B2**
(45) **Date of Patent:** **May 20, 2008**

(54) **IN-PLANE SWITCHING LIQUID CRYSTAL
DISPLAY DEVICE HAVING STORAGE
CAPACITORS**

(75) Inventors: **Chao Chih Lai**, Miao-Li (TW); **Yun
Shih Liu**, Miao-Li (TW); **Tsau Hua
Hsieh**, Miao-Li (TW); **Jia-Pang Pang**,
Miao-Li (TW)

(73) Assignee: **Innolux Display Corp.**, Miao-Li
County (TW)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 158 days.

(21) Appl. No.: **11/026,635**

(22) Filed: **Dec. 30, 2004**

(65) **Prior Publication Data**

US 2005/0151913 A1 Jul. 14, 2005

(30) **Foreign Application Priority Data**

Jan. 13, 2004 (CN) 2004 1 0015202

(51) **Int. Cl.**
G02F 1/1343 (2006.01)

(52) **U.S. Cl.** **349/141; 349/38; 349/39**

(58) **Field of Classification Search** **349/141,**
349/38, 39

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,600,464 A	2/1997	Ohe et al.	
6,628,362 B2	9/2003	Seo et al.	
6,747,722 B2 *	6/2004	Ono et al.	349/141
6,774,956 B2 *	8/2004	Ono et al.	349/39

* cited by examiner

Primary Examiner—David Nelms


Assistant Examiner—David Y. Chung

(74) *Attorney, Agent, or Firm*—Wei Te Chung

(57) **ABSTRACT**

An in-plane switching (IPS) liquid crystal display device (100) includes pixel units each having a storage capacitor. The storage capacitor is formed by a common electrode (112), a drain electrode (103), and a counter electrode (110). The common electrode is electrically coupled with the counter electrode. The counter electrode substantially covers the drain electrode, for shielding unexpected coupling effects on the drain electrode due to data signals on a data line (101) driving other pixels of the liquid crystal display device.

15 Claims, 2 Drawing Sheets






FIGURE 1




FIGURE 2A




FIGURE 2B

IN-PLANE SWITCHING LIQUID CRYSTAL DISPLAY DEVICE HAVING STORAGE CAPACITORS

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to a liquid crystal display device utilizing in-plane switching mode, and more particularly to such a liquid crystal display device having a storage capacitor.

2. Related Art

Liquid crystal displays have been burdened by limited viewing angles for many years. Many researchers in the art have invested huge amounts of time and effort in trying to find possible solutions for this shortcoming. One solution was developed by Masahito Ohe et al., and is disclosed in U.S. Pat. No. 5,600,464. This is the so-called liquid crystal display device with in-plane switching (IPS) mode.

In order for an IPS mode liquid crystal display device to have a higher aperture ratio, Seo et al. developed an "In-Plane Switching Mode Liquid Crystal Display Device Having a High Aperture Ratio," which is disclosed in U.S. Pat. No. 6,628,362 (the '362 patent). In particular, a storage capacitor having a reduced effective area for enlarging the aperture ratio is disclosed. Referring to FIG. 2B of the '362 patent, a circular mark 125 represents a group of electrodes, which are overlapped to form two storage capacitors. As shown, one storage capacitor is formed by a common electrode 109 and a data electrode 108, while the other storage capacitor is formed by the data electrode 108 and a gate electrode 101. However, due to the existence of unexpected coupling effects, such as a capacitive coupling effect, in a liquid crystal display device, especially in an IPS mode liquid crystal display device, the voltage of a pixel electrode is affected by data signals carried on a data signal line driving other pixels. This significantly reduces the quality of images displayed on the liquid crystal display device.

SUMMARY OF THE INVENTION

An objective of the present invention is to provide an IPS mode liquid crystal display device having a storage capacitor capable of shielding unexpected coupling effects.

In order to achieve the above objective, the present invention provides an in-plane switching liquid crystal display device that comprises a storage capacitor capable of shielding unexpected coupling effects such as a capacitive coupling effect. The liquid crystal display device comprises a substrate, a plurality of scanning lines, a plurality of data lines, and a plurality of thin film transistors. The scanning lines and the data lines are arranged on the substrate and cross each other thereby defining a plurality of pixel units. A first dielectric layer is interposed between the scanning lines and the data lines for mutual insulation. The thin film transistors are formed at crossing points of the scanning lines and the data lines. Each thin film transistor comprises a gate electrically coupling to the scanning line, a source electrically coupling to the data line, and a drain.

Each pixel unit comprises a common electrode, a drain electrode, and a counter electrode. The common electrode is formed on the substrate. The drain electrode is electrically coupled to the drain of the thin film transistor. A portion of the drain electrode is formed above a corresponding portion of the common electrode, with the first dielectric layer interposed between the drain electrode and the common electrode. A portion of the counter electrode is formed above

a corresponding portion of the drain electrode, with a second dielectric layer interposed between the drain electrode and the counter electrode. The counter electrode is electrically coupled to the common electrode through a via. The common electrode, the counter electrode and the drain electrode cooperatively form a storage capacitor. In addition, the drain electrode is electrically coupled to the drain electrode through a via. The pixel electrode is arranged substantially parallel to the counter electrode, for generating electric fields substantially parallel to the substrate. The counter electrode substantially covers the drain electrode, for shielding any unexpected coupling effects between the drain electrode and the data lines.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is better understood by referring to the detailed description of the preferred embodiment taken in conjunction with the drawings, wherein:

FIG. 1 is a top elevation illustrating a pixel unit of an IPS liquid crystal display device in accordance with one embodiment of the present invention, the pixel unit comprising a storage capacitor;

FIG. 2A is a cross-sectional view taken along line IIA-IIA of FIG. 1; and

FIG. 2B is a cross-sectional view taken along line IIB-IIB of FIG. 1.

DETAILED DESCRIPTION OF THE INVENTION

The present invention is hereinafter described in detail with reference to the accompanying drawings. FIG. 1 illustrates a pixel unit of an in-plane switching (IPS) liquid crystal display device, while FIG. 2A and FIG. 2B illustrate cross-sectional views taken along line IIA-IIA and line IIB-IIB of FIG. 1 respectively.

Referring to FIG. 1, a pixel unit of an IPS mode liquid crystal display device 100 is illustrated. Referring also to FIGS. 2A and 2B, the liquid crystal display device 100 comprises a plurality of data lines 101, a plurality of scanning lines 102, a first dielectric layer 122, a second dielectric layer 123, and a plurality of thin film transistors 105. The data lines 101 and the scanning lines 102 are arranged on a substrate 130, as shown in FIGS. 2A and 2B, and cross each other thereby defining a plurality of pixel units. The first dielectric layer 122 is interposed between the scanning lines 102 and the data lines 101 for mutual insulation. The thin film transistors 105 are formed at the crossing points of the scanning lines 102 and the data lines 101. Each of the thin film transistors 105 comprises a gate electrically coupling to the scanning line 102, a source electrically coupling to the data line 101, a drain and a channel interposing between the gate, and the drain and the source. In this particular embodiment, an amorphous-silicon (a-Si) film 104 is employed as the channel of the thin-film transistor 105. Other films, such as a poly-silicon film, may alternatively be employed as the channel of the thin-film transistor 105.

Each pixel unit of the liquid crystal display device 100 comprises a common electrode 112, a drain electrode 103, and a counter electrode 110. The common electrode 112 is formed on the substrate 130. The first dielectric layer 122 is formed on the common electrode 112 and the substrate 130.

3

The drain electrode **103** is formed on the first dielectric layer **122**, such that a portion of the drain electrode **103** is formed substantially above a corresponding portion of the common electrode **112**. The drain electrode **103** is electrically coupled to the drain of the thin film transistor **105**. The second dielectric layer **123** is formed on the drain electrode **103**. The counter electrode **110** is formed on the second dielectric layer **123**, such that a portion of the counter electrode **110** is formed substantially above a corresponding portion of the drain electrode **103**. The counter electrode **110** is electrically coupled to the common electrode **112** through a via **121**. The common electrode **112**, the counter electrode **110** and the drain electrode **103** cooperatively form a storage capacitor. In addition, the drain electrode **103** comprises a pixel electrode **111**. In this particular embodiment, the pixel electrode **111** is electrically coupled to the drain electrode **103** through a via **120**. In other embodiments, the pixel electrode **111** may be one part of the drain electrode **103**. The pixel electrode **111** is arranged substantially parallel to the counter electrode **110**, for generating electric fields substantially parallel to the substrate **130**. As shown in FIG. 1, the counter electrode **110** in this particular embodiment is generally fork-shaped with three prongs, while the pixel electrode **111** is generally fork-shaped with two prongs corresponding to the prongs of the counter electrode **110**. However, it will be appreciated that the counter electrode **110** and the corresponding pixel electrode **111** may be formed to have other suitable shapes.

Referring to FIG. 2A, the counter electrode **110** is formed to have a substantially larger area than that of the drain electrode **103**, so that the counter electrode **110** substantially covers the drain electrode **103**. With this configuration, unexpected coupling effects, such as a capacitive coupling effect, on the drain electrode **103** due to data signals being carried on the data line **101** for driving other pixels can be shielded. Therefore, a voltage applied to the drain electrode **103** can be stably maintained, and a voltage applied to the pixel electrode **111** is accordingly stably maintained. Thus, the liquid crystal display device **100** can achieve a steady display. Referring also to FIG. 2B, the counter electrode **110** is electrically coupled to the common electrode **112** through a via **121**.

While the present invention has been described in detail with reference to the illustrated embodiment, it will be appreciated that no limitation to the present invention is intended by the above descriptions. Various equivalents of the preferred embodiment described above will be apparent to those with ordinary skill in the art, and it is therefore contemplated that the present invention be defined according to the following claims in their broadest meaning. Consequently, any modifications or alterations of the preferred embodiments are considered within the scope of the present invention.

What is claimed is:

1. A storage capacitor for an in-plane switching liquid crystal display device, comprising:
 a common electrode;
 a first dielectric layer covering said common electrode;
 a drain electrode disposed on said first dielectric layer above said common electrode, said drain electrode being electrically coupled to a pixel electrode;
 a second dielectric layer covering said drain electrode and said first dielectric layer; and
 a counter electrode disposed on said second dielectric layer above said drain electrode, said counter electrode being arranged substantially parallel to said pixel electrode for generating in-plane switching mode electric

4

fields, being electrically coupled to said common electrode, and substantially covering said drain electrode for shielding unexpected coupling between said drain electrode and an associated data line.

2. The storage capacitor as recited in claim 1, wherein said counter electrode and said common electrode are electrically coupled through a via.

3. An in-plane switching liquid crystal display device comprising:

a substrate;

a plurality of scanning lines and a plurality of data lines arranged on said substrate and crossing each other thereby defining a plurality of pixel units, wherein a first dielectric layer is interposed between the scanning lines and the data lines for mutual insulation; and

a plurality of thin film transistors formed at crossing points of the scanning lines and the data lines, each of the thin film transistors comprising a gate electrically coupled to a corresponding one of the scanning lines, a source electrically coupled to a corresponding one of the data lines, and a drain;

wherein each of the pixel units comprises:

a common electrode;

a drain electrode electrically coupled to the drain of the thin film transistor, a portion of said drain electrode being arranged above a corresponding portion of said common electrode, wherein the first dielectric layer is interposed between said drain electrode and said common electrode; and

a counter electrode electrically coupled to said common electrode and substantially covering said drain electrode for shielding unexpected coupling between said drain electrode and the corresponding data line, wherein a second dielectric layer is interposed between said drain electrode and said counter electrode.

4. The liquid crystal display device as recited in claim 3, wherein said drain electrode further comprises a pixel electrode.

5. The liquid crystal display device as recited in claim 4, wherein said pixel electrode is arranged substantially parallel to said counter electrode for generating electric fields substantially parallel to said substrate.

6. The liquid crystal display device as recited in claim 3, wherein said common electrode and said counter electrode are electrically coupled through a via.

7. The liquid crystal display device as recited in claim 6, wherein said common electrode, said counter electrode and said drain electrode cooperatively form a storage capacitor.

8. An in-plane switching liquid crystal display device including:

pixel units each having a storage capacitor, said storage capacitor formed by a common electrode, a drain electrode, and a counter electrode wherein the common electrode is electrically coupled with the counter electrode and the counter electrode substantially covers the drain electrode for shielding unexpected coupling effects on the drain electrode due to data signals on a data line driving other pixels of the liquid crystal display device.

9. The storage capacitor as recited in claim 1, wherein said counter electrode has a substantially larger area than that of said drain electrode.

10. The storage capacitor as recited in claim 1, wherein said counter electrode is generally fork-shaped with three prongs.

5

11. The storage capacitor as recited in claim 10, wherein said pixel electrode is generally fork-shaped with two prongs corresponding to the prongs of said counter electrode.

12. The storage capacitor as recited in claim 1, wherein said pixel electrode is one part of said drain electrode.

13. The liquid crystal display device as recited in claim 3, wherein said counter electrode has a substantially larger area than that of said drain electrode.

6

14. The liquid crystal display device as recited in claim 4, wherein said counter electrode is generally fork-shaped with three prongs.

15. The liquid crystal display device as recited in claim 14, wherein said pixel electrode is generally fork-shaped with two prongs corresponding to the prongs of said counter electrode.

* * * * *

专利名称(译)	具有存储电容器的面内切换液晶显示装置		
公开(公告)号	US7375785	公开(公告)日	2008-05-20
申请号	US11/026635	申请日	2004-12-30
[标]申请(专利权)人(译)	群创光电股份有限公司		
申请(专利权)人(译)	群创光电股份有限公司.		
当前申请(专利权)人(译)	群创光电		
[标]发明人	LAI CHAO CHIH LIU YUN SHIH HSIEH TSAU HUA PANG JIA PANG		
发明人	LAI, CHAO CHIH LIU, YUN SHIH HSIEH, TSAU HUA PANG, JIA-PANG		
IPC分类号	G02F1/1343 G02F1/136 G02F1/1362 H01L29/786		
CPC分类号	G02F1/134363 G02F1/136213 G02F2001/13606 G02F2001/136218		
审查员(译)	内尔姆斯, DAVID		
助理审查员(译)	CHUNG, DAVID Y.		
优先权	200410015202.X 2004-01-13 CN		
其他公开文献	US20050151913A1		
外部链接	Espacenet USPTO		

摘要(译)

面内切换 (IPS) 液晶显示装置 (100) 包括每个都具有存储电容器的像素单元。存储电容器由公共电极 (112) , 漏电极 (103) 和对电极 (110) 形成。公共电极与对电极电耦合。对电极基本上覆盖漏电极, 用于屏蔽由于驱动液晶显示装置的其他像素的数据线 (101) 上的数据信号而在漏电极上的意外耦合效应。

