



US007719637B2

(12) **United States Patent**
SangYoon et al.

(10) **Patent No.:** **US 7,719,637 B2**
(45) **Date of Patent:** **May 18, 2010**

(54) **LIQUID CRYSTAL DISPLAY DEVICE AND MANUFACTURING METHOD THEREOF**

(75) Inventors: **Paik SangYoon**, Goomi-si (KR); **Lee JoonYoup**, Seoul (KR)

(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 659 days.

(21) Appl. No.: **11/289,034**

(22) Filed: **Nov. 29, 2005**

(65) **Prior Publication Data**

US 2006/0290874 A1 Dec. 28, 2006

(30) **Foreign Application Priority Data**

Jun. 27, 2005 (KR) 10-2005-0055519

(51) **Int. Cl.**
G02F 1/1333 (2006.01)

(52) **U.S. Cl.** **349/110**; 349/158

(58) **Field of Classification Search** 349/110,
349/158

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,297,004 A *	10/1981	Nishimura et al.	349/138
4,721,365 A *	1/1988	Nishimura	349/152
5,058,997 A *	10/1991	Dickerson et al.	349/105
5,285,302 A *	2/1994	Wu	349/43
5,708,483 A *	1/1998	Asai	349/38

5,731,860 A *	3/1998	Harada et al.	349/158
5,739,887 A *	4/1998	Ueda et al.	349/149
5,771,085 A *	6/1998	Ochi et al.	349/158
6,307,613 B1	10/2001	Iida	

FOREIGN PATENT DOCUMENTS

JP	63-113421	5/1988
JP	05-107518	4/1993
JP	10-282464	10/1998
JP	2000-066179	3/2000
JP	2000-147485	5/2000
JP	2000-221462	8/2000
JP	2002-174803	6/2002

OTHER PUBLICATIONS

First Office Action for corresponding Chinese Patent Application Serial No. 2005101304433, dated Dec. 14, 2007.

Office Action dated Feb. 10, 2009 for Japanese Patent No. 2005-356399.

* cited by examiner

Primary Examiner—James A Dudek

(74) *Attorney, Agent, or Firm*—Brinks Hofer Gilson & Lione

(57) **ABSTRACT**

An LCD (liquid crystal display device) and a manufacturing method thereof are provided. The LCD includes a top substrate, a bottom substrate, and an alignment mark for aligning a polarizing plate on the top substrate or the bottom substrate. Also, the method includes: forming a metal layer on a substrate and forming a gate electrode, a gate line, and an alignment mark; forming a thin film transistor and a data line on the substrate with the gate electrode, the gate line, and the alignment mark; and forming a passivation layer and a pixel electrode on the substrate with a source/drain electrode.

13 Claims, 9 Drawing Sheets




Fig. 1
Related Art




Fig.2
Related Art




Fig.3




Fig.4




Fig.5




Fig.6A




Fig.6B




Fig.7




Fig.8





Fig.9



LIQUID CRYSTAL DISPLAY DEVICE AND MANUFACTURING METHOD THEREOF

TECHNICAL FIELD

The present invention relates to a liquid crystal display device, and more particularly, to a liquid crystal display device capable of preventing misattachment of a polarizing plate, and a manufacturing method thereof.

DESCRIPTION OF RELATED ART

Since liquid crystal display devices (LCDs) have low power consumption and high portability through integrated technology, they are considered as a next generation of high-tech display device. The LCD is an image display device that includes liquid crystal injected between an array substrate and a color filter substrate. The array substrate includes thin film transistors (TFTs). The LCD displays an image by using a light refractive index difference according to liquid crystal anisotropy.

An active matrix liquid crystal display (AMLCD) is mainly used in a flat display field. One thin film transistor is used as a switching element to change light transmittance by controlling a voltage applied to the liquid crystal of one pixel. Amorphous silicon:H (hereinafter, referred to as amorphous silicon) is mainly used for a TFT because it can be easily manufactured in a large size.

In manufacturing the LCD, red (R), green (G) and blue (B) color filters are sequentially formed on a top substrate using photolithography, a thin film transistor as a switching element and pixel electrodes are sequentially formed on a bottom substrate using photolithography, and the top substrate and the bottom substrate are attached to each other. Then, an LCD is formed by injecting liquid crystals.

A spacer is dispersed between the substrates to maintain a cell gap between the top substrate and the bottom substrate, and a seal printing process is performed to attach the top substrate and the bottom substrate and seal the liquid crystals.

The subsequent processes after the attachment process will now be described. FIG. 1 is a schematic view illustrating a related art manufacturing process of an LCD.

Referring to FIG. 1, a seal is printed on a TFT with a thin film transistor, and a spacer is dispersed on a color filter substrate (C/F). Then, the two substrates are combined together. The attachment of the substrates is performed with heat, pressure, and ultraviolet irradiation after the TFT substrate is aligned with the color filter substrate. Then, the combined substrate is cut into cells.

When the cell process is completed, liquid crystal is injected into each liquid crystal cell. Then, the injection hole is sealed after the injection process using an ultraviolet hardening resin. A polarizing plate is attached to the liquid crystal cell after liquid crystal is injected into the liquid crystal cell. Attachment of the polarizing plate is performed to press the polarizing plate to the liquid crystal cell using a roller after the polarizing plate is aligned with a liquid crystal surface.

The polarizing plate plays a role in selectively transmitting light polarized in a predetermined direction from light passing through the liquid crystal. The image quality of the LCD display deteriorates if the polarizing plate is not precisely attached to the liquid crystal cell.

After a top polarizing plate and a bottom polarizing plate are attached to the liquid crystal cell, a defect test is applied. The defect test includes determining the lighting status of the liquid crystal cell and whether or not stains are present. The defect test is performed by applying a test signal to a pad

region of the liquid crystal cell. Then, a finished LCD is completed by attaching a circuit substrate to the liquid crystal cell.

However, referring to FIG. 2, misattachment of the polarizing plate 15 frequently occurs in the related art process of attaching a polarizing plate. This occurs as there is often misalignment between the liquid crystal cell 10 and the polarizing plate 15 before the polarizing plate 15 is attached to the liquid crystal cell 10.

FIG. 2 is a plan view illustrating a related art misattachment of a polarizing plate during the process of attaching a polarizing plate. As shown, the polarizing plate 15 is attached to an active area 11 of an image display region, but is tilted during the attachment process.

The misattachment of the polarizing plate occurs because an alignment reference of the polarizing plate 15 and the liquid crystal cell 10 is ambiguous, and the attachment process is performed using a roller right after the polarizing plate 15 is mechanically aligned with the liquid crystal 10. In particular, it is difficult to detect twisting of the polarizing plate when the polarizing plate is attached to the active area 11 of the liquid crystal cell 10.

SUMMARY

By way of introduction only, as embodied and broadly described herein, there is provided an LCD including a top substrate, a bottom substrate, a polarizing plate on the top and/or bottom substrate and a liquid crystal layer between the top substrate and the bottom substrate. The top and/or bottom substrate contains an alignment mark. The polarizing plate is aligned with the alignment mark.

In another aspect of the present invention, a method for manufacturing an LCD is provided. The method includes: forming a layer on a first substrate; etching the layer to form an alignment mark; aligning a polarizing plate on the first substrate using the alignment mark and attaching the aligned polarizing plate to the first substrate; attaching the first substrate to a second substrate; and providing liquid crystal to the first and/or second substrates.

In another embodiment, an LCD (liquid crystal display device) includes color filter and TFT substrates, the first and second polarizing plates on the substrates, and liquid crystal between the substrates. The color filter substrate includes a color filter layer, a black matrix, and a first alignment mark. The first alignment mark is formed along a perimeter of and/or at a corner of an active area in the color filter substrate. The TFT substrate includes gate and data lines, TFTs, pixel electrodes, and a second alignment mark. The second alignment mark is formed along a perimeter of and/or at a corner of an active area in the TFT substrate.

It is to be understood that both the foregoing general description and the following detailed description of the present invention are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate embodiment(s) of the invention and together with the description serve to explain the principle of the invention. In the drawings:

FIG. 1 is a schematic view illustrating a related art manufacturing process of an LCD;

FIG. 2 is a plan view illustrating an attachment defect of a polarizing plate during a process of attaching a polarizing plate according to the related art;

FIG. 3 is a plan view of a polarizing plate attached to an LCD with an alignment mark according to an embodiment of the present invention;

FIG. 4 is an enlarged view of a portion A in FIG. 3;

FIG. 5 is a plan view illustrating a top substrate of a liquid crystal cell with an alignment mark according to an embodiment of the present invention;

FIGS. 6A and 6B are enlarged views of a portion B in FIG. 5;

FIG. 7 is a plan view illustrating a bottom substrate of a liquid crystal cell with an alignment mark according to an embodiment of the present invention;

FIG. 8 is an enlarged view of a portion C in FIG. 7; and

FIG. 9 is a plan view of an LCD according to another embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

FIG. 3 is a plan view of a polarizing plate attached to an LCD with an alignment mark according to an embodiment of the present invention.

Referring to FIG. 3, an LCD includes a top substrate (a color filter substrate) **100a** having R, G and B color filters, a bottom substrate **100b** having pixel electrodes and TFTs, and a liquid crystal layer interposed between the top substrate **100a** and the bottom substrate **100b**. Also, a polarizing plate **150** is attached to a liquid crystal cell **100** formed by attaching the top substrate **100a** and the bottom substrate **100b**.

An alignment mark **150** is formed in a corner region of the top substrate **100a**. The alignment mark **150** permits alignment of the polarizing plate **115** during attachment of the polarizing plate **115** to the liquid crystal cell **100**. The alignment mark can be formed in a black matrix region outside an active area of the top substrate **100a**, or can be formed in a corner region in an active area of the bottom substrate **100b**. That is, the alignment mark **150** can be formed on the top substrate **100a** or the bottom substrate **100b** of the liquid crystal cell **100**. The alignment mark **150** is formed in a '┐'-shape to align with a corner of the polarizing plate **115**.

FIG. 4 is an enlarged view of a portion A in FIG. 3. The alignment mark **150** has a calibrated gauge with a predetermined interval on an x-axis and a y-axis, and is divided with a predetermined angle (θ) inside the x-axis and the y-axis.

Correction of the tilt and alignment are performed with respect to the calibrated gauge when the polarizing plate **115** is attached to the top substrate **100a** or the bottom substrate **100b** of the liquid crystal cell **100**. Misalignment includes tilting that can frequently occur during attachment of the polarizing plate **115** to the top substrate **100a** or the bottom substrate **100b** of the liquid crystal cell **100**. This misalignment can be prevented by aligning a corner of the polarizing plate **115** with the calibrated gauge of the x-axis and the y-axis or the angle θ .

FIG. 5 is a plan view illustrating the top substrate of the liquid crystal cell with the alignment mark according to an embodiment of the present invention. The alignment mark **150** is formed on the corner of an active area **105** in the top substrate **100a** so as enable precise attachment of the polar-

izing plate **115** thereto. The alignment mark **150** is formed by patterning a black matrix **106** of the top substrate **100a**.

Although four alignment marks **150** are illustrated in the corners of the active area **105**, more alignment marks **150** can also be formed along the corners of the active area **105**. Since the alignment mark **150** is formed together with the black matrix during manufacturing of the LCD, additional processes may be avoided in formation of the alignment mark **150**.

FIGS. 6A and 6B are enlarged views of a portion B in FIG. 5.

Referring to FIGS. 6A and 6B, the alignment mark **150** is formed together when the black matrix **106** is formed on the top substrate **100a**. After chrome (Cr) or resin material is formed on the glass, the black matrix **106** is formed by photolithography. The black matrix **106** is formed in a lattice shape in an active area **105** of the top substrate **100a**, and is formed thickly enough to have a predetermined width for preventing light leakage around the corners.

Referring to FIG. 6A, when the black matrix **106** is formed, the alignment mark **150** is formed in an engraved shape with glass exposed by etching and patterning the black matrix **106**. That is, the alignment mark **150** is patterned when the black matrix **106** is patterned according to a photo process. Referring to FIG. 6A, the alignment mark **150** is formed to expose the transparent glass forming the top substrate **100a** by etching the black matrix **106**. Accordingly, the alignment mark **150** and the angle θ are formed in a glass region that is exposed by an etching process.

However, referring to FIG. 6B, after etching the alignment mark region, the alignment mark **150** can be formed of a material of the black matrix **106** in an embossed shape. At this time, the calibrated gauge and the angle θ on the x-axis and the y-axis are formed of the material as the black matrix **106**. When the black matrix **106** is formed on a glass, a color filter layer is formed in the active area **105** by using R, CG and B color resins. Misattachment of the polarizing plate can be prevented by forming the alignment mark **150** on the top substrate **100a** with the color filter layer so as to align the polarizing plate **115**. The polarizing plate **115** is then attached to the liquid crystal cell **100**.

FIG. 7 is a plan view illustrating the bottom substrate of the liquid crystal cell with the alignment mark according to an embodiment of the present invention. FIG. 8 is an enlarged view of a portion C in FIG. 7.

Referring to FIGS. 7 and 8, the alignment mark **150** prevents misalignment when attaching the polarizing plate **115** on the bottom substrate **100b**, which has the TFTs and the pixel electrodes. The alignment mark **150** is formed on the corner region of the active area **109** with the TFTs and the pixel electrodes inside a pad region. That is, the alignment mark **150** is formed on the bottom substrate **100b** corresponding to the region in which the alignment mark is formed in FIG. 5.

The alignment mark **150** is formed on the bottom substrate **100b** when a gate line or data line is formed in manufacturing the bottom substrate **100b**. That is, when a metal layer from which a gate line, a gate electrode, and/or a gate pad are formed on the glass substrate, the alignment mark **150** is formed by patterning a metal layer in the corner region of the active area **109**. The alignment mark **150** is formed in a '┐'-shape.

Next, a thin film transistor, a data line, and a data pad are formed by forming an active layer and source/drain electrodes. Additionally, the active layer includes a gate insulating layer, a channel layer, and an ohmic contact layer.

The alignment mark **150** can be formed during formation of the source/drain electrode, the data line, and/or the data pad. In this case, the alignment mark **150** is not formed during formation of the gate line but is formed by patterning a metal layer during formation of the data line.

Accordingly, the alignment mark **150** is formed of a source/drain electrode metal, and is a 'T'-shaped structure in a corner of an active area **109**. Additionally, the alignment mark **150** is formed in each corner of the active area **109**. However, a plurality of alignment marks can be formed along with the perimeter of the active area **109**.

After the source/drain electrodes and the data line are formed, the bottom substrate (the TFT substrate) **100b** is completed by forming a passivation layer and a pixel electrode. Accordingly, the alignment mark **150** can prevent misalignment and tilting of the polarizing plate **115** during the attachment process because the angle θ and the calibrated gauge on the x-axis and the y-axis are formed to align the polarizing plate **115**.

FIG. 9 is a plan view of an LCD according to another embodiment of the present invention.

Referring to FIG. 9, an alignment mark **250** prevents misalignment when attaching a polarizing plate **115** to a liquid crystal panel. A top substrate **200a** includes a color filter layer and a black matrix, and a bottom substrate **200b** includes TFTs and pixel electrodes. The liquid crystal panel **200** is formed by attaching the top substrate **200a** to the bottom substrate **200b**.

Because the alignment mark **250** has a cross shape, the polarizing plate can be arranged by aligning a corner of the polarizing plate **115** with the alignment mark **250**. The alignment mark **250** of FIG. 9 has a broader range of use for aligning the polarizing plate **115** than that of FIG. 3. Attachment still can be performed even if an end of the corner in the polarizing plate **115** is not disposed on the center of the cross as long as the corner of the polarizing plate **115** is overlapped with the alignment mark **250**, and is vertically and horizontally aligned with the alignment mark **250**.

Additionally, referring to FIGS. 6a to 8, formation of the alignment mark **250** in the cross shape is identical to formation of the top substrate **100a** with the color filter and the black matrix, and the bottom substrate **100b** with the TFTs and pixel electrodes. Accordingly, a description about the formation of the alignment mark **250** in the cross shape will be omitted.

The alignment mark of the polarizing plate can be used during attachment of the polarizing plate, and during attachment of other plates such as an optical sheet and a light guide plate in manufacturing the LCD. Accordingly, misalignment that frequently occurs during attachment of the polarizing plate, such as relative tilting between the polarizing plate and the substrate, can be prevented by forming an alignment mark to permit precise alignment of the polarizing plate with the LCD and accurately attach the polarizing plate to the liquid crystal cell.

It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A method for manufacturing an LCD (liquid crystal display device), the method comprising:

forming a layer on a first substrate;

5 forming a gate electrode, gate and data lines, a thin film transistor, a passivation layer and a pixel electrode on the first substrate;

etching the layer to form an alignment mark;

10 aligning a polarizing plate on the first substrate using the alignment mark and attaching the aligned polarizing plate to the first substrate;

attaching the first substrate to a second substrate;

15 providing liquid crystal to at least one of the first or second substrates, forming a black matrix on the second substrate; and

forming red, green, and blue color filters on the second substrate,

20 wherein the red, green, and blue color filters are formed on the second substrate after the black matrix is formed on the second substrate,

wherein the alignment mark is formed of the same material as the gate electrode and the gate line, and

25 wherein the alignment mark comprises an angle mark, an x-axis and a y-axis.

2. The method according to claim 1, wherein the liquid crystal is provided between the first and second substrate after the first and second substrates are attached to each other.

3. The method according to claim 1, wherein the alignment mark is embossed and formed of the same material as the black matrix.

4. The method according to claim 1, wherein the alignment mark is engraved by etching the black matrix.

5. The method according to claim 1, wherein the alignment mark is formed at a corner of an active area of the first substrate.

6. The method according to claim 1, wherein a plurality of the alignment marks is formed along a perimeter of an active area of the first substrate.

7. The method according to claim 1, wherein the alignment mark comprises a perpendicularly bent shape such that the alignment mark corresponds to a corner of the polarizing plate.

8. The method according to claim 1, wherein the alignment mark comprises a cross shape.

9. The method according to claim 1, wherein the alignment mark, the gate electrode, and the gate line are formed at the same time by etching the layer.

10. The method according to claim 1, wherein the alignment mark is formed of the same material as the data line.

11. The method according to claim 10, wherein the alignment mark and the data line are formed at the same time by etching the layer.

12. The method according to claim 1, further comprising: forming another alignment mark on the second substrate;

15 aligning another polarizing plate on the second substrate using the other alignment mark; and attaching the aligned other polarizing plate to the second substrate.

13. The method according to claim 1, wherein the aligned polarizing plate is attached to the first substrate after the first and second substrates are attached.

* * * * *

专利名称(译)	液晶显示装置及其制造方法		
公开(公告)号	US7719637	公开(公告)日	2010-05-18
申请号	US11/289034	申请日	2005-11-29
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG 飞利浦LCD CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	SANGYOON PAIK JOONYOUP LEE		
发明人	SANGYOON, PAIK JOONYOUP, LEE		
IPC分类号	G02F1/1333		
CPC分类号	G02F1/133528 G02F1/1333		
代理机构(译)	BRINKS 霍费尔 GILSON & LIONE		
优先权	1020050055519 2005-06-27 KR		
其他公开文献	US20060290874A1		
外部链接	Espacenet USPTO		

摘要(译)

提供一种LCD (液晶显示装置)及其制造方法。LCD包括顶部基板,底部基板和用于在顶部基板或底部基板上对准偏振板的对准标记。此外,该方法包括:在基板上形成金属层,并形成栅电极,栅极线和对准标记;利用栅电极,栅极线和对准标记在衬底上形成薄膜晶体管和数据线;用源/漏电极在衬底上形成钝化层和像素电极。

