



US 20050001962A1

(19) **United States**

(12) **Patent Application Publication**

Maeda

(10) **Pub. No.: US 2005/0001962 A1**

(43) **Pub. Date:**

Jan. 6, 2005

(54) **LIQUID CRYSTAL DISPLAY DEVICE, METHOD OF MANUFACTURING THE SAME, AND ELECTRONIC APPARATUS**

(75) Inventor: **Tsuyoshi Maeda**, Ryno-cho (JP)

Correspondence Address:
OLIFF & BERRIDGE, PLC
P.O. BOX 19928
ALEXANDRIA, VA 22320 (US)

(73) Assignee: **SEIKO EPSON CORPORATION**,
Tokyo (JP)

(21) Appl. No.: **10/846,703**

(22) Filed: **May 17, 2004**

(30) **Foreign Application Priority Data**

Jun. 6, 2003 (JP) 2003-162353

Publication Classification

(51) **Int. Cl. 7** **G02F 1/1335**

(52) **U.S. Cl. 349/114**

(57) **ABSTRACT**

The invention provides a liquid crystal display device capable of displaying images with a wide angle in both of transmissive display and reflective display. In the liquid crystal display device, a liquid crystal layer can be interposed between a pair of substrates, and a transmissive display region and a reflective display region can be provided in one dot region. The liquid crystal layer is made of liquid crystal whose dielectric anisotropy showing that liquid crystal molecules are vertically aligned at an initial stage is negative. A liquid crystal layer thickness controlling layer for making the thickness of the liquid crystal layer in the reflective display region different from the thickness of the liquid crystal layer in the transmissive display region can be provided between the substrate and the liquid crystal layer. In the transmissive display region and the reflective display region, protrusions that protrude from the internal surface of the substrate to the inside of the liquid crystal layer are further provided. Therefore, the height of the convex portions formed in the transmissive display region is larger than the height of the convex portions formed in the reflective display region.




Fig. 1




Fig. 2




Fig. 3a




Fig. 3b




Fig. 4a




Fig. 4b




Fig. 5a




Fig. 5b




Fig. 6a




Fig. 6b





Fig. 7



LIQUID CRYSTAL DISPLAY DEVICE, METHOD OF MANUFACTURING THE SAME, AND ELECTRONIC APPARATUS

BACKGROUND OF THE INVENTION

[0001] 1. Field of Invention

[0002] The invention relates to a liquid crystal display device, a method of manufacturing the same, and an electronic apparatus. More specifically, the invention relates to technology for obtaining a wide viewing angle in a liquid crystal display device using a homeotropic alignment liquid crystal.

[0003] 2. Description of Related Art

[0004] Transflective liquid crystal display devices which include a reflective mode and a transmissive mode are known. In a transflective liquid crystal display device, a liquid crystal layer is interposed between an upper substrate and a lower substrate. A reflecting film with a light transmissive window in a metal film, such as aluminum, is provided on the internal surface of the lower substrate. The reflecting film functions as a transflective sheet. In this case, in the reflective mode, external light incident from the upper substrate is reflected from the reflecting film on the internal surface of the lower substrate after passing through the liquid crystal layer, then passes through the liquid crystal layer again and is emitted from the upper substrate to contribute to display. On the other hand, in the transmissive mode, the light from a backlight incident from the lower substrate passes through the liquid crystal layer through the window of the reflecting film and is emitted from the upper substrate to the outside to contribute to the display. Therefore, the region of the reflecting film with the window is the transmissive display region and the other region is the reflective display region.

[0005] In conventional transflective liquid crystal devices, the viewing angle in transmissive display is narrow. This is because, since a transflective sheet is provided on the internal surface of a liquid crystal cell so that parallax is not generated, only one polarizer provided on the observer side works on the reflective display which reduces the freedom of optical design. Therefore, in order to solve this problem, Jisaki et al. suggested a new liquid crystal display device using a homeotropic alignment liquid crystal. See, for example, "Development of transflective LCD for high contrast and wide viewing angle by using homeotropic alignment", M. Jisaki et al., Asia Display/IDW'01, P. 133-136 (2001). The liquid crystal display device has the following three characteristics:

[0006] (1) A vertical alignment (VA) mode, in which liquid crystal molecules with negative dielectric anisotropy are vertically aligned on a substrate and the liquid crystals fall by applying a voltage.

[0007] (2) A "multi-gap structure" is adopted, in which the thickness (a cell gap) of the liquid crystal layer in the transmissive display region is different from that of the liquid crystal layer in the reflective display region (with respect to this point, refer to Japanese Unexamined Patent Application Publication No. 11-242226).

[0008] (3) The transmissive display region is an octagon and protrusions are provided in the middle of the transmis-

sive display region on a counter substrate so that the liquid crystal molecules fall in eight directions in the region.

[0009] See also, generally, Japanese Unexamined Patent Application Publication No. 2002-350853.

SUMMARY OF THE INVENTION

[0010] However, in the thesis of Jisaki et al., the directions in which the liquid crystal molecules in the transmissive display region fall are controlled by protrusions. However, means for controlling the directions in which the liquid crystal molecules fall do not exist in the reflective display region. Therefore, in the reflective display region, the liquid crystal molecules fall in random directions. In this case, a line of discontinuity referred to as disclination appears on the boundary of another liquid crystal alignment region, which causes afterimages. Also, since the respective alignment regions of the liquid crystal have difference visual characteristics, when the liquid crystal device is seen from a tilted direction, spots may appear.

[0011] On the other hand, it is very effective to adjust the electro-optical characteristics (transmittance-voltage characteristics and reflectance-voltage characteristics) of the transmissive display region to those of the reflective display region when the transflective liquid crystal display device includes the multi-gap structure like that in Japanese Unexamined Patent Application Publication No. 11-242226. This is because light passes through the liquid crystal layer only once in the transmissive display region but twice in the reflective display region. However, when such a multi-gap structure is employed and, at the same time, when the directions in which the liquid crystal molecules fall are controlled using the above-mentioned protrusions, since the thickness in the transmissive display region is different from the thickness in the reflective display region, it is not possible to control sufficiently the alignment of the liquid crystal molecules in any one region only by providing the protrusions in the respective regions.

[0012] It is an object of the invention to provide a transflective liquid crystal display device using homeotropic alignment liquid crystal capable of displaying images with a wide viewing angle in both of transmissive display and reflective display and a method of manufacturing the same. It is another object of the invention to provide a reliable transflective liquid crystal display device using homeotropic alignment liquid crystal whose structure is simplified, thus improving the manufacturing efficiency and reducing the occurrence of inferior quality, a method of manufacturing the same, and an electronic apparatus comprising the above-mentioned liquid crystal display device.

[0013] In order to achieve the objects, there can be provided a liquid crystal display device in which a liquid crystal layer is interposed between a pair of substrates, and a transmissive display region and a reflective display region are provided in one dot region. The liquid crystal layer can be made of liquid crystal whose dielectric anisotropy, indicating that liquid crystal are vertically aligned in an initial state, is negative. A liquid crystal layer thickness-adjusting layer to make the thickness of the liquid crystal layer in the reflective display region smaller than the thickness of the liquid crystal layer in the transmissive display region can be formed between at least one substrate of the pair of substrates and the liquid crystal layer. Convex portions that

protrude from the internal surface of the substrates to the inside of the liquid crystal layer are formed in the transmissive display region and the reflective display region, and wherein the height of the convex portions is larger in the transmissive display region than in the reflective display region.

[0014] The liquid crystal display device according to the invention can be obtained by combining liquid crystal in a vertical alignment mode with a transreflective liquid crystal display device and by adding a liquid crystal layer thickness-adjusting layer (that is, a multi-gap structure) to the transreflective liquid crystal display device for making birefringence retardation of a reflective display region almost equal to that of a transmissive display region and thus control the directions of the alignment of liquid crystal molecules.

[0015] In other words, according to the liquid crystal display device in the vertical alignment mode, liquid crystal molecules that are vertically erect with respect to the substrate in an initial state fall by applying an electric field. When nothing is designed (when pre-tilt is not given), the directions in which the liquid crystal molecules fall cannot be controlled and disorder (disclinations) in the alignment is caused which generates display problems such as light leakage and deteriorates display quality. Therefore, when a vertical alignment mode is employed, control of the directions in which the liquid crystal molecules are aligned when the electric field is applied is an important factor. Therefore, in the liquid crystal display device according to the present invention, a convex portion is formed in both the transmissive display region and the reflective display region. The directions in which the liquid crystal molecules are aligned in the each region are regulated.

[0016] According to such alignment regulation, the liquid crystal molecules are vertically aligned in an initial state and have pre-tilt according to the shape of the convex portion. As a result, it is possible to regulate or control the directions in which the liquid crystal molecules fall in both the transmissive display region and the reflective display region. Therefore, it is difficult to cause the disorder (disclinations) in the alignment and it is possible to avoid the inferiority in the display such as light leakage. As a result, it is possible to reduce problems such as afterimages and spots and provide a liquid crystal display device with a wide viewing angle.

[0017] Also, since the multi-gap structure is employed in the liquid crystal display device according to the invention, a thickness of the liquid crystal layer in the transmissive display region is larger than the thickness of the liquid crystal layer in the reflective display region. Therefore, it may be impossible to control sufficiently the alignment of the liquid crystal in any one region only by providing the convex portions in both of the transmissive display region and the reflective display region. In other words, since the thickness of the liquid crystal layer in the transmissive display region is different from the thickness of the liquid crystal layer in the reflective display region, an ability of aligning the liquid crystal molecules in the transmissive display region where the thickness of the liquid crystal layer is larger may deteriorate than that in the reflective display region only by forming the convex portions having the same height in the respective regions.

[0018] Therefore, according to the invention, it is possible to control the alignment of the liquid crystal molecules in

both of the transmissive display region and the reflective display region by making the height of the convex portions in the transmissive display region larger than the height of the convex regions in the reflective display region. Therefore, it is possible to prevent the generation of inferiority in display such as afterimages or spots in both of the transmissive mode and the reflective mode and to thus display images with a wide viewing angle. Also, according to the present invention, for example, the internal surface of the substrate means the liquid crystal layer side of the substrate. That the convex portions protrude above the substrates means that the convex portions protrude from the internal surface of the liquid crystal layer thickness-adjusting layer when the liquid crystal layer thickness-adjusting layer is formed on the internal surface of the substrate.

[0019] In the liquid crystal display device according to the invention, the convex portions can be provided as alignment regulating device for regulating the alignment of the liquid crystal and have surfaces inclined at a predetermined angle with respect to the surfaces of the substrate for interposing the liquid crystal layer therebetween. It is possible to control the directions in which the liquid crystal molecules fall along the tilted surface by including the tilted surfaces. Also, electrodes for driving the liquid crystal are provided on the liquid crystal layer sides of the pair of substrates, and the convex portions are formed on at least one electrode of the electrodes facing the liquid crystal layer. In this case, an alignment film for vertically aligning the liquid crystal is formed on the convex portions and the internal surface of the electrode. It is possible to provide a circular polarizer for making circularly polarized light incident on the liquid crystal layer on the sides of the pair of substrates opposite to the liquid crystal layer. The circular polarizer may be obtained by composing the polarization layer with the retardation layer.

[0020] Furthermore, in the liquid crystal display device according to the invention, an upper substrate and a lower substrate are provided as the pair of substrates, a backlight for transmissive display is provided on the side of the lower substrate opposite to the liquid crystal layer, and a reflective layer selectively formed in the reflective display region is formed on the side of the lower substrate facing the liquid crystal layer. In this case, it is possible to use the light from the backlight, which is incident from the lower substrate, for the transmissive display and to reflect external light, such as illumination, and solar light incident from the upper substrate in the reflective layer to thus be used for the reflective display.

[0021] A color filter layer can be provided on the liquid crystal layer sides of at least one of the pair of substrates. The color filter layer has a plurality of colored layers (for example, colored layers corresponding to three primary colors of light). The plurality of colored layers overlap each other in the inter-dot region in plan view. In this case, it is possible to display black by the colored layer (referred to as an overlap colored layer) formed by overlapping the colored layers of the three primary colors of light and to use the overlap colored layer as a black matrix in the inter-dot region. Therefore, since it is not necessary to additionally form the black matrix, it is possible to simplify the structure of the liquid crystal display device and to improve manufacturing efficiency.

[0022] The liquid crystal layer thickness-adjusting layer and second convex portions that protrude from the liquid crystal layer thickness-adjusting layer to the liquid crystal layer are formed on the side of the liquid crystal layer in the region where the colored layers overlap each other in plan view. In this case, the second convex portions can be used instead of the spacers, that is, as a device for controlling the thickness of the liquid crystal layer (the distance between substrates, that is, the cell gap). The region formed by overlapping the colored layers protrudes above the other regions by the amount the colored layers overlap. However, when the liquid crystal layer thickness-adjusting layer is formed in the overlap colored layer together with the second convex portion, since the second convex portions protrude outermost inside the substrate, it is possible to use the second convex portions as the means for controlling the thickness of the liquid crystal layer.

[0023] Also, the second convex portions are preferably formed in the same step as the convex portions formed in the transmissive display region and the reflective display region in order to improve the manufacturing efficiency. In this case, the convex portions formed in the transmissive display region and the reflective display region are made of the same material as the second convex portion. Also, the height of the second convex portions is almost equal to that of the convex portions formed in the transmissive display region and the reflective display region. In this case, it is possible to use the second convex portions as the device for controlling the thickness of the liquid crystal layer. On the other hand, since the convex portions formed in the transmissive display region and the reflective display region have the height almost equal to the height of the second convex portion, it is possible to prevent the convex portions from contacting an opposite substrate, and to thus control the alignment of the liquid crystal molecules.

[0024] An electronic apparatus according to the invention can include the above-mentioned liquid crystal display device. Such an electronic apparatus can operate in the transmissive mode and the reflective mode. Therefore, it is possible to provide an electronic apparatus having a display in which images can be displayed with a wide viewing angle in both of the display modes.

[0025] In addition, a method of manufacturing the liquid crystal display device according to the invention can include a convex portion forming step of coating a substrate with a photosensitive resin, and exposing and developing the photosensitive resin through a mask. The thickness of the photosensitive resin with which the substrate is coated varies in every predetermined region. According to such a manufacturing method, it is possible to appropriately manufacture the liquid crystal display device according to the invention. In other words, in the above-mentioned liquid crystal display device, the convex portions provided in both of the transmissive display region and the reflective display region are made of the photosensitive resin and the thickness of the photosensitive resin varies in every predetermined region. Therefore, it is possible to form convex portions having different heights in the respective regions. To be specific, the thickness of the photosensitive resin is larger in the region where the transmissive display region is formed and the thickness of the photosensitive resin layer is relatively small in the region where the reflective display region is formed. To be more specific, the manufacturing method may further

include a substrate fabricating step of forming a reflective film of a predetermined pattern on a base. In the region where the reflective film is formed, the thickness of the photosensitive resin may be relatively small.

[0026] According to another aspect, the method of manufacturing the liquid crystal display device according to the invention can include a convex portion forming step of coating a substrate with a photosensitive resin, and exposing and developing the photosensitive resin through a mask. The amount of exposure of the photosensitive resin varies in every predetermined region. According to such a manufacturing method, it is possible to appropriately manufacture the liquid crystal display device according to the invention. That is, in the above-mentioned liquid crystal display device, the convex portions provided in both of the transmissive display region and the reflective display region are made of the photosensitive resin and the amount of exposure of the photosensitive resin varies in every predetermined region. Therefore, it is possible to form convex portions having different heights in the respective regions. To be specific, when a negative photosensitive resin is used, the amount of exposure increases in the region that forms the transmissive display region and decreases in the region that forms the reflective display region. To be more specific, the manufacturing method may further include a substrate fabricating step of forming the reflective film of the predetermined pattern on the base material. The amount of exposure of the photosensitive resin may vary in each of the region in which the reflective film is formed and the region in which the reflective film is not formed.

[0027] The manufacturing method according to the invention may further include a step of forming the color filter layer including the plurality of colored layers corresponding to the three primary colors of light on the base material. In the color filter layer forming step, the plurality of colored layers may overlap each other in the inter-dot region in plan view. On the other hand, the manufacturing method may further include a step of forming an insulating layer so as to cover the colored layers that overlap each other and forming second convex portions protruding from the insulating layer, above the insulating layer. The convex portions and the second convex portions can be formed in the same step. In this case, since the second convex portions for controlling the thickness of the liquid crystal layer is formed in the same step as the convex portions (first convex portions) for controlling the alignment of the liquid crystal molecules formed in the transmissive display region and the reflective display region, it is possible to improve the manufacturing efficiency and to easily and correctly make the height of the second convex portions almost equal to the height of the first convex portions. Also, the insulating layer is for forming the liquid crystal layer thickness-adjusting layer according to the present invention.

[0028] According to the method of manufacturing the liquid crystal display device of the invention, a liquid crystal layer is interposed between a pair of substrates and a transmissive display region and a reflective display region are provided in one dot region. The method can include a first substrate forming step of forming a reflective film of a predetermined pattern on a base material and forming an insulating layer on the region in which the reflective film is formed, a convex portion forming step of forming convex portions on at least one of the first substrate and a second

substrate different from the first substrate, and an attaching step of attaching the first substrate to the second substrate, with the liquid crystal layer therebetween whose dielectric anisotropy, indicating that the liquid crystal is vertically aligned in an initial state, is negative. The convex portion forming step can include the steps of coating the first substrate and/or the second substrate with the photosensitive resin, and exposing and developing the photosensitive resin through a mask. The thickness of the photosensitive resin with which the substrate is coated in the region where the reflective film is formed is different from the thickness of the photosensitive resin in the region in which the reflective film is not formed. According to such a manufacturing method, it is possible to provide a transflective liquid crystal display device having a multi-gap structure and employing liquid crystal of a vertical alignment mode, in which it is possible to appropriately control the directions in which the liquid crystal molecules are aligned in both of the transmissive display region and the reflective display region.

[0029] According to another aspect, in the method of manufacturing the liquid crystal display device of the invention, a liquid crystal layer is interposed between a pair of substrates and a transmissive display region and a reflective display region are provided in one dot region. The method can include a first substrate forming step of forming a reflective film of a predetermined pattern on a base material and forming an insulating layer on the region in which the reflective film is formed, a convex portion forming step of forming convex portions on at least one of the first substrate and a second substrate different from the first substrate, and an attaching step of attaching the first substrate to the second substrate, with a liquid crystal layer therebetween whose dielectric anisotropy, indicating that liquid crystal is vertically aligned in an initial state, is negative. The convex portion forming step includes the steps of coating the first substrate and/or the second substrate with the photosensitive resin, and exposing and developing the photosensitive resin through a mask. The amount of exposure of the photosensitive resin in the region in which the reflective film is formed is different from the amount of exposure of the photosensitive resin in the region in which the reflective film is not formed. According to such a manufacturing method, it is possible to provide a transflective liquid crystal display device having a multi-gap structure and employing liquid crystal of a vertical alignment mode, in which it is possible to appropriately control the directions in which the liquid crystal molecules are aligned in both of the transmissive display region and the reflective display region.

BRIEF DESCRIPTION OF THE DRAWINGS

[0030] The invention will be described with reference to the accompanying drawings, wherein like numerals reference like elements, and wherein:

[0031] **FIG. 1** is an equivalent circuit diagram of a liquid crystal display device according to a first embodiment;

[0032] **FIG. 2** is a plan view illustrating the structure of the electrodes of the liquid crystal display device of **FIG. 1**;

[0033] **FIG. 3** is a plan schematic view and a sectional schematic view illustrating the enlarged main portion of the liquid crystal display device of **FIG. 1**;

[0034] **FIG. 4** is a plan schematic view and a sectional schematic view illustrating the enlarged main portion of a liquid crystal display device according to a second embodiment;

[0035] **FIG. 5** is a plan schematic view and a sectional schematic view illustrating the enlarged main portion of a liquid crystal display device according to a third embodiment;

[0036] **FIG. 6** is a plan schematic view and a sectional schematic view illustrating the enlarged main portion of a liquid crystal display device according to a fourth embodiment; and

[0037] **FIG. 7** is a perspective view illustrating an example of an electronic apparatus according to the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0038] The embodiments of the invention will now be further described with reference to the drawings. In the drawings, it should be understood that the thickness of individual layers and regions are exaggerated for clarity.

[0039] A liquid crystal display device according to the embodiment of the invention is an active matrix liquid crystal display device using a thin film diode (TFD) as a switching element, in particular, a transflective liquid crystal display device capable of performing reflective and transmissive display.

[0040] **FIG. 1** is an equivalent circuit diagram of a liquid crystal display device **100** according to the present embodiment. The liquid crystal display device **100** includes a scanning signal driving circuit **110** and a data signal driving circuit **120**. Signal lines, that is, a plurality of scanning lines **13** and a plurality of data lines **9** that cross the scanning lines **13** are provided in the liquid crystal display device **100**. The scanning lines **13** are driven by the scanning signal driving circuit **110**. The data lines **9** are driven by the data signal driving circuit **120**. In the respective pixel regions **150**, TFD elements **40** are serially connected to liquid crystal display components (liquid crystal layers) **160** between the scanning lines **13** and the data lines **9**. On the other hand, in **FIG. 1**, the TFD elements **40** are connected to the scanning lines **13** and the liquid crystal display elements **160** are connected to the data lines **9**. However, on the contrary, the TFD elements **40** may be connected to the data lines **9** and the liquid crystal display components **160** may be connected to the scanning lines **13**.

[0041] Hereinafter, with reference to **FIG. 2**, the planar structure of the electrodes included in the liquid crystal display device according to the embodiment will now be described. As illustrated in **FIG. 2**, in the liquid crystal display device according to the embodiment, in plan view where the TFD elements **40** are connected to the scanning lines **13**, square pixel electrodes **31** are provided in a matrix and the rectangular common electrodes **9** (in a matrix) are provided to face the pixel electrodes **31** in a direction vertical to the plane of the drawing. The common electrodes **9** are composed of the data lines and cross the scanning lines **13** in strips. According to the embodiment, each region in which each of the pixel electrodes **31** is formed constitutes

one dot region, and images can be displayed in each of the dot regions arranged in a matrix.

[0042] Here, the TFD elements 40 are switching elements for connecting the scanning lines 13 to the pixel electrodes 31. The TFD elements 40 have an MIM structure in which a first conductive film using Ta as a main component, an insulating film formed on the surface of the first conductive film and using Ta_2O_3 as a main component, and a second conductive film formed on the surface of the insulating film and using Cr as a main component are provided. The first conductive films of the TFD elements 40 are connected to the scanning lines 13 so that the second conductive films are connected to the pixel electrodes 31.

[0043] Next, the pixel structure of the liquid crystal display device 100 according to the present embodiment will now be described with reference to FIG. 3. FIG. 3(a) is a schematic view illustrating the pixel structure of the liquid crystal display device 100, in particular, the planar structure of the pixel electrode 31. FIG. 3(b) is a schematic view taken along the line A-A' of FIG. 3(a). As illustrated in FIG. 2, the liquid crystal display device 100 according to the embodiment has the dot regions including the pixel electrodes 31 in the regions surrounded by the data lines 9 and the scanning lines 13. In, the dot regions, as illustrated in FIG. 3(a), a colored layer of one of three primary colors is arranged corresponding to one dot region. The three dot regions D1, D2, and D3 form a pixel including colored layers 22B (blue), 22G (green), and 22R (red).

[0044] On the other hand, as illustrated in FIG. 3(b), in the liquid crystal display device 100 according to the embodiment, liquid crystal whose molecules are vertically aligned in an initial state, that is, a liquid crystal layer 50 made of a liquid crystal material whose dielectric anisotropy is negative, is interposed between an upper substrate (an element substrate) 25 and a lower substrate (a counter substrate) 10 arranged to face the upper substrate.

[0045] The lower substrate 10 has a structure in which a reflecting film 20 made of a metal film having a high reflectance, such as aluminum or silver, is partially formed on the surface of a substrate main body 10A made of a light transmissive material, such as quartz or glass, with an insulating film 24 therebetween. Here, the region in which the reflecting film 20 is formed constitutes a reflective display region R. The region in which the reflecting film 20 is not formed, that is, the region inside an aperture 21 of the reflecting film 20, is a transmissive display region T. As mentioned above, the liquid crystal display device according to the embodiment is a vertical alignment liquid crystal display device including the vertical alignment liquid crystal layer 50 and is a transreflective liquid crystal display device capable of displaying images in a reflective mode and in a transmissive mode.

[0046] The insulating film 24 formed on the substrate main body 10A has a concavo-convex portion 24a on the surface thereof. The surface of the reflecting film 20 also has a concavo-convex portion due to the concavo-convex portion 24a.

[0047] Since reflected light is scattered due to such a concavo-convex portion, it is possible to prevent the reflected light from being incident from the outside and to thus display images with a wide viewing angle.

[0048] Also, the color filter 22 (the red colored layer 22R in FIG. 3(b)) extending over the reflective display region R and the transmissive display region T is provided on the reflecting film 20 in the reflective display region R and on the substrate main body 10A positioned in the transmissive display region T. Here, the edge of the colored layer 22R is surrounded by a black matrix BM composed of chromium or the like. The boundaries of the respective dot regions D1, D2, and D3 are formed by the black matrix BM (refer to FIG. 3(a)).

[0049] Furthermore, an insulating film 26 is formed on the color filter 22 so as to correspond to the reflective display region R. In other words, the insulating film 26 is selectively formed above the reflecting film 20, with the color filter 22 therebetween. The thickness of the liquid crystal layer 50 in the reflective display region R is different from the thickness of the liquid crystal layer 50 in the transmissive display region T due to the formation of the insulating film 26. The insulating film 26 is made of an organic film such as an acryl resin of a thickness of 0.5 to 2.5 μm and has a tilted surface so that the thickness thereof can continuously change around the boundary between the reflective display region R and the transmissive display region T. The thickness of the liquid crystal layer 50 in a portion where the insulating film 26 does not exist is about 1 to 5 μm . The thickness of the liquid crystal layer 50 in the reflective display region R is about half of the thickness of the liquid crystal layer 50 in the transmissive display region T.

[0050] As mentioned above, the insulating film 26 functions as a liquid crystal layer thickness-adjusting layer (a liquid crystal layer thickness-controlling layer) that makes the thickness of the liquid crystal layer 50 in the reflective display region R different from the thickness of the liquid crystal layer in the transmissive display region T. According to the present embodiment, since the edge of the flat surface on the insulating film 26 almost coincides with the edge of the reflecting film 20 (the reflective display region), a part or all of the tilted region of the insulating film 26 is included in the transmissive display region T.

[0051] A common electrode 9 made of indium tin oxide (ITO) is formed on the surface of the lower substrate 10 including the surface of the insulating film 26. An alignment film 27 made of polyimide is formed on the common electrode 9. The alignment film 27 functions as a vertical alignment film for aligning the liquid crystal molecules in a vertical direction with respect to the surface thereof. An alignment process such as rubbing is not performed. On the other hand, in FIG. 3, the common electrode 9 is in strips so as to extend in a vertical direction with respect to the plane of the drawing and is composed of common electrodes in the respective dot regions formed in parallel in a vertical direction with respect to the plane of the drawing. Furthermore, according to the embodiment, the reflecting film 20 and the common electrode 9 are separately provided and stacked. However, in the reflective display region R, a reflecting film made of a metal film may be used as a part of the common electrode.

[0052] Next, in the upper substrate 25, the pixel electrode 31 in a matrix, which is made of a transparent conductive film, such as ITO, and an alignment film 33, which is made of polyimide and on which the vertical alignment process is performed like on the lower substrate 10, are formed on a

substrate main body **25A** made of a light transmissive material, such as glass or quartz (on the liquid crystal layer of the substrate main body **25A**). Also, in the pixel electrode **31**, slits **32** obtained by partially cutting the common electrode are formed.

[0053] A retardation plate **18** and a polarizer **19** are formed on the external surface (opposite to the surface on which the liquid crystal layer **50** is provided) of the lower substrate **10**. A retardation plate **16** and a polarizer **17** are formed on the external surface of the upper substrate **25**. Circular polarized light can be incident on the internal surface of the substrate (the liquid crystal layer **50**). The retardation plate **18** and the polarizer **19**, and the retardation plate **16** and the polarizer **17** constitute circular polarizers, respectively. The polarizer **17**(**19**) transmits only linearly polarized light having a polarization axis in a predetermined direction. A $\lambda/4$ retardation plate can be used as the retardation plate **16**(**18**). A backlight **15** that is a light source for the transmissive display is provided outside the polarizer **19** formed on the lower substrate **10**.

[0054] In the liquid crystal display device **100** according to the embodiment, in order to control the alignment of the liquid crystal molecules of the liquid crystal layer **50**, that is, as means for controlling the directions in which the liquid crystal molecules that are vertically aligned in an initial state fall when a voltage is applied between electrodes, protrusions made of a dielectric material are formed on the internal surface (the liquid crystal layer) of the electrodes. In FIG. 3, the protrusions **28** and **29** are formed on the internal surface (the liquid crystal layer) of the common electrode **9** formed in the lower substrate **10** in both the transmissive display region **T** and the reflective display region **R**, respectively.

[0055] The respective protrusions **28** and **29** are cone-shaped or polypyramid-shaped so as to protrude from the internal surface of the substrate (the main surface of the electrode) to the inside of the liquid crystal layer **50**. The height **L2** of the protrusions **28** formed in the transmissive display region **T** is (for example, 1.5 to 2 times) larger than the height **L1** of the protrusions **29** formed in the reflective display region **R**. To be specific, $L2=1.5\mu m$ and $L1=1.0\mu m$. The height of the protrusions **28** is about 1.5 times larger than the height of the protrusions **29**. Also, the protrusions **28** and **29** include a surface (including a slowly curved shape) tilted at a predetermined angle with respect to the internal surface of the substrate (the main surface of the electrode).

[0056] On the other hand, in the pixel electrode **31** formed on the internal surface of the upper substrate **25**, the slits **32** obtained by partially cutting the common electrode **9** are formed. A distorted electric field is generated between the respective electrodes **9** and **31** by providing the slits **32**. The directions in which the liquid crystal molecules vertically aligned in an initial state fall when a voltage is applied are controlled by the distorted electric field. Also, as illustrated in FIG. 3(a), the slits **32** formed in the pixel electrode **31** surround the protrusions **28** and **29** formed in the common electrode **9**. As a result, it is possible to radically control the directions in which the liquid crystal molecules (LC) fall along the periphery of the protrusions **28** and **29**.

[0057] According to the liquid crystal display device **100** having the above structure, it is possible to obtain the following effects. In other words, in general, when a voltage

is applied to the liquid crystal molecules having negative dielectric anisotropy, which are aligned on a vertical alignment film on which a rubbing process is not performed, since the directions in which the liquid crystal molecules fall are not controlled, the liquid crystal molecules fall in random directions to thus cause inferior alignment. However, according to the present embodiment, since the protrusions **28** and **29** are formed on the internal surface of the common electrode **9** and the slits **32** are formed in the pixel electrode **31** so as to surround the protrusions **28** and **29** in plan view, the alignment of the liquid crystal molecules is controlled by the tilted surfaces of the protrusions **28** and **29** and/or by the distorted electric field caused by the slits **32**. Therefore, the directions in which the liquid crystal molecules vertically aligned at an initial stage fall are controlled by applying a voltage. As a result, it is possible to prevent the generation of disclinations caused by the inferior alignment of the liquid crystal molecules and to thus obtain high quality display in which afterimages caused by the generation of the disclinations or spots observed in the oblique direction are rarely generated.

[0058] In addition, in the liquid crystal display device **100** according to the embodiment, since it is possible to reduce the thickness of the liquid crystal layer **50** in the reflective display region **R** to half of the thickness of the liquid crystal layer **50** in the transmissive display region **T** by forming the insulating film **26** in the reflective display region **R**, it is possible to make the birefringence retardation that contributes to the reflective display almost equal to the birefringence retardation that contributes to the transmissive display, and to thus improve the contrast.

[0059] In the liquid crystal display device **100** in which the thickness of the liquid crystal layer in the transmissive display region **T** is larger than the thickness of the liquid crystal layer in the reflective display region **R**, it is possible to control the alignment of the liquid crystal molecules in both of the transmissive display region **T** and the reflective display region **R** by making the height **L2** of the protrusions **28** formed in the transmissive display region **T** larger than the height of the protrusions **28** formed in the reflective display region **R**. Therefore, it is possible to prevent the generation of the inferiority in display such as the afterimages and the spots in both of the transmissive mode and the reflective mode and to thus display images a wide viewing angle.

[0060] In other words, in the liquid crystal display device in which the thickness of the liquid crystal layer in the transmissive display region is larger than the thickness of the liquid crystal layer in the reflective display region, it is not possible to control the alignment of the liquid crystal molecules in any one region only by providing the protrusions in both of the transmissive display region and the reflective display region. That is, since the thickness of the liquid crystal layer in the transmissive display region is different from the thickness of the liquid crystal layer in the reflective display region, the power of aligning the liquid crystal molecules in the transmissive display region where the thickness of the liquid crystal layer is larger may deteriorate than that in the reflective display region only by forming the convex portions having the same height in the respective regions. However, according to the present embodiment, it is possible to control the alignment of the liquid crystal

molecules in the respective regions by making the height L2 about 1.5 μm and the height L1 about 1.0 μm .

[0061] Next, one manufacturing process of the liquid crystal display device 100 according to the first embodiment will now be described with reference to **FIG. 3(b)**. The process of manufacturing the liquid crystal display device 100 includes a process of manufacturing a lower substrate 10, a process of manufacturing an upper substrate 25, and a process of attaching the lower substrate 10 to the upper substrate 25, with a liquid crystal material therebetween. The respective processes will now be described in detail.

[0062] First, an insulating film 24 made of an acryl resin can be formed on a base material corresponding to the substrate main body 10A in a predetermined pattern (in a region corresponding to the reflective display region R). A concavo-convex portion 24a is formed on the surface thereof by a photolithography process using a photomask, a treatment with hydrofluoric acid, or an embossing process. Next, a reflective film 20 mainly made of a metal material, such as A1, is formed on the insulating film 24. A concavo-convex portion is formed on the surface of the reflective film 20 in the shape of the concavo-convex portion 24a of the insulating film 24. Subsequently, a color filter 22 including colored layer of R, G, and B colors is formed on the almost entire surface of the substrate main body 10A having the insulating film 24 and the reflective film 20.

[0063] After forming the color filter 22, an insulating film 26 that is a liquid crystal layer thickness-adjusting layer mainly made of the acryl resin is selectively formed so as to cover the color filter 22 in the region where the reflective film 20 is formed. Then, a transparent electrode 9 in strips mainly made of ITO is formed on the substrate main body 10A having the insulating film 24, the reflective film 20, the color filter 22, and the insulating film 26 by a sputtering method or a deposition method. Also, a pattern in strips may be formed by mask deposition or etching.

[0064] Subsequently, the protrusions 29 and the protrusions 28 made of a dielectric material are formed on the transparent electrode 9 formed on the substrate main body 10A in both of the region where the reflective film 20 is formed and the region where the reflective film 20 is not formed. Here, the height of the protrusions 28 that protrude from the surface of the transparent electrode 9 is different from the height of the protrusions 29 that protrude from the surface of the transparent electrode 9. According to the embodiment, for example, the height L2 of the protrusions 28 is 1.5 times larger than the height L1 of the protrusions 29.

[0065] To be specific, after forming a photosensitive resin hardened by irradiating UV rays on the transparent electrode 9 formed on the substrate main body 10A to be thicker in the region where the reflective film 20 is formed than in the region where the reflective film 20 is not formed, the photosensitive resin is exposed and developed through a mask and the resultant is processed to cones. Therefore, it is possible to form the protrusions 29 that are lower in the region where the reflective film 20 is formed and to form the protrusions 28 that are higher in the region where the reflective film 20 is not formed. Also, according to a method of providing the tilted surfaces illustrated in **FIG. 3(b)** in the protrusions 28 and 29, that is, a method of processing the resultant to the cones, for example, it is possible to process

the convex portions obtained after performing exposure and development by melting the same.

[0066] It is possible to make the heights of the protrusions 28 and 29 different from each other by coating the transparent electrode 9 formed on the substrate main body 10A with a photosensitive resin hardened by irradiating the UV rays to a uniform thickness and controlling the amount of exposure when the photosensitive resin is exposed through the mask. That is, when the photosensitive resin hardened by irradiation the UV rays is used, it is possible to make the height of the protrusions 29 formed in the region where the reflective film 20 is formed smaller by reducing the amount of exposure in the region where the reflective film 20 is formed and increasing the amount of exposure in the region where the reflective film 20 is not formed.

[0067] An alignment film 27 of vertical alignment made of polyimide is formed on the almost entire surface of the transparent electrode 9 including the protrusions 28 and 29 formed by the above-mentioned method. Also, an alignment process such as rubbing is not performed on the alignment film 27.

[0068] On the other hand, a retardation film 18 and a polarization film 19 made of a 1/4 wavelength plate are formed on the surface opposite to the surface on which the transparent electrode 9 of the substrate main body 10A is formed to thus obtain the lower substrate 10.

[0069] First, a transparent electrode (pixel electrode) 31 in a matrix, which is mainly made of the ITO, is formed on a base material corresponding to the substrate main body 25A by a sputtering method or a deposition method.

[0070] Also, a pattern in a matrix may be formed by the mask deposition or the etching. The slits 32 are formed at the same time of forming the pattern in a matrix. Subsequently, an alignment film 33 of vertical alignment made of polyimide is formed on the almost entire surface of the transparent electrode 31 formed on the substrate main body 25A. Also, the alignment process such as rubbing is not performed on the alignment film 33.

[0071] On the other hand, a retardation plate 16 and a polarization plate 17 made of the 1/4 wavelength plate are formed on the surface opposite to the surface on which the transparent electrode 31 of the substrate main body 25A is formed to thus obtain the upper substrate 25.

[0072] The upper substrate 25 and the lower substrate 10 obtained by the above method are attached to each other under vacuum through a sealing material made of a UV rays hardening resin, in which a liquid crystal implanting hole is formed. A liquid crystal material is implanted into the attached substrates from the liquid crystal implanting hole by a vacuum implanting method. After implanting the liquid crystal material, the liquid crystal implanting hole is sealed by the sealing material to thus obtain the liquid crystal display device 100 according to the embodiment. Also, according to the embodiment, a liquid crystal material whose dielectric anisotropy is negative is used as the liquid crystal material.

[0073] A liquid crystal display device according to a second embodiment will now be described with reference to the drawings. **FIG. 4** is a schematic view illustrating the planar structure (a) and the sectional structure (b) of the

liquid crystal display device **200** according to the second embodiment corresponding to **FIG. 3** according to the first embodiment. The structure of the liquid crystal display device **200** according to the second embodiment is almost identical with the structure of the liquid crystal display device **100** illustrated in **FIG. 3** excluding that the structures of the color filters vary. Therefore, description of the same members denoted by the reference numerals of **FIG. 3** will be omitted.

[0074] In the liquid crystal display device **200** according to the second embodiment, in an active matrix transreflective liquid crystal display device using a TFD as a switching element, liquid crystal whose molecules are vertically aligned in an initial state, that is, a liquid crystal layer **50** made of a liquid crystal material whose dielectric anisotropy is negative, is interposed between an upper substrate (an element substrate) **25** and a lower substrate (a counter substrate) **10** arranged to face the upper substrate.

[0075] In the lower substrate **10**, the reflective film **20** made of a metal film having a high reflectance ratio, such as aluminum and silver, is selectively formed on the surface of the substrate main body **10A** made of a light transmissive material such as quartz and glass in a predetermined pattern, to be specific, in the reflective display region **R**. Also, like in the first embodiment, it is possible to form a concavo-convex portion through the insulating film **24**.

[0076] The color filter **22** (**22R**, **22G**, and **22B**) extending over the reflective display region **R** and the transmissive display region **T** is provided on the reflecting film **20** selectively formed in the reflective display region **R** and on the substrate main body **10A** positioned in the transmissive display region **T**. The color filter **22** includes the colored layers **22R**, **22G**, and **22B** of the **R**, **G**, and **B** colors. The respective colored layers **22R**, **22G**, and **22B** form the respective dot regions **D1**, **D2**, and **D3** (refer to **FIG. 4(a)**).

[0077] According to the embodiment, the black matrix **BM** formed in the boundaries of the respective dot regions **D1**, **D2**, and **D3** is not formed of metal chrome that is generally used in a conventional art but is formed of a substance obtained by stacking the respective colored layers **22R**, **22G**, and **22B**. To be specific, in the inter-dot region adjacent to the reflective display region **R**, the respective colored layers **22R**, **22G**, and **22B** overlap in plan view and black is displayed by the stacked substance. As a result of stacking the respective colored layers, in the inter-dot region, the thickness of the color filter **22** is determined by the amount the respective colored layers are stacked.

[0078] Furthermore, the insulating film **26** that is the liquid crystal layer thickness-adjusting layer is formed on the color filter **22** in the position corresponding to the reflective display region **R**. The common electrode **9** made of the ITO is formed on the surface of the lower substrate **10** including the surface of the insulating film **26**. The protrusions **28**, **29a**, and **29b** are formed on the common electrode **9**. Also, the protrusions **28** are provided in the transmissive display region **T**. The protrusions **29b** are provided in the reflective display region **R**. On the other hand, the protrusions **29a** are provided in the inter-dot region.

[0079] As mentioned above, in the region where the respective colored layers **22R**, **22G**, and **22B** of the color filter **22** overlap each other, the insulating film **26** protrudes

by the amount the colored layers are stacked. Furthermore, the protrusions **29a** that protrude to the liquid crystal layer **50** are formed in the portion where the insulating film **26** protrudes. The protrusions **29a** are made of the same material as the protrusions **28** formed in the transmissive display region **T** and the protrusions **29b** formed in the reflective display region **R** and have the height almost equal to the height of the protrusions **29b**.

[0080] Next, in the upper substrate **25**, the pixel electrode **31** in a matrix, which is made of a transparent conductive film, such as ITO, and an alignment film **33**, which is made of polyimide and on which the vertical alignment process is performed like on the lower substrate **10**, are formed on a substrate main body **25A** made of a light transmissive material such as glass or quartz (on the liquid crystal layer of the substrate main body **25A**). Also, like in the first embodiment, the slits **32** formed by partially cutting the pixel electrode **31** are formed in the pixel electrode **31**.

[0081] In the liquid crystal display device **200** according to the present embodiment, in order to control the alignment of the liquid crystal molecules of the liquid crystal layer **50**, that is, as a device for controlling the directions in which the liquid crystal molecules that are vertically aligned in an initial state fall when a voltage is applied between electrodes, protrusions made of a dielectric material are formed on the internal surface (the liquid crystal layer) of the electrodes. In the example of **FIG. 4**, the protrusions **28** and **29b** are formed on the internal surface (on the side of the liquid crystal layer) of the common electrode **9** formed in the lower substrate **10** in both of the transmissive display region **T** and the reflective display region **R**.

[0082] The respective protrusions **28** and **29b** are generally cone-shaped or polypyramid-shaped so as to protrude from the internal surface of the substrate (the main surface of the electrode) to the inside of the liquid crystal layer **50**. The height **L2** of the protrusions **28** formed in the transmissive display region **T** is (for example, about 1.5 to 2 times) larger than the height **L1** of the protrusions **29** formed in the reflective display region **R**. To be specific, **L2=2.0 μm** and **L1=1.0 μm**. In this case, the height of the protrusions **28** is about 2 times larger than the height of the protrusions **29**. Also, the protrusions **28** and **29** include at least a surface (including a slowly curved shape) tilted at a predetermined angle with respect to the internal surface of the substrate (the main surface of the electrode) to control the direction in which the liquid crystal molecules(LC) fall along the tilted surface.

[0083] On the other hand, in the pixel electrode **31** formed on the internal surface of the upper substrate **25**, the slits **32** obtained by partially cutting the pixel electrodes are formed. A distorted electric field is generated between the respective electrodes **9** and **31** by providing the slits **32**. The directions in which the liquid crystal molecules vertically aligned in an initial state fall when a voltage is applied are controlled by the distorted electric field. Also, as illustrated in **FIG. 4(a)**, the slits **32** formed in the pixel electrode **31** are formed to surround the protrusions **28** and **29** formed in the common electrode **9**. As a result, it is possible to radically control the directions in which the liquid crystal molecules (LC) fall along the periphery of the protrusions **28** and **29**.

[0084] Furthermore, in the liquid crystal display device **200** according to the embodiment, on the side of the liquid

crystal layer **50** of the region formed by overlapping the colored layers **22R**, **22G**, and **22B**, the protrusions **29a** that protrude from the insulating layer **26** that is the liquid crystal layer thickness-adjusting layer to the liquid crystal layer **50** are formed. Therefore, the protrusions **29a** are used as the device (instead of the spacers) for controlling the thickness of the liquid crystal layer **50**. That is, the region formed by overlapping the colored layers **22R**, **22G**, and **22B** protrudes above the other regions by the amount the colored layers overlap. However, when the insulating layer **26** is formed so as to cover the overlapped colored layers and the protrusions **29a** are further formed, the protrusions **29a** protrude outermost inside the substrate. As a result, it is possible to use the protrusions **29a** as the means for controlling the thickness of the liquid crystal layer. Therefore, it is possible to maintain the thickness of the liquid crystal layer to be uniform in the substrate without additionally providing the spacers.

[0085] Also, the protrusions **29a** are formed in the same process as the protrusions **28** and **29b** formed in the transmissive display region **T** and the reflective display region **R** in order to improve the manufacturing efficiency and have the height almost equal to the height of the protrusions **29b**. Therefore, it is possible to use the protrusions **29a** as the device for controlling the thickness of the liquid crystal layer and to prevent the protrusions **28** and **29b** formed in the transmissive display region **T** and the reflective display region **R** from contacting the opposite substrate **25**. Therefore, it is possible to control the alignment of the liquid crystal molecules.

[0086] According to the liquid crystal display device **200** having the above structure, it is possible to obtain several effects that the liquid crystal display device **100** according to the first embodiment has and to form the black matrix (BM) without separately using chromium. Therefore, it is possible to improve the manufacturing efficiency, to reduce manufacturing costs, and to prevent environments from being damaged due to the abandonment of the chromium. Also, since it is possible to control the thickness of the liquid crystal layer without additionally using the spacers, it is possible to improve the manufacturing efficiency and to reduce the manufacturing costs. Furthermore, it is possible to correctly control the alignment of the liquid crystal molecules by the protrusions **28** and **29b** and to thus improve the visual characteristics of display.

[0087] Next, one manufacturing process of the liquid crystal display device **200** according to the second embodiment will be described with reference to FIG. 4(b). The process of manufacturing the liquid crystal display device **200** includes a process of manufacturing the lower substrate **10**, a process of manufacturing the upper substrate **25**, and a process of attaching the lower substrate **10** to the upper substrate **25** with the liquid crystal material interposed between the lower substrate **10** and the upper substrate **25**. The respective processes will now be described in detail.

[0088] First, the reflective film **20** mainly made of the metal material, such as A1, is formed on the base material corresponding to the substrate main body **10A** in a predetermined pattern (in the region corresponding to the reflective display region **R**). Subsequently, the color filter **22** including the respective colored layers of the R, G, and B colors is formed on the almost entire surface of the substrate main body **10A** having the reflective film **20**. Also, in the

process of forming the color filter **22**, the respective colored layers **22R**, **22G**, and **22B** overlap each other in the inter-dot region in plan view. Such a pattern can be formed using the photolithography method. Here, in the color filter **22**, in the region where the respective colored layers **22R**, **22G**, and **22B** overlap each other, the convex portions obtained by stacking the colored layers are formed.

[0089] After forming the color filter **22**, the insulating film **26** that is the liquid crystal thickness controlling layer mainly made of the acryl resin is selectively formed so as to cover the color filter **22** in the region where the reflective film **20** is formed. In this case, the same convex portions are formed in the insulating film **26** in the inter-dot region in accordance with the above-mentioned convex portions of the color filter **22**.

[0090] Then, on the substrate main body **10A** having the reflective film **20**, the color filter **22**, and the insulating film **26**, the transparent electrode **9** in strips is mainly made of the ITO by the deposition method. Also, the pattern in strips may be formed by the mask deposition or the etching.

[0091] Subsequently, on the transparent electrode **9** formed on the substrate main body **10A**, the protrusions **29b**, the protrusions **28**, and the protrusions **29a** formed of the dielectric material can be formed in the region where the reflective film **20** is formed, in the region where the reflective film **20** is not formed, and in the inter-dot region, respectively. Also, in particular, the protrusions **29a** are formed in the convex portions of the insulating film **26**. Here, the heights of the protrusions **28** and **29b** that protrude from the surface of the transparent electrode **9** are different from each other. According to the embodiment, for example, the height **L2** of the protrusions **28** is 2 times larger than the height **L1** of the protrusions **29b**. The method of making the heights different is the same as that of the first embodiment. On the other hand, the protrusions **29a** formed in the inter-dot region are formed in the same height controlling process as the protrusions **29b** in order to make the protrusions **29a** have the height almost equal to the height of the protrusions **29b** formed in the reflective display region **R**.

[0092] On the almost entire surface of the transparent electrode **9** including the protrusions **28**, **29a**, and **29b** formed by the above method, the alignment film **27** of vertical alignment, which is made of polyimide, is formed. Also, the alignment process such as rubbing is not performed on the alignment film **27**.

[0093] On the other hand, on the surface opposite to the surface on which the transparent electrode **9** of the substrate main body **10A** is formed, the retardation plate **18** and the polarization plate **19** made of the 1/4 wavelength plate are formed to thus obtain the lower substrate **10**.

[0094] First, the transparent electrode **31** in a matrix, which is mainly made of the ITO, is formed on a base material corresponding to the substrate main body **25A** by the sputtering method or the deposition method. Also, the pattern in a matrix may be formed by the mask deposition or the etching. The slits **32** are formed at the same time of forming the pattern in a matrix. Subsequently, the alignment film **33** of vertical alignment made of polyimide is formed on the almost entire surface of the transparent electrode **31** formed on the substrate main body **25A**. Also, the alignment process such as rubbing is not performed on the alignment film **33**.

[0095] On the other hand, the retardation plate **16** and the polarization plate **17** made of the 1/4 wavelength plate are formed on the surface opposite to the surface on which the transparent electrode **31** of the substrate main body **25A** is formed to thus obtain the upper substrate **25**.

[0096] The upper substrate **25** and the lower substrate **10** obtained by the above method are attached to each other under vacuum through the sealing material made of UV-hardening resin, in which the liquid crystal implanting hole is formed. The liquid crystal material is implanted into the attached substrates from the liquid crystal implanting hole by the vacuum implanting method. After implanting the liquid crystal material, the liquid crystal implanting hole is sealed by the sealing material to thus obtain the liquid crystal display device **200** according to the present embodiment. Also, according to the present embodiment, a liquid crystal material whose dielectric anisotropy is negative is used as the liquid crystal material.

[0097] A liquid crystal display device according to a third embodiment will now be described with reference to the drawings. FIG. 5 is a schematic view illustrating the planar structure (a) and the sectional structure (b) of the liquid crystal display device **300** according to the third embodiment corresponding to FIG. 4 according to the second embodiment. The structure of the liquid crystal display device **300** according to the third embodiment is almost identical with the structure of the liquid crystal display device **200** illustrated in FIG. 4 excluding that the color filter **22** is formed in the upper substrate **25**, as compared to the second embodiment. Therefore, description of the same members denoted by the reference numerals of FIG. 4 will be omitted.

[0098] According to the liquid crystal display device **300** according to the third embodiment, in an example of a transreflective liquid crystal display device in an active matrix using a thin film transistor (TFT) as a switching element, liquid crystal whose molecules are vertically aligned in an initial state, that is, a liquid crystal layer **50** made of a liquid crystal material whose dielectric anisotropy is negative, is interposed between a lower substrate (an element substrate) **10** and an upper substrate (a counter substrate) **25** arranged to face the upper substrate.

[0099] In the lower substrate **10**, the transreflective film **20** made of the metal film having the high reflectance ratio, such as aluminum and silver, is selectively formed on the surface of the substrate main body **10A** in a predetermined pattern, to be specific, in the reflective display region **R**. Furthermore, a transparent electrode **9a** of a predetermined pattern is formed in the region where the reflective film **20** is not formed, that is, in the transmissive display region **T**. The reflective film **20** and the transparent electrode **9a** make a pair to thus form a pixel electrode in a matrix. Also, slits **9b** and **20b** obtained by partially cutting the pixel electrode are formed in the pixel electrode so that the distorted electric field is generated in the slits **9b** and **20b**. Also, the alignment film **27** of vertical alignment is formed on the pixel electrode.

[0100] On the other hand, in the upper substrate **25**, the color filter **22** including the region in which the respective colored layers **22R**, **22G**, and **22B** overlap each other is formed on the surface of the substrate main body **25A**. The insulating film **26** that is the liquid crystal layer thickness-

adjusting layer and a common electrode **31** a formed over the entire surface are provided on the color filter **22**. Also, the protrusions **28**, **29b**, and **29a** are formed on the common electrode **31** a and in the transmissive display region, the reflective display region, and the inter-dot region, respectively. The structures of the protrusions **28**, **29a**, and **29b** are the same as those of the second embodiment.

[0101] As mentioned above, according to the present embodiment, in the inter-dot region of the color filter **22** among the pixel electrodes, the black matrix (BM) obtained by stacking the respective colored layers **22R**, **22G**, and **22B** is formed. To be specific, in the inter-dot region adjacent to the reflective display region **R**, the respective colored layers **22R**, **22G**, and **22B** overlap each other in plan view and black is displayed by the stacked substance. Also, as a result of stacking the respective colored layers, in the inter-dot region, the thickness of the color filter **22** is determined by the amount the colored layers are stacked.

[0102] As mentioned above, according to the liquid crystal display device **300** including the color filter **22** in which the black matrix is obtained by stacking the respective colored layers **22R**, **22G**, and **22B** in the upper substrate **25**, it is possible to obtain several effects that the liquid crystal display device **100** according to the first embodiment and the liquid crystal display device **200** according to the second embodiment have. Description of the method of manufacturing the liquid crystal display device according to the third embodiment will be omitted since it is almost the same as the method of manufacturing the liquid crystal display device according to the second embodiment excluding that the color filter **22** is formed in the upper substrate **25**.

[0103] A liquid crystal display device according to a fourth embodiment will now be described with reference to the drawings. FIG. 6 is a schematic view illustrating the planar structure (a) and the sectional structure (b) of the liquid crystal display device **400** according to the fourth embodiment corresponding to FIG. 4 according to the second embodiment. The structure of the liquid crystal display device **400** according to the fourth embodiment is almost identical with the structure of the liquid crystal display device **200** illustrated in FIG. 4 excluding that the formed protrusions **28** are formed in the upper substrate **25** in the transmissive display region **T**, as compared to the second embodiment. Therefore, description of the same members denoted by the reference numerals of FIG. 4 will be omitted.

[0104] As mentioned above, it is not necessary to form the protrusions **28** and **29b** for controlling the alignment of the liquid crystal molecules in the same substrate. Like in the embodiment, even when the protrusions are formed in the different substrates, it is possible to obtain the same effects as the effects that can be obtained when the protrusions are formed in the same substrate. Also, the protrusions **29a** for controlling the thickness of the liquid crystal layer may be provided in any one of the upper substrate and the lower substrate.

[0105] A detailed example of an electronic apparatus including the liquid crystal display device according to the embodiment of the invention will now be described.

[0106] FIG. 7 is a perspective view illustrating an example of a mobile telephone. In FIG. 7, reference numer-

als **1000** and **1001** denote a mobile telephone main body and a display portion using the liquid crystal display device, respectively. Since such an electronic apparatus includes a display portion using the liquid crystal display device according to the present embodiment, it is possible to realize an electronic apparatus having a liquid crystal display portion with high contrast and a wide viewing angle, which is not dependent on use environments.

[0107] While this invention has been particularly shown and described with reference to preferred embodiments thereof, it should be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the invention. For example, according to the above embodiments, the retardation plate is a single plate, however, may be a stacked substance obtained by stacking a 1/2 wavelength plate and a 1/4 wavelength plate. The stacked substance functions as a wideband circular polarizer and can make black display achromatic. Also, the shapes of the protrusions and the electrode slits formed in the present embodiments are not limited to the structures of the above embodiments. The protrusions and the electrode slits may have any shapes suitable for controlling the directions in which the vertically aligned liquid crystal molecules fall.

What is claimed is:

1. A liquid crystal display device in which a liquid crystal layer is interposed between a pair of substrates, and a transmissive display region and a reflective display region are provided in one dot region,

the liquid crystal layer being made of liquid crystal whose dielectric anisotropy, indicating that liquid crystal is vertically aligned in an initial state, is negative,

a liquid crystal layer thickness-adjusting layer that makes a thickness of the liquid crystal layer in the reflective display region smaller than a thickness of the liquid crystal layer in the transmissive display region being formed between at least one substrate of the pair of substrates and the liquid crystal layer,

convex portions that protrude from internal surfaces of the substrates to the inside of the liquid crystal layer being provided in the transmissive display region and the reflective display region, and

a height of the convex portions being larger in the transmissive display region than in the reflective display region.

2. The liquid crystal display device according to claim 1,

the convex portions being provided as an alignment regulating device that regulates an alignment of the liquid crystal and have surfaces inclined at a predetermined angle with respect to the surfaces of the substrate for interposing the liquid crystal layer therebetween.

3. The liquid crystal display device according to claim 1,

electrodes that drive the liquid crystal being provided on the liquid crystal layer sides of the pair of substrates, and

the convex portions being formed on at least one electrode of the electrodes facing the liquid crystal layer.

4. The liquid crystal display device according to claim 3, an alignment film that vertically aligns the liquid crystal being formed on the convex portions and the internal surface of the electrodes facing the liquid crystal layer.

5. The liquid crystal display device according to claim 1, circular polarizers that make circularly polarized light incident on the liquid crystal layer being provided on the sides of the pair of substrates opposite to the liquid crystal layer, respectively.

6. The liquid crystal display device according to claim 1, an upper substrate and a lower substrate being provided as the pair of substrates,

a backlight for transmissive display being provided on the side of the lower substrate opposite to the liquid crystal layer, and

a reflective layer selectively formed in the reflective display region being formed on the side of the lower substrate facing the liquid crystal layer.

7. The liquid crystal display device according to claim 1, a color filter layer being provided on the liquid crystal layer sides of at least one substrate of the pair of substrates,

the color filter layer having a plurality of colored layers, and

the plurality of colored layers overlapping each other in an inter-dot region in plan view.

8. The liquid crystal display device according to claim 7, the liquid crystal layer thickness-adjusting layer and second convex portions that protrude from the liquid crystal layer thickness-adjusting layer to the liquid crystal layer being formed on the side of the liquid crystal layer in the region where the colored layers overlap each other in plan view.

9. The liquid crystal display device according to claim 8, the second convex portions being made of a same material as the convex portions formed in the transmissive display region and the reflective display region.

10. The liquid crystal display device according to claim 8, a height of the second convex portions being almost equal to that of the convex portions formed in the transmissive display region and the reflective display region.

11. A method of manufacturing the liquid crystal display device according to claim 1, comprising a convex portion forming step of coating a substrate with a photosensitive resin, and exposing and developing the photosensitive resin through a mask,

a thickness of the photosensitive resin with which the substrate is coated varying in every predetermined region.

12. The method of manufacturing the liquid crystal display device according to claim 11, further comprising a substrate fabricating step of forming a reflective film of a predetermined pattern on a base material,

a thickness of the photosensitive resin layer being relatively small in the region where the reflective film is formed.

13. The method of manufacturing the liquid crystal display device according to claim 1, comprising a convex

portion forming step of coating a substrate with a photosensitive resin, and exposing and developing the photosensitive resin through a mask,

an amount of exposure of the photosensitive resin varies with each predetermined region.

14. The method of manufacturing the liquid crystal display device according to claim 13, further comprising a substrate fabricating step of forming a reflective film of a predetermined pattern on a base material,

the amount of exposure of the photosensitive resin in the region in which the reflective film is formed being different from an amount of exposure of the photosensitive resin in the region in which the reflective film is not formed.

15. The method of manufacturing the liquid crystal display device according to claim 11, further comprising a step of forming a color filter including a plurality of colored layers on a base material,

in the color filter layer forming step, the plurality of colored layers overlap each other in an inter-dot region in plan view; and

a step of forming an insulating layer so as to cover the colored layers that overlap each other and forming second convex portions protruding from the insulating layer, above the insulating layer,

the convex portions and the second convex portions being formed in the same step.

16. A method of manufacturing a liquid crystal display device in which a liquid crystal layer is interposed between a pair of substrates and a transmissive display region, and a reflective display region are provided in one dot region, the method comprising:

a first substrate forming step of forming a reflective film of a predetermined pattern on a base material and forming an insulating layer on the region in which the reflective film is formed;

a convex portion forming step of forming convex portions on at least one of the first substrate and a second substrate different from the first substrate; and

an attaching step of attaching the first substrate to the second substrate, with a liquid crystal layer therebetween whose dielectric anisotropy, indicating that liquid crystal is vertically aligned in an initial state, is negative,

the convex portion forming step including the steps of coating at least one of the first substrate and the second substrate with the photosensitive resin, and exposing and developing the photosensitive resin through a mask, and

a thickness of the photosensitive resin with which the substrate is coated in the region in which the reflective film is formed being different from a thickness of the photosensitive resin in the region in which the reflective film is not formed.

17. A method of manufacturing a liquid crystal display device in which a liquid crystal layer is interposed between a pair of substrates and a transmissive display region, and a reflective display region are provided in one dot region, the method comprising:

a first substrate forming step of forming a reflective film of a predetermined pattern on a base material and forming an insulating layer on the region in which the reflective film is formed;

a convex portion forming step of forming convex portions on at least one of the first substrate and a second substrate different from the first substrate; and

an attaching step of attaching the first substrate to the second substrate, with a liquid crystal layer therebetween whose dielectric anisotropy, indicating that liquid crystal is vertically aligned in an initial state, is negative,

the convex portion forming step including the steps of coating at least one of the first substrate and the second substrate with the photosensitive resin, and exposing and developing the photosensitive resin through a mask, and

an amount of exposure of the photosensitive resin in the region in which the reflective film is formed being different from the amount of exposure of the photosensitive resin in the region in which the reflective film is not formed.

18. An electronic apparatus, comprising the liquid crystal display device according to claim 1.

* * * * *

专利名称(译)	液晶显示装置，其制造方法以及电子设备		
公开(公告)号	<u>US20050001962A1</u>	公开(公告)日	2005-01-06
申请号	US10/846703	申请日	2004-05-17
[标]申请(专利权)人(译)	精工爱普生株式会社		
申请(专利权)人(译)	SEIKO EPSON CORPORATION		
当前申请(专利权)人(译)	SEIKO EPSON CORPORATION		
[标]发明人	MAEDA TSUYOSHI		
发明人	MAEDA, TSUYOSHI		
IPC分类号	G02F1/1333 G02F1/1335 G02F1/1337 G02F1/1362 G02F1/139		
CPC分类号	G02F1/133371 G02F1/133512 G02F1/133514 G02F1/133555 G02F2001/136222 G02F1/133707 G02F1/1393 G02F2001/133742 G02F2001/133776 G02F1/1337		
优先权	2003162353 2003-06-06 JP		
其他公开文献	US7139052		
外部链接	<u>Espacenet</u>	<u>USPTO</u>	

摘要(译)

本发明提供一种能够在透射显示和反射显示两者中显示广角图像的液晶显示装置。在液晶显示装置中，液晶层可以插入在一对基板之间，透射显示区域和反射显示区域可以设置在一个点区域中。液晶层由液晶制成，其介电常数各向异性表明液晶分子在初始阶段垂直取向是负的。用于使反射显示区域中的液晶层的厚度与透射显示区域中的液晶层的厚度不同的液晶层厚度控制层可以设置在基板和液晶层之间。在透射显示区域和反射显示区域中，还设置有从基板的内表面突出到液晶层内部的突起。因此，在透射显示区域中形成的凸起部分的高度大于在反射显示区域中形成的凸起部分的高度。

