



US 20050105021A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2005/0105021 A1**

Lee et al.


(43) **Pub. Date: May 19, 2005**(54) **REFLECTIVE LEQUID CRYSTAL DISPLAY
FOR DUAL DISPLAY**(30) **Foreign Application Priority Data**

Nov. 13, 2003 (TW)..... 92131761

(76) Inventors: **Seok-Lyul Lee**, Taoyuan Hsien (TW);
Teian-Sen Jen, Taoyuan Hsien (TW);
Ming-Tien Lin, Lujhou City (TW)**Publication Classification**(51) **Int. Cl.⁷** **G02F 1/1335**(52) **U.S. Cl.** **349/113**(57) **ABSTRACT**

A reflective liquid crystal display panel for dual display. The panel has a plurality of pixels and each pixel having first and second display regions. Each pixel includes a first substrate and a second substrate opposite thereto, wherein the first substrate includes a pixel driving device. A first reflective layer is formed overlying the first substrate in the first display region. A second reflective layer is formed overlying an interior of the second substrate in the second display region. A liquid crystal layer is interposed between the first substrate and the second substrate.

Correspondence Address:

**THOMAS, KAYDEN, HORSTEMEYER &
RISLEY, LLP****100 GALLERIA PARKWAY, NW****STE 1750****ATLANTA, GA 30339-5948 (US)**(21) Appl. No.: **10/885,435**(22) Filed: **Jul. 6, 2004**





FIG. 1A







FIG. 2






FIG. 4




FIG. 5

REFLECTIVE LEQUID CRYSTAL DISPLAY FOR DUAL DISPLAY

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates to a reflective type liquid crystal display (RLCD) panel, and more particularly, to an RLCD panel of a dual display for displaying data on the front and rear surfaces thereof.

[0003] 2. Description of the Related Art

[0004] High definition, multicolor displays, low power consumption, lower voltage requirements and light weight make liquid crystal displays (LCDs) a leading display device technology. LCDs, for example, have been used for several years as displays in, personal digital assistants (PDAs), portable computers, mobile phones, and the like.

[0005] Recently, a folding type mobile phone, taking advantage of the advances in fabrication techniques and the user desire to display data on the front and rear surfaces of the folding portion (or upper housing) thereof, has been developed. A conventional folding type mobile phone utilizes two individual LCDs whose rear surfaces are in contact with each other to achieve a dual-display.

[0006] However, since the conventional display device uses two individual displays, two sets of electrical equipment for driving the LCDs are required. Accordingly, the display device increases in size and weight, as does the fabrication cost.

SUMMARY OF THE INVENTION

[0007] The object of the present invention is to provide an RLCD panel for dual display.

[0008] Another object of the present invention is to provide an RLCD panel with a single liquid crystal layer.

[0009] In order to achieve these objects, the present invention provides a reflective liquid crystal display panel for dual display. The panel has a plurality of pixels each with first and second display regions, comprising a first substrate and a second substrate opposite thereto. A first transparent electrode is formed on the first substrate. A first reflective layer is formed overlying the first substrate in the first display region. A second transparent electrode is formed overlying the interior of the second substrate. A second reflective layer is formed on the second transparent electrode in the second display region. A liquid crystal layer is interposed between the first substrate and the second substrate.

[0010] In order to achieve these objects, the present invention also provides another reflective liquid crystal display panel for dual display. The panel has a plurality of pixels each with first and second display regions, comprising a first substrate and a second substrate opposite thereto. A first transparent electrode is formed on the first substrate. A first reflective layer is formed overlying the first substrate in the first display region. A second reflective layer is formed overlying the interior of the second substrate in the second display region. A color filter is formed on the second substrate and the second reflective layer. A second transparent electrode is formed on the color filter. A liquid crystal layer is interposed between the first substrate and the second substrate.

[0011] The present invention improves on the conventional technology in that each pixel of the dual-display RLCD panel has a first reflective layer formed on the first substrate in the first display region and a second reflective layer formed on the second substrate in the second display region. In addition, the first and second display regions (or reflective layers) are defined in each pixel so the front surface area of the display panel is the same as the rear surface area thereof. Thus, the RLCD structure with a single liquid crystal layer according to the invention can display data on both surfaces thereof, thereby reducing cost and volume and ameliorating the disadvantages of the conventional technology.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The present invention can be more fully understood by reading the subsequent detailed description in conjunction with the examples and references made to the accompanying drawings, wherein:

[0013] **FIG. 1A** is a top view of one pixel of a dual-display RLCD according to a first embodiment of the present invention;

[0014] **FIG. 1B** is a sectional view of the dual-display RLCD taken along line 1B-1B in **FIG. 1A**;

[0015] **FIG. 2** is a sectional view of the dual-display RLCD according to a modification of the first embodiment;

[0016] **FIG. 3** is a sectional view of a dual-display RLCD according to a second embodiment of the present invention;

[0017] **FIG. 4** is a sectional view of the dual-display RLCD according to a modification of the second embodiment; and

[0018] **FIG. 5** is a schematic view showing an exemplary application of the present invention in a folding type mobile phone having a dual-display LCD.

DETAILED DESCRIPTION OF THE INVENTION

[0019] Reference will now be made in detail to the present preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts.

First Embodiment

[0020] **FIG. 1A** is a top view of one pixel of a dual-display RLCD panel according to the first embodiment of the present invention. **FIG. 1B** is a sectional view of the dual-display RLCD panel taken along line 1B-1B in **FIG. 1A**. In **FIG. 1A**, the dual-display RLCD panel comprises a plurality of pixel regions P (or display regions) arranged in an array matrix. The pixel regions P are defined by the gate lines 10 and data lines 20. In order to simplify the illustration, **FIGS. 1A and 1B** show a panel section in one pixel region P, although there may be a large number of pixel regions P.

[0021] In **FIGS. 1A and 1B**, each pixel P has a first display region 101 and a second display region 102. An overlap 103 is between the first display region 101 and the second display region 102. To avoid light leakage, the width

of the overlap **103** preferably exceeds $2\ \mu\text{m}$. Here, the first display region **101** can serve as a main display region and the second display region **102** can serve as an auxiliary display region. The composition of each pixel region P is described as follows.

[0022] A first substrate **110** and a second substrate **120** opposite the first substrate **110** are provided. The first substrate **110** can be a glass substrate comprising a pixel driving device, such as a thin film transistor (TFT) T, for example, a bottom-gate type transistor. Symbol **112** denotes a gate. Symbol **114** denotes a gate insulating layer. Symbol **116** denotes a semiconductor island. Symbol S denotes a source electrode. Symbol D denotes a drain electrode. The second substrate **120** can be a glass substrate. The detailed process for forming thin film transistor T is described in U.S. Pat. No. 6,342,935 and other references, and is therefore not discussed herein to avoid obscuring aspects of the present invention.

[0023] A protective layer **130** covering the thin film transistor T is formed on the first substrate **110**. The protective layer **130** can be an oxide layer or an organic insulating layer formed by, for example, deposition or coating.

[0024] A first transparent electrode **140** serving as a pixel electrode is formed on the protective layer **130**. The first transparent electrode **140** is electrically connected to the thin film transistor T by means of a through hole **135**. The first transparent electrode **140** can be an indium tin oxide (ITO) layer or an indium zinc oxide (IZO) layer formed by, for example, sputtering.

[0025] A first reflective layer **150** is formed on the first transparent electrode **140** in the first display region **101**. In order to avoid glare, the surface profile of the first reflective layer **150** is preferably rough. The material of the first reflective layer **150** can be aluminum (Al), silver (Ag) or a multilevel material comprising alumina (Al_xO_y) and aluminum (Al), wherein the multilevel material is an anti-glare material.

[0026] A first alignment film **160** (also referred to as an orientation film) is formed on the protective layer **130** to cover the first transparent electrode **140** and the first reflective layer **150**.

[0027] A color filter **170** is formed on the interior of the second substrate **120**. The color filter **170** comprises a black matrix (BM) area **172** and a color area **174** (for example, red, green or blue).

[0028] A second transparent electrode **180** serving as a common electrode is formed on the color filter **170**. The second transparent electrode **180** can be an indium tin oxide (ITO) or indium zinc oxide (IZO) layer formed by, for example, sputtering.

[0029] A second reflective layer **190** is formed on the second transparent electrode **180** in the second display region **102**. In order to avoid glare, the surface profile of the second reflective layer **190** is preferably rough. The material of the second reflective layer **190** can be aluminum (Al), silver (Ag) or a multilevel material comprising alumina (Al_xO_y) and aluminum (Al), wherein the multilevel material is an anti-glare material. It is noted that there is an overlap **103** between the first reflective layer **150** and the second reflective layer **190**. The width of the overlap **103** can exceed

$2\ \mu\text{m}$. In addition, the display brightness of the first and second display regions **101** and **102** is determined by the area of the first and second reflective layers **150** and **190**. For example, when the area of the first reflective layer **150** is 2~3 times greater than that of the second reflective layer **190**, the display brightness of the first display region **101** can exceed that of the second display region **102**. For another example, when the area of the first reflective layer **150** is the same as the second reflective layer **190**, the display brightness of the first and second display region **101** and **102** is approximately equal.

[0030] A second alignment film **165** covering the second reflective layer **190** is formed on the second transparent electrode **180**. Then, a liquid crystal material fills a space between the first substrate **110** and the second substrate **120** to form a liquid crystal layer **195**.

[0031] In FIG. 1B, a first light source **198** can be disposed on the exterior of the first substrate **110**. The first light source **198** can be a light emitting module including a light emitting diode (LED) and a light guiding panel. When the first light source **198** is in the ON state, the first light source **198** serves as a front light for the RLCD panel in the second display region **102**. When the first light source **198** is in the OFF state, an environmental (or ambient) light serves as a reflective light source for the RLCD panel in the second display region **102**.

[0032] In addition, a second light source **199** can also be disposed on the exterior of the second substrate **120**. The second light source **199** can be a light emitting module including a light emitting diode (LED) and a light guiding panel. When the second light source **199** is in the ON state, the second light source **199** serves as a front light for the RLCD panel in the first display region **101**. When the second light source **199** is in the OFF state, an environmental (or ambient) light serves as a reflective light source for the RLCD panel in the first display region **101**.

[0033] FIG. 1B is a sectional view illustrating the operation of the RLCD of the first embodiment. In the first display region **101** of the pixel P, a reflective light **30** from the second light source **199** or the ambient light reflects from the first reflective layer **150** and displays the image on the outer side of the second substrate **120** (i.e. a viewer in the first display region **101**). In the second display region **102** of the pixel P, a reflective light **40** from the first light source **198** or the ambient light reflects from the second reflective layer **190** and displays the image on the outer side of the first substrate **110** (i.e. another viewer in the second display region **102**).

[0034] It is noted that the light **30** penetrates the color filter **170** such that the first display region **101** can display a colored image. Since the light **40** does not penetrate the color filter **170**, the second display region **102** displays a monochromatic image.

[0035] FIG. 2 is a sectional view of the dual-display RLCD according to a modification of the first embodiment. In the modification, a light shield **191** is formed rather than the black matrix area **172**, preventing the color filter **170** from experiencing light leakage.

[0036] The light shield **191** and the second reflective layer **190** can be simultaneously defined on part of the second transparent electrode **180**. That is, the material of the light

shield **191** and the second reflective layer **190** can be the same, formed by the same deposition and photolithography procedures. Thus, the modified embodiment does not require additional processes to form the black matrix area **172** in the color filter **170**, providing reduced costs.

Second Embodiment

[0037] **FIG. 3** is a sectional view of a dual-display RLCD according to a second embodiment of the present invention. Similar to the above, the dual-display RLCD panel of the second embodiment comprises a plurality of pixel regions P (or display regions). In order to simplify the illustration, **FIG. 3** shows a panel section in one pixel region. Elements in the second embodiment repeated from the first embodiment use the same reference numbers.

[0038] In **FIG. 3**, each pixel has a first display region **101** and a second display region **102**. An overlap **103** is between the first display region **101** and the second display region **102**. In order to avoid light leakage, the width of the overlap **103** preferably exceeds $2\ \mu\text{m}$. Here, the first display region **101** can serve as a main display region and the second display region **102** can serve as an auxiliary display region. The composition of each pixel region follows.

[0039] A first substrate **110** and a second substrate **120** opposite thereto are provided. The first substrate **110** can be a glass substrate comprising a pixel driving device, such as a thin film transistor (TFT) T, for example, a bottom-gate type transistor.

[0040] A protective layer **130** covering the thin film transistor T is formed on the first substrate **110**. The protective layer **130** can be an oxide layer or an organic insulating layer.

[0041] A first transparent electrode **140** serving as a pixel electrode is formed on the protective layer **130**. The first transparent electrode **140** is electrically connected to the thin film transistor T by means of a plug **135**. The first transparent electrode **140** can be an indium tin oxide (ITO) or indium zinc oxide (IZO) layer.

[0042] A first reflective layer **150** is formed on the first transparent electrode **140** in the first display region **101**. In order to avoid glare, the surface profile of the first reflective layer **150** is preferably rough. The material of the first reflective layer **150** can be aluminum (Al), silver (Ag) or a multilevel material comprising alumina (Al_xO_y) and aluminum (Al). To avoid glare, the material of the first reflective layer **150** is preferably a multilevel material comprising alumina (Al_xO_y) and aluminum (Al).

[0043] A first alignment film **160** (also referred to as an orientation film) is formed on the protective layer **130** to cover the first transparent electrode **140** and the first reflective layer **150**.

[0044] A second reflective layer **390** is formed on the interior of the second substrate **120** in the second display region **102**. In order to avoid glare, the surface profile of the second reflective layer **390** is preferably rough. The material of the second reflective layer **390** can be aluminum (Al), silver (Ag) or a multilevel material comprising alumina (Al_xO_y) and aluminum (Al). To avoid glare, the material of the second reflective layer **390** is preferably a multilevel material comprising alumina (Al_xO_y) and aluminum (Al). It

is noted that there is an overlap **103** between the first reflective layer **150** and the second reflective layer **390**.

[0045] A color filter **370** is formed on the second substrate **120** and the second reflective layer **390**. The color filter **370** comprises a black matrix area **372** and a color area **374** (for example, red, green or blue).

[0046] A second transparent electrode **380** serving as a common electrode is formed on the color filter **370**. The second transparent electrode **380** can be an indium tin oxide (ITO) or indium zinc oxide (IZO) layer.

[0047] A second alignment film **365** is formed on the second transparent electrode **380**. Then, a liquid crystal material fills a space between the first substrate **110** and the second substrate **120** to form a liquid crystal layer **195**.

[0048] In **FIG. 3**, a first light source **198** is disposed on the exterior of the first substrate **110**, such as a light emitting module including a light emitting diode (LED) and a light guiding panel. When the first light source **198** is in the ON state, the first light source **198** serves as a front light for the RLCD panel in the second display region **102**. When the first light source **198** is in the OFF state, an environmental (or ambient) light serves as a reflective light source for the RLCD panel in the second display region **102**.

[0049] In addition, a second light source **199** can also be disposed on the exterior of the second substrate **120**, such as a light emitting module including a light emitting diode (LED) and a light guiding panel. When the second light source **199** is in the ON state, the second light source **199** serves as a front light for the RLCD panel in the first display region **101**. When the second light source **199** is in the OFF state, an environmental (or ambient) light serves as a reflective light source for the RLCD panel in the first display region **101**.

[0050] **FIG. 3** is a sectional view illustrating the operation of the RLCD of the second embodiment. In the first display region **101** of each pixel, a reflective light **30** from the second light source **199** or the ambient light reflects from the first reflective layer **150** and displays the image on the outer side of the second substrate **120** (i.e. a viewer in the first display region **101**). Nevertheless, in the second display region **102** of each pixel, a reflective light **50** from the first light source **198** or the ambient light reflects from the second reflective layer **390** and displays the image on the outer side of the first substrate **110** (i.e. another viewer in the second display region **102**).

[0051] It is noted that the light **30** penetrates the color filter **370** such that the first display region **101** can display a colored image. The light **50** penetrates the color filter **370** such that the second display region **102** can also display a colored image.

[0052] **FIG. 4** is a sectional view of the dual-display RLCD according to a modification of the second embodiment. In the modification, a light shield **391** is formed rather than the black matrix area **372**, preventing the color filter **370** from experiencing light leakage.

[0053] The light shield **391** and the second reflective layer **390** can be simultaneously defined on part of the second substrate **120**. That is, the material of the light shield **391** and the second reflective layer **390** can be the same, formed by the same deposition and photolithography procedures. Thus,

the modified embodiment does not require additional processes to form the black matrix area **372** in the color filter **370**, providing reduced costs.

[0054] FIG. 5 shows an exemplary application of the present invention in a folding type mobile phone **510** having the present dual-display RLCD. Symbol **501** denotes the main display region consisting of a plurality of first display regions **101**, wherein the main display region **501** is typically located on the interior of the folding type mobile phone **510**. Symbol **502** denotes the auxiliary display region consisting of a plurality of second display regions **102**, wherein the auxiliary display region **502** is typically located on the exterior of the folding type mobile phone **510**. The area of the main display region **501** can be the same as the auxiliary display region **502**. Depending on design, part of the auxiliary display region **502** can be covered by outer housing **520** to reduce (or adjust) the display area, as shown as FIG. 5.

[0055] To control the display direction of the message, the present invention uses a switch (not shown) to detect whether the housing **520** of the folding type mobile phone **510** is open or closed. For example, when the housing **520** is closed, the display direction of the main display region **501** can be reversed by a reverse processor **530** to accommodate the desired display direction of the auxiliary display region **502**.

[0056] Thus, the present invention provides a dual-display RLCD panel with a single liquid crystal layer, a first reflective layer formed on the first substrate in the first display region and a second reflective layer formed on the second substrate in the second display region. In addition, the first and second display regions (or reflective layers) are defined in each pixel so the front surface area of the display panel is the same as the rear surface area thereof. The display structure of the invention uses one display with only one set of electrical equipment for driving the RLCD, thereby reducing costs and volume and ameliorating the disadvantages of the conventional technology.

[0057] Finally, while the invention has been described by way of example and in terms of the above, it is to be understood that the invention is not limited to the disclosed embodiments. On the contrary, it is intended to cover various modifications and similar arrangements as would be apparent to those skilled in the art. Therefore, the scope of the appended claims should be accorded the broadest interpretation so as to encompass all such modifications and similar arrangements.

What is claimed is:

1. A reflective liquid crystal display panel for dual display, the panel comprising a plurality of pixels, each comprising first and second display regions and comprising:

- a first substrate and a second substrate opposite thereto, wherein the first substrate comprises a pixel driving device;
- a first reflective layer formed overlying the first substrate in the first display region;
- a second reflective layer formed overlying the second substrate in the second display region; and
- a liquid crystal layer interposed between the first substrate and the second substrate.

2. The reflective liquid crystal display panel according to claim 1, further comprising an overlap between the first reflective layer and the second reflective layer.

3. The reflective liquid crystal display panel according to claim 2, wherein a width of the overlap exceeds $2\ \mu\text{m}$.

4. The reflective liquid crystal display panel according to claim 1, further comprising:

- a pixel electrode electrically connecting the pixel driving device formed on the first substrate; and

- a color filter formed on the second substrate.

5. A liquid crystal display panel for dual display, the panel comprising a plurality of pixels, each comprising first and second display regions and comprising:

- a first substrate and a second substrate opposite thereto;

- a first transparent electrode formed on the first substrate;

- a first reflective layer formed overlying the first substrate in the first display region;

- a second transparent electrode formed overlying the second substrate;

- a second reflective layer formed on the second transparent electrode in the second display region; and

- a liquid crystal layer interposed between the first substrate and the second substrate.

6. The liquid crystal display panel according to claim 5, further comprising a first light source disposed on an exterior of the first substrate.

7. The liquid crystal display panel according to claim 5, further comprising a second light source disposed on an exterior of the second substrate.

8. The liquid crystal display panel according to claim 5, wherein the first substrate is a first glass substrate comprising a thin film transistor electrically connected to the first transparent electrode.

9. The liquid crystal display panel according to claim 5, wherein the second substrate is a second glass substrate comprising a color filter on the interior thereof.

10. The liquid crystal display panel according to claim 9, wherein the color filter comprises a black matrix area.

11. The liquid crystal display panel according to claim 9, wherein the color filter is disposed between the second substrate and the reflective layer.

12. The liquid crystal display panel according to claim 5, further comprising a light shield formed on part of the second transparent electrode, wherein the light shield and the second reflective layer are simultaneously defined.

13. The liquid crystal display panel according to claim 5, wherein the first and second transparent electrodes are indium tin oxide (ITO) or indium zinc oxide (IZO) layers.

14. The liquid crystal display panel according to claim 5, wherein the first and/or second reflective layers comprise aluminum, silver or a multilevel material comprising alumina (Al_2O_3) and aluminum.

15. The liquid crystal display panel according to claim 5, further comprising an overlap between the first reflective layer and the second reflective layer.

16. The liquid crystal display panel according to claim 15, wherein a width of the overlap exceeds $2\ \mu\text{m}$.

17. A liquid crystal display panel, the panel comprising a plurality of pixels, each comprising first and second display regions and comprising:

a first substrate and a second substrate opposite thereto;
a first transparent electrode formed on the first substrate;
a first reflective layer formed overlying the first substrate in the first display region;
a second reflective layer formed overlying an interior of the second substrate in the second display region;
a color filter formed on the second substrate and the second reflective layer;
a second transparent electrode formed on the color filter; and
a liquid crystal layer interposed between the first substrate and the second substrate.

18. The liquid crystal display panel according to claim 17, further comprising a first light source disposed on an exterior of the first substrate.

19. The liquid crystal display panel according to claim 17, further comprising a second light source disposed on an exterior of the second substrate.

20. The liquid crystal display panel according to claim 17, wherein the first substrate is a first glass substrate compris-

ing a thin film transistor electrically connected to the first transparent electrode.

21. The liquid crystal display panel according to claim 17, wherein the color filter comprises a black matrix area.

22. The liquid crystal display panel according to claim 17, further comprising a light shield formed on part of the second substrate, wherein the light shield and the second reflective layer are simultaneously defined.

23. The liquid crystal display panel according to claim 17, wherein the first and second transparent electrodes are indium tin oxide (ITO) or indium zinc oxide (IZO) layers.

24. The liquid crystal display panel according to claim 17, wherein the first and/or second reflective layers comprise aluminum, silver or a multilevel material comprising alumina (Al_xO_y) and aluminum.

25. The liquid crystal display panel according to claim 17, further comprising an overlap between the first reflective layer and the second reflective layer.

26. The liquid crystal display panel according to claim 25, wherein a width of the overlap exceeds $2\text{ }\mu\text{m}$.

* * * * *

专利名称(译)	用于双显示屏的反射式液晶显示器		
公开(公告)号	US20050105021A1	公开(公告)日	2005-05-19
申请号	US10/885435	申请日	2004-07-06
[标]申请(专利权)人(译)	LEE SEOK LYUL JEN 天安SEN 林铭田		
申请(专利权)人(译)	李硕LYUL JEN 天安森 林铭田		
当前申请(专利权)人(译)	瀚宇彩晶股份有限公司.		
[标]发明人	LEE SEOK LYUL JEN TEAN SEN LIN MING TIEN		
发明人	LEE, SEOK-LYUL JEN, TEAN-SEN LIN, MING-TIEN		
IPC分类号	G02F1/1347 G02F1/1335		
CPC分类号	G02F2001/133342 G02F1/133553		
优先权	092131761 2003-11-13 TW		
其他公开文献	US7148940		
外部链接	Espacenet USPTO		

摘要(译)

一种用于双显示屏的反射式液晶显示面板。面板具有多个像素，并且每个像素具有第一和第二显示区域。每个像素包括第一基板和与其相对的第二基板，其中第一基板包括像素驱动装置。在第一显示区域中形成覆盖第一基板的第一反射层。在第二显示区域中形成覆盖第二基板内部的第二反射层。液晶层介于第一基板和第二基板之间。

