

(10) **Patent No.:** US 8,711,302 B2
(45) **Date of Patent:** Apr. 29, 2014

(54) LIQUID CRYSTAL DISPLAY

(75) Inventor: **Dong-Gyu Kim**, Yongin-si (KR)

(73) Assignee: **Samsung Display Co., Ltd. (KR)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: 12/954,463

(22) Filed: **Nov. 24, 2010**

(65) **Prior Publication Data**

US 2011/0069259 A1 Mar. 24, 2011

Related U.S. Application Data

(62) Division of application No. 11/949,515, filed on Dec. 3, 2007, now abandoned.

(30) **Foreign Application Priority Data**

Dec. 11, 2006 (KR) 10-2006-0125428

(51) **Int. Cl.**
G02F 1/1333 (2006.01)
G02F 1/1343 (2006.01)

(52) **U.S. Cl.**
USPC 349/110; 349/38; 349/145

(58) **Field of Classification Search**

USPC 349/38-42, 110, 139, 145
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,710,825	B2	3/2004	Kubo et al.	
6,903,754	B2	6/2005	Brown Elliott	
6,956,633	B2 *	10/2005	Okada et al.	349/139
7,242,452	B2 *	7/2007	Jeong et al.	349/145
7,812,911	B2 *	10/2010	Song	349/145
7,924,387	B2	4/2011	Hung	
8,035,610	B2 *	10/2011	Hsu	345/103

FOREIGN PATENT DOCUMENTS

JP	11-242244	9/1999
JP	2001-264818	9/2001
JP	2001-281696	10/2001

* cited by examiner

Primary Examiner — Dung Nguyen

(74) *Attorney, Agent, or Firm* — Innovation Counsel LLP

(57) **ABSTRACT**

A liquid crystal display includes: a plurality of pixel electrodes each having a first sub-pixel electrode and a second sub-pixel electrode that face each other in a diagonal direction; a plurality of gate lines; and a plurality of data lines that intersect the plurality of gate lines and at least partially overlap the pixel electrodes.

9 Claims, 13 Drawing Sheets




FIG. 1




FIG.2




FIG.3




FIG.4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG.12





FIG. 13



LIQUID CRYSTAL DISPLAY**CROSS-REFERENCE TO RELATED APPLICATION**

This application is a Divisional of U.S. patent application Ser. No. 11/949,515 filed on Dec. 3, 2007, which claims priority to and the benefit of Korean Patent Application No. 10-2006-0125428 filed in the Korean Intellectual Property Office on Dec. 11, 2006, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The present invention relates to a liquid crystal display.

2. Description of the Related Art

Liquid crystal displays are now the most widely used of the flat panel displays. The liquid crystal displays have two display panels on which electric field generating electrodes such as pixel electrodes and a common electrode are formed, and a liquid crystal layer interposed between the panels. In the liquid crystal displays, a voltage is applied to the electric field generating electrodes so as to generate an electric field in the liquid crystal layer. The alignment of liquid crystal molecules of the liquid crystal layer is determined by the electric field. Accordingly, the polarization of incident light is controlled, thereby providing image display.

The liquid crystal displays also include switching elements connected to the individual pixel electrodes and a plurality of signal lines, such as gate lines and data lines, for controlling the switching elements so as to apply voltages to the pixel electrodes.

In order to prevent a degradation phenomenon that occurs when the electric field is applied in the liquid crystal layer in one direction for a long time, polarities of the data voltage with respect to a common voltage are inverted for every frame, every row, or every pixel.

In these liquid crystal displays, a high-speed driving method is used so as to improve a motion picture display characteristic. However, because high-speed driving requires a larger amount of electric power as the frame speed increases, column inversion is used once per frame to minimize power consumption.

However, the column inversion causes a coupling defect and a stripe defect. Parasitic capacitance arising from an overlap between the data lines and the pixel electrodes causes a data voltage having the same polarity to be continuously applied throughout a frame, thereby generating a coupling defect that causes the upper and lower parts of the display panel of the liquid crystal panel assembly to display images with different luminances. In particular, if a box having a high grayscale level is displayed on a background image having a low grayscale level, a vertical crosstalk phenomenon may occur such that the upper portion and the lower portion of the box have grayscales different from the background image.

The stripe defect refers to a phenomenon in which stripes appear when a data voltage having the same polarity is applied in a vertical direction so that a data voltage having a positive polarity creates an image that is different from a data voltage having a negative polarity.

SUMMARY OF THE INVENTION

An exemplary embodiment of the present invention provides a liquid crystal display that prevents the coupling defect and the stripe defect comprising: a plurality of pixel elec-

trodes each having a first sub-pixel electrode and a second sub-pixel electrode that face each other in a diagonal direction and are connected to each other; a plurality of gate lines; and a plurality of data lines that intersect the plurality of gate lines and at least partially overlap the pixel electrodes.

Each of the first and second sub-pixel electrodes may include first and second edges that are parallel to the gate line, and third and fourth edges that are parallel to the data line.

The liquid crystal display may further include a plurality of thin film transistors connected to the gate lines, the data lines, and the pixel electrodes.

The data lines may include a first data line connected to the pixel electrodes through the thin film transistors and second and third data lines that are adjacent to the first data line, and the pixel electrodes may overlap all of the first to third data lines.

The first data line may overlap both the first and second sub-pixel electrodes, the second data line may overlap the first sub-pixel electrodes, and the third data line may overlap the second sub-pixel electrodes.

Data voltages having the same polarity may be applied to the second and third data lines, and the polarity of the data voltage applied to the first data line may be opposite to that of the data voltage applied the second and third data lines.

The plurality of thin film transistors connected to the pixel electrodes that are adjacent in the column direction may be alternately disposed at both sides of the data line.

The liquid crystal display may further include an organic film formed between the pixel electrodes and the data lines.

The liquid crystal display may further include storage electrode lines that overlap the pixel electrodes.

An opening may be formed in the organic film at a position where each storage electrode line overlaps a pixel electrode.

Each thin film transistor may include a drain electrode connected to the pixel electrode, and at least a portion of the drain electrode may overlap the storage electrode line.

The liquid crystal display may further include a plurality of color filters that are formed between the pixel electrodes and the data lines.

An opening may be formed in each color filter at a position where the storage electrode line overlaps the pixel electrode.

The liquid crystal display may further include a common electrode that faces the pixel electrodes, and a liquid crystal layer interposed between the common electrode and the pixel electrodes. The liquid crystal molecules in the liquid crystal layer may be arranged in parallel with the pixel electrodes and the common electrodes when no electric field is applied.

The liquid crystal display may further include a common electrode that faces the pixel electrodes, and a liquid crystal layer interposed between the common electrode and the pixel electrodes. The liquid crystal molecules in the liquid crystal layer may be aligned in a splay alignment mode when no electric field is applied, and aligned in a bend alignment mode when the electric field is generated.

Another embodiment of the present invention provides a liquid crystal display including: a plurality of pixel electrodes; a plurality of gate lines that transmit gate signals to the pixel electrodes; and a plurality of data lines that intersect the gate lines and transmit data voltages to the pixel electrodes. Each data line overlaps a pixel electrode and includes a first portion that lies on a first imaginary straight line and a second portion that lies on a second imaginary straight line which is separated from and parallel to the first imaginary straight line.

The first and second portions of the data lines may overlap different pixel electrodes.

The pixel electrode may include first and second edges that are parallel to the gate lines, and third and fourth edges that are parallel to the data lines.

The liquid crystal display may further include a plurality of storage electrode lines that overlap the pixel electrodes.

The liquid crystal display may further include a light blocking member disposed between adjacent pixel electrodes.

The light blocking member may include a first light blocking member that is adjacent to the first portion of the data line and a second light blocking member that is adjacent to the second portion of the data line.

The first light blocking member may be separated from the second light blocking member, and the first light blocking member may be connected to the storage electrode line.

The light blocking member may be formed of the same material as the storage electrode line.

The liquid crystal display may further include an organic film formed between the pixel electrodes and the data lines.

An opening may be formed in the organic film at a position where the storage electrode line overlaps the pixel electrode.

The liquid crystal display may further include a plurality of color filters that are formed between the pixel electrodes and the data lines.

An opening may be formed in the color filter at a position where the storage electrode line overlaps the pixel electrode.

The liquid crystal display may further include a plurality of thin film transistors connected to the gate lines, the data lines, and the pixel electrodes. The plurality of thin film transistors connected to the pixel electrodes that are adjacent in the column direction may be alternately disposed at both sides of the data line.

Data voltages having opposite polarities may be applied to the two adjacent data lines.

The liquid crystal display may further include a common electrode that faces the pixel electrodes, and a liquid crystal layer interposed between the common electrode and the pixel electrodes. The liquid crystal molecules in the liquid crystal layer may be arranged in parallel with the pixel electrodes and the common electrodes when no electric field is applied.

The liquid crystal display may further include a common electrode that faces the pixel electrodes, and a liquid crystal layer interposed between the common electrode and the pixel electrodes. The liquid crystal molecules in the liquid crystal layer may be aligned in a splay alignment mode when no electric field is applied, and aligned in a bend alignment mode when the electric field is generated.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a liquid crystal display according to an exemplary embodiment of the present invention.

FIG. 2 is an equivalent circuit diagram of one pixel in the liquid crystal display according to the exemplary embodiment of the present invention.

FIG. 3 is a view illustrating the spatial alignment of the pixels and signal lines of the liquid crystal panel assembly according to the exemplary embodiment of the present invention.

FIG. 4 is a layout view of the liquid crystal panel assembly according to the exemplary embodiment of the present invention.

FIGS. 5 and 6 are cross-sectional views of the liquid crystal panel assembly of FIG. 4 taken along the lines V-V and VI-VI.

FIG. 7 is a layout view illustrating an alignment error occurring in the manufacturing process of the liquid crystal display shown in FIG. 4.

FIG. 8 is a layout view of a liquid crystal panel assembly according to another exemplary embodiment of the present invention.

FIG. 9 is a layout view of a liquid crystal panel assembly according to another exemplary embodiment of the present invention.

FIG. 10 is a cross-sectional view of the liquid crystal panel assembly shown in FIG. 9 taken along the line IX-IX.

FIG. 11 is a view illustrating an alignment state of the liquid crystal molecules of a liquid crystal display according to another exemplary embodiment of the present invention before a predetermined voltage is applied.

FIG. 12 is a view illustrating an alignment state of the liquid crystal molecules of a liquid crystal display according to another exemplary embodiment of the present invention after the predetermined voltage is applied.

FIG. 13 is a layout view illustrating an alignment error occurring in the liquid crystal panel assembly shown in FIG. 9.

DETAILED DESCRIPTION OF THE EMBODIMENTS

In the drawings, the thickness of layers, films, panels, regions, etc., are exaggerated for clarity. It will be understood that when an element such as a layer, film, region, or substrate is referred to as being "on" another element, it can be directly on the other element or intervening elements may also be present. In contrast, when an element is referred to as being "directly on" another element, there are no intervening elements present.

First, a liquid crystal display according to an exemplary embodiment of the present invention will be described in detail with reference to FIGS. 1 and 2.

FIG. 1 is a block diagram of a liquid crystal display according to an exemplary embodiment of the present invention, and FIG. 2 is an equivalent circuit diagram of one pixel in a liquid crystal display according to an exemplary embodiment of the present invention.

Referring to FIG. 1, a liquid crystal display according to an exemplary embodiment of the present invention includes a liquid crystal panel assembly 300, a gate driver 400, a data driver 500, a gray voltage generator 800, and a signal controller 600.

In an equivalent circuit, the liquid crystal panel assembly 300 includes a plurality of signal lines G_1 to G_n and D_1 to D_m , and a plurality of pixels PX that are connected to the plurality of signal lines and are arranged approximately in a matrix. Referring to the structure shown in FIG. 2, the liquid crystal panel assembly 300 includes lower and upper display panels 100 and 200 that face each other, and a liquid crystal layer 3 that is interposed between the lower and upper display panels 100 and 200.

The signal lines G_1 to G_n and D_1 to D_m include a plurality of gate lines G_1 to G_n that transmit gate signals (also referred to as "scanning signals"), and a plurality of data lines D_1 to D_m that transmit data signals. The gate lines G_1 to G_n substantially extend in a row direction and are in parallel with one another, and the data lines D_1 to D_m substantially extend in a column direction and are in parallel with one another.

For example, the pixel PX connected to an i -th gate line G_i ($i=1, 2, \dots, n$) and a j -th data line G_j ($j=1, 2, \dots, m$) includes a switching element Q and a liquid crystal capacitor C_{lc} , and a storage capacitor C_{st} connected thereto. The storage capacitor C_{st} may be omitted if necessary.

The switching element Q is a three terminal element such as a thin film transistor that is provided in the lower display

panel **100**. A control terminal thereof is connected to the gate line G_i , an input terminal thereof is connected to a data line D_j , and an output terminal is connected to the liquid crystal capacitor Clc and the storage capacitor Cst .

The liquid crystal capacitor Clc includes a pixel electrode **191** of the lower display panel **100** and a common electrode **270** of the upper display panel **200** as two terminals, and the liquid crystal layer **3** between the two electrodes **191** and **270** functions as a dielectric. The pixel electrode **191** is connected to the switching element Q , and the common electrode **270** is formed on the entire surface of the upper display panel **200** and has a common voltage V_{com} applied therewith. Unlike the structure shown in FIG. 2, the common electrode **270** may be provided on the lower display panel **100**, and in this case, at least one of the two electrodes **191** and **270** may be formed in a linear or rod shape.

The storage capacitor Cst that supplements the liquid crystal Clc is formed such that an additional signal line (not shown) provided in the lower display panel **100** and the pixel electrode **191** overlaps an insulating material interposed therebetween. The additional signal line is supplied with a predetermined voltage such as a common voltage V_{com} . However, the storage capacitor Cst may be formed by overlapping the pixel electrode **191** and a previous gate line formed directly on the pixel electrode with the insulating material therebetween.

To provide a color display, each pixel PX displays one of the primary colors (spatial division), or the pixels PX alternately display the primary colors with time (temporal division), which causes the primary colors to be spatially and temporally synthesized, thereby displaying a desired color. The primary colors may be composed of, for example, red, green, and blue. As an example of the spatial division, FIG. 2 shows that each pixel PX has a color filter **230** for displaying one of the primary colors in a region of the upper display panel **200** corresponding to the pixel electrode **191**. Unlike the structure shown in FIG. 2, the color filter **230** may be provided above or below the pixel electrode **191** of the lower display panel **100**.

At least one polarizer (not shown) for polarizing light is mounted on an outer surface of the liquid crystal panel assembly **300**.

Referring to FIG. 1 again, the gray voltage generator **800** generates all gray voltages related to the transmittance of the pixel PX , or a limited number of gray voltages (hereinafter, referred to as "reference gray voltages"). However, the gray voltage generator **800** may generate only a given number of gray voltages (referred to as reference gray voltages) instead of generating all of the gray voltages. The (reference) gray voltages may have a positive value with respect to the common voltage V_{com} and a negative value with respect to the common voltage V_{com} .

The gate driver **400** is connected to the gate lines G_1 to G_n of the liquid crystal panel assembly **300**, and supplies gate signals each of which is composed of a combination of a gate-on voltage V_{on} and a gate-off voltage V_{off} to the gate lines G_1 to G_n .

The data driver **500** is connected to the data lines D_1 to D_m of the liquid crystal panel assembly **300**, selects the gray voltage generated by the gray voltage generator **800**, and supplies the selected gray voltage to the data lines D_1 to D_m as a data voltage. However, when the gray voltage generator **800** does not supply all of the gray voltages, but supplies only a predetermined number of reference gray voltages, the data driver **500** divides the reference gray voltage to select a desired data voltage from the generated gray voltages.

The signal controller **600** controls, for example, the gate driver **400** and the data driver **500**.

Each of the drivers **400**, **500**, **600**, and **800** may be directly mounted on the liquid crystal panel assembly **300** in the form of at least one IC chip, may be mounted on a flexible printed circuit film (not shown) and then mounted on the liquid crystal panel assembly **300** in the form of a TCP (tape carrier package), or may be mounted on a separate printed circuit board (not shown). Alternatively, the drivers **400**, **500**, **600**, and **800** may be integrated into the liquid crystal panel assembly **300** together with, for example, the signal lines G_1 to G_n and D_1 to D_m and the thin film transistor switching elements Q . The drivers **400**, **500**, **600**, and **800** may be integrated into a single chip. In this case, at least one of the drivers or at least one circuit forming the drivers may be arranged outside the single chip.

Hereinafter, the operation of the liquid crystal display will be described in detail.

The signal controller **600** receives input image signals R , G , and B and input control signals for displaying the input image signals from an external graphics controller (not shown). The input image signals R , G , and B include luminance information of each pixel PX , and the luminance has a predetermined number of grayscale levels, for example 1024 ($=2^{10}$), 256 ($=2^8$), or 64 ($=2^6$) levels. For example, any of the following signals may be used as the input control signal: a vertical synchronization signal V_{sync} , a horizontal synchronization signal H_{sync} , a main clock signal $MCLK$, and a data enable signal DE .

The signal controller **600** processes the input image signals R , G , and B so as to be suitable for the operational conditions of the liquid crystal panel assembly **300** on the basis of the input image signals R , G , and B and the input control signal, and generates, for example, a gate control signal $CONT1$ and a data control signal $CONT2$. Then, the signal controller **600** transmits the gate control signal $CONT1$ to the gate driver **400** and transmits the data control signal $CONT2$ and the processed image signal DAT to the data driver **500**.

The gate control signal $CONT1$ includes a scanning start signal STV for indicating the start of scanning, and at least one clock signal for controlling the output cycle of the gate-on voltage V_{on} . The gate control signal $CONT1$ may further include an output enable signal OE for defining the duration of the gate-on voltage V_{on} .

The data control signal $CONT2$ includes a horizontal synchronization start signal STH for indicating that the transmission of data to a row of pixels PX starts, a load signal $LOAD$ for allowing data voltages to be transmitted to the data lines D_1 to D_m , and a data clock signal $HCLK$. The data control signal $CONT2$ may further include an inversion signal RVS for inverting the polarity of the data voltage with respect to the common voltage V_{com} (hereinafter, "the polarity of data voltage with respect to the common voltage" is simply referred to as "the polarity of a data voltage").

The data driver **500** receives the digital image signal DAT for a row of pixels PX in response to the data control signal $CONT2$ transmitted from the signal controller **600**, selects a gray voltage corresponding to each digital image signal DAT , converts the digital image signal DAT into an analog data signal, and supplies the analog data signal to the corresponding data lines D_1 to D_m .

The gate driver **400** applies the gate-on voltage V_{on} to the gate lines G_1 to G_n on the basis of the gate control signal $CONT1$ from the signal controller **600** to turn on the switching elements Q connected to the gate lines G_1 to G_n . Then, the

data voltages applied to the data lines D_1 to D_m are supplied to the corresponding pixels PX through the switching elements Q that are in an on state.

The difference between the voltage of the data voltage applied to the pixel PX and the common voltage Vcom is a charging voltage of the liquid crystal capacitor Clc, that is, a pixel voltage. The alignment directions of liquid crystal molecules depend on the level of the pixel voltage, and cause the polarization of light passing through the liquid crystal layer 3 to vary. The variation in polarization causes a variation in the transmittance of light by the polarizer mounted on the liquid crystal panel assembly 300. Therefore, the pixel PX may display the luminance indicated by the grayscale level of the image signal DAT.

These processes are repeatedly performed for every one horizontal period (which is referred to as "1H" and is equal to one period of the horizontal synchronization signal Hsync and the data enable signal DE). In this way, the gate-on voltage Von is sequentially applied to all the gate lines G1 to Gn, and the data signals are supplied to all the pixels PX, thereby displaying one frame of images.

When one frame has ended, the next frame starts. In this case, the state of the inversion signal RVS applied to the data driver 500 is controlled such that the polarity of the data voltage applied to each pixel PX is opposite to the polarity of the data voltage in the previous frame ("frame inversion"). The polarity of the data signal applied to one data line may be inverted in the same frame according to the characteristic of the inversion signal RVS (for example, row inversion and dot inversion), and the polarities of the data voltages to be applied to a row of pixels may be different from each other (for example, column inversion and dot inversion).

The alignment of the pixels and the signal lines of the liquid crystal panel assembly will be described in detail with reference to FIG. 3.

FIG. 3 is a view illustrating the spatial alignment of the pixels and the signal lines of the liquid crystal panel assembly according to the exemplary embodiment of the present invention.

For better comprehension and ease of description, only some of the data lines D_1 to D_7 and some of the gate lines G_{j-1} to G_{j+2} are shown.

Referring to FIG. 3, a row of pixels PX is connected to the gate lines G_{j-1} to G_{j+2} and the data lines D_1 to D_7 through the switching elements Q. In the pixels PX disposed in the same row, all the pixels disposed in first and third rows are connected to the data lines D_2 , D_4 , and D_6 on the right sides of the pixels PX, and all the pixels disposed on second and fourth rows are connected to the data lines D_1 , D_3 , D_5 , and D_7 on the left sides of the pixels PX.

The pixels PX disposed in the same column are alternatively connected to the data lines D_1 to D_7 on the right and left sides of the pixels PX.

Further, data voltages having opposite polarities are applied to every two adjacent data lines D_1 to D_7 . That is, the polarity of the data voltage to be applied to odd-numbered data lines D_1 , D_3 , D_5 , and D_7 are positive and the polarity of the data voltage to be applied to even-numbered data lines D_2 , D_4 , to D_6 are negative.

Therefore, positive and negative data voltages are alternatively applied to the pixels PX (hereinafter, referred to as "pixel polarity"), which causes dot inversion thereby preventing the stripe defect from occurring.

Hereinafter, the liquid crystal panel assembly according to the exemplary embodiment of the present invention will be described in detail with reference to FIGS. 4 to 6.

FIG. 4 is a layout view of the liquid crystal panel assembly according to the exemplary embodiment of the present invention. FIGS. 5 and 6 are cross-sectional views of the liquid crystal panel assembly of FIG. 4 taken along the lines V-V and VI-VI.

Referring to FIGS. 4 to 6, the liquid crystal panel assembly according to the exemplary embodiment of the present invention includes a lower display panel 100, an upper display panel 200, and a liquid crystal layer 3 interposed therebetween.

First, the lower display panel 100 will be described in detail.

A plurality of gate lines 121 and a plurality of storage electrode lines 131 are formed on an insulation substrate 110 formed of, for example, transparent glass.

The gate lines 121 transmit the gate signals and extend in the horizontal direction. Each of the gate lines 121 includes a plurality of gate electrodes 124 that protrude upward, and a wide end portion 129 that is provided for connection to a different layer or an external driving circuit.

The storage electrode lines 131 are supplied with a predetermined voltage, and substantially extend in parallel with the gate lines 121. Each of the storage electrode lines 131 is disposed between two adjacent gate lines 121 and maintains the same interval from the two gate lines 121. The storage electrode lines 131 include the storage electrodes 137 extending in the vertical direction. However, the shape and alignment of the storage electrode lines 131 may be modified in various ways.

The gate lines 121 and the storage electrode lines 131 may be formed of a conductor having low resistance, for example, an aluminum-based metal, such as aluminum (Al) or an aluminum alloy, a silver-based metal, such as silver (Ag) or a silver alloy, a copper-based metal, such as copper (Cu) or a copper alloy, a molybdenum-based metal, such as molybdenum (Mo) or a molybdenum alloy, chromium (Cr), tantalum (Ta), or titanium (Ti). The gate lines 121 and the storage electrode lines 131 may have a multi-layered structure including two conductive layers (not shown) whose physical properties are different from each other. Of these, one conductive layer is formed of a metallic material having low resistivity, such as an aluminum-based metal, a silver-based metal, or a copper-based metal, in order to reduce signal delay or voltage drop. In contrast, the other conductive layer is formed of a different material, particularly a material having excellent physical, chemical, and electrical contact characteristics with ITO (Indium Tin Oxide) and IZO (Indium Zinc Oxide), such as a molybdenum-based metal, chromium, titanium, or tantalum. Specific examples of the combination include a combination of a chromium lower layer and an aluminum (alloy) upper layer, and a combination of an aluminum (alloy) lower layer and a molybdenum (alloy) upper layer. Moreover, the gate lines 121 and the storage electrode lines 131 may be formed of various metals or conductors, other than the above materials.

The lateral side's surface of each of the gate lines 121 and the storage electrode lines 131 is inclined with respect to a surface of the substrate 110, and the inclination angle is preferably in a range of about 30° to 80°.

A gate insulating layer 140 made of silicon nitride (SiN_x) or silicon oxide (SiO_x) is formed on the gate lines 121 and the storage electrode line 131.

A plurality of semiconductor islands 154 formed of hydrogenated amorphous silicon (abbreviated as a-Si) or polycrystalline silicon are formed on the gate insulating layer 140. The semiconductor islands 154 are respectively disposed on the gate electrodes 124.

A plurality of ohmic contacts **163** and **165** are formed on the semiconductor islands **154**. The ohmic contacts **163** and **165** may be formed of a material such as n+ hydrogenated amorphous silicon, in which an n-type impurity is doped with high concentration, or of silicide. A plurality of pairs of ohmic contacts **163** and **165** are formed on the semiconductor islands **154**.

The lateral sides of each of the semiconductor islands **154** and the ohmic contacts **163** and **165** is inclined with respect to the surface of the substrate **110**, and the inclination angle is in a range of about 30° to 80°.

A plurality of data lines **171** and a plurality of drain electrodes **175** are formed on the ohmic contacts **163** and **165** and the gate insulating layer **140**.

The data lines **171** transmit data signals and substantially extend in a vertical direction to cross the gate lines **121** and the storage electrode lines **131**. Each of the data lines **171** includes a plurality of first and second source electrodes **173** extending toward the gate electrodes **124**, and a wide end portion **179** that is provided for connection to a different layer or an external driving circuit.

The drain electrodes **175** are separated from the data lines **171**, and face the source electrodes **173** with electrodes **124** as a center, respectively. Each of the drain electrodes **175** includes one end portion having a wide extension and the other end portion having a bar shape which is surrounded by the source electrodes **173** curved in a "U" shape.

One gate electrode **124**, one source electrode **173**, and one drain electrode **175** form one thin film transistor (TFT) together with the semiconductor island **154**. A channel of the thin film transistor is formed in the semiconductor island **154** between the source electrode **173** and the drain electrode **175**.

The data line **171** and the drain electrodes **175** are preferably formed of a refractory metal, such as molybdenum, chromium, tantalum, or titanium, or an alloy of them. The data line **171** and the drain electrodes **175** may have a multi-layered structure having a refractory metal layer (not shown) and a low-resistive conductive layer (not shown). Examples of the multi-layered structure includes a two-layered structure of a chromium or molybdenum (alloy) lower layer and an aluminum (alloy) upper layer, and a three-layered structure of a molybdenum (alloy) lower layer, an aluminum (alloy) intermediate layer, and a molybdenum (alloy) upper layer. However, the data line **171** and the drain electrodes **175** may be formed of various materials or conductors, other than the above materials.

Preferably, the lateral sides of each of the data line **171** and the drain electrodes **175** is also inclined with respect to the surface of the substrate **110** at an angle of about 30° to 80°.

The ohmic contacts **163** and **165** are provided only between the underlying semiconductor islands **154** and the overlying data lines **171** and drain electrodes **175** so as to reduce contact resistance therebetween. The semiconductor islands **154** have exposed portions that are not covered with the data line **171** and the drain electrodes **175**, including a portion between the source electrode **173** and the drain electrode **175**.

A passivation layer **180** is formed on the data line **171**, the drain electrodes **175**, and the exposed portions of the semiconductor island **154**. The passivation layer **180** is formed of an inorganic insulator and may have a flat surface. The inorganic insulator may be exemplified as silicon nitride or silicon oxide. The upper passivation layer **180** may have photosensitivity, and preferably has a dielectric constant of 4.0 or less. However, the passivation layer **180** may have a dual-layered structure having a lower inorganic layer and an upper organic

layer so as to utilize the excellent insulating characteristic of the organic film and to not damage the exposed semiconductor island **154**.

A plurality of contact holes (contact holes) **182** and **185** are formed in the passivation layer **180** to expose one end of the data lines **171** and the drain electrodes **175**. Further, a plurality of contact holes **181** are formed in the passivation layer **180** and the gate insulating layer **140** to expose an end portion **129** of the gate lines **121**. Further, an opening **183** is formed in the passivation layer **180** to expose the gate insulating layer **140**. The opening **183** overlaps the storage electrode **137**.

A plurality of pixel electrodes **191** and a plurality of contact assistants **81** and **82** are formed on the passivation layer **180**. These may be formed of a transparent conductive material such as ITO or IZO, or a reflective metal such as aluminum, silver, chromium, or an alloy of them.

The pixel electrode **191** includes first and second sub-pixel electrodes **191a** and **191b** that face each other in a diagonal direction. In particular, the first sub-pixel electrode **191a** is disposed at a lower left portion and the second sub-pixel electrode **191b** is disposed at an upper right portion. A second sub-pixel electrode of another pixel electrode is disposed at the upper portion of the first sub-pixel electrode **191a**, and a first sub-pixel electrode of another pixel electrode is disposed at the lower portion of the second sub-pixel electrode **191b**. The first and second sub-pixel electrodes **191a** and **191b** are connected to each other through a connection unit **192**.

Each of the sub-pixel electrodes **191a** and **191b** includes a pair of horizontal edges that are parallel to the gate line **121** and a pair of vertical edges that are parallel to the data line **171**. The length of each edge of the first sub-pixel electrode **191a** is substantially equal to that of each edge of the second sub-pixel electrode **191b**. Therefore, the area of the sub-pixel electrode **191a** is substantially equal to that of the sub-pixel electrode **191b**.

The pixel electrode **191** is physically and electrically connected to the drain electrode **175** through the contact hole **185** so as to be supplied with the data voltage from the drain electrode **175**. The pixel electrode **191** to which the data voltage is applied generates an electric field with the common electrode **270** of another display panel **200** (not shown) to which the common voltage is applied, thereby determining a direction of liquid crystal molecules **31** in the liquid crystal layer **3** interposed between the two electrodes **191** and **270**. The polarization of light passing through the liquid crystal layer **3** varies on the basis of the direction of the liquid crystal molecules determined as described above. The pixel electrode **191** and the common electrode **270** form a capacitor (hereinafter, referred to as a "liquid crystal capacitor") so as to maintain the applied voltage after the thin film transistor is turned off.

The pixel electrode **191** is opposite to the storage electrode line **131** such as the storage electrode **137** with the gate insulating layer **140** interposed therebetween, thereby forming a storage capacitor. The storage capacitor improves the voltage storage capacity of the liquid crystal capacitor. At this time, since the opening **183** is formed in the passivation layer **180**, only the gate insulating layer **140** exists between the pixel electrode **191** and the storage electrode **137**. Therefore, the distance between the pixel electrode **191** and the storage electrode line **131** becomes short, and thus the voltage storage capacity is improved.

At least the storage electrode line **131** disposed between the first and second sub-pixel electrodes **191a** and **191b** extends in a horizontal direction while being overlapped with both the first and second sub-pixel electrodes **191a** and **191b**. The gate line **121** extends below the first sub-pixel electrodes

191a, while at least parts of the gate line **121** overlap the two first sub-pixel electrodes **191a**.

The data line **171** disposed between the first and second sub-pixel electrodes **191a** and **191b** extends in a vertical direction, while at least parts of the data line **171** overlap both the first and second sub-pixel electrodes **191a** and **191b**. Among a plurality of data lines **171**, the data line **171** connected to the pixel electrode **191** through the contact hole **185** is referred to as a first data line **171s**. The data line **171** adjacent to the left of the first data line **171s** is referred to as a second data line **171l**, and the data line **171** adjacent to the right of the first data line **171s** is referred to as the third data line **171r**. At this time, each of the first and second sub-pixel electrodes **191a** and **191b** overlaps the first data line **171s**, the first sub-pixel electrode **191a** overlaps the second data line **171l**, and the second sub-pixel electrode **191b** overlaps the third data line **171r**.

The contact assistant **81** is connected to the end portion **129** of the gate line **121** through the contact hole **181**, and the contact assistant **82** is connected to the end portion **179** of the data line **171** through the contact hole **182**. The contact assistants **81** and **82** supplement the adhesive property between the end portion **129** of the gate line **121** and the external device and between the end portion **179** of the data line **171** and the external device.

Next, the upper display panel **200** will be explained.

A light blocking member **220** is formed on an insulation substrate **210** formed of, for example, transparent glass or plastic. The light blocking member **220** may include curved portions (not shown) corresponding to the curved edges of the pixel electrode **191**, and quadrangle portions (not shown) corresponding to the thin film transistor. The light blocking member **220** prevents light leakage between the pixel electrodes **191** and defines an opening region which faces the pixel electrode **191**.

A plurality of color filters **230** are formed on the substrate **210** and the light blocking member **220**. Most of the plurality of color filters **230** exist in a region surrounded by the light blocking member **220** and may extend along a column of pixel electrodes **191**. Each of the color filters **230** may display one of three primary colors, such as red, green, and blue.

An overcoat **250** is formed on the color filter **230** and the light blocking member **220**. The overcoat **250** may be formed of an organic insulator and functions to prevent the color filter **230** from being exposed and supply a flat surface. The overcoat **250** may be omitted.

The common electrode **270** is formed on the overcoat **250**. The common electrode **270** is formed of a transparent conductor such as ITO or IZO.

Alignment layers **11** and **21** may be formed inside the display panels **100** and **200**. These alignment layers **11** and **21** may be vertical alignment layers.

Polarizers (not shown) may be formed outside the display panels **100** and **200**. It is preferable that polarization axes of two polarizers be perpendicular to each other and have an angle of 45° with the curved edge of the sub-pixel electrodes **191a** and **191b**. In a case of a reflective liquid crystal display, one of the two polarizers may be omitted.

The liquid crystal display may include the polarizers **12** and **22**, retardation films, the display panels **100** and **200**, and a backlight unit (not shown) that supplies light to the liquid crystal layer **3**.

The liquid crystal layer **3** has positive dielectric anisotropy. The liquid crystal molecules of the liquid crystal layer **3** are arranged to be parallel to the upper and lower display panels when no electric field is applied.

Overcoming an alignment error occurring in the liquid crystal panel assembly will be described in detail with reference to FIG. 7.

FIG. 7 is a layout view illustrating a case where the alignment error occurs at the manufacturing process of the liquid crystal display shown in FIG. 4.

Referring to FIG. 7, all the data lines **171** are arranged while being inclined to the left side, as compared with the FIG. 4

Therefore, the overlapped area between the data line **171** and the pixel electrode **191** is different from the overlapped area shown in FIG. 4.

Parasitic capacitance is present between the data line **171** and the pixel electrode **191** which may affect the pixel electrode voltage. When data voltages having opposite polarities are applied to every two adjacent data lines **171**, the parasitic capacitances between each of the adjacent data lines **171** and the pixel electrode **191** are oppositely charged. Therefore, areas where one pixel electrode **191** overlaps the two data lines **171** to which opposite polarity data voltages are applied, the charge on the parasitic capacitance is neutralized. However, if an alignment error occurs between each of the data lines **171** and the pixel electrode **191**, the areas where the pixel electrode **191** overlaps the two data lines **171** are different from each other. Accordingly, the voltages of some of the pixel electrodes **191** may be lower or higher and the charge on the parasitic capacitance is not neutralized and the stripe defect occurs.

However, as described in the exemplary embodiment of the present invention, the stripe defect may be avoided by making the pixel electrode **191** include a first and a second sub-pixel electrode **191a** and **191b** that face each other in the diagonal direction.

As shown in FIG. 7, when the alignment error occurs, the area in which the first sub-pixel electrode **191a** overlaps the first data line **171s** increases, but the area in which the second sub-pixel electrode **191b** overlaps the first data line **171s** decreases. That is, even though the alignment error occurs, the area where the pixel electrode **191** overlaps the first data line **171s** to which a positive data voltage is applied is not changed. Further, even though the area in which the first sub-pixel electrode **191a** overlaps the second data line **171l** decreases, the area in which the second sub-pixel electrode **191b** overlaps the third data line **171r** increases. That is, even though the alignment error occurs, the area where the pixel electrode **191** overlaps the second or third data lines **171l** and **171r** to which a negative data voltage is applied is not changed. Therefore, the charge on the parasitic capacitance between the pixel electrode **191** and the data line **171** may be neutralized.

Hereinafter, a liquid crystal panel assembly according to another exemplary embodiment of the present invention will be described with reference to FIG. 8.

FIG. 8 is a layout view of the liquid crystal panel assembly according to another exemplary embodiment of the present invention.

Referring to FIG. 8, the liquid crystal panel assembly according to this exemplary embodiment of the present invention includes a lower display panel (not shown) and an upper display panel (not shown) that face each other, a liquid crystal layer (not shown) interposed therebetween, and a pair of polarizers (not shown) attached outside the display panels.

The layered structure of the liquid crystal panel assembly according to this exemplary embodiment of the present invention is substantially the same as the layered structure of the liquid crystal panel assembly shown in FIGS. 4 to 6.

Hereinafter, the lower display panel will be described. A plurality of gate conductors that include a plurality of gate lines **121** and a plurality of storage electrode lines **131** are formed on an insulation substrate (not shown). Each of the gate lines **121** includes gate electrodes **124** and end portions **129**. A gate insulating layer (not shown) is formed on the gate conductor **121**. A semiconductor island **154** is formed on the gate insulating layer (not shown). Further, a plurality of ohmic contacts (not shown) is formed on the semiconductor island **154**. The data lines **171** and the drain electrodes **175** which include source electrodes **173** and end portions **179** are formed on the ohmic contacts (not shown) and on the gate insulating layer **140** (not shown). A passivation layer (not shown) is formed on the data conductors **171** and **175** and the exposed semiconductor islands **154**. Further, the contact holes **181**, **182**, and **185** are formed on the passivation layer and the gate insulating layer. The pixel electrodes **191** and contact assistants **81** and **82** are formed on the passivation layer **180**. Further, an alignment film (not shown) is formed on the pixel electrodes **191**, the contact assistants **81** and **82**, and the passivation layer **180**.

Hereinafter, the upper display panel will be described. A light blocking member (not shown), color filters (not shown), an overcoat (not shown), a common electrode (not shown), and an alignment film (not shown) are formed on the insulation substrate (not shown).

However, the liquid crystal panel assembly shown in FIG. **8** is different from the liquid crystal panel assembly shown in FIGS. **4** to **6** in that the openings are not formed in the passivation layer **180** at portions where the storage electrodes **137** overlap the pixel electrodes **191**. Further, the drain electrodes **175** each include one end portion **177** having a wide extension that is opposite to the other end portion having a bar shape that is surrounded by the source electrodes **173**. The end portions **177** having a wide extension of the drain electrodes **175** overlap the storage electrodes **137**.

Each end portion **177** having a wide extension of the drain electrodes **175** and the pixel electrodes **191** overlaps a storage electrode **137** and a storage electrode line **131** so as to form the storage capacitor Cst. Further, the end portion **177** having a wide extension of the drain electrodes **175** improves the capacitance of the storage capacitor Cst.

Next, a liquid crystal panel assembly according to another exemplary embodiment of the present invention will be described in detail with reference to FIGS. **9** and **10**.

FIG. **9** is a layout view of a liquid crystal panel assembly according to another exemplary embodiment of the present invention. FIG. **10** is a cross-sectional view of the liquid crystal panel assembly shown in FIG. **9** taken along the line -.

The liquid crystal panel assembly according to the present exemplary embodiment includes lower and upper display panels **100** and **200** that face each other, a liquid crystal layer **3** that is interposed between the lower and upper display panels **100** and **200**, and a pair of polarizers **12** and **22**.

The layered structure of the liquid crystal panel assembly according to the present exemplary embodiment is substantially the same as the layered structure of the liquid crystal panel assembly shown in FIGS. **4** to **6**.

Hereinafter, the lower display panel **100** will be described. A plurality of gate conductors that include a plurality of gate lines **121** and a plurality of storage electrode lines **131** are formed on the insulation substrate **110**. The gate lines **121** include gate electrodes **124** and end portions **129**. A gate insulating layer **140** is formed on the gate conductor **121**. A semiconductor stripe **151** including a protruding portion **154** is formed on the gate insulating layer **140**. Further, a plurality of ohmic contacts **163** and **165** are formed on the semicon-

ductor stripe **151**. The source electrodes **173**, the data lines **171** that include end portions **179**, and the drain electrodes **175** are formed on the ohmic contacts **161**, **163**, and **165** and the gate insulating layer **140**.

A lower passivation layer **180p**, a color filter **230**, and an upper passivation layer **180q** are formed on the data conductors **171** and **175** and the exposed semiconductor islands **154**. Further, the contact holes **181**, **182**, **185p**, and **185q** are formed in the lower and upper passivation layers **180p** and **180q** and the gate insulating layer **140**. The openings **183p** and **183q** are formed in the lower and upper passivation layers **180p** and **180q**. The pixel electrodes **191** and contact assistants **81** and **82** are formed on the passivation layer **180**. Further, an alignment film **11** is formed on the pixel electrodes **191**, the contact assistants **81** and **82**, and the passivation layer **180**.

Hereinafter, the upper display panel will be described. A light blocking member **220**, an overcoat **250**, a common electrode **270**, and an alignment layer **21** are formed on the insulation substrate **210**.

The liquid crystal panel assembly shown in FIGS. **9** and **10** is different from the liquid crystal panel assembly shown in FIGS. **4** to **6** in that the pixel electrodes **191** are not separated and a region defined by the data lines **171** and the gate lines **121** has a rectangular shape.

Each data line **171** includes a first portion **171ta** and a second portion **171tb** that are not connected in a straight line. The first portion **171ta** is connected to the second portion **171tb** through a connection portion **178**. The entire surface of the first portion **171ta** overlaps a part of the pixel electrode **191** that supplies the data voltage, and the entire surface of the second portion **171tb** overlaps a part of an adjacent pixel electrode **191** that does not supply the data voltage.

On the basis of one pixel electrode **191**, a fourth data line **171t** indicates the data line **171** connected through the thin film transistor Q and a fifth data line **171j** indicates the data line **171** adjacent to the left side of the fourth data line **171t**. Further, a sixth data line **171k** indicates the data line **171** adjacent to the right side of the fourth data line **171t**. Therefore, one pixel electrode **191** overlaps the entire second portion **171tb** of the fourth data line **171t** and the entire first portion **171ja** of the fifth data line **171j**. On the basis of two adjacent pixel electrodes **191**, the second portion **171tb** of the fourth data line **171t** completely overlaps the first portion **171ka** of the sixth data line **171k**. That is, one pixel electrode **191** overlaps two adjacent data lines **171** to which data voltages having opposite polarities are applied.

Further, a light blocking member **132** is formed between adjacent pixel electrodes **191**. The light blocking member **132** includes a first light blocking member **134** that is adjacent to the first portion **171ta** of the data line **171t** and a second light blocking member **135** that is adjacent to the second portion **171tb** of the data line **171t**. The first light blocking member **134** is separated from the second light blocking member **135**, and the second light blocking member **135** extends from the storage electrode line **131**. The light blocking member **132** is formed of the same material as the storage electrode line **131**.

As described above, the data line **171** overlaps the pixel electrodes **191**. Therefore, a space is formed between the pixel electrodes **191**. A horizontal direction electric field is formed in the space between the two pixel electrodes **191** such that the liquid crystal molecules in the liquid crystal layer **3** are arranged in an unexpected direction, that is, in the horizontal direction. Then, light passes through this portion, which causes light leakage. The light blocking member **132** blocks light to prevent the light leakage.

15

Further, the semiconductor island **154** extends along the data lines **171** and the drain electrodes **175** to form a semiconductor stripe **151**, and an ohmic contact **163** extends along the data lines **171** to form an ohmic contact stripe **161**. The semiconductor stripe **151** has substantially the same shape as those of the data lines **171**, the drain electrodes **175**, and the ohmic contacts **161** and **165** under the drain electrodes **175** in a plan view.

According to a method of manufacturing a thin film transistor display panel according to an exemplary embodiment of the present invention, the data lines **171**, the drain electrodes **175**, the semiconductor stripe **151**, and the ohmic contacts **161** and **165** are formed by one photolithography process.

A photosensitive film used for the photolithography process has different thicknesses depending on position, and includes a first portion and a second portion in a descending order of thickness. The first portion is disposed in a wiring region where the data line **171** and the drain electrode **175** are disposed, and the second portion is disposed in a channel region of the thin film transistor.

The thickness of the photosensitive film may differ according to a plurality of methods. For example, the thickness of the photosensitive film may differ by providing a light transmitting area, a light blocking area, and a translucent area with an optical mask. A slit pattern, a lattice pattern, or a thin film having medium transmittance or medium thickness is provided on the translucent area. When using the slit pattern, it is preferable that the width of the slit or the interval between the slits is smaller than the resolution of the light exposer used for the photolithography process. Alternatively, a reflowable photosensitive film may be used. That is, the reflowable photosensitive film is formed by using a general exposure mask having a light transmitting area and a light blocking area. Then, the reflowable photosensitive film is reflowed such that the photosensitive film flows to a region where the photosensitive film does not remain.

With the above-described processing, the photolithography processes may be reduced, thereby making the manufacturing method simple.

The liquid crystal panel assembly according to the present exemplary embodiment is different from the liquid crystal panel assembly described above. That is, the color filters are not provided on the upper display panel **200**, but a plurality of color filters **230** are formed below the passivation layer **180** of the lower display panel **100**.

The color filters **230** extend in a vertical direction while being periodically curved along the column of the pixel electrode **191**. The color filter **230** does not exist in peripheral areas in which the end portion **129** of the gate line **121** and the end portion **179** of the data line **171** are disposed. The contact hole **185q** and the opening **183q** pass through the color filter **230**. The penetration holes **235** and **236** that are larger than the contact hole **185q** and the opening **183q** are formed in the color filter **230**.

The adjacent color filters **230** may function as the light blocking member for blocking light leakage between the adjacent pixel electrodes **191** that overlap the data line **171**. In this case, the light blocking member on the upper display panel **200** may be omitted, thereby making the process simple. The passivation layer **180p** is formed below the color filter **230**. The overcoat **250** of the common electrode panel **200** may be omitted.

The liquid crystal layer **3** of the liquid crystal display according to the present exemplary embodiment includes nematic liquid crystal with positive dielectric anisotropy. The liquid crystal molecules in the liquid crystal layer **3** of the

16

liquid crystal display according to the present exemplary embodiment are splay-arranged and then bend-arranged due to a bend voltage as shown in FIG. 9 so as to drive the display. A liquid crystal display including the liquid crystal layer **3** having the above-described liquid crystal molecules **31** is called an OCB (optically compensated bend) mode display. The liquid crystal display assembly driven in the OCB mode operates a normally white mode. That is, the liquid crystal display assembly displays a white color when no voltage is applied.

Hereinafter, the OCB mode will be described in detail with reference to FIGS. 11 and 12.

FIG. 11 is a view illustrating an alignment state of the liquid crystal molecules before a predetermined voltage is applied. FIG. 12 is a view illustrating an alignment state of the liquid crystal molecules after the predetermined voltage is applied.

Referring to FIG. 11, when the voltage is not applied, the liquid crystal molecules **31** in the vicinity of alignment layers **11** and **21** are arranged in a horizontal direction at a pre-tilt angle θ , in which one end of the liquid crystal molecule rises toward a rubbing direction. Therefore, the liquid crystal molecules **31** are arranged in parallel to the surface of the substrates **110** and **210** and are symmetrical with respect to a surface that is separated from the surfaces of the two alignment layers **11** and **21** at the same distance (hereinafter, referred to as a "center surface"). This alignment is called a splay alignment.

In the above-described state, if a predetermined voltage, that is, a bend voltage, is applied to the liquid crystal molecules **31**, an electric field is generated in the liquid crystal layer **3** and the alignment of the liquid crystal molecule **31** is changed from the splay alignment to another alignment.

More specifically, when a voltage is applied to the electrodes (not shown) of the two display panels **100** and **200** and the electric field that is vertical to the surfaces of the two display panels **100** and **200** is generated in the liquid crystal layer **3**, the liquid crystal molecules **31** in the vicinity of the alignment films **11** and **21** react to the electric field and rise. However, since the rising directions of the liquid crystal molecules **31** in the vicinity of the two alignment films **11** and **21** are the same, the rising directions of the liquid crystal molecules **31** collide with each other at the middle portion of the liquid crystal layer **3**, causing a large stress. Therefore, the alignment of the liquid crystal molecules **31** changes to a twist alignment which is stable from the viewpoint of energy. This is called a transient splay alignment.

In this state, as shown in FIG. 12, when a higher electric field is applied, the alignment of the liquid crystal molecules **31** of the liquid crystal layer changes to a bend alignment. The alignment transition of the liquid crystal molecules **31** should uniformly occur in all the liquid crystal capacitors Clc of the liquid crystal panel assembly **300**.

The characteristics of the liquid crystal panel assembly shown in FIGS. 4 to 6 may be applied to the liquid crystal panel assembly shown in FIGS. 9 and 10.

Hereinafter, a case where the alignment error occurs in the liquid crystal panel assembly according to another exemplary embodiment of the present invention will be described in detail with reference to FIG. 13.

FIG. 13 is a layout view illustrating a case where the alignment error occurs in the liquid crystal panel assembly shown in FIG. 9.

Referring to FIG. 13, all the data lines **171** are arranged while being inclined to the left side based on the pixel electrodes **191** as compared with FIG. 9. Therefore, the over-

17

lapped area between the data line 171 and the pixel electrode 191 is different from the overlapped area shown in FIG. 9

Since the pixel electrode 191 sufficiently overlaps the first portion 171_{ta} of the fourth data line 171_t and the second portion 171_{jb} of the fifth data line 171_j, the overlapped area between the pixel electrode 191 and the fourth data line 171_t and the fifth data line 171_j to which the positive data voltage is applied is not changed even when the alignment error shown in FIG. 10 occurs. Therefore, the positive parasitic capacitance and the negative parasitic capacitance between the pixel electrode 191 and the data line 171 are maintained to be the same as each other. Accordingly, it is possible to remove the parasitic capacitance generated between the pixel electrode 191 and the data line 171.

According to the present invention, it is possible to prevent a coupling defect or a stripe defect while sufficiently securing the aperture ratio of the liquid crystal display.

While this invention has been described in connection with what is presently considered to be practical exemplary embodiments, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent alignments included within the spirit and scope of the appended claims.

What is claimed is:

1. A liquid crystal display comprising:

a substrate;

a gate line disposed on the substrate;

a data line intersecting with the gate line;

a thin film transistor connected to the gate line and the data line;

a first pixel electrode connected to the thin film transistor;

a second pixel electrode disposed adjacent to the first pixel electrode;

a storage electrode line disposed to be substantially parallel with the gate line; and

a first light blocking member connected to the storage electrode,

18

wherein the data line is arranged between the first pixel electrode and the second pixel electrode,

wherein the data line comprises a first region overlapping the first pixel electrode, a second region overlapping the second pixel electrode, and a third region connecting between the first region and the second region, and

wherein the first light blocking member does not overlap the first region and the second region.

2. The liquid crystal display of claim 1, wherein pixel electrodes disposed in a same column are alternatively connected to adjacent data lines configured to supply data voltages having opposite polarities with respect to a common voltage.

3. The liquid crystal display of claim 1, further comprising: a second light blocking member disposed between the second pixel electrode and the first region of the data line,

wherein the first light blocking member is disposed between the first pixel electrode and the second region of the data line.

4. The liquid crystal display of claim 3, wherein the first light blocking member and the second light blocking member are disconnected in a portion overlapping the third region of the data line.

5. The liquid crystal display of claim 4, wherein the storage electrode line is disconnected with the second light blocking member.

6. The liquid crystal display of claim 3, wherein the second light blocking member does not overlap the first region and the second region.

7. The liquid crystal display of claim 3, wherein the first light blocking member overlaps the third region.

8. The liquid crystal display of claim 3, wherein the second light blocking member overlaps the third region.

9. The liquid crystal display of claim 1, wherein the third region is substantially parallel with the gate line.

* * * * *

专利名称(译)	液晶显示器		
公开(公告)号	US8711302	公开(公告)日	2014-04-29
申请号	US12/954463	申请日	2010-11-24
[标]申请(专利权)人(译)	金东GYU		
申请(专利权)人(译)	金东GYU		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KIM DONG GYU		
发明人	KIM, DONG-GYU		
IPC分类号	G02F1/1333 G02F1/1343		
CPC分类号	G02F2001/134345 G09G2300/0491 G02F1/136286 G02F1/134309 G02F1/1395 G09G2300/0417 G09G3/3614 G09G3/3651		
审查员(译)	NGUYEN , 龚便		
优先权	1020060125428 2006-12-11 KR		
其他公开文献	US20110069259A1		
外部链接	Espacenet USPTO		

摘要(译)

一种液晶显示器，包括：多个像素电极，每个像素电极具有在对角线方向上彼此面对的第一子像素电极和第二子像素电极；多条栅极线；多条数据线与多条栅极线交叉并至少部分地与像素电极重叠。

