



US007349056B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 7,349,056 B2**
(45) **Date of Patent:** **Mar. 25, 2008**

(54) **LIQUID CRYSTAL DISPLAY DEVICE AND METHOD OF FABRICATING THE SAME**

(75) Inventors: **Jong Woo Kim**, Kyongsangbuk-do (KR); **Sung Chun Kang**, Kyongsangbuk-do (KR); **Young Hun Ha**, Kyongsangbuk-do (KR)

(73) Assignee: **LG.Philips LCD Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/318,159**

(22) Filed: **Dec. 13, 2002**

(65) **Prior Publication Data**

US 2003/0117541 A1 Jun. 26, 2003

(30) **Foreign Application Priority Data**

Dec. 22, 2001 (KR) 10-2001-0083219

(51) **Int. Cl.**

G02F 1/1339 (2006.01)

(52) **U.S. Cl.** **349/153**; 349/190

(58) **Field of Classification Search** 349/149–152, 349/153–155, 187, 190

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,978,580 A	9/1976	Leupp et al.
4,094,058 A	6/1978	Yasutake et al.
4,653,864 A	3/1987	Baron et al.
4,691,995 A	9/1987	Yamazaki et al.
4,775,225 A	10/1988	Tsuboyama et al.
5,247,377 A	9/1993	Omeis
5,263,888 A	11/1993	Ishihara et al.
5,379,139 A	1/1995	Sato et al.
5,406,989 A	4/1995	Abe
5,499,128 A	3/1996	Hasegawa et al.
5,507,323 A	4/1996	Abe

5,511,591 A	4/1996	Abe
5,539,545 A	7/1996	Shimizu et al.

5,548,429 A	8/1996	Tsujita
-------------	--------	---------

5,642,214 A	6/1997	Ishii
-------------	--------	-------

5,680,189 A	10/1997	Shimizu et al.
-------------	---------	----------------

5,684,555 A *	11/1997	Shiba et al. 349/149
---------------	---------	---------------------------

5,742,370 A	4/1998	Kim
-------------	--------	-----

5,757,451 A	5/1998	Miyazaki et al.
-------------	--------	-----------------

5,852,484 A	12/1998	Inoue et al.
-------------	---------	--------------

5,854,664 A	12/1998	Inoue et al.
-------------	---------	--------------

5,861,932 A	1/1999	Inata et al.
-------------	--------	--------------

5,875,922 A	3/1999	Chastine
-------------	--------	----------

5,952,676 A	9/1999	Sato et al.
-------------	--------	-------------

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1 003 066 A1 5/2000

(Continued)


Primary Examiner—Michael H. Caley

(74) *Attorney, Agent, or Firm*—McKenna Long & Aldridge LLP

(57) **ABSTRACT**

A liquid crystal display device and a method of fabricating the same are disclosed in the present invention. The liquid crystal display device includes a first substrate having a thin film transistor array and a common line with a UV-ray irradiation path passing UV-rays, a second substrate having a color filter array, a sealant between the first and second substrates over the common line, and a liquid crystal layer between the first and second substrates.

9 Claims, 7 Drawing Sheets



U.S. PATENT DOCUMENTS

5,956,112 A 9/1999 Fujimori et al.
 6,001,203 A * 12/1999 Yamada et al. 156/106
 6,011,609 A 1/2000 Kato
 6,016,178 A 1/2000 Kataoka
 6,016,181 A 1/2000 Shimada
 6,055,035 A 4/2000 Von Gutfeld
 6,118,509 A * 9/2000 Miyake 349/153
 6,163,357 A 12/2000 Nakamura
 6,219,126 B1 4/2001 Von Gutfeld
 6,226,067 B1 5/2001 Nishiguchi
 6,236,445 B1 5/2001 Foschaar et al.
 6,292,249 B1 * 9/2001 Kane et al. 349/155
 6,304,306 B1 10/2001 Shiomi
 6,304,311 B1 10/2001 Egami
 6,320,638 B1 * 11/2001 Youn 349/154
 6,337,730 B1 1/2002 Ozaki et al.
 6,414,733 B1 7/2002 Ishikawa
 6,424,394 B1 * 7/2002 Morii 349/110
 6,473,147 B1 * 10/2002 Nakahara et al. 349/153
 6,665,039 B1 * 12/2003 Glowonia et al. 349/153

FOREIGN PATENT DOCUMENTS

JP 51-65656 6/1976
 JP 57-38414 3/1982
 JP 57-038414 3/1982
 JP 57-88428 6/1982
 JP 57-088428 6/1982
 JP 58-27126 2/1983
 JP 58-027126 2/1983
 JP 59-057221 4/1984
 JP 59-195222 11/1984
 JP 60-111221 6/1985
 JP 60-164723 8/1985
 JP 60-217343 10/1985
 JP 61-7822 1/1986
 JP 61-007822 1/1986
 JP 61-055625 3/1986
 JP 61-55625 3/1986
 JP S62-054225 3/1987
 JP S62-054228 3/1987
 JP S62-054229 3/1987
 JP 62-089025 4/1987
 JP 62-89025 4/1987
 JP 62-90622 4/1987
 JP 62-090622 4/1987
 JP 62-205319 9/1987
 JP 63-109413 5/1988
 JP 63-110425 5/1988
 JP 63-128315 5/1988
 JP 63-311233 12/1988
 JP H03-009549 1/1991
 JP H05-036425 2/1993
 JP H05-036426 2/1993
 JP H05-107533 4/1993
 JP 05-127179 5/1993
 JP 5-127179 5/1993
 JP 05-154923 6/1993
 JP 05-265011 10/1993
 JP 5-265011 10/1993
 JP 05-281557 10/1993
 JP 5-281557 10/1993
 JP 5-281562 10/1993
 JP 05-281562 10/1993
 JP H06-018829 1/1994
 JP 06-051256 2/1994
 JP 6-51256 2/1994
 JP H06-064229 3/1994
 JP 06-148657 5/1994
 JP 6-148657 5/1994
 JP 06-160871 6/1994

JP 6-160871 6/1994
 JP H06-194637 7/1994
 JP 06-235925 8/1994
 JP 6235925 8/1994
 JP 6-265915 9/1994
 JP 06-265915 9/1994
 JP 06-313870 11/1994
 JP 07-084268 3/1995
 JP 07-128674 5/1995
 JP 7-128674 5/1995
 JP 07-181507 7/1995
 JP 7-181507 7/1995
 JP H07-275770 10/1995
 JP H07-275771 10/1995
 JP H08-076133 3/1996
 JP 08-095066 4/1996
 JP 8-95066 4/1996
 JP 08-101395 4/1996
 JP 8-106101 4/1996
 JP 08-106101 4/1996
 JP 8101395 4/1996
 JP H08-110504 4/1996
 JP H08-136937 5/1996
 JP 8-171094 7/1996
 JP 08-171094 7/1996
 JP 08-171097 7/1996
 JP 08-190099 7/1996
 JP 8-190099 7/1996
 JP H08-173874 7/1996
 JP 08-240807 9/1996
 JP 8-240807 9/1996
 JP 09-005762 1/1997
 JP 9-5762 1/1997
 JP 09-026578 1/1997
 JP 9-26578 1/1997
 JP H09-001026 1/1997
 JP 09-311340 2/1997
 JP 09-61829 3/1997
 JP 09-073075 3/1997
 JP 9-73075 3/1997
 JP 9-73096 3/1997
 JP 09-073096 3/1997
 JP 9061829 3/1997
 JP H09-094500 4/1997
 JP 9-127528 5/1997
 JP 09-127528 5/1997
 JP 09-230357 9/1997
 JP 9-230357 9/1997
 JP 09-281511 10/1997
 JP 9-281511 10/1997
 JP 9-311340 12/1997
 JP 10-123537 5/1998
 JP 10-123538 5/1998
 JP 10-142616 5/1998
 JP 10-177178 6/1998
 JP 10177178 6/1998
 JP H10-174924 6/1998
 JP 10-221700 8/1998
 JP 10-282507 10/1998
 JP 10-282512 10/1998
 JP 10-333157 12/1998
 JP 10-333159 12/1998
 JP 10333157 12/1998
 JP 10333159 12/1998
 JP 11-14953 1/1999
 JP 11-014953 1/1999
 JP 11-38424 2/1999
 JP 11-038424 2/1999
 JP 11-64811 3/1999
 JP 11-064811 3/1999
 JP 11-109388 4/1999
 JP 11-133438 5/1999
 JP 11-142864 5/1999

US 7,349,056 B2

Page 3

JP	11133438	5/1999	JP	2001-282126	10/2001
JP	11142864	5/1999	JP	2001-305563	10/2001
JP	11-174477	7/1999	JP	2001-330837	11/2001
JP	11-212045	8/1999	JP	2001-330840	11/2001
JP	11-248930	9/1999	JP	2001-356353	12/2001
JP	11248930	9/1999	JP	2001-356354	12/2001
JP	H11-262712	9/1999	JP	2002-014360	1/2002
JP	H11-264991	9/1999	JP	2002-14360	1/2002
JP	11-326922	11/1999	JP	2002-023176	1/2002
JP	11326922	11/1999	JP	2002-23176	1/2002
JP	11-344714	12/1999	JP	2002-49045	2/2002
JP	2000-002879	1/2000	JP	2002-049045	2/2002
JP	2000-029035	1/2000	JP	2002-079160	3/2002
JP	2000-29035	1/2000	JP	2002-080321	3/2002
JP	2000-056311	2/2000	JP	2002-82340	3/2002
JP	2000-066165	3/2000	JP	2002-082340	3/2002
JP	2000-066218	3/2000	JP	2002-090759	3/2002
JP	2000-093866	4/2000	JP	2002-90759	3/2002
JP	2000-137235	5/2000	JP	2002-90760	3/2002
JP	2000-147528	5/2000	JP	2002-090760	3/2002
JP	2000-193988	7/2000	JP	2002-107740	4/2002
JP	2000-241824	9/2000	JP	2002-122870	4/2002
JP	2000-284295	10/2000	JP	2002-122872	4/2002
JP	2000-292799	10/2000	JP	2002-122873	4/2002
JP	2000-310759	11/2000	JP	2002-131762	5/2002
JP	2000-310784	11/2000	JP	2002-139734	5/2002
JP	2000-338501	12/2000	JP	2002-156518	5/2002
JP	2001-005401	1/2001	JP	2002-169166	6/2002
JP	2001-005405	1/2001	JP	2002-169167	6/2002
JP	2001-013506	1/2001	JP	2002-182222	6/2002
JP	2001-033793	2/2001	JP	2002-202512	7/2002
JP	2001-042341	2/2001	JP	2002-202514	7/2002
JP	2001-051284	2/2001	JP	2002-214626	7/2002
JP	2001-066615	3/2001	JP	2002-229042	8/2002
JP	2001-091727	4/2001	JP	2002-236276	8/2002
JP	2001-117105	4/2001	JP	2002-258299	8/2002
JP	2001-117109	4/2001	JP	2002-236292	9/2002
JP	2001-133745	5/2001	JP	2002-277865	9/2002
JP	2001-133794	5/2001	JP	2002-277866	9/2002
JP	2001-133799	5/2001	JP	2002-277881	9/2002
JP	2001-142074	5/2001	JP	2002-287156	10/2002
JP	2001-147437	5/2001	JP	2002-296605	10/2002
JP	2001-154211	6/2001	JP	2002-311438	10/2002
JP	2001-166272	6/2001	JP	2002-311440	10/2002
JP	2001-166310	6/2001	JP	2002-311442	10/2002
JP	2001-183683	7/2001	JP	2002-323687	11/2002
JP	2001-201750	7/2001	JP	2002-323694	11/2002
JP	2001-209052	8/2001	JP	2002-333628	11/2002
JP	2001-209056	8/2001	JP	2002-333635	11/2002
JP	2001-209057	8/2001	JP	2002-333843	11/2002
JP	2001-209058	8/2001	JP	2002-341329	11/2002
JP	2001-209060	8/2001	JP	2002-341355	11/2002
JP	2001-215459	8/2001	JP	2002-341356	11/2002
JP	2001-222017	8/2001	JP	2002-341357	11/2002
JP	2001-235758	8/2001	JP	2002-341358	11/2002
JP	2001222017	8/2001	JP	2002-341359	11/2002
JP	2001-255542	9/2001	JP	2002-341362	11/2002
JP	2001-264782	9/2001	KR	2000-0035302	6/2000
JP	2001-272640	10/2001			
JP	2001-281675	10/2001			
JP	2001-281678	10/2001			

* cited by examiner

FIG. 1A
Related Art




FIG. 1B
Related Art




FIG. 2A
Related Art




FIG. 2B
Related Art




FIG. 2C
Related Art




FIG. 2D
Related Art




FIG. 2E
Related Art




FIG. 2F
Related Art




FIG. 2G
Related Art




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F





FIG. 5G



LIQUID CRYSTAL DISPLAY DEVICE AND METHOD OF FABRICATING THE SAME

This application claims the benefit of the Korean Patent Application No. P2001-083219 filed on Dec. 22, 2001, which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a display device, and more particularly, to a liquid crystal display device and a method of fabricating the same. Although the present invention is suitable for a wide scope of applications, it is particularly suitable for facilitating hardening of a photo-hardening sealant without modifying a black matrix layer pattern or increasing a size of the substrate.

2. Discussion of the Related Art

Generally, a liquid crystal display device has characteristics, such as low-voltage driving, low power consumption, full-color implementation, thin and compact size, and the like. Thus, it has been widely used for calculators, notebook computers, electronic watches, computer monitors, aircraft gauges, personal mobile terminals, and mobile phones.

Screens of liquid crystal display devices are becoming wider and larger in size. When a wide-screen liquid crystal display is fabricated by a liquid crystal injection method, it takes too much time. For this reason, a liquid crystal dropping method has been widely used to form a liquid crystal layer. The liquid crystal dropping method includes the steps of dropping liquid crystals on a substrate before bonding two substrates, forming a photo-hardening sealant, bonding the substrates, and hardening the sealant.

The photo-hardening sealant includes a photo-hardening sealant, which becomes a radical when UV-ray is applied thereto, and a single solution type sealant mixed with acrylate polymerized by the photo-hardening sealant. Hence, in order to harden the photo-hardening sealant, a portion where the sealant is disposed is exposed to UV-ray.

Moreover, the liquid crystal dropping method uses a column spacer attached to the substrate instead of a ball spacer dispersed on the substrate to obtain a uniform cell thickness.

A liquid crystal display device and a method of fabricating the same are explained by referring to the attached drawings as follows.

FIG. 1A illustrates a layout of a thin film transistor array substrate for a related art liquid crystal display device. FIG. 1B illustrates a cross-sectional view taken along line IB—IB in FIG. 1A.

As shown in FIG. 1A, a plurality of gate and data lines **80** and **90** are formed on an active area **120** of a thin film transistor array substrate **100** to cross each other and define a plurality of pixel areas. A pixel electrode **112** is formed at each of the pixel areas. And, a plurality of thin film transistors (not shown) are formed at each intersection between the gate and data lines **80** and **90** and apply signals of the data lines **90** to the pixel electrodes **112** by being turned on/off through signals of the gate lines **80**, respectively.

A common line **140** is formed at the circumference of the active area **120** to provide a common electrode on a color filter array substrate (not shown) with a common voltage. And, a plurality of silver (Ag) dots (not shown) are formed at the common line **140** for electrical connections to the common electrode on the color filter array substrate.

Moreover, a column spacer **105** is formed on the gate or data line **80** or **90** to maintain a uniform cell gap. And, a

photo-hardening sealant **110** is formed at the circumference of the active area **120** to surround the active area **120** for bonding the thin film array substrate and the color filter array substrate to each other. In this case, the photo-hardening sealant **110** is partially formed on the common line **140**.

Hence, in order to bond the substrates with the photo-hardening sealant **110** and to fix the photo-hardening sealant **110** thereto, UV-ray is applied from the color filter array substrate side or a thermo-hardening sealant is used instead of the photo-hardening sealant.

When the UV-ray is applied from the thin film transistor array substrate side, the UV-ray cannot be applied to the photo-hardening sealant **110** on the common line **140**, thereby degrading the adhesion since the photo-hardening sealant **110** is not hardened completely.

In FIG. 1B, an insulating layer **141** to form a gate insulating layer and a passivation layer is formed on the common line **140**, and the photo-hardening sealant **110** is deposited on the insulating layer **141**. Since the insulating layer **141** is transparent, the UV-ray is transmitted. However, since the common line **140** is opaque, the UV-ray is cut off by the common line **140**. Hence, the photo-hardening sealant **110** cannot be hardened by the UV-ray, thereby weakening the adhesion.

A related art method of fabricating a liquid crystal display device using a liquid crystal dropping method is explained in detail as follows.

FIGS. 2A to 2G illustrate layouts and cross-sectional views of a related art fabricating process of a liquid crystal display device.

In the method of fabricating a liquid crystal display device using a liquid crystal dropping method, a plurality of liquid crystal display panel is designed on a mother substrate. More specifically, a plurality of liquid crystal display panels are designed on the mother substrate to form a thin film transistor array and a color filter array on each of the corresponding substrates. Liquid crystals are dispensed on the substrate. A sealant is deposited on the substrate, and the substrates are bonded to each other. The bonded substrates are then cut into a plurality of unit liquid crystal display panels. A plurality of the liquid crystal display panels designed on a single substrate will be explained in the following descriptions.

Although not shown in FIG. 2A, a plurality of gate and data lines are arranged on a first substrate **100** to cross each other and define a plurality of pixel areas. A pixel electrode (not shown) is formed on each of the pixel areas. A plurality of thin film transistors (not shown) are formed at each intersection between the gate and data lines to apply signals of the data lines to the pixel electrodes by being turned on/off through signals of the gate lines. A common line (not shown) is formed on the first substrate **100** to supply a common electrode with a common voltage. Herein, a plurality of liquid crystal display panels **99** are arranged on the first substrate **100**.

Subsequently, a plurality of silver (Ag) dots **101** are formed on the common line of each of the liquid crystal display panels **99** to be electrically connected thereto.

As shown in FIG. 2B, liquid crystals **103** for the size of each liquid crystal display panel **99** is dropped on each of the liquid crystal display panels **99** of the first substrate **100**.

As shown in FIG. 2C, a photo-hardening sealant **110** is deposited at the circumference of each liquid crystal display panel **99** of the first substrate **100**.

As shown in FIG. 2D, a plurality of column spacers **105** are formed on a second substrate having a black matrix layer (not shown), a color filter layer (not shown), and a common

electrode (not shown) formed thereon. And, the second substrate **150** is turned over to be placed over the first substrate **100**.

Namely, the overturned second substrate **150** is fixed to an upper stage **170**, which enables movement in the Z-axis direction (i.e., vertical direction), of a bonding machine having a controllable vacuum chamber. And, the first substrate **100** is fixed to a lower stage **160**, which enables movement in the XY-axes direction (i.e., horizontal direction), of the bonding machine.

As shown in FIG. 2E, the first substrate **100** fixed to the lower stage **160** and the second substrate **150** fixed to the upper stage **170** are aligned. Then, the inside of the bonding machine is pumped down to have a desired vacuum condition. Hence, the first and second substrates **100** and **150** do not contact each other so as to form a first gap between the substrates **100** and **150**.

As shown in FIG. 2F, after both of the substrates are bonded to have the first gap, a gas or air is injected into the bonding machine under a vacuum condition to provide the inner space of the bonding machine with the atmospheric pressure. Since the space between the bonded substrates is in a vacuum state and the surrounding is in the atmospheric pressure, both of the substrates are pressurized by a difference between the pressure within the gap between the first and second substrates and the atmospheric pressure. In this case, both of the substrates are pressurized to have a cell gap by the column spacers **105**. Hence, the liquid crystals **103** are spread between the substrates to form a liquid crystal layer **103a**.

As shown in FIG. 2G, UV-ray is applied from the side of the second substrate **150** to harden the photo-hardening sealant **110**.

However, the related art liquid crystal display device and the method of fabricating the same have the following problems or disadvantages.

Since the common line on the first substrate blocks the UV-ray, the UV-ray should be applied to the first substrate from the upper side instead of the lower side.

Furthermore, when the UV-ray is applied from the upper side of the substrate, either a pattern of the black matrix layer is modified or the size of the substrate is increased, thereby misaligning the sealant from the black matrix layer.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a liquid crystal display device and a method of fabricating the same that substantially obviates one or more of problems due to limitations and disadvantages of the related art.

Another object of the present invention is to provide a liquid crystal display device and a method of fabricating the same that facilitate hardening of the photo-hardening sealant without modifying the black matrix layer pattern or increasing the size of the substrate.

Additional features and advantages of the invention will be set forth in the description which follows and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, a liquid crystal display device includes a first substrate having a thin film transistor array and a

common line with a UV-ray irradiation path passing UV-rays, a second substrate having a color filter array, a sealant between the first and second substrates over the common line, and a liquid crystal layer between the first and second substrates.

In another aspect of the present invention, a method of fabricating a liquid crystal display device includes forming a thin film transistor array on an active area of a first substrate and a metal pattern as a UV-ray irradiation path passing UV-rays at a circumference of the active area, forming a color filter array on a second substrate, forming a sealant at the periphery of the active area of one of the first and second substrates to pass the UV-ray irradiation path, bonding the first and second substrates to each other after overturning the second substrate to dispose over the first substrate, and applying UV-ray to the photo-hardening sealant from a side of the first substrate through the UV-ray irradiation path to harden the sealant.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate embodiments of the invention and together with the description serve to explain the principle of the invention.

In the drawings:

FIG. 1A illustrates a layout of a thin film transistor array substrate for a related art liquid crystal display device;

FIG. 1B illustrates a cross-sectional view taken along line IB-IB in FIG. 1A;

FIGS. 2A to 2G illustrate layouts and cross-sectional views of a related art fabricating process of a liquid crystal display device;

FIG. 3 illustrates a cross-sectional view of a TN type liquid crystal display device according to the present invention;

FIG. 4A illustrates a layout of a thin film transistor array substrate for a liquid crystal display device according to the present invention;

FIG. 4B illustrates a cross-sectional view taken along line IVB-IVB in FIG. 4A; and

FIGS. 5A to 5G illustrate layouts and cross-sectional views of a fabricating process of a liquid crystal display device according to the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

Reference will now be made in detail to the illustrated embodiments of the present invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

FIG. 3 illustrates a cross-sectional view of a TN type liquid crystal display device according to the present invention.

As shown in FIG. 3, a gate line **349**, a gate electrode **309**, and a common line **440** of a thin film transistor are formed on a first substrate **300**. A gate insulating layer **320** is formed on the entire surface of the first substrate **300**. The common line **440** supplies a common electrode with a common

voltage and provides a UV-ray irradiation path through which UV-ray is applied to harden a sealant.

A semiconductor layer **315** is formed on the gate insulating layer **320** over the gate electrode **309**. A data line **330** having source and drain electrodes **316** and **317** is formed at both sides of the semiconductor layer **315**. Herein, when the source and drain electrodes **316** and **317** are formed over the gate line **349**, a storage electrode may be formed to provide a storage capacitor.

A passivation layer **325** is formed on the entire surface including the source and drain electrodes **316** and **317** to provide a contact hole on the drain electrode **316**. A pixel electrode **314** is formed on the passivation layer **325** in the pixel area to be connected to the drain electrode **316**. A first alignment layer **331** is formed on the entire surface including the pixel electrode **314**.

On a second substrate **350**, a black matrix **321** is formed on a surface facing into the first substrate **300** to prevent a light leakage from a portion excluding the pixel area. And, a R/G/B color filter layer **322** is embedded in the black matrix **321**.

A common electrode **326** is formed on the entire surface of the substrate including the color filter layer **322**. A column spacer **305** is formed over the black matrix **321**. A second alignment layer **335** is formed on the entire surface of the substrate including the column spacer **305**. A photo-hardening sealant **410** is formed between the first and second substrates **300** and **350** on the edge portion of the liquid crystal display panel. And, liquid crystals are formed between the first and second substrates **300** and **350** in the liquid crystal display panel area. At this point, the photo-hardening sealant **410** is formed over the common line **440** having a UV-ray irradiation path.

The above-explained structure, wherein the photo-hardening sealant **410** is formed on the common line **440** having a UV-ray irradiation path, may be applied to various modes of liquid crystal display devices, such as vertical alignment (VA) mode, optically compensated birefringence (OCB) mode, ferroelectric liquid crystal (FLC) mode, reflective mode, horizontal electric field mode, and TN mode.

FIG. 4A illustrates a layout of a thin film transistor array substrate for a liquid crystal display device according to the present invention. FIG. 4B illustrates a cross-sectional view taken along line IVB-IVB in FIG. 4A.

As shown in FIG. 4A, a plurality of gate and data lines **349** and **330** are formed on an active area **420** of a thin film transistor array substrate **400** to cross each other, thereby defining a plurality of pixel areas. A pixel electrode **412** is formed on each of the pixel areas. A plurality of thin film transistors (not shown) are formed at each intersection between the gate and data lines **349** and **330** to apply signals of the data lines **330** to the pixel electrodes **412** by being turned on/off through signals of the gate lines **349**.

A common line **440** is formed at the circumference of the active area **420** to provide a common electrode on a color filter array substrate (not shown) with a common voltage. And, a plurality of silver (Ag) dots (not shown) are formed at the common line **440** for electrical connection to the common electrode on the color filter array substrate.

Moreover, a column spacer **405** is formed on the gate line **349** or the data line **330** to maintain a uniform cell gap. And, a photo-hardening sealant **410** is formed at the circumference of the active area **420** to surround the active area **420** in order to bond the thin film array substrate and the color filter array substrate to each other. At this point, the photo-hardening sealant **410** is partially formed on the common line **440**. The column spacer **405** and the photo-hardening

sealant **410** may be formed on a second substrate **450** as a color filter array substrate instead of the first substrate **400**, which acts as a thin film transistor array substrate. A path **442** through which UV-ray **444** is applied is formed in the common line **440**. Alternatively, the common line **440** may be constructed with a plurality of lines each having a fine width to pass the UV-ray **444** (cf. magnified view in FIG. 4A). Furthermore, the path **442** can also be constructed with a plurality of circles or polygons formed along a portion on which the photo-hardening sealant **410** is formed.

Hence, after the bonding of both substrates by the photo-hardening sealant **410**, the UV-ray can be applied to both of the substrates from the backside of the thin film transistor array substrate **400** instead of the side of the color filter array substrate.

In FIG. 4B, an insulating layer **441** for a gate insulating layer or a passivation layer is formed on the common line pattern **440**, and the photo-hardening sealant **410** is deposited on the insulating layer **441**. Even if the common line pattern **440** is opaque cutting off the UV-ray, a path **442** is formed in the common line pattern **440** to pass sufficient UV-ray through to harden the photo-hardening sealant **410**. In this case, the path for UV-ray irradiation has an opening part having an opening ratio of at least about 50%.

The photo-hardening sealant **410** may be shrunk during the hardening process. Hence, a thermo-hardening sealant may be added to the photo-hardening sealant.

A method of fabricating a liquid crystal display device using a liquid crystal dropping method according to the present invention is explained in detail as follows.

FIGS. 5A to 5G illustrate layouts and cross-sectional views of a fabricating process of a liquid crystal display device according to the present invention.

As mentioned in the foregoing descriptions, more than one liquid crystal display panel is designed on a mother substrate. Thus, a plurality of liquid crystal display panels are designed on two substrates to form a thin film transistor array and a color filter array on the substrates, respectively. Liquid crystals are dropped on one of the substrates. A sealant is formed on one of the substrates, and both of the substrates are bonded to each other. The bonded substrates are then cut into a plurality of unit liquid crystal display panels.

In FIG. 5A, a plurality of gate and data lines (not shown) are arranged on a first substrate **400** to cross each other and define a plurality of pixel areas. A pixel electrode (not shown) is formed on each of the pixel areas. A plurality of thin film transistors (not shown) are formed at each intersection between the gate and data lines to apply signals of the data lines to the pixel electrodes by being turned on/off through signals of the gate lines. A common line (not shown) is formed on the first substrate **400** to supply a common electrode with a common voltage. Herein, a plurality of liquid crystal display panels **399** are arranged on the first substrate **400**, and the common line includes a UV-ray irradiation path, as described in FIGS. 4A and 4B.

Subsequently, a plurality of silver (Ag) dots **401** are formed on the common line of each liquid crystal display panel **399** to be electrically connected to the common line.

As shown in FIG. 5B, liquid crystals **403** for the size of each liquid crystal display panel **399** are dropped on each corresponding liquid crystal display panel **399** of the first substrate **400**.

As shown in FIG. 5C, a photo-hardening sealant **410** is deposited at the circumference of each liquid crystal display panel **399** of the first substrate **400**. The photo-hardening sealant **410** may also be deposited on a second substrate **450**.

As shown in FIG. 5D, a plurality of column spacers **405** are formed on the second substrate **450** having a black matrix layer (not shown), a color filter layer (not shown), and a common electrode (not shown). The second substrate **450** is turned over to be placed over the first substrate **400**. The column spacers **405** may also be formed on the first substrate **400**.

The overturned second substrate **450** fixed to an upper stage **470**, which enables movement in the Z-axis direction (i.e., vertical direction), of a bonding machine having a controllable vacuum chamber. The first substrate **400** is fixed to a lower stage **460**, which enables movement in the XY-axes direction (i.e., horizontal direction), of the bonding machine.

As shown in FIG. 5E, the first substrate **400** fixed to the lower stage **460** and the second substrate **450** fixed to the upper stage **470** are aligned. Then, the inside of the bonding machine is pumped down to have a desired vacuum condition. Subsequently, the first and second substrates **400** and **450** are bonded to each other. At this point, the first and second substrates **400** and **450** do not entirely contact each other, so as to form a first gap between the substrates **400** and **450**.

As shown in FIG. 5F, after both of the substrates are bonded to have the first gap, a gas or air is injected in the bonding machine under a vacuum condition to make an inner space of the bonding machine have the atmospheric pressure. Since the space between both of the substrates bonded through the sealant is in a vacuum condition and the surrounding is in atmospheric pressure, both of the substrates are pressurized by a difference between the pressure within the gap between the first and second substrates and the atmospheric pressure. In this case, both of the substrates are pressurized to have a cell gap by the column spacers **405**. Hence, the liquid crystals **403** are uniformly spread between the substrates to become a liquid crystal layer **403a**.

As shown in FIG. 5G, the bonded substrates are placed on a transparent quartz stage **480**. UV-ray is then applied from the side of the first substrate **400** to the photo-hardening sealant **410** to be hardened.

In the above-described embodiment of the present invention, the liquid crystals **403** are dropped on the first substrate **400** only. The photo-hardening sealant **410**, the silver (Ag) dots **401**, and the column spacers **405** may be formed on either the first substrate or the second substrate.

Accordingly, the liquid crystal display device and the method of fabricating the same according to the present invention have the following effects or advantages.

The UV-ray irradiation path is formed in the common line formed on the thin film transistor array substrate, thereby hardening the sealant by applying the UV-ray from the backside of the thin film transistor array substrate.

Moreover, since the sealant can be hardened by forming the UV-ray irradiation path in the common line of the thin film transistor array substrate, a substrate size does not have to be increased.

It will be apparent to those skilled in the art that various modifications and variations can be made in the liquid crystal display device and the method of fabricating the same of the present invention without departing from the spirit or scope of the inventions. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A liquid crystal display device, comprising:

- a first substrate having a thin film transistor array and a common line, the common line including at least a hole for a UV-ray irradiation path for passing UV-rays;
- a second substrate having a color filter array;
- a sealant bonding the first and second substrates over the common line, the sealant having a width narrower than the common line; and
- a liquid crystal layer between the first and second substrates,

wherein the hole in the common line extends substantially the length of the common line and extends to the same direction as the length of the sealant so that the sealant overlapping the common line is cured by the UV-rays passing through the hole.

2. The liquid crystal display device of claim 1, wherein the sealant includes a photo-hardening sealant.

3. The liquid crystal display device of claim 1, wherein the sealant includes a mixture of a photo-hardening sealant and a thermo-hardening sealant.

4. The liquid crystal display device of claim 1, wherein the common line is formed to be a plurality of lines having a width wide enough to pass the UV-rays.

5. The liquid crystal display device of claim 1, further comprising a column spacer between the first and second substrates.

6. The liquid crystal display device of claim 1, wherein the UV-ray irradiation path is formed to have an opening ratio of at least about 50%.

7. The liquid crystal display device of claim 1, wherein the UV-ray irradiation path includes a single UV-ray irradiation path.

8. The liquid crystal display device of claim 1, wherein the sealant has a width narrower than the UV-ray irradiation path through the common line.

9. The liquid crystal display device of claim 1, wherein the common line is formed at the circumference of an active area of the device.

* * * * *

专利名称(译)	液晶显示装置及其制造方法		
公开(公告)号	US7349056	公开(公告)日	2008-03-25
申请号	US10/318159	申请日	2002-12-13
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG.PHILIPS LCD CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	KIM JONG WOO KANG SUNG CHUN HA YOUNG HUN		
发明人	KIM, JONG WOO KANG, SUNG CHUN HA, YOUNG HUN		
IPC分类号	G02F1/1339 G02F1/1362		
CPC分类号	G02F1/1339 G02F2001/13415 G02F2001/136295		
优先权	1020010083219 2001-12-22 KR		
其他公开文献	US20030117541A1		
外部链接	Espacenet USPTO		

摘要(译)

在本发明中公开了一种液晶显示装置及其制造方法。该液晶显示装置包括具有薄膜晶体管阵列的第一基板和具有通过紫外线的紫外线照射路径的公共线，具有滤色器阵列的第二基板，在第一基板和第二基板之间的密封剂。公共线，以及第一和第二基板之间的液晶层。

