



US007499136B2

(12) **United States Patent**
Kubo

(10) **Patent No.:** **US 7,499,136 B2**
(45) **Date of Patent:** **Mar. 3, 2009**

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

(75) Inventor: **Masumi Kubo**, Ikoma (JP)

(73) Assignee: **Sharp Kabushiki Kaisha**, Osaka (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 562 days.

5,309,264 A	5/1994	Lien et al.
5,331,447 A	7/1994	Someya et al.
5,363,294 A	11/1994	Yamamoto et al.
5,408,345 A	4/1995	Mitsui et al.
5,414,547 A	5/1995	Matsuo et al.
5,434,687 A	7/1995	Kawata et al.
5,477,358 A	12/1995	Rosenblatt et al.
5,512,336 A	4/1996	Yamaha

(Continued)

(21) Appl. No.: **11/114,022**

(22) Filed: **Apr. 26, 2005**

(65) **Prior Publication Data**

US 2005/0237463 A1 Oct. 27, 2005

(30) **Foreign Application Priority Data**

Apr. 26, 2004 (JP) 2004-129248

(51) **Int. Cl.**
G02F 1/1343 (2006.01)

(52) **U.S. Cl.** **349/139; 349/130; 349/138**

(58) **Field of Classification Search** **349/139, 349/123, 129, 130, 138, 106**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,368,523 A	1/1983	Kawate
4,437,731 A	3/1984	Sudo et al.
4,955,698 A	9/1990	Knoll et al.
5,132,819 A	7/1992	Noriyama et al.
5,164,851 A	11/1992	Kanemori et al.
5,179,456 A	1/1993	Aizawa et al.
5,182,664 A	1/1993	Clerc
5,245,450 A	9/1993	Ukai et al.
5,260,818 A	11/1993	Wu
5,289,174 A	2/1994	Suzuki

FOREIGN PATENT DOCUMENTS

EP 0 884 626 A2 12/1998

(Continued)

OTHER PUBLICATIONS

Thomson-CSFILR, Jan. 2000, "Optical Compensation for Displays" (2 pages).


(Continued)

Primary Examiner—Thoi V Duong
(74) *Attorney, Agent, or Firm*—Nixon & Vanderhye P.C.

(57) **ABSTRACT**

The LCD of the present invention includes a first substrate, a second substrate, and a vertical alignment type liquid crystal layer provided therebetween. In each picture element region, a first electrode provided on the first substrate on the side of the liquid crystal layer has a solid portion formed of a conductive film and a non-solid portion with no conductive film provided. The liquid crystal layer has an orientation regulated by an inclined electric field produced above the non-solid portion of the first electrode when a voltage is applied. A portion of the liquid crystal layer above the solid portion includes a first region having a first thickness d_1 and a second region having a second thickness d_2 smaller than the first thickness d_1 and located near the non-solid portion.

49 Claims, 27 Drawing Sheets



U.S. PATENT DOCUMENTS

5,558,927 A 9/1996 Aruga et al.
 5,594,570 A 1/1997 Hirata et al.
 5,602,662 A 2/1997 Rosenblatt et al.
 5,608,556 A 3/1997 Koma
 5,636,043 A 6/1997 Uemura et al.
 5,646,702 A 7/1997 Akinwande et al.
 5,666,179 A 9/1997 Koma
 5,668,651 A 9/1997 Yamada et al.
 5,673,092 A 9/1997 Horie et al.
 5,699,137 A 12/1997 Kishimoto
 5,726,728 A 3/1998 Kondo et al.
 5,745,197 A 4/1998 Leung et al.
 5,748,276 A 5/1998 Uno et al.
 5,753,093 A 5/1998 Raguse et al.
 5,771,084 A 6/1998 Fujimori et al.
 5,995,176 A 11/1999 Sibahara
 6,061,117 A 5/2000 Horie et al.
 6,097,464 A 8/2000 Liu
 6,141,077 A 10/2000 Hirata et al.
 6,169,593 B1 1/2001 Kanaya et al.
 6,175,398 B1 1/2001 Yamada et al.
 6,195,140 B1 2/2001 Kubo et al.
 6,201,592 B1 3/2001 Terashita et al.
 6,222,599 B1 4/2001 Yoshida et al.
 6,246,453 B1 6/2001 Zhang et al.
 6,256,082 B1 7/2001 Suzuki et al.
 6,266,122 B1 7/2001 Kishimoto et al.
 6,285,431 B2* 9/2001 Lyu et al. 349/143
 6,287,649 B1 9/2001 Fukushima et al.
 6,330,047 B1 12/2001 Kubo et al.
 6,335,780 B1 1/2002 Kurihara et al.
 6,339,462 B1 1/2002 Kishimoto et al.
 6,340,998 B1 1/2002 Kim et al.
 6,341,002 B1 1/2002 Shimizu et al.
 6,342,938 B1 1/2002 Song et al.
 6,384,887 B1 5/2002 Yasuda et al.
 6,384,889 B1 5/2002 Miyachi et al.
 6,504,592 B1 1/2003 Takatori et al.
 6,512,564 B1 1/2003 Yoshida et al.
 6,542,212 B2 4/2003 Yoshida et al.
 6,567,144 B1* 5/2003 Kim et al. 349/128
 6,573,964 B1 6/2003 Takizawa et al.
 6,573,965 B1 6/2003 Liu et al.
 6,577,366 B1 6/2003 Kim et al.
 6,593,982 B2 7/2003 Yoon et al.
 6,600,539 B2 7/2003 Song
 6,614,497 B2 9/2003 Yamada
 6,630,975 B1 10/2003 Terashita
 6,657,695 B1 12/2003 Song et al.
 6,661,488 B1 12/2003 Takeda et al.
 6,710,825 B2 3/2004 Kubo et al.
 6,788,375 B2 9/2004 Ogishima et al.
 6,812,986 B2 11/2004 Takatori et al.
 6,822,723 B2 11/2004 Song et al.
 6,862,062 B2 3/2005 Kubo et al.
 6,924,856 B2 8/2005 Okumura et al.
 6,924,876 B2 8/2005 Kubo et al.
 6,950,160 B2 9/2005 Kubo et al.
 6,965,422 B2 11/2005 Kubo et al.
 2001/0024257 A1 9/2001 Kubo et al.

2001/0040546 A1 11/2001 Ohmuro et al.
 2002/0036740 A1 3/2002 Kubo et al.
 2002/0036744 A1 3/2002 Kubo et al.
 2002/0060764 A1 5/2002 Taniguchi et al.
 2002/0063834 A1 5/2002 Sawasaki et al.
 2002/0075436 A1 6/2002 Kubo et al.
 2002/0149728 A1 10/2002 Kubo et al.
 2002/0159012 A1 10/2002 Yamada
 2002/0171792 A1 11/2002 Kubota et al.
 2003/0107695 A1 6/2003 Kubo et al.
 2004/0041770 A1 3/2004 Kubo et al.
 2004/0169777 A1 9/2004 Tanaka et al.
 2004/0201810 A1 10/2004 Kubo et al.
 2005/0001947 A1 1/2005 Ogishima et al.
 2005/0001964 A1 1/2005 Kubo et al.
 2005/0140876 A1 6/2005 Kubo
 2005/0168674 A1 8/2005 Kubo
 2005/0174528 A1 8/2005 Kubo et al.

FOREIGN PATENT DOCUMENTS

JP 03-209440 9/1991
 JP 04-139402 5/1992
 JP 04-293018 10/1992
 JP 04-318816 11/1992
 JP 05-289108 11/1993
 JP 06-043461 2/1994
 JP 6-75238 A 3/1994
 JP 06-118909 4/1994
 JP 06-258649 9/1994
 JP 6-301036 A 10/1994
 JP 07-013164 1/1995
 JP 07-036058 2/1995
 JP 07-234400 9/1995
 JP 07-281176 10/1995
 JP 07-311383 11/1995
 JP 08-292423 11/1996
 JP 09-211445 8/1997
 JP 09-258266 10/1997
 JP 09-269509 10/1997
 JP 10-186330 7/1998
 JP 10-301114 A 11/1998
 JP 11-109417 A 4/1999
 JP 11-242225 9/1999
 JP 2000-47217 A 2/2000
 JP 2000-47253 2/2000
 JP 2000-075296 3/2000
 JP 2000-305110 11/2000
 JP 2001-343647 A 12/2001
 JP 2002-055343 A 2/2002
 KR 1999-0048949 7/1999
 WO 00/22677 4/2000

OTHER PUBLICATIONS

Jisaki et al., "Development of transfective LCD for high contrast and wide viewing angle by using homeotropic alignment", Asia Display/IDW '01, pp. 133-136.

Jignesh Gandhi et al., "Performance Enhancement of reflective CMOS Twisted Nematic Disp Projection Applications Using Compensating Films", pp. 1-6, reprinted from <http://www/hanoah.com/publications/sid99> paper Jignesh final pdf. (1999).

* cited by examiner

FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 3C





FIG. 3D








FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11






FIG. 12A



14J

FIG. 12B



14K

FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D




FIG. 13E




FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 17A




FIG. 17B




FIG. 17C




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 29





FIG. 28



LIQUID CRYSTAL DISPLAY DEVICE

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display device, and more particularly to a liquid crystal display device having a wide viewing angle characteristic and being capable of producing a high quality display.

2. Description of the Related Art

In recent years, liquid crystal displays (hereinafter, referred to as "LCDs") have been widely used. Mainstream LCDs so far have been twisted nematic type LCDs in which nematic liquid crystal molecules having a positive dielectric anisotropy are twisted. However, this type of LCDs have a problem of excessive viewing angle dependence, which is caused by the orientation of liquid crystal molecules.

In order to alleviate the viewing angle dependence, alignment-divided vertical alignment type LCDs have been developed, and are now used increasingly widely.

For example, Japanese Patent No. 2947350 discloses an MVA (Multi-domain Vertical Alignment) type LCD, which is one kind of alignment-divided vertical alignment type LCDs. An MVA type LCD displays images in a normally black (NB) mode using a vertical alignment type liquid crystal layer which is provided between a pair of electrodes. The MVA type LCD includes domain-regulating means (slits or ribs), such that liquid crystal molecules fall (are inclined) in a plurality of different directions in each pixel when a voltage is applied.

Japanese Laid-Open Patent Publication No. 2003-43525 discloses a CPA (Continuous Pinwheel Alignment) type LCD, which is one kind of alignment-divided vertical alignment type LCDs. In a CPA type LCD, a pair of electrodes face each other with a vertical alignment type liquid crystal layer interposed therebetween. One of the pair of electrodes includes a portion having no conductive layer (openings or cut-out portions), such that liquid crystal molecules are inclined radially in each pixel when a voltage is applied.

Recently, demands for displaying moving picture information have been rapidly increasing in personal computer monitors and mobile terminal devices (for example, cellular phones and PDAs) as well as in liquid crystal TVs. In order to realize high quality display of moving pictures in an LCD, the response time of the liquid crystal layer needs to be short (i.e., the response speed of the liquid crystal layer needs to be high). More specifically, it is required to reach a predetermined gray level within one-vertical scanning period (typically, within one frame).

As a driving method for improving the response characteristic of LCDs, a method of applying a voltage which is higher than the voltage corresponding to the gray level to be displayed (the predetermined gray level) is known. (The voltage higher than the voltage corresponding to the gray level to be displayed is referred to as an "overshoot voltage", and such a method is referred to as an "overshoot driving".) An application of an overshoot voltage (hereinafter, referred to as an "OS voltage") can improve the response characteristic in gray scale display. For example, Japanese Laid-Open Patent Publication No. 2000-231091 discloses an MVA type LCD which can be driven by overshoot driving (hereinafter, referred to as an "OS driving").

However, in order to drive an LCD by OS driving as disclosed in Japanese Laid-Open Patent Publication No. 2000-231091, a frame memory for storing image information needs to be additionally provided. This increases the production cost.

SUMMARY OF THE INVENTION

In order to overcome the problems described above, preferred embodiments of the present invention improve the response characteristic of an alignment-divided vertical alignment type LCD in a simple manner.

A first liquid crystal display device according to the present invention includes a first substrate; a second substrate; and a vertical alignment type liquid crystal layer provided between the first substrate and the second substrate. A plurality of picture element regions are each defined by a first electrode provided on one surface of the first substrate which is closer to the liquid crystal layer and a second electrode provided on the second substrate and opposing the first electrode with the liquid crystal layer therebetween. In each of the plurality of picture element regions, the first electrode includes a solid portion formed of a conductive film and a non-solid portion with no conductive film provided, and the liquid crystal layer has an orientation which is regulated by an inclined electric field produced above the non-solid portion of the first electrode when a voltage is applied between the first electrode and the second electrode. A portion of the liquid crystal layer above the solid portion of the first electrode includes a first region having a first thickness d_1 and a second region having a second thickness d_2 which is smaller than the first thickness d_1 , the second region being located in the vicinity of the non-solid portion. Thus, the above-described objective is achieved.

In a preferable embodiment, when a voltage is applied between the first electrode and the second electrode, the liquid crystal layer forms a plurality of first liquid crystal domains each taking a radially-inclined orientation above the solid portion by the inclined electric field.

In a preferable embodiment, the solid portion of the first electrode includes a plurality of unit solid portions, above each of which a respective first liquid crystal domain of the plurality of first liquid crystal domains is formed; and the second region of the portion of the liquid crystal layer above the solid portion is located above an edge portion of at least one unit solid portion of the plurality of unit solid portions.

A second liquid crystal display device according to the present invention includes a first substrate; a second substrate; and a vertical alignment type liquid crystal layer provided between the first substrate and the second substrate. A plurality of picture element regions are each defined by a first electrode provided on one surface of the first substrate which is closer to the liquid crystal layer and a second electrode provided on the second substrate and opposing the first electrode with the liquid crystal layer therebetween. In each of the plurality of picture element regions, the first electrode includes a solid portion formed of a conductive film and a non-solid portion with no conductive film provided, and when a voltage is applied between the first electrode and the second electrode, the liquid crystal layer forms a plurality of first liquid crystal domains each taking a radially-inclined orientation above the solid portion by an inclined electric field produced above the non-solid portion of the first electrode. The solid portion of the first electrode includes a plurality of unit solid portions, above each of which a respective first liquid crystal domain of the plurality of first liquid crystal domains is formed. A portion of the liquid crystal layer above at least one unit solid portion of the plurality of unit solid portions includes a first region having a first thickness d_1 and a second region having a second thickness d_2 which is smaller than the first thickness d_1 , the second region being located above an edge portion of the unit solid portion. Thus, the above-described objective is achieved.

In a preferable embodiment, a height of a surface of a portion of the at least one unit solid portion corresponding to the second region is higher than a height of a surface of a portion of the at least one unit solid portion corresponding to the first region.

In a preferable embodiment, the first substrate includes a transparent substrate and an interlayer insulating film provided between the transparent substrate and the first electrode; the interlayer insulating layer includes an inclining region where a height of one surface thereof closer to the liquid crystal layer continuously changes; and the edge portion of the at least one unit solid portion is located on the inclining region.

In a preferable embodiment, the interlayer insulating film includes a flat region where the height of the surface thereof closer to the liquid crystal layer is substantially constant; and the portion of the at least one unit solid portion corresponding to the first region is located on the flat region.

In a preferable embodiment, the interlayer insulating film is formed of a photosensitive transparent resin.

In a preferable embodiment, light incident on the liquid crystal layer is circularly-polarized light, and display is provided by modulating the circularly-polarized light by the liquid crystal layer.

In a preferable embodiment, an orientation in the plurality of first liquid crystal domains and an orientation in a portion of the liquid crystal layer above the non-solid portion are continuous with each other.

In a preferable embodiment, the plurality of unit solid portions each have a shape having rotational symmetry.

In a preferable embodiment, the plurality of unit solid portions are each generally circular.

In a preferable embodiment, the plurality of unit solid portions are each generally rectangular.

In a preferable embodiment, the plurality of unit solid portions are each generally rectangular with rounded corners.

In a preferable embodiment, the plurality of unit solid portions each have a shape with acute angle corner portions.

In a preferable embodiment, when a voltage is applied between the first electrode and the second electrode, the liquid crystal layer forms at least one second liquid crystal domain taking a radially-inclined orientation above the non-solid portion by the inclined electric field.

In a preferable embodiment, an orientation in the plurality of first liquid crystal domains and an orientation in the at least one second liquid crystal domain are continuous with each other.

In a preferable embodiment, the non-solid portion of the first electrode has at least one opening.

In a preferable embodiment, the at least one opening includes a plurality of openings, and at least a part of the plurality of openings have substantially the same shape and substantially the same size and form at least one unit lattice which is arranged so as to have rotational symmetry.

In a preferable embodiment, the at least a part of the plurality of openings each have a shape having rotational symmetry.

In a preferable embodiment, the non-solid portion of the first electrode has at least one cut-out portion.

In a preferable embodiment, the at least one cut-out portion includes a plurality of cut-out portions, and the plurality of cut-out portions are regularly arranged.

In a preferable embodiment, in each of the plurality of picture element regions, an area of the non-solid portion of the first electrode is smaller than an area of the solid portion of the first electrode.

In a preferable embodiment, the second substrate has an orientation-regulating structure in a region corresponding to at least one first liquid crystal domain of the plurality of first liquid crystal domains, the orientation-regulating structure exerting an orientation-regulating force for placing the liquid crystal molecules in the at least one first liquid crystal domain into a radially-inclined orientation at least in the presence of an applied voltage.

In a preferable embodiment, the orientation-regulating structure is provided in a region corresponding to a central portion of the at least one first liquid crystal domain.

In a preferable embodiment, the orientation-regulating structure exerts an orientation-regulating force for placing the liquid crystal molecules into a radially-inclined orientation also in the absence of an applied voltage.

In a preferable embodiment, the orientation-regulating structure is a protrusion protruding from the second substrate through the liquid crystal layer.

In a preferable embodiment, a thickness of the liquid crystal layer is defined by the protrusion protruding from the second substrate through the liquid crystal layer.

In a preferable embodiment, the non-solid portion of the first electrode is a slit provided in the first electrode.

A third liquid crystal display device according to the present invention includes a first substrate; a second substrate; and a vertical alignment type liquid crystal layer provided between the first substrate and the second substrate. A plurality of picture element regions are each defined by a first electrode provided on one surface of the first substrate which is closer to the liquid crystal layer and a second electrode provided on the second substrate and opposing the first electrode with the liquid crystal layer therebetween. In each of the plurality of picture element regions, the first electrode includes a solid portion formed of a conductive film and a slit, and the liquid crystal layer has an orientation which is regulated by an inclined electric field produced above the slit of the first electrode when a voltage is applied between the first electrode and the second electrode. A portion of the liquid crystal layer above the solid portion of the first electrode includes a first region having a first thickness d_1 and a second region having a second thickness d_2 which is smaller than the first thickness d_1 , the second region being located in the vicinity of the slit. Thus, the above-described objective is achieved.

In a preferable embodiment, a height of a surface of a portion of the solid portion of the first electrode corresponding to the second region is higher than a height of a surface of a portion of the solid portion corresponding to the first region.

In a preferable embodiment, the first substrate includes a transparent substrate and an interlayer insulating film provided between the transparent substrate and the first electrode; the interlayer insulating layer includes an inclining region where a height of one surface thereof closer to the liquid crystal layer continuously changes; and the portion of the solid portion of the first electrode corresponding to the second region is located on the inclining region.

In a preferable embodiment, the interlayer insulating film includes a flat region where the height of the surface thereof closer to the liquid crystal layer is substantially constant; and the portion of the solid portion of the first electrode corresponding to the first region is located on the flat region.

In a preferable embodiment, the interlayer insulating film is formed of a photosensitive transparent resin.

In a preferable embodiment, the first substrate includes a transparent substrate and a color filter layer provided between the transparent substrate and the first electrode; the color filter layer includes an inclining region where a height of one

surface thereof closer to the liquid crystal layer continuously changes; and the portion of the solid portion of the first electrode corresponding to the second region is located on the inclining region.

In a preferable embodiment, the color filter layer includes a flat region where the height of the surface thereof closer to the liquid crystal layer is substantially constant; and the portion of the solid portion of the first electrode corresponding to the first region is located on the flat region.

In a preferable embodiment, light incident on the liquid crystal layer is circularly-polarized light, and display is provided by modulating the circularly-polarized light by the liquid crystal layer.

In a preferable embodiment, the liquid crystal display device further includes a pair of polarization plates opposing each other with the liquid crystal layer therebetween, the pair of polarization plates have transmission axes generally perpendicular to each other, one of the transmission axes is located horizontal to a display plane, and the slit is extended in a direction which is inclined with respect to the one of the transmission axes.

In a preferable embodiment, the slit is extended in a direction which makes an angle of about 45° with the one of the transmission axes.

In a preferable embodiment, the second substrate has an orientation-regulating structure exerting an orientation-regulating force which is aligned with the orientation-regulating force provided by the inclined electric field at least in the presence of an applied voltage.

In a preferable embodiment, the orientation-regulating structure of the second substrate is a rib.

In a preferable embodiment, the orientation-regulating structure of the second substrate is a slit provided in the second electrode.

In a preferable embodiment, the first substrate further includes a switching element provided in correspondence with each of the plurality of picture element regions; and the first electrode is a picture element electrode provided in correspondence with each of the plurality of picture element regions and electrically connected to the switching element, and the second electrode is at least one counter electrode opposing the plurality of picture element electrodes.

In a preferable embodiment, a portion of the liquid crystal layer above the solid portion of the picture element electrode does not have the second region in the vicinity of an outer periphery of the picture element electrode.

A fourth liquid crystal display device according to the present invention includes a first substrate; a second substrate; and a vertical alignment type liquid crystal layer provided between the first substrate and the second substrate. A plurality of picture element regions are each defined by a first electrode provided on one surface of the first substrate which is closer to the liquid crystal layer and a second electrode provided on the second substrate and opposing the first electrode with the liquid crystal layer therebetween. In each of the plurality of picture element regions, the first electrode includes a solid portion formed of a conductive film and a slit, and the liquid crystal layer has an orientation which is regulated by an inclined electric field produced above the slit of the first electrode when a voltage is applied between the first electrode and the second electrode. The first substrate further includes a switching element provided in correspondence with each of the plurality of picture element regions. The first electrode is a picture element electrode provided in correspondence with each of the plurality of picture element regions and electrically connected to the switching element, and the second electrode is at least one counter electrode

opposing the plurality of picture element electrodes. A portion of the liquid crystal layer above the solid portion of the picture element electrode includes a first region having a first thickness d_1 and a second region having a second thickness d_2 which is larger than the first thickness d_1 , the second region being located in the vicinity of an outer periphery of the picture element electrode. Thus, the above-described objective is achieved.

In a preferable embodiment, a height of a surface of a portion of the solid portion corresponding to the second region is lower than a height of a surface of a portion of the solid portion corresponding to the first region.

In a preferable embodiment, the first substrate includes a transparent substrate and an interlayer insulating film provided between the transparent substrate and the first electrode; the interlayer insulating layer includes an inclining region where a height of one surface thereof closer to the liquid crystal layer continuously changes; and the portion of the solid portion corresponding to the second region is located on the inclining region.

In a preferable embodiment, the interlayer insulating film includes a flat region where the height of the surface thereof closer to the liquid crystal layer is substantially constant; and the portion of the solid portion corresponding to the first region is located on the flat region.

In a preferable embodiment, the interlayer insulating film is formed of a photosensitive transparent resin.

In a preferable embodiment, the liquid crystal display device further includes a pair of polarization plates opposing each other with the liquid crystal layer therebetween, the pair of polarization plates have transmission axes generally perpendicular to each other, one of the transmission axes is located horizontal to a display plane, and the slit is extended in a direction which is inclined with respect to the one of the transmission axes.

In a preferable embodiment, the slit is extended in a direction which makes an angle of about 45° with the one of the transmission axes.

According to the present invention, the liquid crystal layer above a solid portion of a first electrode has a predetermined thickness distribution. Therefore, the response characteristic of an alignment-divided vertical alignment type LCD can be improved in a simple manner. The present invention is preferably usable to a CPA type LCD and an MVA type LCD.

Other features, elements, processes, steps, characteristics and advantages of the present invention will become more apparent from the following detailed description of preferred embodiments of the present invention with reference to the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A and FIG. 1B schematically illustrate a structure of an LCD 100 of the present invention, wherein FIG. 1A is a plan view, and FIG. 1B is a cross-sectional view taken along line 1B-1B' of FIG. 1A.

FIG. 2A and FIG. 2B illustrate a liquid crystal layer 30 of the LCD 100 in the presence of an applied voltage thereacross, wherein FIG. 2A schematically illustrates a state where an orientation has just started to change (initial ON state), and FIG. 2B schematically illustrates a steady state.

FIG. 3A to FIG. 3D each schematically illustrate the relationship between an electric force line and an orientation of a liquid crystal molecule.

FIG. 4A to FIG. 4C each schematically illustrate an orientation of liquid crystal molecules in the LCD 100 as viewed in a substrate normal direction.

FIG. 5 is an enlarged cross-sectional view of an edge portion and the vicinity thereof of a unit solid portion of the LCD 100.

FIG. 6A to FIG. 6C schematically illustrate exemplary radially-inclined orientations of liquid crystal molecules.

FIGS. 7A and 7B are plan views each schematically illustrating another picture element electrode usable in an LCD of the present invention.

FIGS. 8A and 8B are plan views each schematically illustrating still another picture element electrode usable in an LCD of the present invention.

FIGS. 9A and 9B are plan views each schematically illustrating still another picture element electrode usable in an LCD of the present invention.

FIGS. 10A and 10B are plan views each schematically illustrating still another picture element electrode usable in an LCD of the present invention.

FIG. 11 is a plan view schematically illustrating still another picture element electrode usable in an LCD of the present invention.

FIGS. 12A and 12B are plan views each schematically illustrating still another picture element electrode usable in an LCD of the present invention.

FIG. 13A to FIG. 13E each schematically illustrate a counter substrate 200b including an orientation-regulating structure 28.

FIG. 14A and FIG. 14B schematically illustrate a CPA type LCD 200 of the present invention, wherein FIG. 14A is a plan view, and FIG. 14B is a cross-sectional view taken along line 14B-14B' of FIG. 14A.

FIG. 15A to FIG. 15C are cross-sectional views schematically illustrating the LCD 200, wherein FIG. 15A illustrates a state in the absence of an applied voltage, FIG. 15B illustrates a state where an orientation has just started to change (initial ON state), and FIG. 15C illustrates a steady state.

FIG. 16A and FIG. 16B schematically illustrate a structure of another CPA type LCD 200' of the present invention, wherein FIG. 16A is a plan view, and FIG. 16B is a cross-sectional view taken along line 16B-16B' of FIG. 16A.

FIG. 17A to FIG. 17C are cross-sectional views schematically illustrating the LCD 200', wherein FIG. 17A illustrates a state in the absence of an applied voltage, FIG. 17B illustrates a state where an orientation has just started to change (initial ON state), and FIG. 17C illustrates a steady state.

FIG. 18A to FIG. 18C are cross-sectional views schematically illustrating an LCD including protrusions (ribs) that function also as spacers, wherein FIG. 18A illustrates a state in the absence of an applied voltage, FIG. 18B illustrates a state where an orientation has just started to change (initial ON state), and FIG. 18C illustrates a steady state.

FIG. 19 is a cross-sectional view schematically illustrating protrusions having a side surface whose inclination angle with respect to the substrate plane significantly exceeds 90°.

FIG. 20 is a cross-sectional view schematically illustrating a variation of protrusions that function also as spacers.

FIG. 21 is a cross-sectional view schematically showing a basic structure of an MVA type LCD 300 of the present invention.

FIG. 22 is a plan view schematically showing a structure of two picture element regions of the LCD 300 of the present invention.

FIG. 23 is a cross-sectional view schematically showing a structure of the LCD 300 taken along line 23A-23A' of FIG. 22.

FIG. 24 schematically shows the orientation of liquid crystal molecules in the vicinity of a slit and in the vicinity of the outer periphery of a picture element electrode.

FIG. 25 is a cross-sectional view schematically showing a basic structure of another MVA type LCD 400 of the present invention.

FIG. 26 is a plan view schematically showing a structure of two picture element regions of the LCD 400 of the present invention.

FIG. 27 is a cross-sectional view schematically showing a structure of the LCD 400 taken along line 27A-27A' of FIG. 26.

FIG. 28 is a plan view schematically showing a structure of two picture element regions of still another MVA type LCD 500 of the present invention.

FIG. 29 is a cross-sectional view schematically showing a structure of the LCD 500 taken along line 28A-28A' of FIG. 28.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Hereinafter, preferred embodiments of the present invention will be described with reference to the accompanying drawings.

The following embodiments of the present invention will be described regarding an active matrix type LCD using thin film transistors (TFTs) as an example, but the present invention is not limited thereto and is also applicable to an active matrix LCD using an MIM structure or a simple matrix LCD. The following description will be given regarding a transmission type LCD as an example, but the present invention is not limited thereto and is also applicable to a reflection type LCD or a transmission-reflection type LCD.

Note that in the present specification, a region of an LCD corresponding to a "picture element", which is the minimum unit of display, will be referred to as a "picture element region". In a color LCD, a plurality of "picture elements" including R, G and B "picture elements" correspond to one "pixel". In an active matrix type LCD, a picture element region is defined by a picture element electrode and a counter electrode opposing the picture element electrode. In a passive matrix type LCD, a picture element region is defined as a region where one of column electrodes arranged in a stripe pattern crosses one of row electrodes also arranged in a stripe pattern perpendicular to the column electrodes. In an arrangement with a black matrix, strictly speaking, a picture element region is a portion, of each region across which a voltage is applied according to the intended display state, that corresponds to an opening of the black matrix.

Embodiment 1

The structure of one picture element region of a CPA type LCD 100 according to the present embodiment will now be described with reference to FIG. 1A and FIG. 1B. In the following description, a color filter and a black matrix are omitted for the sake of simplicity. In the figures, each element having substantially the same function as the corresponding element in the LCD 100 will be denoted by the same reference numeral and will not be further described. FIG. 1A is a plan view illustrating the picture element region of the LCD 100 as viewed in the substrate normal direction, and FIG. 1B is a cross-sectional view taken along line 1B-1B' of FIG. 1A. FIG. 1B illustrates a state where no voltage is applied across a liquid crystal layer.

The LCD 100 includes an active matrix substrate (hereinafter referred to as a "TFT substrate") 100a, a counter substrate (referred to also as a "color filter substrate") 100b, and a liquid crystal layer 30 provided between the TFT substrate

100a and the counter substrate 100b. Liquid crystal molecules 30a of the liquid crystal layer 30 have a negative dielectric anisotropy, and are aligned vertical to the surface of a vertical alignment film (not shown), as illustrated in FIG. 1B, in the absence of an applied voltage across the liquid crystal layer 30 by virtue of the vertical alignment film as a vertical alignment layer, which is provided on one surface of each of the TFT substrate 100a and the counter substrate 100b that is closer to the liquid crystal layer 30. This state is described as the liquid crystal layer 30 being in a vertical alignment. Note, however, that the liquid crystal molecules 30a of the liquid crystal layer 30 in a vertical alignment may slightly incline from the normal to the surface of the vertical alignment film (the surface of the substrate) depending upon the type of vertical alignment film or the type of liquid crystal material used. Generally, a vertical alignment is defined as a state where the axis of the liquid crystal molecules (referred to also as the "axial orientation") is oriented at an angle of about 85° or more with respect to the surface of the vertical alignment film.

The TFT substrate 100a of the LCD 100 includes a transparent substrate (e.g., a glass substrate) 11 and a picture element electrode 14 provided on the surface of the transparent substrate 11. The counter substrate 100b includes a transparent substrate (e.g., a glass substrate) 21 and a counter electrode 22 provided on the surface of the transparent substrate 21. The orientation of the liquid crystal layer 30 changes in each picture element region according to the voltage applied between the picture element electrode 14 and the counter electrode 22, which are arranged so as to oppose each other via the liquid crystal layer 30. A display is produced by utilizing a phenomenon that the polarization or amount of light passing through the liquid crystal layer 30 changes along with the change in the orientation of the liquid crystal layer 30.

Next, the structure and the function of the picture element electrode 14 provided in the CPA type LCD 100 will be described.

As illustrated in FIG. 1A and FIG. 1B, the picture element electrode 14 includes a solid portion 14a formed of a conductive film (e.g., an ITO film or an aluminum film) and a non-solid portion 14b with no conductive film provided therein.

The solid portion 14a includes a plurality of regions each substantially surrounded by the non-solid portion 14b (each of such regions will be referred to as a "unit solid portion 14a'"). The unit solid portions 14a' have substantially the same shape and substantially the same size as one another, and each solid portion 14a' has a generally circular shape. Typically, the plurality of unit solid portions 14a' are electrically connected together in each picture element region.

The non-solid portion 14b includes a plurality of openings 14b1, which have substantially the same shape and substantially the same size as one another, and are arranged so that the respective centers thereof form a square lattice pattern. The unit solid portion 14a' at the center of the picture element electrode 14 is substantially surrounded by four openings 14b1 whose respective centers are located at the four lattice points that form one unit lattice. Each of the openings 14b1 has a generally star-like shape having four quarter-arc-shaped sides (edges), with a four-fold rotation axis at the center among the four sides.

The non-solid portion 14b further includes a plurality of cut-out portions 14b2. The plurality of cut-out portions 14b2 are located at edge portions of the picture element region. The cut-out portions 14b2, which are located in areas corresponding to the sides of the picture element region, each have a shape corresponding to about a half of the shape of each

opening 14b1. The cut-out portions 14b2, which are located in areas corresponding to the corners of the picture element region, each have a shape corresponding to about a quarter of the shape of each opening 14b1. The unit solid portions 14a' which are located in the edge portions of the picture element region are each substantially surrounded by the respective cut-out portions 14b2 and the respective openings 14b1. The cut-out portions 14b2 are regularly arranged, and the openings 14b1 and the cut-out portions 14b2 form unit lattices in the entirety of the picture element region (to the end portions thereof). The openings 14b1 and the cut-out portions 14b2 are formed by patterning a conductive film which is used for the picture element electrode 14.

When a voltage is applied between the picture element electrode 14 having such a structure as described above and the counter electrode 22, an inclined electric field is produced around (near the outer periphery of) the solid portion 14a, i.e., at the edge portion of the non-solid portion 14b, thereby producing a plurality of liquid crystal domains each taking a radially-inclined orientation. The liquid crystal domain is produced in each region corresponding to the opening 14b1 and in each region corresponding to the unit solid portion 14a'.

The picture element electrode 14 in this embodiment is square, but the shape of the picture element electrode 14 is not limited thereto. A general shape of the picture element electrode 14 is close to a rectangle (encompassing a square and an oblong rectangle), so that the openings 14b1 and the cut-out portions 14b2 can be regularly arranged in a square lattice pattern. Even when the picture element electrode 14 is not rectangular, the effects of the present invention are provided as long as the openings 14b1 and the cut-out portions 14b2 are arranged regularly (e.g., in a square lattice pattern as described above) such that liquid crystal domains are formed in the entirety of the picture element region.

The mechanism by which liquid crystal domains are formed by an inclined electric field as described above will be described with reference to FIG. 2A and FIG. 2B. FIG. 2A and FIG. 2B each illustrate the liquid crystal layer 30 shown in FIG. 1B with a voltage being applied thereacross. FIG. 2A schematically illustrates a state where the orientation of the liquid crystal molecules 30a has just started to change (initial ON state) according to the voltage applied across the liquid crystal layer 30. FIG. 2B schematically illustrates a state where the orientation of the liquid crystal molecules 30a has changed and become steady according to the applied voltage. Curves EQ in FIG. 2A and FIG. 2B denote equipotential lines.

When the picture element electrode 14 and the counter electrode 22 are at the same potential (a state where no voltage is applied across the liquid crystal layer 30), the liquid crystal molecules 30a in each picture element region are aligned vertical to the surfaces of the substrates 11 and 21, as illustrated in FIG. 1B.

When a voltage is applied across the liquid crystal layer 30, a potential gradient represented by the equipotential lines EQ shown in FIG. 2A (perpendicular to the electric force line) is produced. The equipotential lines EQ, in the liquid crystal layer 30 located between the solid portion 14a of the picture element electrode 14 and the counter electrode 22, are parallel to the surfaces of the solid portion 14a and the counter electrode 22; and drop in a region corresponding to the non-solid portion 14b of the picture element region. An inclined electric field represented by an inclined portion of the equipotential lines EQ is produced in the liquid crystal layer 30 above an edge portion EG of the non-solid portion 14b (at the periph-

eral portion of, and within, the non-solid portion **14b**, including the boundary between the solid portion **14a** and the non-solid portion **14b**).

A torque acts upon the liquid crystal molecules **30a** having a negative dielectric anisotropy so as to direct the axial orientation of the liquid crystal molecules **30a** to be parallel to the equipotential lines EQ (perpendicular to the electric force line). Therefore, as indicated by arrows in FIG. 2A, the liquid crystal molecules **30a** above the right edge portion EG of each non-solid portion **14b** incline (rotate) clockwise, and the liquid crystal molecules **30a** above the left edge portion EG of each non-solid portion **14b** incline (rotate) counterclockwise. As a result, the liquid crystal molecules **30a** above the edge portions EG are oriented parallel to the corresponding portions of the equipotential lines EQ.

Referring to FIG. 3A to FIG. 3D, the change in the orientation of the liquid crystal molecules **30a** will now be described in greater detail.

When an electric field is produced in the liquid crystal layer **30**, a torque acts upon the liquid crystal molecules **30a** having a negative dielectric anisotropy so as to direct the axial orientation thereof to be parallel to an equipotential line EQ. As illustrated in FIG. 3A, when an electric field represented by an equipotential line EQ perpendicular to the axial orientation of the liquid crystal molecule **30a** is produced, either a torque urging the liquid crystal molecule **30a** to incline clockwise or a torque urging the liquid crystal molecule **30a** to incline counterclockwise is produced with the same probability. Therefore, the liquid crystal layer **30** between the pair of parallel plate-shape electrodes opposing each other has some liquid crystal molecules **30a** that are subjected to a clockwise torque and some other liquid crystal molecules **30a** that are subjected to a counterclockwise torque. As a result, the transition to the intended orientation according to the voltage applied across the liquid crystal layer **30** may not proceed smoothly.

When, as illustrated in FIG. 2A, an electric field represented by a portion of the equipotential lines EQ inclined with respect to the axial orientation of the liquid crystal molecules **30a** (an inclined electric field) is produced at the edge portion EG of the non-solid portion **14b** of the LCD **100** of the present invention, the liquid crystal molecules **30a** incline in whichever direction (the counterclockwise direction in the illustrated example) that requires less rotation for the liquid crystal molecules **30a** to be parallel to the equipotential lines EQ, as illustrated in FIG. 3B. The liquid crystal molecules **30a** in a region where an electric field represented by an equipotential line EQ perpendicular to the axial orientation of the liquid crystal molecules **30a** is inclined in the same direction as the liquid crystal molecules **30a** located on the inclined portion of the equipotential lines EQ, so that the orientation thereof is continuous (in conformity) with the orientation of the liquid crystal molecules **30a** located on the inclined portion of the equipotential lines EQ as illustrated in FIG. 3C. When, as illustrated in FIG. 3D, an electric field represented by an equipotential line EQ having a continuous concave/convex pattern is produced, the liquid crystal molecules **30a** located on a flat portion of the equipotential line EQ are oriented so as to conform with the orientation direction defined by the liquid crystal molecules **30a** located on adjacent inclined portions of the equipotential line EQ. The phrase "being located on an equipotential line EQ" as used herein means "being located within an electric field that is represented by the equipotential line EQ".

The change in the orientation of the liquid crystal molecules **30a**, starting from those that are located on the inclined portion of the equipotential line EQ, proceeds as described

above and reaches a steady state, which is schematically illustrated in FIG. 2B. The liquid crystal molecules **30a** located around the central portion of the opening **14b1** are influenced substantially equally by the respective orientations of the liquid crystal molecules **30a** at the opposing edge portions EG of the opening **14b1**, and therefore retain their orientation perpendicular to the equipotential lines EQ. The liquid crystal molecules **30a** away from the center of the opening **14b1** incline by the influence of the orientation of other liquid crystal molecules **30a** at the closer edge portion EG, thereby forming an inclined orientation that is symmetric about the center SA (FIG. 2B) of the opening **14b1**. The orientation is, as viewed in a direction perpendicular to the display plane of the LCD **100** (a direction perpendicular to the surfaces of the substrates **11** and **21**), in a state where the liquid crystal molecules **30a** have a radial axial orientation (not shown) about the center of the opening **14b1**. In the present specification, such an orientation will be referred to as a "radially-inclined orientation". In addition, a region of the liquid crystal layer **30** that takes a radially-inclined orientation about a single axis will be referred to as a "liquid crystal domain".

A liquid crystal domain in which the liquid crystal molecules **30a** take a radially-inclined orientation is formed also in a region corresponding to the unit solid portion **14a'** substantially surrounded by the non-solid portion **14b**. The liquid crystal molecules **30a** in a region corresponding to the unit solid portion **14a'** are influenced by the orientation of the liquid crystal molecules **30a** at each edge portion EG of the non-solid portion **14b** so as to take a radially-inclined orientation that is symmetric about the center SA of the unit solid portion **14a'** (corresponding to the center of a unit lattice formed by the non-solid portion **14b**).

The radially-inclined orientation in a liquid crystal domain formed above the unit solid portion **14a'** and the radially-inclined orientation formed above the opening **14b1** are continuous with each other, and are both in conformity with the orientation of the liquid crystal molecules **30a** at the edge portion EG of the non-solid portion **14b**. The liquid crystal molecules **30a** in the liquid crystal domain formed above the opening **14b1** are oriented in the shape of a cone that spreads upwardly (toward the substrate **100b**), and the liquid crystal molecules **30a** in the liquid crystal domain formed above the unit solid portion **14a'** are oriented in the shape of a cone that spreads downwardly (toward the substrate **100a**). The orientation in the liquid crystal domain formed above the unit solid portion **14a'** is also in conformity with the orientation of the liquid crystal molecules **30a** in the liquid crystal layer **30** above the cut-out portion **14b2**. As described above, the radially-inclined orientation in a liquid crystal domain formed above the solid portion **14a** and that in a liquid crystal layer formed above the non-solid portion **14b** (including the liquid crystal domain formed above the opening **14b1**) are continuous with each other. Therefore, no disclination line (orientation defect) is formed along the boundary therebetween. Thus, a decrease in the display quality due to occurrence of a disclination line does not occur.

In order to alleviate the viewing angle dependence of the display quality of an LCD in all azimuth angles, the existence probabilities of the liquid crystal molecules **30a** oriented in various azimuth angle directions preferably have rotational symmetry, and more preferably have axial symmetry, in each picture element region. In other words, the liquid crystal domains formed in the entirety of the picture element region are preferably arranged to have rotational symmetry, and further axial symmetry. However, it is not absolutely necessary that the liquid crystal domains have rotational symmetry

in the entirety of the picture element region. It is sufficient as long as the liquid crystal layer in the picture element region is formed as a set of liquid crystal domains which are arranged so as to have rotational symmetry (or axial symmetry) (e.g., as a set of a plurality of liquid crystal domains arranged in a square lattice pattern). Therefore, it is not absolutely necessary for the plurality of openings **14b1** in the picture element region to be arranged to have rotational symmetry in the entirety of the picture element region. It is sufficient as long as the picture element region includes a set of openings **14b1** which are arranged so as to have rotational symmetry (or axial symmetry) (e.g., as a set of a plurality of openings arranged in a square lattice pattern). The same is applicable to the unit solid portions **14a'** substantially surrounded by the openings **14b1** (and also by the cut-out portions **14b2**). The shape of each liquid crystal domain preferably has rotation symmetry and even axial symmetry, and the shape of each opening **14b1** and each unit solid portion **14a'** also preferably have rotation symmetry and even axial symmetry.

Note that a sufficient voltage may not be applied across the liquid crystal layer **30** around the central portion of the opening **14b1**, and as a result, the liquid crystal layer **30** around the central portion of the opening **14b1** may not contribute to the display. In other words, even if the radially-inclined orientation of the liquid crystal layer **30** around the central portion of the opening **14b1** is disturbed to some extent (e.g., even if the central axis is shifted from the center of the opening **14b1**), the display quality may not be decreased. Therefore, as long as the liquid crystal domain is formed at least corresponding to a unit solid portion **14a'**, it is possible to obtain a continuity of the liquid crystal molecules in each picture element region and to realize a wide viewing angle characteristic and a high display quality.

As described above with reference to FIG. 2A and FIG. 2B, the picture element electrode **14** of the LCD **100** of the present invention includes a non-solid portion **14b** with no conductive film, and produces, in the liquid crystal layer **30** in the picture element region, an electric field represented by equipotential lines EQ having inclined portions. The liquid crystal molecules **30a** having a negative dielectric anisotropy in the liquid crystal layer **30**, which are in a vertical alignment in the absence of an applied voltage, change the orientation direction thereof, with the change in the orientation of those liquid crystal molecules **30a** located on the inclined portions of the equipotential lines EQ serving as a trigger. Thus, a liquid crystal domain having a stable radially-inclined orientation is formed above the opening **14b1** and the unit solid portion **14a'**. A display is produced by the change in the orientation of the liquid crystal molecules in the liquid crystal domain, the change occurring according to the voltage applied across the liquid crystal layer.

The shape (as viewed in the substrate normal direction) and arrangement of the unit solid portions **14a'**, the openings **14b1** and the cut-out portions **14b2** of the picture element electrode **14** will be described.

The display characteristics of an LCD exhibit an azimuth angle dependence due to the orientation (optical anisotropy) of the liquid crystal molecules. In order to reduce the azimuth angle dependence of the display characteristics, it is preferred that the liquid crystal molecules are oriented in all azimuth angles with substantially the same probability. More preferably, the liquid crystal molecules in each picture element region are oriented in all azimuth angles with substantially the same probability. Therefore, each unit solid portion **14a'** preferably has such a shape that liquid crystal domains are formed so that the liquid crystal molecules **30a** in each liquid crystal domain corresponding to the unit solid portion **14a'** are ori-

ented in all azimuth angles with substantially the same probability. More specifically, the shape of the unit solid portion **14a'** preferably has rotational symmetry (more preferably, symmetry with at least a two-fold rotation axis) about a symmetry axis extending through the center of each unit solid portion **14a'** (in the normal direction). The shape of the opening **14b1** also preferably has rotational symmetry, and the openings **14b1** are also preferably arranged so as to have rotational symmetry.

It is not absolutely necessary that the unit solid portions **14a'** and the openings **14b1** are arranged to have rotational symmetry in the entirety of the picture element region. The liquid crystal molecules **30a** can be oriented in all azimuth angles with substantially the same probability in the entirety of the picture element region as long as, as shown in FIG. 1A, the picture element region is formed of a combination of, for example, a plurality of square lattices (having symmetry with a four-fold rotation axis) as the minimum unit.

The orientation of the liquid crystal molecules **30a** when, as illustrated in FIG. 1A, the generally star-shaped openings **14b1** surrounding the generally circular unit solid portion **14a'** are arranged in a square lattice pattern will be described with reference to FIG. 4A to FIG. 4C.

FIG. 4A to FIG. 4C each schematically illustrate an orientation of the liquid crystal molecules **30a** as viewed in the substrate normal direction. In figures, such as FIG. 4B and FIG. 4C, illustrating the orientation of the liquid crystal molecules **30a** as viewed in the substrate normal direction, a black-spotted end of the liquid crystal molecule **30a** drawn as an ellipse indicates that the liquid crystal molecule **30a** is inclined so that the end is closer than the other end to the substrate on which the picture element electrode **14** is provided. This applies to all of the subsequent figures. A single unit lattice (formed by four openings **14b1**) in the picture element region illustrated in FIG. 1A will be described below. Cross-sectional views taken along the respective diagonals of FIG. 4A to FIG. 4C correspond to FIG. 1B, FIG. 2A and FIG. 2B, respectively, and FIG. 1B, FIG. 2A and FIG. 2B will also be referred to in the following description.

When the picture element electrode **14** and the counter electrode **22** are at the same potential, i.e., in a state where no voltage is applied across the liquid crystal layer **30**, the liquid crystal molecules **30a** whose orientation direction is regulated by the vertical alignment layer (not shown) provided on one side of each of the TFT substrate **100a** and the counter substrate **100b** that is closer to the liquid crystal layer **30** take a vertical alignment as illustrated in FIG. 4A.

When an electric field is applied across the liquid crystal layer **30** so as to produce an electric field represented by equipotential lines EQ shown in FIG. 2A, a torque acts upon the liquid crystal molecules **30a** having a negative dielectric anisotropy so as to direct the axial orientation thereof to be parallel to the equipotential lines EQ. As described above with reference to FIG. 3A and FIG. 3B, for the liquid crystal molecules **30a** under an electric field represented by equipotential lines EQ perpendicular to the molecular axis thereof, the direction in which the liquid crystal molecules **30a** are to incline (rotate) is not uniquely defined (FIG. 3A). Thus, the orientation change (inclination or rotation) does not easily occur. In contrast, for the liquid crystal molecules **30a** placed under equipotential lines EQ inclined with respect to the molecular axis thereof, the direction of inclination (rotation) is uniquely defined. Thus, the orientation change easily occurs. Therefore, as illustrated in FIG. 4B, the liquid crystal molecules **30a** start inclining from the edge portions of the openings **14b1** where the molecular axis of the liquid crystal molecules **30a** is inclined with respect to the equipotential

lines EQ. Then, as described above with reference to FIG. 3C, the surrounding liquid crystal molecules **30a** incline so as to conform with the orientation of the already-inclined liquid crystal molecules **30a** at the edge portions of the openings **14b1**. Then, the axial orientation of the liquid crystal molecules **30a** becomes stable as illustrated in FIG. 4C (radially-inclined orientation).

As described above, when the shape of the openings **14b1** has rotational symmetry, the liquid crystal molecules **30a** in the picture element region successively incline, starting from the edge portion of each opening **14b1** toward the center of the opening **14b1** upon application of a voltage. As a result, those liquid crystal molecules **30a** around the center of each opening **14b1**, where the respective orientation-regulating forces from the liquid crystal molecules **30a** at the edge portions are in equilibrium, remain in a vertical alignment with respect to the substrate plane. The surrounding liquid crystal molecules **30a** are inclined in a radial pattern about those liquid crystal molecules **30a** around the center of each opening **14b1**, with the degree of inclination gradually increasing as the liquid crystal molecules **30a** are farther from the center of the opening **14b1**.

The liquid crystal molecules **30a** in a region corresponding to the generally circular unit solid portion **14a'** surrounded by the four generally star-shaped openings **14b1** arranged in a square lattice pattern also incline so as to conform with the orientation of the liquid crystal molecules **30a** that have been inclined by an inclined electric field produced at the edge portion of each opening **14b1**. As a result, those liquid crystal molecules **30a** around the center of the unit solid portion **14a'**, where the respective orientation-regulating forces from the liquid crystal molecules **30a** at the edge portions are in equilibrium, remain in a vertical alignment with respect to the substrate plane. The surrounding liquid crystal molecules **30a** are inclined in a radial pattern about those liquid crystal molecules **30a** around the center of the unit solid portion **14a'**, with the degree of inclination gradually increasing as the liquid crystal molecules **30a** are farther from the center of the unit solid portion **14a'**.

As described above, when liquid crystal domains, in each of which the liquid crystal molecules **30a** take a radially-inclined orientation, are arranged in a square lattice pattern, the existence probabilities of the liquid crystal molecules **30a** of the respective axial orientations have rotational symmetry. As a result, it is possible to realize a high-quality display without non-uniformity for any viewing angle. In order to reduce the viewing angle dependence of a liquid crystal domain taking a radially-inclined orientation, the liquid crystal domain preferably has a high degree of rotational symmetry (preferably with at least a two-fold rotation axis, and more preferably with at least a four-fold rotation axis).

As described above, in the LCD **100**, each liquid crystal region includes a non-solid portion **14b** including openings **14b1** and cut-out portions **14b2**. Owing to such a structure, liquid crystal domains taking a radially-inclined orientation are formed. As a result, a wide viewing angle can be provided.

In the LCD **100** according to the present invention, as shown in, for example, FIG. 1B, the liquid crystal layer **30** above a unit solid portion **14a'** has a first region having a first thickness d_1 and a second region having a second thickness d_2 which is smaller than the first thickness d_1 . The second region is located above an edge portion of the unit solid portion **14a'** (near the outer periphery of the unit solid portion **14a'**), and the first region is located inner to the second region. In the LCD **100**, the cell gap above the edge portion of the unit solid portion **14a'** is smaller than the cell gap above the remaining portion of the unit solid portion **14a'**.

In general, the response speed of liquid crystal molecules is higher as the thickness of the liquid crystal layer (cell gap) is smaller because the effect of the electric field is more significant, and the response time of the liquid crystal molecules is generally in proportional to the square of the thickness of the liquid crystal layer. Therefore, the response speed of the second region having a relatively small thickness d_2 is higher than the response speed of the first region having a relatively large thickness d_1 . The liquid crystal molecules **30a** in the second region above the edge portion of the unit solid portion **14a'** trigger the formation of a radially-inclined orientation. Therefore, when the response speed of the liquid crystal molecules **30a** in the second region is higher, a liquid crystal domain is formed more quickly. As a result, the response speed of the entirety of the liquid crystal layer **30** is increased. Thus, the LCD **100** according to the present invention has a superb response characteristic.

While the response speed can be further increased by decreasing the cell gap across the entire picture element region, it is then necessary to increase the refractive index anisotropy (Δn) of the liquid crystal material in order to give a predetermined retardation to light passing through the liquid crystal layer **30**. With common liquid crystal materials, however, the viscosity increases as the refractive index anisotropy increases, which cancels out the advantage of an improved response speed obtained by reducing the cell gap. Therefore, it is not possible to sufficiently improve the response speed by simply reducing the thickness of the liquid crystal layer **30** in the entirety of the picture element region. In contrast, in the LCD **100** according to the present invention, the cell gap is reduced only in a portion of the picture element region (a region corresponding to the edge portion of the unit solid portion **14a'**). Thus, the response speed can be sufficiently improved with no need to increase the refractive index anisotropy (Δn) of the liquid crystal material.

The effect of improving the response speed is greater as the thickness d_2 of the second region is smaller and also as the difference between the thickness d_1 of the first region and the thickness d_2 of the second region is greater. Specifically, in order to sufficiently improve the response speed, the difference between the thickness d_1 of the first region and the thickness d_2 of the second region is preferably $0.5 \mu\text{m}$ or greater, more preferably $1 \mu\text{m}$ or greater, and further preferably $1.5 \mu\text{m}$ or greater.

It is not absolutely necessary to reduce the cell gap above the edge portion (thickness d_2) of all the unit solid portions **14a'** in the picture element region. The effect of improving the response speed is obtained by reducing the cell gap above the edge portion of only a part of the unit solid portions **14a'**. In order to improve the response speed, however, it is preferable to reduce the cell gap above the edge portion in as many unit solid portions **14a'** as possible of the picture element region. It is most preferable to reduce the cell gap above the edge portion in all the unit solid portions **14a'** of the picture element region.

In the present embodiment, as shown in, for example, FIG. 1B, the cell gap above the edge portion of the unit solid portion **14a'** is made smaller by setting a surface of the edge portion of the unit solid portion **14a'** (corresponding to the second region) to be higher than a surface of the remaining portion of the unit solid portion **14a'** (corresponding to the first region). More specifically, an interlayer insulating film **12** is provided between the picture element electrode **14** and the transparent substrate **11**, and the height of the surface of the interlayer insulating film **12** is locally changed, such that

the surface of the unit solid portion **14a'** formed thereon is higher in the edge portion than in the remaining portion of the unit solid portion **14a'**.

The interlayer insulating film **12** includes an inclining region **12a** where a height of one surface thereof which is closer to the liquid crystal layer **30** changes continuously and a flat region **12b** where the height of the surface which is closer to the liquid crystal layer **30** is substantially constant. The edge portion (corresponding to the second region) of the unit solid portion **14a'** is located on the inclining region **12a**, and the remaining portion (corresponding to the first region) of the unit solid portion **14a'** is located on the flat region **12b**.

In view of the display quality, it is preferred that the inclination angle of the inclining region **12a** of the interlayer insulating film **12** (the inclination angle with respect to the surface of the substrate **11**) is small. The vertical alignment film formed on the inclining region **12a** has an orientation-regulating force for orienting the liquid crystal molecules **30a** vertical to the surface of the vertical alignment film. Therefore, the liquid crystal molecules **30a** on the inclining region **12a** are oriented in an inclined direction with respect to the surface of the substrate **11**. At this point, the degree of inclination of the liquid crystal molecules **30a** is larger as the inclination angle of the inclining region **12a** is larger. Since the orientation-regulating force of the vertical alignment film acts irrespective of the presence/absence of a voltage application, light leakage occurs in a black display due to the inclined liquid crystal molecules **30a** above the inclining region **12a**. Therefore, when the inclination angle of the inclining region **12a** is excessively large, the contrast ratio decreases. Thus, the inclination angle of the inclining region **12a** is preferably small, and the interlayer insulating film **12** preferably has a gentle slope. Specifically, the inclination angle of the inclining region **12a** of the interlayer insulating film **12** with respect to the surface of the substrate **11** is preferably 30° or less, and more preferably 20° or less.

Note that if the height of the surface of the unit solid portion **14a'** changes continuously across the entire unit solid portion **14a'**, the retardation of the liquid crystal layer **30** is no longer constant across the unit solid portion **14a'**, which may deteriorate the display quality. In such a case, it is difficult to suitably compensate for the phase difference by using a phase difference compensator or the like. In the case where the interlayer insulating film **12** includes the flat region **12b** where the height of the surface which is closer to the liquid crystal layer **30** is substantially constant as in the present embodiment, generation of such a problem can be suppressed.

The interlayer insulating film **12** having a gentle slope as described above can be formed by, for example, exposing and developing a photosensitive transparent resin film using a photomask and then thermally deforming the film by a heat treatment. Specifically, the interlayer insulating film **12** shown in FIG. 1B is formed as follows. First, a photosensitive resin film is formed on a surface of the transparent substrate **11**. Next, the photosensitive resin film is exposed using a photomask, such that a portion of the film corresponding to the non-solid portion **14b** is unexposed and a portion of the film corresponding to the solid portion **14a** is exposed to a predetermined amount of light. Then, the film is developed and heat-treated at a predetermined temperature. As a result, the shape having a gentle slope as shown in FIG. 1B is obtained. The above-mentioned exposure process is performed with such an exposure value that a portion of the photosensitive resin film corresponding to the solid portion

14a is not completely removed but partially remain after the development process. Such an exposure process is referred to as a "half exposure process".

The interlayer insulating film may also be formed after forming an underlying layer on a portion of the transparent substrate **11** corresponding to the non-solid portion **14b**. With this method, the interlayer insulating film is formed such that a part thereof rides on the underlying layer. As a result, the interlayer insulating film having the above-mentioned shape is obtained. When the underlying layer is formed in the same step as, and using the same material as, the black matrix or the lines, an increase of production steps can be restricted.

In the LCD **100** in this embodiment, it is preferable to use a display mode using circularly-polarized light, i.e., a display mode in which light to be incident upon the liquid crystal layer **30** is circularly-polarized light and the circularly-polarized light is modulated by the liquid crystal layer **30** to display an image. Hereinafter, the reason will be described with reference to FIG. 5. FIG. 5 is an enlarged cross-sectional view illustrating an edge portion of the unit solid portion **14a'** in the presence of an applied voltage.

As illustrated in FIG. 5, in the case where the edge portion of the unit solid portion **14a'** is formed on an inclined surface, the orientation continuity between the liquid crystal molecules **30a** above the edge portion of the unit solid portion **14a'** and the liquid crystal molecules **30a** above the non-solid portion **14b** may be deteriorated when a voltage is applied. The liquid crystal molecule **30a** above the edge portion once falls down due to the electric field effect, and then slowly changes the azimuth angle of its orientation as indicated by an arrow in FIG. 5 in order to maintain the orientation continuity with the adjacent liquid crystal molecules **30a** (in order to be oriented vertical to the sheet of FIG. 5). Thus, the liquid crystal molecules **30a** near the edge portion exhibit a two-step response behavior in response to a voltage application. In a display mode using linearly-polarized light, the second step, in which the azimuth angle of orientation changes slowly, changes the transmittance (brightness) and may not provide a sufficient effect of improving the response speed by locally reducing the cell gap above the edge portion of the unit solid portion **14a'**. In a display mode using circularly-polarized light, by contrast, the change in the azimuth angle of the liquid crystal molecules **30a** does not substantially influence the transmittance. Thus, a great effect of improving the response speed can be provided.

A display mode using circularly-polarized light can be realized by, for example, providing a circular polarization plate (e.g., a combination of a linear polarization plate and a $\lambda/4$ plate) on both sides of the liquid crystal layer **30**.

For the radially-inclined orientation of the liquid crystal molecules **30a**, a radially-inclined orientation having a counterclockwise or clockwise spiral pattern, as illustrated in FIG. 6B or FIG. 6C respectively, is more stable than the simple radially-inclined orientation as illustrated in FIG. 6A. The spiral orientation is different from a normal twist orientation in which the orientation direction of the liquid crystal molecules **30a** spirally changes along the thickness of the liquid crystal layer **30**. In the spiral orientation, the orientation direction of the liquid crystal molecules **30a** does not substantially change along the thickness of the liquid crystal layer **30** for a minute region. In other words, the orientation in a cross section (in a plane parallel to the layer plane) at any thickness of the liquid crystal layer **30** is as illustrated in FIG. 6B or FIG. 6C, with substantially no twist deformation along the thickness of the liquid crystal layer **30**. For a liquid crystal domain as a whole, however, there may be a certain degree of twist deformation.

When a material obtained by adding a chiral agent to a nematic liquid crystal material having a negative dielectric anisotropy is used, the liquid crystal molecules **30a** take a radially-inclined orientation of a counterclockwise or clockwise spiral pattern about the opening **14b1** or the unit solid portion **14a'**, as illustrated in FIG. 6B or FIG. 6C, respectively, in the presence of an applied voltage. Whether the spiral pattern is counterclockwise or clockwise is determined by the type of chiral agent used. Thus, by controlling the liquid crystal layer **30** above the opening **14b1** or the unit solid portion **14a'** into a radially-inclined orientation of a spiral pattern in the presence of an applied voltage, the direction of the spiral pattern of the radially-inclined liquid crystal molecules **30a**, about other liquid crystal molecules **30a** standing vertical to the substrate plane, can be constant in all the liquid crystal domains. Therefore, it is possible to realize a uniform display without display non-uniformity. Since the direction of the spiral pattern around the liquid crystal molecules **30a** standing vertical to the substrate plane is definite, the response speed upon application of a voltage across the liquid crystal layer **30** is also improved.

Moreover, when a larger amount of a chiral agent is added, the orientation of the liquid crystal molecules **30a** changes in a spiral pattern along the thickness of the liquid crystal layer **30** as in a normal twisted orientation. Where the orientation of the liquid crystal molecules **30a** does not change in a spiral pattern along the thickness of the liquid crystal layer **30**, the liquid crystal molecules **30a** which are oriented perpendicular or parallel to the polarization axis of the polarization plate do not give a phase difference to the incident light. Therefore, incident light passing through a region of such an orientation does not contribute to the transmittance. In contrast, where the orientation of the liquid crystal molecules **30a** changes in a spiral pattern along the thickness of the liquid crystal layer **30**, the liquid crystal molecules **30a** that are oriented perpendicular or parallel to the polarization axis of the polarization plate also give a phase difference to the incident light, and the optical rotatory power can also be utilized. Therefore, incident light passing through a region of such an orientation also contributes to the transmittance. Thus, it is possible to obtain an LCD capable of producing a bright display.

FIG. 1A illustrates an example in which the unit solid portions **14a'** each have a generally circular shape and the openings **14b1** each have a generally star-like shape and are arranged in a square lattice pattern. However, the shape of the unit solid portions **14a'** and the shape and arrangement of the openings **14b1** are not limited to those of the example above.

FIG. 7A and FIG. 7B are plan views respectively illustrating the picture element electrodes **14A** and **14B** having respective openings **14b1** and the unit solid portions **14a'** of different shapes.

The openings **14b1** and the unit solid portions **14a'** of the picture element electrodes **14A** and **14B** illustrated in FIG. 7A and FIG. 7B, respectively, are slightly distorted from the openings **14b1** and the unit solid portions **14a'** illustrated in FIG. 1A. The openings **14b1** and the unit solid portions **14a'** of the picture element electrodes **14A** and **14B** are regularly arranged so as to have a two-fold rotation axis (not a four-fold rotation axis) to form oblong rectangular unit lattices. In both of the picture element electrodes **14A** and **14B**, the openings **14b1** have a distorted star-like shape, and the unit solid portions **14a'** have a generally elliptical shape (a distorted circular shape). The picture element electrodes **14A** and **14B** also provide an LCD having a high display quality and a desirable viewing angle characteristic.

Moreover, picture element electrodes **14C** and **14D** as illustrated in FIG. 8A and FIG. 8B, respectively, are also usable.

In the picture element electrodes **14C** and **14D**, generally cross-shaped openings **14b1** are arranged in a square lattice pattern so that each unit solid portion **14a'** has a generally square shape. Of course, these patterns may be distorted so that there are oblong rectangular unit lattices. As described above, an LCD having a high display quality and a desirable viewing angle characteristic can be obtained alternatively by regularly arranging the generally rectangular (encompassing square and oblong rectangular) unit solid portions **14a'**.

Notably, the shape of the openings **14b1** and/or the unit solid portions **14a'** is preferably a circle or an ellipse than a rectangle, in order to stabilize the radially-inclined orientation. A conceivable reason for this is that with a circular or elliptical shape, the edge of each opening **14b1** and/or each unit solid portion **14a'** is more continuous (smooth) and thus the orientation direction of the liquid crystal molecules **30a** changes more continuously (smoothly).

In view of the continuity of the orientation direction of the liquid crystal molecules **30a** described above, picture element electrodes **14E** and **14F** as illustrated in FIG. 9A and FIG. 9B respectively are also usable. The picture element electrode **14E** illustrated in FIG. 9A is a variation of the picture element electrode **14A** illustrated in FIG. 1A, and has openings **14b1** defined only by four arcs. The picture element electrode **14F** illustrated in FIG. 9B is a variation of the picture element electrode **14D** illustrated in FIG. 8B, and the sides of the openings **14b1** bordered with the unit solid portions **14a'** are in an arc. In both of the picture element electrodes **14E** and **14F**, the openings **14b1** and the unit solid portions **14a'** are arranged in a square lattice pattern and have a four-fold rotation axis. Alternatively, as illustrated in FIG. 7A and FIG. 7B, the openings **14b1** and the unit solid portions **14a'** may be distorted to be arranged in an oblong rectangular lattice pattern and to have a two-fold rotation axis.

In view of the response speed, picture element electrodes **14G** and **14H** as illustrated in FIG. 10A and FIG. 10B respectively are also usable. The picture element electrode **14G** illustrated in FIG. 10A is a variation of the picture element electrode **14C** illustrated in FIG. 8A including generally square unit solid portions **14a'**. In the picture element electrode **14G**, the unit solid portions **14a'** have a distorted square shape with acute angle corner portions. In the picture element electrode **14H** illustrated in FIG. 10B, the unit solid portions **14a'** have a generally star-like shape having eight sides (edges) with a four-fold rotation axis at the center thereof and also have four acute angle corner portions. The term "acute angle corner portion" as used herein refers to a corner or a rounded corner having an angle less than 90°.

When the unit solid portions **14a'** have acute angle corner portions as illustrated in FIG. 10A and FIG. 10B, the number of edge portions in which an inclined electric field is generated is increased. Therefore, the inclined electric field acts on a greater number of liquid crystal molecules **30a**. The number of liquid crystal molecules **30a** that initially start inclining in response to an electric field is increased, thereby reducing the amount of time required for a radially-inclined orientation to be formed entirely across the picture element region. As a result, the response speed to the application of a voltage across the liquid crystal layer **30** is improved.

Moreover, when the unit solid portions **14a'** have acute angle corner portions, the existence probability of the liquid crystal molecules **30a** that are oriented in a particular azimuth angle direction can be increased (or decreased) as compared to the case where the unit solid portions **14a'** have a generally

circular shape or a generally rectangular shape. In other words, a high directivity can be introduced to the existence probabilities of the liquid crystal molecules **30a** oriented in various azimuth angle directions. Therefore, when an acute angle corner is employed in the unit solid portions **14a'** in an LCD including a polarization plate in which linearly-polarized light is incident upon the liquid crystal layer **30**, it is possible to decrease the existence probability of the liquid crystal molecules **30a** oriented vertical or horizontal to the polarization axis of the polarization plate, i.e., the liquid crystal molecules **30a** that do not give a phase difference to the incident light. This improves the light transmittance and realizes a brighter display.

FIGS. 7A and 7B, 8A and 8B, 9A and 9B, and 10A and 10B illustrate a structure in which each picture element region includes a plurality of openings **14b1**. Alternatively, as described with reference to FIG. 1B, a plurality of liquid crystal domains can be formed in each picture element region by providing one opening **14b1** in the picture element region, or by providing only a cut-out portions **14b2** with no opening **14b1**. It is not absolutely necessary to form liquid crystal domains in region(s) corresponding to the opening(s) **14b1** of the picture element electrode **14**. It is sufficient as long as liquid crystal domains taking a radially-inclined orientation are formed in correspondence with the solid portion **14a** (unit solid portions **14a'**). With this structure, even though the liquid crystal domains formed in correspondence with the openings **14b1** do not have a radially-inclined orientation, the continuity of the orientation of the liquid crystal molecules **30a** is realized in the picture element region. Therefore, the radially-inclined orientation of the liquid crystal domains provided in correspondence with the solid portion **14a** is stabilized. Especially when, as illustrated in FIG. 8A and FIG. 8B, the openings **14b1** have a small area, the degree of contribution of the openings **14b1** to the display is also small. Therefore, the decrease in the display quality caused by the absence of the liquid crystal domains taking a radially-inclined orientation in correspondence with the openings **14b1** is negligible.

In the above-described examples, the openings **14b1** are generally star-shaped or generally cross-shaped and the unit solid portions **14a'** are generally circular, generally elliptical, generally square (rectangular) or generally rectangular with rounded corners. Alternatively, the openings **14b1** and the unit solid portions **14a'** may be inverted in a negative/positive manner. FIG. 11 is a plan view illustrating a picture element electrode **14I** having a pattern in which the openings **14b1** and the unit solid portions **14a'** of the picture element electrode **14** illustrated in FIG. 1A are inverted in a negative/positive manner. The picture element electrode **14I** illustrated in FIG. 11 has substantially the same functions and effects as those of the picture element electrode **14** illustrated in FIG. 1A. FIG. 12A and FIG. 12B respectively illustrate a picture element electrode **14J** and a picture element electrode **14K**. The picture element electrode **14K** has a pattern in which the openings **14b1** and the unit solid portions **14a'** of the picture element electrode **14J** are inverted in a negative/positive manner. Where the openings **14b1** and the unit solid portions **14a'** are both generally square as in the case of the picture element electrodes **14J** and **14K**, the pattern obtained by the negative/positive inversion may result in the same pattern as the pre-inversion pattern.

Even in the case where the openings **14b1** and the unit solid portions **14a'** in FIG. 1B are inverted as illustrated in FIG. 11, it is preferable to form cut-out portions **14b2** (each having a shape corresponding to about a half or a quarter of each opening **14b1**) in the edge portions of the picture element

electrode **14**, such that the unit solid portions **14a'** have rotational symmetry. With such a pattern, the effect by the inclined electric field is provided in the edge portions of the picture element region as in the central portions thereof, which realizes a stable radially-inclined orientation in the entirety of the picture element region.

With or without the negative/position inversion, the length of the boundary between the non-solid portion **14b** and the solid portion **14a** is the same. No difference is presented by the difference in these patterns in terms of the function of generating an inclined electric field. However, the area ratio of the unit solid portions **14a'** with respect to the entire area of the picture element region may be different between these patterns. More specifically, the area of the unit solid portions **14a'** for generating an electric field acting on the liquid crystal molecules **30a** in the liquid crystal layer **30** (the area actually having the conductive film) may be different between these patterns.

The voltage applied across the liquid crystal domains formed in correspondence with the openings **14b1** is lower than the voltage applied across the liquid crystal domains formed in correspondence with the unit solid portions **14a'**. Therefore, with a normally black display, the display provided by the liquid crystal domains in correspondence with the openings **14b1** is darker. Thus, it is preferable to decrease the area ratio of the non-solid portion **14b** and increase the area ratio of the unit solid portions **14a'** in each picture element region.

Now, the relationship between the shape of the unit solid portions **14a'** with the stability of a radially-inclined orientation and the transmittance value will be described.

A research by the present inventor revealed that with the spacing (arrangement pitch) of the unit solid portions **14a'** being constant, the orientation stability is higher as the shape of the unit solid portions **14a'** is closer to a circle or an ellipse. This is because as the shape of the unit solid portions **14a'** is closer to a circle or an ellipse, the continuity in the orientation direction of the liquid crystal molecules **30a** in a radially-inclined orientation is higher.

It was also revealed that the transmittance is higher as the shape of the unit solid portions **14a'** is closer to a rectangle such as a square or an oblong rectangle. This is because as the shape of the unit solid portions **14a'** is closer to a rectangle, the area ratio of the unit solid portions **14a'** is higher, thereby increasing the area of the liquid crystal layer that is directly influenced by the electric field produced by the electrodes (the area defined in the plane perpendicular to the substrate normal direction) and thus increasing the effective aperture ratio.

Therefore, the shape of the unit solid portion **14a'** can be determined in view of the intended orientation stability and the intended transmittance.

When each unit solid portion **14a'** has a generally square shape with generally arc-shaped corner portions, as illustrated in FIG. 9B, it is possible to realize both of a relatively high orientation stability and a relatively high transmittance. Of course, substantially the same effects can be obtained when the unit solid portions **14a'** have a generally rectangular shape with generally arc-shaped corner portions. Note that due to limitations on the production process, the corner portions of the unit solid portions **14a'** formed of a conductive film may not be arc-shaped strictly speaking, but may instead be an obtuse polygonal shape (a shape including a plurality of angles exceeding 90°), and the corner portions may have a slightly distorted arc shape (e.g., a portion of an ellipse) or a distorted polygonal shape, instead of a quarter-arc shape or a regular polygonal shape (e.g., a portion of a regular polygon).

Alternatively, the corner portions may have a shape that is a combination of curves and an obtuse angle. The term “generally arc shape” as used herein encompasses any of these shapes. Note that due to similar process-related reasons, the generally-circular unit solid portions **14a'** as illustrated in FIG. 1A may have a polygonal shape or a distorted shape instead of a strictly circular shape.

For the LCD **100** in this embodiment, the same structure as that of a known vertical alignment type LCD can be adopted except that the picture element electrode **14** is patterned in a predetermined manner so as to include a solid portion **14a** and a non-solid portion **14b** and that the thickness d_1 of the liquid crystal layer **30** above the edge portion of the unit solid portion **14a'** is smaller than the thickness d_2 of the liquid crystal layer **30** above the remaining portion of the unit solid portion **14a'**. Thus, the LCD **100** can be produced using a known production method.

Typically, a vertical alignment film (not shown) as a vertical alignment layer is provided on one side of each of the picture element electrode **14** and the counter electrode **22** that is closer to the liquid crystal layer **30**, so as to vertically align the liquid crystal molecules having a negative dielectric anisotropy.

The liquid crystal material may be a nematic liquid crystal material having a negative dielectric anisotropy. A guest-host mode LCD can be obtained by adding a dichroic dye to a nematic liquid crystal material having a negative dielectric anisotropy. A guest-host mode LCD does not require a polarization plate.

A so-called “vertical alignment type LCD”, including a liquid crystal layer in which liquid crystal molecules having a negative dielectric anisotropy are vertically aligned in the absence of an applied voltage, is capable of displaying an image in various display modes. For example, a vertical alignment type LCD may be used in a birefringence mode in which an image is displayed by controlling the birefringence of the liquid crystal layer with an electric field, an optical rotation mode, or in a display mode that is a combination of an optical rotation mode and a birefringence mode. It is possible to obtain a birefringence-mode LCD by providing a pair of polarization plates on the outer side (the side away from the liquid crystal layer **30**) of the pair of substrates (e.g., the TFT substrate and the counter substrate) of any of the LCDs described above. Moreover, a phase difference compensator (typically a phase plate) may be provided as necessary. In order to obtain a superb response characteristic by suppressing the two-step response behavior, it is preferable to use the display mode using circularly-polarized light mentioned above.

Embodiment 2

An LCD of the present embodiment is different from the LCD **100** of Embodiment 1 in that the counter substrate includes an orientation-regulating structure.

FIG. 13A to FIG. 13E each schematically illustrate a counter substrate **200b** having an orientation-regulating structure **28**. Each element having substantially the same function as that in the LCD **100** will be denoted by the same reference numeral and will not be further described.

Each of the orientation-regulating structures **28** illustrated in FIG. 13A to FIG. 13E functions to orient the liquid crystal molecules **30a** of the liquid crystal layer **30** into a radially-inclined orientation. Note that the orientation-regulating structure **28** illustrated in FIG. 13A to FIG. 13D and that illustrated in FIG. 13E are different in terms of the direction in which the liquid crystal molecules **30a** are to be inclined.

The direction in which the liquid crystal molecules **30a** are inclined by the orientation-regulating structures **28** illustrated in FIG. 13A to FIG. 13D is aligned with the orientation direction of the radially-inclined orientation of each liquid crystal domain that is formed in a region corresponding to the unit solid portion **14a'** (see, for example, FIG. 1A and FIG. 1B) of the picture element electrode **14**. In contrast, the direction in which the liquid crystal molecules **30a** are inclined by the orientation-regulating structure **28** illustrated in FIG. 13E is aligned with the orientation direction of the radially-inclined orientation of each liquid crystal domain that is formed in a region corresponding to the opening **14b1** (see, for example, FIG. 1A and FIG. 1B) of the picture element electrode **14**.

The orientation-regulating structure **28** illustrated in FIG. 13A is formed by an opening **22a** of the counter electrode **22**. A vertical alignment film (not shown) is provided on one surface of the counter substrate **200b** that is closer to the liquid crystal layer **30**.

The orientation-regulating structure **28** exerts an orientation-regulating force only in the presence of an applied voltage. Since the orientation-regulating structure **28** is only required to exert an orientation-regulating force upon the liquid crystal molecules **30a** in each liquid crystal domain in a radially-inclined orientation formed by the electrode structure of the TFT substrate **100a**, the size of the opening **22a** is smaller than the opening **14b1** provided in the TFT substrate **100a**, and is smaller than the unit solid portion **14a'** (see, for example, FIG. 1A). A sufficient effect can be obtained, for example, only with an area less than or equal to one half of that of the opening **14b1** or the unit solid portion **14a'**. When the opening **22a** of the counter electrode **22** is provided so as to oppose the central portion of the unit solid portion **14a'** of the picture element electrode **14**, the continuity of the orientation of the liquid crystal molecules **30a** increases, and the position of the central axis of the radially-inclined orientation can be fixed.

As described above, when a structure exerting an orientation-regulating force only in the presence of an applied voltage is employed as the orientation-regulating structure, substantially all of the liquid crystal molecules **30a** of the liquid crystal layer **30** take a vertical alignment in the absence of an applied voltage. Therefore, when employing a normally black mode, substantially no light leakage occurs in a black display, thereby realizing a display with a desirable contrast ratio.

However, in the absence of an applied voltage, the orientation-regulating force is not exerted and thus the radially-inclined orientation is not formed. Moreover, when the applied voltage is low, there is only a weak orientation-regulating force. In a consequence, an after image may be observed when a considerably large stress is applied upon the liquid crystal panel.

Each of the orientation-regulating structures **28** illustrated in FIG. 13B to FIG. 13D exerts an orientation-regulating force regardless of the presence/absence of an applied voltage. Thus, a stable radially-inclined orientation can be obtained at any display gray level, and a high resistance to a stress is provided.

The orientation-regulating structure **28** illustrated in FIG. 13B includes a protrusion (rib) **22b** that is provided on the counter electrode **22** so as to protrude into the liquid crystal layer **30**. While there is no particular limitation on the material of the protrusion **22b**, the protrusion **22b** can be easily formed by using a dielectric material such as a resin. A vertical alignment film (not shown) is provided on one surface of the counter substrate **200b** that is closer to the liquid crystal layer **30**. The protrusion **22b** orients the liquid crystal mol-

ecules **30a** into a radially-inclined orientation by virtue of the configuration of the surface thereof (with a vertical alignment power). It is preferred to use a resin material that deforms by heat, in which case it is possible to easily form the protrusion **22b** having a slightly-humped cross section as illustrated in FIG. **13B** through a heat treatment after patterning. The protrusion **22b** having a slightly-humped cross section with a vertex (e.g., a portion of a sphere) as illustrated in FIG. **13B** or a conical protrusion provides a superb effect of fixing the central position of the radially-inclined orientation.

The orientation-regulating structure **28** illustrated in FIG. **13C** is provided as a horizontal alignment surface, facing the liquid crystal layer **30**, that is provided in an opening (or a depressed portion) **23a** in a dielectric layer **23** formed under the counter electrode **22** (i.e., on one side of the counter electrode **22** that is closer to the substrate **21**). The horizontal alignment surface is provided by forming a vertical alignment film **24** so as to cover one side of the counter substrate **200b** that is closer to the liquid crystal layer **30** but not to cover a region corresponding to the opening **23a**. Alternatively, a horizontal alignment film **25** may be provided only in the opening **23a** as illustrated in FIG. **13D**.

The horizontal alignment film illustrated in FIG. **13D** may be provided by, for example, once providing the vertical alignment film **24** across the entire surface of the counter substrate **200b**, and then selectively irradiating a portion of the vertical alignment film **24** in the opening **23a** with UV light so as to reduce the vertical alignment power thereof. The horizontal orientation power required for the orientation-regulating structure **28** does not have to be so high that the resulting pretilt angle is as small as that resulting from an alignment film used in a TN type LCD. For example, a pretilt angle of 45° or less is sufficient.

As illustrated in FIG. **13C** and FIG. **13D**, on the horizontal orientation surface in the opening **23a**, the liquid crystal molecules **30a** are urged to be horizontal with respect to the substrate plane. As a result, the liquid crystal molecules **30a** form an orientation that is continuous with the orientation of the surrounding, vertically aligned liquid crystal molecules **30a** on the vertical alignment film **24**, thereby obtaining a radially-inclined orientation as illustrated in FIG. **13C** and FIG. **13D**.

A radially-inclined orientation can be obtained only by selectively providing a horizontal orientation surface (e.g., the surface of the electrode, or a horizontal alignment film) on the flat surface of the counter electrode **22** without providing a depressed portion (that is formed by the opening in the dielectric layer **23**) on the surface of the counter electrode **22**. However, the radially-inclined orientation can be further stabilized by virtue of the surface configuration of the depressed portion.

It is preferred to use, for example, a color filter layer or an overcoat layer of a color filter layer as the dielectric layer **23** to form the depressed portion in the surface of the counter substrate **200b** that is closer to the liquid crystal layer **30**, because it does not increase the number of production steps. In the structures illustrated in FIG. **13C** and FIG. **13D**, the light utilization efficiency decreases very little because there is no region where a voltage is applied across the liquid crystal layer **30** via the protrusion **22b** unlike in the structure illustrated in FIG. **13B**.

In the orientation-regulating structure **28** illustrated in FIG. **13E**, a depressed portion is formed on one side of the counter substrate **200b** that is closer to the liquid crystal layer **30** by using the opening **23a** of the dielectric layer **23**, as in the orientation-regulating structure **28** illustrated in FIG. **13D**, and a horizontal alignment film **26** is formed only in the

bottom portion of the depressed portion. Instead of forming the horizontal alignment film **26**, the surface of the counter electrode **22** may be exposed as illustrated in FIG. **13C**.

An LCD **200** having any of the orientation-regulating structures as described above is shown in FIG. **14A** and FIG. **14B**. FIG. **14A** is a plan view, and FIG. **14B** is a cross-sectional view taken along line **14A-14A'** of FIG. **14A**.

The LCD **200** includes the TFT substrate **100a** having the picture element electrode **14** including a solid portion **14a** and a non-solid portion **14b**, and the counter substrate **200b** having the orientation-regulating structure **28**. The structure of the TFT substrate **100a** is not limited to the structure illustrated here, but may be any other structure described above. Moreover, while a structure that exerts an orientation-regulating force even in the absence of an applied voltage (FIG. **13B** to FIG. **13D** and FIG. **13E**) will be used as the orientation-regulating structure **28**, the orientation-regulating structure **28** illustrated in FIG. **13B** to FIG. **13D** can be replaced with that illustrated in FIG. **13A**.

Among the orientation-regulating structures **28** provided in the counter substrate **200b** of the LCD **200**, the orientation-regulating structure **28** provided around the center of a region opposing the solid portion **14a** of the picture element electrode **14** is one of those illustrated in FIG. **13B** to FIG. **13D**, and the orientation-regulating structure **28** provided around the center of a region opposing the non-solid portion **14b** of the picture element electrode **14** is the one illustrated in FIG. **13E**.

With such an arrangement, in the presence of an applied voltage across the liquid crystal layer **30**, i.e., in the presence of an applied voltage between the picture element electrode **14** and the counter electrode **22**, the direction of the radially-inclined orientation formed by the unit solid portion **14a'** of the picture element electrode **14** is aligned with the direction of the radially-inclined orientation formed by the orientation-regulating structure **28**, thereby stabilizing the radially-inclined orientation. This is schematically shown in FIG. **15A** to FIG. **15C**. FIG. **15A** illustrates a state in the absence of an applied voltage, FIG. **15B** illustrates a state where the orientation has just started to change (initial ON state) after application of a voltage, and FIG. **15C** schematically illustrates a steady state during the voltage application.

As illustrated in FIG. **15A**, the orientation-regulating force exerted by the orientation-regulating structure **28** (FIG. **13B** to FIG. **13D**) acts upon the liquid crystal molecules **30a** in the vicinity thereof even in the absence of an applied voltage, thereby forming a radially-inclined orientation.

When voltage application begins, an electric field represented by equipotential lines EQ shown in FIG. **15B** is produced (by the electrode structure of the TFT substrate **100a**), and a liquid crystal domain in which the liquid crystal molecules **30a** are in a radially-inclined orientation is formed in each region corresponding to the opening **14b1** and each region corresponding to the unit solid portion **14a'**, and the liquid crystal layer **30** reaches a steady state as illustrated in FIG. **15C**. The inclination direction of the liquid crystal molecules **30a** in each liquid crystal domain coincides with the direction in which the liquid crystal molecules **30a** are inclined by the orientation-regulating force exerted by the orientation-regulating structure **28** that is provided in a corresponding region.

When a stress is applied upon the LCD **200** in a steady state, the radially-inclined orientation of the liquid crystal layer **30** once collapses, but upon removal of the stress, the radially-inclined orientation is restored because of the orientation-regulating forces by the unit solid portion **14a'** and the orientation-regulating structure **28** acting upon the liquid

crystal molecules **30a**. Therefore, the occurrence of an after image due to a stress is suppressed. When the orientation-regulating force by the orientation-regulating structure **28** is excessively strong, retardation occurs even in the absence of an applied voltage due to the radially-inclined orientation, which may decrease the display contrast ratio. However, the orientation-regulating force by the orientation-regulating structure **28** does not have to be strong because it is only required to have an effect of stabilizing a radially-inclined orientation formed by an inclined electric field and fixing the central axis position thereof. Therefore, an orientation-regulating force that would not cause such a degree of retardation as to deteriorate the display quality is sufficient.

For example, when the protrusions (ribs) **22b** illustrated in FIG. 13B are employed, each protrusion **22b** may have a diameter of about 15 μm and a height (thickness) of about 1 μm for the unit solid portion **14a'** having a diameter of about 30 μm to about 35 μm . With such protrusions, a sufficient orientation-regulating force can be obtained and the reduction in the contrast ratio due to retardation can be suppressed to a practical level.

FIG. 16A and FIG. 16B illustrate another LCD **200'** including an orientation-regulating structure.

The LCD **200'** does not have the orientation-regulating structure in a region opposing the opening **14b1** of the picture element electrode **14**. Formation of the orientation-regulating structure **28** illustrated in FIG. 13E which should be formed in a region opposing the opening **14b1** introduces difficulties into the process. Therefore, in view of the productivity, it is preferred to use only one of the orientation-regulating structures **28** illustrated in FIG. 13A to FIG. 13D. Particularly, the orientation-regulating structure **28** illustrated in FIG. 13B is preferred because it can be produced by a simple process.

Even if no orientation-regulating structure is provided in a region corresponding to the opening **14b1** as in the LCD **200'**, substantially the same radially-inclined orientation as that of the LCD **200** is obtained, as schematically illustrated in FIG. 17A to FIG. 17C, and also the stress resistance thereof is at a practical level.

In a case where the protrusion **22b** as illustrated in FIG. 13B is employed as the orientation-regulating structure **28**, the thickness of the liquid crystal layer **30** may be defined by the protrusion **22b** as illustrated in FIG. 18A. In other words, the protrusion **22b** may function also as a spacer that controls the cell gap (the thickness of the liquid crystal layer **30**). Such an arrangement is advantageous in that it is not necessary to separately provide a spacer for defining the thickness of the liquid crystal layer **30**, thereby simplifying the production process.

In the illustrated example, the protrusion **22b** has a truncated cone shape with a side surface **22b1** that is inclined by a taper angle θ less than 90° with respect to the substrate plane of the substrate **21**. When the side surface **22b1** is inclined by an angle less than 90° with respect to the substrate plane, the side surface **22b1** of the protrusion **22b** has an orientation-regulating force of the same direction as that of the orientation-regulating force exerted by the inclined electric field for the liquid crystal molecules **30a** of the liquid crystal layer **30**, thereby functioning to stabilize the radially-inclined orientation.

As schematically illustrated in FIG. 18A to FIG. 18C, a radially-inclined orientation similar to that obtained with the LCD **200'** can be obtained also with the protrusion **22b** that functions also as a spacer.

While the protrusion **22b** has the side surface **22b1** that is inclined by an angle less than 90° with respect to the substrate plane in the example illustrated in FIG. 18A to FIG. 18C, the

protrusion **22b** may alternatively have the side surface **22b1** that is inclined by an angle of 90° or more with respect to the substrate plane. In view of the stability of the radially-inclined orientation, the inclination angle of the side surface **22b1** preferably does not significantly exceed 90° , and more preferably is less than 90° . Even if the inclination angle exceeds 90° , as long as it is close to 90° (as long as it does not significantly exceed 90°), the liquid crystal molecules **30a** in the vicinity of the side surface **22b1** of the protrusion **22b** are inclined in a direction substantially parallel to the substrate plane and thus take a radially-inclined orientation conforming with the inclination direction of the liquid crystal molecules **30a** at the edge portion, with only a slight twist. However, if the inclination angle of the side surface **22b1** of the protrusion **22b** significantly exceeds 90° as illustrated in FIG. 19, the side surface **22b1** of the protrusion **22b** will have an orientation-regulating force of the opposite direction to the orientation-regulating force exerted by the inclined electric field for the liquid crystal molecules **30a** of the liquid crystal layer **30**. This may result in unstable radially-inclined orientation.

The protrusion **22b** that functions also as a spacer is not limited to a protrusion having a truncated cone shape as illustrated in FIG. 18A to FIG. 18C. For example, the protrusion **22b** may have a shape as illustrated in FIG. 20 such that the cross section thereof in a plane vertical to the substrate plane is a part of an ellipse (i.e., a shape such as a part of an elliptical sphere). In the protrusion **22b** illustrated in FIG. 20, while the inclination angle (taper angle) of the side surface **22b1** with respect to the substrate plane varies along the thickness of the liquid crystal layer **30**, the inclination angle of the side surface **22b1** is less than 90° regardless of the position along the thickness of the liquid crystal layer **30**. Thus, the protrusion **22b** having such a shape may suitably be used as a protrusion for stabilizing a radially-inclined orientation.

It is not necessary that all of the protrusions **22b** provided in regions opposing the unit solid portions **14a'** function as spacers. By forming some of the protrusions **22b** to be lower than the other protrusions **22b** that function as spacers, the occurrence of light leakage can be suppressed.

Embodiment 3

In Embodiments 1 and 2, a CPA type LCD to which the present invention is applied is described. In this embodiment, an MVA type LCD to which the present invention is applied will be described.

With reference to FIG. 21, a basic structure of an MVA type LCD in this embodiment will be described.

An LCD **300** in this embodiment includes a plurality of picture element regions, each of which includes a first electrode **44**, a second electrode **52** opposing the first electrode **44**, and a vertical alignment type liquid crystal layer **30** provided between the first electrode **44** and the second electrode **52**. In the vertical alignment type liquid crystal layer **30**, liquid crystal molecules **30a** having a negative dielectric anisotropy are oriented generally vertical (for example, at an angle of 87° or greater but 90° or less) to surfaces of the first electrode **44** and the second electrode **52** in an absence of an applied voltage. The vertical alignment type liquid crystal layer **30** is typically obtained by providing a vertical alignment layer (not shown) on one surface of each of the first electrode **44** and the second electrode **52** which is closer to the liquid crystal layer **30**. In the case where ribs (protrusions) or the like are provided as orientation-regulating means, the

liquid crystal molecules **30a** are oriented generally vertical to a surface of the ribs or the like which is closer to the liquid crystal layer **30**.

The first electrode **44** has slits **44b**, and ribs **53** are provided on the surface of the second electrode **52** closer to the liquid crystal layer **30**. In each of liquid crystal regions defined between the slits **44b** and the ribs **53**, the liquid crystal molecules **30a** receive an orientation-regulating force by the slits **44b** and the rib **53**. When a voltage is applied between the first electrode **44** and the second electrode **52**, the liquid crystal molecules **30a** fall (are inclined) in the directions represented by the arrows in FIG. 21. Namely, in each liquid crystal region, the liquid crystal molecules **30a** are inclined in a uniform direction. Each liquid crystal region having the liquid crystal molecules **30a** inclined in a uniform direction is also referred to as a "liquid crystal domain". In a liquid crystal domain of a CPA type LCD, the liquid crystal molecules are oriented radially; whereas in a liquid crystal domain of an MVA type LCD, the liquid crystal molecules are oriented in one, uniform direction.

The slits **44b** and the ribs **53** (also collectively referred to as "orientation-regulating means"; corresponding to the domain-regulating means described in Japanese Patent No. 2947350) are provided in a strip pattern in each picture element region. FIG. 21 is a cross-sectional view of the LCD **300** taken in a direction perpendicular to the direction in which the strip-shaped orientation-regulating means is extended. On both sides of each orientation-regulating means, liquid crystal regions (liquid crystal domains) in which the liquid crystal molecules **30a** are inclined in directions different from each other by 180° are formed.

In the LCD **300**, the slits **44b** and the ribs **53** are extended in a strip pattern. When a potential difference is formed between the first electrode **44** and the second electrode **52**, each slit **44b** produces an inclined electric field at an edge portion of the slit **44b** so as to orient the liquid crystal molecules **30a** in a direction perpendicular to the direction in which the slit **44b** is extended. Each rib **53** orients the liquid crystal molecules **30a** generally vertical to a side surface **53a** thereof, and thus orients the liquid crystal molecules **30a** generally perpendicular to the direction in which the rib **53** is extended. The slits **44b** and the ribs **53** are provided parallel to each other with a certain gap interposed therebetween. A liquid crystal region (liquid crystal domain) is formed between a slit **44b** and a rib **53** which are adjacent to each other. Namely, the liquid crystal layer **30** is subjected to alignment division.

Next, with reference to FIG. 22 and FIG. 23, the structure of the LCD **300** will be described more specifically. FIG. 22 is a plan view schematically showing a structure of two picture element regions of the LCD **300**, and FIG. 23 is a cross-sectional view of the LCD **300** taken along line 23A-23A' of FIG. 22.

The LCD **300** includes an active matrix substrate (hereinafter, referred to as a "TFT substrate") **300a**, a counter substrate (also referred to as a "color filter substrate") **300b**, and a vertical alignment type liquid crystal layer **30** provided between the TFT substrate **300a** and the counter substrate **300b**.

The TFT substrate **300a** includes a transparent substrate (for example, a glass substrate) **41**. On one surface of the transparent substrate **41** which is closer to the liquid crystal layer **30**, gate bus lines (scanning lines; not shown), source bus lines (signal lines; not shown) and TFTs (not shown) are provided. An interlayer insulating film (transparent resin film) **42** covers the gate bus lines, the source bus lines and the TFTs. On the interlayer insulating film **42**, the picture ele-

ment electrode (first electrode) **44** is provided for each picture element region. The picture element electrode **44** is electrically connected to a corresponding TFT. In this example, the interlayer insulating film **42** is formed of a transparent resin film having a thickness of 1.5 μm or greater but 3.5 μm or less. Owing to such a structure, the picture element electrode **44** can partially overlap a gate bus line and/or a source bus line. This advantageously improves the numerical aperture.

The picture element electrode **44** includes a portion formed of a conductive film (i.e., a solid portion) **44a** and a strip-shaped slit (i.e., a non-solid portion) **44b**. The surface of the picture element electrode **44** which is closer to the liquid crystal layer **30** is substantially entirely covered with a vertical alignment film (not shown). As shown in FIG. 22, the slits **44b** are extended in a strip pattern, and have a uniform width (the size in a direction perpendicular to the direction in which the slits **44b** are extended). The slits **44b** adjacent to each other are parallel with a uniform gap (pitch).

The counter substrate **300b** has a transparent substrate (for example, a glass substrate) **51**. The counter electrode (second electrode) **52** is provided on the transparent substrate **51**. The ribs **53** are provided on the counter electrode **52**. The surface of the counter electrode **52** which is closer to the liquid crystal layer **30**, including the ribs **53b**, is substantially entirely covered with a vertical alignment film (not shown). As shown in FIG. 22, the ribs **53** are extended in a strip pattern, and have a uniform width (the size in a direction perpendicular to the direction in which the ribs **53** are extended). The ribs **53** adjacent to each other are parallel. Each rib **53** is provided so as to divide a gap between two slits **44b** adjacent thereto generally equally into two.

A strip-shaped liquid crystal region is defined between a strip-shaped slit **44b** and a strip-shaped rib **53** provided parallel to each other. The orientation direction of the liquid crystal molecules **30a** in each liquid crystal region is regulated by the slit **44b** and the rib **53** defining the liquid crystal region. On both sides of each slit **44b** and on both sides of each rib **53**, liquid crystal regions in which the liquid crystal molecules **30a** are inclined in directions different from each other by 180° are formed. In the LCD **300**, as shown in FIG. 22, the slits **44b** and the ribs **53** are extended in two directions which are different from each other by 90°. Thus, each picture element region includes four types of liquid crystal regions (liquid crystal domains), in which the orientation direction of the liquid crystal molecules **30a** are different from one another by 90°. The arrangement of the slits **44b** and the ribs **53** is not limited to the above-described arrangement, but this arrangement can provide a superb viewing angle characteristic.

A pair of polarization plates (not shown) provided externally to the TFT substrate **300a** and the counter substrate **300b** are arranged such that the transmission axes thereof are generally perpendicular to each other (in a cross Nicols state). It is preferable to provide the polarization plates such that the transmission axis of each polarization plate makes an angle of 45° with the orientation direction of the liquid crystal molecules **30a** in each of the four types of liquid crystal regions having orientation directions different by 90°. With such an arrangement, a change in retardation caused by the liquid crystal region can be utilized most efficiently. In other words, it is preferable to provide the polarization plates such that the transmission axis of each polarization plate makes an angle of about 45° with the direction in which the slits **44b** and the ribs **53** are extended. In the case of a display apparatus, the viewing direction to which is often moved horizontally with respect to the display plane, such as a TV, the polarization plates are preferably provided such that one of the transmis-

sion axes is horizontal with respect to the display plane, in order to suppress the viewing angle dependence of the display quality.

The MVA type LCD **300** having the above-described structure can display images with a superb viewing angle characteristic. In addition, in the LCD **300** according to the present invention, as shown in FIG. **23**, a portion of the liquid crystal layer **30** which is above the solid portion **44a** of the picture element electrode **44** includes a first region having a first thickness d_1 and a second region having a second thickness d_2 which is smaller than the first thickness d_1 . The second region is located in the vicinity of the slit **44b**, more specifically, between the first region and the slit **44b**. The response speed of the second region having a relatively small thickness d_2 is higher than the response speed of the first region having a relatively large thickness d_1 . The liquid crystal molecules **30a** in the second region located in the vicinity of the slit **44b** trigger the formation of a liquid crystal domain. Therefore, when the response speed of the liquid crystal molecules **30a** in the vicinity of the slit **44b** is higher, a liquid crystal domain is formed more quickly. As a result, the response speed of the entire liquid crystal layer **30** is increased. Thus, the LCD **300** according to the present invention has a superb response characteristic.

According to the present invention, the cell gap is not reduced in the entire picture element region but is reduced only in a portion thereof. Therefore, the response speed can be sufficiently improved with no need to increase the refractive index anisotropy (Δn) of the liquid crystal material. Specifically, in order to sufficiently improve the response speed, the difference between the thickness d_1 of the first region and the thickness d_2 of the second region is preferably $0.5 \mu\text{m}$ or greater, more preferably $1 \mu\text{m}$ or greater, and further preferably $1.5 \mu\text{m}$ or greater.

In this embodiment, as shown in FIG. **23**, the cell gap in the vicinity of the slit **44b** is made smaller by setting a surface of a portion of the solid portion **44a** in the vicinity of the slit **44b** (corresponding to the second region) to be higher than a surface of the remaining portion of the solid portion **44a** (corresponding to the first region). More specifically, an interlayer insulating film **42** is provided between the picture element electrode **44** and the transparent substrate **41**, and the height of the surface of the interlayer insulating film **42** is locally changed, such that the surface of the solid portion **44a** formed thereon is higher in the portion in the vicinity of the slit **44b** than in the remaining portion.

The interlayer insulating film **42** includes an inclining region **42a** where a height of one surface thereof which is closer to the liquid crystal layer **30** changes continuously and a flat region **42b** where the height of the surface thereof which is closer to the liquid crystal layer **30** is substantially constant. The portion of the solid portion **44a** in the vicinity of the slit **44b** (corresponding to the second region) is located on the inclining region **42a**, and the remaining portion of the solid portion **44a** (corresponding to the first region) is located on the flat region **42b**.

In view of the display quality, the inclination angle of the inclining region **42a** of the interlayer insulating film **42** (the inclination angle with respect to the surface of the substrate **41**) is preferably small, and the interlayer insulating film **42** preferably has a gentle slope. Specifically, the inclination angle of the inclining region **42a** of the interlayer insulating film **42** with respect to the surface of the substrate **41** is preferably 30° or less, and more preferably 20° or less.

Note that if the height of the surface of the solid portion **44a** changes continuously across the entire solid portion **44a**, the retardation of the liquid crystal layer **30** is no longer constant

across the solid portion **44a**, which may deteriorate the display quality. In such a case, it is difficult to suitably compensate for the phase difference by using a phase difference compensator or the like. In the case where the interlayer insulating film **42** includes the flat region **42b** where the height of the surface thereof which is closer to the liquid crystal layer **30** is substantially constant, as in the present embodiment, generation of such a problem can be suppressed.

The interlayer insulating film **42** having a gentle slope as described above can be formed by, for example, treating a photosensitive transparent resin film with a half exposure process.

In this embodiment, the liquid crystal layer **30** above the solid portion **44a** of the picture element electrode **44** includes the second region having a relatively small thickness d_2 in the vicinity of the slit **44b**, but not in the vicinity of an outer periphery of the picture element electrode **44**. With such a structure, the orientation in the liquid crystal layer **30** can further be stabilized and the response speed can be further improved. The reason for this will be described with reference to FIG. **24**.

FIG. **24** schematically shows the orientation of the liquid crystal layer **30a** in the vicinity of the slit **44b** and in the vicinity of an outer periphery **44E** of the picture element electrode **44**. Among the liquid crystal molecules **30a** above the solid portion **44a** of the picture element electrode **44**, the liquid crystal molecules **30a** in the vicinity of the slit **44b** are influenced by the inclined electric field to be inclined in a direction perpendicular to the direction in which the slit **44b** is extended. By contrast, the liquid crystal molecules **30a** influenced by the inclined electric field in the vicinity of the outer periphery **44E** of the picture element electrode **44** are inclined in a different direction from those in the vicinity of the slit **44b**. Namely, the liquid crystal molecules **30a** in the vicinity of the outer periphery **44E** of the picture element electrode **44** are inclined in a direction different from the predetermined direction which is defined by the orientation-regulating force of the slit **44b**, and thus disturb the orientation of the liquid crystal molecules **30a** in the liquid crystal domain. Thus, if the cell gap in the vicinity of the outer periphery **44E** of the picture element electrode **44** is reduced as the cell gap in the vicinity of the slit **44b**, the orientation-regulating force acting to disturb the orientation of the liquid crystal molecules **30a** in the liquid crystal domain is strengthened. As a result, the orientation in the liquid crystal domain is unstabilized and the response characteristic is deteriorated. By contrast, with a structure of this embodiment, in which the cell gap in the vicinity of the outer periphery **44E** of the picture element electrode **44** is not reduced, the orientation can be stabilized and the response characteristic can be improved.

In this embodiment, a display mode using linearly-polarized light is used. Alternatively, a display mode using circularly-polarized light may be used in order to suppress the influence of the two-step response behavior described above with reference to FIG. **5**.

Embodiment 4

A basic structure of an MVA type LCD **400** in this embodiment will be described with reference to FIG. **25**.

Whereas the LCD **300** shown in FIG. **21** has the slits **44b** and the ribs **53** as the orientation-regulating means, the LCD **400** in this embodiment has slits **62b** and slits **74b** as the orientation-regulating means. When a potential difference is formed between a first electrode **62** and a second electrode **74**,

each of the slits **62b** and the slits **74b** produces an inclined electric field in a portion of the liquid crystal layer **30** in the vicinity thereof so as to orient the liquid crystal molecules **30a** in a direction perpendicular to the direction in which the slits **62b** and the slits **74b** are extended. The slits **62b** and the slits **74b** are provided parallel to each other with a certain gap interposed therebetween. A liquid crystal region (liquid crystal domain) is formed between a slit **62b** and a slit **74b** which are adjacent to each other. An MVA type LCD including the slits **62b** and the slits **74b** as the orientation-regulating means, such as the LCD **400**, is also referred to as a PVA (Patterned Vertical Alignment) type LCD.

Next, with reference to FIG. **26** and FIG. **27**, the structure of the LCD **400** will be described more specifically. FIG. **26** is a plan view schematically showing a structure of two picture element regions of the LCD **400**, and FIG. **27** is a cross-sectional view of the LCD **400** taken along line **27A-27A'** of FIG. **26**.

The LCD **400** includes an active matrix substrate (hereinafter, referred to as a "TFT substrate") **400a**, a counter substrate (also referred to as a "color filter substrate") **400b**, and a vertical alignment type liquid crystal layer **30** provided between the TFT substrate **400a** and the counter substrate **400b**.

The TFT substrate **400a** includes a transparent substrate (for example, a glass substrate) **71**. On the surface of the transparent substrate **71** which is closer to the liquid crystal layer **30**, gate bus lines (scanning lines; not shown), source bus lines (signal lines; not shown) and TFTs (not shown) are provided. An interlayer insulating film (transparent resin film) **72** covers the gate bus lines, the source bus lines and the TFTs. On the interlayer insulating film **72**, the picture element electrode (second electrode) **74** is provided for each picture element region. The picture element electrode **74** is electrically connected to a corresponding TFT.

The picture element electrode **74** includes a portion formed of a conductive film (i.e., a solid portion) **74a** and a strip-shaped slit (i.e., a non-solid portion) **74b**. One surface of the picture element electrode **74** which is closer to the liquid crystal layer **30** is substantially entirely covered with a vertical alignment film (not shown). As shown in FIG. **26**, the slits **74b** are extended in a strip pattern, and have a uniform width (the size in a direction perpendicular to the direction in which the slits **74b** are extended). The slits **74b** adjacent to each other are parallel with a uniform gap (pitch).

The counter substrate **400b** has a transparent substrate (for example, a glass substrate) **61**. A color filter layer **65** is provided on the transparent substrate **61**. The counter electrode (first electrode) **62** is provided on the color filter layer **65**. The counter electrode **62**, like the picture element electrode **74**, includes a portion formed of a conductive film (i.e., a solid portion) **62a** and a strip-shaped slit (i.e., a non-solid portion) **62b**. One surface of the counter electrode **62** which is closer to the liquid crystal layer **30** is substantially entirely covered with a vertical alignment film (not shown). As shown in FIG. **26**, the slits **62b** are extended in a strip pattern, and have a uniform width (the size in a direction perpendicular to the direction in which the slits **62b** are extended). The slits **62b** adjacent to each other are parallel. Each slit **62b** is provided so as to divide a gap between two slits **74b** adjacent thereto generally equally into two.

A strip-shaped liquid crystal region is defined between a strip-shaped slit **62b** and a strip-shaped slit **74b** provided parallel to each other. The orientation direction of the liquid crystal molecules **30a** in each liquid crystal region is regulated by the slit **62b** and the slit **74b** defining the liquid crystal region. On both sides of each slit **62b** and on both sides of

each slit **74b**, liquid crystal regions in which the liquid crystal molecules **30a** are inclined in directions different from each other by 180° are formed. In the LCD **400**, as shown in FIG. **26**, the slits **62b** and the slits **74b** are extended in two directions which are different from each other by 90° . Thus, each picture element region includes four types of liquid crystal regions (liquid crystal domains), in which the orientation direction of the liquid crystal molecules **30a** are different from one another by 90° . The arrangement of the slits **62b** and the slits **74b** is not limited to the above-described arrangement, but this arrangement can provide a superb viewing angle characteristic.

A pair of polarization plates (not shown) provided externally to the TFT substrate **400a** and the counter substrate **400b** are arranged such that the transmission axes thereof are generally perpendicular to each other (in a cross Nicols state). It is preferable to provide the polarization plates such that the transmission axis of each polarization plate makes an angle of 45° with the orientation direction of the liquid crystal molecules **30a** in each of the four types of liquid crystal regions having orientation directions different by 90° . With such an arrangement, a change in retardation caused by the liquid crystal region can be utilized most efficiently. In other words, it is preferable to provide the polarization plates such that the transmission axis of each polarization plate makes an angle of about 45° with the direction in which the slits **62b** and the slits **74b** are extended. In the case of a display apparatus, the viewing direction to which is often moved horizontally with respect to the display plane, such as a TV, the polarization plates are preferably provided such that one of the transmission axes is horizontal with respect to the display plane, in order to suppress the viewing angle dependence of the display quality.

The MVA type LCD **400** having the above-described structure can display images with a superb viewing angle characteristic. In addition, in the LCD **400** according to the present invention, as shown in FIG. **27**, a portion of the liquid crystal layer **30** which is above the solid portion **62a** of the counter electrode **62** includes a first region having a first thickness d_1 and a second region having a second thickness d_2 which is smaller than the first thickness d_1 . The second region is located in the vicinity of the slit **62b**, more specifically, between the first region and the slit **62b**. The response speed of the second region having a relatively small thickness d_2 is higher than the response speed of the first region having a relatively large thickness d_1 . The liquid crystal molecules **30a** in the second region located in the vicinity of the slit **62b** trigger the formation of a liquid crystal domain. Therefore, when the response speed of the liquid crystal molecules **30a** in the vicinity of the slit **62b** is higher, a liquid crystal domain is formed more quickly. As a result, the response speed of the entire liquid crystal layer **30** is increased. Thus, the LCD **400** according to the present invention has a superb response characteristic.

According to the present invention, the cell gap is not reduced in the entire picture element region but is reduced only in a portion thereof. Therefore, the response speed can be sufficiently improved with no need to increase the refractive index anisotropy (Δn) of the liquid crystal material. Specifically, in order to sufficiently improve the response speed, the difference between the thickness d_1 of the first region and the thickness d_2 of the second region is preferably $0.5 \mu\text{m}$ or greater, more preferably $1 \mu\text{m}$ or greater, and further preferably $1.5 \mu\text{m}$ or greater.

In this embodiment, as shown in FIG. **27**, the cell gap in the vicinity of the slit **62b** is made smaller by setting a surface of a portion of the solid portion **62a** in the vicinity of the slit **62b**

(corresponding to the second region) to be higher, from the transparent substrate **61**, than a surface of the remaining portion of the solid portion **62a** (corresponding to the first region). More specifically, the height of the color filter layer **65** provided between the counter electrode **62** and the transparent substrate **61** is locally changed, such that the surface of the solid portion **62a** formed thereon is higher in the portion in the vicinity of the slit **62b** than in the remaining portion from the transparent substrate **61**.

The color filter layer **65** includes an inclining region **65a** where a height of one surface thereof which is closer to the liquid crystal layer **30** changes continuously and a flat region **65b** where the height of the surface thereof which is closer to the liquid crystal layer **30** is substantially constant. The portion of the solid portion **65a** in the vicinity of the slit **62b** (corresponding to the second region) is located on the inclining region **65a**, and the remaining portion of the solid portion **62a** (corresponding to the first region) is located on the flat region **65b**.

In view of the display quality, the inclination angle of the inclining region **65a** of the color filter layer **65** (the inclination angle with respect to the surface of the substrate **61**) is preferably small, and the color filter layer **65** preferably has a gentle slope. Specifically, the inclination angle of the inclining region **65a** of the color filter layer **65** with respect to the surface of the substrate **61** is preferably 30° or less, and more preferably 20° or less.

Note that if the height of the surface of the solid portion **62a** changes continuously across the entire solid portion **62a**, the retardation of the liquid crystal layer **30** is no longer constant across the solid portion **62a**, which may deteriorate the display quality. In such a case, it is difficult to suitably compensate for the phase difference by using a phase difference compensator or the like. In the case where the color filter layer **65** includes the flat region **65b** where the height of the surface which is closer to the liquid crystal layer **30** is substantially constant, as in the present embodiment, generation of such a problem can be suppressed.

The color filter layer **65** having a gentle slope as described above can be formed by, for example, treating a photosensitive transparent resin film containing a pigment with a half exposure process. Alternatively, the color filter layer **65** as described above may be obtained by first forming an underlying layer on a portion of the transparent substrate **61** corresponding to the non-solid portion **62b** and then forming a color filter layer thereon.

In this embodiment, the cell gap in the vicinity of the slit **62b** of the counter electrode **62** is reduced. Alternatively, the cell gap in the vicinity of the slit **74b** of the picture element electrode **74** may be reduced, or both the cell gap in the vicinity of the slit **62b** of the counter electrode **62** and the cell gap in the vicinity of the slit **74b** of the picture element electrode **74** may be reduced. For further improving the response characteristic, it is preferable to reduce both the cell gap in the vicinity of the slit **62b** of the counter electrode **62** and the cell gap in the vicinity of the slit **74b** of the picture element electrode **74**. For restricting an increase in the number of production steps and thus the production cost, it is preferable to reduce one of the cell gaps.

Embodiment 5

A MVA type LCD **500** in this embodiment will be described with reference to FIG. **28** and FIG. **29**. FIG. **28** is a plan view schematically showing a structure of two picture

element regions of the LCD **500**, and FIG. **29** is a cross-sectional view of the LCD **500** taken along line **29A-29A'** of FIG. **28**.

The MVA type LCD **500** in this embodiment has slits **84b** and ribs **93** as the orientation-regulating means. The basic orientation mechanism is the same as that of the LCD **300** shown in FIG. **21**.

The LCD **500** includes a TFT substrate **500a**, a counter substrate **500b**, and a vertical alignment type liquid crystal layer **30** provided between the TFT substrate **500a** and the counter substrate **500b**. The TFT substrate **500a** includes a transparent substrate (for example, a glass substrate) **81**, an interlayer insulating film (transparent resin film) **82**, and a picture element electrode **84**. The picture element electrode **84** includes a portion formed of a conductive film (i.e., a solid portion) **84a** and a strip-shaped slit (i.e., a non-solid portion) **84b**. The counter substrate **500b** includes a transparent substrate (for example, a glass substrate) **91**. A counter electrode **92** is provided on the transparent substrate **91**, and the ribs **93** are provided on the counter electrode **92**.

The planar positional relationship between the slits **84b** and the ribs **93b** (the positional relationship when seen in the substrate normal direction) is the same as that of the slits **44b** and the ribs **53** of the LCD **300**. When a voltage is applied, four types of liquid crystal regions (liquid crystal domains) are formed, in which the orientation direction of the liquid crystal molecules **30a** are different from one another by 90°.

A portion of the liquid crystal layer **30** which is above the solid portion **84a** of the picture element electrode **84** includes a first region having a first thickness d_1 and a second region having a second thickness d_2 which is larger than the first thickness d_1 . The second region is located in the vicinity of the outer periphery of the picture element electrode **84**, and the first region is located inner to the second region. Namely, in the LCD **500**, the cell gap in the vicinity of the outer periphery of the picture element electrode **84** is selectively made large.

As described above with reference to FIG. **24**, the liquid crystal molecules **30a** in the vicinity of the outer periphery of the picture element electrode would be inclined in a direction different from the predetermined direction defined by the orientation-regulating force of the slits **84b** and thus disturb the orientation of the liquid crystal molecules **30a** in the liquid crystal domain. In this embodiment, however, the thickness of the liquid crystal layer **30** in the vicinity of the outer periphery of the picture element electrode **84** is selectively made large. This structure can weaken the orientation-regulating force in the vicinity of the outer periphery of the picture element electrode **84** (which is not aligned with the orientation-regulating force provided by the slits **84b**). As a result, the orientation can be stabilized and the response characteristic can be improved.

As a technique for reducing the orientation-regulating force in the vicinity of the outer periphery of the picture element electrode **84**, it is conceivable to reduce the pitch of the picture element electrodes **84**. However, this increases the possibility of shortcircuiting occurring between adjacent picture element electrodes **84**, and thus declines the reliability of the LCD. By contrast, the LCD **500** according to the present invention does not have such a problem.

The effect of reducing the orientation-regulating force in the vicinity of the outer periphery of the picture element electrode **84** is greater as the thickness d_2 of the second region is greater and also as the difference between the thickness d_1 of the first region and the thickness d_2 of the second region is greater. Specifically, in order to sufficiently weaken the orientation-regulating force in the vicinity of the outer periphery

of the picture element electrode **84**, the difference between the thickness d_1 of the first region and the thickness d_2 of the second region is preferably 0.5 μm or greater, more preferably 1 μm or greater, and further preferably 1.5 μm or greater.

In this embodiment, as shown in FIG. 29, the cell gap in the vicinity of the outer periphery of the picture element electrode **84** is made larger by setting a surface of a portion of the solid portion **84a** in the vicinity of the outer periphery of the picture element electrode **84** (corresponding to the second region) to be lower than a surface of the remaining portion of the solid portion **84a** (corresponding to the first region). More specifically, the height of the interlayer insulating film **82** provided between the picture element electrode **84** and the transparent substrate **81** is locally changed, such that the surface of the solid portion **84a** formed thereon is lower in the portion in the vicinity of the outer periphery of the picture element electrode **84** than in the remaining portion.

The interlayer insulating film **82** includes an inclining region **82a** where a height of one surface thereof which is closer to the liquid crystal layer **30** changes continuously and a flat region **82b** where the height of the surface thereof which is closer to the liquid crystal layer **30** is substantially constant. The portion of the solid portion **84a** in the vicinity of the outer periphery of the picture element electrode **84** (corresponding to the second region) is located on the inclining region **82a**, and the remaining portion of the solid portion **84a** (corresponding to the first region) is located on the flat region **82b**.

In view of the display quality, the inclination angle of the inclining region **82a** of the interlayer insulating film **82** (the inclination angle with respect to the surface of the substrate **81**) is preferably small, and the interlayer insulating film **82** preferably has a gentle slope. Specifically, the inclination angle of the inclining region **82a** of the interlayer insulating film **82** with respect to the surface of the substrate **81** is preferably 30° or less, and more preferably 20° or less.

Note that if the height of the surface of the solid portion **84a** changes continuously across the entire solid portion **84a**, the retardation of the liquid crystal layer **30** is no longer constant across the solid portion **84a**, which may deteriorate the display quality. In such a case, it is difficult to suitably compensate for the phase difference by using a phase difference compensator or the like. In the case where the interlayer insulating film **82** includes the flat region **82b** where the height of the surface which is closer to the liquid crystal layer **30** is substantially constant, as in the present embodiment, generation of such a problem can be suppressed.

The interlayer insulating film **82** having a gentle slope as described above can be formed by, for example, treating a photosensitive transparent resin film with a half exposure process.

According to the present invention, the response characteristic of an alignment-divided vertical alignment type LCD can be improved in a simple manner. The present invention is preferably usable in a CPA type LCD and an MVA type LCD.

While the present invention has been described with respect to preferred embodiments thereof, it will be apparent to those skilled in the art that the disclosed invention may be modified in numerous ways and may assume many embodiments other than those specifically described above. Accordingly, it is intended by the appended claims to cover all modifications of the invention that fall within the true spirit and scope of the invention.

This non-provisional application claims priority under 35 USC § 119(a) on Patent Application No. 2004-129248 filed in Japan on Apr. 26, 2004, the entire contents of which are hereby incorporated by reference.

What is claimed is:

1. A liquid crystal display device, comprising:

a first substrate;

a second substrate; and

a vertical alignment type liquid crystal layer provided between the first substrate and the second substrate, wherein:

a plurality of picture element regions are each defined by a first electrode provided on one surface of the first substrate which is closer to the liquid crystal layer and a second electrode provided on the second substrate and opposing the first electrode with the liquid crystal layer therebetween;

in each of the plurality of picture element regions, the first electrode includes a solid portion formed of a conductive film and a non-solid portion with no conductive film provided, and the liquid crystal layer has an orientation which is regulated by an inclined electric field produced above the non-solid portion of the first electrode when a voltage is applied between the first electrode and the second electrode;

a portion of the liquid crystal layer above the solid portion of the first electrode includes a first region having a first thickness d_1 and a second region having a second thickness d_2 which is smaller than the first thickness d_1 , the second region being located in the vicinity of the non-solid portion; and

wherein the first substrate includes a transparent substrate and an interlayer insulating layer provided between at least the transparent substrate and at least a majority of each of the solid portions of the first electrode, and wherein the interlayer insulating layer includes an inclining region where a height of one surface thereof closer to the liquid crystal layer changes substantially continuously, and wherein an edge portion of the solid portion of the first electrode in the second region is located on the inclining region.

2. The liquid crystal display device according to claim 1, wherein when a voltage is applied between the first electrode and the second electrode, the liquid crystal layer forms a plurality of first liquid crystal domains each taking a radially-inclined orientation above the solid portion by the inclined electric field.

3. The liquid crystal display device according to claim 2, wherein:

the solid portion of the first electrode includes a plurality of unit solid portions, above each of which a respective first liquid crystal domain of the plurality of first liquid crystal domains is formed; and

the second region of the portion of the liquid crystal layer above the solid portion is located above an edge portion of at least one unit solid portion of the plurality of unit solid portions.

4. The liquid crystal display device according to claim 3, wherein a height of a surface of a portion of the at least one unit solid portion corresponding to the second region is higher than a height of a surface of a portion of the at least one unit solid portion corresponding to the first region.

5. The liquid crystal display device according to claim 4, wherein:

the interlayer insulating film includes a flat region where the height of the surface thereof closer to the liquid crystal layer is substantially constant; and

the portion of the at least one unit solid portion corresponding to the first region is located on the flat region.

6. The liquid crystal display device according to claim 4, wherein the interlayer insulating film is formed of a photo-sensitive transparent resin.

7. The liquid crystal display device according to claim 3, wherein light incident on the liquid crystal layer is circularly-polarized light, and display is provided by modulating the circularly-polarized light by the liquid crystal layer.

8. The liquid crystal display device according to claim 3, wherein an orientation in the plurality of first liquid crystal domains and an orientation in a portion of the liquid crystal layer above the non-solid portion are continuous with each other.

9. The liquid crystal display device according to claim 3, wherein the plurality of unit solid portions each have a shape having rotational symmetry.

10. The liquid crystal display device according to claim 9, wherein the plurality of unit solid portions are each generally circular.

11. The liquid crystal display device according to claim 9, wherein the plurality of unit solid portions are each generally rectangular.

12. The liquid crystal display device according to claim 9, wherein the plurality of unit solid portions are each generally rectangular with rounded corners.

13. The liquid crystal display device according to claim 9, wherein the plurality of unit solid portions each have a shape with acute angle corner portions.

14. The liquid crystal display device according to claim 2, wherein when a voltage is applied between the first electrode and the second electrode, the liquid crystal layer forms at least one second liquid crystal domain taking a radially-inclined orientation above the non-solid portion by the inclined electric field.

15. The liquid crystal display device according to claim 14, wherein an orientation in the plurality of first liquid crystal domains and an orientation in the at least one second liquid crystal domain are continuous with each other.

16. The liquid crystal display device according to claim 2, wherein the non-solid portion of the first electrode has at least one opening.

17. The liquid crystal display device according to claim 16, wherein the at least one opening includes a plurality of openings, and at least a part of the plurality of openings have substantially the same shape and substantially the same size and form at least one unit lattice which is arranged so as to have rotational symmetry.

18. The liquid crystal display device according to claim 17, wherein the at least a part of the plurality of openings each have a shape having rotational symmetry.

19. The liquid crystal display device according to claim 2, wherein the non-solid portion of the first electrode has at least one cut-out portion.

20. The liquid crystal display device according to claim 19, wherein the at least one cut-out portion includes a plurality of cut-out portions, and the plurality of cut-out portions are regularly arranged.

21. The liquid crystal display device according to claim 2, wherein in each of the plurality of picture element regions, an area of the non-solid portion of the first electrode is smaller than an area of the solid portion of the first electrode.

22. The liquid crystal display device according to claim 2, wherein the second substrate has an orientation-regulating structure in a region corresponding to at least one first liquid crystal domain of the plurality of first liquid crystal domains, the orientation-regulating structure exerting an orientation-regulating force for placing the liquid crystal molecules in the

at least one first liquid crystal domain into a radially-inclined orientation at least in the presence of an applied voltage.

23. The liquid crystal display device according to claim 22, wherein the orientation-regulating structure is provided in a region corresponding to a central portion of the at least one first liquid crystal domain.

24. The liquid crystal display device according to claim 22, wherein the orientation-regulating structure exerts an orientation-regulating force for placing the liquid crystal molecules into a radially-inclined orientation also in the absence of an applied voltage.

25. The liquid crystal display device according to claim 24, wherein the orientation-regulating structure is a protrusion protruding from the second substrate through the liquid crystal layer.

26. The liquid crystal display device according to claim 25, wherein a thickness of the liquid crystal layer is defined by the protrusion protruding from the second substrate through the liquid crystal layer.

27. The liquid crystal display device according to claim 1, wherein the non-solid portion of the first electrode is a slit provided in the first electrode.

28. The liquid crystal display device according to claim 27, wherein a height of a surface of a portion of the solid portion of the first electrode corresponding to the second region is higher than a height of a surface of a portion of the solid portion corresponding to the first region.

29. The liquid crystal display device according to claim 28, wherein:

the interlayer insulating film includes a flat region where the height of the surface thereof closer to the liquid crystal layer is substantially constant; and the portion of the solid portion of the first electrode corresponding to the first region is located on the flat region.

30. The liquid crystal display device according to claim 28, wherein the interlayer insulating film is formed of a photo-sensitive transparent resin.

31. The liquid crystal display device according to claim 28, wherein:

the first substrate includes a transparent substrate and a color filter layer provided between the transparent substrate and the first electrode;

the color filter layer includes an inclining region where a height of one surface thereof closer to the liquid crystal layer continuously changes; and

the portion of the solid portion of the first electrode corresponding to the second region is located on the inclining region.

32. The liquid crystal display device according to claim 31, wherein:

the color filter layer includes a flat region where the height of the surface thereof closer to the liquid crystal layer is substantially constant; and

the portion of the solid portion of the first electrode corresponding to the first region is located on the flat region.

33. The liquid crystal display device according to claim 27, wherein light incident on the liquid crystal layer is circularly-polarized light, and display is provided by modulating the circularly-polarized light by the liquid crystal layer.

34. The liquid crystal display device according to claim 27, further comprising a pair of polarization plates opposing each other with the liquid crystal layer therebetween, the pair of polarization plates have transmission axes generally perpendicular to each other, one of the transmission axes is located horizontal to a display plane, and the slit is extended in a direction which is inclined with respect to the one of the transmission axes.

41

35. The liquid crystal display device according to claim 34, wherein the slit is extended in a direction which makes an angle of about 45° with the one of the transmission axes.

36. The liquid crystal display device according to claim 27, wherein the second substrate has an orientation-regulating structure exerting an orientation-regulating force which is aligned with the orientation-regulating force provided by the inclined electric field at least in the presence of an applied voltage.

37. The liquid crystal display device according to claim 36, wherein the orientation-regulating structure of the second substrate is a rib.

38. The liquid crystal display device according to claim 36, wherein the orientation-regulating structure of the second substrate is a slit provided in the second electrode.

39. The liquid crystal display device according to claim 27, wherein:

the first substrate further includes a switching element provided in correspondence with each of the plurality of picture element regions; and

the first electrode is a picture element electrode provided in correspondence with each of the plurality of picture element regions and electrically connected to the switching element, and the second electrode is at least one counter electrode opposing the plurality of picture element electrodes.

40. The liquid crystal display device according to claim 39, wherein a portion of the liquid crystal layer above the solid portion of the picture element electrode does not have the second region in the vicinity of an outer periphery of the picture element electrode.

41. A liquid crystal display device, comprising:

a first substrate;

a second substrate; and

a vertical alignment type liquid crystal layer provided between the first substrate and the second substrate, wherein:

a plurality of picture element regions are each defined by a first electrode provided on one surface of the first substrate which is closer to the liquid crystal layer and a second electrode provided on the second substrate and opposing the first electrode with the liquid crystal layer therebetween;

in each of the plurality of picture element regions, the first electrode includes a solid portion formed of a conductive film and a non-solid portion with no conductive film provided, and when a voltage is applied between the first electrode and the second electrode, the liquid crystal layer forms a plurality of first liquid crystal domains each taking a radially-inclined orientation above the solid portion by an inclined electric field produced above the non-solid portion of the first electrode;

the solid portion of the first electrode includes a plurality of unit solid portions, above each of which a respective first liquid crystal domain of the plurality of first liquid crystal domains is formed;

a portion of the liquid crystal layer above at least one unit solid portion of the plurality of unit solid portions includes a first region having a first thickness d_1 and a second region having a second thickness d_2 which is smaller than the first thickness d_1 , the second region being located above an edge portion of the unit solid portion; and

wherein the first substrate includes a transparent substrate and an interlayer insulating layer provided between at least the transparent substrate and at least a majority of each of the solid portions of the first electrode, and

42

wherein the interlayer insulating layer includes an inclining region where a height of one surface thereof closer to the liquid crystal layer changes substantially continuously, and wherein an edge portion of the solid portion of the first electrode in the second region is located on the inclining region.

42. A liquid crystal display device, comprising:

a first substrate;

a second substrate; and

a vertical alignment type liquid crystal layer provided between the first substrate and the second substrate, wherein:

a plurality of picture element regions are each defined by a first electrode provided on one surface of the first substrate which is closer to the liquid crystal layer and a second electrode provided on the second substrate and opposing the first electrode with the liquid crystal layer therebetween;

in each of the plurality of picture element regions, the first electrode includes a solid portion formed of a conductive film and a slit, and the liquid crystal layer has an orientation which is regulated by an inclined electric field produced above the slit of the first electrode when a voltage is applied between the first electrode and the second electrode;

a portion of the liquid crystal layer above the solid portion of the first electrode includes a first region having a first thickness d_1 and a second region having a second thickness d_2 which is smaller than the first thickness d_1 , the second region being located in the vicinity of the slit; and wherein the first substrate includes a transparent substrate and an interlayer insulating layer provided between at least the transparent substrate and at least a majority of each of the solid portions of the first electrode, and wherein the interlayer insulating layer includes an inclining region where a height of one surface thereof closer to the liquid crystal layer changes substantially continuously, and wherein an edge portion of the solid portion of the first electrode in the second region is located on the inclining region.

43. A liquid crystal display device, comprising:

a first substrate;

a second substrate; and

a vertical alignment type liquid crystal layer provided between the first substrate and the second substrate, wherein:

a plurality of picture element regions are each defined by a first electrode provided on one surface of the first substrate which is closer to the liquid crystal layer and a second electrode provided on the second substrate and opposing the first electrode with the liquid crystal layer therebetween;

in each of the plurality of picture element regions, the first electrode includes a solid portion formed of a conductive film and a slit, and the liquid crystal layer has an orientation which is regulated by an inclined electric field produced above the slit of the first electrode when a voltage is applied between the first electrode and the second electrode;

the first substrate further includes a switching element provided in correspondence with each of the plurality of picture element regions;

the first electrode is a picture element electrode provided in correspondence with each of the plurality of picture element regions and electrically connected to the

43

switching element, and the second electrode is at least one counter electrode opposing the plurality of picture element electrodes; and

a portion of the liquid crystal layer above the solid portion of the picture element electrode includes a first region having a first thickness d_1 and a second region having a second thickness d_2 which is larger than the first thickness d_1 , the second region being located in the vicinity of an outer periphery of the picture element electrode.

44. The liquid crystal display device according to claim 43, wherein a height of a surface of a portion of the solid portion corresponding to the second region is lower than a height of a surface of a portion of the solid portion corresponding to the first region.

45. The liquid crystal display device according to claim 44, wherein:

the first substrate includes a transparent substrate and an interlayer insulating film provided between the transparent substrate and the first electrode;

the interlayer insulating layer includes an inclining region where a height of one surface thereof closer to the liquid crystal layer continuously changes; and

the portion of the solid portion corresponding to the second region is located on the inclining region.

44

46. The liquid crystal display device according to claim 45, wherein:

the interlayer insulating film includes a flat region where the height of the surface thereof closer to the liquid crystal layer is substantially constant; and

the portion of the solid portion corresponding to the first region is located on the flat region.

47. The liquid crystal display device according to claim 45, wherein the interlayer insulating film is formed of a photosensitive transparent resin.

48. The liquid crystal display device according to claim 43, further comprising a pair of polarization plates opposing each other with the liquid crystal layer therebetween, the pair of polarization plates have transmission axes generally perpendicular to each other, one of the transmission axes is located horizontal to a display plane, and the slit is extended in a direction which is inclined with respect to the one of the transmission axes.

49. The liquid crystal display device according to claim 48, wherein the slit is extended in a direction which makes an angle of about 45° with the one of the transmission axes.

* * * * *

专利名称(译)	液晶显示装置		
公开(公告)号	US7499136	公开(公告)日	2009-03-03
申请号	US11/114022	申请日	2005-04-26
[标]申请(专利权)人(译)	夏普株式会社		
申请(专利权)人(译)	夏普株式会社		
当前申请(专利权)人(译)	夏普株式会社		
[标]发明人	KUBO MASUMI		
发明人	KUBO, MASUMI		
IPC分类号	G02F1/1343 G02F1/1337 G02F1/1333 G02F1/139		
CPC分类号	G02F1/133707 G02F1/1393 G02F1/133371 G02F1/134309		
优先权	2004129248 2004-04-26 JP		
其他公开文献	US20050237463A1		
外部链接	Espacenet USPTO		

摘要(译)

本发明的LCD包括第一基板，第二基板和设置在它们之间的垂直取向型液晶层。在每个像素区域中，设置在液晶层一侧的第一基板上的第一电极具有由导电膜形成的实心部分和不提供导电膜的非实心部分。当施加电压时，液晶层具有由在第一电极的非实心部分上方产生的倾斜电场调节的取向。在实心部分上方的液晶层的一部分包括具有第一厚度d1的第一区域和具有小于第一厚度d1并且位于非实心部分附近的第二厚度d2的第二区域。

