



US008537320B2

(12) **United States Patent**
Kwon et al.

(10) **Patent No.:** **US 8,537,320 B2**
(45) **Date of Patent:** **Sep. 17, 2013**

(54) **LIQUID CRYSTAL DISPLAY DEVICE
COMPRISING FIRST AND SECOND DATA
LINK LINES ELECTRICALLY CONNECTED
TO ODD AND EVEN DATA LINES
RESPECTIVELY AND CROSSING EACH
OTHER TO CONNECT EVEN AND ODD DATA
PAD ELECTRODES RESPECTIVELY**

(75) Inventors: **Jang-Un Kwon**, Seoul (KR); **Su-Woong Lee**, Gumi-si (KR)

(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 990 days.

(21) Appl. No.: **12/247,671**

(22) Filed: **Oct. 8, 2008**

(65) **Prior Publication Data**
US 2009/0096975 A1 Apr. 16, 2009

(30) **Foreign Application Priority Data**
Oct. 16, 2007 (KR) 10-2007-0104092

(51) **Int. Cl.**
G02F 1/1345 (2006.01)
G02F 1/1333 (2006.01)

(52) **U.S. Cl.**
USPC **349/149**; 349/138

(58) **Field of Classification Search**
USPC 349/41–43, 138–139, 142–145, 149
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2004/0036070 A1* 2/2004 Yun 257/59
2006/0139551 A1 6/2006 Kimura

FOREIGN PATENT DOCUMENTS

KR 10-2007-0003178 A 1/2007
TW 2006/17553 6/2006

OTHER PUBLICATIONS

First Office Action issued in corresponding Taiwanese Patent Application No. 097136678; issued May 24, 2012.

* cited by examiner

Primary Examiner — Paul Lee

(74) *Attorney, Agent, or Firm* — Brinks Hofer Gilson & Lione

(57) **ABSTRACT**

A liquid crystal display device includes a gate line on a substrate including a display region and a non-display region; odd and even data lines crossing the gate line to define a pixel region in the display region; a thin film transistor connected to the gate line and one of the odd and even data lines; a pixel electrode in the pixel region and connected to the thin film transistor; first and second data link lines electrically connected to the odd and even data lines, respectively, and formed with a gate insulating layer therebetween; and first and second data pad electrodes at one ends of the first and second data link lines, respectively.

1 Claim, 11 Drawing Sheets




FIG. 1
RELATED ART




FIG. 2
RELATED ART




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 9





FIG. 10



**LIQUID CRYSTAL DISPLAY DEVICE
COMPRISING FIRST AND SECOND DATA
LINK LINES ELECTRICALLY CONNECTED
TO ODD AND EVEN DATA LINES
RESPECTIVELY AND CROSSING EACH
OTHER TO CONNECT EVEN AND ODD DATA
PAD ELECTRODES RESPECTIVELY**

The present invention claims the benefit of Korean Patent Application No. 2007-0104092, filed in Korea on Oct. 16, 2007, which is hereby incorporated by reference for all purposes as if fully set forth herein.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display device, and more particularly, to a liquid crystal display (LCD) device and a method of manufacturing the same.

2. Discussion of the Related Art

Until recently, display devices have typically used cathode-ray tubes (CRTs). Presently, many efforts and studies are being made to develop various types of flat panel displays, such as liquid crystal display (LCD) devices, plasma display panels (PDPs), field emission displays, and electro-luminescence displays (ELDs), as a substitute for CRTs. Of these flat panel displays, LCD devices have many advantages, such as high resolution, light weight, thin profile, compact size, and low voltage power supply requirements.

In general, an LCD device includes two substrates that are spaced apart and face each other with a liquid crystal material interposed between the two substrates. The two substrates include electrodes that face each other such that a voltage applied between the electrodes induces an electric field across the liquid crystal material. Alignment of the liquid crystal molecules in the liquid crystal material changes in accordance with the intensity of the induced electric field into the direction of the induced electric field, thereby changing the light transmissivity of the LCD device. Thus, the LCD device displays images by varying the intensity of the induced electric field.

FIG. 1 is a schematic view illustrating an array substrate of an LCD device according to the related art.

Referring to FIG. 1, the array substrate includes a display region AA to display images and a non-display region NAA. The array substrate 10 includes first to m^{th} gate lines GL1 to GLm and first to n^{th} data lines DL1 to DLn crossing each other on a substrate 10 to define a plurality of pixel regions P in the display region AA. A thin film transistor T is in each pixel region P and connected to the corresponding gate and data lines, and a pixel electrode 80 is in each pixel region P and connected to the thin film transistor T.

In the non-display region NAA, the array substrate includes first to m^{th} gate link lines GLL1 to GLLm and first to n^{th} data link lines DLL1 to DLLn, first to m^{th} gate pads GP1 to GPm connected to the first to m^{th} gate link lines GLL1 to GLLm, respectively, first to n^{th} data pads DP1 to DPn connected to the first to n^{th} data link lines DLL1 to DLLn, respectively. The first to m^{th} gate lines GL1 to GLm are connected to the first to m^{th} gate link lines GLL1 to GLLm, respectively, and the first to n^{th} data lines DL1 to DLn are connected to the first to n^{th} data link lines DLL1 to DLLn, respectively.

The gate pads GP1 to GPm and the data pads DP1 to DPn are attached to gate and data driving portions, for example, through a TAB (tape automated bonding) process. Accord-

ingly, gate and data signals are supplied from the driving portions to the gate and data lines GL1 to GLm to DL1 to DLn.

In the related art, the gate lines, the gate link lines and the gate pads are formed at the same layer, and the data lines, the data link lines and the data pads are formed at the same layer. Accordingly, there is a limit to reducing an area of the non-display region. This problem is explained as follows.

FIG. 2 is a view enlarging a portion A of FIG. 1.

Referring to FIG. 2, in a display region AA, gate lines include odd and even gate lines 20a and 20b alternately arranged on a substrate 10, and data lines include odd and even data lines 30a and 30b alternately arranged.

A thin film transistor T includes a gate electrode 25, a semiconductor layer 40 on the gate electrode 25, and source and drain electrodes 32 and 34 on the semiconductor layer 40. The semiconductor layer 40 includes an active layer made of intrinsic amorphous silicon and an ohmic contact layer made of extrinsic amorphous silicon. A pixel electrode 80 in a pixel region P is connected to the drain electrode 34.

A non-display region NAA includes a data link region DLA, and a data pad region DPA. In the data link region DLA, data link lines include odd and even data link lines 50a and 50b alternately arranged. In the data pad region DPA, data pads include odd and even data pads. The odd data pad include an odd data pad electrode 60a and an odd data pad terminal electrode 70 connected to the odd data pad electrode 60a through an odd data pad contact hole DPH1. The even data pad include an even data pad electrode 60b and an even data pad terminal electrode 70b connected to an even data pad contact hole DPH2.

The odd and even data lines 30a and 30b, the odd and even data link lines 50a and 50b, and the odd and even data pad electrodes 60a and 60b are formed at the same layer.

To reduce an area of the non-display region NAA, it is suggested to reduce areas of the data pads. This, however, causes increase of resistance of the data pad and delay of the data signal, and thus, display degradation, for example, after-image occurs.

Alternatively, when a width CD of the data link line is reduced, this causes increase of resistance of the data link line and delay of the data signal. Accordingly, reduction of the width of the data link line has a limit.

Alternatively, it has been suggested to reduce an area of the data link region DLA and form the data pad region DPA closer to the display region AA. This involves reducing distances P1, P2 and P3 between the data link lines. As the distances are reduced, the data link lines may be subject to a short-circuit due to conductive particles, which are in a process chamber, stuck to the data link lines.

These problems make it difficult to reduce the area of the non-display region.

SUMMARY OF THE INVENTION

A liquid crystal display device includes a gate line on a substrate including a display region and a non-display region; odd and even data lines crossing the gate line to define a pixel region in the display region; a thin film transistor connected to the gate line and one of the odd and even data lines; a pixel electrode in the pixel region and connected to the thin film transistor; first and second data link lines electrically connected to the odd and even data lines, respectively, and formed with a gate insulating layer therebetween; and first and second data pad electrodes at one ends of the first and second data link lines, respectively.

In another aspect, a method of manufacturing a liquid crystal display device includes forming a gate line, a first data link line and a first data pad electrode at an end of the first data link line on a substrate; forming a gate insulating layer on the gate line, the first data link line and the first data pad electrode; forming odd and even data lines, a second data link line and a second data pad electrode at an end of the second data link line, wherein one of the first and second data link lines is electrically connected to the odd data line, and the other of the first and second data link lines is electrically connected to the even data line; forming a thin film transistor connected to the gate line and one of the odd and even data lines; forming a passivation layer on the odd and even data lines, the second data link line, the second data pad electrode; and forming a pixel electrode on the passivation layer and connected to the thin film transistor.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

In the drawings:

FIG. 1 is a schematic view illustrating an array substrate of an LCD device according to the related art;

FIG. 2 is a view enlarging a portion A of FIG. 1;

FIG. 3 is a plan view illustrating an array substrate of an LCD device according to a first embodiment of the present invention;

FIG. 4 is a plan view enlarging a portion B of FIG. 3;

FIGS. 5A and 5B are cross-sectional views taken along lines Va-Va and Vb-Vb, respectively;

FIGS. 6A to 6D are cross-sectional views, taken along the line Va-Va of FIG. 4, illustrating processes of manufacturing the array substrate of the LCD device according to the first embodiment of the present invention;

FIGS. 7A to 7D are cross-sectional views, taken along the line Vb-Vb of FIG. 4, illustrating processes of manufacturing the array substrate of the LCD device according to the first embodiment of the present invention;

FIGS. 8A to 8D are cross-sectional views, taken along a line VIII-VIII of FIG. 4, illustrating processes of manufacturing the array substrate of the LCD device according to the first embodiment of the present invention;

FIG. 9 is a plan view illustrating an array substrate of an LCD device according to a second embodiment of the present invention; and

FIG. 10 is a plan view illustrating an array substrate of an LCD device according to a third embodiment of the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

Reference will now be made in detail to illustrated embodiments of the present invention, which are illustrated in the accompanying drawings.

FIG. 3 is a plan view illustrating an array substrate of an LCD device according to a first embodiment of the present invention.

Referring to FIG. 3, the array substrate includes a display region AA to display images and a non-display region NAA.

In the display region AA, the array substrate includes first to m^{th} gate lines GL1 to GLm each extended in a first direction and first to n^{th} data lines DL1 to DLn each extended in a second direction and crossing the first to m^{th} gate lines GL1 to GLm to define a plurality of pixel regions P in a matrix form.

A thin film transistor T is located in each pixel region P and connected to the corresponding gate and data lines. A pixel electrode 180 is located in each pixel region P and connected to the thin film transistor T. The pixel electrode 180 may be formed of a transparent conductive material including indium-tin-oxide (ITO), indium-zinc-oxide (IZO) and indium-tin-zinc-oxide (ITZO). When the LCD device is an in-plane switching mode LCD device, a pixel electrode and a common electrode to induce an in-plane electric field may be located in common in the array substrate, and first to m^{th} common lines may be formed in parallel to the first to m^{th} gate lines, respectively.

In the non-display region NAA, first to m^{th} gate link lines GLL1 to GLLm, first to m^{th} gate pads GP1 to GPm, first to n^{th} data link lines DLL1 to DLLn, and first to n^{th} data pads DP1 to DPn are formed. The gate link lines are connected to the corresponding gate lines at one ends of the gate link lines and connected to the corresponding gate pads at the other ends of the gate link lines. The data link lines are connected to the corresponding data lines at one ends of the data link lines and connected to the corresponding data pads at the other ends of the data link lines. The gate pad may include a gate pad electrode and a gate pad terminal electrode on and connected to the gate pad electrode, and the data pad may include a data pad electrode and a data pad terminal electrode on and connected to the data pad electrode.

The first to n^{th} data lines DL1 to DLn, the first to n^{th} data pads DP1 to DPn, and the first to n^{th} data link lines DLL1 to DLLn may be numbered in the first direction, for example, left to right, and the first to n^{th} data pads DP1 to DPn may be numbered in the numbering direction of the data lines. The data link lines may be connected to the same-numbered data pads. The odd data link line may be paired with and cross the next-numbered even data link line, and the odd data link line may be connected to the next-numbered even data line and the next-numbered even data link line may be connected to the odd data line numbered in same as the odd data link line. For example, the first data link line DLL1 connected to the first data pad DP1 crosses the second data link line DLL2 connected to the second data pad DP2, the first data link line DLL1 is connected to the second data line DL2, and the second data link line DLL2 is connected to the first data line DL1.

FIG. 4 is a plan view enlarging a portion B of FIG. 3, and FIGS. 5A and 5B are cross-sectional views taken along lines Va-Va and Vb-Vb, respectively.

Referring to FIG. 4, in a display region AA, gate lines extended in a first direction include odd and even gate lines 120a and 120b alternately arranged in a second direction on a substrate 100, and data lines extended in the second direction include odd and even data lines 130a and 130b alternately arranged in the first direction.

A thin film transistor T includes a gate electrode 125, a semiconductor layer 140 on the gate electrode 125, and source and drain electrodes 132 and 134 on the semiconductor layer 140. The semiconductor layer 140 includes an active layer made of intrinsic amorphous silicon and an ohmic contact layer made of extrinsic amorphous silicon. A pixel electrode 180 in a pixel region P is connected to the drain electrode 134. The pixel electrode 180 may be formed of a

transparent conductive material including indium-tin-oxide (ITO), indium-zinc-oxide (IZO) and indium-tin-zinc-oxide (ITZO). The pixel electrode **180** may overlap the gate line **120a** and **120b** with a gate insulating layer therebetween to form a storage capacitor Cst. A portion of the pixel electrode **180** overlapping the gate line **120a** and **120b** may be a first storage electrode, and a portion of the gate line **120a** or **120b** may be a second storage electrode.

A non-display region NAA includes a data link region DLA, and a data pad region DPA. In the data link region DLA, data link lines include odd and even data link lines **150a** and **150b** alternately arranged. In the data pad region DPA, data pads include odd and even data pads alternately arranged. The odd data pad include an odd data pad electrode **160a** and an odd data pad terminal electrode **170a** connected to the odd data pad electrode **160a** through an odd data pad contact hole DPH3. The even data pad include an even data pad electrode **160b** and an even data pad terminal electrode **170b** connected to an even data pad contact hole DPH4.

The data pad electrodes **160a** and **160b** are connected to one ends of the data link lines **150a** and **150b**. The odd data link line **150a** and the odd data pad electrode **160a** may be formed at the same process and be in a single body, and the even data link line **150b** and the even data pad electrode **160b** may be formed at the same process and be in a single body. The odd data link line **150a** and the odd data pad electrode **160a** may be formed at the process and at the layer different from the even data link line **150b** and the even data pad electrode **160b**.

The other ends of the data link lines **150a** and **150b** are connected to the data lines **130a** and **130b** through bridge patterns. The bridge patterns include odd and even bridge patterns **190a** and **190b**. The odd bridge pattern **190a** connects the odd data line **130a** and the even data link line **150b**, and the even bridge pattern **190b** connects the even data line **130b** and the odd data link line **150a**.

The one of the odd and even data link lines **150a** and **150b** may be formed at the same process as the data lines **130a** and **130b**, and the other of the odd and even data link lines **150a** and **150b** may be formed at the same process as the gate lines **120a** and **120b**. For example, the odd data link lines **150a** are formed at the data lines **130a** and **130b**, and the even data link lines **150b** are formed at the gate lines **120a** and **120b**. Accordingly, the odd data link line **150a** can be formed at the different layer from and cross the even data link line **150b**.

Referring to FIGS. 4, 5A and 5B, the gate line **120a** and **120b**, the even data link line **150b** and the even data pad electrode **160b** are formed on the substrate **100**. A gate insulating layer **145** is formed on the gate line **120a** and **120b**, the even data link line **150b** and the even data pad electrode **160b**. The gate insulating layer **145** may be formed of an inorganic insulating material including silicon oxide (SiO₂) and silicon nitride (SiNx). The data line **130a** and **130b**, the odd data link line **150a** and the odd data pad electrode **160a** are formed on the gate insulating layer **145**.

A passivation layer **155** is formed on the data line **130a** and **130b**, the odd data link line **150a** and the odd data pad electrode **160a**. The passivation layer **155** may be formed of an organic insulating material including benzocyclobutene (BCB) and photo acrylic, or an inorganic insulating material including (SiO₂) and silicon nitride (SiNx). The pixel electrode **180**, the bridge pattern **190a** and **190b** and the data pad terminal electrode **170a** and **170b** are formed on the passivation layer **155**.

One end of the odd bridge pattern **190a** is connected to the odd data line **130a** through a first contact hole BH1, and the other end of the odd bridge **190** is connected to the even data

link line **150b** through a second contact hole BH2. One end of the even bridge pattern **190b** is connected to the even data line **130b** through a third contact hole BH3, and the other end of the even bridge pattern **190b** is connected to the odd data link line **150a** through a fourth contact hole BH4. The first contact hole BH1, the second contact hole BH2 and the fourth contact hole BH4 are formed in the passivation layer **155**. The second contact hole BH2 is formed in the passivation layer **155** and the gate insulating layer **145**.

The odd data pad terminal electrode **170a** is connected to the odd data pad electrode **160a** through the first data pad contact hole DPH3, and the even data pad terminal electrode **170b** is connected to the even data pad electrode **160b** through the second data pad contact hole DPH4. The first data pad contact hole DPH3 is formed in the passivation layer **155**, and the second data pad contact hole DPH4 is formed in the passivation layer **155** and the gate insulating layer **145**.

Since the odd data link line **150a** and the even data link line **150b** are formed with the gate insulating layer **145** therebetween, short-circuit between the even and odd data link lines **150a** and **150b** can be prevented. Accordingly, the distance between the even and odd data link lines **150a** and **150b** does not need to be considered and can be minimized, and the data link region DLA and the non-display region NAA can thus be minimized. Further, when the odd and even data link lines **150a** and **150b** cross each other, the data link region DLA and the non-display region NAA can be further minimized.

The odd data link line **150a** and the odd data pad electrode **160a** are formed at the same layer and the same material as the data line **130a** and **130b** while the even data link line **150b** and the even data pad electrode **160b** are formed at the different layer from the data line **130a** and **130b**, and there may be a difference between a resistance of the odd data link line **150a**, the odd data pad electrode **160a** and the even data line **130b** and a resistance of the even data link line **150b**, the even data pad electrode **160b** and the odd data line **130a**. To minimize the resistance difference, the even bridge pattern **190b** connecting the even data line **130b** and the odd data link line and data pad electrode **150a** and **160a** is used. Since the resistance difference between the lines transmitting data signals is minimized using the bridge patterns **190a** and **190b**, display quality can be improved.

To further reduce the distance between the odd and even data link lines **150a** and **150b**, there might be suggested a method that the odd and even data link lines **150a** and **150b** are formed in the same line in plane to maximize the overlapping area of the odd and even data link lines **150a** and **150b**. However, this method would increase a parasitic capacitance of the odd and even data link lines **150a** and **150b**. Accordingly, to minimize the parasitic capacitance of the odd and even data link lines **150a** and **150b**, the overlapping area of the odd and even data link lines **150a** and **150b** may be minimized.

FIGS. 6A to 6D are cross-sectional views, taken along the line Va-Va of FIG. 4, illustrating processes of manufacturing the array substrate of the LCD device the according to the first embodiment of the present invention, FIGS. 7A to 7D are cross-sectional views, taken along the line Vb-Vb of FIG. 4, illustrating processes of manufacturing the array substrate of the LCD device the according to the first embodiment of the present invention, and FIGS. 8A to 8D are cross-sectional views, taken along a line VIII-VIII of FIG. 4, illustrating processes of manufacturing the array substrate of the LCD device the according to the first embodiment of the present invention.

Referring to FIGS. 6A, 7A and 8A, a first metal layer is formed on a substrate **100** and patterned to form a gate line

120a (and **120b** of FIG. 4), a gate electrode **125** in a switching region S of a display region AA, an even data link line **150b** in a data link region (DLA) of a non-display region (NAA) and an even data pad electrode **160b** in a data pad region (DPA). The first metal layer may be formed of at least one of copper (Cu), molybdenum (Mo), molybdenum alloy (MoTi), aluminum alloy (AlNd) and chromium (Cr). A gate insulating layer **145** is formed on the substrate **100** having the gate electrode **125**.

Referring to FIGS. 6B, 7B and 8B, an intrinsic amorphous silicon layer and an extrinsic amorphous silicon layer are sequentially formed on the gate insulating layer **145** and patterned to form a semiconductor layer **140**. The semiconductor layer **140** includes an active layer **141** of intrinsic amorphous silicon and an ohmic contact layer **142** of extrinsic amorphous silicon.

A second metal layer is formed on the substrate **100** having the semiconductor layer **140** and patterned to form source and drain electrodes **132** and **134**, a data line **130a** and **130b**, an odd data link line **150a** and an odd data pad electrode **160a**. The second metal layer may be formed of at least one of copper (Cu), molybdenum (Mo), molybdenum alloy (MoTi), aluminum alloy (AlNd) and chromium (Cr). The ohmic contact layer **142** may be etched using the source and drain electrodes **132** and **134** spaced apart from each other, and a center portion of the ohmic contact layer **142** may be removed. Further, a portion of the active layer **141** below the removed portion of the ohmic contact layer **142** may be partially etched, and the exposed portion of the active layer **141** through the removed portion of the ohmic contact layer **142** functions as a channel CH. The gate electrode **125**, the semiconductor layer **140** and the source and drain electrodes **132** and **134** form a thin film transistor T. The odd link line **150a** crosses the even link line **150b** with the gate insulating layer therebetween, and short-circuit can be prevented.

A passivation layer **155** is formed on the substrate **100** having the source and drain electrodes **132** and **134**. The passivation layer **155** is etched, for example, dry-etched, to form a drain contact hole CH2 exposing the drain electrode **134**, a first contact hole BH1 exposing an end of the odd data line **130a**, a third contact hole BH3 exposing an end of the even data line **130b**, a fourth contact hole BH4 exposing an end of the odd data link line **150a**, and a first data pad contact hole DPH3 exposing the odd data pad electrode **160a**. Further, the passivation layer **155** and the gate insulating layer **145** are etched, for example, dry-etched, to form a second contact hole BH2 exposing an end of the even data link line **150b**, and a second data pad contact hole DPH4 exposing the even data pad electrode **160b**.

Referring to FIGS. 6D, 7D and 8D, a transparent conductive material is deposited on the passivation layer **155** and patterned to form a pixel electrode **180**, odd and even data pad terminal electrodes **170a** and **170b**, and odd and even bridge patterns **190a** and **190b**. The pixel electrode **180** is connected to the drain electrode **134** through the drain contact hole CH2. The odd data pad terminal electrode **170a** is connected to the odd data pad electrode **160a** through the first data pad contact hole DPH3, and the even data pad terminal electrode **170b** is connected to the even data pad electrode **160b** through the second data pad contact hole DPH4. The odd bridge pattern **190a** is connected to the odd data line **130a** through the first contact hole BH1 and the even data link line **150b** through the second contact hole BH2, and the even bridge pattern **190b** is connected to the even data line **130b** through the third contact hole BH3 and the odd data link line **150a** through the fourth contact hole BH4.

The pixel electrode **180** may extend over the gate line **120a** (and **120b** of FIG. 4) with the gate insulating layer **145** therebetween to form a storage capacitor Cst.

Through the above-described processes, the array substrate according to the first embodiment is manufactured. Further, an opposing substrate is attached to the array substrate so that the LCD device is manufactured.

In manufacturing the array substrate according to the first embodiment, the first to fourth contact holes are formed at the same process of forming the drain contact hole and the gate pad contact holes, and the bridge patterns are formed at the same process of forming the pixel electrode and the data pad terminal electrodes. Accordingly, the first to fourth contact holes and the bridge patterns can be formed without additional process.

In the method of manufacturing the array substrate according to the first embodiment, it is explained that the array substrate is manufactured with five mask processes. Alternatively, the array substrate can be manufactured with four or less mask processes.

FIG. 9 is a plan view illustrating an array substrate of an LCD device according to a second embodiment of the present invention. The array substrate according to the second embodiment is similar to the array substrate according to the first embodiment. Accordingly, explanations of parts similar to parts of the first embodiment may be omitted.

Odd and even data link lines **250a** and **250b** of FIG. 9 change positions compared to the odd and even data link lines **150a** and **150b** of FIG. 4. In other words, the odd data link line **250a** is formed at the same layer as a gate line **220a** and **220b**, and the even data link line **250b** is formed at the same layer as a data line **230a** and **230b**. Further, an odd data pad electrode **260a** is formed at the same layer as the gate line **220a** and **220b**, and an even data pad electrode **260b** is formed at the same layer as the data line **230a** and **230b**.

Further, a second contact hole BH2 and a second data pad contact hole DPH4 are formed in a passivation layer since the even data link line **250b** and the even data pad electrode **260b** are formed at the same layer as the data line **230a** and **230b**. A fourth contact hole BH4 and a first data pad contact hole DPH3 are formed in the passivation layer and a gate insulating layer since the odd data link line **250a** and the odd data pad electrode **260a** are formed at the same layer as the gate line **220a** and **220b**.

In the second embodiment, even though the odd and even data link lines change positions in layer compared to those of the first embodiment, the odd and even data link lines cross each other with the gate insulating layer therebetween.

A method of manufacturing the array substrate according to the second embodiment is similar to the method of manufacturing the array substrate according to the first embodiment and has a little variation as described above, for example, in forming the odd and even data link lines, the odd and even data pad electrodes, the first to fourth contact holes and the gate pad contact holes. Accordingly, explanations of the method of manufacturing the array substrate according to the second embodiment are omitted.

FIG. 10 is a plan view illustrating an array substrate of an LCD device according to a third embodiment of the present invention. The array substrate according to the third embodiment is similar to the array substrates according to the first and second embodiments. Accordingly, explanations of parts similar to parts of the first and second embodiments may be omitted.

Odd and even data link lines **350a** and **350b** of FIG. 10 are formed at different layers and do not cross each other. For example, the odd data link line **350a** is formed at the same

layer as a gate line **320a** and **320b**, and the even data link line **350b** is formed at the same layer as a data line **330a** and **330b**. The odd data link line **350a** is close to the even data link line **350b** to the extent that the odd and even data link lines **350a** and **350b** do not overlap and a parasitic capacitance of the odd and even data link lines **350a** and **350b** is minimized. Accordingly, the odd data link line **350a** is connected to the odd data line **330a** through an odd bridge pattern **390a**, and the even data link line **350b** is connected to the even data line **330b** through an even bridge pattern **390b**.

Further, the odd data pad electrode **360a** is formed at the same layer as the gate line **320a** and **320b**, and the even data pad electrode **360b** is formed at the same layer as the data line **330a** and **330b**. The odd data pad electrode **360a** is close to the even data pad electrode **360b** as the odd data link line **350a** is close to the even data link line **350b**.

First, third and fourth contact holes **BH1**, **BH3** and **BH4** and a second data pad contact hole **DPH4** are formed in a passivation layer, and a second contact hole **BH2** and a first data pad contact hole **DPH3** are formed in the passivation layer and a gate insulating layer.

A method of manufacturing the array substrate according to the third embodiment is similar to the method of manufacturing the array substrates according to the first and second embodiments and has a little variation as described above, for example, in forming the odd and even data link lines, the odd and even data pad electrodes, the first to fourth contact holes and the gate pad contact holes. Accordingly, explanations of the method of manufacturing the array substrate according to the third embodiment are omitted.

In the array substrate according to the third embodiment, it is explained that the odd data link line **350a** and the odd data pad electrode **360a** are formed at the same layer as the gate line **320a** and **320b**, and the even data link line **350b** and the even data pad electrode **360b** are formed at the same layer as the data line **330a** and **330b**. Alternatively, the odd data link line **350a** and the odd data pad electrode **360a** may be formed at the same layer as the data line **330a** and **330b**, and the even data link line **350b** and the even data pad electrode **360b** are formed at the same layer as the gate line **320a** and **320b**.

As described in the embodiments of the present invention, since the odd and even data link lines are formed at different layers with the gate insulating layer therebetween, short-circuit between the even and odd data link lines can be prevented, and the data link region and the non-display region can be minimized. Further, since the bridge patterns are used, the resistance difference between the metal lines transmitting data signals can be minimized, and display quality can thus be improved.

In the embodiments of the present invention, the data link lines and the data pad electrodes formed at different layers are explained. In similar manners to the first to third embodiments, the gate link lines and the gate pad electrodes can be formed. For example, the odd and even gate link lines are formed at the different layers with the gate insulating layer. Further, the odd and even gate link lines cross each other.

Further, the odd and even gate pad electrodes are formed at the different layers with the gate insulating layer. Further, bridge patterns and contact holes and gate pad contact holes are formed according to the lamination structure of the gate link lines and the gate pad electrodes.

It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A liquid crystal display device, comprising:

a gate line on a substrate including a display region and a non-display region;

odd and even data lines crossing the gate line to define a pixel region in the display region;

a thin film transistor connected to the gate line and one of the odd and even data lines;

a pixel electrode in the pixel region and connected to the thin film transistor;

first and second data link lines electrically connected to the odd and even data lines and not electrically connected to the even and odd data lines, respectively, the first data link line and the second data link line crossing each other and overlapping each other at the crossing portion thereof in a plane view, and a gate insulating layer below one of the first and second data link lines and on the other one of the first and second data link lines; and

even and odd data pad electrodes at one ends of the first and second data link lines, respectively;

first and second bridge patterns connecting the first and second data link lines and the odd and even data lines, respectively,

wherein one of the first and second data link lines is at the same layer as the gate line, and the other of the first and second data link lines is at the same layer as the odd and even data lines, and wherein the gate insulating layer is on the gate line;

a passivation layer on the odd and even data lines and the other of the first and second data link lines,

wherein the first and second bridge patterns and the pixel electrode are on the passivation layer,

wherein the passivation layer includes a first contact hole to contact the odd data line and the first bridge pattern, a second contact hole to contact the first data link line and the first bridge pattern, a third contact hole to contact the even data line and the second bridge pattern, and a fourth contact hole to contact the second data link line and the second bridge pattern, and wherein the gate insulating layer includes one of the third and fourth contact holes corresponding to the one of the first and second data link lines.

* * * * *

一种液晶显示装置,包括在包括显示区域和非显示区域的基板上的栅极线;奇数和偶数数据线与栅极线交叉以限定显示区域中的像素区域;薄膜晶体管连接到栅极线和奇数和偶数数据线之一;像素区域中的像素电极并连接到薄膜晶体管;第一和第二数据连接线分别电连接到奇数和偶数数据线,并且在它们之间形成栅极绝缘层;第一和第二数据焊盘电极分别位于第一和第二数据连接线的一端。

