



US008228452B2

(12) **United States Patent**  
**Lee et al.**

(10) **Patent No.:** **US 8,228,452 B2**  
(45) **Date of Patent:** **Jul. 24, 2012**

(54) **LIQUID CRYSTAL DISPLAY AND THIN FILM TRANSISTOR ARRAY PANEL THEREFOR**

(75) Inventors: **Jung-Hee Lee**, Suwon (KR);  
**Yoon-Sung Um**, Yongin (KR); **Jong-Ho Son**, Seoul (KR); **Jae-Jin Lyu**, Kyungki-do (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.** (KR)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/630,249**

(22) Filed: **Dec. 3, 2009**

(65) **Prior Publication Data**  
US 2010/0149447 A1 Jun. 17, 2010

**Related U.S. Application Data**

(63) Continuation of application No. 11/288,246, filed on Nov. 29, 2005, now Pat. No. 7,652,725, which is a continuation of application No. 10/445,849, filed on May 28, 2003, now Pat. No. 6,999,134.

(30) **Foreign Application Priority Data**

Nov. 14, 2002 (KR) ..... 10-2002-0070706

(51) **Int. Cl.**  
**G02F 1/1343** (2006.01)

(52) **U.S. Cl.** ..... **349/39; 349/48**

(58) **Field of Classification Search** ..... None  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,132,819 A \* 7/1992 Noriyama et al. .... 349/55  
5,343,216 A \* 8/1994 Katayama et al. .... 345/92  
5,818,407 A \* 10/1998 Hori et al. .... 345/92  
6,191,831 B1 2/2001 Kim et al.

6,249,325 B1 \* 6/2001 Ohkawara et al. .... 349/38  
6,724,444 B2 4/2004 Ashizawa et al.  
6,819,385 B2 \* 11/2004 Lu ..... 349/144  
6,999,134 B2 2/2006 Lee et al.  
7,084,942 B2 8/2006 Luo  
7,652,725 B2 1/2010 Lee et al.  
2001/0030719 A1 10/2001 Yamaguchi et al.  
2002/0060764 A1 \* 5/2002 Taniguchi et al. .... 349/130  
2003/0025661 A1 2/2003 Karman et al.  
2003/0095223 A1 \* 5/2003 Song ..... 349/141  
2005/0174528 A1 \* 8/2005 Kubo et al. .... 349/193

(Continued)

**FOREIGN PATENT DOCUMENTS**

CN 1366653 8/2002

(Continued)


*Primary Examiner* — Thanh-Nhan P. Nguyen

(74) *Attorney, Agent, or Firm* — Cantor Colburn LLP

(57) **ABSTRACT**

A thin film transistor array panel is provided, which includes: an insulating substrate; a gate line formed on the substrate and including a gate electrode; a gate insulating layer formed on the gate line; a semiconductor layer formed on the gate insulating layer opposite the gate electrode; a data line formed on the gate insulating layer and including a first source electrode located on the semiconductor layer; first and second drain electrodes formed on the semiconductor layer, separated from each other and overlapping the gate electrode; a passivation layer formed on the data line and the first and second drain electrodes; and first and second pixel electrodes electrically connected to the first and second electrodes, respectively, wherein an overlapping area between the gate electrode and the first drain electrode is different from an overlapping area between the gate electrode and the second drain electrode.

**2 Claims, 4 Drawing Sheets**



# US 8,228,452 B2

Page 2

---

## U.S. PATENT DOCUMENTS

2006/0007082 A1 1/2006 Chiu

## FOREIGN PATENT DOCUMENTS

JP 03-242625 10/1991  
JP 04-075030 3/1992  
JP 07072509 3/1995

JP 08-146464 6/1996  
JP 09-043610 2/1997  
JP 09-179141 7/1997  
JP 10-268349 10/1998  
JP 2002287712 10/2002  
KR 199611524 4/1996  
TW 489230 6/2002

\* cited by examiner



FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7



# LIQUID CRYSTAL DISPLAY AND THIN FILM TRANSISTOR ARRAY PANEL THEREFOR

## CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation application of U.S. patent application Ser. No. 11/288,246, filed on Nov. 29, 2005, which is a continuation application of U.S. patent application Ser. No. 10/445,849, filed on May 28, 2003 which issued as U.S. Pat. No. 6,999,134, which claims the benefit of Korean patent application no. 2002-0070706, filed on Nov. 14, 2002, which is hereby incorporated by reference for all purposes as if fully set forth herein.

## BACKGROUND OF THE INVENTION

### (A) Field of the Invention

The present invention relates to a liquid crystal display and a thin film transistor array panel therefor.

### (B) Description of the Related Art

A typical liquid crystal display ("LCD") includes an upper panel provided with a common electrode and an array of color filters, a lower panel provided with a plurality of thin film transistors ("TFTs") and a plurality of pixel electrodes, and a liquid crystal layer interposed therebetween. The pixel electrodes and the common electrode are supplied with electric voltages and the voltage difference therebetween causes electric field. The variation of the electric field changes the orientations of liquid crystal molecules in the liquid crystal layer, and thus it changes the transmittance of light passing through the liquid crystal layer. As a result, the LCD displays desired images by adjusting the voltage difference between the pixel electrodes and the common electrode.

Since the LCD has disadvantages of narrow viewing angle and poor lateral visibility, several techniques for improving these disadvantages have been developed. Among these techniques, the provision of cutouts or projections on the pixel electrodes and the common electrode opposite each other along with the vertical alignment of the liquid crystal molecules with respect to the panels is promising.

The cutouts provided at the pixel electrodes and the common electrode induce fringe field, which disperses the tilt directions of the liquid crystal molecules to give wide viewing angle. The provision of the projections on the pixel electrode and the common electrode distorts the electric field to adjust the tilt directions of the liquid crystal molecules. The liquid crystal layer of the LCD provided with the cutouts or the protrusions is divided into a plurality of domains based on the tilt directions of the liquid crystal molecules.

However, the lateral visibility of these conventional LCDs is still poor since the tilt angles of the liquid crystal molecules even in the different domains are the same for the same voltages applied to the pixel electrodes.

## SUMMARY OF THE INVENTION

A thin film transistor array panel is provided, which includes: first and second signal lines transmitting first and second signals, respectively; first and second switching elements connected to the first and the second signal lines, each of the first and the second switching elements having a first terminal connected to the first signal line, a second terminal connected to the second signal and a third terminal and transmitting the second signal in response to the first signal; and first and second liquid crystal capacitors connected to the third terminals of the first and the second switching elements,

respectively, wherein a capacitance between the first and the third terminals of the first switching element is different from a capacitance between the first and the third terminals of the second switching element.

The liquid crystal display preferably includes first and second storage capacitors connected to the third terminals of the first and the second switching elements in parallel to the first and the second liquid crystal capacitors, respectively.

A thin film transistor array panel is provided, which includes: an insulating substrate; a first signal line provided on the substrate; a second signal line provided on the substrate; first and second thin film transistors connected to the first signal line and the second signal line, each of the first and the second thin film transistors having a first terminal connected to the first signal line, a second terminal connected to the second signal and a third terminal; and first and second pixel electrodes connected to the third terminals of the first and the second thin film transistors, respectively, wherein a capacitance between the first and the third terminals of the first thin film transistor is different from a capacitance between the first and the third terminals of the second thin film transistor.

Another liquid crystal display is provided, which includes: a first panel including a first insulating substrate, a first signal line provided on the first substrate, a second signal line provided on the first substrate, first and second thin film transistors connected to the first signal line and the second signal line, and first and second pixel electrodes connected to the first and the second thin film transistors, respectively; a second panel facing the first panel and including a second insulating substrate and a common electrode provided on the second substrate; and a liquid crystal layer interposed between the first panel and the second panel, wherein each of the first and the second thin film transistors has a first terminal connected to the first signal line, a second terminal connected to the second signal and a third terminal connected to a corresponding one of the first and the second pixel electrodes, and a capacitance between the first and the third terminals of the first thin film transistor is different from a capacitance between the first and the third terminals of the second thin film transistor.

Another thin film transistor array panel is provided, which includes: an insulating substrate; a gate line formed on the substrate and including a gate electrode; a gate insulating layer formed on the gate line; a semiconductor layer formed on the gate insulating layer opposite the gate electrode; a data line formed on the gate insulating layer and including a first source electrode located on the semiconductor layer; first and second drain electrodes formed on the semiconductor layer, separated from each other and overlapping the gate electrode; a passivation layer formed on the data line and the first and the second drain electrodes; and first and second pixel electrodes electrically connected to the first and the second drain electrodes, respectively, wherein an overlapping area between the gate electrode and the first drain electrode is different from an overlapping area between the gate electrode and the second drain electrode.

The source electrode may be connected to the first and the second drain electrodes via the semiconductor layer.

Alternatively, the first source electrode is connected to the first drain electrode via the semiconductor layer, and the data line further comprises a second source electrode located on the semiconductor layer and connected to the second drain electrode via the semiconductor layer.

The thin film transistor array panel preferably further includes an ohmic contact layer disposed between the semiconductor layer and the source electrode and the first and the

second drain electrodes and/or a storage electrode overlapping at least one of the first and the second pixel electrodes.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The above and other advantages of the present invention will become more apparent by describing preferred embodiments thereof in detail with reference to the accompanying drawings in which:

FIG. 1 is a layout view of a TFT array panel for an LCD according to an embodiment of the present invention;

FIG. 2 is a sectional view of the TFT array panel shown in FIG. 1 taken along the line II-II';

FIG. 3 is an equivalent circuit diagram of an LCD including the TFT array panel shown in FIGS. 1 and 2;

FIG. 4 illustrates a pixel voltage of an LCD as function of time;

FIG. 5 shows voltage-transmittance curves for subpixel regions of a normally black mode LCD;

FIG. 6 is a layout view of a TFT array panel for an LCD according to another embodiment of the present invention; and

FIG. 7 is a sectional view of the TFT array panel shown in FIG. 1 taken along the line VII-VII'.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the inventions invention are shown. The present invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein.

In the drawings, the thickness of layers and regions are exaggerated for clarity. Like numerals refer to like elements throughout. It will be understood that when an element such as a layer, region or substrate is referred to as being "on" another element, it can be directly on the other element or intervening elements may also be present. In contrast, when an element is referred to as being "directly on" another element, there are no intervening elements present.

Now, LCDs according to embodiments of this invention will be described in detail with reference to the accompanying drawings.

FIG. 1 is a layout view of a TFT array panel for an LCD according to an embodiment of the present invention, FIG. 2 is a sectional view of the TFT array panel shown in FIG. 1 taken along the line II-II', and FIG. 3 is an equivalent circuit diagram of an LCD including the TFT array panel shown in FIGS. 1 and 2.

A plurality of gate lines **121** and a plurality of storage electrode lines **131** are formed on an insulating substrate **110** preferably made of transparent glass. The gate lines **121** extend substantially in a row direction and substantially parallel to each other and each gate line **121** includes a plurality of expansions forming gate electrodes **123**. The storage electrode lines **131** extend substantially parallel to the gate lines **121** and are supplied with a common voltage  $V_{com}$  to be applied to a common electrode (not shown) of another panel (not shown) of an LCD. Each storage electrode **131** may include a plurality of branches (not shown).

The gate lines **121** and the storage electrode lines **131** are preferably made of Al, Cr or their alloys, Mo or Mo alloy. The gate lines **121** and the storage electrode lines **131** preferably include a layer preferably made of Cr or Mo alloys having excellent physical and chemical characteristics and another

layer preferably made of Al or Ag alloys having low resistivity. In addition, the lateral sides of the gate lines **121** are tapered, and the inclination angle of the lateral sides with respect to a horizontal surface ranges 30-80 degrees.

A gate insulating layer **140** is formed on the gate lines **121** and the storage electrode lines **131**.

A plurality of semiconductor islands **150** preferably made of hydrogenated amorphous silicon ("a-Si") are formed on the gate insulating layer **140** and located opposite the gate electrodes **123** with respect to the gate insulating layer **130**. Each semiconductor island **150** forms a channel of TFT.

A plurality of sets of ohmic contacts **163**, **165a** and **165b** preferably made of silicide or hydrogenated a-Si heavily doped with n type impurity such as phosphorous are formed on the semiconductor islands **150**. The lateral sides of the semiconductor islands **150** and the ohmic contacts **163**, **165a** and **165b** are tapered, and the inclination angles thereof are in the range between 30-80 degrees.

A plurality of sets of a data line **171** and a plurality of pairs of first and second drain electrodes **175a** and **175b** are formed on the ohmic contacts **163**, **165a** and **165b**, and the gate insulating layer **140**. The data lines **171** extend substantially in the column direction intersect the gate lines **121** and the storage electrode lines **131**. Each data line **171** includes a plurality of source electrodes **173** extending onto the semiconductor islands **150**. Each pair of the drain electrodes **175a** and **175b** are separated from an associated source electrode **173**, located opposite each other with respect to the source electrode **173**, and extends in opposite directions from an associated semiconductor island **150** on an associated gate electrode **123**.

The data lines **171** and the drain electrodes **175a** and **175b** are preferably made of Al, Cr or their alloys, Mo or Mo alloy. The data lines **171** and the drain electrodes **175a** and **175b** preferably include a layer preferably made of Cr or Mo alloys having excellent physical and chemical characteristics and another layer preferably made of Al or Ag alloys having low resistivity. The data lines **171** and the drain electrodes **175a** and **175b** have tapered lateral sides, and the inclination angles of the lateral sides ranges 30-80 degrees.

The ohmic contacts **163**, **165a** and **165b** are interposed only between the semiconductor islands **150** and the data lines **171** and the drain electrodes **175a** and **175b** to reduce the contact resistance therebetween. Some portions of the semiconductor islands **150** are exposed out of the data lines **171** and the drain electrodes **175a** and **175b**.

The gate electrode **123**, the source electrode **173** and the first drain electrode **175a** along with a portion of the semiconductor island **150** located between the source electrode **173** and the first drain electrode **175a** form a TFT, while the gate electrode **123**, the source electrode **173** and the second drain electrode **175b** along with a portion of the semiconductor island **150** located between the source electrode **173** and the second drain electrode **175b** form another TFT.

Each of the first and the second drain electrodes **175a** and **175b** overlap the gate electrode **123** to form a parasitic capacitor  $C_{gda}$  or  $C_{gdb}$ . The capacitance of the parasitic capacitor  $C_{gda}$  or  $C_{gdb}$  is proportional to the overlapping area. According to an embodiment of the present invention, the overlapping area between the first drain electrode **175a** and the gate electrode **123** is different from the overlapping area between the second drain electrode **175b** and the gate electrode **123** such that the capacitance between the first drain electrode **175a** and the gate electrode **123** is different from the capacitance between the second drain electrode **175b** and the gate electrode **123**.

A passivation layer **180** preferably made of silicon nitride or organic insulator is formed on the data lines **171** and the drain electrodes **175a** and **175b**, and the exposed portions of the semiconductor islands **150**. The passivation layer **180** is provided with a plurality of first and second contact holes **181** and **182** exposing the first and the second drain electrodes **175a** and **175b**, respectively.

A plurality of pairs of first and second pixel electrodes **190a** and **190b** are formed on the passivation layer **180**. The first and the second pixel electrodes **190a** and **190b** are connected to the first and the second drain electrodes **175a** and **175b** through the first and the second contact holes, respectively. That is, a pair of the first and the second pixel electrodes **190a** and **190b** are connected to respective TFTs connected to the same gate line **121** and the same data line **171**. The first and the second pixel electrodes **190a** and **190b** overlap the storage electrode lines **131** to form storage capacitors  $C_{sta}$  and  $C_{stb}$ , respectively. The pixel electrodes **190a** and **190b** are preferably made of transparent conductive material such as indium zinc oxide ("EO") and indium tin oxide ("ITO"), or reflective conductive material.

An LCD according to an embodiment of the present invention further includes a common electrode panel (not shown) facing the TFT array panel as well as the TFT array panel and a liquid crystal layer interposed therebetween. The common electrode panel includes a common electrode (not shown) forming a plurality of liquid crystal capacitors  $CLCa$  and  $CLCb$  along with the first and the second pixel electrodes **190a** and **190b** of the TFT array panel. As described above, the common electrode is supplied with the common voltage  $V_{com}$ . A polarizer or polarizers (not shown) are attached on outer surfaces of the panels, and a retardation film or films (not shown) may be attached to the outer surface of the common electrode panel.

In circuitual view, an LCD according to this embodiment of the present invention includes a plurality of pixels including two subpixels. Each subpixel includes a TFT including a parasitic capacitor  $C_{gda}$  or  $C_{gdb}$ , and a liquid crystal capacitor  $CLCa$  or  $CLCb$  and a storage capacitor  $C_{sta}$  or  $C_{stb}$  connected to the TFT in parallel as shown in FIG. 3.

When a gate-on voltage  $V_g$  is applied to a gate line **121** and a data voltage  $V_d$  is applied to a data line **171**, the TFTs connected to the gate line **121** are turned on and thus the capacitors  $CLCa$  and  $CLCb$  connected thereto are charged with pixel voltages  $V_{pa}$  and  $V_{pb}$ . If the data voltage  $V_d$  is larger than the common voltage  $V_{com}$ , the pixel voltages  $V_{pa}$  and  $V_{pb}$  increase during the application of the data voltage  $V_d$  and are abruptly dropped upon turning off of the TFTs as shown in FIG. 4, which illustrates a pixel voltage  $V_p$  as function of time. On the contrary, the data voltage  $V_d$  is smaller than the common voltage  $V_{com}$ , the pixel voltages  $V_{pa}$  and  $V_{pb}$  decrease during the application of the data voltage  $V_d$ , and are abruptly increased upon turning off of the TFTs. The voltage drop is called a "kick-back voltage," which is resulted from the parasitic capacitor  $C_{gda}$  or  $C_{gdb}$ .

The kick-back voltages  $\Delta V_{pa}$  and  $\Delta V_{pb}$  for two respective subpixels are given by:

$$\begin{aligned} \Delta V_{pa} &= V_g \times \frac{C_{gda}}{C_{Lca} + C_{sta} + C_{gda}} \\ &= V_g \left( 1 - \frac{C_{Lca} + C_{sta}}{C_{Lca} + C_{sta} + C_{gda}} \right) \end{aligned} \quad (1)$$

-continued

$$\begin{aligned} \Delta V_{pb} &= V_g \times \frac{C_{gdb}}{C_{Lcb} + C_{stb} + C_{gdb}} \\ &= V_g \left( 1 - \frac{C_{Lcb} + C_{stb}}{C_{Lcb} + C_{stb} + C_{gdb}} \right) \end{aligned} \quad (2)$$

where the capacitors and their capacitances are indicated by the same reference numerals.

As shown in Equations (1) and (2), the kick-back voltage increases as the parasitic capacitance increases and vice versa.

According to this embodiment, the parasitic capacitance  $C_{gda}$  is different from the parasitic capacitance  $C_{gdb}$  and thus the kick-back voltage  $\Delta V_{pa}$  is different from the kick-back voltage  $\Delta V_{pb}$  since the overlapping area between the first drain electrode **175a** and the gate electrode **123** is different from the overlapping area between the second drain electrode **175b** and the gate electrode **123** as described above.

Referring to FIG. 2, the overlapping areas are adjusted by changing the overlapping width while maintaining the overlapping length to be constant. In this embodiment, the overlapping width  $d_{2a}$  between the first drain electrode **175a** and the gate electrode **123** is different from the overlapping width  $d_{2b}$  between the second drain electrode **175b** and the gate electrode **123**.

Accordingly, the pixel voltage  $V_{pa}$  is different from the pixel voltage  $V_{pb}$ .

It is noted that the kick-back voltages  $\Delta V_{pa}$  and  $\Delta V_{pb}$  are as small as possible since the kick-back voltages may generate afterimage and flicker. A measured value of a kick-back voltage upon application of a data voltage  $V_d$  of 10 V was about 0.5 V to 1.0 V, which was expected to be about 0.8 V to 0.9 V through a simulation.

The difference of the pixel voltages  $V_{pa}$  and  $V_{pb}$  differentiates the strength of electric fields in respective subpixel regions  $P_a$  and  $P_b$ , which are portions of the liquid crystal layer located on the first and the second pixel electrodes **190a** and **190b**, respectively. The different field strength in turn differentiates the tilt angles of liquid crystal molecules in the subpixel regions  $P_a$  and  $P_b$ .

FIG. 5 shows voltage-transmittance (V-T) curves for the subpixel regions  $P_a$  and  $P_b$  of a normally black mode LCD, which are different from each other. The V-T curve for the subpixel region  $P_a$  with a larger parasitic capacitance  $C_{gda}$  underlies that for the subpixel region  $P_b$  with a smaller parasitic capacitance  $C_{gdb}$ .

Accordingly, the characteristics of the subpixel regions  $P_a$  and  $P_b$  effectively compensate each other to widen the viewing angle of the LCD. The LCD may be in a vertically aligned (VA) mode, twisted-nematic (TN) mode or optical-compensated bend (OCB) mode.

Now, an LCD according to another embodiment of the present invention is described in detail with reference to FIGS. 6-8.

FIG. 6 is a layout view of a TFT array panel for an LCD according to another embodiment of the present invention, and FIG. 7 is a sectional view of the TFT array panel shown in FIG. 1 taken along the line VII-VII'.

Referring to FIGS. 6 and 7, a TFT array panel according to this embodiment includes a plurality of gate lines **121** and a plurality of storage electrode lines **131** formed on an insulating substrate **110**, a gate insulating layer **140** formed on the gate lines **121** and the storage electrode lines **131**, and a plurality of semiconductor islands **150** formed on the gate insulating layer **140**.

A plurality of ohmic contacts **163a**, **163b**, **165a** and **165b** are formed on the semiconductor islands **150**.

A plurality of sets of a data line **171** and a plurality of pairs of first and second drain electrodes **175a** and **175b** are formed on the ohmic contacts **163**, **165a** and **165b**, and the gate insulating layer **140**. Each data line **171** includes a plurality of first and second source electrodes **173a** and **173b** extending onto the semiconductor islands **150**. Each of the first and the second drain electrodes **175a** and **175b** are separated from the first and the second source electrodes **173a** and **173b**. The first source electrode **173a** and the first drain electrode **175a** face each other while the second source electrode **173b** and the second drain electrode **175b** faces each other.

The gate electrode **123**, the first source electrode **173a** and the first drain electrode **175a** along with a portion of the semiconductor island **150** located between the first source electrode **173a** and the first drain electrode **175a** form a TFT, while the gate electrode **123**, the second source electrode **173b** and the second drain electrode **175b** along with a portion of the semiconductor island **150** located between the second source electrode **173b** and the second drain electrode **175b** form another TFT.

According to this embodiment of the present invention, the overlapping areas between the first drain electrode **175a** and the gate electrode **123** and between the second drain electrode **175b** and the gate electrode **123** are different such that the capacitance between the first drain electrode **175a** and the gate electrode **123** is different from the capacitance between the second drain electrode **175b** and the gate electrode **123**.

A passivation layer **180** is formed on the data lines **171** and the drain electrodes **175a** and **175b**, and the semiconductor islands **150**. The passivation layer **180** is provided with a plurality of first and second contact holes **181** and **182** exposing the first and the second drain electrodes **175a** and **175b**, respectively. A plurality of pairs of first and second pixel electrodes **190a** and **190b** are formed on the passivation layer **180**. The first and the second pixel electrodes **190a** and **190b** are connected to the first and the second drain electrodes **175a** and **175b** through the first and the second contact holes, respectively. That is, a pair of the first and the second pixel electrodes **190a** and **190b** are connected to respective TFTs connected to the same gate line **121** and the same data line **171**. The first and the second pixel electrodes **190a** and **190b** overlap the storage electrode lines **131** to form storage capacitors Csta and Cstb, respectively.

According to this embodiment, the parasitic capacitance Cgda is different from the parasitic capacitance Cgdb and thus the kick-back voltage  $\Delta V_{pa}$  is different from the kick-back voltage  $\Delta V_{pb}$  since the overlapping area between the first drain electrode **175a** and the gate electrode **123** is different from the overlapping area between the second drain electrode **175b** and the gate electrode **123** as described above.

Referring to FIG. 7, the overlapping width  $d2a$  between the first drain electrode **175a** and the gate electrode **123** is different from the overlapping width  $d2b$  between the second drain electrode **175b** and the gate electrode **123**.

Accordingly, the pixel voltage  $V_{pa}$  is different from the pixel voltage  $V_{pb}$ , and V-T curves for subpixel regions Pa and Pb on the first and the second pixel electrodes **190a** and **190b** are different from each other. Therefore, the characteristics of the subpixel regions Pa and Pb effectively compensate each other to widen the viewing angle of the LCD.

Although preferred embodiments of the present invention have been described in detail hereinabove, it should be clearly understood that many variations and/or modifications of the

basic inventive concepts herein taught which may appear to those skilled in the present art will still fall within the spirit and scope of the present invention, as defined in the appended claims.

What is claimed is:

1. A liquid crystal display, comprising:

a first panel including:

a first insulating substrate;

a plurality of gate lines provided on the first substrate;

a plurality of first storage electrode lines and a plurality of second storage electrode lines provided on the first substrate

a plurality of data lines provided on the first substrate;

a plurality of first thin film transistors connected to the gate lines and the data lines;

a plurality of second thin film transistor connected to the gate lines and the data lines;

a plurality of first pixel electrodes connected to the first thin film transistors; and

a plurality of second pixel electrodes connected to the second thin film transistors;

a second panel facing the first panel and including a second insulating substrate and a common electrode provided on the second substrate; and

a liquid crystal layer interposed between the first panel and the second panel and comprising a plurality of liquid crystal molecules,

wherein two different voltages originated from a single signal are applied to the first and second pixel electrodes,

wherein a capacitance of a first liquid crystal capacitor is different from a capacitance of a second liquid crystal capacitor, wherein the first liquid crystal capacitor is formed by the first pixel electrode and the common electrode, and the second liquid crystal capacitor is formed by the second pixel electrode and the common electrode,

wherein the first thin film transistor includes a first terminal, a second terminal, and a third terminal connected to the first pixel electrode and the second thin film transistor includes a first terminal, a second terminal, and a third terminal connected to the second pixel electrode,

wherein the third terminal of the first thin film transistor connects to a first storage capacitor and the third terminal of the second thin film transistor connects to a second storage capacitor, wherein the first storage capacitor is formed by the first storage electrode line and the first pixel electrode, and the second storage capacitor is formed by the second storage electrode line and the second pixel electrode,

wherein a capacitance of the first storage capacitor is substantially the same as a capacitance of the second storage capacitor,

wherein a capacitance between the first terminal and the third terminal of the first thin film transistor is different from that between the first terminal and the third terminal of the second thin film transistor, and

wherein the liquid crystal molecules are vertically aligned when an electric field is not applied to the liquid crystal layer.

2. The liquid crystal display of claim 1, wherein the first pixel electrode connects to a first liquid crystal capacitor and the second pixel electrode connects to a second liquid crystal capacitor.

\* \* \* \* \*

专利名称(译)	液晶显示器及其薄膜晶体管阵列面板		
公开(公告)号	<a href="#">US8228452</a>	公开(公告)日	2012-07-24
申请号	US12/630249	申请日	2009-12-03
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
[标]发明人	LEE JUNG HEE UM YOON SUNG SON JONG HO LYU JAE JIN		
发明人	LEE, JUNG-HEE UM, YOON-SUNG SON, JONG-HO LYU, JAE-JIN		
IPC分类号	G02F1/1343 G02F1/1333 G02F1/136 G02F1/1362 G02F1/1368 G09F9/30 G09F9/35 H01L27/12 H01L27/13		
CPC分类号	G02F1/13624 H01L27/1255 G02F1/1368 G02F2001/134345		
代理机构(译)	康托科尔伯恩LLP		
优先权	1020020070706 2002-11-14 KR 10/445849 2006-02-14 US		
其他公开文献	US20100149447A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

提供一种薄膜晶体管阵列面板，包括：绝缘基板；栅极线形成在基板上并包括栅极电极；栅极绝缘层形成在栅极线上；半导体层形成在与栅电极相对的栅极绝缘层上；数据线，形成在栅极绝缘层上，并包括位于半导体层上的第一源电极；第一和第二漏电极形成在半导体层上，彼此分开并与栅电极重叠；形成在数据线和第一和第二漏电极上的钝化层；第一和第二像素电极分别电连接到第一和第二电极，其中栅电极和第一漏电极之间的重叠区域不同于栅电极和第二漏电极之间的重叠区域。

