



US 20070126687A1

(19) **United States**(12) **Patent Application Publication**
Choi(10) **Pub. No.: US 2007/0126687 A1**(43) **Pub. Date: Jun. 7, 2007**(54) **LIQUID CRYSTAL DISPLAY DEVICE AND
DRIVING METHOD THEREOF****Publication Classification**(75) Inventor: **Yeon Ho Choi**, Paju-si (KR)(51) **Int. Cl.****G09G 3/36** (2006.01)(52) **U.S. Cl.** **345/98**

Correspondence Address:

BRINKS HOFER GILSON & LIONE**P.O. BOX 10395****CHICAGO, IL 60610 (US)**(57) **ABSTRACT**

A liquid crystal display device for automatically selecting a common voltage adaptive for a scan line system to supply it to a common electrode of liquid crystal cells is disclosed. In the liquid crystal display device, a controller is selectively controls a supply of a first common voltage or a second common voltage in accordance with a scan line system of an image signal displayed at a liquid crystal display panel. A first common voltage generator supplies the first common voltage in accordance with a control of the controller to the common electrode of the liquid crystal cells. And, a second common voltage generator supplies the second common voltage in accordance with a control of the controller to the common electrode of the liquid crystal cells.

(73) Assignee: **LG PHILIPS LCD CO., LTD.**(21) Appl. No.: **11/634,442**(22) Filed: **Dec. 6, 2006**(30) **Foreign Application Priority Data**

Dec. 6, 2005 (KR) P05-0118062




FIG.1
RELATED ART




FIG. 2
RELATED ART




FIG. 3




FIG. 4




FIG. 5





FIG.6



LIQUID CRYSTAL DISPLAY DEVICE AND DRIVING METHOD THEREOF

[0001] This application claims the benefit of priority of Korean Patent Application No. P05-0118062, filed in Korea on Dec. 6, 2005, which is hereby incorporated by reference.

BACKGROUND

[0002] 1. Technical Field

[0003] The present invention relates to a liquid crystal display device, and more particularly to a liquid crystal display device and a driving method thereof that are capable of automatically selecting a common voltage to supply it to a common electrode of liquid crystal cells.

[0004] 2. Description of the Related Art

[0005] A liquid crystal display device (LCD) controls light transmittance of liquid crystal cells based on video signals to thereby display a picture. An active matrix type of liquid crystal display device with a switching device provided for each liquid crystal cell is advantageous for an implementation of moving pictures because it permits an active control of the switching device. The switching device used for the active matrix liquid crystal display device may employ a thin film transistor (hereinafter, referred to as "TFT") as shown in FIG. 1.

[0006] Referring to FIG. 1, the active matrix LCD converts a digital input data into an analog data voltage based on a gamma reference voltage to supply it to a data line DL and, at the same time, supplies a scanning pulse to a gate line GL to thereby charge a liquid crystal cell Clc.

[0007] A gate electrode of the TFT is connected to the gate line GL while a source electrode thereof is connected to the data line DL. Further, a drain electrode of the TFT is connected to a pixel electrode of the liquid crystal cell Clc and to one electrode of a storage capacitor Cst.

[0008] A common electrode of the liquid crystal cell Clc is supplied with a common voltage Vcom.

[0009] The storage capacitor Cst charges a data voltage fed from the data line DL when the TFT is turned-on, thereby constantly keeping a voltage at the liquid crystal cell Clc.

[0010] If the scanning pulse is applied to the gate line GL, then the TFT is turned on to provide a channel between the source electrode and the drain electrode thereof, thereby supplying a voltage on the data line DL to the pixel electrode of the liquid crystal cell Clc. In this case, liquid crystal molecules of the liquid crystal cell have an alignment changed by an electric field between the pixel electrode and the common electrode to thereby modulate an incident light.

[0011] A configuration of the related art LCD including pixels having the above-mentioned structure will be described with reference to FIG. 2. FIG. 2 is a block diagram showing a configuration of a general liquid crystal display device. Referring to FIG. 2, a general liquid crystal display device 100 includes a liquid crystal display panel 110 provided with a thin film transistor (TFT) that drives the liquid crystal cell Clc at an intersection of data lines DL1 to DLm and gate lines GL1 to GLn crossing each other, a data driver 120 that supplies data to the data lines DL1 to DLm of the liquid crystal display panel 110, a gate driver 130 that

supplies a scanning pulse to the gate lines GL1 to GLn of the liquid crystal display panel 110, a gamma reference voltage generator 140 that generates a gamma reference voltage to supply it to the data driver 120, a common voltage generator 150 that generates a common voltage Vcom to supply it to the common electrode of the liquid crystal cell Clc of the liquid crystal display panel 110, a gate driving voltage generator 160 that generates a gate high voltage VGH and a gate low voltage VGL to supply them to the gate driver 130, and a timing controller 170 that controls the data driver 120 and the gate driver 130.

[0012] The liquid crystal display panel 110 has a liquid crystal injected between two glass substrates. On the lower glass substrate of the liquid crystal display panel 110, the data lines DL1 to DLm and the gate lines GL1 to GLn perpendicularly cross each other. Each intersection between the data lines DL1 to DLm and the gate lines GL1 to GLn is provided with the TFT. The TFT supplies a data on the data lines DL1 to DLm to the liquid crystal cell Clc in response to the scanning pulse. The gate electrode of the TFT is connected to the gate lines GL1 to GLn while the source electrode thereof is connected to the data line DL1 to DLm. Further, the drain electrode of the TFT is connected to the pixel electrode of the liquid crystal cell Clc and to the storage capacitor Cst.

[0013] The TFT is turned-on in response to the scanning pulse applied, via the gate lines GL1 to GLn, to the gate terminal thereof. Upon turning-on of the TFT, video data on the data lines DL1 to DLm is supplied to the pixel electrode of the liquid crystal cell Clc. The data driver 120 supplies data to the data lines DL1 to DLm based on a data driving control signal DDC supplied from the timing controller 170. Further, the data driver 120 samples and latches a digital video data RGB fed from the timing controller 170, and then converts it into an analog data voltage capable of expressing a gray scale level at the liquid crystal cell Clc of the liquid crystal display panel 110 based on a gamma reference voltage from the gamma reference voltage generator 140, thereby supplying it the data lines DL1 to DLm.

[0014] The gate driver 130 sequentially generates a scanning pulse, that is, a gate pulse in response to a gate driving control signal GDC and a gate shift clock GSC supplied from the timing controller 170 to supply them to the gate lines GL1 to GLn. In this case, the gate driver 130 determines a high level voltage and a low level voltage of the scanning pulse in accordance with the gate high voltage VGH and the gate low voltage VGL from the gate driving voltage generator 160.

[0015] The gamma reference voltage generator 140 receives a power supply voltage VCC of 0V to 3.3V supplied from a system installed the liquid crystal display device 100, for example, a controller (not shown) of an image display apparatus such as a TV set, etc to generate a positive gamma reference voltage and a negative gamma reference voltage and output them to the data driver 120.

[0016] The common voltage generator 150 receives the power supply voltage VCC to generate a common voltage Vcom, and supplies it to the common electrode of the liquid crystal cell Clc provided at each pixel of the liquid crystal display panel 110.

[0017] The gate driving voltage generator 160 is applied with the power supply voltage VCC of 3.3V supplied from

the system to generate the gate high voltage VGH and the gate low voltage VGL, and supplies them to the gate driver **130**. Herein, the gate driving voltage generator **160** generates a gate high voltage VGH more than a threshold voltage of the TFT provided at each pixel of the liquid crystal display panel **110** and a gate low voltage VGL less than the threshold voltage of the TFT. The gate high voltage VGH and the gate low voltage VGL generated in this manner are used to determine a high level voltage and a low level voltage of the scanning pulse generated by the gate driver **130**, respectively.

[0018] The timing controller **170** supplies a digital video data RGB supplied from a digital video card (not shown) to the data driver **120** and, at the same time, generates a data driving control signal DCC and a gate driving control signal GDC using horizontal/vertical synchronizing signals H and V in response to a clock signal CLK to supply them to the data driver **120** and the gate driver **130**, respectively. Herein, the data driving control signal DDC includes a source shift clock SSC, a source start pulse SSP, a polarity control signal POL and a source output enable signal SOE, or other signals, and the gate driving control signal GDC includes a gate start pulse GSP and a gate output enable signal GOE, or other signals. The timing controller **170** generates a gate shift clock GSC to adjust a swing width of a gate pulse output from the gate driver **130** to supply it to the gate driver **130**. In this case, a high-level voltage and a low-level voltage of the gate shift clock GSC is 3.3V and 0V, respectively. If the gate shift clock GSC is supplied, then the gate driver **130** determines a high-level voltage and a low-level voltage of the gate pulse using the gate high voltage VGH and the gate low voltage VGL supplied from the gate driving voltage generator **160** in accordance with the gate shift clock GSC.

[0019] As described above, since a related art liquid crystal display device always supplies a constant common voltage to a common electrode of liquid crystal cells Clc regardless of a scan line system such as a phase-alternating line (PAL) system driven with a frequency of 50 Hz or a National Television Systems Committee NTSC system driven with a frequency of 60 Hz, there is raised a problem in that a flicker and a residual image are generated on the screen.

SUMMARY

[0020] A liquid crystal display device comprises a controller that selectively controls a supply of a first common voltage or a second common voltage based on a scan line system of an image signal displayed at a liquid crystal display panel; a first common voltage generator that supplies the first common voltage based on a control of the controller to the common electrode of the liquid crystal cells; and a second common voltage generator that supplies the second common voltage based on a control of the controller to the common electrode of the liquid crystal cells.

Input

[0021] A method of driving a liquid crystal display device includes judging a scan line system of an image signal displayed at a liquid crystal display panel via a scan line format; and supplying a common voltage adaptive for the judged scan line system to a common electrode of liquid crystal cells.

[0022] A liquid crystal display device is disclosed that includes a frame counter that counts the number of the input frame; a controller that judges a scan line system of an image signal displayed at a liquid crystal display panel via a frame number counted by the frame counter during a designated unit time to selectively control a supply of a first common voltage and a second common voltage based on the judged scan line system; a first common voltage generator that supplies the first common voltage to a common electrode of liquid crystal cells based on a control of the controller; and a second common voltage generator that supplies the second common voltage to a common electrode of liquid crystal cells based on a control of the controller.

[0023] A method of driving a liquid crystal display device includes counting the input frame number during a designated unit time; judging a scan line system of an image signal displayed at a liquid crystal display panel via the counted frame number; and supplying a common voltage adaptive for the judged scan line system to a common electrode of liquid crystal cells.

[0024] Other systems, methods, features and advantages of the invention will be, or will become, apparent to one with skill in the art upon examination of the following figures and detailed description. It is intended that all such additional systems, methods, features and advantages be included within this description, be within the scope of the invention, and be protected by the following claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0025] These and other objects of the invention will be apparent from the following detailed description of the embodiments of the present invention with reference to the accompanying drawings, in which:

[0026] FIG. 1 is an equivalent circuit diagram of a pixel provided at an example liquid crystal display device.

[0027] FIG. 2 is an example block diagram showing a configuration of a related art liquid crystal display device.

[0028] FIG. 3 is an example block diagram showing a configuration of a liquid crystal display device.

[0029] FIG. 4 is an example flow chart of acts taken to drive the liquid crystal display device.

[0030] FIG. 5 is an example block diagram showing a configuration of a liquid crystal display device.

[0031] FIG. 6 is an example flow chart showing acts taken to drive the liquid crystal display device.

DETAILED DESCRIPTION

[0032] FIG. 3 is a block diagram showing a configuration of a liquid crystal display device. Referring to FIG. 3, a liquid crystal display device **200** includes the liquid crystal display panel **110**, a data driver **120**, a gate driver **130**, a gamma reference voltage generator **140** and a gate driving voltage generator **160** likewise the liquid crystal display device **100** as shown in FIG. 2. The liquid crystal display device **200** includes a first common voltage generator **210** driven by an enable ENB signal to supply a PAL system common voltage to a common electrode of liquid crystal cells Clc. A second common voltage generator **220** is driven by an enable ENB signal to supply a NTSC system common

voltage to a common electrode of liquid crystal cells Clc. A timing controller **230** judges a scan line system of an image signal displayed at the liquid crystal display panel **110** via the input scan line format to selectively control a common voltage supply of the first and second common voltage generator **210** and **220**.

[0033] The first common voltage generator **210** sets a common voltage value to generate a PAL system common voltage and if an enable signal ENB is input from the timing controller **230**, then the first common voltage generator **210** is enabled to supply a PAL system common voltage to a common electrode of liquid crystal cells Clc, and if a disable signal DIB is input from the timing controller **230**, then the first common voltage generator **210** is disabled to stop a supply of a PAL system common voltage.

[0034] The second common voltage generator **220** sets a common voltage value to generate an NTSC system common voltage and if an enable signal ENB is input from the timing controller **230**, then the second common voltage generator **220** is enabled to supply a NTSC system common voltage to a common electrode of liquid crystal cells Clc, and if a disable signal DIB is input from the timing controller **230**, then the second common voltage generator **220** is disabled to stop a supply of a NTSC system common voltage.

[0035] The timing controller **230** supplies a digital video data RGB supplied from a digital video card (not shown) to the data driver **120** and, at the same time, generates a data driving control signal DCC and a gate driving control signal GDC using horizontal/vertical synchronizing signals H and V in response to a clock signal CLK to supply them to the data driver **120** and the gate driver **130**, respectively. The timing controller **230** generates a gate shift clock GSC used for adjusting a swing width of a gate pulse output from the gate driver **130** to supply it to the gate driver **130**.

[0036] A common voltage control execution program for judging a scan line system via a scan line format to control a generation of a PAL system common voltage and a NTSC system common voltage is set at the timing controller **230** to control a supply of a common voltage as follows.

[0037] The timing controller **230** judges whether a scan line system of an image signal displayed at the liquid crystal display panel **110** via a scan line format input via a connector (not shown) is a PAL system or a NTSC system. If a scan line system is a PAL system, then the timing controller **230** supplies an enable signal ENB to the first common voltage generator **210** and supplies a disable signal DIB to the second common voltage generator **220**. Accordingly, the first common voltage generator **210** is enabled by an enable signal ENB to supply a PAL system common voltage to a common electrode of liquid crystal cells Clc while the second common voltage generator **220** is disabled by a disable signal DIB to stop a supply of a NTSC system common voltage.

[0038] If a scan line system of an image signal displayed at the liquid crystal display panel **110** is an NTSC system, then the timing controller **230** supplies an enable signal ENB to the second common voltage generator **220** and supplies a disable signal DIB to the first common voltage generator **210** at the same time. The second common voltage generator **220** is enabled by an enable signal ENB to supply a NTSC

system common voltage to a common electrode of liquid crystal cells Clc while the first common voltage generator **210** is disabled by a disable signal DIB to stop a supply of a PAL system common voltage.

[0039] On the other hand, the common voltage control execution program is set at the timing controller **230** to selectively supply a common voltage adaptive for a scan line system, but it is not confined by this. For example, the common voltage control execution program is set at a controller (not shown) implemented separately other than the timing controller **230**, so that the controller may control a common voltage supply of the first and second common voltage generator **210** and **220**.

[0040] FIG. 4 illustrates a process by which the liquid crystal display device **200** selectively supplies a common voltage in accordance with a scan line system via a scan line format

[0041] Referring to FIG. 4, if video data to be displayed and a scan line format are input at the liquid crystal display panel **110** (S401), then the timing controller **230** judges whether a scan line system of an image signal to be displayed at the liquid crystal display panel **110** via the input scan line format is a PAL system or an NTSC system (S402).

[0042] If the result is a PAL system, then the timing controller **230** supplies an enable signal ENB to the first common voltage generator **210** and supplies a disable signal DIB to the second common voltage generator **220** at the same time (S403). The first common voltage generator **210** is enabled by an enable signal ENB to supply a PAL system common voltage to a common electrode of liquid crystal cells Clc, while the second common voltage generator **220** is disabled by a disable signal DIB to stop a supply of a NTSC system common voltage (S404).

[0043] If the result is an NTSC system, then the timing controller **230** supplies an enable signal ENB to the second common voltage generator **220** and supplies a disable signal DIB to the first common voltage generator **210** at the same time (S405). The second common voltage generator **220** is enabled by an enable signal ENB to supply a NTSC system common voltage to a common electrode of liquid crystal cells Clc, while the first common voltage generator **210** is disabled by a disable signal DIB to stop a supply of a PAL system common voltage (S406).

[0044] FIG. 5 is a block diagram showing a configuration of a liquid crystal display device. Referring to FIG. 5, a liquid crystal display device **300** includes the liquid crystal display panel **110**, the data driver **120**, the gate driver **130**, the gamma reference voltage generator **140**, the gate driving voltage generator **160**, the first common voltage generator **210** and the second common voltage generator **220**.

[0045] The liquid crystal display device **300** includes a frame counter **310** that counts the number of the input frame; and a timing controller **320** that judges a scan line system of an image signal displayed at the liquid crystal display panel **110** via a frame number counted by the frame counter **310** during a designated unit time to selectively control a common voltage supply of the first and second common voltage generator **210** and **220** based on the judged scan line system.

[0046] The frame counter **310** counts the input frame number to output the counted frame number into the timing

controller 320. For example, the frame counter 310 counts the number of a rising edge of the input vertical synchronizing signal to thereby count a frame number.

[0047] The timing controller 320 supplies a digital video data RGB supplied from a digital video card (not shown) to the data driver 120 and, at the same time, generates a data driving control signal DCC and a gate driving control signal GDC using horizontal/vertical synchronizing signals H and V in response to a clock signal CLK to supply them to the data driver 120 and the gate driver 130, respectively. The timing controller 320 generates a gate shift clock GSC used for adjusting a swing width of a gate pulse output from the gate driver 130 to supply it to the gate driver 130.

[0048] A common voltage control execution program for judging a scan line system via a frame number to control a generation of a PAL system common voltage and a NTSC system common voltage is set at the timing controller 320 to control a supply of a common voltage as follows.

[0049] The timing controller 320 judges whether a scan line system of an image signal displayed at the liquid crystal display panel 110 via a frame number counted by the frame counter 310 during a designated unit time is a PAL system or a NTSC system. Herein, if a frame number counted during a designated unit time, that is, one second, is a predetermined first reference frame number, that is, fifty frames, then the timing controller 320 judges a PAL system using a frequency of 50 Hz. If a frame number counted during a designated unit time, that is, one second, is a predetermined second reference frame number, that is, sixty frames, then the timing controller 320 judges a NTSC system using a frequency of 60 Hz. A method of judging a scan line system using a frame number can be changed in a variety of system by the users.

[0050] If a scan line system is judged as a PAL system by the counted frame number, then the timing controller 320 supplies an enable signal ENB to the first common voltage generator 210 and supplies a disable signal DIB to the second common voltage generator 220 at the same time. The first common voltage generator 210 is enabled by an enable signal ENB to supply a PAL system common voltage to a common electrode of liquid crystal cells Clc while the second common voltage generator 220 is disabled by a disable signal DIB to stop a supply of a NTSC system common voltage.

[0051] If a scan line system is judged as a NTSC system by the counted frame number, then the timing controller 320 supplies an enable signal ENB to the second common voltage generator 220 and supplies a disable signal DIB to the first common voltage generator 210 at the same time. The second common voltage generator 220 is enabled by an enable signal ENB to supply a NTSC system common voltage to a common electrode of liquid crystal cells Clc while the first common voltage generator 210 is disabled by a disable signal DIB to stop a supply of a PAL system common voltage.

[0052] The common voltage control execution program may be set for judging a scan line system using a frame number at the timing controller 320 to selectively supply a common voltage adaptive for a scan line system, but it is not confined by this. For example, the common voltage control execution program is set at a controller (not shown) imple-

mented separately other than the timing controller 320, so that the controller may control a common voltage supply of the first and second common voltage generator 210 and 220. The frame counter 310 may then be implemented in such a manner to output the counted frame number into the controller.

[0053] FIG. 6 illustrates example acts in a process which the liquid crystal display device 300 having the above-mentioned configuration selectively supplies a common voltage based on a scan line system judged via a frame number. Referring to FIG. 6, if a video data to be displayed and a vertical synchronizing signal are input at the liquid crystal display panel 110 (S601), then the frame counter 310 counts the number of the input frame to output the timing controller 320 (S602).

[0054] The timing controller 320 compares whether a frame number counted during a designated unit time is the same as the number of a predetermined first reference frame or the number of a predetermined second reference frame. The timing controller 320 judges whether a scan line system of an image signal to be displayed at the liquid crystal display panel 110 is a PAL system or a NTSC system (S603). Herein, the number of a predetermined first reference frame can be set in fifty frames, which shows a frame number of a PAL system, and the number of a predetermined second reference frame can be set in sixty frames which shows a frame number of a NTSC system.

[0055] As a result, if the counted frame number is the same as the predetermined first reference frame number to be judged as a PAL system, then the timing controller 320 supplies an enable signal ENB to the first common voltage generator 210 and supplies a disable signal DIB to the second common voltage generator 220 at the same time (S604). The first common voltage generator 210 is enabled by an enable signal ENB to supply a PAL system common voltage to a common electrode of liquid crystal cells Clc while the second common voltage generator 220 is disabled by a disable signal DIB to stop a supply of a NTSC system common voltage (S605).

[0056] If the counted frame number is the same as the predetermined second reference frame number to be judged as a NTSC system, then the timing controller 320 supplies an enable signal ENB to the second common voltage generator 220 and supplies a disable signal DIB to the first common voltage generator 210 at the same time (S606). Accordingly, the second common voltage generator 220 is enabled by an enable signal ENB to supply a NTSC system common voltage to a common electrode of liquid crystal cells Clc while the first common voltage generator 210 is disabled by a disable signal DIB to stop a supply of a PAL system common voltage (S607).

[0057] As described above, the disclosed system automatically selects a PAL system common voltage and a NTSC system common voltage based on a scan line system such as a PAL system or a NTSC system, so that it becomes possible to prevent a generation of a flicker and a residual image on the screen.

[0058] Although the present invention has been explained by the embodiments shown in the drawings described above, it should be understood to the ordinary skilled person in the art that the invention is not limited to the embodiments, but

rather that various changes or modifications thereof are possible without departing from the spirit of the invention. Accordingly, the scope of the invention shall be determined only by the appended claims and their equivalents.

What is claimed is:

1. A liquid crystal display device including a common electrode coupled with liquid crystal cells, comprising:

a controller operable to selectively control a supply of a first common voltage or a second common voltage based on a scan line system of an image signal displayed on a liquid crystal display panel;

a first common voltage generator operable to supply the first common voltage based on a control signal of the controller to the common electrode of the liquid crystal cells; and

a second common voltage generator operable to supply the second common voltage based on a control signal of the controller to the common electrode of the liquid crystal cells.

2. The liquid crystal display device of claim 1, wherein said controller judges a scan line system of an image signal displayed on the liquid crystal display panel via an input scan line format.

3. The liquid crystal display device of claim 2, wherein said first common voltage is a common voltage for a phase-alternating line (PAL) system.

4. The liquid crystal display device of claim 3, wherein if the scan line system of the image signal displayed at the liquid crystal display panel is judged as the PAL system, then the controller supplies an enable signal to the first common voltage generator.

5. The liquid crystal display device of claim 4, wherein said first common voltage generator is driven by the enable signal to supply the first common voltage.

6. The liquid crystal display device of claim 2, wherein said second common voltage is a common voltage for a National Television Systems Committee (NTSC) system.

7. The liquid crystal display device of claim 6, wherein if the scan line system of the image signal displayed at the liquid crystal display panel is judged as the NTSC system, then the controller supplies an enable signal to the second common voltage generator.

8. The liquid crystal display device of claim 7, wherein said second common voltage generator is driven by the enable signal to supply the second common voltage.

9. A method of driving a liquid crystal display device comprising:

judging a scan line system of an image signal displayed on a liquid crystal display panel via a scan line format; and

supplying a common voltage adaptive for the judged scan line system to a common electrode of liquid crystal cells.

10. The method of driving the liquid crystal display device of claim 9, wherein judging a scan line system of an image signal comprises judging as a phase-alternating line (PAL) system or a National Television Systems Committee (NTSC) system.

11. The method of driving the liquid crystal display device of claim 10, further comprising, if the judged scan line

system is the PAL system, supplying the PAL system common voltage to a common electrode of the liquid crystal cells.

12. The method of driving the liquid crystal display device of claim 10, further comprising, if the judged scan line system is the NTSC system, supplying an NTSC system common voltage to a common electrode of the liquid crystal cells.

13. A liquid crystal display device comprising:

a frame counter operable to count a number of an input frame;

a controller operable to judge a scan line system of an image signal displayed on a liquid crystal display panel via a frame number counted by the frame counter during a designated unit time to selectively control a supply of a first common voltage and a second common voltage based on the judged scan line system;

a first common voltage generator operable to supply the first common voltage to a common electrode of liquid crystal cells based on a control of the controller; and

a second common voltage generator operable to supply the second common voltage to a common electrode of liquid crystal cells based on a control signal of the controller.

14. The liquid crystal display device of claim 13, wherein said first common voltage is a common voltage for a phase-alternating line (PAL) system.

15. The liquid crystal display device as claimed in claim 14, wherein if a frame number counted by the frame counter and a predetermined first reference frame number are the same each other during a designated unit time, then the controller judges the scan line system as the PAL system.

16. The liquid crystal display device of claim 14, wherein if a scan line system is judged as the PAL system, then the controller supplies an enable signal to the first common voltage generator.

17. The liquid crystal display device of claim 16, wherein said first common voltage generator is driven by the enable signal to supply the first common voltage.

18. The liquid crystal display device of claim 13, wherein said second common voltage is a common voltage for a National Television Systems Committee (NTSC) system.

19. The liquid crystal display device of claim 18, wherein if a frame number counted by the frame counter and a predetermined second reference frame number are the same during a designated unit time, then the controller judges a scan line system as the NTSC system.

20. The liquid crystal display device of claim 19, wherein if a scan line system is judged as the NTSC system, then the controller supplies an enable signal to the second common voltage generator.

21. The liquid crystal display device of claim 20, wherein said second common voltage generator is driven by the enable signal to supply the second common voltage.

22. A method of driving a liquid crystal display device comprises the steps of:

counting the input frame number during a designated unit time;

judging a scan line system of an image signal displayed at a liquid crystal display panel via the counted frame number; and

supplying a common voltage adaptive for the judged scan line system to a common electrode of liquid crystal cells.

23. The method of driving the liquid crystal display device as claimed in claim 22, wherein if the counted frame number and a predetermined first reference frame number are the same each other, then a scan line system is judged as a PAL system.

24. The method of driving the liquid crystal display device as claimed in claim 23, wherein if the judged scan line system is a PAL system, then a PAL system common voltage is supplied to a common electrode of the liquid crystal display cells.

25. The method of driving the liquid crystal display device as claimed in claim 22, wherein if the counted frame number and a predetermined second reference frame number are the same each other, then a scan line system is judged as a NTSC system.

26. The method of driving the liquid crystal display device as claimed in claim 25, wherein if the judged scan line system is a NTSC system, then a NTSC system common voltage is supplied to a common electrode of the liquid crystal display cells.

* * * * *

专利名称(译)	液晶显示装置及其驱动方法		
公开(公告)号	US20070126687A1	公开(公告)日	2007-06-07
申请号	US11/634442	申请日	2006-12-06
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG 飞利浦LCD CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	CHOI YEON HO		
发明人	CHOI, YEON HO		
IPC分类号	G09G3/36		
CPC分类号	G09G3/3611 G09G3/3655 G09G2320/0247 G09G2320/0613 G09G2320/08		
优先权	1020050118062 2005-12-06 KR		
其他公开文献	US8711068		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种用于自动选择适合于扫描线系统的公共电压以将其提供给液晶单元的公共电极的液晶显示装置。在液晶显示装置中，控制器根据在液晶显示板上显示的图像信号的扫描线系统选择性地控制第一公共电压或第二公共电压的供应。第一公共电压发生器根据控制器的控制将第一公共电压提供给液晶单元的公共电极。并且，第二公共电压发生器根据控制器的控制将第二公共电压提供给液晶单元的公共电极。

