



US008098358B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 8,098,358 B2**
(45) **Date of Patent:** **Jan. 17, 2012**

(54) **LIQUID CRYSTAL DISPLAY**

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Hoon Kim**, Ansan-si (KR); **Seung-Soo Baek**, Seoul (KR); **Hye-Seok Na**, Seoul (KR)

JP	2003066453	3/2003
JP	2007212914	8/2007
JP	2007249243	9/2007
JP	2008116916	5/2008
KR	1020070049882	5/2007
KR	1020070082752	8/2007
KR	1020070101549	10/2007
KR	1020080049366	6/2008

(73) Assignee: **Samsung Electronics Co., Ltd.**, Suwon-si (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 251 days.

* cited by examiner

(21) Appl. No.: **12/472,983**

Primary Examiner — Jennifer Doan

(22) Filed: **May 27, 2009**

(74) Attorney, Agent, or Firm — H.C. Park & Associates, PLC

(65) **Prior Publication Data**

US 2010/0134742 A1 Jun. 3, 2010

(30) **Foreign Application Priority Data**

Nov. 28, 2008 (KR) 10-2008-0120014

(51) **Int. Cl.**
G02F 1/1343 (2006.01)

(52) **U.S. Cl.** **349/141**; 349/56; 349/84; 349/139; 349/140

(58) **Field of Classification Search** 349/56, 349/84, 139, 140, 141
See application file for complete search history.

(56) **References Cited**


U.S. PATENT DOCUMENTS


7,440,040 B2 * 10/2008 Kwak et al. 349/39
2007/0242009 A1 10/2007 Su
2008/0088783 A1 4/2008 Tai

(57) **ABSTRACT**

The present invention relates to a liquid crystal display that includes: gate lines and data lines arranged on a first substrate; pixel electrodes connected to the gate lines and the data lines, and including a first sub-pixel electrode and a second sub-pixel electrode separated from each other by a gap; a common electrode arranged on a second substrate, and facing the pixel electrodes; and a liquid crystal layer disposed between the pixel electrodes and the common electrode and including a plurality of liquid crystal molecules, wherein each of the first sub-pixel electrode and the second sub-pixel electrode includes a plurality of fine branch portions, the second sub-pixel electrodes include a connection portion surrounding the fine branch portions of the first sub-pixel electrodes, and a plurality of notches are formed in the connection portion of the second sub-pixel electrode.

15 Claims, 7 Drawing Sheets








FIG. 3




FIG.4A




FIG.4B




FIG.4C




FIG. 5A




FIG. 5B




FIG. 5C




FIG.6A





FIG.6B



LIQUID CRYSTAL DISPLAY**CROSS REFERENCE TO RELATED APPLICATION**

This application claims priority from and the benefit of Korean Patent Application No. 10-2008-0120014, filed on Nov. 28, 2008, which is hereby incorporated by reference for all purposes as if fully set forth herein.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The present invention relates to a liquid crystal display.

2. Discussion of the Background

A liquid crystal display (LCD) is one of the most widely used types of flat panel displays. An LCD includes two display panels having field-generating electrodes, such as pixel electrodes and a common electrode, and a liquid crystal layer interposed between the display panels. The LCD induces an electric field in the liquid crystal layer by applying voltages to the field generating electrodes. The electric field determines the orientation of liquid crystal molecules in the liquid crystal layer, and this orientation controls the polarization of incident light so as to form an image.

Among the LCDs, a vertical alignment (VA) mode LCD is used in which the longitudinal axes of the liquid crystal molecules are arranged to be perpendicular to the display panels in a state where the electric field is not applied.

Forming cutouts such as fine slits in the field generating electrodes or forming protrusions on the field generating electrodes may be used to achieve a wide viewing angle in the VA mode LCD. Since the cutouts and the protrusions determine a tilt direction of the liquid crystal molecules, the tilt direction of the liquid crystal molecules may be decentralized by appropriately disposing the cutouts and the protrusions on the field generating electrodes, thereby widening the reference viewing angle.

Furthermore, a VA mode LCD may have poor lateral visibility compared to front visibility. In order to solve this problem, a method of dividing one pixel into two sub-pixels and applying different voltages to the two sub-pixels has been proposed. In an LCD with two sub-pixels, sub-pixels to which a high voltage is applied and gate lines should be spaced apart from each other a certain distance. Spacing the pixel electrodes and gate lines apart may reduce a kickback voltage of the LCD.

However, when pixel electrodes and gate lines are spaced apart, liquid crystal molecules located near the gate lines may not be affected by a tilt direction determining member formed on the pixel electrodes, thus producing an irregular texture. This irregular texture may deteriorate the display quality of the LCD.

The above information disclosed in this Background section is only for enhancement of understanding of the background of the invention and therefore it may contain information that does not form the prior art that is already known in this country to a person of ordinary skill in the art.

SUMMARY OF THE INVENTION

The present invention relates to a liquid crystal display (LCD) that reduces a kickback voltage of a display device and does not produce an irregular texture.

Additional features of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention.

The present invention discloses a liquid crystal display that includes: gate lines and data lines arranged on a first substrate; pixel electrodes connected to the gate lines and the data lines, and including a first sub-pixel electrode and a second sub-pixel electrode separated from each other by a gap; a common electrode arranged on a second substrate, and facing the pixel electrodes; and a liquid crystal layer disposed between the pixel electrodes and the common electrode, and including a plurality of liquid crystal molecules, wherein each of the first sub-pixel electrode and the second sub-pixel electrode includes a plurality of fine branch portions, the second sub-pixel electrode includes a connection portion surrounding the fine branch portions of the first sub-pixel electrode, and a plurality of notches are formed in the connection portion of the second sub-pixel electrode.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention, and together with the description serve to explain the principles of the invention.

FIG. 1 is an equivalent circuit diagram of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention.

FIG. 2 is a layout view of a liquid crystal display according to an exemplary embodiment of the present invention.

FIG. 3 is a cross-sectional view taken along line III-III of the liquid crystal display shown in FIG. 2.

FIG. 4A, FIG. 4B, and FIG. 4C are microphotographs showing an irregular texture.

FIG. 5A, FIG. 5B, and FIG. 5C are microphotographs of a liquid crystal display.

FIG. 6A and FIG. 6B are drawings showing simulation results of a liquid crystal molecules director in a liquid crystal display according to an exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

The invention is described more fully hereinafter with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the exemplary embodiments set forth herein. Rather, these exemplary embodiments are provided so that this disclosure is thorough, and will fully convey the scope of the invention to those skilled in the art. In the drawings, the size and relative sizes of layers and regions may be exaggerated for clarity. Like reference numerals in the drawings denote like elements.

It will be understood that when an element or layer is referred to as being "on" or "connected to" another element or layer, it can be directly on or directly connected to the other element or layer, or intervening elements or layers may be present. In contrast, when an element is referred to as being "directly on" or "directly connected to" another element or layer, there are no intervening elements or layers present.

FIG. 1 is an equivalent circuit diagram of one pixel of a LCD according to an exemplary embodiment of the present invention.

Referring to FIG. 1, a liquid crystal display according to the present exemplary embodiment includes signal lines including a plurality of gate lines GL, a plurality of data lines DL_a and DL_b, and a plurality of pixels PX connected to the signal lines GL, DL_a, and DL_b. From a structural point of view, the liquid crystal display includes a lower display panel 100 and an upper display panel 200 that face each other, and a liquid crystal layer 3 interposed between the lower display panel 100 and the upper display panel 200.

Each pixel PX includes a pair of sub-pixels PX_a and PX_b. The sub-pixels PX_a and PX_b respectively include switching elements Q_a and Q_b, liquid crystal capacitors Cl_{ca} and Cl_{cb}, and storage capacitors C_{sta} and C_{stb}.

Each switching element Q_a/Q_b, which includes a thin film transistor (TFT), is a three-terminal element provided on the lower display panel 100. The control terminals of the first and second switching elements Q_a and Q_b are connected to the gate lines GL, the input terminals thereof are connected to the data lines DL_a and DL_b, and the output terminals thereof are connected to the liquid crystal capacitors Cl_{ca} and Cl_{cb} and the storage capacitors C_{sta} and C_{stb}.

The liquid crystal capacitors Cl_{ca} and Cl_{cb} use sub-pixel electrodes 191_a and 191_b and a common electrode 270 as two terminals, while the liquid crystal layer 3 interposed between the two terminals is used as a dielectric material.

The storage capacitors C_{sta} and C_{stb}, which assist the liquid crystal capacitors Cl_{ca} and Cl_{cb}, have storage electrode lines SL and sub-pixel electrodes 191_a and 191_b provided on the lower display panel 100 and overlap with each other. An insulator is interposed between the storage capacitors C_{sta} and C_{stb}. A fixed voltage, such as a common voltage V_{com}, is applied to the storage electrode lines SL.

Voltages charged in the two liquid crystal capacitors Cl_{ca} and Cl_{cb} are set to be slightly different from each other. For example, a data voltage applied to the liquid crystal capacitor Cl_{ca} is set to be lower or higher than a data voltage applied to the liquid crystal capacitor Cl_{cb}. Accordingly, the voltages of the two liquid crystal capacitors Cl_{ca} and Cl_{cb} can be adjusted so that an image viewed from a lateral side of the pixel approaches the image viewed from the front, thereby improving the lateral visibility of the LCD.

An LCD according to an exemplary embodiment of the present invention will be described in detail below with reference to FIG. 2 and FIG. 3.

FIG. 2 is a layout view of an LCD according to an exemplary embodiment of the present invention, and FIG. 3 is a cross-sectional view taken along line III-III of the LCD shown in FIG. 2.

An LCD of the present exemplary embodiment includes a TFT display panel 100 and a common electrode display panel 200 facing each other, and a liquid crystal layer 3 interposed between the TFT display panel 100 and the common electrode display panel 200.

First, the TFT display panel 100 will be described below.

Referring to FIG. 2 and FIG. 3, a plurality of gate lines 121 and a plurality of storage electrode lines 131 are formed on an insulating substrate 110.

The gate lines 121 transmit gate signals and extend in a substantially horizontal direction. Each of the gate lines 121 includes a plurality of gate electrodes 124_a and 124_b protruding upward.

Each of the storage electrode lines 131 includes a stem line extending in a direction substantially parallel with the gate line 121 and a plurality of electrodes 135 branched from the stem line.

The shape and arrangement of the storage electrode lines 131 may be modified in various ways.

A gate insulating layer 140 is formed on the gate lines 121 and the storage electrode lines 131. A plurality of first and second semiconductor stripes 151_a and 151_b made of amorphous silicon or crystalline silicon are formed on the gate insulating layer 140. Each of the semiconductor stripes 151_a and 151_b includes a plurality of projections 154_a and 154_b protruding toward the gate electrodes 124.

A plurality of pairs of ohmic contact members 161_a, 161_b, 163_a, 163_b, 165_a, and 165_b are formed on the semiconductor stripes 151_a and 151_b. The ohmic contacts 161_a, 161_b, 163_a, 163_b, 165_a, and 165_b may be made of n+ hydrogenated amorphous silicon in which silicide or an n-type impurity is doped with a high concentration.

A plurality of data lines 171_a and 171_b and a plurality of first and second drain electrodes 175_a and 175_b are formed on the ohmic contact members 161_a, 161_b, 163_a, 163_b, 165_a, and 165_b and the gate insulating layer 140.

The data lines 171 transmit data signals, and extend in a substantially vertical direction so as to cross the gate lines 121 and the stem lines of the storage electrode lines 131. The data lines 171_a and 171_b include first and second source electrodes 173_a and 173_b. The first and second source electrodes 173_a and 173_b are bent in a U-shape by extending toward the first and second gate electrode 124_a and 124_b, and the first and second source electrodes 175_a and 175_b face the first and second source electrodes 173_a and 173_b with respect to the first and second gate electrode 124_a and 124_b.

The drain electrodes 175_a and 175_b each include one end portion extending upward, which is partially surrounded by the first and second source electrodes 173_a and 173_b, respectively, and another end portion having a wide area so as to be connected to another layer.

However, the shape and arrangement of the data lines 171_a and 171_b including the first and second drain electrodes 175_a and 175_b may be modified in various ways.

The first and second gate electrodes 124_a and 124_b, the first and second source electrodes 173_a and 173_b, and the first and second drain electrodes 175_a and 175_b, along with the projections 154_a and 154_b of the first and second semiconductor stripes 151_a and 151_b, form first and second TFTs Q_a and Q_b. Each of the first and second TFTs Q_a and Q_b has a channel formed in the projections 154_a and 154_b of the semiconductor stripes 151_a and 151_b disposed between the first and second source electrodes 173_a and 173_b and the first and second drain electrodes 175_a and 175_b, respectively.

The ohmic contacts 161_a, 161_b, 163_a, 163_b, 165_a, and 165_b are interposed between the projections 154_a and 154_b of the underlying semiconductor stripes 151_a and 151_b and the overlying data lines 171_a and 171_b, the source electrodes 173_a and 173_b, and drain electrodes 175_a and 175_b. The ohmic contacts 161_a, 161_b, 163_a, 163_b, 165_a, and 165_b may reduce the contact resistance between the projections 154_a and 154_b of the underlying semiconductor stripes 151_a and 151_b and the overlying data lines 171_a and 171_b, the source electrodes 173_a and 173_b, and drain electrodes 175_a and 175_b. The semiconductor stripes 151_a and 151_b include some exposed portions that are not covered with the data lines 171_a and 171_b and the drain electrodes 175_a and 175_b, such as portions located between the source electrodes 173_a and 173_b and the drain electrodes 175_a and 175_b.

The ohmic contact members 161_a, 161_b, 163_a, 163_b, 165_a, and 165_b, the data lines 171_a, 171_b, 173_a, and 173_b, and the drain electrodes 175_a and 175_b have the same planar pattern, and have substantially the same planar pattern as the semiconductor stripes 151_a and 151_b except for exposed portions between the drain electrodes 175_a and 175_b and the source electrodes 173_a and 173_b.

A lower passivation film **180p** made of silicon nitride or silicon oxide is formed on the data lines **171a** and **171b**, the drain electrodes **175a** and **175b**, and the exposed semiconductor stripes **151a** and **151b**.

A color filter **230** is formed on the lower passivation film **180p**. The lower passivation film **180p** may prevent a pigment of the color filter **230** from flowing to the exposed portions of the semiconductor stripes **154a** and **154b**. The color filter **230** may alternately be formed on the common electrode display panel **200**.

An upper passivation film **180q** is formed on the color filter **230**. The upper passivation layer **180q** may be made of an inorganic material. The upper passivation layer **180q** prevents the color filter **230** from separating from the layers on which it is formed and suppresses contamination of the liquid crystal layer **3** caused by an organic material, such as a solvent, flowing from the color filter **230**. Forming the upper passivation layer **180q** on the color filter **230** may help prevent defects such as an afterimage that may be caused when the LCD is driven.

A plurality of pixel electrodes **191** are formed on the upper passivation film **180q**.

Each of the pixel electrodes **191** includes first and second sub-pixel electrodes **191a** and **191b** separated from each other by a gap **91**.

The first and second sub-pixel electrodes **191a** and **191b** have an overall shape of a quadrangle, and include cross-shaped stem portions including horizontal stem portions and vertical stem portions extending from the horizontal stem portions, so the horizontal and vertical stem portions are substantially perpendicular to each other. The first and second sub-pixel electrodes **191a** and **191b** are divided into four sub-regions by the horizontal stem portions and the vertical stem portions, and each of the sub-regions includes a plurality of fine branch portions.

The second sub-pixel electrode **191b** surrounds the first sub-pixel electrode **191a**. The second sub-pixel electrode **191b** is connected from the fine branch portions to surround three sides of the first sub-pixel electrode **191a**, and includes a connection portion **93** having a quadrangular semicircular shape. The connection portion **93** includes a first portion **93a** formed in parallel with the gate lines **121**, and two second portions **93b** formed in parallel with the data lines **171a** and **171b**. The first portion **93a** and the two second portions **93b** are interconnected and surround three sides of the first sub-pixel electrode **191a**.

One of the fine branch portions of each the first sub-pixel electrode **191a** and the second sub-pixel electrode **191b** obliquely extends in a left-upward direction from the horizontal stem portions or the vertical stem portions, and another fine branch portion of each sub-pixel electrode **191a** and **191b** obliquely extends in a right-upward direction from the horizontal stem portions or the vertical stem portions. Another fine branch portion of each sub-pixel electrode **191a** and **191b** extends in a left-downward direction from the horizontal stem portions or the vertical stem portions, and the remaining branch portion of each sub-pixel electrode **191a** and **191b** obliquely extends in a right-downward direction from the horizontal stem portions or the vertical stem portions.

Each of the fine branch portions makes an angle of about 45 or 135 degrees to the gate lines **121** or the horizontal stem portions. The branch portions in two adjacent sub-regions may extend substantially perpendicular to each other.

Although not shown, the fine branch portions may be wider when they are closer to the horizontal stem portions or the vertical stem portions.

The area occupied by the second sub-pixel electrode **191b** in the entire pixel electrode **191** may be larger than the area occupied by the first sub-pixel electrode **191a**, and the area of the second sub-pixel electrode **191b** may be 1.0 to 2.5 times larger than the area of the first sub-pixel electrode **191a**. However, the shape or area ratio of the first and second sub-pixel electrodes **191a** and **191b** may be modified in various ways.

Referring to FIG. 2, the first sub-pixel electrode **191a** of the pixel electrode **191** is spaced apart from the gate lines **121** on a planar surface. A gap between the first sub-pixel electrode **191a** and the gate lines **121** that are spaced apart may be about 2 μm to 7 μm . By spacing the first sub-pixel electrode **191a**, to which a high data voltage is applied, apart from the gate lines **121**, an unnecessary capacitance formed between the first sub-pixel electrode **191a** and the gate lines **121** can be reduced, thereby reducing the kickback voltage.

A plurality of notches **7**, which are recessed, are formed in the first portion **93a** of the second sub-pixel electrode **191b**. The plurality of notches **7** may be spaced apart at equal intervals. The notches **7** should control the movement of the liquid crystal molecules disposed on the first portion **93a** of the second sub-pixel electrode **191b** spaced apart from the fine branch portions of the second sub-pixel electrode **191b**. By controlling the movement of the liquid crystal molecules disposed on the first portion **93a** of the second sub-pixel electrode **191b**, a singular point where the alignment direction of the liquid crystal molecules is changed is always at the same position. That is, a singular point is always formed on the notches **7**, to prevent a portion where liquid crystal molecules are scattered from being changed. Therefore, the generation of irregular texture may be suppressed, thus preventing the generation of spots or afterimages. The notches **7** may have the shape of a triangle, a quadrangle, a trapezoid, or a semicircle.

The first and second sub-pixel electrodes **191a** and **191b** are physically and electrically connected to the first and second drain electrodes **175a** and **175b** via contact holes **185a** and **185b**, and are applied with a data voltage from the first and second drain electrodes **175a** and **175b**.

The planar pattern of these pixel electrodes **191** may be formed in various shapes. In the present exemplary embodiment, the pixel electrodes **191** include the first and second sub-pixel electrodes **191a** and **191b**, and the first and second sub-pixel electrodes **191a** and **191b** are connected to the first and second drain electrodes **175a** and **175b**. Alternatively, the pixel electrodes **191** may include one electrode and be connected to one drain electrode.

A lower alignment film **11** is formed on the pixel electrodes **191**.

The common electrode display panel **200** will be described below.

A light blocking member **220** is formed on an insulating substrate **210** made of transparent glass or plastic. The light blocking member **220** is also called a black matrix and blocks light leakage.

The light blocking member **220** has a plurality of openings (not shown) that face the pixel electrodes **191** and have substantially the same shape as the pixel electrodes **191**, and blocks light leakage between the pixel electrodes **191**. However, the light blocking member **220** may consist of portions corresponding to the gate lines **121** and the data lines **171** and portions corresponding to the TFTs.

An overcoat **250** is formed on the light blocking member **220**. The overcoat **250** is made of an organic insulator and provides a flat surface. The overcoat **250** may be omitted.

The common electrode **270** is formed on the overcoat **250**. The common electrode **270** is made of a transparent conductor such as indium tin oxide (ITO) or indium zinc oxide (IZO).

An upper alignment film **21** is formed on the common electrode **270**.

The lower alignment film **11** and the upper alignment film **21** may be vertical alignment films.

Polarizers (not shown) may be provided on outer surfaces of the lower thin film transistor display panel and the upper common electrode display panel.

The liquid crystal layer **3** is interposed between the lower thin film transistor display panel and the upper common electrode display panel, and the liquid crystal layer **3** includes liquid crystal molecules **31** having negative dielectric anisotropy. The liquid crystal molecules **31** of the liquid crystal layer **3** may have a pretilt angle so that their long axes are substantially parallel to the lengthwise direction of the fine branch portions of the first and second sub-pixel electrodes **191a** and **191b**, and they may be aligned so as to be substantially perpendicular to the surfaces of the two display panels **100** and **200**. The liquid crystal layer **3** further includes an optical polymer, which enables the liquid crystal molecules **31** to have a pretilt angle so that their long axes are substantially parallel to the lengthwise direction of the fine branch portions of the first and second sub-pixel electrodes **191a** and **191b**. A light alignment method in which light such as ultraviolet rays may be obliquely irradiated to the alignment layers **11** and **21** may be used to control the alignment direction and the alignment angle of the liquid crystal molecules **31** as a means for forming a plurality of subregions where the liquid crystal molecules **31** are inclined in different directions.

When the gate lines **121** are supplied with a gate signal, the first and second sub-pixel electrodes **191a** and **191b** are supplied with data voltages via the data lines **171a** and **171b**. Then, the sub-pixel electrodes **191a** and **191b** supplied with the data voltages generate electric fields in cooperation with the common electrode **270** supplied with a common voltage. At this time, the sides of the fine branch portions distort the electric field to create a horizontal component that is perpendicular to the sides of the fine branch portions, and the tilt directions of the liquid crystal molecules **31** are determined by the horizontal component. Therefore, the liquid crystal molecules **31** initially tend to be tilted in a direction perpendicular to the sides of the fine branch portions. However, the directions of the horizontal component of the electric field distorted by the sides of the adjacent fine branch portions are opposite to each other and the gap between the fine branch portions is narrow, so that the liquid crystal molecules **31** tending to be tilted in opposite directions to each other are tilted together in a direction parallel to the lengthwise direction of the fine branch portions.

In an exemplary embodiment of the present invention, since the long axes of the fine branch portions of one pixel are distributed in four directions, the tilt directions of the liquid crystal molecules **31** are classified into four directions. When the tilt directions of the liquid crystal molecules **31** are diversified in this way, the reference viewing angle of the LCD may be increased.

As described above, a plurality of notches **7** are formed in the first portion **93a** of the second sub-pixel electrode **191b** of the LCD in accordance with an exemplary embodiment of the present invention. Therefore, the liquid crystal molecules **31** of the first portion **93a** of the second sub-pixel electrode **191b**, which are spaced apart from the fine branch portions of the first sub-pixel electrode **191a** and second sub-pixel electrode **191b**, may be arranged in a predetermined pattern by the notches **7**. These notches **7** may have the shape of a triangle,

a quadrangle, a trapezoid, or a semicircle, and the liquid crystal molecules **31** director arranged around the first portion **93a** of the second sub-pixel electrode **191b** is controlled to be directed toward the notches **7**. Therefore, since the liquid crystal molecules **31** are stably arranged around the first portion **93a** of the second sub-pixel electrode **191b** spaced apart from the fine branch portions of the first sub-pixel electrode **191a** and second sub-pixel electrode **191b**, the texture generated at this portion may have the same shape. Consequently, this may prevent a change in picture quality caused by a change in texture, and a countermeasure such as blocking this portion by a light blocking film may be avoided.

The first sub-pixel electrode **191a** and the second sub-pixel electrode **191b** are supplied with respective data voltages through different data lines **171a** and **171b**, and the voltage of the first sub-pixel electrode **191a** having a relatively small area is higher than the voltage of the second sub-pixel electrode **191b** having a relatively large area.

When the voltages of the first sub-pixel electrode **191a** and second sub-pixel electrode **191b** are different from each other, the voltages applied to the liquid crystal capacitors **Clca** and **Clcb** formed in the two pixel electrodes **191a** and **191b** are different from each other. Thus, the tilt angles of the liquid crystal molecules **31** of each of the sub-pixels **PXa** and **PXb** are also different from each other. Therefore, the voltage applied to the liquid crystal capacitors **Clca** and **Clcb** can be adjusted so that an image viewed from a lateral side is similar to an image viewed from the front, thereby improving the lateral visibility of the LCD.

Next, the arrangement of liquid crystal molecules of a liLCD in accordance with an experimental example of the present invention will be described with reference to FIG. 4A, FIG. 4B, FIG. 4C, FIG. 5A, FIG. 5B, FIG. 5C, FIG. 6A, and FIG. 6B.

FIG. 4A, FIG. 4B, and FIG. 4C are microphotographs showing an irregular texture of an LCD, FIG. 5A, FIG. 5B, and FIG. 5C are microphotographs of an LCD, and FIG. 6A and FIG. 6B are drawings showing simulation results of the liquid crystal molecules director of an LCD.

In an exemplary embodiment of the present invention, the arrangement of liquid crystal molecules of the LCD is measured by applying a predetermined voltage to the first sub-pixel electrode **191a**, the second sub-pixel electrode **191b**, and the common electrode **270**, without forming notches **7** in the LCD, and the arrangement of the liquid crystal molecules is also measured after forming three notches **7** and five notches **7** in the LCD under the same condition. The results of the measurement are shown in FIG. 4A, FIG. 4B, FIG. 4C, FIG. 5A, FIG. 5B, and FIG. 5C. Also, under the above condition, simulation of the liquid crystal molecules director is carried out, and the results thereof are shown in FIG. 6A and FIG. 6B.

First, referring to FIG. 4A, FIG. 4B, and FIG. 4C, an irregular texture is formed around the first portion **93a** of the second sub-pixel electrode **191b**. The portion where an irregular texture is formed is indicated by a dotted line. As shown in FIG. 4, unlike the LCD according to the exemplary embodiment of the present invention described above, if there are no notches **7** formed in the first portion **93a** of the second sub-pixel electrode **191b**, an irregular texture is generated around the first portion **93a** of the second sub-pixel electrode **191b**. The location or pattern of the irregular texture is varied even in the same LCD, and thus an irregular texture appears.

Next, referring to FIG. 5A shows a part of the LCD when there are no notches **7** formed in the first portion **93a** of the second sub-pixel electrode **191b** is shown. FIG. 5B and FIG. 5C show a part of the LCD when there are three notches **7** and

five notches 7, respectively, formed in the first portion 93a of the second sub-pixel electrode.

Comparing FIG. 5A with FIG. 5B and FIG. 5C, if there are no notches 7 in the first portion 93a of the second sub-pixel electrode 191b, an irregular texture is generated around the first portion 93a of the second sub-pixel electrode 191b, and it can be seen that, if notches 7 are formed in the first portion 93a of the second sub-pixel electrode 191b, the liquid crystal molecules around the first portion 93a of the second sub-pixel electrode 191b are regularly arranged and thus a texture appears regularly formed. Further, it can be seen that the alignment of the liquid crystal molecules is varied according to the number of notches 7.

Next, simulation results of the liquid crystal molecules director will be described with reference to FIG. 6A and FIG. 6B. FIG. 6A depicts the movement of the liquid crystal molecules director when there are no notches 7 formed in the first portion 93a of the second sub-pixel electrode 191b, and FIG. 6B depicts the movement of the liquid crystal molecules director when there are three notches 7 formed in the first portion 93a of the second sub-pixel like in the LCD, according to an exemplary embodiment of the present invention.

In FIG. 6A and FIG. 6B, portions where the liquid crystal molecules director around the first portion 93a of the second sub-pixel electrode 191b is located are respectively circled by a solid line.

By evaluating the portion of FIG. 6A circled by the solid line "a", the movement direction of the liquid crystal molecules director is very irregular, and the position of the portion where the liquid crystal molecules director is moved is also irregular. However, by evaluating the portion of FIG. 6B circled by the solid line "b", the liquid crystal molecules director in the vicinity of the notches 7 formed in the first portion 93a of the second sub-pixel electrode 191b is moved toward the notches 7, and thus the liquid crystal molecules director is moved very regularly.

In this way, as in the LCD described in accordance with an exemplary embodiment of the present invention, pixels to which a high voltage is applied are spaced apart from the gate lines, thus reducing an unnecessary capacitance and reducing a kickback voltage. Further, the liquid crystal molecules are spaced apart from the fine branch portions of the pixel electrode and notches are formed in a part of the pixel electrode where no fine branch portions are formed, thereby controlling the movement of the liquid crystal molecules and reducing the generation of an irregular texture.

It will be apparent to those skilled in the art that various modifications and variation can be made in the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A liquid crystal display, comprising:
 - gate lines and data lines arranged on a first substrate;
 - pixel electrodes connected to the gate lines and the data lines, each pixel electrode comprising a first sub-pixel electrode and a second sub-pixel electrode separated from each other by a gap;
 - a common electrode arranged on a second substrate, and facing the pixel electrodes; and
 - a liquid crystal layer disposed between the pixel electrodes and the common electrode, and comprising a plurality of liquid crystal molecules,

wherein each of the first sub-pixel electrode and the second sub-pixel electrode comprises a plurality of fine branch portions,

the second sub-pixel electrode comprises a connection portion surrounding the fine branch portions of the first sub-pixel electrode, and a plurality of notches are formed in the connection portion of the second sub-pixel electrode.

2. The liquid crystal display of claim 1, wherein each of the first sub-pixel electrode and the second sub-pixel electrode further comprises a plurality of sub-regions in which lengthwise directions of the fine branch portions are different from each other.

3. The liquid crystal display of claim 2, wherein the plurality of liquid crystal molecules are aligned with pretilt in the lengthwise direction of the fine branch portions.

4. The liquid crystal display of claim 2, further comprising: an alignment film arranged on the pixel electrodes or the common electrode,

wherein the alignment film is light-aligned in the lengthwise direction of the fine branch portions.

5. The liquid crystal display of claim 2, wherein: each of the first sub-pixel electrode and the second sub-pixel electrode further comprises a horizontal stem portion and a vertical stem portion that form boundaries of the plurality of sub-regions; and

the fine branch portions of the first sub-pixel electrode and the second sub-pixel electrode, respectively, extend toward the edges of the first sub-pixel electrode and the second sub-pixel electrode from the horizontal stem portion or the vertical stem portion.

6. The liquid crystal display of claim 1, wherein a part of boundaries of the fine branch portions of the first sub-pixel electrode is disposed on a first virtual straight line, and the gate lines are disposed on a second virtual straight line spaced apart from and parallel to the first virtual straight line.

7. The liquid crystal display of claim 6, wherein the first virtual straight line and the second virtual straight line are spaced apart from each other by 2 μm to 7 μm .

8. The liquid crystal display of claim 7, wherein the plurality of notches are disposed at equal intervals.

9. The liquid crystal display of claim 8, wherein the second sub-pixel electrode comprises three to five notches.

10. The liquid crystal display of claim 7, wherein the notches comprise the shape of a triangle, a quadrangle, a trapezoid, or a semicircle.

11. The liquid crystal display of claim 7, wherein a voltage of the first sub-pixel electrode is higher than a voltage of the second sub-pixel electrode.

12. The liquid crystal display of claim 1, wherein the plurality of notches are disposed at equal intervals.

13. The liquid crystal display of claim 12, wherein the second sub-pixel electrode comprises three to five notches.

14. The liquid crystal display of claim 1, wherein the notches comprise the shape of a triangle, a quadrangle, a trapezoid, or a semicircle.

15. The liquid crystal display of claim 1, wherein a voltage of the first sub-pixel electrode is higher than a voltage of the second sub-pixel electrode.

* * * * *

专利名称(译)	液晶显示器		
公开(公告)号	US8098358	公开(公告)日	2012-01-17
申请号	US12/472983	申请日	2009-05-27
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KIM HOON BAEK SEUNG SOO NA HYE SEOK		
发明人	KIM, HOON BAEK, SEUNG-SOO NA, HYE-SEOK		
IPC分类号	G02F1/1343		
CPC分类号	G02F1/133707 G02F1/13624 G02F2001/134345		
审查员(译)	杜安, JENNIFER		
优先权	1020080120014 2008-11-28 KR		
其他公开文献	US20100134742A1		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示器技术领域本发明涉及一种液晶显示器，包括：布置在第一基板上的栅极线和数据线；像素电极连接到栅极线和数据线，并包括通过间隙彼此分开的第一子像素电极和第二子像素电极；公共电极，设置在第二基板上，并面向像素电极；液晶层设置在像素电极和公共电极之间并包括多个液晶分子，其中第一子像素电极和第二子像素电极中的每一个包括多个细分支部分，第二子电极像素电极包括围绕第一子像素电极的细分支部分的连接部分，并且在第二子像素电极的连接部分中形成多个凹口。

